Norwest Holst Soil Engineering Ltd.

Borehole No. 2

BOREHOLE LOG

Contract No. F5305
Location Markham Colliery
Client National Coal Board
Method of Boring Percussion
Diameter of Borehole 150 mm

Sheet 1 of 3
Chainage
Ground Level 64.74 m.A.O.D.
Date 29.7.82 - 2.8.82

Description of Strata	Legend	Depth Below G.L.(m)	O.D. Level (m)	Casing Depth at Sampling	Sampling and Coring	"N"/ R.Q.D.%	Daily Progress
MADE GROUND - Black ash, stores and coal dust		0.50	64.24		0.50	65 for 125 mm	
MADE GROUND - Wooden railway sleeper		0.80	63.94				
MADE GROUND - Black ash and gravel		1.30	63.44		1.40	(31)	
MADE GROUND - Grey silty clay, coal dust and brick fragments		2.80	61.94		2.55	(25)	
Firm brown silty CLAY with occasional gravel		3.30	61.44		3.55		
Brown and grey mottled silty CLAY		4.00	60.74			(30)	
Soft brown mottled sandy gravelly CLAY		4.90	59.84		4.55	(33)	
Brown very sandy very gravelly CLAY		5.70	59.04		5.55	(61)	
Brown silty sandy CLAY with coarse angular sandstone gravel		6.20	58.54				
Fine to coarse sub angular GRAVEL		6.60	58.14		6.50	12	
Brown silty very sandy gravelly CLAY					7.55	15	
Brown sandy very gravelly CLAY		8.20	56.54			25	
Grey and brown silty CLAY with sandstone gravel		9.40	55.34		8.55		
Brown and grey weathered SANDSTONE		9.80	54.94		9.50	(56)	
					9.95		

Type of Sample

Is	S.P.T.	■	Undisturbed
Ic.	C.P.T.	×	Vane
O	Jar	Δ	Water
●	Bulk		Piezometer

Remarks (Observations of Ground Water etc.)

Water seepage at 4.30m
Water struck at 5.50m rising to 5.00 m
Standing water level 5.20m
Chiselling sandstone 9.80m to 10.50m, 11.40m to 15.00m
Chisel mudstone (intermittently) 17.50m to 20.95m
Chisel shale 20.95m to 22.00m
( ) Blows to drive U100

Water levels are subject to seasonal or tidal variations and should not be taken as constant

Norwest Holst Soil Engineering Ltd.

Borehole No. 2

BOREHOLE LOG

Contract No. F5305
Location Markham Colliery
Client National Coal Board
Method of Boring Percussion
Diameter of Borehole 150 mm

Sheet 2 of 3
Chainage
Ground Level 64.74 m.A.O.D.
Date 29.7.82 - 2.8.82

Description of Strata	Legend	Depth Below G.L.(m)	O.D. Level (m)	Casing Depth at Sampling	Sampling and Coring	"N"/ R.Q.D.%	Daily Progress
Brown and grey weathered SANDSTONE		10.50	54.24			78	
Light grey weathered sandy SILTSTONE		11.40	53.34		11.00	73	
Light grey weathered silty SANDSTONE		12.25	52.49		11.50 12.00	64 for 150 mm* 68 for 150 mm*	
Light grey weathered sandy SILTSTONE		15.00	49.74		13.00 14.00	74 for 150 mm 73 for 150 mm	
Grey weathered clayey SILTSTONE		17.50	47.24		15.00 16.00 17.00	88 for 150 mm 87 for 125 mm 82 for 125 mm	
Grey silty MUDSTONE					18.00 19.00	50 for 75 mm 50 for 50 mm	

Type of Sample

- Is S.P.T.
- Undisturbed
- Ic. C.P.T.
- Vane
- O Jar
- Δ Water
- Bulk
- Piezometer

Remarks (Observations of Ground Water etc.)

* Seating blows only

See sheet 1

Water levels are subject to seasonal or tidal variations and should not be taken as constant

Norwest Holst Soil Engineering Ltd.

Borehole No. 2

BOREHOLE LOG

Contract No. F5305
Location Markham Colliery
Client National Coal Board
Method of Boring Percussion
Diameter of Borehole 150 mm

Sheet 3 of 3
Chainage
Ground Level 64.74 m.A.O.D.
Date 29.7.82 - 2.8.82

Description of Strata	Legend	Depth Below G.L.(m)	O.D. Level (m)	Casing Depth at Sampling	Sampling and Coring	"N"/ R.Q.D.%	Daily Progress
Grey silty MUDSTONE		20.95	43.79		20.00	84 for 150 mm*	
Dark grey shaley MUDSTONE					21.00	50 for 75 mm*	
End of borehole		22.05	42.69		22.00	50 for 25mm*	

Type of Sample

Is S.P.T. ■ Undisturbed
Ic. C.P.T. × Vane
O Jar △ Water
● Bulk ◧ Piezometer

Remarks (Observations of Ground Water etc.)

*Seating blows only.
See sheet 1.

Water levels are subject to seasonal or tidal variations and should not be taken as constant