



FLOSS Solutions for Open Land Administration (SOLA)

Data Dictionary

FAO NRC Land Tenure Team
version: 1.1
25/07/2012

Contents

| | |
|--|----|
| Introduction | 6 |
| source | 7 |
| Table: source | 7 |
| Table: availability_status_type | 11 |
| Table: administrative_source_type | 12 |
| Table: spatial_source | 14 |
| Table: spatial_source_type | 15 |
| Table: spatial_source_measurement | 17 |
| Table: presentation_form_type | 18 |
| Table: archive | 20 |
| Table: deed | 21 |
| Table: land_use_type | 23 |
| Sequence: source_la_nr_seq | 24 |
| party | 25 |
| Table: party | 25 |
| Table: party_type | 28 |
| Table: group_party | 29 |
| Table: group_party_type | 30 |
| Table: party_member | 31 |
| Table: party_role | 32 |
| Table: party_role_type | 33 |
| Table: communication_type | 35 |
| Table: id_type | 36 |
| Table: gender_type | 37 |
| Table: party_id | 38 |
| Table: country | 39 |
| Function: is_rightholder | 40 |
| administrative | 41 |
| Table: ba_unit | 41 |
| Table: ba_unit_type | 44 |
| Table: rrr | 45 |
| Table: rrr_group_type | 48 |
| Table: rrr_type | 49 |
| Table: mortgage_type | 53 |
| Table: mortgage_isbased_in_rrr | 54 |
| Table: source_describes_rrr | 55 |
| Table: source_describes_ba_unit | 56 |
| Table: required_relationship_baunit | 57 |
| Table: ba_unit_contains_spatial_unit | 58 |
| Table: ba_unit_as_party | 59 |
| Table: ba_unit_rel_type | 60 |
| Table: notation | 61 |

| | |
|---|-----|
| Table: ba_unit_area | 62 |
| Table: rrr_share | 63 |
| Table: party_for_rrr | 64 |
| Table: ba_unit_target | 65 |
| Sequence: rrr_nr_seq | 66 |
| Sequence: notation_reference_nr_seq | 67 |
| Sequence: ba_unit_first_name_part_seq | 68 |
| Sequence: ba_unit_last_name_part_seq | 69 |
| Function: get_ba_unit_pending_action | 70 |
| Function: ba_unit_name_is_valid | 71 |
| cadastre | 72 |
| Table: spatial_unit | 72 |
| Table: spatial_value_area | 75 |
| Table: area_type | 76 |
| Table: spatial_unit_address | 78 |
| Table: surface_relation_type | 79 |
| Table: level | 80 |
| Table: register_type | 82 |
| Table: structure_type | 83 |
| Table: level_content_type | 84 |
| Table: legal_space_utility_network | 86 |
| Table: building_unit_type | 87 |
| Table: utility_network_status_type | 88 |
| Table: utility_network_type | 89 |
| Table: dimension_type | 90 |
| Table: cadastre_object_type | 91 |
| Table: cadastre_object | 92 |
| Table: cadastre_object_target | 94 |
| Table: survey_point | 95 |
| Table: cadastre_object_node_target | 96 |
| Table: region | 97 |
| Table: district | 98 |
| Table: section | 99 |
| Table: block | 100 |
| View: survey_control | 101 |
| View: road | 102 |
| View: place_name | 103 |
| Function: cadastre_object_name_is_valid | 104 |
| application | 105 |
| Table: application | 105 |
| Table: request_type | 108 |
| Table: request_category_type | 111 |
| Table: application_action_type | 112 |
| Table: service_status_type | 114 |

| | | |
|-------------------|--|-----|
| | Table: service_action_type | 115 |
| | Table: application_property | 117 |
| | Table: application_uses_source | 118 |
| | Table: request_type_requires_source_type | 119 |
| | Table: application_status_type | 120 |
| | Table: type_action | 122 |
| | Table: application_party | 123 |
| | Table: fee_type | 124 |
| | Table: application_fee | 125 |
| | Table: request_type_fee_type | 126 |
| | Table: action_data_field_type | 127 |
| | Table: application_action | 128 |
| | Table: application_status | 129 |
| | Table: action_data | 130 |
| | Table: data_type | 131 |
| | Table: application_spatial_unit | 132 |
| | View: application_log | 133 |
| | Sequence: application_nr_seq | 134 |
| | Function: getlodgement | 135 |
| | Function: getlodgetiming | 136 |
| address | | 137 |
| | Table: address | 137 |
| system | | 139 |
| | Table: appuser | 139 |
| | Table: setting | 141 |
| | Table: appuser_setting | 142 |
| | Table: language | 143 |
| | Table: config_map_layer | 144 |
| | Table: config_map_layer_type | 147 |
| | Table: br | 148 |
| | Table: br_technical_type | 149 |
| | Table: br_validation | 150 |
| | Table: br_definition | 152 |
| | Table: br_severity_type | 153 |
| | Table: br_validation_target_type | 154 |
| | Table: approle | 155 |
| | Table: approle_appgroup | 158 |
| | Table: appgroup | 159 |
| | Table: appuser_appgroup | 160 |
| | Table: query | 161 |
| | Table: map_search_option | 167 |
| | Table: query_field | 169 |
| | View: user_roles | 172 |
| | View: br_current | 173 |

| | | |
|-------------|---|-----|
| | View: br_report | 174 |
| | Function: setPassword | 175 |
| | Function: get_setting | 176 |
| document | | 177 |
| | Table: document | 179 |
| | Sequence: document_nr_seq | 180 |
| transaction | | 181 |
| | Table: reg_status_type | 181 |
| | Table: transaction | 183 |
| | Table: transaction_status_type | 185 |
| | Table: transaction_source | 186 |
| public | | 187 |
| | Function: f_for_trg_track_changes | 187 |
| | Function: f_for_trg_track_history | 188 |
| | Function: fn_triggerall | 189 |
| | Function: clean_db | 190 |
| | Function: compare_strings | 191 |
| | Function: snap_geometry_to_geometry | 192 |
| | Function: get_geometry_with_srid | 193 |
| | Function: get_translation | 194 |

Introduction

The SOLA database has been created as part of a project undertaken by the UN Food and Agriculture Organization (with funding from the Government of Finland) to develop open source software that supports cadastre and registration functions in land administration agencies. It has a particular goal of making computerized systems supporting open land administration more affordable and sustainable in developing countries.

The SOLA database is implemented in a Postgre SQL database and is a relational database implementation of an extended version of the Land Administration Data Model (LADM) which is currently a Draft International Standard (DIS 19152). It has been necessary to extend DIS 19152 because of the operational needs of land administration agencies to incorporate case management and other features into any system that supports the processing of client service requests (for land information, registration and cadastre change requests and others) and the maintaining and updating of the record of rights and restrictions, ownership and property boundaries. The FLOSS SOLA software supports this range of land administration business processes and the SOLA database is an integral part of the FLOSS SOLA database.

The SOLA Data Dictionary is organized according to the database schemas defined in the SOLA database. Within each section for a schema there is a definition of all tables including their description, column, constraints and relationship details.

The SOLA database should be considered a work in progress over the period 2011 - 2013 while the initial FLOSS SOLA software is under development and pilot implementation are being undertaken. For this reason those referring to this document should check www.flossola.org to ensure they have the latest version.

source




Table: source

Documents or recognised facts providing the basis for the recording of a registration, cadastre change, right, responsibility or administrative action performed by the land office

LADM Reference Object

LA_Source

LADM Definition

Not defined

Columns

| Name | Type | Optional | Default | Description |
|------|------|----------|---------|-------------|
|------|------|----------|---------|-------------|

| | | | | |
|--------------------------|---------------|-------|-------------|--|
| id | varchar(40) | False | | LADM Definition - Source identifier |
| maintype | varchar(20) | True | | LADM Definition - The type of the representation of the content of the source. |
| la_nr | varchar(20) | False | | SOLA Extension - This number is given by the land administration office for their own administration. |
| reference_nr | varchar(20) | True | | SOLA Extension -This is the number as given by the external agency. |
| archive_id | varchar(40) | True | | SOLA Extension - The archive identifier of the source |
| acceptance | date | True | | LADM Definition -The date of force of law of the source by an authority. Date of Registration - Day on which the deed was registered by the commission |
| recordation | date | True | | LADM Definition - The date of formalization by the source agency. Ghana extension: This date in Ghana is refeerd as Date of Instrument |
| submission | date | True | now() | LADM Definition - The date when the document was submitted to the system |
| expiration_date | date | True | | Date of expiration |
| commencement_date | date | True | | Ghana extension: Date of commencement. |
| ext_archive_id | varchar(40) | True | | LADM Definition -The identifier of a source in an external registration. This attribute is used to link the source with the document management system. |
| availability_status_code | varchar(20) | False | 'available' | LADM Definition - the code describing how available this source (document) is |
| type_code | varchar(20) | False | | LADM Definition - Type of the document (administrative_source) |
| content | varchar(4000) | True | | LADM Definition -Content of the source (administrative_source) |
| status_code | varchar(20) | True | | The status of the document. For some documents is important to know if the document is valid or not. |
| transaction_id | varchar(40) | True | | The transaction that brought the document in the system. This is not valid for all documents but for some of them. There are request types that bring only documents in the system without involving a ba unit. In this case is important to know which transaction brought this document in order to handle it within transaction (approve, reject) life cycle. |

Constraints

| Name | Type | Explanation |
|-------------|-------------|--|
| source_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--------------------------------------|--|---|
| source_maintype_fk35 | From columns: maintype To Entity: presentation_form_type From cardinality: 0..* To Cardinality: 0..1 | LADM relationship - no refinement |
| source_archive_id_fk36 | From columns: archive_id To Entity: archive From cardinality: 0..* To Cardinality: 0..1 | FLOSS SOLA relationship - no refinement |
| source_availability_status_code_fk44 | From columns: availability_status_code To Entity: availability_status_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| source_type_code_fk45 | From columns: type_code To Entity: administrative_source_type From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| source_transaction_id_fk85 | From columns: transaction_id To Entity: transaction From cardinality: 0..* To Cardinality: 0..1 | |
| source_status_code_fk86 | From columns: status_code To Entity: reg_status_type From cardinality: 0..* To Cardinality: 0..1 | |

Relationships (to)

| Name | Information | Description |
|---|---|---|
| spatial_source_id_fk11 | From columns: id From Entity: spatial_source From cardinality: 1 To Cardinality: 1 | LADM relationship - no refinement |
| application_uses_source_source_id_fk38 | From columns: source_id From Entity: application_uses_source From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| source_describes_ba_unit_source_id_fk65 | From columns: source_id From Entity: source_describes_ba_unit From cardinality: 0..* To Cardinality: 1 | |
| source_describes_rrr_source_id_fk75 | From columns: source_id From Entity: source_describes_rrr From cardinality: 0..* To Cardinality: 1 | |
| transaction_source_source_id_fk94 | From columns: source_id From Entity: transaction_source From cardinality: 0..* To Cardinality: 1 | |

| | | |
|---------------|---|--|
| deed_id_fk135 | From columns: id From Entity: deed From cardinality: 1 To Cardinality: 1 | |
|---------------|---|--|

Triggers

| Name | Event |
|------------------|---------------|
| change_of_status | before update |

Table: availability_status_type

Reference Table / Code list of source (document) availability status type

LADM Reference Object

LA_AvailabilityStatusType

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | LADM Definition -The code for the availability status type |
| display_value | varchar(250) | False | | LADM Definition - The display value assigned to the availability status type |
| status | char(1) | False | 'c' | SOLA Extension - The status of the availability status type |
| description | varchar(555) | True | | LADM Definition - description of the availability status type |

Constraints

| Name | Type | Explanation |
|---|-------------|--|
| availability_status_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| availability_status_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|--------------------------------------|---|-----------------------------------|
| source_availability_status_code_fk44 | From columns: availability_status_code From Entity: source From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | status | description |
|----|------------------|--------------------------|--------|-------------------|
| 1 | archiveConverted | Converted::::Convertito | c | |
| 2 | archiveDestroyed | Destroyed::::Distrutto | x | |
| 3 | incomplete | Incomplete::::Incompleto | c | |
| 4 | archiveUnknown | Unknown::::Sconosciuto | c | |
| 5 | available | Available | c | Extension to LADM |

Table: administrative_source_type

Reference Table / Code list of administrative source types

LADM Reference Object

LA_AdministrativeSourceType

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | LADM Definition -The code for the administrative source type |
| display_value | varchar(250) | False | | LADM Definition - displayed value of the administrative source type |
| status | char(1) | False | | SOLA Extension - Status of the administrative source type |
| has_status | bool | False | false | |
| description | varchar(555) | True | | LADM Definition - Description of the administrative source type |

Constraints

| Name | Type | Explanation |
|---|-------------|--|
| administrative_source_type_display_value_UNIQUE | UNIQUE | Combination of (display_value) is unique |
| administrative_source_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---|---|---|
| source_type_code_fk45 | From columns: type_code From Entity: source From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| request_type_requires_source_type_source_type_code_fk46 | From columns: request_type_requires_source_type_code From Entity: request_type_requires_source_type From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |

Data

| Nr | code | display_value | status | has_status | description |
|----|-------------|---|--------|------------|-------------|
| 1 | agriConsent | Agricultural Consent:::Permesso Agricolo | x | false | |
| 2 | agriLease | Agricultural Lease:::Contratto Affitto Agricolo | x | false | |

| | | | | | |
|----|---------------------|--|---|-------|-------------------|
| 3 | agriNotaryStatement | Agricultural Notary Statement::::Dichiarazione Agricola Notaio | x | false | |
| 4 | deed | Deed | c | false | |
| 5 | lease | Lease::::ITALIANO | c | false | |
| 6 | mortgage | Mortgage::::Ipoteca | c | false | |
| 7 | title | Title::::Titolo | c | false | |
| 8 | proclamation | Proclamation::::Bando | c | false | Extension to LADM |
| 9 | courtOrder | Court Order::::Ordine Tribunale | c | false | Extension to LADM |
| 10 | agreement | Agreement::::Accordo | c | false | Extension to LADM |
| 11 | contractForSale | Contract for Sale::::ITALIANO | c | false | Extension to LADM |
| 12 | will | Will::::ITALIANO | c | false | Extension to LADM |
| 13 | powerOfAttorney | Power of Attorney::::ITALIANO | c | true | Extension to LADM |
| 14 | standardDocument | Standard Document::::ITALIANO | c | false | Extension to LADM |
| 15 | cadastralMap | Cadastral Map::::Mappa Catastale | c | false | Extension to LADM |
| 16 | cadastralSurvey | Cadastral Survey::::Rilevamento Catastale | c | false | Extension to LADM |
| 17 | waiver | Waiver to Caveat or other requirement | c | false | Extension to LADM |
| 18 | idVerification | Form of Identification including Personal ID | c | false | Extension to LADM |

Table: spatial_source

Refer to LADM Definition

LADM Reference Object

LA_Source

LADM Definition

A spatial source may be the final (sometimes formal) documents, or all documents related to a survey. Sometimes several documents are the result of a single survey. A spatial source may be official or not (ie a registered survey plan or an aerial photograph).

Columns

| Name | Type | Optional | Default | Description |
|-----------|--------------|----------|---------|--|
| id | varchar(40) | False | | LADM Definition - Spatial source identifier |
| procedure | varchar(255) | True | | LADM Definition - Procedures, steps or method adopted |
| type_code | varchar(20) | False | | LADM Definition - Code type assigned to the source |

Constraints

| Name | Type | Explanation |
|---------------------|-------------|--|
| spatial_source_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|------------------------------|--|-----------------------------------|
| spatial_source_type_code_fk0 | From columns: type_code To Entity: spatial_source_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| spatial_source_id_fk11 | From columns: id To Entity: source From cardinality: 1 To Cardinality: 1 | LADM relationship - no refinement |

Relationships (to)

| Name | Information | Description |
|---|---|-----------------------------------|
| spatial_source_measurement_spatial_source | From columns: spatial_source_id From Entity: spatial_source_measurement From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Table: spatial_source_type

Reference Table / Code list of spatial source type

LADM Reference Object

LA_SpatialSourceType

LADM Definition

Type of Spatial Source

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | LADM Definition - The code for the spatial source type |
| display_value | varchar(250) | False | | LADM Definition - The display value of the spatial source type |
| status | char(1) | False | 't' | SOLA Extension The status of the spatial source type |
| description | varchar(555) | True | | LADM Definition - description of the spatial source type |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| spatial_source_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| spatial_source_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|------------------------------|---|-----------------------------------|
| spatial_source_type_code_fk0 | From columns: type_code From Entity: spatial_source From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | status | description |
|----|---------------------|--|--------|-------------|
| 1 | fieldSketch | Field Sketch:::Schizzo Campo | c | |
| 2 | gnssSurvey | GNSS (GPS) Survey:::Rilevamento GNSS (GPS) | c | |
| 3 | orthoPhoto | Orthophoto:::Foto Ortopanoramica | c | |
| 4 | relativeMeasurement | Relative Measurements:::Misura relativa | c | |

| | | | | |
|---|-----------------|--|---|-------------------|
| 5 | topoMap | Topographical Map::::Mappa Topografica | c | |
| 6 | video | Video::::Video | c | |
| 7 | cadastralSurvey | Cadastral Survey::::Perizia Catastale | c | Extension to LADM |

Table: spatial_source_measurement

Refer to LADM Definition

LADM Reference Object

OM_Observation

LADM Definition

The observations, and measurements, as a basis for mapping, and as a basis for historical reconstruction of the location of (parts of) the spatial unit in the field

Columns

| Name | Type | Optional | Default | Description |
|-------------------|-------------|----------|---------|--|
| spatial_source_id | varchar(40) | False | | Spatial source identifier |
| id | varchar(40) | False | | LADM Definition - This is an identifier of a measurement within a spatial source. |

Constraints

| Name | Type | Explanation |
|---------------------------------|-------------|--|
| spatial_source_measurement_pkey | PRIMARY KEY | Combination of (spatial_source_id,id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|---|-----------------------------------|
| spatial_source_measurement_spatial_source | From columns: spatial_source_id To Entity: spatial_source From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Table: presentation_form_type

Reference Table / Code list for the different formats of sources (documents) that are presented to the land office

LADM Reference Object

CI_PresentationFormCode

LADM Definition

The type of document;

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | LADM Definition - Code for the presentation form type |
| display_value | varchar(250) | False | | LADM Definition - The display value for presentation form type |
| status | char(1) | False | 't' | SOLA Extension - The status of the presentation form type |
| description | varchar(555) | True | | LADM Definition - description of the presentation form type |

Constraints

| Name | Type | Explanation |
|---|-------------|--|
| presentation_form_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| presentation_form_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|----------------------|---|-----------------------------------|
| source_maintype_fk35 | From columns: maintype From Entity: source From cardinality: 0..* To Cardinality: 0..1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | status | description |
|----|------------------|---|--------|-------------|
| 1 | documentDigital | Digital Document:::Documento Digitale | c | |
| 2 | documentHardcopy | Hardcopy Document:::Documento in Hardcopy | c | |
| 3 | imageDigital | Digital Image:::Immagine Digitale | c | |
| 4 | imageHardcopy | Hardcopy Image:::Immagine in Hardcopy | c | |

| | | | | |
|----|-----------------|--|---|--|
| 5 | mapDigital | Digital Map:::Mappa Digitale | c | |
| 6 | mapHardcopy | Hardcopy Map:::Mappa in Hardcopy | c | |
| 7 | modelDigital | Digital Model:::Modello Digitale', | c | |
| 8 | modelHarcopy | Hardcopy Model:::Modello in Hardcopy | c | |
| 9 | profileDigital | Digital Profile:::Profilo Digitale | c | |
| 10 | profileHardcopy | Hardcopy Profile:::Profilo in Hardcopy | c | |
| 11 | tableDigital | Digital Table:::Tabella Digitale | c | |
| 12 | tableHardcopy | Hardcopy Table:::Tabella in Hardcopy | c | |
| 13 | videoDigital | Digital Video:::Video Digitale', | c | |
| 14 | videoHardcopy | Hardcopy Video:::Video in Hardcopy | c | |

Table: archive

Details about collections of sources (documents) in both paper and digital formats

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|--------|-------------|----------|---------|--|
| id | varchar(40) | False | | SOLA Extension The archive identifier of the source |
| box_nr | varchar(50) | False | | SOLA Extension - The name description of the source |

Constraints

| Name | Type | Explanation |
|--------------|-------------|--|
| archive_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (to)

| Name | Information | Description |
|------------------------|---|---|
| source_archive_id_fk36 | From columns: archive_id From Entity: source From cardinality: 0..* To Cardinality: 0..1 | FLOSS SOLA relationship - no refinement |

Table: deed**Columns**

| Name | Type | Optional | Default | Description |
|-----------------------|-------------|----------|---------|-------------|
| id | varchar(40) | False | | |
| no | varchar(30) | False | | |
| instrument_type_code | varchar(20) | False | | |
| first_party_id | varchar(40) | False | | |
| second_party_id | varchar(40) | False | | |
| forward_reference_id | varchar(40) | True | | |
| backward_reference_id | varchar(40) | True | | |
| file_no | varchar(50) | True | | |
| property_nr | varchar(30) | True | | |
| land_use_code | varchar(20) | True | | |

Constraints

| Name | Type | Explanation |
|-----------|-------------|--|
| deed_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---------------------------------|--|-------------|
| deed_id_fk135 | From columns: id To Entity: source From cardinality: 1 To Cardinality: 1 | |
| deed_instrument_type_code_fk136 | From columns: instrument_type_code To Entity: rrr_type From cardinality: 0..* To Cardinality: 1 | |
| deed_first_party_id_fk137 | From columns: first_party_id To Entity: party From cardinality: 0..* To Cardinality: 1 | |
| deed_second_party_id_fk138 | From columns: second_party_id To Entity: party From cardinality: 0..* To Cardinality: 1 | |
| deed_forward_reference_id_fk139 | From columns: forward_reference_id To Entity: deed From cardinality: 0..* To Cardinality: 1 | |

| | | |
|----------------------------------|---|--|
| deed_backward_reference_id_fk140 | From columns: backward_reference_id To Entity: deed From cardinality: 0..* To Cardinality: 1 | |
| deed_land_use_code_fk145 | From columns: land_use_code To Entity: land_use_type From cardinality: 0..* To Cardinality: 0..1 | |

Table: land_use_type

Ghana extension: It contains the list of possible land use types.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|-------------|
| code | varchar(20) | False | | |
| display_value | varchar(250) | False | | |
| status | char(1) | False | 't' | |
| description | varchar(555) | True | | |

Constraints

| Name | Type | Explanation |
|------------------------------------|-------------|--|
| land_use_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| land_use_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|--------------------------|--|-------------|
| deed_land_use_code_fk145 | From columns: land_use_code From Entity: deed From cardinality: 0..* To Cardinality: 0..1 | |

Data

| Nr | code | display_value | status | description |
|----|----------------|----------------|--------|-------------|
| 1 | residential | Residential | c | |
| 2 | commercial | Commercial | c | |
| 3 | industrial | Industrial | c | |
| 4 | educational | Educational | c | |
| 5 | agricultural | Agricultural | c | |
| 6 | recreational | Recreational | c | |
| 7 | civic-cultural | Civic Cultural | c | |

Sequence: source_la_nr_seq

Allocates numbers 1 to 999999999 for source la number.



Columns

- 25 -

| | | | | |
|------------------------------|-------------|------|--|---|
| previous_last_name | varchar(50) | True | | SOLA Extension - Last name of father of the party. |
| alias | varchar(50) | True | | SOLA Extension - Alias of the party. |
| gender_code | varchar(20) | True | | The gender of the party. If type of the party is naturalPerson then the gender_code must be given. |
| physical_address_id | varchar(40) | True | | Ghana extension: An identifier for the physical address of party. In the generic model this is the column address_id. |
| postal_address_id | varchar(40) | True | | Ghana extension: This is the address id of the postal address. |
| email | varchar(50) | True | | SOLA Extension Party's contact email address |
| mobile | varchar(15) | True | | SOLA Extension Contact mobile number of party |
| phone | varchar(15) | True | | SOLA Extension Landline phone number of party |
| fax | varchar(15) | True | | SOLA Extension Fax number of party |
| preferred_communication_code | varchar(20) | True | | SOLA Extension Code for mode of preferred communication |
| nationality_code | varchar(20) | True | | |
| dob_doi | date | True | | |

Constraints

| Name | Type | Explanation |
|------------|-------------|--|
| party_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|---|---|
| party_type_code_fk2 | From columns: type_code To Entity: party_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| party_physical_address_id_fk31 | From columns: physical_address_id To Entity: address From cardinality: 0..* To Cardinality: 0..1 | FLOSS SOLA relationship - no refinement |
| party_preferred_communication_code_fk34 | From columns: preferred_communication_code To Entity: communication_type From cardinality: 0..* To Cardinality: 0..1 | FLOSS SOLA relationship - no refinement |
| party_gender_code_fk90 | From columns: gender_code To Entity: gender_type From cardinality: 0..* To Cardinality: 0..1 | |

| | | |
|-------------------------------|---|--|
| party_postal_address_id_fk119 | From columns: postal_address_id To Entity: address From cardinality: 0..* To Cardinality: 0..1 | |
| party_nationality_code_fk146 | From columns: nationality_code To Entity: country From cardinality: 0..* To Cardinality: 0..1 | |

Relationships (to)

| Name | Information | Description |
|----------------------------------|---|---|
| party_member_party_id_fk4 | From columns: party_id From Entity: party_member From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| group_party_id_fk10 | From columns: id From Entity: group_party From cardinality: 1 To Cardinality: 1 | LADM relationship - no refinement |
| party_role_party_id_fk30 | From columns: party_id From Entity: party_role From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| ba_unit_as_party_party_id_fk48 | From columns: party_id From Entity: ba_unit_as_party From cardinality: 0..* To Cardinality: 1 | |
| party_for_rrr_party_id_fk76 | From columns: party_id From Entity: party_for_rrr From cardinality: 0..* To Cardinality: 1 | |
| application_party_party_id_fk112 | From columns: party_id From Entity: application_party From cardinality: 0..* To Cardinality: 1 | |
| party_id_party_id_fk120 | From columns: party_id From Entity: party_id From cardinality: 0..* To Cardinality: 1 | |
| deed_first_party_id_fk137 | From columns: first_party_id From Entity: deed From cardinality: 0..* To Cardinality: 1 | |
| deed_second_party_id_fk138 | From columns: second_party_id From Entity: deed From cardinality: 0..* To Cardinality: 1 | |

Table: party_type

Reference Table / Code list of party types

LADM Reference Object

LA_

LADM Definition

The type of party

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | LADM Definition - Code for party type |
| display_value | varchar(250) | False | | LADM Definition - displayed value for party type |
| status | char(1) | False | 't' | SOLA Extension party type status |
| description | varchar(555) | True | | LADM Definition - description of party type |

Constraints

| Name | Type | Explanation |
|---------------------------------|-------------|--|
| party_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| party_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---------------------|--|-----------------------------------|
| party_type_code_fk2 | From columns: type_code From Entity: party From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | status | description |
|----|------------------|--|--------|-------------|
| 1 | naturalPerson | Natural Person:::Persona Naturale | c | |
| 2 | nonNaturalPerson | Non-natural Person:::Persona Giuridica | c | |
| 3 | baunit | Basic Administrative Unit:::Unita Amministrativa di Base | c | |
| 4 | group | Group:::Gruppo | | |

Table: group_party

Refer to LADM Definition

LADM Reference Object

LA_GroupParty

LADM Definition

Any number of parties, forming together a distinct entity, with each party identified

Columns

| Name | Type | Optional | Default | Description |
|-----------|-------------|----------|---------|--|
| id | varchar(40) | False | | LADM Description - Identifier of a group party |
| type_code | varchar(20) | False | | LADM Description - The type of a group party |

Constraints

| Name | Type | Explanation |
|------------------|-------------|--|
| group_party_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---------------------------|---|-----------------------------------|
| group_party_type_code_fk3 | From columns: type_code To Entity: group_party_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| group_party_id_fk10 | From columns: id To Entity: party From cardinality: 1 To Cardinality: 1 | LADM relationship - no refinement |

Relationships (to)

| Name | Information | Description |
|---------------------------|--|-----------------------------------|
| party_member_group_id_fk5 | From columns: group_id From Entity: party_member From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Table: group_party_type

Reference Table / Code list to identify different types of groups being a party to some form of land office transaction

LADM Reference Object

LA_

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | LADM Definition - Group type code/identifier |
| display_value | varchar(250) | False | | LADM Definition - A value assigned for group party type |
| status | char(1) | False | 't' | SOLA Extension - Indication of party group type status |
| description | varchar(555) | True | | LADM Definition -A brief description of party type |

Constraints

| Name | Type | Explanation |
|---------------------------------------|-------------|--|
| group_party_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| group_party_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---------------------------|--|-----------------------------------|
| group_party_type_code_fk3 | From columns: type_code From Entity: group_party From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | status | description |
|----|-------------|--|--------|-------------|
| 1 | tribe | Tribes::Tribu | x | |
| 2 | association | Association::Associazione | c | |
| 3 | family | Family::Famiglia | c | |
| 4 | baunitGroup | Basic Administrative Unit Group::Unita Gruppo Amministrativo di Base | x | |

Table: party_member

Refer to LADM Definition

LADM Reference Object

LA_PartyMember

LADM Definition

A member belonging to a party.

Columns

| Name | Type | Optional | Default | Description |
|----------|------------------|----------|---------|---|
| party_id | varchar(40) | False | | LADM Definition - The identifier of the party |
| group_id | varchar(40) | False | | LADM Definition - The identifier of the party group |
| share | double precision | True | | LADM Definition - the share of a right (restriction or responsibility) held by a party member expressed as a fraction with a numerator and denominator |

Constraints

| Name | Type | Explanation |
|-------------------|-------------|---|
| party_member_pkey | PRIMARY KEY | Combination of (party_id,group_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---------------------------|---|-----------------------------------|
| party_member_party_id_fk4 | From columns: party_id To Entity: party From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| party_member_group_id_fk5 | From columns: group_id To Entity: group_party From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Table: party_role

Records the role(s) a party has in land office processes

LADM Reference Object

FLOSS SOLA Extension LA_Party.role

LADM Definition

The role of a party in the data update and maintenance process

Columns

| Name | Type | Optional | Default | Description |
|-----------|-------------|----------|---------|--|
| party_id | varchar(40) | False | | LADM Definition - The identifier of the party |
| type_code | varchar(20) | False | | SOLA Extension - The code for role type |

Constraints

| Name | Type | Explanation |
|-----------------|-------------|--|
| party_role_pkey | PRIMARY KEY | Combination of (party_id,type_code) is the primary key |

Relationships (from)

| Name | Information | Description |
|---------------------------|--|---|
| party_role_type_code_fk29 | From columns: type_code To Entity: party_role_type From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| party_role_party_id_fk30 | From columns: party_id To Entity: party From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |

Table: party_role_type

Reference Table / Code list of types of party roles

LADM Reference Object

LA_

LADM Definition

The role of the party in the data update and maintenance process;

Columns

| Name | Type | Optional | Default | Description |
|---------------------|--------------|----------|---------|---|
| code | varchar(20) | False | | SOLA Extension - code for party role type |
| display_value | varchar(250) | False | | SOLA Extension - displayed value of party role type |
| used_in_application | bool | False | false | This field is used to filter role_types that are used by applications only. Value is True if used by application. |
| status | char(1) | False | 't' | SOLA Extension - Indication of party role type status |
| description | varchar(555) | True | | SOLA Extension - description of party role type |

Constraints

| Name | Type | Explanation |
|--------------------------------------|-------------|--|
| party_role_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| party_role_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|-----------------------------------|--|---|
| party_role_type_code_fk29 | From columns: type_code From Entity: party_role From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| application_party_role_code_fk113 | From columns: role_code From Entity: application_party From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | used_in_application | status | description |
|----|----------|--------------------------|---------------------|--------|-------------|
| 1 | conveyor | Conveyor:::Trasportatore | | x | |
| 2 | notary | Notary:::Notaio | | c | |
| 3 | writer | Writer:::Autore | | x | |
| 4 | surveyor | Surveyor:::Perito | | x | |

| | | | | | |
|----|--------------------|--|------|---|-------------------|
| 5 | certifiedSurveyor | Licenced Surveyor::::Perito con Licenza | true | c | |
| 6 | bank | Bank::::Banca | | c | |
| 7 | moneyProvider | Money Provider::::Istituto Credito | | c | |
| 8 | employee | Employee::::Impiegato | | x | |
| 9 | farmer | Farmer::::Contadino | | x | |
| 10 | citizen | Citizen::::Cittadino | | c | |
| 11 | stateAdministrator | Registrar / Approving Surveyor::::Cancelliere/ Perito Approvatore/ | | c | |
| 12 | landOfficer | Land Officer::::Ufficiale del Registro Territoriale | | c | Extension to LADM |
| 13 | lodgingAgent | Lodging Agent::::Richiedente Registrazione | true | c | Extension to LADM |
| 14 | powerOfAttorney | Power of Attorney::::Procuratore | | c | Extension to LADM |
| 15 | transferee | Transferee (to)::::Avente Causa | | c | Extension to LADM |
| 16 | transferor | Transferor (from)::::Dante Causa | | c | Extension to LADM |
| 17 | applicant | Applicant | | c | Extension to LADM |

Table: communication_type

Reference Table / Code list for the different means of communication (from land office to their clients)

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | SOLA Extension - Communication type code |
| display_value | varchar(250) | False | | SOLA Extension - Display value for the communication type |
| status | char(1) | False | 't' | SOLA Extension - Status of the communication type |
| description | varchar(555) | True | | SOLA Extension - Description of the communication type |

Constraints

| Name | Type | Explanation |
|---|-------------|--|
| communication_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| communication_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---|---|---|
| party_preferred_communication_code_fk34 | From columns: preferred_communication_code From Entity: party From cardinality: 0..* To Cardinality: 0..1 | FLOSS SOLA relationship - no refinement |

Data

| Nr | code | display_value | status | description |
|----|---------|--------------------|--------|-------------|
| 1 | eMail | e-Mail:::E-mail | c | |
| 2 | fax | Fax:::Fax | c | |
| 3 | post | Post:::Posta | c | |
| 4 | phone | Phone:::Telefono | c | |
| 5 | courier | Courier:::Corriere | c | |

Table: id_type

Reference Table / Code list for the types of the documents that can be used to identify a party.

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | SOLA Extension - identifier for the type of person ID |
| display_value | varchar(250) | False | | SOLA Extension - displayed value of type of personal ID |
| status | char(1) | False | 't' | SOLA Extension - (personal) ID type status |
| description | varchar(555) | True | | SOLA Extension - description of personal ID type |

Constraints

| Name | Type | Explanation |
|------------------------------|-------------|--|
| id_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| id_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|--------------------------|---|-------------|
| party_id_type_code_fk121 | From columns: type_code From Entity: party_id From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | status | description |
|----|------------------|--|--------|--|
| 1 | nationalID | National ID:::Carta Identita Nazionale | c | The main person ID that exists in the country:::Il principale documento identificativo nel paese |
| 2 | nationalPassport | National Passport:::Passaporto Nazionale | c | A passport issued by the country:::Passaporto fornito dal paese |
| 3 | otherPassport | Other Passport:::Altro Passaporto | c | A passport issued by another country:::Passaporto Fornito da un altro paese |
| 4 | surveyorId | Surveyor ID | c | An id that is given to a surveyor |

Table: gender_type

The gender type list a party can have.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | SOLA Extension - code for party role type |
| display_value | varchar(250) | False | | SOLA Extension - displayed value of party role type |
| status | char(1) | False | 't' | SOLA Extension - Indication of party role type status |
| description | varchar(555) | True | | SOLA Extension - description of party role type |

Constraints

| Name | Type | Explanation |
|----------------------------------|-------------|--|
| gender_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| gender_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|------------------------|---|-------------|
| party_gender_code_fk90 | From columns: gender_code From Entity: party From cardinality: 0..* To Cardinality: 0..1 | |

Data

| Nr | code | display_value | status | description |
|----|--------|---------------|--------|-------------|
| 1 | male | Male | c | |
| 2 | female | Female | c | |

Table: party_id

Ghana extension: The list of ids that are associated with a party. In the generic model, there was space only for one id defined by the columns id_type_code and id_number. These columns are removed from the party.

Columns

| Name | Type | Optional | Default | Description |
|-----------|-------------|----------|---------|--|
| id | varchar(40) | False | | Meaningless identifier of the id for a certain |
| party_id | varchar(40) | False | | Id of the party |
| type_code | varchar(20) | False | | Type code of the id |
| id_number | integer | False | | The id number |

Constraints

| Name | Type | Explanation |
|----------------------|-------------|---|
| party_id_logical_key | UNIQUE | Combination of (party_id, type_code, id_number) is unique |
| party_id_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--------------------------|--|-------------|
| party_id_party_id_fk120 | From columns: party_id To Entity: party From cardinality: 0..* To Cardinality: 1 | |
| party_id_type_code_fk121 | From columns: type_code To Entity: id_type From cardinality: 0..* To Cardinality: 1 | |

Table: country

Ghana extension: List of countries that are used in the system.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|-------------|
| code | varchar(20) | False | | |
| display_value | varchar(250) | False | | |
| status | char(1) | False | 't' | |
| description | varchar(555) | True | | |

Constraints

| Name | Type | Explanation |
|------------------------------|-------------|--|
| country_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| country_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|------------------------------|--|-------------|
| party_nationality_code_fk146 | From columns: nationality_code From Entity: party From cardinality: 0..* To Cardinality: 0..1 | |

Function: is_rightholder

Gets if a party is rightholder.

Parameters

| Name | Type | Direction | Description |
|------|---------|-----------|-------------|
| id | varchar | | Party id |

administrative




Table: ba_unit

Refer to LADM Definition

LADM Reference Object

LA_BAUnit

LADM Definition

Basic administrative units (abbreviated as baunits), are needed, among other things, to register 'basic property units', which consist of several spatial units, belonging to a party, under the same right (a right must be 'homogeneous' over the whole baunit).

Columns

| Name | Type | Optional | Default | Description |
|------|-------------|----------|---------|--|
| id | varchar(40) | False | | LADM Definition - The identifier of the basic administrative unit |

| | | | | |
|----------------|--------------|-------|--|--|
| type_code | varchar(20) | False | | LADM Definition - The type of the basic administrative unit |
| name | varchar(255) | True | | LADM Definition - The name of the basic administrative unit |
| name_firstpart | varchar(20) | False | | LADM Definition - It is the part of the identifier of the property. Together with the name_lastpart is supposed to uniquely identify the property. This constraint it is not enforced, because there will be cases when it is not unique. Combination of name_firstpart and name_lastpart must derive the value of ba_unit. |
| name_lastpart | varchar(50) | False | | LADM Definition - It is the last part of the identifier of the property. Together with the name_firstpart is supposed to uniquely identify the property. This constraint it is not enforced, because there will be cases when it is not unique. Combination of name_firstpart and name_lastpart must derive the value of ba_unit. |
| status_code | varchar(20) | False | | The status of the ba unit. |
| transaction_id | varchar(40) | True | | Transaction which creates the baunit. |

Constraints

| Name | Type | Explanation |
|--------------|-------------|--|
| ba_unit_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|-----------------------------|--|-----------------------------------|
| ba_unit_type_code_fk6 | From columns: type_code To Entity: ba_unit_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| ba_unit_status_code_fk60 | From columns: status_code To Entity: reg_status_type From cardinality: 0..* To Cardinality: 1 | |
| ba_unit_transaction_id_fk82 | From columns: transaction_id To Entity: transaction From cardinality: 0..* To Cardinality: 0..1 | |

Relationships (to)

| Name | Information | Description |
|--------------------|---|---------------------------------|
| rrr_ba_unit_id_fk7 | From columns: ba_unit_id From Entity: rrr From cardinality: 1..* To Cardinality: 1 | LADM Definition - no refinement |

| | | |
|--|---|---|
| source_describes_ba_unit_ba_unit_id_fk1 | From columns: ba_unit_id From Entity: source_describes_ba_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| required_relationship_baunit_from_ba_unit_id_fk1 | From columns: from_ba_unit_id From Entity: required_relationship_baunit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| required_relationship_baunit_to_ba_unit_id_fk1 | From columns: to_ba_unit_id From Entity: required_relationship_baunit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| ba_unit_contains_spatial_unit_ba_unit_id_fk1 | From columns: ba_unit_id From Entity: ba_unit_contains_spatial_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| application_property_ba_unit_id_fk41 | From columns: ba_unit_id From Entity: application_property From cardinality: 0..* To Cardinality: 1 | SOLA Extension relationship - no refinement |
| ba_unit_as_party_ba_unit_id_fk49 | From columns: ba_unit_id From Entity: ba_unit_as_party From cardinality: 0..* To Cardinality: 1 | |
| notation_ba_unit_id_fk69 | From columns: ba_unit_id From Entity: notation From cardinality: 0..* To Cardinality: 0..1 | |
| ba_unit_area_ba_unit_id_fk71 | From columns: ba_unit_id From Entity: ba_unit_area From cardinality: 0..* To Cardinality: 1 | |
| ba_unit_target_ba_unit_id_fk108 | From columns: ba_unit_id From Entity: ba_unit_target From cardinality: 0..* To Cardinality: 1 | |

Table: ba_unit_type

Reference Table / Code list for types of BA Units

LADM Reference Object

LA_BAUnitType

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | LADM Definition Basic unit type code |
| display_value | varchar(250) | False | | LADM Definition Display value for the basic unit type |
| description | varchar(555) | True | | LADM Definition Description of the unit type |
| status | char(1) | False | 't' | SOLA Extension Status of the basic unit type |

Constraints

| Name | Type | Explanation |
|-----------------------------------|-------------|--|
| ba_unit_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| ba_unit_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|-----------------------|--|-----------------------------------|
| ba_unit_type_code_fk6 | From columns: type_code From Entity: ba_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | description | status |
|----|----------------------|------------------------|-------------|--------|
| 1 | allodial | Allodial | | c |
| 2 | customaryLawFreehold | Customary Law Freehold | | c |
| 3 | leaseHold | Lease Hold | | c |
| 4 | commonLawFreehold | Common Law Freehold | | c |

Table: rrr

Refer to LADM DefinitionLADM Reference Object LA_RRRLADM DefinitionA right, restriction or responsibility.

Columns

| Name | Type | Optional | Default | Description |
|------------------------|------------------|----------|-----------|---|
| id | varchar(40) | False | | LADM Definition - Identifier for the right, responsibility and restrictions |
| ba_unit_id | varchar(40) | False | | LADM Definition - basic administrative unit identifier |
| nr | varchar(20) | False | | This is a unique number of rrr within a baunit to identify it in baunit. |
| type_code | varchar(20) | False | | LADM Definition - code for type of right, responsibility restriction |
| status_code | varchar(20) | False | 'pending' | The status of the rrr. |
| is_primary | bool | False | false | It marks the rrr as being primary. Only one rrr can be primary for one BaUnit. |
| transaction_id | varchar(40) | False | | The transaction that brought changes to the rrr. |
| registration_date | timestamp | True | | This is the registration date of the rrr. It takes the value from the approval date. |
| expiration_date | timestamp | True | | LADM Definition - the dates defining when the rrr remains in force LADM Reference Object - rrr.timespec |
| share | double precision | True | | Actually, SOLA is defining shares in a separate table. So within one rrr we can have multiple shares instead of multiple rrr of the same type within a baunit as LADM proposes. LADM Definition - share of a right, (restriction or responsibility) expressed as a fraction with numerator and denominator |
| mortgage_amount | numeric(29, 2) | True | | LADM Definition The amount of money of the mortgage |
| mortgage_interest_rate | numeric(5, 2) | True | | LADM Definition Interest rate of the mortgage (percentage) |
| mortgage_ranking | integer | True | | LADM Definition The ranking order if more than one mortgage applies to a right |
| mortgage_type_code | varchar(20) | True | | |
| mortgage_installment | numeric(29, 2) | True | | The installment for the mortgage |

Constraints

| Name | Type | Explanation |
|----------|-------------|--|
| rrr_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|------|-------------|-------------|
|------|-------------|-------------|

| | | |
|-----------------------------|--|-----------------------------------|
| rrr_ba_unit_id_fk7 | From columns: ba_unit_id To Entity: ba_unit From cardinality: 1..* To Cardinality: 1 | LADM Definition - no refinement |
| rrr_type_code_fk9 | From columns: type_code To Entity: rrr_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| rrr_status_code_fk59 | From columns: status_code To Entity: reg_status_type From cardinality: 0..* To Cardinality: 1 | |
| rrr_mortgage_type_code_fk80 | From columns: mortgage_type_code To Entity: mortgage_type From cardinality: 0..* To Cardinality: 0..1 | |
| rrr_transaction_id_fk81 | From columns: transaction_id To Entity: transaction From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|--|---|---|
| source_describes_rrr_rrr_id_fk12 | From columns: rrr_id From Entity: source_describes_rrr From cardinality: 0..* To Cardinality: 1 | SOLA Extension relationship - no refinement |
| mortgage_isbased_in_rrr_rrr_id_fk57 | From columns: rrr_id From Entity: mortgage_isbased_in_rrr From cardinality: 0..* To Cardinality: 0..1 | |
| mortgage_isbased_in_rrr_mortgage_id_fk58 | From columns: mortgage_id From Entity: mortgage_isbased_in_rrr From cardinality: 0..* To Cardinality: 0..1 | |
| rrr_share_rrr_id_fk72 | From columns: rrr_id From Entity: rrr_share From cardinality: 0..* To Cardinality: 1 | |
| party_for_rrr_rrr_id_fk83 | From columns: rrr_id From Entity: party_for_rrr From cardinality: 0..* To Cardinality: 1 | |
| notation_rrr_id_fk84 | From columns: rrr_id From Entity: notation From cardinality: 0..* To Cardinality: 0..1 | |

Triggers

| Name | Event |
|---------------------|---------------|
| change_from_pending | before update |

Table: rrr_group_type

Reference Table / Code list for different categories of LA_RRR

LADM Reference Object

LA_Responsibility, LA_Right, LA_Restriction as specialisations of LA_RR

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | LADM Definition - Identifier of group type of restriction, rights responsibility |
| display_value | varchar(250) | False | | LADM Definition - the value to be displayed |
| description | varchar(555) | True | | LADM Definition - description of group type of restriction, rights responsibility |
| status | char(1) | False | | SOLA Extension Status of group type of restriction, rights responsibility |

Constraints

| Name | Type | Explanation |
|-------------------------------------|-------------|--|
| rrr_group_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| rrr_group_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|----------------------------------|--|-----------------------------------|
| rrr_type_rrr_group_type_code_fk8 | From columns: rrr_group_type_code From Entity: rrr_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | description | status |
|----|------------------|-----------------------------------|-------------|--------|
| 1 | rights | Rights:::Diritti | | c |
| 2 | restrictions | Restrictions:::Restrizioni | | c |
| 3 | responsibilities | Responsibilities:::Responsabilita | | x |

Table: rrr_type

Reference Table / Code list of rrr types
 LADM Reference Object LA_RightType, LA_RestrictionType
 &LA_ResponsibilityType
 LADM Definition The type of right/restriction/responsibility

Columns

| Name | Type | Optional | Default | Description |
|---------------------|--------------|----------|---------|--|
| code | varchar(20) | False | | LADM Definition - Code for responsibility and rights type code |
| rrr_group_type_code | varchar(20) | False | | LADM Definition - Group restriction, responsibility and rights type code |
| display_value | varchar(250) | False | | LADM Definition - displayed value of right (responsibility or restriction) type |
| is_primary | bool | False | false | |
| share_check | bool | False | | LADM Definition - the check that totals all shares of a right (restriction or responsibility) to ensure they equal 1 (100%) |
| party_required | bool | False | | LADM Definition - A flag to indicate that a party must related to this type of right (restriction or responsibility) |
| description | varchar(555) | True | | LADM Definition - Description for restriction, responsibility and rights type |
| status | char(1) | False | 't' | SOLA Extension - Status of restriction, responsibility and rights type |

Constraints

| Name | Type | Explanation |
|-------------------------------|-------------|--|
| rrr_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| rrr_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (from)

| Name | Information | Description |
|----------------------------------|--|-----------------------------------|
| rrr_type_rrr_group_type_code_fk8 | From columns: rrr_group_type_code To Entity: rrr_group_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Relationships (to)

| Name | Information | Description |
|-------------------|--|-----------------------------------|
| rrr_type_code_fk9 | From columns: type_code From Entity: rrr From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

| | | |
|---|---|--|
| br_validation_target_rrr_type_code_fk56 | From columns: target_rrr_type_code From Entity: br_validation From cardinality: 0..* To Cardinality: 0..1 | |
| request_type_rrr_type_code_fk78 | From columns: rrr_type_code From Entity: request_type From cardinality: 0..* To Cardinality: 0..1 | |
| deed_instrument_type_code_fk136 | From columns: instrument_type_code From Entity: deed From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | rrr_group_type_code | display_value | is_primary |
|----|----------------------|---------------------|--|------------|
| 1 | agriActivity | rights | Agriculture Activity:::Attività Agricola | false |
| 2 | commonOwnership | rights | Common Ownership:::Proprietà Comune | false |
| 3 | customaryType | rights | Customary Right:::Diritto Abituale | false |
| 4 | firewood | rights | Firewood Collection:::Collezione legna da ardere | false |
| 5 | fishing | rights | Fishing Right:::Diritto di Pesca | false |
| 6 | grazing | rights | Grazing Right:::Diritto di Pascolo | false |
| 7 | informalOccupation | rights | Informal Occupation:::Occupazione informale | false |
| 8 | lease | rights | Lease:::Affitto | false |
| 9 | occupation | rights | Occupation:::Occupazione | false |
| 10 | ownership | rights | Ownership:::Proprietà | true |
| 11 | ownershipAssumed | rights | Ownership Assumed:::Proprietà Assunta | true |
| 12 | superficies | rights | Superficies:::Superficie | false |
| 13 | tenancy | rights | Tenancy:::Locazione | true |
| 14 | usufruct | rights | Usufruct:::Usufrutto | false |
| 15 | waterrights | rights | Water Right:::Servitù di Acqua | false |
| 16 | adminPublicServitude | restrictions | Administrative Public Servitude:::Servitù Amministrazione Pubblica | false |
| 17 | monument | restrictions | Monument:::Monumento | false |
| 18 | mortgage | restrictions | Mortgage:::Ipoteca | false |
| 19 | noBuilding | restrictions | Building Restriction:::Restrizione di Costruzione | false |
| 20 | servitude | restrictions | Servitude:::Servitù | false |
| 21 | monumentMaintenance | responsibilities | Monument Maintenance:::Mantenimento Monumenti | false |

| | | | | |
|----|----------------------|------------------|--|-------|
| 22 | waterwayMaintenance | responsibilities | Waterway Maintenance::::Mantenimento Acquedotti | false |
| 23 | lifeEstate | rights | Life Estate::::Patrimonio vita | true |
| 24 | apartment | rights | Apartment Ownership::::Proprieta Appartamento | true |
| 25 | stateOwnership | rights | State Ownership::::Proprieta di Stato | true |
| 26 | caveat | restrictions | Caveat::::Ammonizione | false |
| 27 | historicPreservation | restrictions | Historic Preservation::::Conservazione Storica | false |
| 28 | limitedAccess | restrictions | Limited Access (to Road)::::Accesso limitato (su strada) | false |
| 29 | rrrStandard | rights | Incidence of Interest | true |

| Nr | share_check | party_required | description | status |
|----|-------------|----------------|-------------------|--------|
| 1 | true | true | | x |
| 2 | true | true | | x |
| 3 | true | true | | x |
| 4 | true | true | | x |
| 5 | true | true | | x |
| 6 | true | true | | x |
| 7 | false | false | | x |
| 8 | true | true | | c |
| 9 | true | true | | c |
| 10 | true | true | | c |
| 11 | true | true | | x |
| 12 | true | true | | x |
| 13 | true | true | | x |
| 14 | true | true | | c |
| 15 | true | true | | c |
| 16 | true | true | | x |
| 17 | true | true | | x |
| 18 | true | true | | c |
| 19 | false | false | | c |
| 20 | false | false | | c |
| 21 | false | false | | x |
| 22 | false | false | | x |
| 23 | true | true | Extension to LADM | x |
| 24 | true | true | Extension to LADM | c |
| 25 | false | false | Extension to LADM | c |

| | | | | |
|----|-------|-------|----------------------|---|
| 26 | true | true | Extension to LADM | c |
| 27 | false | false | Extension to LADM | c |
| 28 | false | false | Extension to LADM | c |
| 29 | true | true | | c |

Table: mortgage_type

Reference Table / Code list for types of mortgage

LADM Reference Object

LA_

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | LADM Definition Type of mortgage code |
| display_value | varchar(250) | False | | LADM Definition display value of mortgage type |
| description | varchar(555) | True | | LADM Definition Description of type of mortgage |
| status | char(1) | False | | SOLA Extension Status of mortgage type |

Constraints

| Name | Type | Explanation |
|------------------------------------|-------------|--|
| mortgage_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| mortgage_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|-----------------------------|---|-------------|
| rrr_mortgage_type_code_fk80 | From columns: mortgage_type_code From Entity: rrr From cardinality: 0..* To Cardinality: 0..1 | |

Data

| Nr | code | display_value | description | status |
|----|--------------|-----------------------------------|-------------|--------|
| 1 | levelPayment | Level Payment:::Livello Pagamento | | c |
| 2 | linear | Linear:::Lineare | | c |
| 3 | microCredit | Micro Credit:::Micro Credito | | c |

Table: mortgage_isbased_in_rrr

This is left in the data model but is not implemented, because the right that is basis for the mortgage can be implied by the primary right for ba_unit.LADM Reference Object LA_Mortgage - LA_Right RelationshipLADM DefinitionIdentifies the right that is the basis for a mortgage.

Columns

| Name | Type | Optional | Default | Description |
|-------------|-------------|----------|---------|--|
| mortgage_id | varchar(40) | False | | |
| rrr_id | varchar(40) | False | | LADM Definition - Identifier for the right, responsibility and restrictions |

Constraints

| Name | Type | Explanation |
|------------------------------|-------------|--|
| mortgage_isbased_in_rrr_pkey | PRIMARY KEY | Combination of (mortgage_id,rrr_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--|---|-------------|
| mortgage_isbased_in_rrr_rrr_id_fk57 | From columns: rrr_id To Entity: rrr From cardinality: 0..* To Cardinality: 0..1 | |
| mortgage_isbased_in_rrr_mortgage_id_fk58 | From columns: mortgage_id To Entity: rrr From cardinality: 0..* To Cardinality: 0..1 | |

Table: source_describes_rrr

Implements the many-to-many relationship identifying administrative source instances with rrr instances

LADM Reference Object

Relationship LA_AdministrativeSource - LA_RRR

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|-----------|-------------|----------|---------|--|
| rrr_id | varchar(40) | False | | LADM Definition - Identifier for the right, responsibility and restrictions |
| source_id | varchar(40) | False | | |

Constraints

| Name | Type | Explanation |
|---------------------------|-------------|--|
| source_describes_rrr_pkey | PRIMARY KEY | Combination of (rrr_id,source_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|-------------------------------------|---|---|
| source_describes_rrr_rrr_id_fk12 | From columns: rrr_id To Entity: rrr From cardinality: 0..* To Cardinality: 1 | SOLA Extension relationship - no refinement |
| source_describes_rrr_source_id_fk75 | From columns: source_id To Entity: source From cardinality: 0..* To Cardinality: 1 | |

Table: source_describes_ba_unit

Implements the many-to-many relationship identifying administrative source instances with ba_unit instances

LADM Reference Object

Relationship LA_AdministrativeSource - LA_BAUnit

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|------------|-------------|----------|---------|--|
| ba_unit_id | varchar(40) | False | | LADM Definition Basic unit identifier |
| source_id | varchar(40) | False | | In Sola the source is referenced instead of the Administrative source. LADM Definition Administrative source identifier |

Constraints

| Name | Type | Explanation |
|-------------------------------|-------------|--|
| source_describes_ba_unit_pkey | PRIMARY KEY | Combination of (ba_unit_id,source_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--|---|-----------------------------------|
| source_describes_ba_unit_ba_unit_id_fk13 | From columns: ba_unit_id To Entity: ba_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| source_describes_ba_unit_source_id_fk65 | From columns: source_id To Entity: source From cardinality: 0..* To Cardinality: 1 | |

Table: required_relationship_baunit

Refer to LADM Definition

LADM Reference Object

LA_RequiredRelationshipBAUnit

LADM Definition

A required relationship between basic administrative units.

Columns

| Name | Type | Optional | Default | Description |
|-----------------|-------------|----------|---------|---|
| from_ba_unit_id | varchar(40) | False | | LADM Definition -The identifier of the originating basic administrative unit |
| to_ba_unit_id | varchar(40) | False | | LADM Definition -The identifier of the target basic administrative unit |
| relation_code | varchar(20) | False | | The relationship between the basic administrative units. It exists in LADM as a open text. It is decided to make it a codelist to be used also in business rules. LADM Definition LADM Reference Object Relationship |

Constraints

| Name | Type | Explanation |
|-----------------------------------|-------------|---|
| required_relationship_baunit_pkey | PRIMARY KEY | Combination of (from_ba_unit_id,to_ba_unit_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--|---|-----------------------------------|
| required_relationship_baunit_from_ba_unit_id | From columns: from_ba_unit_id To Entity: ba_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| required_relationship_baunit_to_ba_unit_id | From columns: to_ba_unit_id To Entity: ba_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| required_relationship_baunit_relation_code | From columns: relation_code To Entity: ba_unit_rel_type From cardinality: 0..* To Cardinality: 1 | |

Table: ba_unit_contains_spatial_unit

Defines the spatial unit(s) associated with ba_unit

LADM Reference Object

Implements the many to many relationship LA_BAUnit - LA_SpatialUnit

LADM Definition

Not defined .

Columns

| Name | Type | Optional | Default | Description |
|-----------------|-------------|----------|---------|---|
| ba_unit_id | varchar(40) | False | | LADM Definition Basic administrative unit identifier |
| spatial_unit_id | varchar(40) | False | | LADM Definition Spatial unit identifier |

Constraints

| Name | Type | Explanation |
|------------------------------------|-------------|--|
| ba_unit_contains_spatial_unit_pkey | PRIMARY KEY | Combination of (ba_unit_id,spatial_unit_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|--|-----------------------------------|
| ba_unit_contains_spatial_unit_ba_unit_id | From columns: ba_unit_id To Entity: ba_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| ba_unit_contains_spatial_unit_spatial_unit_id | From columns: spatial_unit_id To Entity: spatial_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| ba_unit_contains_spatial_unit_spatial_unit_id | From columns: spatial_unit_id To Entity: cadastre_object From cardinality: 0..* To Cardinality: 1 | |

Table: ba_unit_as_party

LADM Definition LA_BAUnit is associated to class LA_Party (a party may be an basic administrative unit, indicated by the attribute 'partyType'). LADM Reference ObjectAssociation baunitAsParty

Columns

| Name | Type | Optional | Default | Description |
|------------|-------------|----------|---------|---------------------|
| ba_unit_id | varchar(40) | False | | The id of ba_unit |
| party_id | varchar(40) | False | | The id of the party |

Constraints

| Name | Type | Explanation |
|-----------------------|-------------|---|
| ba_unit_as_party_pkey | PRIMARY KEY | Combination of (ba_unit_id,party_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|----------------------------------|---|-------------|
| ba_unit_as_party_party_id_fk48 | From columns: party_id To Entity: party From cardinality: 0..* To Cardinality: 1 | |
| ba_unit_as_party_ba_unit_id_fk49 | From columns: ba_unit_id To Entity: ba_unit From cardinality: 0..* To Cardinality: 1 | |

Table: ba_unit_rel_type

The types of relation two ba_units can have between each other.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | The code |
| display_value | varchar(250) | False | | The value that will be displayed to the user |
| description | varchar(555) | True | | Description |
| status | char(1) | False | | The status of this code itself. |

Constraints

| Name | Type | Explanation |
|---------------------------------------|-------------|--|
| ba_unit_rel_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| ba_unit_rel_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|--|---|-------------|
| required_relationship_baunit_relation_code | From columns: relation_code From Entity: required_relationship_baunit From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | description | status |
|----|------------|---------------|---------------|--------|
| 1 | priorTitle | Prior Title | Prior Title | c |
| 2 | rootTitle | Root of Title | Root of Title | c |

Table: notation

All notations related with a baunit are maintained here. Every notation gets a reference number and it is always associated with a transaction.

Columns

| Name | Type | Optional | Default | Description |
|----------------|---------------|----------|-----------|---|
| id | varchar(40) | False | | Meaningless id. |
| ba_unit_id | varchar(40) | True | | If the notation is only related to baunit the baunit id is given. |
| rrr_id | varchar(40) | True | | |
| transaction_id | varchar(40) | False | | The transaction id which brought the notation. |
| reference_nr | varchar(15) | False | | A reference number for the notation |
| notation_text | varchar(1000) | True | | The notation text. This text is defined by a template which is to be found in request_type. The link is established by the fact that a notation comes from a transaction which optionally can be initiated by a service which is of a certain request_type. |
| status_code | varchar(20) | False | 'pending' | The status of the notation. |

Constraints

| Name | Type | Explanation |
|---------------|-------------|--|
| notation_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|------------------------------|--|-------------|
| notation_status_code_fk68 | From columns: status_code To Entity: reg_status_type From cardinality: 0..* To Cardinality: 1 | |
| notation_ba_unit_id_fk69 | From columns: ba_unit_id To Entity: ba_unit From cardinality: 0..* To Cardinality: 0..1 | |
| notation_transaction_id_fk74 | From columns: transaction_id To Entity: transaction From cardinality: 0..* To Cardinality: 1 | |
| notation_rrr_id_fk84 | From columns: rrr_id To Entity: rrr From cardinality: 0..* To Cardinality: 0..1 | |

Table: ba_unit_area

Columns

| Name | Type | Optional | Default | Description |
|------------|----------------|----------|---------|-------------|
| id | varchar(40) | False | | |
| ba_unit_id | varchar(40) | False | | |
| type_code | varchar(20) | False | | |
| size | numeric(19, 2) | False | | |

Constraints

| Name | Type | Explanation |
|-------------------|-------------|--|
| ba_unit_area_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|------------------------------|--|-------------|
| ba_unit_area_type_code_fk70 | From columns: type_code To Entity: area_type From cardinality: 0..* To Cardinality: 1 | |
| ba_unit_area_ba_unit_id_fk71 | From columns: ba_unit_id To Entity: ba_unit From cardinality: 0..* To Cardinality: 1 | |

Table: rrr_share

If parties are involved in an rrr then they participate in shares. There is at least one share for each rrr.LADM
Reference Object LA_RRR.share

Columns

| Name | Type | Optional | Default | Description |
|-------------|-------------|----------|---------|---|
| rrr_id | varchar(40) | False | | Rrr where the share belongs to. |
| id | varchar(40) | False | | Id of the share within a RRR. |
| nominator | smallint | False | | Nominator / Denominator define the share. |
| denominator | smallint | False | | Nominator / Denominator define the share. |

Constraints

| Name | Type | Explanation |
|----------------|-------------|---|
| rrr_share_pkey | PRIMARY KEY | Combination of (rrr_id,id) is the primary key |

Relationships (from)

| Name | Information | Description |
|-----------------------|---|-------------|
| rrr_share_rrr_id_fk72 | From columns: rrr_id To Entity: rrr From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|---------------------------|---|-------------|
| party_for_rrr_rrr_id_fk73 | From columns: rrr_id,share_id From Entity: party_for_rrr From cardinality: 0..* To Cardinality: 0..1 | |

Table: party_for_rrr

There may be parties involved in an RRR. Parties can be involved also in Shares.

Columns

| Name | Type | Optional | Default | Description |
|----------|-------------|----------|---------|---------------------------------------|
| rrr_id | varchar(40) | False | | Rrr where party belongs to. |
| party_id | varchar(40) | False | | Id of the party. |
| share_id | varchar(40) | True | | The share where the party belongs to. |

Constraints

| Name | Type | Explanation |
|--------------------|-------------|---|
| party_for_rrr_pkey | PRIMARY KEY | Combination of (rrr_id,party_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|-----------------------------|---|-------------|
| party_for_rrr_rrr_id_fk73 | From columns: rrr_id,share_id To Entity: rrr_share From cardinality: 0..* To Cardinality: 0..1 | |
| party_for_rrr_party_id_fk76 | From columns: party_id To Entity: party From cardinality: 0..* To Cardinality: 1 | |
| party_for_rrr_rrr_id_fk83 | From columns: rrr_id To Entity: rrr From cardinality: 0..* To Cardinality: 1 | |

Table: ba_unit_target

This table holds information about which ba units are being targets of a transaction. It is used when a ba unit is marked for cancellation.

Columns

| Name | Type | Optional | Default | Description |
|----------------|-------------|----------|---------|--|
| ba_unit_id | varchar(40) | False | | Id of the ba unit being target. |
| transaction_id | varchar(40) | False | | Id of the transaction that targes the ba unit. |

Constraints

| Name | Type | Explanation |
|---------------------|-------------|---|
| ba_unit_target_pkey | PRIMARY KEY | Combination of (ba_unit_id,transaction_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|-------------------------------------|---|-------------|
| ba_unit_target_ba_unit_id_fk108 | From columns: ba_unit_id To Entity: ba_unit From cardinality: 0..* To Cardinality: 1 | |
| ba_unit_target_transaction_id_fk109 | From columns: transaction_id To Entity: transaction From cardinality: 0..* To Cardinality: 1 | |

Sequence: rrr_nr_seq

Allocates numbers 1 to 9999 for rrr number

Sequence: notation_reference_nr_seq

Allocates numbers 1 to 9999 for reference number for notation.

Sequence: ba_unit_first_name_part_seq

Allocates numbers 1 to 9999 for ba unit first name part.

Sequence: ba_unit_last_name_part_seq

Allocates numbers 1 to 9999 for ba unit last name part.

Function: get_ba_unit_pending_action

It returns the action that must be taken in the pending ba_unit.

Parameters

| Name | Type | Direction | Description |
|-----------|---------|-----------|----------------|
| baunit_id | varchar | | Id of ba unit. |

Function: ba_unit_name_is_valid

This function, checks if the name parts of the ba unit are valid.

Parameters

| Name | Type | Direction | Description |
|----------------|---------|-----------|-------------|
| name_firstpart | varchar | | |
| name_lastpart | varchar | | |

cadastre




Table: spatial_unit

Single area (or multiple areas) of land or water, or a single volume (or multiple volumes) of spaceLADM Reference Object LA_SpatialUnitLADM DefinitionNot Defined

Columns

| Name | Type | Optional | Default | Description |
|------|-------------|----------|---------|--|
| id | varchar(40) | False | | LADM Definition - Spatial unit identifier |

| | | | | |
|-----------------------|--------------|-------|-------------|--|
| dimension_code | varchar(20) | False | '2D' | LADM Definition - Code for dimension |
| label | varchar(255) | True | | LADM Definition -Label for the spatial unit |
| surface_relation_code | varchar(20) | False | 'onSurface' | LADM Definition - Code given to the surface relation to indicate whether a spatial unit is above or below the surface |
| level_id | varchar(40) | True | | LADM Definition - Level identifier |
| reference_point | GEOMETRY | True | | LADM Definition -The coordinates of a point inside the spatial unit |
| geom | GEOMETRY | True | | SOLA Extension -The geometry type of the spatial unit |

Constraints

| Name | Type | Explanation |
|-------------------|-------------|--|
| spatial_unit_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|--|-----------------------------------|
| spatial_unit_surface_relation_code_fk19 | From columns: surface_relation_code To Entity: surface_relation_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| spatial_unit_level_id_fk20 | From columns: level_id To Entity: level From cardinality: 0..* To Cardinality: 0..1 | LADM relationship - no refinement |
| spatial_unit_dimension_code_fk33 | From columns: dimension_code To Entity: dimension_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Relationships (to)

| Name | Information | Description |
|--|--|---|
| spatial_value_area_spatial_unit_id_fk16 | From columns: spatial_unit_id From Entity: spatial_value_area From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| spatial_unit_address_spatial_unit_id_fk18 | From columns: spatial_unit_id From Entity: spatial_unit_address From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| ba_unit_contains_spatial_unit_spatial_unit_id_fk25 | From columns: spatial_unit_id From Entity: ba_unit_contains_spatial_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

| | | |
|--|---|--|
| cadastre_object_id_fk61 | From columns: id From Entity: cadastre_object From cardinality: 1 To Cardinality: 1 | |
| application_spatial_unit_spatial_unit_id_fk1 | From columns: spatial_unit_id From Entity: application_spatial_unit From cardinality: 0..* To Cardinality: 1 | |

Table: spatial_value_area

Refer to LADM Definition

LADM Reference Object

LA_AreaValue

LADM Definition

The area (size) of 2 dimension spatial unit

Columns

| Name | Type | Optional | Default | Description |
|-----------------|----------------|----------|---------|---|
| spatial_unit_id | varchar(40) | False | | LADM Definition - Spatial unit identifier |
| type_code | varchar(20) | False | | LADM Definition - Type of the spatial value area |
| size | numeric(29, 2) | False | | LADM Definition - The area of the spatial unit |

Constraints

| Name | Type | Explanation |
|-------------------------|-------------|---|
| spatial_value_area_pkey | PRIMARY KEY | Combination of (spatial_unit_id,type_code) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|---|-----------------------------------|
| spatial_value_area_spatial_unit_id_fk16 | From columns: spatial_unit_id To Entity: spatial_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| spatial_value_area_type_code_fk17 | From columns: type_code To Entity: area_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Table: area_type

Reference Table / Code list of the different versions or means of calculated area

LADM Reference Object

LA_AreaType

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | LADM Definition - code for area type |
| display_value | varchar(250) | False | | LADM Definition - displayed value of area type |
| description | varchar(555) | True | | LADM Definition - description of area type |
| status | char(1) | False | 'c' | SOLA Extension - status of area type values |

Constraints

| Name | Type | Explanation |
|--------------------------------|-------------|--|
| area_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| area_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|-----------------------------------|---|-----------------------------------|
| spatial_value_area_type_code_fk17 | From columns: type_code From Entity: spatial_value_area From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| ba_unit_area_type_code_fk70 | From columns: type_code From Entity: ba_unit_area From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | description | status |
|----|-----------------|--|-------------|--------|
| 1 | calculatedArea | Calculated Area:::Area calcolata | | c |
| 2 | nonOfficialArea | Non-official Area:::Area Non ufficiale | | c |
| 3 | officialArea | Official Area:::Area Ufficiale | | c |

| | | | | |
|---|--------------|---|--|---|
| 4 | surveyedArea | Surveyed Area::::Area Sorvegliata | | c |
|---|--------------|---|--|---|

Table: spatial_unit_address

Implements the many-to-many relationship between address and spatial_unit

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|-----------------|-------------|----------|---------|--|
| spatial_unit_id | varchar(40) | False | | LADM Definition - Spatial unit identifier |
| address_id | varchar(40) | False | | LADM Definition - Address identifier |

Constraints

| Name | Type | Explanation |
|---------------------------|-------------|--|
| spatial_unit_address_pkey | PRIMARY KEY | Combination of (spatial_unit_id,address_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|---|---|
| spatial_unit_address_spatial_unit_id_fk18 | From columns: spatial_unit_id To Entity: spatial_unit From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| spatial_unit_address_address_id_fk32 | From columns: address_id To Entity: address From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |

Table: surface_relation_type

Refer to LADM Definition

LADM Reference Object

LA_SurfaceRelationType

LADM Definition

The type of relation that exists between spatial objects and space (surface)

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | LADM Definition - the code identifying a surface relation type |
| display_value | varchar(250) | False | | LADM Definition - the displayed value for a surface relation type |
| description | varchar(555) | True | | LADM Definition - the description of a surface relation type |
| status | char(1) | False | 't' | SOLA Extension - the status of an instance of surface relation type |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| surface_relation_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| surface_relation_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---|--|-----------------------------------|
| spatial_unit_surface_relation_code_fk19 | From columns: surface_relation_code From Entity: spatial_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | description | status |
|----|-----------|-------------------------------|-------------|--------|
| 1 | above | Above:::Sopra | | x |
| 2 | below | Below:::Sotto | | x |
| 3 | mixed | Mixed:::Misto | | x |
| 4 | onSurface | On Surface:::Sulla Superficie | | c |

Table: level

Refer to LADM Definition

LADM Reference Object

LA_Level

LADM Definition

A set of spatial units, with a geometric, and/or topologic, and/or thematic coherence
 EXAMPLE 1 One level for an urban cadastre and another level for a rural cadastre.

EXAMPLE 2 One level with rights and another level with restrictions.

EXAMPLE 3 One level with formal rights, a second level with informal rights and a third level with customary rights.

EXAMPLE 4 One level with point based spatial units, a second level with line based spatial units, and a third level with polygon based spatial units..

Columns

| Name | Type | Optional | Default | Description |
|--------------------|-------------|----------|---------|--|
| id | varchar(40) | False | | LADM Definition - Level identifier |
| name | varchar(50) | True | | LADM Definition - The name of the level |
| register_type_code | varchar(20) | False | | LADM Definition - The register type of the content of the level |
| structure_code | varchar(20) | True | | LADM Definition - Code for the structure of the level geometry |
| type_code | varchar(20) | True | | LADM Definition - The type of the content the level |

Constraints

| Name | Type | Explanation |
|------------|-------------|--|
| level_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|-------------------------------|---|-----------------------------------|
| level_structure_code_fk21 | From columns: structure_code To Entity: structure_type From cardinality: 0..* To Cardinality: 0..1 | LADM relationship - no refinement |
| level_register_type_code_fk22 | From columns: register_type_code To Entity: register_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| level_type_code_fk23 | From columns: type_code To Entity: level_content_type From cardinality: 0..* To Cardinality: 0..1 | LADM relationship - no refinement |

Relationships (to)

| Name | Information | Description |
|----------------------------|---|-----------------------------------|
| spatial_unit_level_id_fk20 | From columns: level_id From Entity: spatial_unit From cardinality: 0..* To Cardinality: 0..1 | LADM relationship - no refinement |

Table: register_type

Reference Table / Code list for register types

LADM Reference Object

LA_

LADM Definition

The register type of the content of the [map] level

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | LADM Definition - the code identifying a register type |
| display_value | varchar(250) | False | | LADM Definition - the displayed value of a register type |
| description | varchar(555) | True | | LADM Definition - the description of a register type |
| status | char(1) | False | | SOLA Extension - the status of an instance of register type |

Constraints

| Name | Type | Explanation |
|------------------------------------|-------------|--|
| register_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| register_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|-------------------------------|--|-----------------------------------|
| level_register_type_code_fk22 | From columns: register_type_code From Entity: level From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | description | status |
|----|-------------|--------------------------------|-------------|--------|
| 1 | all | All:::Tutti | | c |
| 2 | forest | Forest:::Forestale | | c |
| 3 | mining | Mining:::Minerario | | c |
| 4 | publicSpace | Public Space:::Spazio Pubblico | | c |
| 5 | rural | Rural:::Rurale | | c |
| 6 | urban | Urban:::Urbano | | c |

Table: structure_type

Reference Table / Code list of different forms of spatial unit definitions (within a level)

LADM Reference Object

LA_StructureType

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | LADM Definition - the code identifying a structure type |
| display_value | varchar(250) | False | | LADM Definition - the displayed value for a structure type |
| description | varchar(555) | True | | LADM Definition - the description of a structure type |
| status | char(1) | False | 't' | SOLA Extension - the status of an instance of structure type |

Constraints

| Name | Type | Explanation |
|-------------------------------------|-------------|--|
| structure_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| structure_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---------------------------|--|-----------------------------------|
| level_structure_code_fk21 | From columns: structure_code From Entity: level From cardinality: 0..* To Cardinality: 0..1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | description | status |
|----|------------------|-------------------------------------|-------------|--------|
| 1 | point | Point:::Punto | | c |
| 2 | polygon | Polygon:::Poligono | | c |
| 3 | sketch | Sketch:::Schizzo | | c |
| 4 | text | Text:::Testo | | c |
| 5 | topological | Topological:::Topologico | | c |
| 6 | unStructuredLine | UnstructuredLine:::LineanonDefinita | | c |

Table: level_content_type

Reference Table / Code list for the content type of a level

LADM Reference Object

LA_

LADM Definition

The type of the content of the level;

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | LADM Definition - the code identifying a level content type |
| display_value | varchar(250) | False | | LADM Definition - the displayed value of a level content type |
| description | varchar(555) | True | | LADM Definition - a description for a level content type |
| status | char(1) | False | 't' | SOLA Extension - the status of an instance of level content type |

Constraints

| Name | Type | Explanation |
|---|-------------|--|
| level_content_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| level_content_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|----------------------|---|-----------------------------------|
| level_type_code_fk23 | From columns: type_code From Entity: level From cardinality: 0..* To Cardinality: 0..1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | description | status |
|----|----------------|----------------------------------|-------------|--------|
| 1 | building | Building:::Costruzione | | x |
| 2 | customary | Customary:::Consueto | | x |
| 3 | informal | Informal:::Informale | | x |
| 4 | mixed | Mixed:::Misto | | x |
| 5 | network | Network:::Rete | | x |
| 6 | primaryRight | Primary Right:::Diritto Primario | | c |
| 7 | responsibility | Responsibility:::Responsabilita | | x |
| 8 | restriction | Restriction:::Restrizione | | c |

| | | | | |
|---|-------------------|--|----------------------|---|
| 9 | geographicLocator | Geographic Locators:::Locatori Geografici | Extension to LADM | c |
|---|-------------------|--|----------------------|---|

Table: legal_space_utility_network

Refer to LADM Definition

LADM Reference Object

LA_LegalSpaceUtilityNetwork

LADM Definition

A utility network concerns legal space, which does not necessarily coincide with the physical space of a utility network..

Columns

| Name | Type | Optional | Default | Description |
|-------------------------|-------------|----------|---------|---|
| id | varchar(40) | False | | LADM Definition - Legal space utility network identifier |
| ext_physical_network_id | varchar(40) | True | | LADM Definition - External Identifier for a physical utility network |
| status_code | varchar(20) | True | | LADM Definition - Code for the legal space utility network |
| type_code | varchar(20) | False | | LADM Definition - Type code for the legal space utility network |
| geom | GEOMETRY | True | | |

Constraints

| Name | Type | Explanation |
|----------------------------------|-------------|--|
| legal_space_utility_network_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--|---|-----------------------------------|
| legal_space_utility_network_status_code_fk26 | From columns: status_code To Entity: utility_network_status_type From cardinality: 0..* To Cardinality: 0..1 | LADM relationship - no refinement |
| legal_space_utility_network_type_code_fk27 | From columns: type_code To Entity: utility_network_type From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |
| legal_space_utility_network_id_fk64 | From columns: id To Entity: cadastre_object From cardinality: 1 To Cardinality: 1 | |

Table: building_unit_type

Reference Table / Code list for types of building units

LADM Reference Object

LA_BuildingUnitType

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | LADM Definition - the code identifying different building unit types |
| display_value | varchar(250) | False | | LADM Definition - the displayed value of building unit type |
| description | varchar(555) | True | | LADM Definition - the description of building unit type |
| status | char(1) | False | 't' | SOLA Extension - the status of the code value for building unit type |

Constraints

| Name | Type | Explanation |
|---|-------------|--|
| building_unit_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| building_unit_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---|--|-------------|
| cadastre_object_building_unit_type_code | From columns: building_unit_type_code From Entity: cadastre_object From cardinality: 0..* To Cardinality: 0..1 | |

Data

| Nr | code | display_value | description | status |
|----|------------|--------------------------|-------------|--------|
| 1 | individual | Individual:::Individuale | | c |
| 2 | shared | Shared:::Condiviso | | c |

Table: utility_network_status_type

Reference Table / Code list for the status of utility networks

LADM Reference Object

LA_UtilityNetworkStatusType

LADM Definition

Status of the type of utility network

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | LADM Definition - a code identifying a utility network status type |
| display_value | varchar(250) | False | | LADM Definition - the displayed value of a utility network status type |
| description | varchar(555) | True | | LADM Definition - a description of a utility network status type |
| status | char(1) | False | 't' | SOLA Extension - the status of an instance of utility network status type |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| utility_network_status_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| utility_network_status_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---|---|-----------------------------------|
| legal_space_utility_network_status_code_ref | From columns: status_code From Entity: legal_space_utility_network From cardinality: 0..* To Cardinality: 0..1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | description | status |
|----|----------|------------------------|-------------|--------|
| 1 | inUse | In Use:::In uso | | c |
| 2 | outOfUse | Out of Use:::Fuori uso | | c |
| 3 | planned | Planned:::Pianificato | | c |

Table: utility_network_type

Reference Table / Code list of utility network types

LADM Reference Object

LA_

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | LADM Definition - a code identifying a utility network type |
| display_value | varchar(250) | False | | LADM Definition - the displayed value for a utility network type |
| description | varchar(555) | True | | LADM Definition - the description of a utility network type |
| status | char(1) | False | | SOLA Extension - the status of an instance of utility network type |

Constraints

| Name | Type | Explanation |
|---|-------------|--|
| utility_network_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| utility_network_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---|--|-----------------------------------|
| legal_space_utility_network_type_code_fk2 | From columns: type_code From Entity: legal_space_utility_network From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | description | status |
|----|-------------------|---------------------------------------|-------------|--------|
| 1 | chemical | Chemicals:::Cimica | | c |
| 2 | electricity | Electricity:::Elettricita | | c |
| 3 | gas | Gas:::Gas | | c |
| 4 | heating | Heating:::Riscaldamento | | c |
| 5 | oil | Oil:::Carburante | | c |
| 6 | telecommunication | Telecommunication:::Telecomunicazione | | c |
| 7 | water | Water:::Acqua | | c |

Table: dimension_type

Reference Table / Code list to identify the number of dimensions used to define a spatial unit

LADM Reference Object

LA_DimensionType

LADM Definition

Not Defined

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | LADM Definition - the code value to identify different dimension types |
| display_value | varchar(250) | False | | LADM Definition - the displayed value for a dimension type |
| description | varchar(555) | True | | LADM Definition - the description of a dimension type |
| status | char(1) | False | 't' | |

Constraints

| Name | Type | Explanation |
|-------------------------------------|-------------|--|
| dimension_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| dimension_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|----------------------------------|--|-----------------------------------|
| spatial_unit_dimension_code_fk33 | From columns: dimension_code From Entity: spatial_unit From cardinality: 0..* To Cardinality: 1 | LADM relationship - no refinement |

Data

| Nr | code | display_value | description | status |
|----|---------|---------------|-------------|--------|
| 1 | 0D | 0D:::0D | | c |
| 2 | 1D | 1D:::1D | | c |
| 3 | 2D | 2D:::sD | | c |
| 4 | 3D | 3D:::3D | | c |
| 5 | liminal | Liminal | | x |

Table: cadastre_object_type

The type of spatial object. This defines the specialisation of the spatial unit. It can be a parcel, building_unit or backgroup data like a road etc.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | The code |
| display_value | varchar(250) | False | | The value that will be displayed to the user |
| description | varchar(555) | True | | Description |
| status | char(1) | False | | The status of this code itself. |

Constraints

| Name | Type | Explanation |
|---|-------------|--|
| cadastre_object_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| cadastre_object_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|--------------------------------|--|-------------|
| cadastre_object_type_code_fk63 | From columns: type_code From Entity: cadastre_object From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | description | status |
|----|----------|---------------|-------------|--------|
| 1 | parcel | Parcel | | c |
| 2 | building | Building | | c |
| 3 | strata | Strata | | c |

Table: cadastre_object

Columns

| Name | Type | Optional | Default | Description |
|-----------------------------|--------------|----------|-----------|---|
| id | varchar(40) | False | | |
| type_code | varchar(20) | False | 'parcel' | SOLA Extention - It defines the type of the spatial unit. |
| building_unit_type_code | varchar(20) | True | | |
| approval_datetime | timestamp | True | | SOLA Extension - Approval datetime of the spatial unit change. |
| historic_datetime | timestamp | True | | SOLA Extension - Datetime when the spatial unit is superseded and has status of historic. |
| source_reference | varchar(100) | True | | This is a temporary solution. It is an identifier |
| name_firstpart | varchar(40) | False | | SOLA Extension - First part of the parcel identifier. First part in combination with last part are supposed to identify uniquely the parcel. |
| name_lastpart | varchar(50) | False | | SOLA Extension - Last part of the parcel identifier. First part in combination with last part are supposed to identify uniquely the parcel. |
| status_code | varchar(20) | False | 'pending' | SOLA Extension - It is the status of the spatial_unit which defines if it is pending or approved. |
| geom_polygon | GEOMETRY | True | | SOLA Extension - The polygon geometry |
| transaction_id | varchar(40) | False | | |
| upn | varchar(30) | True | | |
| description | varchar(200) | True | | |
| legacy_lot_nr | varchar(20) | True | | Ghana extension: The SMD number of the lots before the new numbering was done. |
| legacy_property_nr | varchar(20) | True | | Ghana extension: The number on the PVLMD townsheet for a parcel. |
| found_in_cadastre_object_id | varchar(40) | True | | |

Constraints

| Name | Type | Explanation |
|----------------------|-------------|--|
| cadastre_object_name | UNIQUE | Combination of (name_firstpart, name_lastpart) is unique |
| cadastre_object_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|-------------------------|---|-------------|
| cadastre_object_id_fk61 | From columns: id To Entity: spatial_unit From cardinality: 1 To Cardinality: 1 | |

| | | |
|--|--|--|
| cadastre_object_status_code_fk62 | From columns: status_code To Entity: reg_status_type From cardinality: 0..* To Cardinality: 1 | |
| cadastre_object_type_code_fk63 | From columns: type_code To Entity: cadastre_object_type From cardinality: 0..* To Cardinality: 1 | |
| cadastre_object_building_unit_type_code_fk67 | From columns: building_unit_type_code To Entity: building_unit_type From cardinality: 0..* To Cardinality: 0..1 | |
| cadastre_object_transaction_id_fk88 | From columns: transaction_id To Entity: transaction From cardinality: 0..* To Cardinality: 1 | |
| cadastre_object_found_in_cadastre_object_id_fk84 | From columns: found_in_cadastre_object_id To Entity: cadastre_object From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|--|--|-------------|
| legal_space_utility_network_id_fk64 | From columns: id From Entity: legal_space_utility_network From cardinality: 1 To Cardinality: 1 | |
| ba_unit_contains_spatial_unit_spatial_unit_id_fk67 | From columns: spatial_unit_id From Entity: ba_unit_contains_spatial_unit From cardinality: 0..* To Cardinality: 1 | |
| cadastre_object_target_cadastre_object_id_fk66 | From columns: cadastre_object_id From Entity: cadastre_object_target From cardinality: 0..* To Cardinality: 1 | |

Triggers

| Name | Event |
|------------|-------------------------|
| remove | before delete |
| new | before insert |
| geommodify | before insert or update |

Table: cadastre_object_target

This is a cadastre object that is a target of a cadastre related transaction. If the transaction is not yet approved or cancelled, the cadastre object gets a pending status.

Columns

| Name | Type | Optional | Default | Description |
|--------------------|-------------|----------|---------|---|
| transaction_id | varchar(40) | False | | The id of the transaction that is doing changes to the cadastre object. |
| cadastre_object_id | varchar(40) | False | | The id of the cadastre object being target of transaction. |
| geom_polygon | GEOMETRY | True | | The new geometry of the target cadastre object. It is used only when the transaction involves changes of the existing cadastre object geometry. Example of a transaction that changes an existing cadastre object is cadastre redefinition. |

Constraints

| Name | Type | Explanation |
|-----------------------------|-------------|---|
| cadastre_object_target_pkey | PRIMARY KEY | Combination of (transaction_id,cadastre_object_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--|--|-------------|
| cadastre_object_target_cadastre_object_id_fk99 | From columns: cadastre_object_id To Entity: cadastre_object From cardinality: 0..* To Cardinality: 1 | |
| cadastre_object_target_transaction_id_fk92 | From columns: transaction_id To Entity: transaction From cardinality: 0..* To Cardinality: 1 | |

Table: survey_point

Columns

| Name | Type | Optional | Default | Description |
|----------------|-------------|----------|---------|-------------|
| transaction_id | varchar(40) | False | | |
| id | varchar(40) | False | | |
| boundary | bool | False | true | |
| geom | GEOMETRY | False | | |
| original_geom | GEOMETRY | False | | |

Constraints

| Name | Type | Explanation |
|-------------------|-------------|---|
| survey_point_pkey | PRIMARY KEY | Combination of (transaction_id,id) is the primary key |

Relationships (from)

| Name | Information | Description |
|----------------------------------|---|-------------|
| survey_point_transaction_id_fk91 | From columns: transaction_id To Entity: transaction From cardinality: 0..* To Cardinality: 1 | |

Table: cadastre_object_node_target

The nodes that have been changed or added from the transaction.

Columns

| Name | Type | Optional | Default | Description |
|----------------|-------------|----------|---------|---|
| transaction_id | varchar(40) | False | | The id of the transaction that is changing or inserting a new node. |
| node_id | varchar(40) | False | | The node id. |
| geom | GEOMETRY | False | | The geometry of the node. |

Constraints

| Name | Type | Explanation |
|----------------------------------|-------------|--|
| cadastre_object_node_target_pkey | PRIMARY KEY | Combination of (transaction_id,node_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|---|-------------|
| cadastre_object_node_target_transaction | From Columns: transaction_id To Entity: transaction From cardinality: 0..* To Cardinality: 1 | |

Table: region

Columns

| Name | Type | Optional | Default | Description |
|----------|-------------|----------|---------|-------------|
| id | varchar(40) | False | | |
| code | varchar(5) | False | | |
| name | varchar(30) | False | | |
| the_geom | GEOMETRY | True | | |

Constraints

| Name | Type | Explanation |
|--------------------|-------------|--|
| region_code_unique | UNIQUE | Combination of (code) is unique |
| region_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (to)

| Name | Information | Description |
|--------------------------|---|-------------|
| district_region_id_fk141 | From columns: region_id From Entity: district From cardinality: 0..* To Cardinality: 1 | |

Table: district

Columns

| Name | Type | Optional | Default | Description |
|---------------|-------------|----------|---------|-------------|
| id | varchar(40) | False | | |
| region_id | varchar(40) | False | | |
| num | varchar(30) | False | | |
| year_declared | integer | False | | |
| the_geom | GEOMETRY | True | | |

Constraints

| Name | Type | Explanation |
|---------------|-------------|--|
| district_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--------------------------|---|-------------|
| district_region_id_fk141 | From columns: region_id To Entity: region From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|---------------------------|--|-------------|
| section_district_id_fk142 | From columns: district_id From Entity: section From cardinality: 0..* To Cardinality: 1 | |

Table: section

Columns

| Name | Type | Optional | Default | Description |
|-------------|--------------|----------|---------|-------------|
| id | varchar(40) | False | | |
| district_id | varchar(40) | False | | |
| num | varchar(30) | False | | |
| locality | varchar(200) | True | | |
| the_geom | GEOMETRY | True | | |

Constraints

| Name | Type | Explanation |
|--------------|-------------|--|
| section_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---------------------------|---|-------------|
| section_district_id_fk142 | From columns: district_id To Entity: district From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|------------------------|---|-------------|
| block_section_id_fk143 | From columns: section_id From Entity: block From cardinality: 0..* To Cardinality: 1 | |

Table: block

Columns

| Name | Type | Optional | Default | Description |
|------------|-------------|----------|---------|-------------|
| id | varchar(40) | False | | |
| section_id | varchar(40) | False | | |
| num | varchar(30) | False | | |
| is_pseudo | bool | False | false | |
| the_geom | GEOMETRY | True | | |

Constraints

| Name | Type | Explanation |
|------------|-------------|--|
| block_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|------------------------|---|-------------|
| block_section_id_fk143 | From columns: section_id To Entity: section From cardinality: 0..* To Cardinality: 1 | |

View: survey_control

This is a view which is used to retrieve the survey points from the spatial units. It is used from the gis component.

Columns

| Name | Type | Optional | Default | Description |
|-------|--------------|----------|---------|-------------------------|
| id | varchar(40) | True | | identifier |
| label | varchar(255) | True | | Label of island |
| geom | GEOMETRY | True | | geometry type of island |

View: road

A map feature (used in the Samoa implementation) that identifies the centrelines of roads in SamoaLADM Reference ObjectFLOSS SOLA ExtensionLADM DefinitionNot Applicable

Columns

| Name | Type | Optional | Default | Description |
|-------|--------------|----------|---------|----------------------|
| id | varchar(40) | True | | Road identifier |
| label | varchar(255) | True | | Name of each of road |
| geom | GEOMETRY | True | | Geometry type |

View: place_name

View for retrieving place names to be used in the gis component.

Columns

| Name | Type | Optional | Default | Description |
|-------|--------------|----------|---------|-----------------------------------|
| id | varchar(40) | True | | Identifier of village |
| label | varchar(255) | True | | Labels and description of village |
| geom | GEOMETRY | True | | Description of the geometry type |

Function: cadastre_object_name_is_valid

This function, checks if the name parts of the cadastre_object are valid.

Parameters

| Name | Type | Direction | Description |
|----------------|---------|-----------|-------------|
| name_firstpart | varchar | | |
| name_lastpart | varchar | | |



LADM Reference Object

FLOSS SOLA Extension

Columns

- 105 -

| | | | | |
|--------------------------|----------------|-------|-------|--|
| id | varchar(40) | False | | SOLA Extension - application identifier |
| nr | varchar(15) | False | | SOLA Extension - This is the application number that is exposed to the user. It is generated as the date + the ordinal number within that day. |
| lodging_datetime | timestamp | False | now() | SOLA Extension - The lodging date and time of the application. This date is important because it marks the time when the application has been officially accepted from the RO. |
| expected_completion_date | date | True | now() | SOLA Extension - The date when the application is supposed to be completed or cancelled by then. It is a derived value by picking up the most later expected date from the services that are boundled with the application. |
| assignee_id | varchar(40) | True | | SOLA Extension - The person that is assigned to the application. If this value is missing it means that the application is not assigned. |
| assigned_datetime | timestamp | True | | SOLA Extension - Date and time the application is assigned. It has a meaning only if the assignee_login_name is present. |
| location | GEOMETRY | True | | SOLA Extension - The location of the application given as multi point in the map. |
| total_fee | numeric(20, 2) | False | 0 | Ghana extension: The column is also present in generic model, but the calculates changes. This is calculated as the total amount of fees found in application_fee table in column total_amount. |
| total_amount_paid | numeric(20, 2) | False | 0 | Ghana extension: The column is also present in generic model, but the calculates changes. This is calculated as the total amount of fees found in application_fee table in column paid_amount. |
| request_code | varchar(20) | False | | |

Constraints

| Name | Type | Explanation |
|----------------------------|-------------|--|
| application_check_assigned | CHECK | Rule ((assignee_id is null and assigned_datetime is null) or (assignee_id is not null and assigned_datetime is not null)) must be true |
| application_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|------------------------------|---|---|
| application_assignee_id_fk42 | From columns: assignee_id To Entity: appuser From cardinality: 0..* To Cardinality: 0..1 | FLOSS SOLA relationship - no refinement |

| | | |
|--------------------------------|--|--|
| application_request_code_fk114 | From columns: request_code To Entity: request_type From cardinality: 0..* To Cardinality: 1 | |
|--------------------------------|--|--|

Relationships (to)

| Name | Information | Description |
|---|--|---|
| application_property_application_id_fk37 | From columns: application_id From Entity: application_property From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| application_uses_source_application_id_fk38 | From columns: application_id From Entity: application_uses_source From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| application_party_application_id_fk111 | From columns: application_id From Entity: application_party From cardinality: 0..* To Cardinality: 1 | |
| application_fee_application_id_fk115 | From columns: application_id From Entity: application_fee From cardinality: 0..* To Cardinality: 1 | |
| application_status_application_id_fk124 | From columns: application_id From Entity: application_status From cardinality: 0..* To Cardinality: 1 | |
| application_spatial_unit_application_id_fk132 | From columns: application_id From Entity: application_spatial_unit From cardinality: 0..* To Cardinality: 1 | |
| transaction_from_application_id_fk134 | From columns: from_application_id From Entity: transaction From cardinality: 0..* To Cardinality: 1 | |

Table: request_type

Reference Table / Code list of the (service) request types received by a land officeLADM Reference Object FLOSS
SOLA ExtensionLADM DefinitionNot Applicable

Columns

| Name | Type | Optional | Default | Description |
|------------------------|----------------|----------|---------|---|
| code | varchar(20) | False | | SOLA Extension - Code for the request type |
| request_category_code | varchar(20) | False | | SOLA Extension - The code for the request category type |
| display_value | varchar(250) | False | | SOLA Extension - The display value for the request type |
| description | varchar(555) | True | | SOLA Extension - The description of the request type |
| status | char(1) | False | 't' | SOLA Extension - Status of the request type |
| nr_days_to_complete | integer | False | 0 | SOLA Extension - The number of days within the service must be completed. |
| base_fee | numeric(20, 2) | False | 0 | SOLA Extension - The base fee that will be asked for this kind of request. |
| area_base_fee | numeric(20, 2) | False | 0 | SOLA Extension - The fee that will be asked per m2 of the area of the properties that will be dealt with for this kind of request. |
| value_base_fee | numeric(20, 2) | False | 0 | SOLA Extension - The fee that will be asked per value unit of the properties that will be dealt with for this kind of request. |
| nr_properties_required | integer | False | 0 | SOLA Extension - The minimum number of properties that is required by this service. |
| notation_template | varchar(1000) | True | | |
| rrr_type_code | varchar(20) | True | | The type of rrr which will be affected from the service of this request type. It is optional because not every request type affects rrr. If this value is filled then also the column rrr_type_action must be filled. |
| type_action_code | varchar(20) | True | | This holds the action that has to happen on the rrr or ba unit if the request type targets rrr or ba unit. |
| starting_status_code | varchar(20) | False | | |

Constraints

| Name | Type | Explanation |
|-----------------------------------|-------------|--|
| request_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| request_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (from)

| Name | Information | Description |
|------|-------------|-------------|
|------|-------------|-------------|

| | | |
|---|--|---|
| request_type_request_category_code_fk28 | From columns: request_category_code To Entity: request_category_type From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| request_type_rrr_type_code_fk78 | From columns: rrr_type_code To Entity: rrr_type From cardinality: 0..* To Cardinality: 0..1 | |
| request_type_type_action_code_fk79 | From columns: type_action_code To Entity: type_action From cardinality: 0..* To Cardinality: 0..1 | |
| request_type_starting_status_code_fk129 | From columns: starting_status_code To Entity: application_status_type From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|--|--|---|
| request_type_requires_source_type_request_type_code_fk40 | From columns: request_type_code From Entity: request_type_requires_source_type From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| br_validation_target_request_type_code_fk55 | From columns: target_request_type_code From Entity: br_validation From cardinality: 0..* To Cardinality: 0..1 | |
| application_request_code_fk114 | From columns: request_code From Entity: application From cardinality: 0..* To Cardinality: 1 | |
| request_type_fee_type_request_code_fk117 | From columns: request_code From Entity: request_type_fee_type From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | request_category_code | display_value | description | status |
|----|-----------------|-----------------------|-----------------|-------------|--------|
| 1 | smdPlanApproval | registrationServices | Plan approval | | c |
| 2 | smdApplyRegNo | registrationServices | Regional number | | c |

| Nr | nr_days_to_complete | base_fee | area_base_fee | value_base_fee | nr_properties_required | notation_template |
|----|---------------------|----------|---------------|----------------|------------------------|-------------------|
| 1 | 10 | 100 | 100 | 100 | 100 | |
| 2 | 10 | 100 | 100 | 100 | 100 | |

| Nr | rrr_type_code | type_action_code | starting_status_code |
|----|---------------|------------------|----------------------|
| 1 | | | smdplanapp-submit |
| 2 | | | smdregnr-submit |

Table: request_category_type

Reference Table / Code list for categories of (service) requests received by a land office

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | SOLA Extension - The code request category type |
| display_value | varchar(250) | False | | SOLA Extension - The display value for the request category type |
| description | varchar(555) | True | | SOLA Extension - Description of the request category type |
| status | char(1) | False | 't' | SOLA Extension - Status of the request category type |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| request_category_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| request_category_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---|--|---|
| request_type_request_category_code_fk28 | From columns: request_category_code From Entity: request_type From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |

Data

| Nr | code | display_value | description | status |
|----|----------------------|---|-------------|--------|
| 1 | registrationServices | Registration Services::::Servizi di Registrazione | | c |
| 2 | informationServices | Information Services::::Servizi Informativi | | c |

Table: application_action_type

Reference Table / Code list of action types that are performed in relation to an (land office) application for servicesLADM Reference Object FLOSS SOLA ExtensionLADM DefinitionNot Applicable

Columns

| Name | Type | Optional | Default | Description |
|------------------------|--------------|----------|---------|--|
| code | varchar(20) | False | | SOLA Extension - Communication type code |
| start_status_type_code | varchar(20) | False | | |
| display_value | varchar(250) | False | | SOLA Extension - Display value for the communication type |
| next_status_type_code | varchar(20) | True | | |
| status | char(1) | False | 't' | SOLA Extension - Status of the communication type |
| description | varchar(555) | True | | SOLA Extension - Description of the communication type |

Constraints

| Name | Type | Explanation |
|------------------------------|-------------|--|
| application_action_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|--|-------------|
| application_action_type_next_status_type | From columns: next_status_type_code To Entity: application_status_type From cardinality: 0..* To Cardinality: 0..1 | |
| application_action_type_start_status_type | From columns: start_status_type_code To Entity: application_status_type From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|---|--|-------------|
| br_validation_target_application_moment | From columns: target_application_moment From Entity: br_validation From cardinality: 0..* To Cardinality: 0..1 | |
| action_data_field_type_action_type_code | From columns: action_type_code From Entity: action_data_field_type From cardinality: 0..* To Cardinality: 1 | |

| | | |
|------------------------------------|---|--|
| application_action_type_code_fk123 | From columns: type_code From Entity: application_action From cardinality: 0..* To Cardinality: 1 | |
|------------------------------------|---|--|

Data

| Nr | code | start_status_type_code | display_value | next_status_type_code |
|----|----------------------|------------------------|------------------------------|-----------------------|
| 1 | regno-vetchecklist | smdregnr-submit | Vet against checklist | |
| 2 | regno-receivepayment | smdregnr-submit | Receive payment | |
| 3 | plangen-vetchecklist | smdplanapp-submit | Vet against checklist | |
| 4 | plangen-receivepay | smdplanapp-submit | Receive payment | |
| 5 | plangen-movenext | smdplanapp-submit | Move application to Registry | smdplanapp-registry |

| Nr | status | description |
|----|--------|-------------|
| 1 | | |
| 2 | | |
| 3 | | |
| 4 | | |
| 5 | | |

Table: service_status_type

It is the status that a service can have.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | SOLA Extension - the code identifying a service status type |
| display_value | varchar(250) | False | | SOLA Extension - the displayed value of a service status type |
| status | char(1) | False | 't' | SOLA Extension - the status of an instance of service status type |
| description | varchar(555) | True | | SOLA Extension - the description of a service status type |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| service_status_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| service_status_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|--|---|-------------|
| service_action_type_status_to_set_fk99 | From columns: status_to_set From Entity: service_action_type From cardinality: 0..* To Cardinality: 0..1 | |

Data

| Nr | code | display_value | status | description |
|----|-----------|------------------------|--------|--|
| 1 | lodged | Lodged:::Registrata | c | Application for a service has been lodged and officially received by land office:::La pratica per un servizio, registrata e formalmente ricevuta da ufficio territoriale |
| 2 | completed | Completed:::Completata | c | |
| 3 | pending | Pending:::ITALIANO | c | |
| 4 | cancelled | Cancelled:::Cancellato | c | |

Table: service_action_type

Reference Table / Code list of types of action that a land officer can perform to complete a service request

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | SOLA Extension - the code identifying a service action type |
| display_value | varchar(250) | False | | SOLA Extension - the displayed value of a service action type |
| status_to_set | varchar(20) | True | | |
| status | char(1) | False | 't' | SOLA Extension - the status of an instance of service action type |
| description | varchar(555) | True | | SOLA Extension - the description of a service action type |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| service_action_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| service_action_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (from)

| Name | Information | Description |
|--|---|-------------|
| service_action_type_status_to_set_fk99 | From columns: status_to_set To Entity: service_status_type From cardinality: 0..* To Cardinality: 0..1 | |

Relationships (to)

| Name | Information | Description |
|---|--|-------------|
| br_validation_target_service_moment_fk102 | From columns: target_service_moment From Entity: br_validation From cardinality: 0..* To Cardinality: 0..1 | |

Data

| Nr | code | display_value | status_to_set | status | description |
|----|------|---------------|---------------|--------|-------------|
|----|------|---------------|---------------|--------|-------------|

| | | | | | |
|---|----------|-------------------------------|-----------|---|--|
| 1 | lodge | Lodge::::Registrata | lodged | c | Application for service(s) is officially received by land office (action is automatically logged when application is saved for the first time)::::La pratica per i servizi formalmente ricevuta da ufficio territoriale |
| 2 | start | Start::::Comincia | pending | c | Provisional RRR Changes Made to Database as a result of application (action is automatically logged when a change is made to a rrr object)::::Apportate Modifiche Provvisorie di tipo RRR al Database come risultato della pratica |
| 3 | cancel | Cancel::::Cancella la pratica | cancelled | c | Service is cancelled by Land Office (action is automatically logged when a service is cancelled)::::Pratica cancellata da Ufficio Territoriale |
| 4 | complete | Complete::::Completa | completed | c | Application is ready for approval (action is automatically logged when service is marked as complete)::::Pratica pronta per approvazione |
| 5 | revert | Revert::::ITALIANO | pending | c | The status of the service has been reverted to pending from being completed (action is automatically logged when a service is reverted back for further work)::::ITALIANO |

Table: application_property

Details of the property associated with an application

Columns

| Name | Type | Optional | Default | Description |
|----------------|-------------|----------|---------|---|
| application_id | varchar(40) | False | | SOLA Extension - the application id |
| ba_unit_id | varchar(40) | False | | LADM Definition - the id for ba_unit |

Constraints

| Name | Type | Explanation |
|---------------------------|-------------|---|
| application_property_pkey | PRIMARY KEY | Combination of (application_id,ba_unit_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--|---|---|
| application_property_application_id_fk37 | From columns: application_id To Entity: application From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| application_property_ba_unit_id_fk41 | From columns: ba_unit_id To Entity: ba_unit From cardinality: 0..* To Cardinality: 1 | SOLA Extension relationship - no refinement |

Table: application_uses_source

Sources (documents) submitted with an application, created as a result of the application by land officers or further documents added to assist in the processing of the application

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|----------------|-------------|----------|---------|--|
| id | varchar(40) | False | | |
| application_id | varchar(40) | False | | SOLA Extension - the application id |
| source_id | varchar(40) | False | | LADM Definition - the source (document) id |
| is_primary | bool | False | false | It is a flag that shows if the source is primary for the particular application. |

Constraints

| Name | Type | Explanation |
|------------------------------|-------------|--|
| application_uses_source_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|---|---|
| application_uses_source_source_id_fk38 | From columns: source_id To Entity: source From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| application_uses_source_application_id_fk39 | From columns: application_id To Entity: application From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |

Table: request_type_requires_source_type

Source (documents) required for a particular (Service) Request received by a land office

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|-------------------|-------------|----------|---------|---|
| source_type_code | varchar(20) | False | | SOLA Extension - source type code |
| request_type_code | varchar(20) | False | | SOLA Extension - request type code |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| request_type_requires_source_type_pkey | PRIMARY KEY | Combination of (source_type_code,request_type_code) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|---|---|
| request_type_requires_source_type_request_type_code | From column: request_type_code To Entity: request_type From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| request_type_requires_source_type_source_type_code | From column: source_type_code To Entity: administrative_source_type From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |

Table: application_status_type

Reference Table / Code list for application status type

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | SOLA Extension - status type code |
| display_value | varchar(250) | False | | SOLA Extension - Display value for the status type |
| is_terminal | bool | False | false | |
| status | char(1) | False | 't' | SOLA Extension - Status of an instance of application status |
| description | varchar(555) | True | | SOLA Extension - Description of application status |

Constraints

| Name | Type | Explanation |
|------------------------------|-------------|--|
| application_status_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---|---|-------------|
| application_action_type_next_status_type | From columns: next_status_type_code From Entity: application_action_type From cardinality: 0..* To Cardinality: 0..1 | |
| application_status_type_code_fk125 | From columns: type_code From Entity: application_status From cardinality: 0..* To Cardinality: 1 | |
| request_type_starting_status_code_fk129 | From columns: starting_status_code From Entity: request_type From cardinality: 0..* To Cardinality: 1 | |
| application_action_type_start_status_type | From columns: start_status_type_code From Entity: application_action_type From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | is_terminal | status | description |
|----|---------------------|----------------------------------|-------------|--------|-------------|
| 1 | smdregnr-submit | Submit | true | c | |
| 2 | smdplanapp-submit | Submit | | c | |
| 3 | smdplanapp-registry | Registry (Regional Office) | | c | |

Table: type_action

This is the coded list of allowed operations on rrr and ba_unit. Present values are: new, remove, vary.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|-------------|
| code | varchar(20) | False | | |
| display_value | varchar(250) | False | | |
| description | varchar(555) | True | | |
| status | char(1) | False | 't' | |

Constraints

| Name | Type | Explanation |
|----------------------------------|-------------|--|
| type_action_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| type_action_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|------------------------------------|---|-------------|
| request_type_type_action_code_fk79 | From columns: type_action_code From Entity: request_type From cardinality: 0..* To Cardinality: 0..1 | |

Data

| Nr | code | display_value | description | status |
|----|--------|--------------------|-------------|--------|
| 1 | new | New::::ITALIANO | | c |
| 2 | vary | Vary::::ITALIANO | | c |
| 3 | cancel | Cancel::::ITALIANO | | c |

Table: application_party

Ghana extension: For each application can be a number of parties that can have different roles. In generic model, there were two parties referenced directly agent_id and contact_person_id. These two parties can be defined through this table so they are removed from the application.

Columns

| Name | Type | Optional | Default | Description |
|----------------|-------------|----------|---------|--|
| id | varchar(40) | False | | Meaningless id of the party within an application. |
| application_id | varchar(40) | False | | |
| party_id | varchar(40) | False | | |
| role_code | varchar(20) | False | | The role that a party can get in an application. The allowed values are from the coded list party_role_type where party_role_type.used_in_application is true. |

Constraints

| Name | Type | Explanation |
|-------------------------------|-------------|---|
| application_party_logical_key | UNIQUE | Combination of (application_id, party_id) is unique |
| application_party_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--|---|-------------|
| application_party_application_id_fk111 | From columns: application_id To Entity: application From cardinality: 0..* To Cardinality: 1 | |
| application_party_party_id_fk112 | From columns: party_id To Entity: party From cardinality: 0..* To Cardinality: 1 | |
| application_party_role_code_fk113 | From columns: role_code To Entity: party_role_type From cardinality: 0..* To Cardinality: 1 | |

Table: fee_type

Ghana extension: The types of fees applicable for a certain request.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|-------------|
| code | varchar(20) | False | | |
| display_value | varchar(250) | False | | |
| status | char(1) | False | 't' | |
| description | varchar(555) | True | | |

Constraints

| Name | Type | Explanation |
|-------------------------------|-------------|--|
| fee_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| fee_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|--------------------------------------|---|-------------|
| application_fee_fee_code_fk116 | From columns: fee_code From Entity: application_fee From cardinality: 0..* To Cardinality: 1 | |
| request_type_fee_type_fee_code_fk118 | From columns: fee_code From Entity: request_type_fee_type From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | status | description |
|----|-----------|----------------|--------|-------------|
| 1 | dutyStamp | Duty stamp tax | c | |

Table: application_fee

Ghana extension: The fees that are applicable to an application. The fees that are listed here are already calculated by other means and they are only recorded.

Columns

| Name | Type | Optional | Default | Description |
|----------------|----------------|----------|---------|---|
| id | varchar(40) | False | | |
| application_id | varchar(40) | False | | |
| fee_code | varchar(20) | False | | The type of the fee |
| paid_amount | numeric(20, 2) | False | | The amount paid for the fee type. This has to be equal or less than the total_amount. In order to be considered fully paid, it should be equal to total amount. |
| total_amount | numeric(20, 2) | False | | Total amount of the fee type that needs to be paid. |
| receipt_nr | varchar(20) | True | | The receipt number |

Constraints

| Name | Type | Explanation |
|------------------------------|-------------|---|
| application_fee_logical_key | UNIQUE | Combination of (application_id, fee_code) is unique |
| application_fee_amount_check | CHECK | Rule (paid_amount |
| application_fee_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--------------------------------------|---|-------------|
| application_fee_application_id_fk115 | From columns: application_id To Entity: application From cardinality: 0..* To Cardinality: 1 | |
| application_fee_fee_code_fk116 | From columns: fee_code To Entity: fee_type From cardinality: 0..* To Cardinality: 1 | |

Triggers

| Name | Event |
|--------------|------------------------|
| after_change | after insert or update |

Table: request_type_fee_type

Ghana extension: The types of fees applicable to a given request type

Columns

| Name | Type | Optional | Default | Description |
|--------------|-------------|----------|---------|-------------|
| request_code | varchar(20) | False | | |
| fee_code | varchar(20) | False | | |

Constraints

| Name | Type | Explanation |
|----------------------------|-------------|---|
| request_type_fee_type_pkey | PRIMARY KEY | Combination of (request_code,fee_code) is the primary key |

Relationships (from)

| Name | Information | Description |
|--|--|-------------|
| request_type_fee_type_request_code_fk117 | From columns: request_code To Entity: request_type From cardinality: 0..* To Cardinality: 1 | |
| request_type_fee_type_fee_code_fk118 | From columns: fee_code To Entity: fee_type From cardinality: 0..* To Cardinality: 1 | |

Table: action_data_field_type

Columns

| Name | Type | Optional | Default | Description |
|------------------|--------------|----------|---------|-------------|
| code | varchar(20) | False | | |
| display_value | varchar(250) | False | | |
| action_type_code | varchar(20) | False | | |
| type_code | varchar(20) | False | | |
| is_mandatory | bool | False | false | |
| status | char(1) | True | | |
| description | varchar(555) | True | | |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| action_data_field_type_display_in_action | UNIQUE | Combination of (display_value, action_type_code) is unique |
| action_data_field_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|---|-------------|
| action_data_field_type_action_type_code_fk122 | From columns: action_type_code To Entity: application_action_type From cardinality: 0..* To Cardinality: 1 | |
| action_data_field_type_type_code_fk131 | From columns: type_code To Entity: data_type From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|-----------------------------|--|-------------|
| action_data_type_code_fk128 | From columns: type_code From Entity: action_data From cardinality: 0..* To Cardinality: 1 | |

Table: application_action**Columns**

| Name | Type | Optional | Default | Description |
|-----------|--------------|----------|---------|-------------|
| id | varchar(40) | False | | |
| status_id | varchar(40) | False | | |
| type_code | varchar(20) | False | | |
| is_done | bool | False | false | |
| remarks | varchar(500) | True | | |

Constraints

| Name | Type | Explanation |
|---------------------------|-------------|---|
| application_action_action | UNIQUE | Combination of (status_id, type_code) is unique |
| application_action_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|------------------------------------|--|-------------|
| application_action_type_code_fk123 | From columns: type_code To Entity: application_action_type From cardinality: 0..* To Cardinality: 1 | |
| application_action_status_id_fk126 | From columns: status_id To Entity: application_status From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|-----------------------------|--|-------------|
| action_data_action_id_fk127 | From columns: action_id From Entity: action_data From cardinality: 0..* To Cardinality: 1 | |

Table: application_status**Columns**

| Name | Type | Optional | Default | Description |
|----------------|-------------|----------|---------|-------------|
| id | varchar(40) | False | | |
| application_id | varchar(40) | False | | |
| type_code | varchar(20) | False | | |
| is_current | bool | False | true | |

Constraints

| Name | Type | Explanation |
|-------------------------|-------------|--|
| application_status_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|--|-------------|
| application_status_application_id_fk124 | From columns: application_id To Entity: application From cardinality: 0..* To Cardinality: 1 | |
| application_status_type_code_fk125 | From columns: type_code To Entity: application_status_type From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|------------------------------------|---|-------------|
| application_action_status_id_fk126 | From columns: status_id From Entity: application_action From cardinality: 0..* To Cardinality: 1 | |

Table: action_data

Columns

| Name | Type | Optional | Default | Description |
|------------|--------------|----------|---------|-------------|
| action_id | varchar(40) | False | | |
| type_code | varchar(20) | False | | |
| data_value | varchar(500) | True | | |

Constraints

| Name | Type | Explanation |
|------------------|-------------|---|
| action_data_pkey | PRIMARY KEY | Combination of (action_id,type_code) is the primary key |

Relationships (from)

| Name | Information | Description |
|-----------------------------|---|-------------|
| action_data_action_id_fk127 | From columns: action_id To Entity: application_action From cardinality: 0..* To Cardinality: 1 | |
| action_data_type_code_fk128 | From columns: type_code To Entity: action_data_field_type From cardinality: 0..* To Cardinality: 1 | |

Table: data_type

Reference Table / Code list for categories of (service) requests received by a land office

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|---|
| code | varchar(20) | False | | SOLA Extension - The code request category type |
| display_value | varchar(250) | False | | SOLA Extension - The display value for the request category type |
| description | varchar(555) | True | | SOLA Extension - Description of the request category type |
| status | char(1) | False | 't' | SOLA Extension - Status of the request category type |

Constraints

| Name | Type | Explanation |
|--------------------------------|-------------|--|
| data_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| data_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|--|---|-------------|
| action_data_field_type_type_code_fk131 | From columns: type_code From Entity: action_data_field_type From cardinality: 0..* To Cardinality: 1 | |

Table: application_spatial_unit

Columns

| Name | Type | Optional | Default | Description |
|-----------------|-------------|----------|---------|-------------|
| application_id | varchar(40) | False | | |
| spatial_unit_id | varchar(40) | False | | |

Constraints

| Name | Type | Explanation |
|-------------------------------|-------------|--|
| application_spatial_unit_pkey | PRIMARY KEY | Combination of (application_id,spatial_unit_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--|---|-------------|
| application_spatial_unit_application_id_fk1 | From columns: application_id To Entity: application From cardinality: 0..* To Cardinality: 1 | |
| application_spatial_unit_spatial_unit_id_fk1 | From columns: spatial_unit_id To Entity: spatial_unit From cardinality: 0..* To Cardinality: 1 | |

View: application_log

A log of applications for land office servicesGhana extension: It gives a list of actions that has happen with an application.

Sequence: application_nr_seq

Allocates numbers 1 to 9999 for application number

Function: getlodgement

Parameters

| Name | Type | Direction | Description |
|----------|---------|-----------|-------------|
| fromdate | varchar | | From date |
| todate | varchar | | To date. |

Function: getlodgetiming

Parameters

| Name | Type | Direction | Description |
|----------|------|-----------|-------------|
| fromdate | date | | From date |
| todate | date | | To date |

address

| address.address | | | |
|---|----------------|--------------|---|
|  | id | varchar(40) | |
|  | description | varchar(255) | N |
|  | ext_address_id | varchar(40) | N |

Table: address

Describes a postal or location address

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|----------------|--------------|----------|---------|--|
| id | varchar(40) | False | | SOLA Extension - Address identifier |
| description | varchar(255) | True | | SOLA Extension - Description of an address |
| ext_address_id | varchar(40) | True | | SOLA Extension Identifier of an address referencing an external system. |

Constraints

| Name | Type | Explanation |
|--------------|-------------|--|
| address_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (to)

| Name | Information | Description |
|--------------------------------|--|---|
| party_physical_address_id_fk31 | From columns: physical_address_id From Entity: party From cardinality: 0..* To Cardinality: 0..1 | FLOSS SOLA relationship - no refinement |

| | | |
|--------------------------------------|--|---|
| spatial_unit_address_address_id_fk32 | From columns: address_id From Entity: spatial_unit_address From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| party_postal_address_id_fk119 | From columns: postal_address_id From Entity: party From cardinality: 0..* To Cardinality: 0..1 | |

system




Table: appuser

This table contains list of users, who has an access to the application, can login and do certain actions.

Columns

| Name | Type | Optional | Default | Description |
|------------|--------------|----------|-------------------|---|
| id | varchar(40) | False | | SOLA Extension - the SOLA user id |
| username | varchar(40) | False | | SOLA Extension - User name of a SOLA user |
| first_name | varchar(30) | False | | SOLA Extension - First name of SOLA user |
| last_name | varchar(30) | False | | SOLA Extension - Last name of SOLA user |
| passwd | varchar(100) | False | uuid_generate(16) | SOLA Extension - Password of the SOLA user |

| | | | | |
|-------------|--------------|-------|------|--|
| active | bool | False | true | SOLA Extension - the flag for whether a SOLA user is considered active (or not) |
| description | varchar(255) | True | | SOLA Extension - a description of the SOLA user |

Constraints

| Name | Type | Explanation |
|-------------------------|-------------|--|
| appuser_username_unique | UNIQUE | Combination of (username) is unique |
| appuser_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (to)

| Name | Information | Description |
|----------------------------------|--|---|
| application_assignee_id_fk42 | From columns: assignee_id From Entity: application From cardinality: 0..* To Cardinality: 0..1 | FLOSS SOLA relationship - no refinement |
| appuser_setting_user_id_fk43 | From columns: user_id From Entity: appuser_setting From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |
| appuser_appgroup_appuser_id_fk95 | From columns: appuser_id From Entity: appuser_appgroup From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | id | username | first_name |
|----|---------|----------|------------|
| 1 | test-id | test | Test |

| Nr | last_name | passwd | active | description |
|----|-----------|--|--------|-------------|
| 1 | The BOSS | 9f86d081884c7d659a2feaa0c55ad015a3bf4f1b2b0b822cd15d6c15b0f00a08 | true | |

Table: setting

Global settings for the FLOSS SOLA application

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|-------------|---------------|----------|---------|--|
| name | varchar(50) | False | | SOLA Extension - name of the setting |
| vl | varchar(2000) | False | | SOLA Extension - Value of the setting |
| active | bool | False | true | SOLA Extension - if the setting is active or not. |
| description | varchar(555) | False | | |

Constraints

| Name | Type | Explanation |
|--------------|-------------|--|
| setting_pkey | PRIMARY KEY | Combination of (name) is the primary key |

Data

| Nr | name | vl | active | description |
|----|---------------------------|--------|--------|---|
| 1 | map-srid | 32630 | true | The srid of the geographic data that are administered in the system. |
| 2 | map-west | 812000 | true | The most west coordinate. It is used in the map control. |
| 3 | map-south | 615000 | true | The most south coordinate. It is used in the map control. |
| 4 | map-east | 814200 | true | The most east coordinate. It is used in the map control. |
| 5 | map-north | 617200 | true | The most north coordinate. It is used in the map control. |
| 6 | map-tolerance | 0.01 | true | The tolerance that is used while snapping geometries to each other. If two points are within this distance are considered being in the same location. |
| 7 | map-shift-tolerance-rural | 20 | true | The shift tolerance of boundary points used in cadastre change in rural areas. |
| 8 | map-shift-tolerance-urban | 5 | true | The shift tolerance of boundary points used in cadastre change in urban areas. |

Table: appuser_setting

Software settings specific for a user within the FLOSS SOLA application

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|---------|---------------|----------|---------|--|
| user_id | varchar(40) | False | | SOLA Extension - SOLA user id |
| name | varchar(50) | False | | SOLA Extension - name of the setting |
| vl | varchar(2000) | False | | SOLA Extension - value of the setting |
| active | bool | False | true | SOLA Extension - if the setting is active |

Constraints

| Name | Type | Explanation |
|----------------------|-------------|--|
| appuser_setting_pkey | PRIMARY KEY | Combination of (user_id,name) is the primary key |

Relationships (from)

| Name | Information | Description |
|------------------------------|--|---|
| appuser_setting_user_id_fk43 | From columns: user_id To Entity: appuser From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |

Table: language

The languages that can be used within the FLOSS SOLA application.

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(7) | False | | SOLA Extension - A unique code of the localization. |
| display_value | varchar(250) | False | | SOLA Extension - displayed value of localisation setting |
| active | bool | False | true | SOLA Extension -status of the instance of language |
| is_default | bool | False | false | SOLA Extension - If it is the default. One of the records in this table can have this value true. |
| item_order | integer | False | 1 | |

Constraints

| Name | Type | Explanation |
|-------------------------------|-------------|--|
| language_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| language_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Data

| Nr | code | display_value | active | is_default | item_order |
|----|-------|--------------------|--------|------------|------------|
| 1 | en-US | English:::Inglese | true | true | 1 |
| 2 | it-IT | Italian:::Italiano | true | false | 2 |

Table: config_map_layer

Parameters for defining map layers in FLOSS SOLA gis componentLADM Reference ObjectFLOSS SOLA ExtensionLADM DefinitionNot Applicable

Columns

| Name | Type | Optional | Default | Description |
|----------------------------|---------------|----------|---------|--|
| name | varchar(50) | False | | SOLA Extension - name of map layer |
| title | varchar(100) | False | | |
| type_code | varchar(20) | False | | SOLA Extension - map layer type |
| wms_url | varchar(500) | True | | SOLA Extension - wms url of map layer |
| wms_layers | varchar(500) | True | | SOLA Extension - wms layer id (or name) |
| pojo_query_name | varchar(100) | False | | SOLA Extension - plain old java object query name |
| pojo_structure | varchar(500) | True | | SOLA Extension - plain old java object structure |
| pojo_query_name_for_select | varchar(100) | False | | SOLA Extension - plain old java object query name for select |
| shape_location | varchar(500) | True | | SOLA Extension - location of map layer shape definitions |
| style | varchar(4000) | True | | Map layer style given in SLD. |
| active | bool | False | true | SOLA Extension - flag to indicate whether instance of config map layer is active (or not) |
| item_order | integer | False | 0 | SOLA Extension - map layer order of display |
| visible_in_start | bool | False | true | If it is true, the layer will be switched on in the start of the map control. |

Constraints

| Name | Type | Explanation |
|---------------------------------|-------------|---|
| config_map_layer_style_required | CHECK | Rule (case when type_code = 'wms' then wms_url is not null and wms_layers is not null when type_code = 'pojo' then pojo_query_name is not null and pojo_structure is not null and style is not null when type_code = 'shape' then shape_location is not null and style is not null end) must be true It checks if the information is filled properly for each of type of the layer supported. |
| config_map_layer_title_unique | UNIQUE | Combination of (title) is unique |
| config_map_layer_pkey | PRIMARY KEY | Combination of (name) is the primary key |

Relationships (from)

| Name | Information | Description |
|---------------------------------|--|---|
| config_map_layer_type_code_fk47 | From columns: type_code To Entity: config_map_layer_type From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |

| | | |
|---|---|--|
| config_map_layer_pojo_query_name_fk10 | From columns: pojo_query_name To Entity: query From cardinality: 1 To Cardinality: 1 | |
| config_map_layer_pojo_query_name_for_select | From columns: pojo_query_name_for_select To Entity: query From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | name | title | type_code | wms_url |
|----|-----------------------------|--------------------------------------|-----------|---------|
| 1 | parcels | Parcels | pojo | |
| 2 | pending-parcels | Pending parcels | pojo | |
| 3 | applications | Applications | pojo | |
| 4 | parcels-historic-current-ba | Historic parcels with current titles | pojo | |
| 5 | regions | Regions | pojo | |
| 6 | districts | Districts | pojo | |
| 7 | sections | Sections | pojo | |
| 8 | blocks | Blocks | pojo | |

| Nr | wms_layers | pojo_query_name |
|----|------------|---|
| 1 | | SpatialResult.getParcels |
| 2 | | SpatialResult.getParcelsPending |
| 3 | | SpatialResult.getApplications |
| 4 | | SpatialResult.getParcelsHistoricWithCurrentBA |
| 5 | | SpatialResult.getRegion |
| 6 | | SpatialResult.getDistrict |
| 7 | | SpatialResult.getSection |
| 8 | | SpatialResult.getBlock |

| Nr | pojo_structure | pojo_query_name_for_select |
|----|-----------------------------|--|
| 1 | theGeom:Polygon,label:"" | dynamic.informationtool.get_parcel |
| 2 | theGeom:Polygon,label:"" | dynamic.informationtool.get_parcel_pending |
| 3 | theGeom:MultiPoint,label:"" | dynamic.informationtool.get_application |
| 4 | theGeom:Polygon,label:"" | dynamic.informationtool.get_parcel_historic_current_ba |
| 5 | theGeom:Polygon,label:"" | dynamic.informationtool.get_region |
| 6 | theGeom:Polygon,label:"" | dynamic.informationtool.get_district |
| 7 | theGeom:Polygon,label:"" | dynamic.informationtool.get_section |
| 8 | theGeom:Polygon,label:"" | dynamic.informationtool.get_block |

| Nr | shape_location | style | active | item_order | visible_in_start |
|----|----------------|-------|--------|------------|------------------|
|----|----------------|-------|--------|------------|------------------|

| | | | | | |
|---|--|--------------------------------|------|-----|------|
| 1 | | parcel.xml | true | 20 | true |
| 2 | | pending_parcel.xml | true | 30 | true |
| 3 | | application.xml | true | 70 | true |
| 4 | | parcel_historic_current_ba.xml | true | 10 | true |
| 5 | | region.xml | true | 80 | true |
| 6 | | district.xml | true | 90 | true |
| 7 | | section.xml | true | 100 | true |
| 8 | | block.xml | true | 110 | true |

Table: config_map_layer_type

Parameters for defining categories/types of map layers in FLOSS SOLA gis component

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | SOLA Extension - code identifying a config map layer type |
| display_value | varchar(250) | False | | SOLA Extension - displayed value of config map layer type |
| status | char(1) | False | | SOLA Extension - status of an instance of config map layer type |
| description | varchar(555) | True | | SOLA Extension - description of config map layer type |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| config_map_layer_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| config_map_layer_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---------------------------------|---|---|
| config_map_layer_type_code_fk47 | From columns: type_code From Entity: config_map_layer From cardinality: 0..* To Cardinality: 1 | FLOSS SOLA relationship - no refinement |

Data

| Nr | code | display_value | status | description |
|----|-------|--|--------|-------------|
| 1 | wms | WMS server with layers::::Server WMS con layer | c | |
| 2 | shape | Shapefile::::Shapefile | c | |
| 3 | pojo | Pojo layer::::Pojo layer | c | |

Table: br

In this table there are defined the business rules that are used in the system.

Columns

| Name | Type | Optional | Default | Description |
|-----------------------|---------------|----------|--------------------|--|
| id | varchar(100) | False | | The name of the business rule |
| display_name | varchar(250) | False | uuid_generate_v4() | This is a compact identifier for the business rule. |
| technical_type_code | varchar(20) | False | | The implementation type of the rule. This defines also which engine must interpret the rule. |
| feedback | varchar(2000) | True | | A message that will be sent to the user if the rule is broken. It is not always relevant. |
| description | varchar(1000) | True | | Here it comes description about the rule for the end-user. |
| technical_description | varchar(1000) | True | | This is a description aimed for developers. Here it should come also description about parameters used for the rule. |

Constraints

| Name | Type | Explanation |
|------------------------|-------------|---|
| br_display_name_unique | UNIQUE | Combination of (display_name) is unique |
| br_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|-----------------------------|---|-------------|
| br_technical_type_code_fk50 | From columns: technical_type_code To Entity: br_technical_type From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|--------------------------|--|-------------|
| br_validation_br_id_fk51 | From columns: br_id From Entity: br_validation From cardinality: 0..* To Cardinality: 1 | |
| br_definition_br_id_fk52 | From columns: br_id From Entity: br_definition From cardinality: 0..* To Cardinality: 1 | |

Table: br_technical_type

Here are specified the types of technical implementations of the business rule.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | The code |
| display_value | varchar(250) | False | | The value that will be displayed to the user |
| status | char(1) | False | | The status of this code itself. |
| description | varchar(555) | True | | Description |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| br_technical_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| br_technical_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|-----------------------------|--|-------------|
| br_technical_type_code_fk50 | From columns: technical_type_code From Entity: br From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | status | description |
|----|--------|-----------------|--------|--|
| 1 | sql | SQL:::SQL | c | The rule definition is based in sql and it is executed by the database engine. |
| 2 | drools | Drools:::Drools | c | The rule definition is based on Drools engine. |

Table: br_validation

In this table are defined the sets of rules that has to be executed. If for a rule there is not target moment specified, then the rule will not be part of the set.

Columns

| Name | Type | Optional | Default | Description |
|---------------------------|--------------|----------|--------------------|--|
| id | varchar(40) | False | uuid_generate_v4() | This is a meaningless identifier for the rule. |
| br_id | varchar(100) | False | | Name of the business rule |
| target_code | varchar(20) | False | | The type of the target of the the validation. |
| target_application_moment | varchar(20) | True | | The moment of execution of the rule if the target is the application. |
| target_service_moment | varchar(20) | True | | The moment of execution of the rule if the target is the service. |
| target_reg_moment | varchar(20) | True | | The moment of execution of the rule if the target is the ba_unit, rrr or cadastre_object. |
| target_request_type_code | varchar(20) | True | | If the target is a request type then here is given which is the request type. If this is null the business rule will be relevant for all services. |
| target_rrr_type_code | varchar(20) | True | | If the target is a registration on RRR then here is given the rrr type. If this is null the business rule validation will be valid for all rrr-s. |
| severity_code | varchar(20) | False | | Severity of the failure of the business rule. |
| order_of_execution | integer | False | 0 | The order of the execution of the rule. |

Constraints

| Name | Type | Explanation |
|--|--------|--|
| br_validation_service_request_type_valid | CHECK | Rule (target_request_type_code is null or (target_request_type_code is not null and target_code != 'application')) must be true It checks if the target_request_type_code is provided then the target_code must not be of value 'application'. |
| br_validation_rrr_rrr_type_valid | CHECK | Rule (target_rrr_type_code is null or (target_rrr_type_code is not null and target_code = 'rrr')) must be true It checks if the target_rrr_type_code is provided then the target_code must be of value 'rrr'. |
| br_validation_app_moment_unique | UNIQUE | Combination of (br_id, target_code, target_application_moment) is unique |
| br_validation_service_moment_unique | UNIQUE | Combination of (br_id, target_code, target_service_moment) is unique |
| br_validation_reg_moment_unique | UNIQUE | Combination of (br_id, target_code, target_reg_moment) is unique |
| br_validation_service_moment_valid | CHECK | Rule (target_code!= 'service' or (target_code = 'service' and target_application_moment is null and target_reg_moment is null)) must be true |
| br_validation_application_moment_valid | CHECK | Rule (target_code!= 'application' or (target_code = 'application' and target_service_moment is null and target_reg_moment is null)) must be true |

| | | |
|--------------------------------|-------------|--|
| br_validation_reg_moment_valid | CHECK | Rule (target_code in ('application', 'service') or (target_code not in ('application', 'service') and target_service_moment is null and target_application_moment is null)) must be true |
| br_validation_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---|---|-------------|
| br_validation_br_id_fk51 | From columns: br_id To Entity: br From cardinality: 0..* To Cardinality: 1 | |
| br_validation_severity_code_fk53 | From columns: severity_code To Entity: br_severity_type From cardinality: 0..* To Cardinality: 1 | |
| br_validation_target_code_fk54 | From columns: target_code To Entity: br_validation_target_type From cardinality: 0..* To Cardinality: 1 | |
| br_validation_target_request_type_code_fk55 | From columns: target_request_type_code To Entity: request_type From cardinality: 0..* To Cardinality: 0..1 | |
| br_validation_target_rrr_type_code_fk56 | From columns: target_rrr_type_code To Entity: rrr_type From cardinality: 0..* To Cardinality: 0..1 | |
| br_validation_target_application_moment_fk101 | From columns: target_application_moment To Entity: application_action_type From cardinality: 0..* To Cardinality: 0..1 | |
| br_validation_target_service_moment_fk102 | From columns: target_service_moment To Entity: service_action_type From cardinality: 0..* To Cardinality: 0..1 | |
| br_validation_target_reg_moment_fk103 | From columns: target_reg_moment To Entity: reg_status_type From cardinality: 0..* To Cardinality: 0..1 | |

Table: br_definition

Columns

| Name | Type | Optional | Default | Description |
|--------------|---------------|----------|------------|---|
| br_id | varchar(100) | False | | |
| active_from | date | False | | |
| active_until | date | False | 'infinity' | The date until this rule is active. |
| body | varchar(4000) | False | | The definition of the rule. The interpretation of the definition is done from the rule engine in use. |

Constraints

| Name | Type | Explanation |
|--------------------|-------------|---|
| br_definition_pkey | PRIMARY KEY | Combination of (br_id,active_from) is the primary key |

Relationships (from)

| Name | Information | Description |
|--------------------------|---|-------------|
| br_definition_br_id_fk52 | From columns: br_id To Entity: br From cardinality: 0..* To Cardinality: 1 | |

Table: br_severity_type

These are the types of severity of the business rules within the context of there use.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | The code |
| display_value | varchar(250) | False | | The value that will be displayed to the user |
| status | char(1) | False | | The status of this code itself. |
| description | varchar(555) | True | | Description |

Constraints

| Name | Type | Explanation |
|---------------------------------------|-------------|--|
| br_severity_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| br_severity_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|----------------------------------|--|-------------|
| br_validation_severity_code_fk53 | From columns: severity_code From Entity: br_validation From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | status | description |
|----|----------|---------------|--------|-------------|
| 1 | critical | Critical | c | |
| 2 | medium | Medium | c | |
| 3 | warning | Warning | c | |

Table: br_validation_target_type

The potential targets of the validation rules.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | The code |
| display_value | varchar(250) | False | | The value that will be displayed to the user |
| status | char(1) | False | | The status of this code itself. |
| description | varchar(555) | True | | Description |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| br_validation_target_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| br_validation_target_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|--------------------------------|--|-------------|
| br_validation_target_code_fk54 | From columns: target_code From Entity: br_validation From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | status | description |
|----|-----------------|----------------------------------|--------|--|
| 1 | application | Application::::ITALIANO | c | The target of the validation is the application. It accepts one parameter {id} which is the application id. |
| 2 | service | Service::::ITALIANO | c | The target of the validation is the service. It accepts one parameter {id} which is the service id. |
| 3 | rrr | Right or Restriction::::ITALIANO | c | The target of the validation is the rrr. It accepts one parameter {id} which is the rrr id. |
| 4 | ba_unit | Administrative Unit::::ITALIANO | c | The target of the validation is the ba_unit. It accepts one parameter {id} which is the ba_unit id. |
| 5 | source | Source::::ITALIANO | c | The target of the validation is the source. It accepts one parameter {id} which is the source id. |
| 6 | cadastre_object | Cadastre Object::::ITALIANO | c | The target of the validation is the transaction related with the cadastre change. It accepts one parameter {id} which is the transaction id. |

Table: approle

This table contains list of security roles, used to restrict access to the different parts of application, both on server and client side.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | The code |
| display_value | varchar(250) | False | | The value that will be displayed to the user |
| status | char(1) | False | | The status of this code itself. |
| description | varchar(555) | True | | Description |

Constraints

| Name | Type | Explanation |
|------------------------------|-------------|--|
| approle_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| approle_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|------------------------------------|--|-------------|
| approle_appgroup_approle_code_fk97 | From columns: approle_code From Entity: approle_appgroup From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | status | description |
|----|---------------------|---------------------------------|--------|--|
| 1 | DashbrdViewAssign | View Assigned Applications | c | View Assigned Applications in Dashboard |
| 2 | DashbrdViewUnassign | View Unassigned Applications | c | View Unassigned Applications in Dashboard |
| 3 | DashbrdViewOwn | View Own Applications | c | View Applications assigned to user in Dashboard |
| 4 | ApplnView | Search and View Applications | c | Search and view applications |
| 5 | ApplnCreate | Lodge new Applications | c | Lodge new Applications |
| 6 | ApplnStatus | Generate and View Status Report | c | Generate and View Status Report |
| 7 | ApplnAssignSelf | Assign Applications to Self | c | Able to assign (unassigned) applications to yourself |

| | | | | |
|----|---------------------|--|---|---|
| 8 | ApplnUnassignSelf | Unassign Applications to Self | c | Able to unassign (assigned) applications from yourself |
| 9 | ApplnAssignOthers | Assign Applications to Other Users | c | Able to assign (unassigned) applications to other users |
| 10 | ApplnUnassignOthers | Unassign Applications to Others | c | Able to unassign (assigned) applications to other users |
| 11 | StartService | Start Service | c | Start Service |
| 12 | CompleteService | Complete Service | c | Complete Service (prior to approval) |
| 13 | CancelService | Cancel Service | c | Cancel Service |
| 14 | RevertService | Revert Service | c | Revert previously Complete Service |
| 15 | ApplnRequisition | Requisition application and request | c | Request further information from applicant |
| 16 | ApplnResubmit | Resubmit Application | c | Resubmit (requisitioned) application |
| 17 | ApplnApprove | Approve Application | c | Approve Application |
| 18 | ApplnWithdraw | Withdraw Application | c | Applicant withdraws their application |
| 19 | ApplnReject | Reject Application | c | Land Office rejects an application |
| 20 | ApplnValidate | Validate Application | c | User manually runs validation rules for application |
| 21 | ApplnDispatch | Dispatch Application | c | Dispatch any documents to be returned to applicant and any certificates/reports/map prints requested by applicant |
| 22 | ApplnArchive | Archive Application | c | Paper Application File is stored in Land Office Archive |
| 23 | BaunitSave | Create or Modify BA Unit | c | Create or Modify BA Unit (Property) |
| 24 | BauunitrrrSave | Create or Modify Rights or Restrictions | c | Create or Modify Rights or Restrictions |
| 25 | BaunitParcelSave | Create or Modify (BA Unit) Parcels | c | Create or Modify (BA Unit) Parcels |
| 26 | BaunitNotatSave | Create or Modify (BA Unit) Notations | c | Create or Modify (BA Unit) Notations |
| 27 | BaunitCertificate | Generate and Print (BA Unit) Certificate | c | Generate and Print (BA Unit) Certificate |
| 28 | BaunitSearch | Search BA Unit | c | Search BA Unit |

| | | | | |
|----|-------------------|------------------------------------|---|------------------------------------|
| 29 | TransactionCommit | Approve (and Cancel) Transaction | c | Approve (and Cancel) Transaction |
| 30 | ViewMap | View Cadastral Map | c | View Cadastral Map |
| 31 | PrintMap | Print Map | c | Print Map |
| 32 | ParcelSave | Create or modify (Cadastre) Parcel | c | Create or modify (Cadastre) Parcel |
| 33 | PartySave | Create or modify Party | c | Create or modify Party |
| 34 | SourceSave | Create or modify Source | c | Create or modify Source |
| 35 | SourceSearch | Search Sources | c | Search sources |
| 36 | SourcePrint | Print Sources | c | Print Source |
| 37 | ReportGenerate | Generate and View Reports | c | Generate and View reports |
| 38 | ArchiveApps | Archive applications | c | Archive applications |
| 39 | ManageSecurity | Manage users, groups and roles | c | Manage users, groups and roles |
| 40 | ManageRefdata | Manage reference data | c | Manage reference data |
| 41 | ManageSettings | Manage system settings | c | Manage system settings |
| 42 | ApplnEdit | Application Edit | c | Allows editing of Applications |
| 43 | ManageBR | Manage business rules | c | Allows to manage business rules |

Table: approle_appgroup

This many-to-many table contains groups, related to security roles. Allows to have multiple roles for one group.

Columns

| Name | Type | Optional | Default | Description |
|--------------|-------------|----------|---------|-------------|
| approle_code | varchar(20) | False | | |
| appgroup_id | varchar(40) | False | | |

Constraints

| Name | Type | Explanation |
|-----------------------|-------------|---|
| approle_appgroup_pkey | PRIMARY KEY | Combination of (approle_code, appgroup_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|------------------------------------|---|-------------|
| approle_appgroup_approle_code_fk97 | From columns: approle_code To Entity: approle From cardinality: 0..* To Cardinality: 1 | |
| approle_appgroup_appgroup_id_fk98 | From columns: appgroup_id To Entity: appgroup From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | approle_code | appgroup_id |
|----|---------------------|----------------|
| 1 | DashbrdViewAssign | super-group-id |
| 2 | DashbrdViewUnassign | super-group-id |
| 3 | DashbrdViewOwn | super-group-id |
| 4 | ApplnView | super-group-id |
| 5 | ApplnCreate | super-group-id |
| 6 | ApplnStatus | super-group-id |
| 7 | ApplnAssignSelf | super-group-id |
| 8 | ApplnUnassignSelf | super-group-id |
| 9 | ApplnAssignOthers | super-group-id |
| 10 | ApplnUnassignOthers | super-group-id |

Table: appgroup

This table contains list of groups, which are used to group users with similar rights in the system.

Columns

| Name | Type | Optional | Default | Description |
|-------------|--------------|----------|---------|-------------|
| id | varchar(40) | False | | |
| name | varchar(300) | False | | |
| description | varchar(500) | True | | |

Constraints

| Name | Type | Explanation |
|----------------------|-------------|--|
| appgroup_name_unique | UNIQUE | Combination of (name) is unique |
| appgroup_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (to)

| Name | Information | Description |
|-----------------------------------|---|-------------|
| appuser_appgroup_appgroup_id_fk96 | From columns: appgroup_id From Entity: appuser_appgroup From cardinality: 0..* To Cardinality: 1 | |
| approle_appgroup_appgroup_id_fk98 | From columns: appgroup_id From Entity: approle_appgroup From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | id | name | description |
|----|----------------|-------------|---|
| 1 | super-group-id | Super group | This is a group of users that has right in anything. It is used in developement. In production must be removed. |

Table: appuser_appgroup

This many-to-many table contains users, related to groups. Allows to have multiple groups for one user.

Columns

| Name | Type | Optional | Default | Description |
|-------------|-------------|----------|---------|-------------|
| appuser_id | varchar(40) | False | | |
| appgroup_id | varchar(40) | False | | |

Constraints

| Name | Type | Explanation |
|-----------------------|-------------|---|
| appuser_appgroup_pkey | PRIMARY KEY | Combination of (appuser_id, appgroup_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|-----------------------------------|---|-------------|
| appuser_appgroup_appuser_id_fk95 | From columns: appuser_id To Entity: appuser From cardinality: 0..* To Cardinality: 1 | |
| appuser_appgroup_appgroup_id_fk96 | From columns: appgroup_id To Entity: appgroup From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | appuser_id | appgroup_id |
|----|------------|----------------|
| 1 | test-id | super-group-id |

Table: query

It defines a query that can be executed by the search ejb.

Columns

| Name | Type | Optional | Default | Description |
|-------------|---------------|----------|---------|--|
| name | varchar(100) | False | | Unique identifier for the query |
| sql | varchar(4000) | False | | Query definition |
| description | varchar(1000) | True | | Technical description about the query. |

Constraints

| Name | Type | Explanation |
|------------|-------------|--|
| query_pkey | PRIMARY KEY | Combination of (name) is the primary key |

Relationships (to)

| Name | Information | Description |
|---|--|-------------|
| query_field_query_name_fk104 | From columns: query_name From Entity: query_field From cardinality: 0..* To Cardinality: 1 | |
| config_map_layer_pojo_query_name_fk105 | From columns: pojo_query_name From Entity: config_map_layer From cardinality: 1 To Cardinality: 1 | |
| config_map_layer_pojo_query_name_for_select_fk106 | From columns: pojo_query_name_for_select From Entity: config_map_layer From cardinality: 0..* To Cardinality: 1 | |
| map_search_option_query_name_fk110 | From columns: query_name From Entity: map_search_option From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr |
|----|
| 1 |
| 2 |
| 3 |
| 4 |
| 5 |
| 6 |
| 7 |
| 8 |

| |
|----|
| 9 |
| 10 |
| 11 |
| 12 |
| 13 |
| 14 |
| 15 |
| 16 |
| 17 |
| 18 |
| 19 |
| 20 |
| 21 |
| 22 |
| 23 |

| | sql | description |
|---------------------|--|-------------|
| t.getParcels | select co.id, co.name_lastpart as label, st_asewkb(co.geom_polygon) as the_geom from cadastre.cadastre_object co where type_code= 'parcel' and status_code= 'current' and ST_Intersects(co.geom_polygon, ST_SetSRID(ST_MakeBox3D(ST_Point({minx}, {miny}),ST_Point({maxx}, {maxy})), {srid})) | |
| t.getParcelsPending | select co.id, co.name_lastpart as label, st_asewkb(co.geom_polygon) as the_geom from cadastre.cadastre_object co where type_code= 'parcel' and status_code= 'pending' and ST_Intersects(co.geom_polygon, ST_SetSRID(ST_MakeBox3D(ST_Point({minx}, {miny}),ST_Point({maxx}, {maxy})), {srid})) union select co.id, co.name_firstpart '/' co.name_lastpart as label, st_asewkb(co_t.geom_polygon) as the_geom from cadastre.cadastre_object co inner join cadastre.cadastre_object_target co_t on co.id = co_t.cadastre_object_id and co_t.geom_polygon is not null where ST_Intersects(co_t.geom_polygon, ST_SetSRID(ST_MakeBox3D(ST_Point({minx}, {miny}),ST_Point({maxx}, {maxy})), {srid})) and co_t.transaction_id in (select id from transaction.transaction where status_code not in ('approved')) | |
| t.getApplications | select id, nr as label, st_asewkb(location) as the_geom from application.application where ST_Intersects(location, ST_SetSRID(ST_MakeBox3D(ST_Point({minx}, {miny}),ST_Point({maxx}, {maxy})), {srid})) | |

| | | |
|-----------------------------------|--|--|
| rmationtool.get_parcel | <pre> select co.id, co.name_firstpart '/' co.name_lastpart as parcel_nr, (select string_agg(ba.name_firstpart '/' ba.name_lastpart, ',') from administrative.ba_unit_contains_spatial_unit bas, administrative.ba_unit ba where spatial_unit_id= co.id and bas.ba_unit_id= ba.id) as ba_units, (SELECT spatial_value_area.size FROM cadastre.spatial_value_area WHERE spatial_value_area.type_code='officialArea' and spatial_value_area.spatial_unit_id = co.id) AS area_official_sqm, st_asewkb(co.geom_polygon) as the_geom from cadastre.cadastre_object co where type_code= 'parcel' and status_code= 'current' and ST_Intersects(co.geom_polygon, ST_SetSRID(ST_GeomFromWKB({wkb_geom}), #{srid})) </pre> | |
| rmationtool.get_parcel_pending | <pre> select co.id, co.name_firstpart '/' co.name_lastpart as parcel_nr, (SELECT spatial_value_area.size FROM cadastre.spatial_value_area WHERE spatial_value_area.type_code='officialArea' and spatial_value_area.spatial_unit_id = co.id) AS area_official_sqm, st_asewkb(co.geom_polygon) as the_geom from cadastre.cadastre_object co where type_code= 'parcel' and ((status_code= 'pending' and ST_Intersects(co.geom_polygon, ST_SetSRID(ST_GeomFromWKB({wkb_geom}), #{srid}))) or (co.id in (select cadastre_object_id from cadastre.cadastre_object_target co_t inner join transaction.transaction t on co_t.transaction_id=t.id where ST_Intersects(co_t.geom_polygon, ST_SetSRID(ST_GeomFromWKB({wkb_geom}), #{srid}))) and t.status_code not in ('approved')))) </pre> | |
| rmationtool.get_application | <pre> select id, nr, st_asewkb(location) as the_geom from application.application where ST_Intersects(location, ST_SetSRID(ST_GeomFromWKB({wkb_geom}), #{srid})) </pre> | |
| t.getParcelsHistoricWithCurrentBA | <pre> select co.id, co.name_firstpart '/' co.name_lastpart as label, st_asewkb(co.geom_polygon) as the_geom from cadastre.cadastre_object co inner join administrative.ba_unit_contains_spatial_unit ba_co on co.id = ba_co.spatial_unit_id inner join administrative.ba_unit ba_unit on ba_unit.id= ba_co.ba_unit_id where co.type_code='parcel' and co.status_code= 'historic' and ba_unit.status_code = 'current' and ST_Intersects(co.geom_polygon, ST_SetSRID(ST_MakeBox3D(ST_Point({minx}, #{miny}),ST_Point({maxx}, #{maxy})), #{srid})) </pre> | |

| | | |
|--|--|--|
| informationtool.get_parcel_historic_current_ba | <pre> select co.id, co.name_firstpart '/' co.name_lastpart as parcel_nr, (select string_agg(ba.name_firstpart '/' ba.name_lastpart, ',') from administrative.ba_unit_contains_spatial_unit bas, administrative.ba_unit ba where spatial_unit_id= co.id and bas.ba_unit_id= ba.id) as ba_units, (SELECT spatial_value_area.size FROM cadastre.spatial_value_area WHERE spatial_value_area.type_code='officialArea' and spatial_value_area.spatial_unit_id = co.id) AS area_official_sqm, st_asewkb(co.geom_polygon) as the_geom from cadastre.cadastre_object co inner join administrative.ba_unit_contains_spatial_unit ba_co on co.id = ba_co.spatial_unit_id inner join administrative.ba_unit ba_unit on ba_unit.id= ba_co.ba_unit_id where co.type_code='parcel' and co.status_code= 'historic' and ba_unit.status_code = 'current' and ST_Intersects(co.geom_polygon, ST_SetSRID(ST_GeomFromWKB({wkb_geom}), #{srid})) </pre> | |
| cadastre_object_by_number | <pre> select id, name_firstpart '/' name_lastpart as label, st_asewkb(geom_polygon) as the_geom from cadastre.cadastre_object where status_code= 'current' and compare_strings(#{search_string}, name_firstpart '/' name_lastpart) limit 30 </pre> | |
| cadastre_object_by_baunit | <pre> select distinct co.id, ba_unit.name_firstpart '/' ba_unit.name_lastpart ' > ' co.name_firstpart '/' co.name_lastpart as label, st_asewkb(geom_polygon) as the_geom from cadastre.cadastre_object co inner join administrative.ba_unit_contains_spatial_unit bas on co.id = bas.spatial_unit_id inner join administrative.ba_unit on ba_unit.id = bas.ba_unit_id where (co.status_code= 'current' or ba_unit.status_code= 'current') and compare_strings(#{search_string}, ba_unit.name_firstpart '/' ba_unit.name_lastpart) limit 30 </pre> | |
| cadastre_object_by_baunit_owner | <pre> select distinct co.id, coalesce(party.name, '') ' ' coalesce(party.last_name, '') ' > ' co.name_firstpart '/' co.name_lastpart as label, st_asewkb(co.geom_polygon) as the_geom from cadastre.cadastre_object co inner join administrative.ba_unit_contains_spatial_unit bas on co.id = bas.spatial_unit_id inner join administrative.ba_unit on bas.ba_unit_id= ba_unit.id inner join administrative.rrr on (ba_unit.id = rrr.ba_unit_id and rrr.status_code = 'current' and rrr.type_code = 'ownership') inner join administrative.party_for_rrr pfr on rrr.id = pfr.rrr_id inner join party.party on pfr.party_id= pfr.party_id where (co.status_code= 'current' or ba_unit.status_code= 'current') and compare_strings(#{search_string}, coalesce(party.name, '') ' ' coalesce(party.last_name, '')) limit 30 </pre> | |

| | | |
|---------------------------------|--|---------------------------|
| ch.cadastre_object_by_baunit_id | SELECT id, name_firstpart '/' name_lastpart as label, st_asewkb(geom_polygon) as the_geom FROM cadastre.cadastre_object WHERE transaction_id IN (SELECT cot.transaction_id FROM (administrative.ba_unit_contains_spatial_unit ba_su INNER JOIN cadastre.cadastre_object co ON ba_su.spatial_unit_id = co.id) INNER JOIN cadastre.cadastre_object_target cot ON co.id = cot.cadastre_object_id WHERE ba_su.ba_unit_id = #{search_string}) AND (SELECT COUNT(1) FROM administrative.ba_unit_contains_spatial_unit WHERE spatial_unit_id = cadastre_object.id) = 0 AND status_code = 'current' | Query used by BaUnitBean. |
| t.getRegion | select sup.id, sup.label, st_asewkb(sup.geom) as the_geom from cadastre.spatial_unit_group as sup where hierarchy_level=1 and ST_Intersects(sup.geom, ST_SetSRID(ST_MakeBox3D(ST_Point(#{minx}, #{miny}),ST_Point(#{maxx}, #{maxy})), #{srid})) | |
| t.getDistrict | select sup.id, sup.label, st_asewkb(sup.geom) as the_geom from cadastre.spatial_unit_group as sup where hierarchy_level=2 and ST_Intersects(sup.geom, ST_SetSRID(ST_MakeBox3D(ST_Point(#{minx}, #{miny}),ST_Point(#{maxx}, #{maxy})), #{srid})) | |
| t.getSection | select sup.id, sup.label, st_asewkb(sup.geom) as the_geom from cadastre.spatial_unit_group as sup where hierarchy_level=3 and ST_Intersects(sup.geom, ST_SetSRID(ST_MakeBox3D(ST_Point(#{minx}, #{miny}),ST_Point(#{maxx}, #{maxy})), #{srid})) | |
| t.getBlock | select sup.id, sup.label, st_asewkb(sup.geom) as the_geom from cadastre.spatial_unit_group as sup where hierarchy_level=4 and ST_Intersects(sup.geom, ST_SetSRID(ST_MakeBox3D(ST_Point(#{minx}, #{miny}),ST_Point(#{maxx}, #{maxy})), #{srid})) | |
| rmationtool.get_region | select sup.id, sup.label, st_asewkb(sup.geom) as the_geom from cadastre.spatial_unit_group as sup where hierarchy_level=1 and ST_Intersects(sup.geom, ST_SetSRID(ST_GeomFromWKB(#{wkb_geom}), #{srid})) | |
| rmationtool.get_district | select sup.id, sup.label, st_asewkb(sup.geom) as the_geom from cadastre.spatial_unit_group as sup where hierarchy_level=2 and ST_Intersects(sup.geom, ST_SetSRID(ST_GeomFromWKB(#{wkb_geom}), #{srid})) | |
| rmationtool.get_section | select sup.id, sup.label, st_asewkb(sup.geom) as the_geom from cadastre.spatial_unit_group as sup where hierarchy_level=3 and ST_Intersects(sup.geom, ST_SetSRID(ST_GeomFromWKB(#{wkb_geom}), #{srid})) | |
| rmationtool.get_block | select sup.id, sup.label, st_asewkb(sup.geom) as the_geom from cadastre.spatial_unit_group as sup where hierarchy_level=4 and ST_Intersects(sup.geom, ST_SetSRID(ST_GeomFromWKB(#{wkb_geom}), #{srid})) | |
| district | select id, name as label, st_asewkb(geom) as the_geom from cadastre.spatial_unit_group where compare_strings(#{search_string}, name) and hierarchy_level=2 limit 30 | |

| | | |
|---------|--|--|
| section | <pre>select id, name as label, st_asewkb(geom) as the_geom from cadastre.spatial_unit_group where compare_strings("#{search_string}", name) and hierarchy_level=2 limit 30</pre> | |
| block | <pre>select id, name as label, st_asewkb(geom) as the_geom from cadastre.spatial_unit_group where compare_strings("#{search_string}", name) and hierarchy_level=2 limit 30</pre> | |

Table: map_search_option

This table contains information about the options to search objects in the map. The list of options here will be used to configure the list of search by options in the Map Search Component.

Columns

| Name | Type | Optional | Default | Description |
|--------------------|----------------|----------|---------|---|
| code | varchar(20) | False | | The unique code of the search option. This code is used programatically. |
| title | varchar(50) | False | | The unique title that is visible to the user. It can be localizable. |
| query_name | varchar(100) | False | | The query that will be used for retrieving the search results. The query requires only one parameter: search_string. So, it means that queries that are used here, should contain only one parameter with this name. These queries also should return only 3 fields: - id: Unique id of returned match - label: What will be displayed to the user - the_geom: the WKB form of the geometry |
| active | bool | False | true | If the search option is active or not |
| min_search_str_len | smallint | False | 3 | The minimum number of characters required for the search string. |
| zoom_in_buffer | numeric(20, 2) | False | 50 | The buffer distance to use when zooming the map to display the selected object. The units of this value are dependent on the coordinate system of the map (usually meters). |
| description | varchar(500) | True | | A description about the option |

Constraints

| Name | Type | Explanation |
|--------------------------------|-------------|--|
| map_search_option_title_unique | UNIQUE | Combination of (title) is unique |
| map_search_option_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (from)

| Name | Information | Description |
|------------------------------------|---|-------------|
| map_search_option_query_name_fk110 | From columns: query_name To Entity: query From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | title | query_name | active |
|----|--------|--------|--------------------------------------|--------|
| 1 | NUMBER | Number | map_search.cadastre_object_by_number | true |

| | | | | |
|---|-----------------|-----------------|--|------|
| 2 | BAUNIT | Property number | map_search.cadastre_object_by_baunit | true |
| 3 | OWNER_OF_BAUNIT | Property owner | map_search.cadastre_object_by_baunit_owner | true |
| 4 | DISTRICT | District | map_search.district | true |
| 5 | SECTION | Section | map_search.section | true |
| 6 | BLOCK | Block | map_search.block | true |

| Nr | min_search_str_len | zoom_in_buffer | description |
|----|--------------------|----------------|-------------|
| 1 | 3 | 50 | |
| 2 | 3 | 50 | |
| 3 | 3 | 50 | |
| 4 | 3 | 50 | |
| 5 | 3 | 50 | |
| 6 | 3 | 50 | |

Table: query_field

It defines a field in the query. The field is returned by the select part. Not for all queries is needed to define the fields. It becomes important only for queries that will need to have fields that has to be localized.

Columns

| Name | Type | Optional | Default | Description |
|----------------|--------------|----------|---------|--|
| query_name | varchar(100) | False | | Query identifier |
| index_in_query | integer | False | | |
| name | varchar(100) | False | | The index of the field in the query. The index is zero based. It should not exceed the number of fields in the select part of the query. |
| display_value | varchar(200) | True | | The title of the field to be used in the query. It can be localized. |

Constraints

| Name | Type | Explanation |
|---------------------------|-------------|--|
| query_field_display_value | UNIQUE | Combination of (query_name, display_value) is unique |
| query_field_name | UNIQUE | Combination of (query_name, name) is unique |
| query_field_pkey | PRIMARY KEY | Combination of (query_name, index_in_query) is the primary key |

Relationships (from)

| Name | Information | Description |
|------------------------------|---|-------------|
| query_field_query_name_fk104 | From columns: query_name To Entity: query From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | query_name | index_in_query |
|----|--|----------------|
| 1 | dynamic.informationtool.get_parcel | 1 |
| 2 | dynamic.informationtool.get_parcel | 2 |
| 3 | dynamic.informationtool.get_parcel | 3 |
| 4 | dynamic.informationtool.get_parcel | 0 |
| 5 | dynamic.informationtool.get_parcel | 4 |
| 6 | dynamic.informationtool.get_parcel_pending | 0 |
| 7 | dynamic.informationtool.get_parcel_pending | 1 |
| 8 | dynamic.informationtool.get_parcel_pending | 2 |
| 9 | dynamic.informationtool.get_parcel_pending | 3 |
| 10 | dynamic.informationtool.get_application | 0 |
| 11 | dynamic.informationtool.get_application | 1 |
| 12 | dynamic.informationtool.get_application | 2 |

| | | |
|----|--|---|
| 13 | dynamic.informationtool.get_parcel_historic_current_ba | 0 |
| 14 | dynamic.informationtool.get_parcel_historic_current_ba | 1 |
| 15 | dynamic.informationtool.get_parcel_historic_current_ba | 2 |
| 16 | dynamic.informationtool.get_parcel_historic_current_ba | 3 |
| 17 | dynamic.informationtool.get_parcel_historic_current_ba | 4 |
| 18 | dynamic.informationtool.get_region | 0 |
| 19 | dynamic.informationtool.get_region | 1 |
| 20 | dynamic.informationtool.get_region | 2 |
| 21 | dynamic.informationtool.get_district | 0 |
| 22 | dynamic.informationtool.get_district | 1 |
| 23 | dynamic.informationtool.get_district | 2 |
| 24 | dynamic.informationtool.get_section | 0 |
| 25 | dynamic.informationtool.get_section | 1 |
| 26 | dynamic.informationtool.get_section | 2 |
| 27 | dynamic.informationtool.get_block | 0 |
| 28 | dynamic.informationtool.get_block | 1 |
| 29 | dynamic.informationtool.get_block | 2 |

| Nr | name | display_value |
|----|-------------------|--------------------------------|
| 1 | parcel_nr | Parcel number::::ITALIANO |
| 2 | ba_units | Properties::::ITALIANO |
| 3 | area_official_sqm | Official area (m2)::::ITALIANO |
| 4 | id | |
| 5 | the_geom | |
| 6 | id | |
| 7 | parcel_nr | Parcel number::::ITALIANO |
| 8 | area_official_sqm | Official area (m2)::::ITALIANO |
| 9 | the_geom | |
| 10 | id | |
| 11 | nr | Number::::Numero |
| 12 | the_geom | |
| 13 | id | |
| 14 | parcel_nr | Parcel number::::ITALIANO |
| 15 | ba_units | Properties::::ITALIANO |
| 16 | area_official_sqm | Official area (m2)::::ITALIANO |
| 17 | the_geom | |
| 18 | id | |
| 19 | label | Region |
| 20 | the_geom | |
| 21 | id | |
| 22 | label | District |

| | | |
|----|----------|---------|
| 23 | the_geom | |
| 24 | id | |
| 25 | label | Section |
| 26 | the_geom | |
| 27 | id | |
| 28 | label | Block |
| 29 | the_geom | |

View: user_roles

This view is used to retrieve the roles of a user.

View: br_current

It retrieves the active business rules.

View: br_report

This view is used in a report to document the business rules.

Function: setPassword

This function changes the password of the user.

Parameters

| Name | Type | Direction | Description |
|---------|---------|-----------|--|
| usrName | varchar | | The user name. |
| pass | varchar | | Password. The password is given encrypted. |

Function: get_setting

Gets the value of a setting.

Parameters

| Name | Type | Direction | Description |
|--------------|---------|-----------|---------------|
| setting_name | varchar | | Setting name. |

document

document.document



id

varchar(40)



nr

varchar(15)

U

extension

varchar(5)



body

blob



description

varchar(400)

N

Document functions

document_nr_seq()

Table: document

An extension of the source table to contain the image files of scanned documents forming part of the land office archive including the paper documents presented or created through cadastre or registration processes

LADM Reference Object

FLOSS SOLA Extension

LADM Definition

Not Applicable

Columns

| Name | Type | Optional | Default | Description |
|-------------|--------------|----------|---------|--|
| id | varchar(40) | False | | LADM Definition - The identifier of the source document |
| nr | varchar(15) | False | | SOLA Extension - A unique number to identify the document |
| extension | varchar(5) | False | | SOLA Extension - The extension of the original file. |
| body | bytea | False | | SOLA Extension - The content of the document |
| description | varchar(100) | True | | SOLA Extension - A name to recognize the document |

Constraints

| Name | Type | Explanation |
|--------------------|-------------|--|
| document_nr_unique | UNIQUE | Combination of (nr) is unique |
| document_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Sequence: document_nr_seq

Allocates numbers 1 to 9999 for document number.

transaction




Table: reg_status_type

This table has the list of statuses that a registration about Rights/Restrictions/ Responsibilities/ Cadastral objects / Sources can have.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | The code of the status that an rrr can have |
| display_value | varchar(250) | False | | The value that will be displayed to the user |
| description | varchar(555) | True | | Description of the status |
| status | char(1) | False | | The status of this code itself. |

Constraints

| Name | Type | Explanation |
|--------------------------------------|-------------|--|
| reg_status_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| reg_status_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|---------------------------------------|---|-------------|
| rrr_status_code_fk59 | From columns: status_code From Entity: rrr From cardinality: 0..* To Cardinality: 1 | |
| ba_unit_status_code_fk60 | From columns: status_code From Entity: ba_unit From cardinality: 0..* To Cardinality: 1 | |
| cadastre_object_status_code_fk62 | From columns: status_code From Entity: cadastre_object From cardinality: 0..* To Cardinality: 1 | |
| notation_status_code_fk68 | From columns: status_code From Entity: notation From cardinality: 0..* To Cardinality: 1 | |
| source_status_code_fk86 | From columns: status_code From Entity: source From cardinality: 0..* To Cardinality: 0..1 | |
| br_validation_target_reg_moment_fk103 | From columns: target_reg_moment From Entity: br_validation From cardinality: 0..* To Cardinality: 0..1 | |

Data

| Nr | code | display_value | description | status |
|----|----------|---------------|-------------|--------|
| 1 | current | Current | | c |
| 2 | pending | Pending | | c |
| 3 | historic | Historic | | c |
| 4 | previous | Previous | | c |

Table: transaction

Changes in the system come by transactions. A transaction is initiated (optionally) by a service. By introducing the concept of transaction it can be traced how the changes in the administrative schema came. Also by approving the transaction we can approve changes or by rejecting a transaction we can remove the pending changes that came with it and restore the previous state of the administrative schema.

Columns

| Name | Type | Optional | Default | Description |
|---------------------|-------------|----------|-----------|---|
| id | varchar(40) | False | | Meaningless id. |
| from_application_id | varchar(40) | False | | Ghana extension: This was from_service_id. Because now the service is merged into the application, the transaction can be started from a application. |
| status_code | varchar(20) | False | 'pending' | The status of the transaction. |
| approval_datetime | timestamp | True | | The approval datetime of the transaction. |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| transaction_from_application_id_unique | UNIQUE | Combination of (from_application_id) is unique |
| transaction_pkey | PRIMARY KEY | Combination of (id) is the primary key |

Relationships (from)

| Name | Information | Description |
|---------------------------------------|--|-------------|
| transaction_status_code_fk77 | From columns: status_code To Entity: transaction_status_type From cardinality: 0..* To Cardinality: 1 | |
| transaction_from_application_id_fk134 | From columns: from_application_id To Entity: application From cardinality: 0..* To Cardinality: 1 | |

Relationships (to)

| Name | Information | Description |
|------------------------------|--|-------------|
| notation_transaction_id_fk74 | From columns: transaction_id From Entity: notation From cardinality: 0..* To Cardinality: 1 | |
| rrr_transaction_id_fk81 | From columns: transaction_id From Entity: rrr From cardinality: 0..* To Cardinality: 1 | |

| | | |
|---|---|--|
| ba_unit_transaction_id_fk82 | From columns: transaction_id From Entity: ba_unit From cardinality: 0..* To Cardinality: 0..1 | |
| source_transaction_id_fk85 | From columns: transaction_id From Entity: source From cardinality: 0..* To Cardinality: 0..1 | |
| cadastre_object_transaction_id_fk88 | From columns: transaction_id From Entity: cadastre_object From cardinality: 0..* To Cardinality: 1 | |
| survey_point_transaction_id_fk91 | From columns: transaction_id From Entity: survey_point From cardinality: 0..* To Cardinality: 1 | |
| cadastre_object_target_transaction_id_fk92 | From columns: transaction_id From Entity: cadastre_object_target From cardinality: 0..* To Cardinality: 1 | |
| transaction_source_transaction_id_fk93 | From columns: transaction_id From Entity: transaction_source From cardinality: 0..* To Cardinality: 1 | |
| cadastre_object_node_target_transaction_id_fk97 | From columns: transaction_id From Entity: cadastre_object_node_target From cardinality: 0..* To Cardinality: 1 | |
| ba_unit_target_transaction_id_fk109 | From columns: transaction_id From Entity: ba_unit_target From cardinality: 0..* To Cardinality: 1 | |

Table: transaction_status_type

This table has the list of statuses that a transaction can take. Potential values are current, pending, rejected.

Columns

| Name | Type | Optional | Default | Description |
|---------------|--------------|----------|---------|--|
| code | varchar(20) | False | | The code of the status that an rrr can have |
| display_value | varchar(250) | False | | The value that will be displayed to the user |
| description | varchar(555) | True | | Description of the status |
| status | char(1) | False | | The status of this code itself. |

Constraints

| Name | Type | Explanation |
|--|-------------|--|
| transaction_status_type_display_value_unique | UNIQUE | Combination of (display_value) is unique |
| transaction_status_type_pkey | PRIMARY KEY | Combination of (code) is the primary key |

Relationships (to)

| Name | Information | Description |
|------------------------------|--|-------------|
| transaction_status_code_fk77 | From columns: status_code From Entity: transaction From cardinality: 0..* To Cardinality: 1 | |

Data

| Nr | code | display_value | description | status |
|----|-----------|---------------------------------|-------------|--------|
| 1 | approved | Approved::::Approvata | | c |
| 2 | cancelled | CancelledApproved::::Cancellata | | c |
| 3 | pending | Pending::::In Attesa | | c |
| 4 | completed | Completed::::ITALIANO | | c |

Table: transaction_source

Columns

| Name | Type | Optional | Default | Description |
|----------------|-------------|----------|---------|-------------|
| transaction_id | varchar(40) | False | | |
| source_id | varchar(40) | False | | |

Constraints

| Name | Type | Explanation |
|-------------------------|-------------|--|
| transaction_source_pkey | PRIMARY KEY | Combination of (transaction_id,source_id) is the primary key |

Relationships (from)

| Name | Information | Description |
|--|---|-------------|
| transaction_source_transaction_id_fk93 | From columns: transaction_id To Entity: transaction From cardinality: 0..* To Cardinality: 1 | |
| transaction_source_source_id_fk94 | From columns: source_id To Entity: source From cardinality: 0..* To Cardinality: 1 | |

public

Public functions

```
f_for_trg_track_changes()
f_for_trg_track_history()
fn_triggerall(doenable : bit)
clean_db(schema_name : varchar)
compare_strings(string1 : varchar, string2 : varchar)
snap_geometry_to_geometry(geom_to_snap : varbinary, target_geom : varbinary, snap_distance : float, change_target_if_needed : bit, snapped : bit, target_is_changed : bit)
get_geometry_with_srid(geom : varbinary)
get_translation(mixed_value : varchar, language_code : varchar)
```

Function: f_for_trg_track_changes

This function is called from triggers in every table that has the columns to track changes. It also checks if the record has been already updated from another client application by checking the rowversion.

Function: f_for_trg_track_history

This function is called after a change is happening in a table to push the former values to the historic keeping table.

Function: fn_triggerall

This function can be used to disable all triggers in the database. **How to use** to call to disable all triggers in all schemas in db select fn_triggerall(false); to call to enable all triggers in all schemas in db select fn_triggerall(true);

Parameters

| Name | Type | Direction | Description |
|----------|------|-----------|--|
| doenable | bool | | If true all triggers will be enabled.If false triggers will be disabled. |

Function: `clean_db`

This function will delete any table and function in a schema that does not belong to the standard postgis template.

Parameters

| Name | Type | Direction | Description |
|-------------|---------|-----------|--|
| schema_name | varchar | | The name of schema that will be cleaned. |

Function: `compare_strings`

Special string compare function.

Parameters

| Name | Type | Direction | Description |
|---------|---------|-----------|-------------|
| string1 | varchar | | |
| string2 | varchar | | |

Function: snap_geometry_to_geometry

Used to snap a geometry to another geometry. Usage sample: select geom_to_snap, target_geom, snapped, target_is_changed FROM snap_geometry_to_geometry(geomfromtext('POLYGON((0.1 0, 0.1 5.7, 4 3, 0.1 0))'), geomfromtext('POLYGON((0 0, 0 6, 6 6, 6 0, 0 0),(1 1, 3 5, 4 5, 1 1))'), 1, true)

Parameters

| Name | Type | Direction | Description |
|-------------------------|----------|-----------|---|
| geom_to_snap | geometry | inout | Geometry that has to be snapped. It can be point, linestring or polygon |
| target_geom | geometry | inout | Geometry that will be the target to used for snapping |
| snap_distance | float | | The snap distance in meters |
| change_target_if_needed | bool | | It gives if it is allowed to change target during snapping |
| snapped | bool | out | An output value showing if the geometry is snapped. If it is a linestring or polygon, even if one point of them is snapped it returns true. |
| target_is_changed | bool | out | It shows if the target changed during the snapping process |

Function: `get_geometry_with_srid`

This function assigns a srid found in the settings to the geometry passed as parameter.

Parameters

| Name | Type | Direction | Description |
|------|----------|-----------|-------------|
| geom | geometry | | |

Function: get_translation

This function is used to translate the values that are supposed to be multilingual like the reference data values (display_value)

Parameters

| Name | Type | Direction | Description |
|---------------|---------|-----------|-------------|
| mixed_value | varchar | | |
| language_code | varchar | | |