

Splay Tree | Set 3 (Delete)

Difficulty Level: Hard • Last Updated: 03 Dec, 2019

It is recommended to refer following post as prerequisite of this post.

Splay Tree | Set 1 (Search)


Following are the different cases to delete a key \mathbf{k} from splay tree.

- 1. If **Root is NULL:** We simply return the root.
- 2. Else <u>Splay</u> the given key k. If k is present, then it becomes the new root. If not present, then last accessed leaf node becomes the new root.
- 3. If new root's key is not same as \mathbf{k} , then return the root as \mathbf{k} is not present.
- 4. Else the key **k** is present.
 - Split the tree into two trees **Tree1** = root's left subtree and **Tree2** = root's right subtree and delete the root node.
 - Let the root's of Tree1 and Tree2 be Root1 and Root2 respectively.
 - If Root1 is NULL: Return Root2.
 - Else, Splay the maximum node (node having the maximum value) of **Tree1**.
 - After the Splay procedure, make Root2 as the right child of Root1 and return
 Root1.



Login

Register



```
// C implementation to delete a node from Splay Tree
#include<stdio.h>
#include<stdlib.h>
// An AVL tree node
struct node
{
   int key;
    struct node *left, *right;
};
/* Helper function that allocates a new node with the given key and
   NULL left and right pointers. */
struct node* newNode(int key)
{
    struct node* node = (struct node*)malloc(sizeof(struct node));
    node->key
               = key;
   node->left = node->right = NULL;
    return (node);
}
// A utility function to right rotate subtree rooted with y
// See the diagram given above.
struct node *rightRotate(struct node *x)
{
    struct node *y = x->left;
   x->left = y->right;
   y - right = x;
   return y;
}
 A utility function to left rotate subtree rooted with x
// See the diagram given above.
struct node *leftRotate(struct node
{
```

Login

Register

```
// This function brings the key at root if key is present in tree.
// If key is not present, then it brings the last accessed item at
// root. This function modifies the tree and returns the new root
struct node *splay(struct node *root, int key)
{
    // Base cases: root is NULL or key is present at root
    if (root == NULL || root->key == key)
        return root;
    // Key lies in left subtree
    if (root->key > key)
        // Key is not in tree, we are done
        if (root->left == NULL) return root;
        // Zig-Zig (Left Left)
        if (root->left->key > key)
            // First recursively bring the key as root of left-left
            root->left->left = splay(root->left->left, key);
            // Do first rotation for root, second rotation is
            // done after else
            root = rightRotate(root);
        else if (root->left->key < key) // Zig-Zag (Left Right)</pre>
            // First recursively bring the key as root of left-right
            root->left->right = splay(root->left->right, key);
            // Do first rotation for root->left
            if (root->left->right != NULL)
                root->left = leftRotate(root->left);
        }
        // Do second rotation for root
        return (root->left == NULL)? root: rightRotate(root);
    else // Key lies in right subtree
    {
        // Key is not in tree, we are done
        if (root->right == NULL) return root;
        // Zag-Zig (Right Left)
        if (root->right->key > key)
        {
            // Bring the key as root
```

Login

Register

```
else if (root->right->key < key)// Zag-Zag (Right Right)</pre>
        {
            // Bring the key as root of right-right and do
            // first rotation
            root->right->right = splay(root->right->right, key);
            root = leftRotate(root);
        }
        // Do second rotation for root
        return (root->right == NULL)? root: leftRotate(root);
    }
}
// The delete function for Splay tree. Note that this function
// returns the new root of Splay Tree after removing the key
struct node* delete_key(struct node *root, int key)
{
    struct node *temp;
    if (!root)
        return NULL;
    // Splay the given key
    root = splay(root, key);
    // If key is not present, then
    // return root
    if (key != root->key)
        return root;
    // If key is present
    // If left child of root does not exist
    // make root->right as root
    if (!root->left)
    {
        temp = root;
        root = root->right;
    }
```

_

96

Q



```
so after Splay(key, root->lchild),
the tree we get will have no might child tree
and maximum node in left subt
```

Login

Register

```
}
    // free the previous root node, that is,
    // the node containing the key
    free(temp);
    // return root of the new Splay Tree
    return root;
}
// A utility function to print preorder traversal of the tree.
// The function also prints height of every node
void preOrder(struct node *root)
{
    if (root != NULL)
    {
        printf("%d ", root->key);
        preOrder(root->left);
        preOrder(root->right);
    }
}
/* Driver program to test above function*/
int main()
{
    // Splay Tree Formation
    struct node *root = newNode(6);
    root->left = newNode(1);
    root->right = newNode(9);
    root->left->right = newNode(4);
    root->left->right->left = newNode(2);
    root->right->left = newNode(7);
     int key = 4;
    root = delete_key(root, key);
    printf("Preorder traversal of the modified Splay tree is \n");
    preOrder(root);
    return 0;
}
```

C Itput:

Login

Register

https://www.geeksforgeeks.org/splay-tree-set-1-insert/

http://courses.cs.washington.edu/courses/cse326/01au/lectures/SplayTrees.ppt

This article is contributed by **Ayush Jauhari**. If you like GeeksforGeeks and would like to contribute, you can also write an article using <u>contribute.geeksforgeeks.org</u> or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



Like

Previous Next >

RECOMMENDED ARTICLES

Write a program to Delete a Tree

Page: 1 2 3

Splay Tree | Set 2 (Insert)

16, Jan 14

27, Jun 09

Login

Register

an entire binary tree

Red-Black Tree | Set 3 (Delete)
01, Apr 14

07, May 16

Deleting a binary tree using the delete keyword

K Dimensional Tree | Set 3 (Delete)

06, Oct 15

26, Jul 18

Article Contributed By:



GeeksforGeeks

Vote for difficulty

Current difficulty: Hard

Easy

Normal

Medium

Hard

Expert

Improved By: nidhi_biet

Article Tags: Advanced Data Structure, Tree

Practice Tags: Tree

Improve Article

Report Issue

Login

Register



5th Floor, A-118,Sector-136, Noida, Uttar Pradesh - 201305



Company

About Us

Careers

In Media

Contact Us

Privacy Policy

Copyright Policy

Learn

Algorithms

Data Structures

SDE Cheat Sheet

Machine learning

CS Subjects

Video Tutorials

News

Top News

Technology

Work & Career

Business

Finance

Lifestyle

Languages

Python

Java

CPP

Golang

C#

SQL

Web Development

Web Tutorials

Django Tutorial

HTML

CSS

JavaScript

Contribute

Write an Article

Improve an Article

Pick Topics to Write

Write Interview Experience

Internships





Login

Register

