



Splay Tree | Set 2 (Insert)

Difficulty Level : Medium • Last Updated : 11 Aug, 2021

It is recommended to refer following post as prerequisite of this post.


[Splay Tree | Set 1 \(Search\)](#)

As discussed in the [previous post](#), Splay tree is a self-balancing data structure where the last accessed key is always at root. The insert operation is similar to Binary Search Tree insert with additional steps to make sure that the newly inserted key becomes the new root.

Following are different cases to insert a key k in splay tree.

- 1) Root is NULL: We simply allocate a new node and return it as root.
- 2) [Splay](#) the given key k . If k is already present, then it becomes the new root. If not present, then last accessed leaf node becomes the new root.
- 3) If new root's key is same as k , don't do anything as k is already present.
- 4) Else allocate memory for new node and compare root's key with k .
 -4.a) If k is smaller than root's key, make root as right child of new node, copy left child of root as left child of new node and make left child of root as NULL.
 -4.b) If k is greater than root's key, make root as left child of new node, copy right child of root as right child of new node and make right child of root as NULL.
- 5) Return new node as new root of tree.

Example:



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
#include <bits/stdc++.h>
using namespace std;

// An AVL tree node
class node
{
    public:
    int key;
    node *left, *right;
};

/* Helper function that allocates
a new node with the given key and
NULL left and right pointers. */
node* newNode(int key)
{
    node* Node = new node();
    Node->key = key;
    Node->left = Node->right = NULL;
    return (Node);
}

// A utility function to right
// rotate subtree rooted with y
// See the diagram given above.
node *rightRotate(node *x)
{
    node *y = x->left;
    x->left = y->right;
    y->right = x;
    return y;
}

// A utility function to left
// rotate subtree rooted with x
// See the diagram given above.
node *leftRotate(node *x)
{
    node *y = x->right;
    x->right = y->left;
```

Start Your Coding Journey Now!

[Login](#)
[Register](#)

```
// If key is not present, then it
// brings the last accessed item at
// root. This function modifies the
// tree and returns the new root
node *splay(node *root, int key)
{
    // Base cases: root is NULL or
    // key is present at root
    if (root == NULL || root->key == key)
        return root;

    // Key lies in left subtree
    if (root->key > key)
    {
        // Key is not in tree, we are done
        if (root->left == NULL) return root;

        // Zig-Zig (Left Left)
        if (root->left->key > key)
        {
            // First recursively bring the
            // key as root of left-left
            root->left->left = splay(root->left->left, key);

            // Do first rotation for root,
            // second rotation is done after else
            root = rightRotate(root);
        }
        else if (root->left->key < key) // Zig-Zag (Left Right)
        {
            // First recursively bring
            // the key as root of left-right
            root->left->right = splay(root->left->right, key);

            // Do first rotation for root->left
            if (root->left->right != NULL)
                root->left = leftRotate(root->left);
        }

        // Do second rotation for root
        return (root->left == NULL)? root: rightRotate(root);
    }
    else // Key lies in right subtree
    {
        // Key is not in tree, we are done
        if (root->right == NULL) return root;
```



Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

        // Do first rotation for root->right
        if (root->right->left != NULL)
            root->right = rightRotate(root->right);
    }
    else if (root->right->key < key) // Zag-Zag (Right Right)
    {
        // Bring the key as root of
        // right-right and do first rotation
        root->right->right = splay(root->right->right, key);
        root = leftRotate(root);
    }

    // Do second rotation for root
    return (root->right == NULL)? root: leftRotate(root);
}

// Function to insert a new key k
// in splay tree with given root
node *insert(node *root, int k)
{
    // Simple Case: If tree is empty
    if (root == NULL) return newNode(k);

    // Bring the closest leaf node to root
    root = splay(root, k);

    // If key is already present, then return
    if (root->key == k) return root;

    // Otherwise allocate memory for new node
    node *newnode = newNode(k);

    // If root's key is greater, make
    // root as right child of newnode
    // and copy the left child of root to newnode
    if (root->key > k)
    {
        newnode->right = root;
        newnode->left = root->left;
        root->left = NULL;
    }

    // If root's key is smaller, make
    // root as left child of newnode
    // and copy the right child of root to newnode
    else

```



Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

    return newnode; // newnode becomes new root
}

// A utility function to print
// preorder traversal of the tree.
// The function also prints height of every node
void preOrder(node *root)
{
    if (root != NULL)
    {

```



[← Array](#)
[Matrix](#)
[Strings](#)
[Hashing](#)
[Linked List](#)
[Stack](#)
[Queue](#)
[Binary Tree](#)
[Binary Search ▶](#)

```

/* Driver code*/
int main()
{
    node *root = newNode(100);
    root->left = newNode(50);
    root->right = newNode(200);
    root->left->left = newNode(40);
    root->left->left->left = newNode(30);
    root->left->left->left->left = newNode(20);
    root = insert(root, 25);
    cout<<"Preorder traversal of the modified Splay tree is \n";
    preOrder(root);
    return 0;
}

// This code is contributed by rathbhupendra

```

C




```

// This code is adopted from http://algs4.cs.princeton.edu/33balanced/SplayBST.j;
#include<stdio.h>
#include<stdlib.h>

// An AVL tree node
struct node
{
    int key;
    struct node *left, *right;
};

```



Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

    node->key    = key;
    node->left   = node->right = NULL;
    return (node);
}

// A utility function to right rotate subtree rooted with y
// See the diagram given above.
struct node *rightRotate(struct node *x)
{
    struct node *y = x->left;
    x->left = y->right;
    y->right = x;
    return y;
}

// A utility function to left rotate subtree rooted with x
// See the diagram given above.
struct node *leftRotate(struct node *x)
{
    struct node *y = x->right;
    x->right = y->left;
    y->left = x;
    return y;
}

// This function brings the key at root if key is present in tree.
// If key is not present, then it brings the last accessed item at
// root. This function modifies the tree and returns the new root
struct node *splay(struct node *root, int key)
{
    // Base cases: root is NULL or key is present at root
    if (root == NULL || root->key == key)
        return root;

    // Key lies in left subtree
    if (root->key > key)
    {
        // Key is not in tree, we are done
        if (root->left == NULL) return root;

        // Zig-Zig (Left Left)
        if (root->left->key > key)
        {
            // First recursively bring the key as root of left-left
            root->left->left = splay(root->left->left, key);

            // Do first rotation for root, second rotation is done after else

```



Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

        // Do first rotation for root->left
        if (root->left->right != NULL)
            root->left = leftRotate(root->left);
    }

    // Do second rotation for root
    return (root->left == NULL)? root: rightRotate(root);
}
else // Key lies in right subtree
{
    // Key is not in tree, we are done
    if (root->right == NULL) return root;

    // Zig-Zag (Right Left)
    if (root->right->key > key)
    {
        // Bring the key as root of right-left
        root->right->left = splay(root->right->left, key);

        // Do first rotation for root->right
        if (root->right->left != NULL)
            root->right = rightRotate(root->right);
    }
    else if (root->right->key < key) // Zag-Zag (Right Right)
    {
        // Bring the key as root of right-right and do first rotation
        root->right->right = splay(root->right->right, key);
        root = leftRotate(root);
    }

    // Do second rotation for root
    return (root->right == NULL)? root: leftRotate(root);
}
}

// Function to insert a new key k in splay tree with given root
struct node *insert(struct node *root, int k)
{
    // Simple Case: If tree is empty
    if (root == NULL) return newNode(k);

    // Bring the closest leaf node to root
    root = splay(root, k);

    // If key is already present, then return
    if (root->key == k) return root;
}

```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
if (root->key > k)
{
    newnode->right = root;
    newnode->left = root->left;
    root->left = NULL;
}

// If root's key is smaller, make root as left child
// of newnode and copy the right child of root to newnode
else
{
    newnode->left = root;
    newnode->right = root->right;
    root->right = NULL;
}

return newnode; // newnode becomes new root
}

// A utility function to print preorder traversal of the tree.
// The function also prints height of every node
void preOrder(struct node *root)
{
    if (root != NULL)
    {
        printf("%d ", root->key);
        preOrder(root->left);
        preOrder(root->right);
    }
}

/* Driver program to test above function*/
int main()
{
    struct node *root = newNode(100);
    root->left = newNode(50);
    root->right = newNode(200);
    root->left->left = newNode(40);
    root->left->left->left = newNode(30);
    root->left->left->left->left = newNode(20);
    root = insert(root, 25);
    printf("Preorder traversal of the modified Splay tree is \n");
    preOrder(root);
    return 0;
}
```



Start Your Coding Journey Now!

[Login](#)
[Register](#)

```
class Node {
```

```
// An AVL tree node
static class node
{
    int key;
    node left, right;
};

/* Helper function that allocates
a new node with the given key and
null left and right pointers. */
static node newNode(int key)
{
    node Node = new node();
    Node.key = key;
    Node.left = Node.right = null;
    return (Node);
}

// A utility function to right
// rotate subtree rooted with y
// See the diagram given above.
static node rightRotate(node x)
{
    node y = x.left;
    x.left = y.right;
    y.right = x;
    return y;
}

// A utility function to left
// rotate subtree rooted with x
// See the diagram given above.
static node leftRotate(node x)
{
    node y = x.right;
    x.right = y.left;
    y.left = x;
    return y;
}
```



```
// This function brings the key at
// root if key is present in tree.
// If key is not present, then it
// brings the last accessed item at
```



Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

if (root == null || root.key == key)
    return root;

// Key lies in left subtree
if (root.key > key)
{
    // Key is not in tree, we are done
    if (root.left == null) return root;

    // Zig-Zig (Left Left)
    if (root.left.key > key)
    {
        // First recursively bring the
        // key as root of left-left
        root.left.left = splay(root.left.left, key);

        // Do first rotation for root,
        // second rotation is done after else
        root = rightRotate(root);
    }
    else if (root.left.key < key) // Zig-Zag (Left Right)
    {
        // First recursively bring
        // the key as root of left-right
        root.left.right = splay(root.left.right, key);

        // Do first rotation for root.left
        if (root.left.right != null)
            root.left = leftRotate(root.left);
    }

    // Do second rotation for root
    return (root.left == null)? root: rightRotate(root);
}
else // Key lies in right subtree
{
    // Key is not in tree, we are done
    if (root.right == null) return root;

    // Zig-Zag (Right Left)
    if (root.right.key > key)
    {
        // Bring the key as root of right-left
        root.right.left = splay(root.right.left, key);

        // Do first rotation for root.right
        if (root.right.left != null)

```



Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

        root.right.right = splay(root.right.right, key);
        root = leftRotate(root);
    }

    // Do second rotation for root
    return (root.right == null)? root: leftRotate(root);
}

// Function to insert a new key k
// in splay tree with given root
static node insert(node root, int k)
{
    // Simple Case: If tree is empty
    if (root == null) return newNode(k);

    // Bring the closest leaf node to root
    root = splay(root, k);

    // If key is already present, then return
    if (root.key == k) return root;

    // Otherwise allocate memory for new node
    node newnode = newNode(k);

    // If root's key is greater, make
    // root as right child of newnode
    // and copy the left child of root to newnode
    if (root.key > k)
    {
        newnode.right = root;
        newnode.left = root.left;
        root.left = null;
    }

    // If root's key is smaller, make
    // root as left child of newnode
    // and copy the right child of root to newnode
    else
    {
        newnode.left = root;
        newnode.right = root.right;
        root.right = null;
    }

    return newnode; // newnode becomes new root
}

```



Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

    if (root != null)
    {
        System.out.print(root.key+" ");
        preOrder(root.left);
        preOrder(root.right);
    }
}

/* Driver code*/
public static void main(String[] args)
{
    node root = newNode(100);
    root.left = newNode(50);
    root.right = newNode(200);
    root.left.left = newNode(40);
    root.left.left.left = newNode(30);
    root.left.left.left.left = newNode(20);
    root = insert(root, 25);
    System.out.print("Preorder traversal of the modified Splay tree is \n");
    preOrder(root);
}
}

// This code is contributed by Rajput-Ji

```

C#

```

using System;

public class node
{
    public int key;
    public node left, right;
}

public class GFG{

    /* Helper function that allocates
    a new node with the given key and
    null left and right pointers. */
    static node newNode(int key)
    {
        node Node = new node();
        Node.key = key;
    }
}

```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// See the diagram given above.
static node rightRotate(node x)
{
    node y = x.left;
    x.left = y.right;
    y.right = x;
    return y;
}

// A utility function to left
// rotate subtree rooted with x
// See the diagram given above.
static node leftRotate(node x)
{
    node y = x.right;
    x.right = y.left;
    y.left = x;
    return y;
}

// This function brings the key at
// root if key is present in tree.
// If key is not present, then it
// brings the last accessed item at
// root. This function modifies the
// tree and returns the new root
static node splay(node root, int key)
{
    // Base cases: root is null or
    // key is present at root
    if (root == null || root.key == key)
        return root;

    // Key lies in left subtree
    if (root.key > key)
    {
        // Key is not in tree, we are done
        if (root.left == null) return root;

        // Zig-Zig (Left Left)
        if (root.left.key > key)
        {
            // First recursively bring the
            // key as root of left-left
            root.left.left = splay(root.left.left, key);

            // Do first rotation for root
```



Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

    // the key as root of left-right
    root.left.right = splay(root.left.right, key);

    // Do first rotation for root.left
    if (root.left.right != null)
        root.left = leftRotate(root.left);
}

// Do second rotation for root
return (root.left == null)? root: rightRotate(root);
}
else // Key lies in right subtree
{
    // Key is not in tree, we are done
    if (root.right == null) return root;

    // Zig-Zag (Right Left)
    if (root.right.key > key)
    {
        // Bring the key as root of right-left
        root.right.left = splay(root.right.left, key);

        // Do first rotation for root.right
        if (root.right.left != null)
            root.right = rightRotate(root.right);
    }
    else if (root.right.key < key) // Zag-Zag (Right Right)
    {
        // Bring the key as root of
        // right-right and do first rotation
        root.right.right = splay(root.right.right, key);
        root = leftRotate(root);
    }

    // Do second rotation for root
    return (root.right == null)? root: leftRotate(root);
}
}

// Function to insert a new key k
// in splay tree with given root
static node insert(node root, int k)
{
    // Simple Case: If tree is empty
    if (root == null) return newNode(k);

    // Bring the closest leaf node to root

```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
node newnode = newNode(k);

// If root's key is greater, make
// root as right child of newnode
// and copy the left child of root to newnode
if (root.key > k)
{
    newnode.right = root;
    newnode.left = root.left;
    root.left = null;
}

// If root's key is smaller, make
// root as left child of newnode
// and copy the right child of root to newnode
else
{
    newnode.left = root;
    newnode.right = root.right;
    root.right = null;
}

return newnode; // newnode becomes new root
}

// A utility function to print
// preorder traversal of the tree.
// The function also prints height of every node
static void preOrder(node root)
{
    if (root != null)
    {
        Console.Write(root.key+" ");
        preOrder(root.left);
        preOrder(root.right);
    }
}

/* Driver code*/
static public void Main ()
{
    node root = newNode(100);
    root.left = newNode(50);
    root.right = newNode(200);
    root.left.left = newNode(40);
    root.left.left.left = newNode(30);
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

// This code is contributed by patel2127.

Javascript

<script>

```
// An AVL tree node
class Node {
  constructor(val) {
    this.key = val;
    this.left = null;
    this.right = null;
  }
}

/*
Helper function that allocates a new
node with the given key and null left
and right pointers.
*/
function newNode(key) {
  var node = new Node();
  node.key = key;
  node.left = node.right = null;
  return (node);
}

// A utility function to right
// rotate subtree rooted with y
// See the diagram given above.
function rightRotate( x ) {
  var y = x.left;
  x.left = y.right;
  y.right = x;
  return y;
}

// A utility function to left
// rotate subtree rooted with x
// See the diagram given above.
function leftRotate( x ) {
  var y = x.right;
  x.right = y.left;
  y.left = x;
```



Start Your Coding Journey Now!

[Login](#)
[Register](#)

```
// brings the last accessed item at
// root. This function modifies the
// tree and returns the new root
function splay( root , key) {
    // Base cases: root is null or
    // key is present at root
    if (root == null || root.key == key)
        return root;

    // Key lies in left subtree
    if (root.key > key) {
        // Key is not in tree, we are done
        if (root.left == null)
            return root;

        // Zig-Zig (Left Left)
        if (root.left.key > key) {
            // First recursively bring the
            // key as root of left-left
            root.left.left = splay(root.left.left, key);

            // Do first rotation for root,
            // second rotation is done after else
            root = rightRotate(root);
        } else if (root.left.key < key) // Zig-Zag (Left Right)
        {
            // First recursively bring
            // the key as root of left-right
            root.left.right = splay(root.left.right, key);

            // Do first rotation for root.left
            if (root.left.right != null)
                root.left = leftRotate(root.left);
        }

        // Do second rotation for root
        return (root.left == null) ? root : rightRotate(root);
    } else // Key lies in right subtree
    {
        // Key is not in tree, we are done
        if (root.right == null)
            return root;

        // Zig-Zag (Right Left)
        if (root.right.key > key) {
            // Bring the key as root of right-left
            root.right.left = splay(root.right.left, key);
```



Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

        // Bring the key as root of
        // right-right and do first rotation
        root.right.right = splay(root.right.right, key);
        root = leftRotate(root);
    }

    // Do second rotation for root
    return (root.right == null) ? root : leftRotate(root);
}

// Function to insert a new key k
// in splay tree with given root
function insert( root , k) {
    // Simple Case: If tree is empty
    if (root == null)
        return newNode(k);

    // Bring the closest leaf node to root
    root = splay(root, k);

    // If key is already present, then return
    if (root.key == k)
        return root;

    // Otherwise allocate memory for new node
    var newnode = newNode(k);

    // If root's key is greater, make
    // root as right child of newnode
    // and copy the left child of root to newnode
    if (root.key > k) {
        newnode.right = root;
        newnode.left = root.left;
        root.left = null;
    }

    // If root's key is smaller, make
    // root as left child of newnode
    // and copy the right child of root to newnode
    else {
        newnode.left = root;
        newnode.right = root.right;
        root.right = null;
    }

    return newnode; // newnode becomes new root
}

```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
if (root != null) {
    document.write(root.key + " ");
    preOrder(root.left);
    preOrder(root.right);
}
}

/* Driver code */

var root = newNode(100);
root.left = newNode(50);
root.right = newNode(200);
root.left.left = newNode(40);
root.left.left.left = newNode(30);
root.left.left.left.left = newNode(20);
root = insert(root, 25);

document.write(
    "Preorder traversal of the modified Splay tree is <br/>"
);
preOrder(root);

// This code contributed by umadevi9616

</script>
```

Output:

```
Preorder traversal of the modified Splay tree is
25 20 50 30 40 100 200
```

This article is compiled by **Abhay Rathi**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



Start Your Coding Journey Now!

Login

Register

 Like

Next >

Splay Tree | Set 1 (Search)

RECOMMENDED ARTICLES

Page : 1 2 3

- 01

Splay Tree | Set 3 (Delete)

13, Jun 17
- 02

Splay Tree | Set 1 (Search)

14, Jan 14
- 03

Red-Black Tree | Set 2 (Insert)

16, Feb 14
- 04

K Dimensional Tree | Set 1 (Search and Insert)

31, Oct 14

- 05

Insert Operation in B-Tree

23, Apr 13
- 06

B-Tree Insert without aggressive splitting

03, May 19
- 07

How to insert Strings into an AVL Tree

11, Oct 21
- 08

Convert a Generic Tree(N-array Tree) to Binary Tree

29, Oct 20



Article Contributed By :



Start Your Coding Journey Now!

[Login](#)[Register](#)

Improved By : [rathbhupendra](#), [Akanksha_Rai](#), [Rajput-Ji](#), [umadevi9616](#), [patel2127](#)

Article Tags : [Self-Balancing-BST](#), [splay-tree](#), [Advanced Data Structure](#)

[Report Issue](#)

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

[Load Comments](#)

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org



Company

[About Us](#)[Careers](#)[In Media](#)[Contact Us](#)[Privacy Policy](#)[Copyright Policy](#)

Learn

[Algorithms](#)[Data Structures](#)[SDE Cheat Sheet](#)[Machine learning](#)[CS Subjects](#)[Video Tutorials](#)[News](#)[Languages](#)

Start Your Coding Journey Now!

Login

Register

Business

Finance

Lifestyle

C#

SQL

Web Development

Web Tutorials

Django Tutorial

HTML

CSS

JavaScript

Bootstrap

Contribute

Write an Article

Improve an Article

Pick Topics to Write

Write Interview Experience

Internships

Video Internship

@geeksforgeeks , Some rights reserved

