


Knome Platform: 6-Tier Architecture Specification Document

Executive Summary

This document provides the complete technical specification for the **6-Tier Architecture** of the **Knome Enterprise Knowledge Management Platform** developed for **MPOnline Limited**.

The platform decouples client presentation, backend-for-frontend orchestration, enterprise gateway security, reverse proxy routing, core business logic/repositories, and relational data persistence into 6 distinct, loosely coupled layers.

High-Level System Architecture Diagram



Detailed Layer Specifications

Layer 1: React UI Presentation Layer

- **Location:** knomeUI/frontend

- **Technologies:** React 18, Vite, Tailwind CSS, JavaScript (ES6+)
- **Port:** `http://localhost:5173` (Vite Dev) / `http://localhost:3001`
- **Primary Responsibilities:**
 1. Render client UI components, interactive navigation, media player feeds, post creation modal dialogs, and community management interfaces.
 2. Maintain local component UI state, form input validations, and client side routing.
 3. Never store raw JWT access tokens in vulnerable `localStorage` or `sessionStorage`.
 4. Communicate exclusively with Layer 2 (Next.js BFF) via `/api/proxy/*` endpoints.

Key Configuration File: ``src/utils/apiClient.js``

```
// Layer 1 (React UI) -> Layer 2 (Next.js BFF)
const BASE_URL = window.ENV_BFF_URL || 'http://localhost:3000/api/proxy';

export const apiClient = {
  async request(endpoint, options = {}) {
    const url = `${BASE_URL}${endpoint}`;
    const config = { ...options, headers: { 'Content-Type': 'application/json', ...options.headers } };
    const response = await fetch(url, config);
    // ... response handling
  }
};
```

Layer 2: Next.js Backend-For-Frontend (BFF) Layer

- **Location:** `Bff/knome-bff`
- **Technologies:** Next.js 14+ (App Router), TypeScript, Node.js runtime
- **Port:** `http://localhost:3000`
- **Primary Responsibilities:**
 1. Receive login credentials from Layer 1 and forward them to Layer 3 Gateway.
 2. Extract returned JWT tokens and store them safely inside **HTTP-Only, Secure, SameSite=Lax** cookies (`knome_token`).
 3. Intercept outgoing requests from Layer 1, read the secure `knome_token` cookie, attach the `Authorization: Bearer` header, and forward the request to Layer 3 (API Gateway).
 4. Provide Server-Side Rendering (SSR) and data aggregation for complex views (e.g. combining Dashboard Feed + Karma summary in a single call).

Key Code Snippets

1. Secure Login Route Handler (`src/app/api/auth/login/route.ts`)

```

import { NextRequest, NextResponse } from "next/server";

const GATEWAY_URL = process.env.GATEWAY_URL || "http://localhost:5000";

export async function POST(req: NextRequest) {
  const body = await req.json();
  const response = await fetch(`${GATEWAY_URL}/api/v1/auth/login`, {
    method: "POST",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify(body),
  });

  const data = await response.json();
  if (!response.ok) return NextResponse.json(data, { status: response.status });

  const res = NextResponse.json({ success: true, data: data.data || data });
  const token = data.data?.token || data.token;

  if (token) {
    res.cookies.set({
      name: "knome_token",
      value: token,
      httpOnly: true,
      secure: process.env.NODE_ENV === "production",
      sameSite: "lax",
      path: "/",
      maxAge: 60 * 60 * 24 * 7, // 7 days
    });
  }
  return res;
}

```

2. Dynamic Catch-All Proxy Route Handler (src/app/api/proxy/[...path]/route.ts)

```

import { NextRequest, NextResponse } from "next/server";

const GATEWAY_URL = process.env.GATEWAY_URL || "http://localhost:5000";

async function proxyRequest(req: NextRequest, params: { path: string[] }) {
  const pathStr = params.path ? params.path.join("/") : "";
  const targetUrl = `${GATEWAY_URL}/api/${pathStr}${req.nextUrl.search}`;
  const token = req.cookies.get("knome_token")?.value;

  const headers = new Headers();
  req.headers.forEach((val, key) => {
    if (key.toLowerCase() !== "host" && key.toLowerCase() !== "cookie") {
      headers.set(key, val);
    }
  });

  if (token) {
    headers.set("Authorization", `Bearer ${token}`);
  }

  let body: any = null;
  if (req.method !== "GET" && req.method !== "HEAD") {
    body = await req.arrayBuffer();
  }

  const gatewayRes = await fetch(targetUrl, {
    method: req.method,
    headers: headers,
    body: body,
    // @ts-ignore
    duplex: "half",
  });

  const resData = await gatewayRes.arrayBuffer();
  return new NextResponse(resData, {
    status: gatewayRes.status,
    headers: gatewayRes.headers,
  });
}

export async function GET(req: NextRequest, { params }: { params: { path: string[] } }) { return proxyRequest(req, params); }
export async function POST(req: NextRequest, { params }: { params: { path: string[] } }) { return proxyRequest(req, params); }
export async function PUT(req: NextRequest, { params }: { params: { path: string[] } }) { return proxyRequest(req, params); }
export async function PATCH(req: NextRequest, { params }: { params: { path: string[] } }) { return proxyRequest(req, params); }
export async function DELETE(req: NextRequest, { params }: { params: { path: string[] } }) { return proxyRequest(req, params); }

```

Layer 3: API Gateway (.NET Core 9)

- **Location:** Gateway/Knome.Gateway
- **Technologies:** ASP.NET Core 9 Web API, Microsoft Rate Limiting, OpenAPI / Swashbuckle
- **Port:** http://localhost:5000 / http://localhost:5001
- **Primary Responsibilities:**
 1. Entry gateway for all external microservices and BFF calls.
 2. Enforce global Gateway Rate Limiting (Fixed Window policy: 100 requests / minute per client).
 3. Enforce Strict CORS rules for allowed frontend and BFF origin servers (http://localhost:3000, http://localhost:5173).
 4. Serve Swagger UI diagnostics for proxy infrastructure monitoring at http://localhost:5000/swagger.

Key Code Snippet: `Program.cs`

```
using Microsoft.AspNetCore.RateLimiting;
using System.Threading.RateLimiting;

var builder = WebApplication.CreateBuilder(args);

// Add YARP Reverse Proxy services
builder.Services.AddReverseProxy()
    .LoadFromConfig(builder.Configuration.GetSection("ReverseProxy"));

builder.Services.AddEndpointsApiExplorer();
builder.Services.AddSwaggerGen(c =>
{
    c.SwaggerDoc("v1", new Microsoft.OpenApi.Models.OpenApiInfo
    {
        Title = "Knome API Gateway (YARP)",
        Version = "v1",
        Description = "Layer 3 API Gateway & Layer 4 YARP Reverse Proxy for Knome Platform"
    });
});

// Configure CORS for Next.js BFF & React UI
builder.Services.AddCors(options =>
{
    options.AddPolicy("AllowFrontendAndBff", policy =>
    {
        policy.WithOrigins("http://localhost:3000", "http://localhost:5173", "http://localhost:3001")
            .AllowAnyHeader()
            .AllowAnyMethod()
            .AllowCredentials();
    });
});

// Gateway Rate Limiter Policy
builder.Services.AddRateLimiter(options =>
{
    options.AddFixedWindowLimiter("GatewayRatePolicy", opt =>
    {
        opt.PermitLimit = 100;
        opt.Window = TimeSpan.FromMinutes(1);
        opt.QueueProcessingOrder = QueueProcessingOrder.OldestFirst;
        opt.QueueLimit = 10;
    });
});

var app = builder.Build();

if (app.Environment.IsDevelopment())
{
    app.UseSwagger();
    app.UseSwaggerUI(c => c.SwaggerEndpoint("/swagger/v1/swagger.json", "Knome API Gateway v1"));
}

app.UseCors("AllowFrontendAndBff");
app.UseRateLimiter();

app.MapGet("/health", () => Results.Ok(new { Status = "Healthy", Layer = "Layer 3 API Gateway & Layer 4 YARP"
}));
app.MapReverseProxy();

app.Run();
```

Layer 4: YARP Reverse Proxy Engine

- **Location:** Integrated into Gateway/Knome.Gateway
- **Technologies:** Yarp.ReverseProxy (v2.2.0)
- **Primary Responsibilities:**
 1. Inspect incoming URL path patterns (/api/v1/auth/*, /api/v1/users/*, /api/v1/posts/*, /api/v1/communities/*, /api/v1/jobs/*, /api/v1/notifications/*, /api/v1/search/*, /api/v1/karma/*).
 2. Dynamically route matched requests to downstream backend clusters (knome-backend-cluster at http://localhost:5095/).
 3. Maintain path parameters, headers, and request body payload streaming without alteration.

Key Configuration: `appsettings.json`

```
{
  "Logging": {
    "LogLevel": {
      "Default": "Information",
      "Microsoft.AspNetCore": "Warning",
      "Yarp": "Information"
    }
  },
  "AllowedHosts": "*",
  "ReverseProxy": {
    "Routes": {
      "auth-route": {
        "ClusterId": "knome-backend-cluster",
        "Match": { "Path": "/api/v1/auth/{**catch-all}" }
      },
      "users-route": {
        "ClusterId": "knome-backend-cluster",
        "Match": { "Path": "/api/v1/users/{**catch-all}" }
      },
      "posts-route": {
        "ClusterId": "knome-backend-cluster",
        "Match": { "Path": "/api/v1/posts/{**catch-all}" }
      },
      "communities-route": {
        "ClusterId": "knome-backend-cluster",
        "Match": { "Path": "/api/v1/communities/{**catch-all}" }
      },
      "jobs-route": {
        "ClusterId": "knome-backend-cluster",
        "Match": { "Path": "/api/v1/jobs/{**catch-all}" }
      },
      "notifications-route": {
        "ClusterId": "knome-backend-cluster",
        "Match": { "Path": "/api/v1/notifications/{**catch-all}" }
      },
      "search-route": {
        "ClusterId": "knome-backend-cluster",
        "Match": { "Path": "/api/v1/search/{**catch-all}" }
      },
      "karma-route": {
        "ClusterId": "knome-backend-cluster",
        "Match": { "Path": "/api/v1/karma/{**catch-all}" }
      },
      "catch-all-route": {
        "ClusterId": "knome-backend-cluster",
        "Match": { "Path": "/api/{**catch-all}" }
      }
    },
    "Clusters": {
      "knome-backend-cluster": {
        "Destinations": {
          "backend-destination": {
            "Address": "http://localhost:5095/"
          }
        }
      }
    }
  }
}
```

Layer 5: Backend API & Repository Layer

- **Location:** Backend/Knome.API

- **Technologies:** ASP.NET Core 9 Web API, Entity Framework Core 9, AutoMapper, FluentValidation, Serilog, BCrypt, JWT Authentication
 - **Port:** http://localhost:5095
 - **Primary Responsibilities:**
 1. Contain all business application logic inside dedicated Services/ (e.g. AuthService, UserService, PostService, NotificationService, KarmaService).
 2. Implement Repository Pattern via Repositories/ (e.g. UserRepository, PostRepository, AuditLogRepository) to abstract Entity Framework Core queries.
 3. Keep controllers thin, using standardized KnomeControllerBase and ApiResponse wrappers.
 4. Perform JWT validation, claims extraction, role-based authorization guards, and FluentValidation intercepting.
-

Layer 6: Relational Database Layer

- **Location:** MS SQL Server (localhost, Database: Knome)
 - **Technologies:** MS SQL Server, Entity Framework Core Database-First Scaffolding
 - **Primary Responsibilities:**
 1. Relational schema storage, indexes, primary/foreign key constraints, and seed data.
 2. **Database-First Principle:** Database schema changes originate exclusively from SQL Server.
 3. Re-scaffold EF Core KnomeDbContext and models (Models/) whenever SQL Server schema changes using `dotnet ef dbcontext scaffold`. Never manually edit scaffolded models or DbContext.
-

Authentication & Proxy Sequence Flow

```
sequenceDiagram
    autonumber
    actor User as User (Browser)
    participant L1 as Layer 1: React UI
    participant L2 as Layer 2: Next.js BFF
    participant L3_4 as Layers 3 & 4: Gateway + YARP
    participant L5 as Layer 5: Backend API
    participant L6 as Layer 6: SQL Database

    %% Login Flow
    User->>L1: Enter Credentials (EMP001 / Password@123)
    L1->>L2: POST /api/auth/login
    L2->>L3_4: POST /api/v1/auth/login
    L3_4->>L5: YARP Proxy to http://localhost:5095/api/v1/auth/login
    L5->>L6: Query User & Verify BCrypt Password
    L6-->>L5: User Profile & Claims
    L5-->>L3_4: Return 200 OK + JWT Token
    L3_4-->>L2: Return 200 OK + JWT Token
    L2-->>L1: Return 200 OK (Set HTTP-Only Cookie knome_token)

    %% Authenticated Request Flow
    User->>L1: Click "View Feed"
    L1->>L2: GET /api/proxy/v1/posts
    Note over L2: Extract knome_token cookie & Attach Bearer Token Header
    L2->>L3_4: GET /api/v1/posts (Header: Authorization: Bearer <JWT>)
    Note over L3_4: Apply Rate Limiting Policy
    L3_4->>L5: YARP Proxy to http://localhost:5095/api/v1/posts
    L5->>L6: Fetch Posts via PostRepository & EF Core
    L6-->>L5: Post Entities
    L5-->>L3_4: Return ApiResponse<List<PostDto>>
    L3_4-->>L2: Forward Response
    L2-->>L1: Return Data to React UI
```


Verification & Execution Commands

1. Build Verification (.NET Core Solutions)

```
# Build API Gateway (Layers 3 & 4)
cd Gateway/Knome.Gateway
dotnet build -nologo

# Build Backend API & Repositories (Layers 5 & 6)
cd Backend/Knome.API
dotnet build -nologo
```

2. Service Launch Strategy

```
# Terminal 1: Run Backend API & Database Service (Layer 5 & 6)
cd Backend/Knome.API
dotnet run    # Target: http://localhost:5095

# Terminal 2: Run Gateway & YARP Engine (Layer 3 & 4)
cd Gateway/Knome.Gateway
dotnet run    # Target: http://localhost:5000

# Terminal 3: Run Next.js BFF (Layer 2)
cd Bff/knome-bff
npm run dev   # Target: http://localhost:3000

# Terminal 4: Run React UI (Layer 1)
cd knomeUI/frontend
npm run dev   # Target: http://localhost:5173
```

Summary Matrix

Layer	Component Name	Technology	Port	Access Boundary
Layer 1	React UI	React 18 / Vite	5173	Public Client Presentation
Layer 2	Next.js BFF	Next.js App Router	3000	Client-Facing BFF Proxy
Layer 3	API Gateway	ASP.NET Core 9	5000	Gateway Middleware & Security
Layer 4	YARP Reverse Proxy	Yarp.ReverseProxy	5000	Internal Cluster Proxy Engine
Layer 5	Backend API / Repo	ASP.NET Core 9	5095	Internal Business & Data Services
Layer 6	Database Layer	MS SQL Server	1433	Internal Database Source-of-Truth