

3RW4027 2B004

UL: 20V
IEC 60947-4-1 CLASS 10
32.2 A AC 534-4 30-75
UL: 20-480V 50/60Hz
Ue [V] 230 400
P AC-3(KV) 7.5 15
Ie 32.2 A <= 40°C
UL 480V: Uimp 8kV
BVB 10 II (2) G
ATEX F80 II (2) D
KCC-REM
S43-3RW
01.5A

AC Semiconductor Motor Starter *E07* LQ/210810

IEC 60347-5-1
(S) 714048 6.50Hz
AUX CONT. SHORT CIRCUIT 1A.
230V Max Fuse 6A UL3300V
AC 15.3A 0.24V-DC 13 1A/24V
Uimp 4kV

UL IND CONT 15
LITTE 195G

1P3RW4027-2B004-SLQ/210810

V AC	200	230	460
3PH (HP)	7.5	7.5	20
FLA 20	<= 50°C		
Surrounding air temp 50°C			

SHORT CIRCUIT 0 kA, 500V
MAX FUSE 125 A CLASS RG
75°C CU WIRE ONLY
AUX CONT: 3200, P2000
With Auto Reset and 2 Wire
Control Motor may restart
automatically

10 - 2x 1.5mm²
2x AWG 16 to 10

10 - 2x 1.5mm²
2x AWG 16 to 10

10 - 2x 1.5mm²
2x AWG 16 to 10

WARRANTY IF SEAL BROKEN!

0 112 030 004 900 0 G

Siemens AG, DE 92228 Amberg

http://support.industry.siemens.com

Made in Czech Republic

SCAN

SCAN HISTORY QUEUE CONFIG

HISTORY_LOG

STATUS: MONITORING ENCRYPTED STREAM

FILTER BY STRING...

OCT_24_2023

2023.10.27_14:20:01

SUCCESS

NODE_ID: ALPHA-09 // HASH: 0X82...F2

2023.10.27_13:45:12

FAILED

ERR_TIMEOUT: PACKET_LOSS_DETECTION

RESEND_ATTEMPT

2023.10.27_12:10:59

PENDING

VERIFYING_SIGNATURE... [88%]

2023.10.27_10:04:22

SUCCESS

NODE_ID: DELTA-01 // HASH: 0X4A...A1

2023.10.26_23:15:00

FAILED

ERR_AUTH: INVALID_TOKEN_ID

RESEND_ATTEMPT

2023.10.26_21:44:18

SUCCESS

NODE_ID: GAMMA-14 // HASH: 0XBB...00

SCAN

HISTORY

QUEUE

CONFIG