```cpp
/*********************************************************************
*
* Software License Agreement (BSD License)
*
*  Copyright (c) 2009, Willow Garage, Inc.
*  All rights reserved.
*
*  Redistribution and use in source and binary forms, with or without
*  modification, are permitted provided that the following conditions
*  are met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*   * Redistributions in binary form must reproduce the above
*     copyright notice, this list of conditions and the following
*     disclaimer in the documentation and/or other materials provided
*     with the distribution.
*   * Neither the name of Willow Garage, Inc. nor the names of its
*     contributors may be used to endorse or promote products derived
*     from this software without specific prior written permission.
*
*  THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
*  "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
*  LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
*  FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
*  COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
*  INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
*  BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
*  LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
*  CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
*  LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN
*  ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
*  POSSIBILITY OF SUCH DAMAGE.
*
* Author: Eitan Marder-Eppstein
*********************************************************************/
#include <ros/ros.h>
#include <tf/transform_broadcaster.h>
#include <nav_msgs/Odometry.h>
#include "std_msgs/Int32.h"
#include "deadreckon.h"
#define ticksPerRev 210.461538 //ticks per rev is a double to the possibility of non whole number gear ratios due to how the encdoers are coupled
#define pi 3.141592
#define tau 2*pi
#define bad -2147483648
double baseWidth;
double wheelRadius;
int rightCount=bad,leftCount=bad;
void rin(const std_msgs::Int32ConstPtr &msg){
        rightCount = msg->data;
}

void lin(const std_msgs::Int32ConstPtr &msg){
        leftCount = msg->data;
}

int main(int argc, char** argv){
  ros::init(argc, argv, "odometry_publisher");
  ros::NodeHandle n;
```

```
60   n.getParam("baseWidth", baseWidth);
61   n.getParam("wheelRadius", wheelRadius);
62   ros::Publisher odom_pub = n.advertise<nav_msgs::Odometry>("fuck/odom", 1);
63   ros::Subscriber lsub = n.subscribe<std_msgs::Int32>("lwheel",1,lin);
64   ros::Subscriber rsub = n.subscribe<std_msgs::Int32>("rwheel",1,rin);
65 //  tf::TransformBroadcaster odom_broadcaster;
66
67   odomIntegral odomI(baseWidth,wheelRadius);//base and radius in meters. TODO get
   accurate values here
68
69
70   ros::Time current_time, last_time;
71   while(rightCount == bad || leftCount == bad){
72   ros::spinOnce();
73   }
74   int lastValueR=rightCount,lastValueL=leftCount,curValueR,curValueL;
75   ros::Rate r(120);
76   last_time = ros::Time::now();
77   while(n.ok()){
78     ros::spinOnce();
79     current_time = ros::Time::now();
80     //compute odometry in a typical way given the velocities of the robot
81     double dt = (current_time - last_time).toSec();
82     if(dt != 0){
83       curValueR = rightCount;
84       curValueL = leftCount;
85 //    std::cout << curValueR << " " << curValueL << std::endl;
86       double diffR = curValueR-lastValueR;
87       double diffL = curValueL-lastValueL;
88       double wR = (tau*diffR)/(ticksPerRev*dt); //revolution speed of the right
   wheel in radians per second. This is computed as an instantneous measurement since
   the last time we updated
89       double wL = (tau*diffL)/(ticksPerRev*dt);
90       odomI.proc(wL,wR,dt);  //this performs all the integration
91       lastValueR = curValueR;
92       lastValueL = curValueL;
93     //since all odometry is 6DOF we'll need a quaternion created from yaw
94       geometry_msgs::Quaternion odom_quat =
   tf::createQuaternionMsgFromYaw(odomI.theta);
95
96     //first, we'll publish the transform over tf
97     /*geometry_msgs::TransformStamped odom_trans;
98     odom_trans.header.stamp = current_time;
99     odom_trans.header.frame_id = "fuck/odom";
100    odom_trans.child_frame_id = "base_footprint";
101
102    odom_trans.transform.translation.x = odomI.x;
103    odom_trans.transform.translation.y = odomI.y;
104    odom_trans.transform.translation.z = 0.0;
105    odom_trans.transform.rotation = odom_quat;
106
107    //send the transform
108    odom_broadcaster.sendTransform(odom_trans);
109  */
110    //next, we'll publish the odometry message over ROS
111    nav_msgs::Odometry odom;
112    odom.header.stamp = current_time;
113    odom.header.frame_id = "odom";
114    odom.child_frame_id = "odom_footprint";
115
```

```
116     //set the position
117     odom.pose.pose.position.x = odomI.x;
118     odom.pose.pose.position.y = odomI.y;
119     odom.pose.pose.position.z = 0.0;
120     odom.pose.pose.orientation = odom_quat;
121     odom.pose.covariance[0] = 1e-3;
122     odom.pose.covariance[7] = 1e-3;
123     odom.pose.covariance[35] = 1e-3;
124 
125     //set the velocity
126     odom.twist.twist.linear.x = odomI.xdot;
127     odom.twist.twist.linear.y = odomI.ydot;
128     odom.twist.twist.angular.z = odomI.thetadot;
129     odom.twist.covariance[0] = 1e-3;
130     odom.twist.covariance[7] = 1e-3;
131     odom.twist.covariance[35] = 1e-3;
132 
133     //publish the message
134     odom_pub.publish(odom);
135     }
136     last_time = current_time;
137 //    std::cout << "x:" << odomI.x << " y:" << odomI.y << " t:" << odomI.theta <<
    std::endl;
138     r.sleep();
139   }
140 }
141 
```