

Greedy algorithms

CMPSC 465 - Yana Safonova

Cover set

The cover set problem

Problem (Set Cover)

Input:

- a set B
- subsets $S_1, \dots, S_m \subseteq B$

Output: a collection of subsets S_{i_1}, \dots, S_{i_k} s.t. $\bigcup_{j=1}^k S_{i_j} = B$


Goal: minimize the number of selected subsets

Set cover: example

Each post office can serve 30 miles. How to build the minimum number of posts to serve the Centre county?


Set cover: example

Each post office can serve 30 miles. How to build the minimum number of posts to serve the Centre county?




Set cover: example

Each post office can serve 30 miles. How to build the minimum number of posts to serve the Centre county?



Set cover: example


Each post office can serve 30 miles. How to build the minimum number of posts to serve the Centre county?



Let's connect towns with ≤ 30 mile distance

Set cover: example

Each post office can serve 30 miles. How to build the minimum number of posts to serve the Centre county?




Towns reachable from each town:

$$S(a) = \{a, b, d, e, k, i, h\}$$

Set cover: example

Each post office can serve 30 miles. How to build the minimum number of posts to serve the Centre county?




Towns reachable from each town:

$S(a) = \{a, b, d, e, k, i, h\}$

$S(b) = \{a, b, c, d\}$

Set cover: example

Each post office can serve 30 miles. How to build the minimum number of posts to serve the Centre county?



Towns reachable from each town:


$S(a) = \{a, b, d, e, k, i, h\}$

$S(b) = \{a, b, c, d\}$

$S(c) = \{b, c, d\}$

Set cover: example

Each post office can serve 30 miles. How to build the minimum number of posts to serve the Centre county?



Towns reachable from each town:

$$S(a) = \{a, b, d, e, k, i, h\}$$

$$S(b) = \{a, b, c, d\}$$


$$S(c) = \{b, c, d\}$$

...

$$S(k) = \{a, h, i, j, k\}$$

Set cover: example

Finding the cover set for $S(a)$, ..., $S(k)$ will solve the post office problem



Towns reachable from each town:

$S(a) = \{a, b, d, e, k, i, h\}$

$S(b) = \{a, b, c, d\}$


$S(c) = \{b, c, d\}$

...

$S(k) = \{a, h, i, j, k\}$

Set cover: example

The optimal solution:



Towns reachable from each town:

$$S(a) = \{a, b, d, e, k, i, h\}$$

$$S(b) = \{a, b, c, d\}$$


$$S(c) = \{b, c, d\}$$

...

$$S(k) = \{a, h, i, j, k\}$$

Set cover: example

The optimal solution: $S(b)$, $S(f)$, $S(i)$



Towns reachable from each town:

$S(a) = \{a, b, d, e, k, i, h\}$

$S(b) = \{a, b, c, d\}$


$S(c) = \{b, c, d\}$

...

$S(k) = \{a, h, i, j, k\}$

The greedy algorithm

Greedy heuristic: choose the next subset with the most number of uncovered items, until B gets covered



$S(a) = \{a, b, d, e, k, i, h\}$

$S(b) = \{a, b, c, d\}$

$S(c) = \{b, c, d\}$

$S(d) = \{d, b, c, a\}$

$S(e) = \{e, a, f, g\}$

$S(f) = \{f, e, g\}$

$S(g) = \{g, e, f\}$

$S(i) = \{i, a, h, j, k\}$


$S(j) = \{j, h, i, k\}$

$S(h) = \{h, a, i, j, k\}$

$S(k) = \{a, h, i, j, k\}$

The greedy algorithm

Greedy heuristic: choose the next subset with the most number of uncovered items, until B gets covered



$S(a) = \{a, b, d, e, k, i, h\}$

$S(b) = \{a, b, c, d\}$

$S(c) = \{b, c, d\}$

$S(d) = \{d, b, c, a\}$

$S(e) = \{e, a, f, g\}$

$S(f) = \{f, e, g\}$

$S(g) = \{g, e, f\}$

$S(i) = \{i, a, h, j, k\}$


$S(j) = \{j, h, i, k\}$

$S(h) = \{h, a, i, j, k\}$

$S(k) = \{a, h, i, j, k\}$

The greedy algorithm

Greedy heuristic: choose the next subset with the most number of uncovered items, until B gets covered



$S(a) = \{a, b, d, e, k, i, h\}$

$S(b) = \{a, b, c, d\}$

$S(c) = \{b, c, d\}$

$S(d) = \{d, b, c, a\}$

$S(e) = \{e, a, f, g\}$

$S(f) = \{f, e, g\}$

$S(g) = \{g, e, f\}$

$S(i) = \{i, a, h, j, k\}$


$S(j) = \{j, h, i, k\}$

$S(h) = \{h, a, i, j, k\}$

$S(k) = \{a, h, i, j, k\}$

The greedy algorithm

Greedy heuristic: choose the next subset with the most number of uncovered items, until B gets covered



$S(a) = \{a, b, d, e, k, i, h\}$

$S(b) = \{a, b, c, d\}$

$S(c) = \{b, c, d\}$

$S(d) = \{d, b, c, a\}$

$S(e) = \{e, a, f, g\}$

$S(f) = \{f, e, g\}$

$S(g) = \{g, e, f\}$

$S(i) = \{i, a, h, j, k\}$


$S(j) = \{j, h, i, k\}$

$S(h) = \{h, a, i, j, k\}$

$S(k) = \{a, h, i, j, k\}$

The greedy algorithm

Greedy heuristic: choose the next subset with the most number of uncovered items, until B gets covered



$S(a) = \{a, b, d, e, k, i, h\}$

$S(b) = \{a, b, c, d\}$

$S(c) = \{b, c, d\}$

$S(d) = \{d, b, c, a\}$

$S(e) = \{e, a, f, g\}$

$S(f) = \{f, e, g\}$

$S(g) = \{g, e, f\}$

$S(i) = \{i, a, h, j, k\}$


$S(j) = \{j, h, i, k\}$

$S(h) = \{h, a, i, j, k\}$

$S(k) = \{a, h, i, j, k\}$

The greedy algorithm

Greedy heuristic: choose the next subset with the most number of uncovered items, until B gets covered



S(a) = {a, b, d, e, k, i, h}

S(b) = {a, b, c, d}

S(c) = {b, c, d}

S(d) = {d, b, c, a}

S(e) = {e, a, f, g}

S(f) = {f, e, g}

S(g) = {g, e, f}

S(i) = {i, a, h, j, k}


S(j) = {j, h, i, k}

S(h) = {h, a, i, j, k}

S(k) = {a, h, i, j, k}

The greedy algorithm

Greedy heuristic: choose the next subset with the most number of uncovered items, until B gets covered



S(a) = {a, b, d, e, k, i, h}

S(b) = {a, b, c, d}

S(c) = {b, c, d}

S(d) = {d, b, c, a}

S(e) = {e, a, f, g}

S(f) = {f, e, g}

S(g) = {g, e, f}

S(i) = {i, a, h, j, k}


S(j) = {j, h, i, k}

S(h) = {h, a, i, j, k}

S(k) = {a, h, i, j, k}

The greedy algorithm

Greedy heuristic: choose the next subset with the most number of uncovered items, until B gets covered



S(a) = {a, b, d, e, k, i, h}

S(b) = {a, b, c, d}

S(c) = {b, c, d}

S(d) = {d, b, c, a}

S(e) = {e, a, f, g}

S(f) = {f, e, g}

S(g) = {g, e, f}

S(i) = {i, a, h, j, k}


S(j) = {j, h, i, k}

S(h) = {h, a, i, j, k}

S(k) = {a, h, i, j, k}

The greedy algorithm

Greedy heuristic: choose the next subset with the most number of uncovered items, until B gets covered



S(a) = {a, b, d, e, k, i, h}

S(b) = {a, b, c, d}

S(c) = {b, c, d}

S(d) = {d, b, c, a}

S(e) = {e, a, f, g}

S(f) = {f, e, g}

S(g) = {g, e, f}

S(i) = {i, a, h, j, k}


S(j) = {j, h, i, k}

S(h) = {h, a, i, j, k}

S(k) = {a, h, i, j, k}

The greedy algorithm

Greedy heuristic: choose the next subset with the most number of uncovered items, until B gets covered



$$S(a) = \{a, b, d, e, k, i, h\}$$

$$S(b) = \{a, b, c, d\}$$


$$S(e) = \{e, a, f, g\}$$

$$S(i) = \{i, a, h, j, k\}$$

$$k_{\text{GREEDY}} = 4$$

The greedy algorithm

Greedy heuristic: choose the next subset with the most number of uncovered items, until B gets covered



$$S(a) = \{a, b, d, e, k, i, h\}$$

$$S(b) = \{a, b, c, d\}$$

$$S(e) = \{e, a, f, g\}$$

$$S(i) = \{i, a, h, j, k\}$$

$$k_{\text{GREEDY}} = 4$$

$$k_{\text{OPT}} = 3$$

The optimal algorithm

S1	S2	S3	S4	Cover all elements?	# sets
0	0	0	0	No	0
0	0	0	1	No	1
0	0	1	0	No	1
0	0	1	1	Yes	2
0	1	0	0	Yes	1
0	1	0	1	Yes	2
...
1	1	1	1	Yes	4

The optimal algorithm

S1	S2	S3	S4	Cover all elements?	# sets
0	0	0	0	No	0
0	0	0	1	No	1
0	0	1	0	No	1
0	0	1	1	Yes	2
0	1	0	0	Yes	1 (!!!)
0	1	0	1	Yes	2
...
1	1	1	1	Yes	4

$O(2^N)$ = exponential running time

Greedy vs optimal algorithms for the cover set problem

Although the greedy solution is not optimal, but it's not off by much

Theorem

Assume $|B| = n$ and the optimal solution uses k subsets. Then the greedy algorithm uses at most $k \ln(n)$ subsets

Proof

Proof: Let n_t be the number of elements not covered by the greedy algorithm after t iterations.

Proof

Proof: Let n_t be the number of elements not covered by the greedy algorithm after t iterations. These remaining n_t elements are covered by the optimal k subsets.

Proof

Proof: Let n_t be the number of elements not covered by the greedy algorithm after t iterations. These remaining n_t elements are covered by the optimal k subsets. So some subsets has $\geq \frac{n_t}{k}$ of these uncovered elements, and the greedy algorithm will pick a set of size at least $\frac{n_t}{k}$.

Proof


Proof: Let n_t be the number of elements not covered by the greedy algorithm after t iterations. These remaining n_t elements are covered by the optimal k subsets. So some subsets has $\geq \frac{n_t}{k}$ of these uncovered elements, and the greedy algorithm will pick a set of size at least $\frac{n_t}{k}$.



$$n_t = 6, \quad k = 4$$


Proof

Proof: Let n_t be the number of elements not covered by the greedy algorithm after t iterations. These remaining n_t elements are covered by the optimal k subsets. So some subsets has $\geq \frac{n_t}{k}$ of these uncovered elements, and the greedy algorithm will pick a set of size at least $\frac{n_t}{k}$.




Proof

Proof: Let n_t be the number of elements not covered by the greedy algorithm after t iterations. These remaining n_t elements are covered by the optimal k subsets. So some subsets has $\geq \frac{n_t}{k}$ of these uncovered elements, and the greedy algorithm will pick a set of size at least $\frac{n_t}{k}$.



Proof

Proof: Let n_t be the number of elements not covered by the greedy algorithm after t iterations. These remaining n_t elements are covered by the optimal k subsets. So some subsets has $\geq \frac{n_t}{k}$ of these uncovered elements, and the greedy algorithm will pick a set of size at least $\frac{n_t}{k}$.



Proof

Proof: Let n_t be the number of elements not covered by the greedy algorithm after t iterations. These remaining n_t elements are covered by the optimal k subsets. So some subsets has $\geq \frac{n_t}{k}$ of these uncovered elements, and the greedy algorithm will pick a set of size at least $\frac{n_t}{k}$. So, $n_{t+1} \leq n_t - \frac{n_t}{k} = n_t \left(1 - \frac{1}{k}\right)$

Proof

Proof: Let n_t be the number of elements not covered by the greedy algorithm after t iterations. These remaining n_t elements are covered by the optimal k subsets. So some subsets has $\geq \frac{n_t}{k}$ of these uncovered elements, and the greedy algorithm will pick a set of size at least $\frac{n_t}{k}$.

So, $n_{t+1} \leq n_t - \frac{n_t}{k} = n_t \left(1 - \frac{1}{k}\right)$

Repeatedly applying this:

$$n_t \leq n_{t-1} \left(1 - \frac{1}{k}\right) \leq n_{t-2} \left(1 - \frac{1}{k}\right)^2 \leq \dots \leq n_0 \left(1 - \frac{1}{k}\right)^t = n \left(1 - \frac{1}{k}\right)^t$$

Proof

Proof: Let n_t be the number of elements not covered by the greedy algorithm after t iterations. These remaining n_t elements are covered by the optimal k subsets. So some subsets has $\geq \frac{n_t}{k}$ of these uncovered elements, and the greedy algorithm will pick a set of size at least $\frac{n_t}{k}$. So, $n_{t+1} \leq n_t - \frac{n_t}{k} = n_t \left(1 - \frac{1}{k}\right)$

Repeatedly applying this:

$$n_t \leq n_{t-1} \left(1 - \frac{1}{k}\right) \leq n_{t-2} \left(1 - \frac{1}{k}\right)^2 \leq \dots \leq n_0 \left(1 - \frac{1}{k}\right)^t = n \left(1 - \frac{1}{k}\right)^t$$

Using the fact: $1 - x \leq e^{-x}$ (equality when $x = 0$)

$$n_t \leq n \left(1 - \frac{1}{k}\right)^t \leq ne^{-t/k}$$

Proof

Proof: Let n_t be the number of elements not covered by the greedy algorithm after t iterations. These remaining n_t elements are covered by the optimal k subsets. So some subsets has $\geq \frac{n_t}{k}$ of these uncovered elements, and the greedy algorithm will pick a set of size at least $\frac{n_t}{k}$.

$$\text{So, } n_{t+1} \leq n_t - \frac{n_t}{k} = n_t \left(1 - \frac{1}{k}\right)$$

Repeatedly applying this:

$$n_t \leq n_{t-1} \left(1 - \frac{1}{k}\right) \leq n_{t-2} \left(1 - \frac{1}{k}\right)^2 \leq \dots \leq n_0 \left(1 - \frac{1}{k}\right)^t = n \left(1 - \frac{1}{k}\right)^t$$

Using the fact: $1 - x \leq e^{-x}$ (equality when $x = 0$)

$$n_t \leq n \left(1 - \frac{1}{k}\right)^t \leq ne^{-t/k}$$

Greedy algorithm terminates when $n_t < 1$. Let's find out what t makes $n_t < 1$

Proof

Since $n_t < ne^{-t/k}$, it suffices to make $ne^{-t/k} \leq 1$

Proof

Since $n_t < ne^{-t/k}$, it suffices to make $ne^{-t/k} \leq 1$

Solving $ne^{-t/k} \leq 1$

$$\iff e^{-t/k} \leq \frac{1}{n} \iff -\frac{t}{k} \leq \ln\left(\frac{1}{n}\right) \iff t \geq -k \ln\left(\frac{1}{n}\right) = k \ln(n)$$

Proof

Since $n_t < ne^{-t/k}$, it suffices to make $ne^{-t/k} \leq 1$

Solving $ne^{-t/k} \leq 1$

$$\iff e^{-t/k} \leq \frac{1}{n} \iff -\frac{t}{k} \leq \ln\left(\frac{1}{n}\right) \iff t \geq -k \ln\left(\frac{1}{n}\right) = k \ln(n)$$

At $t = k \ln(n)$, $n_t < 1$. Everything is covered



Proof

Since $n_t < ne^{-t/k}$, it suffices to make $ne^{-t/k} \leq 1$

Solving $ne^{-t/k} \leq 1$

$$\iff e^{-t/k} \leq \frac{1}{n} \iff -\frac{t}{k} \leq \ln\left(\frac{1}{n}\right) \iff t \geq -k \ln\left(\frac{1}{n}\right) = k \ln(n)$$

At $t = k \ln(n)$, $n_t < 1$. Everything is covered



Proof of the fact $1 - x \leq e^{-x}$ (equality when $x = 0$):

Proof

Since $n_t < ne^{-t/k}$, it suffices to make $ne^{-t/k} \leq 1$

Solving $ne^{-t/k} \leq 1$

$$\iff e^{-t/k} \leq \frac{1}{n} \iff -\frac{t}{k} \leq \ln\left(\frac{1}{n}\right) \iff t \geq -k \ln\left(\frac{1}{n}\right) = k \ln(n)$$

At $t = k \ln(n)$, $n_t < 1$. Everything is covered




Proof of the fact $1 - x \leq e^{-x}$ (equality when $x = 0$):

Consider $f(x) = e^{-x} - (1 - x) \geq 0$

$$f(x) = e^{-x} - (1 - x)$$

Graph Plotter :: An Online Graphing Calculator



Proof

Since $n_t < ne^{-t/k}$, it suffices to make $ne^{-t/k} \leq 1$

Solving $ne^{-t/k} \leq 1$

$$\iff e^{-t/k} \leq \frac{1}{n} \iff -\frac{t}{k} \leq \ln\left(\frac{1}{n}\right) \iff t \geq -k \ln\left(\frac{1}{n}\right) = k \ln(n)$$

At $t = k \ln(n)$, $n_t < 1$. Everything is covered



Proof of the fact $1 - x \leq e^{-x}$ (equality when $x = 0$):

Consider $f(x) = e^{-x} - (1 - x) \geq 0$

$f'(x) = -e^{-x} + 1$. Critical point at $x = 0$, achieving minimum



Implementation

Input:

U - set of elements,

F - family of sets: $\bigcup_{S \in F} S = U$

Output:

E - a family of sets; $E \subseteq F$: $\bigcup_{S \in E} S = U$

Pseudocode:

$E = \{\}$

while U is not empty do:

 choose S from F that maximizes the cover of elements in U

 add S to E

 subtract S 's elements from U

return E

Implementation

```
from collections import defaultdict
```

```
# F is a list of sets
```

```
# First prepare a list of all sets where each element appears
```

```
D = defaultdict(list)
```

```
for S_idx, S in enumerate(F):
```

```
    for element in S:
```

```
        D[element].append(S_idx)
```

```
L = defaultdict(set)
```

```
# Place sets into an array that tells us which sets have  
corresponding size
```

```
for S_idx, S in enumerate(F):
```

```
    L[len(S)].add(S_idx)
```


Implementation

E = [] # Keep track of selected sets

Now loop over each set size

for set_size in range(max(len(S) for S in F), 0, -1):

if set_size in L:

P = L[set_size] # set of all sets with size = set_size

while len(P) > 0:

S_idx = P.pop()

E.append(S_idx)

for a in F[S_idx]: # all elements in the current set

for y in D[a]: # all sets containing the element a

if y != S_idx: # not the current set

removing a from y

S2 = F[y]

L[len(S2)].remove(y)

S2.remove(a)

L[len(S2)].add(y)

print E

F = the input list of sets

D = map from elements to the
list of sets containing it

L = map of set lengths to
indices of sets in F

Implementation

`E = [] # Keep track of selected sets`

`# Now loop over each set size`

`for set_size in range(max(len(S) for S in F), 0, -1):`

`if set_size in L:`

`P = L[set_size] # set of all sets with size = set_size`

`while len(P) > 0:`

`S_idx = P.pop()`

`E.append(S_idx)`

`for a in F[S_idx]: # all elements in the current set`

`for y in D[a]: # all sets containing the element a`

`if y != S_idx: # not the current set`

`# removing a from y`

`S2 = F[y]`

`L[len(S2)].remove(y)`

`S2.remove(a)`

`L[len(S2)].add(y)`

Cannot be
executed
more times
than the
number of
elements

`print E`

`F = the input list of sets`

`D = map from elements to the
list of sets containing it`

`L = map of set lengths to
indices of sets in F`

Hashsets access and
edit elements using Θ
(1)

Total:
 $O(N)$
 $N = \# \text{ elements}$