

Checklist

Mixer

F8 Manual references

- 1 Plugin Mics
- 2 Turn Phantom power On for condenser mic channels, Boom. - [90](#) -
Keep Off for Radio Mic channels.
- 3 Turn Limiter On for all channels (on ZoomF8 “On Normal” is fine). - [83](#) -
- 4 Bring Faders up to just above zero (centre).
- 5 Set input levels (Trim or Gain). Average -12Db. - [28](#) -
- 6 Check/Set Sample Rate (48kHz) and Bit Depth (24bits) – [30](#) -
- 7 Name folders (if recorder allows it) – [55](#) -
- 8 Test Record
- 9 Engage EQ (High Pass Filter HPF) if required. - [82](#) -

Radio Mics

ew-100p G4 Manual references

- 1 Turn on the Receivers.
- 2 Scan bandwidth. Select: Set – Easy Setup – Scan New List – Current List – Bank ‘X’ – Channel ‘X’ – Set. (remember to have all actors on the same Bank different Channels).
- 3 Sync the Transmitter and Receiver to the same frequency. Select Sync with both units doors open facing each other. - [121](#) -
Alternatively tune it manually. Advanced – Tune – Adjust the frequency and ‘Set’ to confirm each choice. - [100](#) -
- 4 Listen and check for a clean signal.