

Interview presentation

Stefano Trevisani

December 2, 2022

Università degli Studi di Udine

Alpen Adria Universität Klagenfurt

ZK-SNARKs, what?

Zero-Knowledge Succinct Non-interactive ARgument of Knowledge:

- A multidisciplinary topic: math, complexity, cryptography¹.
- **Prover** wants to prove a statement, might be dishonest!
- **Verifier** wants to verify the proof, might be curious!
- **Prover** does not want to disclose secrets: **Zero-Knowledge**.
- **Verifier** does not want to waste time: **Succinct** proof.
- **Prover** proves once and for all: **Non-interactive**.
- Parties are “not too powerful”: **ARgument of Knowledge**.


¹A few milestones: [GMR89, Sha92, Dam93, Mic00, GGPR12, Gro16].

ZK-SNARKs, why?

Many useful applications! For example:

- Cloud computing [PGHR13].
- Households figuring out their bills privately.
- **Anonymous transactions on the blockchain** [BSCG⁺14].

The Blockchain




- Groups of transactions are leaves of a *Merkle tree* [Mer88].
- Bottom-up computation using a **compression function**.
- The root contains the *commitment* (among other data).
- Verify a commitment following the *authentication path*.

Compression functions

One-way compression functions (OWCF):

- Many (e.g. 2) inputs and few (e.g. 1) outputs.
- Easy to compute, but hard to invert (and find collisions).
- Usually derived from one-way permutations.
- Standard designs (SHA [Dan15]) work over *boolean fields*.
- Davies-Meyer [Pre05], sponge [BDPVA07]...



ZK-SNARK and compression functions

SHA is very fast natively, but what about in ZK-SNARK?

- Efficient ZK-SNARKs over prime fields \mathbb{F}_p [GGPR12].
- Input-output relationship as bi-linear constraints (R1CS) [BSCTV13].
- One multiplication = one constraint.
- What about SHA-256? 25000+ constraints!
- Can we do better?

Minimal Multiplicative Complexity (MiMC) hash function [AGR⁺16]:

- Extremely simple: *round function* is $x^3 + c^2$.
- Many rounds to be secure against *algebraic attacks*.
- MiMCHash-256: 640 constraints.
- Can we do better?

²Warning: might not be a permutation!

Many improvements in the last years, POSEIDON [GKR⁺21]³:

- Partial *substitution-permutation network* (SPN) rounds.
- Full SPN for classic attacks (linear, differential. . .).
- Partial SPN for algebraic attacks (interpolation, Gröbner. . .).
- POSEIDON-256: 276 constraints.
- Can we do better?

³See also: [GHR⁺22, BBC⁺22, AABS⁺19].

Our design Arion [RST23]:

- Builds on the GTDS algebraic framework [RS22].
- Two variants: Arion and α -Arion.
- α -ArionHash-256: 76 constraints.

Comparisons

libsnark: used by ZCash [BSCG⁺14] for its blockchain.

We used it to implement:

- Several primitives designed for ZK-SNARK, including ours.
- A self-parametrizing Merkle tree.
- A new mode of hash, the Augmented Binary tRee [ABR21].

Proof generation times for MT commitments over 256-bit prime fields

Tree height	α -ArionHash	GRIFFIN	POSEIDON
4	73 ms	88 ms	186 ms
8	145 ms	181 ms	386 ms
16	278 ms	338 ms	745 ms
32	509 ms	622 ms	1422 ms

The End

Thank you for your attention!



Abdelrahman Aly, Tomer Ashur, Eli Ben-Sasson, Siemen Dhooghe, and Alan Szepieniec.

Design of symmetric-key primitives for advanced cryptographic protocols.

Cryptology ePrint Archive, Paper 2019/426, 2019.

<https://eprint.iacr.org/2019/426>.



Elena Andreeva, Rishiraj Bhattacharyya, and Arnab Roy.

Compactness of hashing modes and efficiency beyond merkle tree.

Cryptology ePrint Archive, Paper 2021/573, 2021.

<https://eprint.iacr.org/2021/573>.



Martin Albrecht, Lorenzo Grassi, Christian Rechberger, Arnab Roy, and Tyge Tiessen.

Mimc: Efficient encryption and cryptographic hashing with minimal multiplicative complexity.

In Jung Hee Cheon and Tsuyoshi Takagi, editors, *Advances in Cryptology – ASIACRYPT 2016*, pages 191–219, Berlin, Heidelberg, 2016. Springer Berlin Heidelberg.



Clémence Bouvier, Pierre Briaud, Pyrros Chaidos, Léo Perrin, Robin Salen, Vesselin Velichkov, and Danny Willems.

New design techniques for efficient arithmetization-oriented hash functions: anemoi permutations and jive compression mode.

Cryptology ePrint Archive, Paper 2022/840, 2022.

<https://eprint.iacr.org/2022/840>.



Guido Bertoni, Joan Daemen, Michaël Peeters, and Gilles Van Assche.

Sponge functions.

In *ECRYPT hash workshop*, volume 2007, 2007.



Eli Ben Sasson, Alessandro Chiesa, Christina Garman, Matthew Green, Ian Miers, Eran Tromer, and Madars Virza.

Zerocash: Decentralized anonymous payments from bitcoin.

In *2014 IEEE Symposium on Security and Privacy*, pages 459–474, 2014.



Eli Ben-Sasson, Alessandro Chiesa, Eran Tromer, and Madars Virza.
Succinct non-interactive zero knowledge for a von neumann architecture.
Cryptology ePrint Archive, Paper 2013/879, 2013.
<https://eprint.iacr.org/2013/879>.



Ivan Damgård.
Non-interactive circuit based proofs and non-interactive perfect zero-knowledge with preprocessing.
In Rainer A. Rueppel, editor, *Advances in Cryptology — EUROCRYPT' 92*, pages 341–355, Berlin, Heidelberg, 1993. Springer Berlin Heidelberg.



Quynh H. Dang.
Secure Hash Standard.
National Institute of Standards and Technology, Jul 2015.



Rosario Gennaro, Craig Gentry, Bryan Parno, and Mariana Raykova.
Quadratic span programs and succinct nizks without pcps.
Cryptology ePrint Archive, Paper 2012/215, 2012.
<https://eprint.iacr.org/2012/215>.



Lorenzo Grassi, Yongling Hao, Christian Rechberger, Markus Schofnegger, Roman Walch, and Qingju Wang.
A new feistel approach meets fluid-spn: Griffin for zero-knowledge applications.
IACR Cryptol. ePrint Arch., 2022:403, 2022.



Lorenzo Grassi, Dmitry Khovratovich, Christian Rechberger, Arnab Roy, and Markus Schofnegger.
Poseidon: A new hash function for zero-knowledge proof systems.
In *USENIX Security Symposium*, 2021.



Shafi Goldwasser, Silvio Micali, and Charles Rackoff.
The knowledge complexity of interactive proof systems.
SIAM Journal on Computing, 18(1):186–208, 1989.



Jens Groth.

On the size of pairing-based non-interactive arguments.

Cryptology ePrint Archive, Paper 2016/260, 2016.

<https://eprint.iacr.org/2016/260>.



Ralph C. Merkle.

A digital signature based on a conventional encryption function.

In Carl Pomerance, editor, *Advances in Cryptology — CRYPTO '87*, pages 369–378, Berlin, Heidelberg, 1988. Springer Berlin Heidelberg.



Silvio Micali.

Computationally sound proofs.

SIAM J. Comput., 30(4):1253–1298, oct 2000.



Bryan Parno, Craig Gentry, Jon Howell, and Mariana Raykova.

Pinocchio: Nearly practical verifiable computation.

Cryptology ePrint Archive, Paper 2013/279, 2013.

<https://eprint.iacr.org/2013/279>.



Bart Preneel.

Davies–Meyer Hash Function, pages 136–136.

Springer US, Boston, MA, 2005.



Arnab Roy and Matthias Steiner.

Generalized triangular dynamical system: An algebraic system for constructing cryptographic permutations over finite fields, 2022.



Arnab Roy, Matthias Steiner, and Stefano Trevisani.

Arion: Arithmetization-oriented permutation and hashing from generalized triangular dynamical systems.

Undergoing submission, 2023.



Adi Shamir.

$lp = pspace$.

J. ACM, 39(4):869–877, oct 1992.