



$\begin{array}{c} {\bf Type 977~fitting~for~heat~pump}\\ {\bf HP10L\text{-}WEB} \end{array}$

Parametric Heat Pump calculation

Dani Carbonell

dani.carbonell@spf.ch

2019/02/26 at: 13:28:54 h





Table 1: Fitted coefficients for the heat pump.


| Coefficient | Description | |
|--|--|---------------|
| | | [kW] |
| P_{Q_1} | 1 st condenser polynomial coefficient | 1.3928e+01 |
| P_{Q_2} | 2^{st} condenser polynomial coefficient | 7.0109e+01 |
| P_{Q_3} | 3^{st} condenser polynomial coefficient | -2.8286e+01 |
| P_{Q_4} | 4^{st} condenser polynomial coefficient | 7.9397e + 01 |
| P_{Q_5} | 5^{st} condenser polynomial coefficient | 1.4315e + 02 |
| P_{Q_6} | 6 st condenser polynomial coefficient | 7.0718e+00 |
| P_{COP_1} | 1 st COP polynomial coefficient | 9.5084e+00 |
| P_{COP_2} | 2 st COP polynomial coefficient | 5.7050e+01 |
| P_{COP_3} | 3 st COP polynomial coefficient | -5.0748e + 01 |
| P_{COP_4} | 4 st COP polynomial coefficient | -1.9264e+02 |
| P_{COP_5} | 5 st COP polynomial coefficient | 8.9936e+01 |
| P_{COP_6} | 6 st COP polynomial coefficient | 7.3762e+01 |
| \dot{m}_{cond} | $2100.00 \ [kg/h]$ | |
| \dot{m}_{evap} | 5250.00 [kg/h] | |
| $\overline{COP_{nom} \text{ (A0W35)}}$ | 4.21 | |
| $Q_{cond,nom}$ (A0W35) | $9.95 \ [kW]$ | |
| $Q_{evap,nom}$ (A0W35) | 7.58 [kW] | |
| $W_{comp,nom}$ (A0W35) | 2.36~[kW] | |
| RMS_{COP} | 9.03e - 02 | |
| $RMS_{Q_{cond}}$ | 2.68e - 01 | |
| $RMS_{W_{comp}}$ | 6.26e - 02 | |
| Fit model | Average Temperature | |





Table 2: Differences between experiments and fitted data for the heat pump. $error = 100 \cdot |\frac{Q_{exp} - Q_{num}}{Q_{exp}}|$ and $RMS = \sqrt{\sum \frac{(Q_{exp} - Q_{num})^2}{n_p}}$ where n_p is the number of data points.

| $T_{cond,out}$ | $T_{evap,in}$ | COP | COP_{exp} | error | Q_{cond} | $Q_{cond,exp}$ | error | W_{comp} | $W_{comp,exp}$ | error |
|------------------|---------------|------|-------------|-------|------------|----------------|-------|------------|----------------|-------|
| ^{o}C | ^{o}C | [-] | [-] | [%] | [kW] | [kW] | [%] | [kW] | [kW] | [%] |
| 35.00 | 20.00 | 6.95 | 6.98 | 0.4 | 15.91 | 15.63 | 1.8 | 2.29 | 2.24 | 2.23 |
| 35.00 | 10.00 | 5.49 | 5.53 | 0.7 | 12.82 | 13.15 | 2.5 | 2.34 | 2.38 | 1.79 |
| 35.00 | 7.00 | 5.09 | 5.20 | 2.0 | 11.95 | 12.47 | 4.1 | 2.35 | 2.40 | 2.14 |
| 35.00 | 2.00 | 4.41 | 4.17 | 5.8 | 10.52 | 10.00 | 5.2 | 2.39 | 2.40 | 0.59 |
| 35.00 | -7.00 | 3.43 | 3.40 | 1.0 | 8.19 | 7.99 | 2.5 | 2.38 | 2.35 | 1.47 |
| 35.00 | -15.00 | 2.72 | 2.83 | 3.8 | 6.33 | 6.45 | 1.9 | 2.33 | 2.28 | 2.03 |
| 45.00 | 7.00 | 3.87 | 3.89 | 0.4 | 11.13 | 11.43 | 2.6 | 2.87 | 2.94 | 2.23 |
| 45.00 | 2.00 | 3.34 | 3.25 | 2.6 | 9.66 | 9.30 | 3.8 | 2.89 | 2.86 | 1.17 |
| 45.00 | -7.00 | 2.58 | 2.56 | 0.5 | 7.23 | 7.13 | 1.3 | 2.80 | 2.78 | 0.84 |
| 45.00 | -15.00 | 2.05 | 2.05 | 0.3 | 5.26 | 5.47 | 3.8 | 2.56 | 2.67 | 4.04 |
| 50.00 | 20.00 | 4.75 | 4.66 | 2.0 | 14.91 | 14.81 | 0.7 | 3.14 | 3.18 | 1.35 |
| 50.00 | 15.00 | 4.18 | 4.30 | 2.9 | 13.26 | 13.60 | 2.5 | 3.17 | 3.16 | 0.38 |
| 50.00 | 7.00 | 3.33 | 3.44 | 3.0 | 10.74 | 10.83 | 0.9 | 3.22 | 3.15 | 2.25 |
| 50.00 | 2.00 | 2.87 | 2.88 | 0.2 | 9.24 | 8.95 | 3.3 | 3.22 | 3.11 | 3.48 |
| 50.00 | -7.00 | 2.22 | 2.21 | 0.2 | 6.75 | 6.68 | 1.1 | 3.05 | 3.02 | 0.87 |
| 55.00 | 20.00 | 4.11 | 4.03 | 2.1 | 14.60 | 14.46 | 1.0 | 3.55 | 3.59 | 1.10 |
| 55.00 | 7.00 | 2.85 | 2.94 | 3.1 | 10.36 | 10.48 | 1.1 | 3.63 | 3.56 | 2.07 |
| 55.00 | -7.00 | 1.91 | 1.85 | 3.3 | 6.30 | 6.33 | 0.6 | 3.30 | 3.43 | 3.69 |
| Sum | | | | 34.5 | | | 40.5 | | | 33.71 |
| RMS_{COP} | 9.03e - 02 | | | | | | | | | |
| RMS_{O} | 2.68e - 01 | | | | | | | | | |
| $RMS_{W_{comp}}$ | 6.26e - 02 | | | | | | | | | |








Figure 1: Q_{cond} differences between experiments and fitted data








Figure 2: W_{comp} differences between experiments and fitted data








Figure 3: COP differences between experiments and fitted data