



## Type977 fitting for heat pump SIN-11TU Parametric Heat Pump calculation

Dani Carbonell

dani. carbonell@spf.ch

2019/03/12 at: 16:07:47 h





Table 1: Fitted coefficients for the heat pump.

Coefficient	Description	
		[kW]
$P_{Q_1}$	1 <sup>st</sup> condenser polynomial coefficient	1.0347e + 01
$P_{Q_2}$	$2^{st}$ condenser polynomial coefficient	1.1794e + 02
$P_{Q_3}$	$3^{st}$ condenser polynomial coefficient	2.9112e+01
$P_{Q_4}$	4 <sup>st</sup> condenser polynomial coefficient	-2.0540e+02
$P_{Q_5}$	$5^{st}$ condenser polynomial coefficient	6.8104e+01
$P_{Q_6}$	6 <sup>st</sup> condenser polynomial coefficient	-1.4845e+02
$P_{COP_1}$	1 <sup>st</sup> COP polynomial coefficient	7.3541e+00
$P_{COP_2}$	2 <sup>st</sup> COP polynomial coefficient	7.4987e + 01
$P_{COP_3}$	3 <sup>st</sup> COP polynomial coefficient	-1.0135e+01
$P_{COP_4}$	4 <sup>st</sup> COP polynomial coefficient	-2.9177e + 02
$P_{COP_5}$	5 <sup>st</sup> COP polynomial coefficient	-3.3744e+01
$P_{COP_6}$	6 <sup>st</sup> COP polynomial coefficient	-6.5273e+01
$\dot{m}_{cond}$	$1900.00 \ [kg/h]$	
$\dot{m}_{evap}$	$1900.00 \ [kg/h]$	
$COP_{nom}$ (A0W35)	4.85	
$Q_{cond,nom}$ (A0W35)	$10.86 \ [kW]$	
$Q_{evap,nom}$ (A0W35)	8.62 [kW]	
$W_{comp,nom}$ (A0W35)	2.24 [kW]	
$RMS_{COP}$	5.14e - 02	
$RMS_{Q_{cond}}$	4.08e - 02	
$RMS_{W_{comp}}$	3.44e - 02	
Fit model	Average Temperature	





Table 2: Differences between experiments and fitted data for the heat pump.  $error = 100 \cdot |\frac{Q_{exp} - Q_{num}}{Q_{exp}}|$  and  $RMS = \sqrt{\sum \frac{(Q_{exp} - Q_{num})^2}{n_p}}$  where  $n_p$  is the number of data points.

$T_{cond,out}$	$T_{evap,in}$	COP	$COP_{exp}$	error	$Q_{cond}$	$Q_{cond,exp}$	error	$W_{comp}$	$W_{comp,exp}$	error
${}^{o}C$	°C	[-]	[-]	[%]	[kW]	[kW]	[%]	[kW]	[kW]	[%]
35.00	-5.00	4.18	4.20	0.5	9.43	9.50	0.8	2.26	2.26	0.22
35.00	0.00	4.90	4.87	0.7	10.97	10.90	0.6	2.24	2.24	0.01
35.00	5.00	5.62	5.59	0.5	12.56	12.55	0.1	2.24	2.25	0.38
50.00	-5.00	2.98	2.92	2.1	8.98	8.97	0.1	3.01	3.07	1.92
50.00	0.00	3.43	3.38	1.6	10.36	10.30	0.6	3.02	3.05	0.97
50.00	5.00	3.89	3.82	1.7	11.79	11.78	0.1	3.03	3.08	1.64
45.00	-5.00	3.42	3.46	1.1	9.22	9.23	0.1	2.69	2.67	0.94
45.00	0.00	3.97	4.01	1.0	10.66	10.60	0.5	2.69	2.64	1.59
45.00	5.00	4.51	4.57	1.2	12.14	12.17	0.2	2.69	2.67	0.97
55.00	0.00	2.85	2.90	1.5	9.98	10.00	0.2	3.50	3.45	1.33
55.00	5.00	3.21	3.25	1.2	11.36	11.40	0.4	3.53	3.50	0.78
35.00	10.00	6.32	6.31	0.2	14.19	14.20	0.1	2.24	2.25	0.28
35.00	15.00	7.03	7.03	0.0	15.87	15.85	0.1	2.26	2.25	0.15
50.00	10.00	4.33	4.25	1.9	13.27	13.27	0.0	3.06	3.12	1.86
50.00	15.00	4.76	4.66	2.1	14.79	14.75	0.3	3.10	3.16	1.80
45.00	10.00	5.05	5.11	1.2	13.67	13.73	0.4	2.71	2.69	0.81
45.00	15.00	5.57	5.65	1.3	15.25	15.30	0.3	2.74	2.71	1.01
55.00	10.00	3.57	3.60	0.8	12.78	12.80	0.2	3.58	3.56	0.67
55.00	15.00	3.91	3.93	0.6	14.25	14.20	0.3	3.65	3.62	0.90
Sum				21.3			5.5			18.24
$RMS_{COP}$	5.14e - 02									
$RMS_{Q_{cond}}$	4.08e - 02									
$RMS_{W_{comp}}^{Q_{comp}}$	3.44e - 02									





## $\rm Meier/SIN\text{-}11TU/SIN\text{-}11TU\text{-}Qcond.pdf}$




Figure 1:  $Q_{cond}$  differences between experiments and fitted data





## $\rm Meier/SIN\text{-}11TU/SIN\text{-}11TU\text{-}Qcomp.pdf$




Figure 2:  $W_{comp}$  differences between experiments and fitted data





## $\rm Meier/SIN\text{-}11TU/SIN\text{-}11TU\text{-}COP.pdf$




Figure 3: COP differences between experiments and fitted data