

Set up IP MetroCluster peering

ONTAP 9

[netapp-aherbin], Thom Illingworth November 04, 2020

This PDF was generated from https://docs.netapp.com/us-en/ontap/task_metrocluster_peering.html on May 08, 2021. Always check docs.netapp.com for the latest.

Table of Contents

| Set up IP MetroCluster peering | g | |
 | . 1 |
|--------------------------------|-----------------|---|------|------|------|------|------|------|------|------|------|-----|
| Performing the peering prod | ess from Site A | |
 | . 1 |
| Performing the peering prod | ess from Site E | 3 |
 | . 1 |

Set up IP MetroCluster peering

Starting with ONTAP 9.8, you can manage an IP configuration of a MetroCluster operation with System Manager. After setting up two clusters, you set up peering between them.

Before you start

You should have completed the following procedure to set up two clusters:

· Set up an IP MetroCluster site

Certain steps of this process are performed by different system administrators located at the geographical sites of each cluster. For the purposes of explaining this process, the clusters are called "Site A cluster" and "Site B cluster".

Performing the peering process from Site A

This process is performed by a system administrator at Site A.

Steps

- 1. Log in to Site A cluster.
- 2. In System Manager, select **Dashboard** from the left navigation column to display the cluster overview.

The dashboard shows the details for this cluster (Site A). In the **MetroCluster** section, Site A cluster is shown on the left.

- 3. Click Attach Partner Cluster.
- Enter the details of the network interfaces that allow the nodes in Site A cluster to communicate with the nodes in Site B cluster.
- 5. Click Save and Continue.
- 6. On the **Attach Partner Cluster** window, select **I do not have a passphrase**, which lets you generate a passphrase.
- 7. Copy the generated passphrase and share it with the system administrator at Site B.
- 8. Select Close.

Performing the peering process from Site B

This process is performed by a system administrator at Site B.

Steps

- 1. Log in to Site B cluster.
- In System Manager, select Dashboard to display the cluster overview.

The dashboard shows the details for this cluster (Site B). In the MetroCluster section, Site B cluster is shown on the left.

- Click Attach Partner Cluster to start the peering process.
- 4. Enter the details of the network interfaces that allow the nodes in Site B cluster to communicate with the

nodes in Site A cluster.

- 5. Click Save and Continue.
- 6. On the **Attach Partner Cluster** window, select **I have a passphrase**, which lets you enter the passphrase that you received from the system administrator at Site A.
- 7. Select **Peer** to complete the peering process.

What's next?

After the peering process is successfully completed, you configure the clusters. See Configure an IP MetroCluster site.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.