Category	Code	Description
Understanding Benefits	Overview-EndToEndWorkflow	This code captures instances where participants valued seeing the entire MCP workflow in one place, including how the agent and MCP servers are connected and in what order data passes between them.
	DataVisibility-WhatIsShared	This code captures instances where FlowLens helped participants understand what types of data would be shared during the task.
	DataVisibility-WhereDataGoes	This code captures instances where the visual elements of FlowLens helped participants see where data would go.
	DataVisibility-ServerAccessScope	This code captures instances where FlowLens allowed participants to evaluate how much data an MCP server actually accessed.
	Information-Concise	This code captures participants' views that the amount of information in FlowLens was about right.
	Anticipation-BeforeExecution	This code captures instances where FlowLens helped participants know what the LLM would do before it actually acted.
	Anticipation-ConditionalSteps	This code captures instances where FlowLens laid out the conditional steps of a task so that participants could know in advance how it would proceed.
Understanding Boundaries	Readability-RequiresTaskUnderstanding	This code captures the view that FlowLens cannot substitute for understanding the task itself, as users first need to understand their own prompt.
	Readability-DependsOnBackground	This code captures concerns that interpreting FlowLens depends on users' technical background.
	Readability-ClutteredArrows	This code captures difficulties following the arrows in FlowLens because they appeared cluttered.
	Readability-PrefersText	This code captures a preference for textual over visual representations of the data flow.
	DecisionGuidance-ApprovalSteps	This code captures the wish for FlowLens to indicate which steps in the workflow would require user approval.
	DecisionGuidance-Recommendation	This code captures the wish for FlowLens to provide hints or suggestions that support tool-calling request decisions.

Category	Code	Description
	Customization-DetailDisplay	This code captures the wish to view data flow details directly alongside the overall diagram rather than opening them one at a time.
	Customization-Timing	This code captures suggestions that FlowLens be presented at key moments rather than all the time.
	Customization-UserExperience	This code captures suggestions to provide a detailed version of FlowLens for new users and a concise version for returning users.
	Customization-DataOnly	This code captures the wish to see only the data transferred to the AI rather than the entire data flow.
Privacy Decisions	Decision-MoreCautious	This code captures instances where FlowLens made participants more cautious with sensitive operations.
	Decision-Unchanged-PriorFamiliarity	This code captures instances where FlowLens did not change participants' decisions because they were already familiar with tool-calling requests and MCP servers.
	Decision-Unchanged-TrustInAgent	This code captures instances where FlowLens did not change participants' decisions because they already trusted the agent.
	Decision-Unchanged-AccessNecessary	This code captures instances where FlowLens did not change participants' decisions because MCP servers need access to complete tasks.
	Decision-Unchanged-ApprovalBurden	This code captures the view that approving each tool-calling request individually is cumbersome.
	Decision-Unchanged-AvoidAllowAll	This code captures instances where FlowLens did not change participants' decisions because they already avoided allowing all requests.
	MCPUse-Discouraged	This code captures instances where FlowLens discouraged participants from using MCP servers at all.
Disclosure Provider	Provider-LLM	This code captures the view that the LLM should provide FlowLens.
	Provider-MCPServer	This code captures the view that the MCP server should provide FlowLens.
	Provider-ThirdParty	This code captures the view that an independent third party not involved in the interaction should provide FlowLens.

Category	Code	Description
	Provider-Both	This code captures the view that both the LLM and the MCP server should provide FlowLens so that users can compare them.
Privacy Responsibility	Responsibility-Shared	This code captures the view that privacy protection is a shared responsibility among the parties involved.
	Responsibility-LLMPrimary	This code captures the view that the LLM bears primary responsibility for protecting user privacy.
	Doubt-LLMProtection	This code captures doubts about whether the LLM would actually protect user privacy.
	Risk-Acceptance	This code captures instances where participants expected their data might be leaked but accepted the risk.
Trust Comparison	Trust-DependsOnFamiliarity	This code captures the view that trust in MCP relative to familiar permission systems depends on how familiar the specific system is.
	Trust-DependsOnTrustworthiness	This code captures the view that trust in MCP relative to familiar permission systems depends on how trustworthy the specific system is.
	Trust-MCPRiskier	This code captures the view that granting access to an AI agent via MCP is riskier than standard app permissions.
	Trust-ZeroTrust	This code captures a zero-trust stance toward both apps and LLMs.