

# 607 SSPS

## Tubular Lock

Knob Locks



### Specifications

|                       |                                                     |
|-----------------------|-----------------------------------------------------|
| <b>Material</b>       | Stainless steel/Brass/Solid steel                   |
| <b>Cylinder</b>       | Brass cylinder                                      |
| <b>Backset</b>        | 60mm / 70mm adjustable                              |
| <b>Door thickness</b> | 35mm to 45mm adjustable                             |
| <b>Cycle life</b>     | 200,000 cycles                                      |
| <b>Chassis</b>        | Solid steel chassis and latch case, zinc plated     |
| <b>Trim</b>           | Wrought stainless steel or brass                    |
| <b>Strike</b>         | 57mm curved lip standard; 70mm available on request |
| <b>Handing</b>        | Fully reversible, left or right hand                |
| <b>Application</b>    | Residential use                                     |
| <b>Finish</b>         | Satin stainless steel (US32D)                       |
| <b>Function</b>       | Passage                                             |
| <b>Latch</b>          | Adjustable 60–70mm                                  |

### Features

- Key Features:
- Latch Bolt: 12mm (1/2”) throw, deadlocking for keyed functions
- Door Thickness: Adjustable 35–45mm (1-3/8” to 1-3/4”)
- Backset: Adjustable 60mm or 70mm (2-3/8” or 2-3/4”)
- Optional Latch: 1” round drive-in 4-way latch (upon request)
- Strike Plate: 57mm curved lip standard, 70mm optional
- Handing: Reversible for left or right-hand doors

### Finish codes

■ SS

### Confirm on order

Not stated in our published data, so confirm on the order: fixing-hole positions, order code per finish.

As published on [cantonlock.com](https://www.cantonlock.com). The order confirmation is the binding specification.