

587 PBET

Light Duty Cylindrical Lock

Knob Locks



Specifications	
Material	Stainless steel
Finish	Satin nickel, chrome, antique brass, polished brass,all available
Cylinder	Solid brass/Zinc & brass cylinder
Cycle life	200,000 cycles
Chassis	Solid steel chassis and latch case, zinc plated
Trim	Wrought stainless steel or brass
Latch	Deadlocking on keyed functions
Handing	Fully reversible, left or right hand
Application	Standard residential use
Keying	Can be keyed alike to the deadbolt series, or master keyed
Function	Entrance, keyed outside
Key options	Nickel-Plated Brass, Solid Brass, Brushed Nickel

Features

- Technical Specifications
- Latch: 12mm (1/2") throw, dead-locking for keyed functions
- Door Thickness: Adjustable 35–50mm (1-3/8" to 2")
- Backset: Standard 60mm (2-3/8"); optional 70mm (2-3/4") and 90mm (3-9/16")
- Handing: Fully reversible for left or right-hand doors
- Product Highlights
- Economical Choice – Ideal for light-duty residential applications
- Durable Use – Tested for over 200,000 life cycles

Confirm on order

Not stated in our published data, so confirm on the order: finish codes, fixing-hole positions, overall dimensions, order code per finish.