

# 5871 SSET

## Heavy Duty Cylindrical Lock

Knob Locks



### Specifications

|                    |                                                         |
|--------------------|---------------------------------------------------------|
| <b>Material</b>    | Stainless steel                                         |
| <b>Cycle life</b>  | 200,000 cycles                                          |
| <b>Chassis</b>     | Solid steel chassis and latch case, zinc plated         |
| <b>Trim</b>        | Zinc die-casting electro-plated or solid brass          |
| <b>Cylinder</b>    | 5-pin tumbler, brass plug, two nickel-plated brass keys |
| <b>Latch</b>       | Deadlocking on keyed functions                          |
| <b>Handing</b>     | Fully reversible, left or right hand                    |
| <b>Application</b> | Commercial offices, schools and heavy-duty residential  |
| <b>Keying</b>      | Can be keyed alike to deadbolts                         |
| <b>Finish</b>      | Satin stainless steel (US32D)                           |
| <b>Function</b>    | Entrance, keyed outside                                 |

### Features

- Latch Bolt: 12mm (1/2") throw with deadlocking
- Door Thickness: 35–50mm (1-3/8" to 2"), adjustable
- Backset: Standard 70mm (2-3/4"); optional 60mm or 90mm available
- Handing: Fully reversible for left or right hand doors
- Introduction
- Ideal for medium-grade commercial and heavy-duty residential applications
- Supports keyed alike function with deadbolts to enhance security
- Tested for over 200,000 life cycles

### Confirm on order

Not stated in our published data, so confirm on the order: finish codes, fixing-hole positions, overall dimensions, order code per finish.

As published on [cantonlock.com](https://www.cantonlock.com). The order confirmation is the binding specification.