

564 MB

Night Latch And Rim Lock

Night Latches & Rim Locks



SPECIFICATIONS

Installation	Surface Mounted
Application	Wooden Doors / Metal Doors / Residential Doors
Door thickness	35mm to 55mm standard; 30mm to 60mm on request
Latch extension	13mm, with inside deadlocking button
Deadbolt throw	25mm on rim deadbolt versions
Chassis	Zinc die-cast case, zinc-plated steel internal components
Strike	Angle strike standard for inward-opening doors; flat strike available
Handing	Fully reversible, left or right hand
Function	Single cylinder, double cylinder or self-locking
Feature	Anti-picking slide gate on single-cylinder deadlock
Finish	Matt black
Product Type	Anti-Theft Rim Lock / Night Latch
Material	Zinc Alloy
Latch Bolt Material	Zinc Alloy
Thumbturn Button	Brass
Lock Cylinder Housing	Aluminum
Cylinder Core	Brass

More rows on the product page.

FEATURES

- This anti-theft rim lock night latch is designed for surface-mounted door installation, providing dependable security for residential applications.
- The lock cylinder features an aluminum outer housing with a brass core, delivering consistent key rotation and stable locking performance.
- The rotating tail bar is made of iron, providing secure power transmission during locking and unlocking.
- Supplied as a complete hardware set, the lock includes an iron cylinder decorative ring, iron keys, iron decorative plate, and iron fixing screws, making installation simple and convenient.
- With its classic night latch structure and anti-theft design, this lock is widely used on wooden and metal doors in homes, apartments, and similar environments.

As published on [cantonlock.com](https://www.cantonlock.com) on 2026-09-28. The order confirmation is the binding specification.

OEM / ODM customization, surface finishes, and packaging options are available upon request.

<https://www.cantonlock.com> Canton Hyland Hardware (Group) Co., Ltd., Zhongshan, Guangdong, China

CONFIRM ON ORDER

Not stated in our published data, so confirm on the order: finish codes, order code per finish.