



# Manage Security for Azure SQL Database

Module 5



# Learning Units covered in this Module

- Lesson 1: Implement Data Encryption In Transit
- Lesson 2: Implement Transparent Data Encryption
- Lesson 3: Implement Always Encrypted
- Lesson 4: Implement Row Level Security
- Lesson 5: Implement Dynamic Data Masking

# Lesson 1: Implement Data Encryption In Transit

# Objectives


After completing this learning, you will be able to:

- Know the types of data encryption for an Azure SQL Database.
- Implementing Transport Layer Security (TLS) to protect data in transit.




# Types of data encryption

Data encryption	Encryption technology	Customer value
In transit	Transport Layer Security (TLS) from the client to the server.	Protects data between client and server against snooping and man-in-the-middle attacks.  NOTE: Azure SQL Database is phasing out Secure Sockets Layer (SSL) 3.0 and TLS 1.0 in favor of TLS 1.2.
At rest	Transparent Data Encryption (TDE) for Azure SQL Database.	Protects data on the disk. Key management is done by Azure, which makes it easier to obtain compliance.
In use (end-to-end)	Always Encrypted for client-side column encryption.	Data is protected end-to-end, but the application is aware of encrypted columns. This is used in the absence of data masking and TDE for compliance-related scenarios.



# Data encryption – In Transit



Microsoft gives customers the ability to use the Transport Layer Security (TLS) protocol to protect data when it's traveling between the cloud services and customers.

TLS provides strong authentication, message privacy, and integrity (enabling detection of message tampering, interception, and forgery)

You should only use TLS 1.2 or higher as the earlier protocols are vulnerable and have been deprecated.

Questions?



# Knowledge Check

What is the minimum version of TLS that should be used?

Name the feature to encrypt the data both at rest and motion.



## Lesson 2: Implement Transparent Data Encryption

# Objectives

After completing this learning, you will be able to:

- Know how to secure data at rest using Transparent Data Encryption.



# Understanding TDE Functionality

Data is encrypted at rest.

Encryption keys are managed by Azure.

Performs real-time I/O encryption and decryption of the data at the page level.

Each page is decrypted when it's read into memory and then encrypted before being written to disk.


TDE is enabled for all newly deployed Azure SQL Databases.

No need for application change.

Support for equality operations (including joins) on encrypted data.

Bring Your Own Key (BYOK) supported.

SQL Database



# Encryption Keys

## Service-managed transparent data encryption

- The database encryption key is protected by a built-in server certificate.
- Unique for each server.
- Primary and geo-secondary database are protected by the primary database's parent server key.
- Microsoft automatically rotates these certificates at least every 90 days.

## Bring Your Own Key

- Take control over your transparent data encryption keys and control who can access them and when.
- Azure Key Vault.
- You set the asymmetric key at the server level, and all databases under that server inherit it.
- You can control key management tasks such as key rotations and key vault permissions.

# Enable TDE Using Azure Portal

Home > Azure SQL > jdsqcentral | SQL databases > SalesDB (jdsqcentral/SalesDB)

## SalesDB (jdsqcentral/SalesDB) | Data Encryption

SQL database

Search Save Discard Feedback

- Overview
- Activity log
- Tags
- Diagnose and solve problems
- Query editor (preview)
- Resource visualizer
- Settings
- Data management
- Integrations
- Power Platform
- Security
  - Auditing
  - Ledger
  - Data Discovery & Classification
  - Dynamic Data Masking
  - Microsoft Defender for Cloud
  - Identity
  - Data Encryption**

### Transparent data encryption

Always encrypted

Transparent data encryption encrypts your databases, backups, and logs at rest without any changes to your application. To enable encryption, go to each database. [Learn more](#)

**Data encryption** **ON** OFF

Encryption status ✓ Encrypted

Once database level customer-managed key is selected, switching to server level encryption key is only possible if the server is configured with service managed key.

Transparent data encryption ⓘ  
☒ Server level encryption key  
☐ Database level customer-managed key (CMK)

# TDE with customer-managed key (BYOK)

You are responsible for and in a full control of a key lifecycle management (key creation, upload, rotation, deletion), key usage permissions, and auditing of operations on keys.

The key used for encryption of the Database Encryption Key (DEK), called TDE protector, is a customer-managed asymmetric key stored in a customer-owned and customer-managed Azure Key Vault (AKV), a cloud-based external key management system.

TDE protector is set at the logical server level and is inherited by all encrypted databases associated with that server.



# Demonstration

## Implement TDE using Azure Portal and T-SQL Code

- Enable TDE With Bring Your Own Key using Azure Portal.



Questions?





# Knowledge Check

Does TDE encrypt the data in motion?

What kind of application changes are required to use TDE?

Which 2 types of Encryption Keys can be used for TDE?

# Lesson 3: Implement Always Encrypted

# Objectives


After completing this learning, you will be able to:

- Know how to secure data at rest and in motion using Always encrypted.




# Always Encrypted

Always Encrypted allows clients to encrypt sensitive data inside client applications and never reveal the encryption keys to SQL Database.



As a result, Always Encrypted provides a separation between those who own the data (and can view it) and those who manage the data (but should have no access).

# Understanding Always Encrypted Functionality




## Capability

- Transparent client-side encryption, while SQL Server executes T-SQL queries on encrypted data.

## Benefits

- Sensitive data remains encrypted and query-able at all times.
- Unauthorized users never have access to data or keys.
- No changes to applications are necessary.

# Understanding Always Encrypted Functionality (Contd.)



# Encryption Methodologies

Two types of encryption  
are available:



```
graph TD; A[Two types of encryption are available:] --> B[Randomized encryption]; A --> C[Deterministic encryption];
```

Randomized encryption  
uses a method that  
encrypts data in less  
predictable manner.

Deterministic encryption  
uses method that always  
generates the same  
ciphertext


## Randomized encryption

- `Encrypt('123-45-6789') = 0x17cfd50a`
- Repeat: `Encrypt('123-45-6789') = 0x9b1fcf32`
- Allows for transparent retrieval of encrypted data **but no operations**.
- More secure

## Deterministic encryption


- `Encrypt('123-45-6789') = 0x85a55d3f`
- Repeat: `Encrypt('123-45-6789') = 0x85a55d3f`
- Allows for transparent retrieval of encrypted data **and quality**.
- **Comparison** (for example, in WHERE clauses and joins, distinct, group by).

# Enabling Always Encrypted on Azure SQL DB





# Enabling Always Encrypted on Azure SQL DB (contd.)



Same local stored certificate.

"Column Encryption Setting=Enabled;"  
in connection string.

Make sure you use the correct driver.

# Demonstration

## Enable Always Encrypted

- Enable Always Encrypted
- Select data through Application.



# Implement Always Encrypted

- **Exercise 1:** Implement Always Encrypted on Azure SQL Database.
- **Exercise 2:** Use the .Net Client App to Test Always Encrypted.



Questions?



# Knowledge Check

Can a DBA see Always Encrypted data?

What are the 4 steps that you need to perform to enable Always Encrypted?

## Lesson 4: Implement Row Level Security

# Objectives

After completing this learning, you will be able to:

- Know how to control access to the data using Row Level Security (RLS).



# Row Level Security (RLS)

Row-Level Security enables customers to control access to rows in a database table based on the characteristics of the user executing a query.




# Understanding RLS Functionality


Fine-grained access control over specific rows in a database table.

Helps to prevent unauthorized access when multiple users share the same tables, or to implement connection filtering in multitenant applications.

Enforcement logic inside the database and schema is bound to the table.



# RLS Implementation details



```
CREATE SECURITY POLICY mySecurityPolicy  
ADD FILTER PREDICATE dbo.fn_securitypredicate(wing, startTime, endTime)  
ON dbo.patients
```

# Demonstration

## Implement RLS using T-SQL Code

- Enable RLS using T-SQL.



# Implement Row Level Security

- **Exercise 1:** Implement Row Level Security on Azure SQL Database.



Questions?



# Knowledge Check

What is the purpose of the predicate function?


Why do we need row level security (RLS)?

# Lesson 5: Implement Dynamic Data Masking

# Objectives

After completing this learning, you will be able to:

- Know how to mask the critical data using Dynamic Data Masking.







# Dynamic Data Masking

Dynamic Data Masking is a policy-based security feature that helps to limit the exposure of data in a database by returning masked data to non-privileged users who run queries over designated database fields.

# Understanding Dynamic Data Masking Functionality




# Enable Dynamic Data Masking on Azure SQL DB

Security officer defines dynamic data masking policy in T-SQL over sensitive data in the Employee table.

The app user selects from the Employee table.

The dynamic data masking policy obfuscates the sensitive data in the query results.



Business app



```
ALTER TABLE dbo.Employee
ALTER COLUMN [FirstName] ADD MASKED WITH (FUNCTION = 'partial(1,
"xxx", 2)')

ALTER TABLE dbo.Employee
ALTER COLUMN [EMAIL] ADD MASKED WITH (FUNCTION = 'email()')

ALTER TABLE dbo.Employee
ALTER COLUMN [Salary] ADD MASKED WITH (FUNCTION =
'random(2000,20000)')

GRANT UNMASK to admin1
```



Security officer

```
SELECT EmployeeID,
FirstName, MiddleInitial,
LastName, EMAIL, Salary
FROM [Employee]
```


Other Login

	EmployeeID	FirstName	MiddleInitial	LastName	EMAIL	Salary
1	1	Lydia	L	Kelley	Lydia.Kelley@contoso.com	57353
2	2	Julia	T	James	Julia.James@contoso.com	138286
3	3	Chester	D	Dixon	Chester.Dixon@contoso.com	117503
4	4	Darla	D	Faulkner	Darla.Faulkner@contoso.com	74581
5	5	Danny	S	Velasquez	ngyacn17@contoso.com	94116


Admin Login

	EmployeeID	FirstName	MiddleInitial	LastName	EMAIL	Salary
1	1	Lxxxia	L	Kelley	LXXX@XXXX.com	19530
2	2	Jxxxia	T	James	JXXX@XXXX.com	7376
3	3	Cxxxer	D	Dixon	CXXX@XXXX.com	17612
4	4	Dxxxla	D	Faulkner	DXXX@XXXX.com	7050
5	5	Dxxxny	S	Velasquez	nXXX@XXXX.com	12530

# Dynamic Data Masking Functions



DEFAULT



RANDOM



CUSTOM



EMAIL



DATETIME  
(2022)



CREDIT CARD  
(AZURE)

# Demonstration

## Implement Dynamic Data masking T-SQL Code

- Enable Dynamic Data masking using T-SQL.



Questions?



# Knowledge Check

What's the purpose of Dynamic Data Masking?

List two different masking rules in Dynamic Data Masking?

## Module Summary

Implement Data Encryption in Transit

Implement Transparent Data Encryption

Implement Always Encrypted

Implement Row Level Security

Implement Dynamic Data Masking



