

```

    uData.id = sData.data1;
    return (0);
}

```

5.1.1.9 准则 R-1-1-9

结构体定义中禁止含有无名结构体。

违背示例：

```

struct Sdata
{
    unsigned char id;
    struct Scoor
    {
        unsigned char xs;
        unsigned char ys;
        unsigned char zs;
    };           //违背 1
};
int main(void)
{
    struct Sdata data;
    data.id = 1;
    return (0);
}

```

遵循示例：

```

struct Sdata
{
    unsigned char id;
    struct Scoor
    {
        unsigned char xs;
        unsigned char ys;
        unsigned char zs;
    } coor;       //遵循 1
};
int main(void)
{
    struct Sdata data;
    data.id = 1;
    return (0);
}

```

5.1.1.10 准则 R-1-1-10

位定义的有符号整型变量位长必须大于 1。

违背示例:

```
typedef struct
{
    signed int si01 : 1;    //违背 1
    signed int si02 : 2;
    unsigned int serv : 29;
} sData;
int main(void)
{
    sData my_data;
    my_data.si01 = -1;
    my_data.si02 = -1;
    return (0);
}
```

遵循示例:

```
typedef struct
{
    signed int si01 : 2;    //遵循 1
    signed int si02 : 2;
    unsigned int serv : 28;
} sData;
int main(void)
{
    sData my_data;
    my_data.si01 = -1;
    my_data.si02 = -1;
    return (0);
}
```

5.1.1.11 准则 R-1-1-11

位定义的整型变量必须明确定义是有符号还是无符号的。

违背示例:

```
typedef struct
{
    short d01 : 2;        //违背 1
    short d02 : 2;        //违背 2
    short res : 12;       //违背 3
} sData;
int main(void)
{
    sData my_data;
    my_data.d01 = 1;
```

```

    my_data.d02 = 1;
    my_data.res = 0;
    return (0);
}

```

遵循示例:

```

typedef struct
{
    signed short  d01 : 2;      //遵循 1
    unsigned short d02 : 2;     //遵循 2
    unsigned short res : 12;    //遵循 3
} sData;
int main(void)
{
    sData my_data;
    my_data.d01 = 1;
    my_data.d02 = 1;
    my_data.res = 0;
    return (0);
}

```

5.1.1.12 准则 R-1-1-12

位定义的变量必须是同长度的类型且定义位禁止跨越类型的长度。

违背示例:

```

typedef struct
{
    unsigned char  d01 : 2;
    unsigned char  d02 : 2;
    unsigned char  d03 : 2;
    unsigned short d04 : 2;    //违背 1
} stData1;
typedef struct
{
    unsigned short d01 : 2;
    unsigned short d02 : 2;
    unsigned short d03 : 2;
    unsigned short d04 : 12;   //违背 2
    unsigned short d05 : 2;
    unsigned short d06 : 2;
    unsigned short d07 : 2;
    unsigned short d08 : 8;
} stData2;
int main(void)

```