



Administration Guide

SQream Technologies

Version 2019.2

Copyright © 2010-2019. All rights reserved.

This document is provided for information purposes only and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchant- ability or fitness for a particular purpose.

We specifically disclaim any liability with respect to this document and no contractual obligations are formed either directly or indirectly by this document.

This document may not be reproduced in any form, for any purpose, without our prior written permission.

Table of Contents

Table of Contents	3
SQream DB Administrator Guide	5
Overview	5
Administration Guide	6
Getting Started	7
Understanding the SQream DB environment	7
Setting up SQream DB	8
Create the cluster	9
Configure the instances	9
Configuring instances parameters	10
Starting and Stopping the SQream DB daemons	11
SQream based on Docker	12
SQream based on RPM	12
Connect to the SQream DB server with ClientCmd	14
Using SSL Server Authentication with SQream	14
Enabling SSL server authentication within SQream Instance:	14
Configure SSL Authentication for JDBC/ODBC drivers	15
Adding SSL to JDBC	15
Adding SSL to ODBC	15
Highly available installations	15
Operations	16
Upgrading a version	16
Key administration concepts	16
Monitoring the system	16
From the OS	16
From each node	16
See connections to the server	16
Show server / cluster status	17
By running a query	18

Stopping existing statements	18
Logs	18
Log file format:	19
Log rotation policy	20
Log Levels	21
Support Utilities	21
Report Collection	21
Export Reproducible Sample Data	22

SQream DB Administrator Guide

Version 2019.2

Overview

This guide is intended for SQream DB administrators.

The guide will go through the DBA main tasks, as well as describing some of the best practices in SQream DB.

This guide is a complementary guide to the SQL Reference.

For further support please contact support@sqreamtech.com or your account manager.

Administration Guide

This document is mostly a conceptual overview and recommendations on best practices regarding SQream internal behavior. For SQL syntax and supported features, please refer to the [SQL Reference Guide](#).

NOTE:

All keywords in are **case insensitive**.


Getting Started

Understanding the SQream DB environment

The SQream environment is usually made up of two folders - the installation directory and the storage cluster.

The installation directory

This folder contains the SQream DB binary applications.




The main applications found in the binary directory are:

Executable Name	Description
screamd	The screamd server daemon
ClientCmd	Command line client
upgrade_storage	Metadata storage upgrader to be used between versions
ScreamStorage	Storage utility to create new clusters and restore access
metadata_server	Metadata server for clustered installations
server_picker	Load balancer for clustered installations

The storage cluster root

This directory contains the entire database storage.



Directory	Description
databases	The files containing all databases, tables, columns, chunks, etc.
metadata	Internal metadata structures for accessing data from disk
temp	Temporary pools
logs	The logs folder contains subfolders per SQream instance with folder name = [IP_port]. One folder per running SQream instance.
127.0.0.1_5000 [IP_port]	Contains all logs files of a specific SQream instance


Setting up SQream DB

If you would like to deploy SQream DB on AWS or Azure please contact SQream directly at info@sqream.com.

Make sure that you are running on a 64-bit Linux operating system, and have an Nvidia GPU installed.

See the Hardware Requirements page to verify your system meets the minimum

requirements for running SQream DB.



Create the cluster

1. Enter the `sqream` directory and create a storage cluster
2. `./bin/SqreamStorage -C -r <full path to new cluster>`

Example: Create storage cluster

If your main storage is on `/mnt/storage`, you can run
`./bin/SqreamStorage -C -r /mnt/storage/sqream_storage`

Configure the instances

Each SQream DB daemon must run against a configuration file.

Below is a sample **minimal** configuration file. It is recommended that it be placed in `/etc/sqream/sqream_config.json`. This file will start the server on port **5000**, against GPU #0.

Example minimal configuration JSON

```

{
  "compileFlags": {
  },
  "runtimeFlags": {
  },
  "runtimeGlobalFlags": {
  }
}
  
```

```

    },
    "server": {
      "licensePath" : "/etc/sqream/license.enc",
      "port": 5000,
      "cluster": "/mnt/storage/sqream_storage",
      "gpu": 0,
      "ssl_port": 5100
    }
  }
}

```

NOTE:

- JSON files can not contain any comments
- When altering the JSON file, pay close attention to the field-separating commas at the end of the lines.

Permanent instance options may be placed in this file, based on consultation with SQream support or through the configuration utility.

Configuring instances parameters

Table 20. Common parameters setting

Flag Name	Description	Default Value	Range of Values	Remark
spoolmemorygb	Select what size spool SQream DB can use for writing intermediate results to RAM, in GB	128gb	1-machine ram size	Should consider total ram size and number of SQream instances
insertParsers	Set the number of parsing threads to be launched for each file, during the bulk load process	4	1-32	Should consider total ram size and number of SQream instances
insertCompressors	Set the number of compression threads to be	4	1-32	Should consider total ram

Flag Name	Description	Default Value	Range of Values	Remark
	launched for each file, during the bulk load process			size and number of SQream instances
statementLockTimeout	Set the number of seconds SQream will wait for a lock before returning an error	3	1-no limit	
showFullExceptionInfo	Show complete error message	FALSE	TRUE/FALSE	Enabling this setting will often show more detailed error message
initialSubscribedServices	List of services the instance will be subscribed to	sqream	list of strings	Example: "sqream,etl_service,query_service"
useLogMaxFileSize	Defines whether SQream logs should be cycle every logMaxFileSize MB size	TRUE	TRUE/FALSE	
logMaxFileSizeMB	Set the size of SQream logs cycle	20	>0	Set in MB

Starting and Stopping the SQream DB daemons

The procedure for starting and stopping the SQream DB daemons varies depending on your installation type:

- SQream based on Docker
- SQream based on RPM

SQream based on Docker

Use the start and stop options of the sqreamd command as described in the sqream-console commands in **Start the SQream Console**.

SQream based on RPM

A SQream RPM installation uses the Monit service to control the SQream services.

To start the SQream demons (Metadata, Server Picker and SQreamD):

```
$ sudo systemctl start monit
```

To check the SQream demons (Metadata, Server Picker and SQreamD):

- Option 1:

```
$ sqream_status
```

Expected output:

```
SQreamDB monit.service: ACTIVE pid=6406 [ OK ]
SQreamDB metadataserver.service: ACTIVE pid=6427 [ OK ]
SQreamDB serverpicker.service: ACTIVE pid=6579 [ OK ]
SQreamDB sqreaml.service: ACTIVE pid= 7440 [ OK ]
```

- Option 2:

```
$ ps axuwww | grep -v 'grep\|tail\|monitor' | grep -i
'sqreamd\|metadata_server\|server_pick\|monit'
```

Expected output:

```
root      7690  0.0  0.0 191916  2464 ?        Ss   15:27   0:00
/bin/su - sqream -c /bin/nohup /usr/local/sqream/bin/metadata_
server &>> /var/log/sqream/metadataserver.log
sqream    7693  0.0  0.0 115304  1680 ?        Ss   15:27   0:00 -
bash -c /bin/nohup /usr/local/sqream/bin/metadata_server &>>
/var/log/sqream/metadataserver.log
sqream    7708  0.2  1.8 1110888704 183644 ?      Sl   15:27   0:02
/usr/local/sqream/bin/metadata_server
root      8105  0.0  0.0 191916  2456 ?        Ss   15:27   0:00
/bin/su - sqream -c exec /usr/local/sqream/bin/server_picker
127.0.0.1 3105 &>> /var/log/sqream/serverpicker.log
sqream    8116  0.2  1.5 34887308 156592 ?      Ssl  15:27   0:02
/usr/local/sqream/bin/server_picker 127.0.0.1 3105
root      8450  0.2  0.0 131124  3452 ?        Ssl  15:34   0:01
/usr/bin/monit -I
root      8453  0.0  0.0 191916  2460 ?        Ss   15:34   0:00
/bin/su - sqream -c exec /usr/local/sqream/bin/sqreamd -config
/etc/sqream/sqreaml\_config.json &>> /var/log/sqream/sqreaml.log
```

```
sqream      8456  0.6  5.5 1111154756 542644 ?    Ssl  15:34    0:04
/usr/local/sqream/bin/sqreamd -config /etc/sqream/sqream1_
config.json
```

To stop all SQream services:

```
$ sudo /usr/local/sqream/config/sqream-stop.sh
```

Expected output:

```
==>Stopping SQreamDB Services
UNIT                                LOAD    ACTIVE SUB    DESCRIPTION
• metadataserver.service loaded Metadata Server For SQreamDB
• serverpicker.service   loaded Server Picker - Load Balancer For
SQreamDB
• sqream1.service        loaded SQream SQL Server

LOAD    = Reflects whether the unit definition was properly loaded.
ACTIVE  = The high-level unit activation state, i.e. generalization of
SUB.
SUB      = The low-level unit activation state, values depend on unit
type.
3 loaded units listed. Pass --all to see loaded but inactive units, too.
To show all installed unit files use 'systemctl list-unit-files'.
==>SQreamDB Services have been stopped
```

To stop a specific SQream service:

1. Stop the Monit service:

```
$ sudo systemctl stop monit
```

2. Stop the specific SQream service, for example stopping sqream1:

- Option 1:

```
$ sudo systemctl stop sqream1
```

- Option 2:

```
$ pkill -9 sqreamd
```

To restart a service that was stopped:

- Option 1:

Start the Monit service and monit will start all stopped services:

```
$ sudo systemctl start monit
```

- Option 2:

Start the stopped service manually:

```
$ sudo systemctl start sqream1.service
```

Connect to the SQream DB server with ClientCmd

To connect to the database server, you may use the ClientCmd command line interface by running

ClientCmd command line arguments

```
./bin/ClientCmd --user=<username> --password=<password> --  
database=<database name> --host=<host> --port=<port> --  
service=<service_name>
```

Connect to the `master` database:

Connecting to `master` on a local host running SQream DB on port 5000 via service 'etl_service'

```
./bin/ClientCmd --user=sqream --password=sqream --database=master -  
-host=127.0.0.1 --port=5000 --service=etl_service
```

Using SSL Server Authentication with SQream

From version 2.1, SQream DB supports secure sockets layer (SSL) encryption and authentication for connections to its cluster via JDBC and ODBC drivers.

To use this option, the server must first be set-up to accept SSL connections.

Enabling SSL server authentication within SQream Instance:

Configure the SERVER flag `ssl_port` in the SQream instance configuration file to the needed port number.

For Example:

```
{  
  "server": {  
    "port": 5001,  
    "ssl_port": 5100,  
    "cluster": "/path/sqream_cluster",  
    "gpu": 0,  
    "licensePath": "/path/license.enc"  
  }  
}
```

NOTE:

Restart the SQream DB daemons after making this configuration change

Configure SSL Authentication for JDBC/ODBC drivers

Adding SSL to JDBC

1. Add ssl=true in the connection string
2. Change the port to the SSL port

NOTE:

When connecting via load balancer, the default endpoint for SSH is port 3109

Example for direct connection

```
jdbc:Sqream://hostname:5100/master;user=sqream;password=mypassword;
ssl=true;
```

Example for connection to load balancer

```
jdbc:Sqream://hostname:3109/master;user=sqream;password=mypassword;
service=sqream;cluster=true;ssl=true;
```

Adding SSL to ODBC

In Windows, make sure the SSL checkbox is selected in the DSN settings.

In Linux, add Ssl=true to the connection string

Linux ODBC connection string sample

```
Driver=
{libODBCDrv.so}:Server=hostname:Port=5100:Database=master:User=sqre
am:Password=mypassword:Ssl=true:Service=sqream
```

Highly available installations

Contact your SQream representative for further information about installing our highly available solutions.

Operations

Upgrading a version

Here are the necessary steps that ensure a smooth upgrade of your SQream DB version

1. Stop SQream instances on all servers
2. On each node that SQream is installed, unpack the new tarball alongside the old SQream DB directory.
For example:

```
$ cd /home/sqream
$ mv sqream sqream-old
$ tar xf sqream-<version>.tar.gz
```

3. Repeat the above step for each node that the SQream DB executables exist
4. It may be necessary to run the metadata upgrade utility.
(This may take a few moments)

```
$ cd sqream/bin
$ ./upgrade_storage <path to sqream storage cluster>
```

5. Restart the services

Key administration concepts

See Concepts above

Monitoring the system

Because SQream DB can be run in a distributed setting, all nodes should be monitored to ensure smooth operation. It is possible to monitor SQream DB with third party tools like Zabbix, Nagios and others, but also through the OS and SQream DB directly.

From the OS

See Identifying which SQream daemons are running

From each node

See connections to the server

You can monitor existing connections to the database by using the `show_connections()` utility function:


```
SELECT show_connections();
```

Table 21. Sample result from `show_connections()`

ip	conn_id	conn_start_time	stmt_id	stmt_start_time	stmt
192.168.0.93	19	2017-06-22 18:56:54	14	2017-06-22 18:56:54	select show_connections()
192.168.0.93	17	2017-06-22 18:56:48	-1	2017-06-22 18:56:48	

Show server / cluster status

The `show_server_status()` utility function can be used to see which statements are running across the cluster, across all databases.

NOTE:

If no queries are running, this query will return 0 rows in the result set.

```
SELECT show_server_status();
```

Table 22. Sample result from `show_server_status()`

service_id	connection_id	server_ip	server_port	database_name	user_name	client_ip	statement_id	statement	statement_start_time	statement_status	statement_status_start
sqream	32	192.168.0.93	5000	faa	sqream	192.168.0.1	25	SELECT Year	Carrier	destCityName	COUNT (DISTINCT originCityName) from ontime JOIN I_airport_i

Possible statement status values

Status	Description
Executing	The statement is in execution, awaiting results
Preparing	The statement is compiling, and is awaiting execution
Waiting	The statement is waiting in the queue for execution

The DBA can use the show server status output as a baseline for identifying locks and if needed to stop running statements (based on the **server ip : server port** and **statement_id** columns).

By running a query

Running a query, even the most basic one, should give you an indication if a server is up. If you immediately get "Connection refused" or similar, the server is down.

```
SELECT 1;
```

Stopping existing statements

The **stop_statement()** utility function can be used to cancel or stop a running statement before it finishes.

Usage

- Identify the running statement ID and server IP and port (see **show server status** or **show_connections** above)
- From the same server/port combination - run the stop_statement command:

```
SELECT stop_statement(42);
```

Logs

Each SQream instance generates its own set of log files based on the log rotation policy (see **Log rotation policy**). The files will be located in a dedicated folder (folder name contains IP and port).

For example: `/home/sqream/sqream_storage/sqreamdb/logs/127.0.0.1_5000`.

TIP:

SQream recommends storing the log files in the shared storage so they can be all

analyzed in a single tool (e.g: SQream external table, Kibana etc.).

To generate an external table over the log files, use the command:

```
create or replace external table t
( start_message varchar(4),
  row_id bigint,
  timestamp datetime,
  message_level nvarchar(6),
  thread_id nvarchar(40),
  ip nvarchar(15),
  port int,
  connection_id int,
  db_name nvarchar(128),
  user_name nvarchar(128),
  statement_id int,

  service_name nvarchar(128),
  message_type_id int,
  message nvarchar(10000),
  end_message varchar(5))
using format csv with path
'/home/sqream/sqream_storage/sqreamdb/logs/*.log' field delimiter '|');
```

Log file format:

Delimited text format with the following column list:

- Row Id
- Timestamp
- Message Level
- Thread id
- IP
- Port
- Connection Id
- DB name
- User Id
- Statement Id
- Service name
- Message type id
- Message

Message type/contents:

Message Type Code	Message Type	Message Content	Log level
1	Statement started	Statement	Info
2	Statement	Statement	Info

Message Type Code	Message Type	Message Content	Log level
	reconstruct		
4	Statement execution	"Executing"	Info
10	Statement ended	"Success" / "Failed"	Info
20	Compilation error	Error text	Info
21	Execution error	Error text	Info
30	Size	#MB	Info
31	Result Set Rows	#records	Info
32	Processed Rows	#records	Info
100	Session started	Client IP address	Info
101	Login	"Success" / "Failed"	Info
110	Session ended	"Session ended"	Info
200	Node info	Node info lines	Info
500	Exception	Exception data	Error
1000	Server startup	"Server startup"	System
1002	Metadata	Metadata server location	System
1003	Configuration	Configuration flags	System
1004	STORAGE VERSION	storage version number	System
1010	Server Error	Error message	fatal
1090	Set config	Successful set config <flag_name> to value: <value>	info
1100	Server shutdown	Server shutdown	System

Log rotation policy

Parameter	Description	Possible Values	Default Value	Comment
useLogMaxFileSize	Apply rotation based on log file size limit	TRUE / FALSE	FALSE	When set to 'TRUE' logRotateSizeMB configuration parameter is enabled.
logMaxFileSizeMB	Log file size in MB.	Integer between 1-1024	20	
logFileRotateTimeFrequency	Frequency of log rotation	Daily Weekly Monthly Never	Never	Not case sensitive

Log Levels

Parameter	Description	Possible Values	Default Value
logClientLevel	Log level	0 SYSTEM 1 FATAL 2 ERROR 3 WARNING 4 INFO	4 (INFO)
nodeInfoLoggingSec	Theshold for writing from execution log to the instance log	Number to represent seconds	60

Support Utilities

Report Collection

This support utility is used to collect logs and/or the leveledb at a client's site. The generated tar file can then be sent to the SQream support team for further investigation.

- Output file format: report_[date]_[time].tar

Can run as a utility function or executable, allowing to collect information also if the SQream server is not running. Supported collection modes:

- log = only log files are collected
- db = only leveledb
- db_and_log = both log files and leveledb are collected

Syntax and example when running as a utility function:

```
SELECT report_collection('</pathToOutputFolder>', '<mode>');

SELECT report_collection('/home/sqream/log_collection','log'); )
```

Syntax and example for executable. The executable works only when no SQream instance is running:

```
./bin/report_collection <pathToSqreamDb> </pathToOutputFolder>
<mode>./bin/report_collection /home/sqream/sqream_storage/
/home/sqream/log_collection log
```

Export Reproducible Sample Data

This support utility is used to collect data in order to reproduce a problematic query in a support lab (not only onsite at customer's site). Typically used for query issues that are data related. It runs a query, collects the data and stores the data in a small SQream DB (compressed into a single tar file). This file together with the query can be used in a remote system (support lab) to recreate and investigate the issue.

The output folder contains both the final tar file and data before its compression. It is sufficient to send the tar file. Works as utility function. No executable.

Syntax and example:

```
select export_reproducible_sample('</pathToOutputFolder>', 'sql
query1', 'sql query 2', ..);

select export_reproducible_sample('home/sqream/data_collection',
'select * from t');
```