



JAW TYPE BUSHED COUPLINGS

	COUPLING SIZE CODE	Material	BORE		Joseph Dia	Over all	BOSS DIA	
			MIN.	MAX.	Out Side DIA	Lenght	BUSS DIA	
	AJ 030	AL.	3	10	16	19	16	
	AJ 050	AL.	6	16	28	46	28	2
	AJ 070	AL.	9	20	35	51	35	Available if Required
	AJ 075	AL.	6	22	44.5	55	44.5	. Sed
	AJ 095	AL.	12	28	54	63	54	=
	AJ 095	C.I	12	28	54	63	49	ple
	AJ 099	AL.	12	30	65	72	51	aila
	AJ 099	C.I	12	30	65	72	51	A
	AJ 100	AL.	12	35	. 65	88	65	on Request. Rubber Spider
c	AJ 100	C.I	12	35	65	88	57	est
	AJ 110	C.I	15	42	85	108	76	Price on Request. Spare Rubber Spic
	AJ 150	C.I	15	48	96	115	80	a Adu
	AJ 190	C.I	20	55	115	133	102	9 G
	AJ 225	C.I	20	60	127	154	108	Price o
	AJ 226	C.I	25	70	137	178	119	10000 10000
	AJ 276	C.I	25	75	157	200	127	ρ g
	AJ 280	C.I	30	80	192	200	140	
	AJ 295	C.I	30	95	237	238	162	
	AJ2955	C.I	30	105	237	264	180	

N. B.: All dimensions are in mm.

COUPLING	Rated Torque in K.G. Cms	HORSE POWER CAPACITY AT VARYING SPEEDS (R. P. M.)							
NO.		100	500	750	1000	1500	3000	3600	
AJ 035	4	0.0056	0.028	0.042	0.056	0.084	0.17	0.2	
AJ 050	29	0.04	0.2	0.3	0.4	0.6	1.2	1.44	
AJ 070	43	0.06	0.3	0.45	0.6	0.9	1.8	2.16	
AJ 075	87	0.12	0.6	0.9	1.2	1.8	3.6	4.32	
AJ 095	202	0.28	1.4	2.1	2.8	4.2	8.4	10.08	
AJ 099	305	0.42	2.1	3.15	4.2	6.3	12.6	15.1	
AJ 100	435	0.6	3	4.5	6	9	18	21.6	
AJ 110	797	1.1	5.5	8.25	11	16.5	33	39.6	
AJ 150	1232	1.7	8.5	12.75	17	25.5	51	61.2	
AJ 190	1594	2.2	11	16.5	22	33	66	79.2	
AJ 225	2392	3.3	16.5	24.75	33	49.5	99	118.8	

COUPLING FOR BETTER PERFORMANCE - Used in Chemical, Textile, Fertilisers and Other Process Industries and ready available RRL / RRS / SW / C Type Couplings & Spiders.



42/44, BHAJIPALA STREET, MUMBAI-400 003.

Tel.: (022) 23424336 / 2344 1194 Fax: (022) 2344 7116

E-mail : albrotradingco@mtnl.net.in Website : www.albro-india.com

