SAVEETHA
INSTITUTE OF MEDICAL AND TECHNICAL SCIENCES
(Declared as Deemed to be University under Section 3 of UGC Act 1956)

ASSIGNMENT 1

QUESTIONS

CO1: Apply classical encryption techniques using symmetric and asymmetric ciphers to encrypt and decrypt data for the ensuring data security.

Assignment Title: Evaluate, Design and Defend a Secure Patient-Record Exchange Strategy for a Multi-Hospital Healthcare Network (Total Marks: 50)

Scenario — Confidential Patient Record Exchange

A regional healthcare network links one central hospital with 25 satellite clinics. Clinics send patient records, diagnostic reports, prescriptions and billing data to the central hospital over a public network and receive specialist opinions in return. Personnel hold different clearance levels: Medical Director (Top Secret), Specialist Doctors (Secret), Nurses and Lab Staff (Confidential), Billing and Front-Desk Staff (Restricted), Patients (Public).

The system must:

- Keep diagnoses, especially for sensitive conditions, confidential.
- Detect tampering with prescriptions, dosage and lab values.
- Prevent staff from reading or writing records beyond their clearance.
- Work in rural clinics where staff have limited technical training and hardware is basic.

You must evaluate, design and defend a protection strategy built only from classical (pre-modern) techniques and access-control reasoning

covered in CO1. You are expected to judge how strong each technique actually is, not just describe it.

Design Challenge : An insider at a satellite clinic has been copying ciphertexts for months. Hundreds of messages under the same key are now exposed, and many begin with predictable text (e.g., "PATIENT ID", "DIAGNOSIS:", "PRESCRIPTION:"). The network also wants to embed a short report inside medical scan images sent between

hospitals. Re-evaluate your design.

- Encrypt clinical notes (200 to 10,000 characters) using Caesar, monoalphabetic, Vigenère and columnar transposition, and derive each key space. Break at least three schemes by frequency analysis, Kasiski or index of coincidence, and rank the schemes by resistance.
- Extend the alphabet to digits and symbols (mod 36) and encrypt IDs and dosages such as PT-20481, AMOX 500MG using a Hill cipher on 3-character blocks. Prove the key's invertibility, compute one inverse, and recover the key by a known-plaintext attack.
- Apply columnar transposition to a lab table of 20+ rows and test whether a changed cell or a swapped row is detected. Design a classical checksum and show where an attacker defeats it.
- Encrypt a 256×256 or larger medical image with two classical methods (intensity shift mod 256 and pixel permutation) and verify decryption. Compare histograms and entropy, and explain which method leaks the image's structure.
- Hide a short report in an image by LSB embedding and in a text circular by a text method, then extract it. Measure PSNR, capacity and chi-square detectability, and test survival under JPEG compression.
- Decide 12+ access requests using Bell-LaPadula with compartments, including declassification and break-glass cases. Rank six attacks by likelihood × impact and recommend

a final design, stating which security goals classical techniques cannot meet.

TASK 1 – Evaluate Threats, Attacks and Risks 4 Marks

Identify at least six security attacks relevant to the healthcare scenario.

- Classify each as passive or active (eavesdropping, traffic analysis, modification of prescriptions, masquerade as a doctor, replay of old orders, denial of service on the records system).
- Distinguish clearly between threat, vulnerability, attack and risk, with examples from this scenario.
- Rank the attacks by risk using a justified likelihood × impact rating. Consider patient-safety impact, not just privacy.
- Defend your ranking: which attack would you address first, and why?

Evidence Expected: A risk table with reasoned ratings and a justification of the priority order.

TASK 2 – Map and Judge Security Goals 3 Marks

For each system function (record upload, prescription transmission, specialist consultation), decide which goals matter most: confidentiality integrity availability authentication non-repudiation

- Judge which goals classical ciphers can and cannot deliver.
- Justify why a correctly decrypted message does not prove it came from the right doctor, or that its dosage was not altered.

Evidence Expected: A goal-to-function analysis with an evaluation of the gaps classical techniques leave.

TASK 3 – Apply and Critique the Bell-LaPadula Model 5 Marks

- Define the security levels and subject/object assignments for the network.
- Apply the simple security property (no read up) and the *-property (no write down) to at least five

access requests, including two that must be denied. Show the reasoning for each.

- Evaluate the model critically in a medical setting: what happens in an emergency when a nurse needs a Secret-level allergy record? How does the model handle a doctor who must write a note to a lower-level billing file? Discuss tranquility and trusted subjects.
- Judge the model's limitations (no integrity guarantees, covert channels, rigidity in emergencies) and argue whether Bell-LaPadula alone suits healthcare.

Evidence Expected: Worked access decisions, a justified critique, and a clear verdict on the model's suitability.

TASK 4 – Design the Cryptographic Strategies 4 Marks

Select at least three meaningfully different classical schemes from: Caesar, monoalphabetic substitution, Vigenère (polyalphabetic), Hill cipher, a transposition cipher. For each, provide:

- The encryption and decryption algorithm (pseudocode or formula) and the key definition.

- A worked example on a 20+ character message from the scenario.
- A justification for including it in your comparison.

Evidence Expected: Three distinct schemes with algorithms, worked examples and justified selection.

TASK 5 – Mathematical Analysis of the Schemes 5 Marks

- Derive the key-space size of each scheme (e.g., 25, 26!, 26^m, number of invertible n×n matrices mod 26, n! permutations).
- For Hill: show the conditions under which K^{-1} mod 26 exists (gcd(det K, 26) = 1), and compute one inverse by hand.
- Express each encryption as a modular function (e.g., C = (aP + b) mod 26 for an affine variant, C = KP mod 26 for Hill).
- Judge whether a large key space guarantees strength. Support your answer with the monoalphabetic example.

Evidence Expected: Correct derivations with a reasoned judgment on key space versus real security.

TASK 6 – Evaluate Cryptanalytic Resistance 4 Marks

Attack each chosen scheme using a technique suited to it:

- Brute force, frequency analysis, Kasiski examination / index of coincidence, known-plaintext attack on Hill, digram analysis.
- Explain why each attack succeeds or fails, in terms of letter-frequency preservation, key repetition and linearity.
- Rank the schemes by resistance and justify the ranking with evidence.

Evidence Expected: Worked attacks with reasoning, and a ranking of schemes supported by the results.

TASK 7 – Assess Transposition and Product Ciphers 3 Marks

- Implement a columnar (or rail-fence) transposition and explain how it diffuses plaintext structure.
- Evaluate whether *substitution followed by transposition* is stronger than either alone. Justify with letter-frequency evidence and an attack attempt.
- Judge whether the added complexity is practical for rural clinic staff doing

manual or low-resource encryption.

Evidence Expected: A reasoned evaluation of the combined scheme against its components.

TASK 8 – Evaluate Steganography 3 Marks

Design a steganographic method (e.g., LSB embedding in a scan image, or text-based hiding) for carrying a short report inside a medical image.

- Compare it with encryption on capacity, imperceptibility, robustness and detectability.
- Evaluate the risk specific to medical imaging: could embedding alter pixel data enough to affect a diagnosis? Judge the trade-off.
- Judge when steganography is appropriate, and argue why hiding is not a substitute for encrypting. Evaluate an encrypt-then-embed approach.

Evidence Expected: A criteria-based comparison with a justified conclusion.

TASK 9 – Implement and Test
4 Marks

Implement all chosen schemes, the cryptanalysis tools and (where feasible) the steganography method, in a language of your choice.

- Provide correctness tests: decrypt(encrypt(m)) = m, including edge cases (digits in patient IDs, punctuation, non-multiple block length for Hill).
- Use identical plaintexts of 100, 1,000, 10,000 and 100,000 characters across schemes.
- State the testing procedure clearly so it can be reproduced.

Evidence Expected: Working code with a documented, reproducible test procedure.

TASK 10 – Record and Interpret Experimental Evidence
3 Marks

Present data in tables and graphs for:

- Letter-frequency histograms of plaintext versus each ciphertext.
- Index of coincidence per scheme.
- Encryption/decryption time against message size.

- Attack success rate against

ciphertext length. Evaluate what the

data shows. Do not just present it.

Evidence Expected: Clear, comparable results with interpretation tied to Tasks 5 and 6.

TASK 11 – Recommend and Defend the Final Design
4
Marks

Recommend one scheme, or a layered combination, together with the Bell-LaPadula policy.

- Justify against the alternatives using your mathematical and experimental evidence.
- State the residual risks and limitations honestly. Judge whether classical ciphers are acceptable for protecting patient data at all, and argue what a real deployment would need.
- Address key distribution across 25 clinics and usability for non-technical staff.

Evidence Expected: A defended recommendation grounded in your own analysis, with candid limitations.

DAY-4 DESIGN CHALLENGE

TASK 12 – Re-evaluate and Adapt the Design 8 Marks

Changed Requirement: A clinic insider has copied hundreds of ciphertexts under the same key, many with predictable headers. The network also wants reports hidden inside medical scan images.

You may RETAIN → MODIFY → or REDESIGN your original solution.

A. Impact Analysis (2 Marks)

- What has changed in the threat model (insider versus external attacker)?
- Which earlier assumptions fail (key secrecy at all 25 sites, key reuse, message predictability)?
- Why does a high volume of known-format messages change the risk ranking?

B. Evaluation of the Original Design (2 Marks)

- Test your recommended scheme against the new attacker capabilities (known-plaintext, repeated-key attacks).
- Support the evaluation with a demonstration or calculation.
- Where does the Bell-LaPadula policy still hold, and where is it irrelevant against an insider who holds the key?

C. Adaptation or Redesign (2 Marks)

- Decide to retain, modify or redesign. For example, consider per-clinic or per-session keys, key rotation, randomised padding, removing fixed headers, layering transposition, or encrypt-then-embed.
- Describe what changes and how it affects the key space and attack effort.

D. Evidence-Based Defence (2 Marks)

Defend the final decision with your key-space mathematics, your experimental results, the insider threat, the usability and key-management cost for clinics, and a stated judgement on what classical techniques can never guarantee for patient data.

MARK DISTRIBUTION

Task	**Marks**
Task 1 – Threats, Attacks and Risk Evaluation	4
Task 2 – Security Goals Mapping	3
Task 3 – Bell-LaPadula Application and Critique	5
Task 4 – Cipher Design	4
Task 5 – Mathematical Analysis	5
Task 6 – Cryptanalytic Resistance	4
Task 7 – Transposition / Product Ciphers	3
Task 8 – Steganography Evaluation	3
Task 9 – Implementation & Testing	4
Task 10 – Experimental Evidence	3
Task 11 – Final Design Recommendation	4
Subtotal	**42**
Task 12 – Day-4 Design Challenge	**8**
TOTAL	**50**