

SRIRAM S (12/08/2006) 2024-IT**S2****Started on** Wednesday, 5 November 2025, 4:03 AM**State** Finished**Completed on** Wednesday, 5 November 2025, 4:05 AM**Time taken** 1 min 20 secs**Grade** 10.00 out of 10.00 (**100%**)

Question 1 | Correct Mark 10.00 out of 10.00**Playing with Chessboard:**

Ram is given with an $n \times n$ chessboard with each cell with a monetary value. Ram stands at the $(0,0)$, that the position of the top left white rook. He is been given a task to reach the bottom right black rook position $(n-1, n-1)$ constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:**Input**

3

1 2 4

2 3 4

8 7 1

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value: $1+2+8+7+1=19$

Input Format

First Line contains the integer n

The next n lines contain the $n \times n$ chessboard values

Output Format

Print Maximum monetary value of the path

Answer: (penalty regime: 0 %)

```

1 #include <stdio.h>
2
3 #define MAX 100
4
5 int max(int a, int b) {
6     return (a > b) ? a : b;
7 }
8
9 int main() {
10    int n;
11    int board[MAX][MAX];
12    int dp[MAX][MAX];
13
14    // Read size of the board
15    scanf("%d", &n);
16
17    // Read board values
18    for (int i = 0; i < n; i++)
19        for (int j = 0; j < n; j++)
20            scanf("%d", &board[i][j]);
21
22    // Initialize DP table
23    dp[0][0] = board[0][0];
24
25    // Fill first row
26    for (int j = 1; j < n; j++)
27        dp[0][j] = dp[0][j - 1] + board[0][j];
28
29    // Fill first column

```

```

-- 30
31     dp[i][0] = dp[i - 1][0] + board[i][0];
32
33     // Fill rest of the DP table
34     for (int i = 1; i < n; i++) {
35         for (int j = 1; j < n; j++) {
36             dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]) + board[i][j];
37         }
38     }
39
40     // Output the result
41     printf("%d\n", dp[n - 1][n - 1]);
42
43     return 0;
44 }
45

```

	Input	Expected	Got	
✓	3 1 2 4 2 3 4 8 7 1	19	19	✓
✓	3 1 3 1 1 5 1 4 2 1	12	12	✓
✓	4 1 1 3 4 1 5 7 8 2 3 4 6 1 6 9 0	28	28	✓

Passed all tests! ✓

Correct

Marks for this submission: 10.00/10.00.

[Back to Course](#)