# **Fine-tuned Language Models for Text Classification**

## Jeremy Howard

fast.ai University of San Francisco Singularity University j@fast.ai

#### Sebastian Ruder

Insight Centre, NUI Galway Aylien Ltd., Dublin sebastian@ruder.io

#### **Abstract**

Transfer learning has revolutionized computer vision, but existing approaches in NLP still require task-specific modifications and training from scratch. We propose Fine-tuned Language Models (FitLaM), an effective transfer learning method that can be applied to any task in NLP, and introduce techniques that are key for fine-tuning a state-of-the-art language model. Our method significantly outperforms the state-of-the-art on five text classification tasks, reducing the error by 18-24% on the majority of datasets. We opensource our pretrained models and code to enable adoption by the community<sup>1</sup>.

# 1 Introduction

Transfer learning has had a large impact on computer vision (CV). Applied CV models (including object detection, classification, and segmentation) are rarely trained from scratch, but instead are fine-tuned from models that have been pretrained on ImageNet, MS-COCO, and other datasets (Sharif Razavian et al., 2014; Long et al., 2015a; He et al., 2016; Huang et al., 2017).

Text classification is a category of Natural Language Processing (NLP) tasks with many important real-world applications such as spam, fraud, and bot detection (Jindal and Liu, 2007; Ngai et al., 2011; Chu et al., 2012), emergency response (Caragea et al., 2011), and commercial document classification, such as for legal discovery (Roitblat et al., 2010).

While Deep Learning models have achieved state-of-the-art on many NLP tasks, these models are trained from scratch, requiring large datasets, and days to converge. Adoption of

transfer learning for NLP has lagged behind CV. Fine-tuning pretrained word embeddings (Mikolov et al., 2013; Pennington et al., 2014), a simple transfer learning technique that only targets a model's first layer, has had an outsized impact in practice and is used in most state-of-theart models. In light of the benefits of pretraining (Erhan et al., 2010), we should be able to do better than *randomly initializing* the remaining parameters of our models.

Recent approaches concatenate embeddings derived from other tasks such as language modeling or machine translation with the input at different layers (Peters et al., 2017; McCann et al., 2017; Anonymous, 2018). These approaches, however, still train the main task model from scratch and treat the pretrained embeddings as fixed parameters, limiting their usefulness.

Arguably, a successful transfer learning technique for NLP should fulfill similar criteria as its CV counterpart: a) The method should be able to leverage large amounts of available data; b) it should utilize a task, which can be optimized independently, leading to further downstream improvements; c) it should rely on a single model that can be used as-is for most NLP tasks; d) it should be easy to use in practice.

We propose Fine-tuned Language Models (Fit-LaM) as an effective form of transfer learning for NLP that fulfills the aforementioned criteria. Our method uses language modeling, a task with almost infinite amounts of data and a stream of recent advances pushing the state-of-the-art. It seamlessly integrates large amounts of external data as well as in-domain data via pretraining.

FitLaM relies on a simple recurrent neural network (RNN) without any additional modifications; we only augment the model with one or more task-specific linear layers, accounting for a small number of parameters relative to existing approaches.

<sup>&</sup>lt;sup>1</sup>The code will be made available at a future time.

We propose a new fine-tuning technique, discriminative fine-tuning, that fine-tunes lower layers to a lesser extent than higher layers in order to retain the knowledge acquired through language modeling. We furthermore introduce several techniques that are key for good fine-tuning performance and faster training.

We evaluate our transfer learning method on five widely-studied text classification tasks of various sizes and types, on which we significantly outperform highly task-specific previous work and existing transfer learning approaches.

Our contributions are the following:

- 1. We draw parallels of transfer learning in CV and NLP and make the case for an effective transfer learning method for NLP.
- 2. We propose Fine-tuned Language Models (FitLaM), a method that can be used to achieve CV-like transfer learning for any task for NLP.
- 3. We propose Discriminative Fine-Tuning to retain previous knowledge and avoid catastrophic forgetting during fine-tuning.
- 4. We introduce Back-Propagation Through Time for Text Classification (BPT3C), a new method to back-propagate a classifier loss through linear layers to an RNN output of any sequence size.
- 5. We introduce techniques that are key for finetuning the pretrained language model.
- 6. We significantly outperform the state-of-theart on five representative text classification datasets, with an error reduction of 18-24% on the majority of datasets.
- 7. We make the pretrained models and our code available to enable wider adoption.

#### 2 Related work

**Transfer learning in CV** Features in deep neural networks in CV have been observed to transition from task-*specific* to *general* from the first to the last layer (Yosinski et al., 2014). For this reason, most work in CV focuses on transferring the last layers of the model (Long et al., 2015b). Sharif Razavian et al. (2014) achieve state-of-theart results using features of an ImageNet model as input to a simple classifier. In recent years, this

approach has been superseded by fine-tuning either the last (Donahue et al., 2014) or several of the last layers of a pretrained model and leaving the remaining layers frozen (Long et al., 2015a).

Hypercolumns In NLP, only recently have methods been proposed that go beyond transferring word embeddings. The prevailing approach is to pretrain embeddings that capture additional context via other tasks. The embeddings are then concatenated either with the word embeddings or with the inputs at intermediate layers. This approach is known as hypercolumns in CV (Hariharan et al., 2015) and is used by Peters et al. (2017), Anonymous (2018), and McCann et al. (2017) who use language modeling and Machine Translation (MT) respectively for pretraining. A similar approach is used by Conneau et al. (2017) for learning sentence representations. In CV, hypercolumns have been nearly entirely superseded by end-to-end fine-tuning (Long et al., 2015a).

Multi-task learning A related direction is multi-task learning (MTL) (Caruana, 1993). This is the approach taken by Rei (2017) and Liu et al. (2018) who add a language modeling objective to the model that is trained jointly with the main task model. MTL could potentially be combined with FitLaM.

**Fine-tuning** Fine-tuning, which fine-tunes a pretrained model on the target task, has been used successfully for certain tasks such as sentiment analysis with distant supervision (Severyn and Moschitti, 2015; Felbo et al., 2017). In the following, we will show that fine-tuning is superior to both hypercolumns and MTL as a general-purpose transfer learning method for NLP.

#### 3 Transfer Learning for NLP

Transfer learning has many instantiations (Pan and Yang, 2010). Here, we are interested in the most general inductive transfer learning setting for NLP: Given a static source task  $\mathcal{T}_S$  and any target task  $\mathcal{T}_T$  with  $\mathcal{T}_S \neq \mathcal{T}_T$ , we would like to improve performance on  $\mathcal{T}_T$ . The main questions are: 1) which transfer learning method to use; and 2) from which source task  $\mathcal{T}_S$  to transfer. For both settings, we let insights from CV inform our reasoning.

The case for fine-tuning To facilitate wide adoption, a transfer learning method for NLP should be a) practical, b) efficient, and c) effective. MTL requires the tasks to be trained from scratch every time and often requires careful weighting of the task-specific objective functions (Chen et al., 2017). As its success in CV has shown (Long et al., 2015a), fine-tuning is clearly superior to hypercolumns. Given sufficient data is available, fine-tuning representations outperforms freezing them; similar observations have been made for word embeddings (Kim, 2014). Furthermore, when pretrained weights capturing certain properties of natural language are available, using random weights as initialization appears to be a suboptimal choice (Erhan et al., 2010).

The case for language modeling The ideal pretraining task for NLP should have similar properties as ImageNet in CV: It should a) provide abundant data and b) enable us to induce representations that are helpful for many NLP tasks. Formally, the pretraining task should allow us to induce a hypothesis space  ${\mathcal H}$  that will be useful for many other NLP tasks (Vapnik and Kotz, 1982; Baxter, 2000). While MT is possibly the NLP task with the largest amount of labeled data, reliance on labeled data imposes an upper bound and precludes using data from the target task distribution for training in order to bridge a domain shift. Language modeling can be seen as the prototypical NLP task: Language models capture many facets of language, such as long-term dependencies and sentiment that are relevant for downstream tasks (Radford et al., 2017). In addition, data is available in near-unlimited quantities and for the majority of target domains.

We thus argue that pretraining a language model and fine-tuning it on the target task is the most useful transfer learning method for NLP. We empirically validate this in Section 5 where our approach—which we introduce in the next Section—outperforms existing transfer learning methods significantly across five text classification tasks.

## 4 Fine-tuned Language Models (FitLaM)

We propose Fine-tuned Language Models (Fit-LaM), which pretrains a highly-optimized language model (LM) on a large general-domain corpus and fine-tunes it on the target task. (The basic idea of unidirectional FitLaM was first described

in (Howard, 2018), where it was demonstrated on the IMDb dataset, but the details have not been shared previously.)

Language modeling Statistical language models try to learn the probability of the next word given its previous words. Models rely on an auto-regressive factorization of the joint probability of a corpus using different approaches, from n-gram models to RNNs, which achieve state-of-the-art results across various benchmarks. In our experiments, we use the state-of-the-art language model AWD-LSTM (Merity et al., 2017a), a regular LSTM with various highly tuned regularization strategies. Analogous to CV, downstream performance can be improved by using higher-performance language models in the future.

FitLaM consists of the following steps: 1) General-domain LM pretraining; 2) target task LM fine-tuning; and 3) target task classifier fine-tuning. We discuss these in the following sections.

## 4.1 General-domain LM pretraining

We pretrain the language model on Wikitext-103 (Merity et al., 2017b) consisting of 28,595 pre-processed Wikipedia articles. Pretraining on additional and more diverse datasets should boost performance. This stage is the most expensive, but because it only needs to be performed once, it vastly benefits the following stages by improving performance and convergence of downstream models. We make the weights of the pretrained model available to facilitate experimentation.

# 4.2 Target task LM fine-tuning

No matter how diverse the general-domain data used for pretraining is, the data of the target task will likely come from a different distribution. We thus fine-tune the language model on the training examples of the target task. Given a pretrained general-domain LM, this stage converges much faster as it only needs to adapt to the idiosyncrasies of the target data, and it allows us to train a robust LM even for small datasets.

**Gradual unfreezing** While we could fine-tune all parameters of the pretrained language model at the same time, we have found it to be most useful to gradually unfreeze the model starting from the last layer as this contains the *least general* knowledge (Yosinski et al., 2014): We first unfreeze the last layer and fine-tune all unfrozen layers. We then additionally unfreeze the next lower frozen

layer and repeat, until all layers are fine-tuned at the last iteration. This is similar to the approach used in (Felbo et al., 2017), except that we add a layer at a time to the set of 'thawed' layers, rather than only training a single layer at a time.

Fine-tuning with cosine annealing We have observed the best results by fine-tuning with an aggressive cosine annealing schedule (Loshchilov and Hutter, 2017). Rather than lowering the learning rate over several epochs, we train for only one epoch and lower the learning rate for each batch with the following schedule:

$$\eta_t = \eta_{min} + \frac{1}{2}(\eta_{max} - \eta_{min})(1 + \cos(\frac{t}{T}\pi))$$
 (1)

where  $\eta_t$  is the learning rate for the batch at time step t and T is the size of an epoch. We set  $\eta_{min}=0$  and  $\eta_{max}=0.002$ .

**Warm-up reverse annealing** We have also found it useful to first train all layers with a gradually increasing, i.e. reverse annealed learning rate for an epoch as a warm-up before gradual unfreezing. This is similar to the approach used in (Smith and Topin, 2017).

#### 4.3 Target task classifier fine-tuning

For target task classifier fine-tuning, we augment the pretrained language model with one or more additional linear blocks. Each block uses batch normalization (Ioffe and Szegedy, 2015) and dropout, with ReLU activations for any intermediate layers and a softmax activation that outputs a probability distribution over the target task classes at the last layer. Note that the parameters in these task-specific classifier layers are the only ones that need to be learned from scratch. The first linear layer takes as the input the pooled last hidden layer states.

Concat pooling The signal in text classification tasks is often contained in a few words, which may occur anywhere in the document. As input documents can consist of hundreds of words, information may get lost if we only consider the last hidden state of the model. For this reason, we concatenate the hidden state at the last time step  $\mathbf{h}_T$  of the document with both the max-pooled and the mean-pooled representation of the hidden states over as many time steps as fit in GPU memory  $\mathbf{H} = \{\mathbf{h}_1, \dots, \mathbf{h}_T\}$ :

$$\mathbf{h}_c = [\mathbf{h}_T, \mathtt{maxpool}(\mathbf{H}), \mathtt{meanpool}(\mathbf{H})]$$
 (2)

where [] is concatentation.

Fine-tuning the target task classifier is the most critical part of the transfer learning method. Overly aggressive fine-tuning will cause catastrophic forgetting, eliminating the benefit of the information captured through language modeling; too cautious fine-tuning will lead to slow convergence (and resultant overfitting).

#### 4.4 Discriminative fine-tuning

As different layers capture different types of information (Yosinski et al., 2014), they should be fine-tuned to different extents. In CV where fine-tuning the entire model is too costly as networks can have more than 100 layers (Huang et al., 2017), a common practice is to fine-tune initially just the last hidden layer, and then unfreeze additional layers for further fine-tuning.

The simplest approach to treating different layers appropriately is to fine-tune the model one layer at a time, analogous to greedy layer-wise training (Bengio et al., 2007) and 'chain-thaw' (Felbo et al., 2017). However, this introduces a sequential requirement, hindering parallelism, and requires multiple passes through the dataset, resulting in overfitting for small datasets<sup>2</sup>. For this reason, we propose a more efficient fine-tuning method, discriminative fine-tuning<sup>3</sup>.

Instead of using the same learning rate for *all* layers of the model, discriminative fine-tuning allows us to tune *each* layer with different learning rates. For context, the regular stochastic gradient descent (SGD) update of a model's parameters  $\theta$  at time step t looks like the following (Ruder, 2016):

$$\theta_t = \theta_{t-1} - \eta \cdot \nabla_{\theta} J(\theta) \tag{3}$$

where  $\eta$  is the learning rate and  $\nabla_{\theta}J(\theta)$  is the gradient with regard to the model's objective function. For discriminative fine-tuning, we split the parameters  $\theta$  into  $\{\theta^1,\ldots,\theta^L\}$  where  $\theta^l$  contains the parameters of the model at the l-th layer and L is the number of layers of the model. Similarly, we obtain  $\{\eta^1,\ldots,\eta^L\}$  where  $\eta^l$  is the learning rate of the l-th layer.

The SGD update with discriminative fine-

<sup>&</sup>lt;sup>2</sup>This is why we do not use gradual unfreezing and cosine annealing for fine-tuning the target task classifier.

<sup>&</sup>lt;sup>3</sup>Fine-tuning a language model to different degrees was first proposed in (Howard, 2018) who called it *differential learning rates*. A method of the same name exists for deep Boltzmann machines (Salakhutdinov and Hinton, 2009).

tuning is then the following:

$$\theta_t^l = \theta_{t-1}^l - \eta^l \cdot \nabla_{\theta^l} J(\theta) \tag{4}$$

We empirically found it to work well to first choose the learning rate  $\eta^L$  of the last layer by fine-tuning only the last layer and using  $\eta^l = \eta^{l+1} \cdot 0.3$  as the learning rate for lower layers.

#### **4.5** BPTT for Text Classification (BPT3C)

Language models are trained with backpropagation through time (BPTT) to enable gradient propagation for large input sequences. In order to make fine-tuning a classifier for large documents feasible, we propose BPTT for Text Classification (BPT3C): We divide the document into fixed-length batches of size b. At the beginning of each batch, the model is initialized with the final state of the previous batch; we keep track of the hidden states for mean and max-pooling; gradients are back-propagated to the batches whose hidden states contributed to the classifier prediction at the end of the document. In practice, we use variable length backpropagation sequences (Merity et al., 2017a).

#### 4.6 Bidirectional language model

Similar to existing work (Peters et al., 2017; Anonymous, 2018), we are not limited to fine-tuning a uni-directional language model. For all our experiments, we pretrain both a forward and a backward LM. We fine-tune a classifier for each LM independently using BPT3C and average their predictions.<sup>4</sup>

# 5 Experiments

While our approach is equally applicable to sequence labeling tasks, we focus on text classification tasks in this work due to their important real-world applications.

# 5.1 Experimental setup

**Datasets and tasks** We evaluate our method on five widely-studied datasets of different sizes used by state-of-the-art text classification and transfer learning approaches (Johnson and Zhang, 2017; McCann et al., 2017) as instances of three common text classification tasks: sentiment analy-

Dataset	Type	# classes	# examples	
IMDb	Sentiment	2	22.5k	
Yelp-bi	Sentiment	2	560k	
TREC-6	Question	6	4.3k	
AG-News	Topic	4	120k	
DBpedia	Topic	14	560k	

Table 1: Text classification datasets and tasks.

sis, question classification, and topic classification. We show the statistics for each dataset and task in Table 1.

**Sentiment Analysis** For sentiment analysis, we evaluate our approach on the binary movie review IMDb dataset (Maas et al., 2011) and on the binary Yelp review dataset compiled by Zhang et al. (2015).

**Question** Classification We use the six-class version of the small TREC dataset (Voorhees and Tice, 1999) dataset of open-domain, fact-based questions divided into broad semantic categories.

**Topic classification** For topic classification, we evaluate on the large-scale AG-News and DBpedia ontology datasets created by Zhang et al. (2015).

**Pre-processing** We use the same pre-processing as in earlier work (Johnson and Zhang, 2017; McCann et al., 2017). In addition, to allow the language model to capture aspects that might be relevant for classification, we add special tokens for upper-case words, elongation, and repetition.

Hyperparameters We use the AWD-LSTM language model (Merity et al., 2017a) with an embedding size of 400, 3 layers, 1150 hidden activations per layer, and a BPTT batch size of 70. We apply dropout of 0.4 to layers, of 0.3 to RNN layers, of 0.4 to input embedding layers, of 0.05 to embedding layers, and weight dropout of 0.5 to the RNN hidden-to-hidden matrix. The classifier has a hidden layer of size 50. We use Adam with  $\beta_1 = 0.7$  instead of the default  $\beta_1 = 0.9$  and  $\beta_2 = 0.99$ , similar to (Dozat and Manning, 2017). We otherwise use the same hyperparameters and practices used in (Merity et al., 2017a).

**Baselines and comparison models** For each task, we compare against the current state-of-theart. For the IMDb and TREC-6 datasets, we compare against CoVe (McCann et al., 2017), a state-

<sup>&</sup>lt;sup>4</sup>Note that we already achieve state-of-the-art results on most datasets with unidirectional LMs. Bidirectional LMs generally improve performance. We will report detailed ablations in future work.

	Model	Test	Model	Test
	BCN+Char+CoVe (McCann et al., 2017)	91.8	BCN+Char+CoVe (McCann et al., 2017)	95.8
Db	oh-LSTM (Johnson and Zhang, 2016)	94.1	TBCNN (Mou et al., 2015)	96.0
$\mathbb{Z}$	Virtual (Miyato et al., 2016)	94.1	LSTM-CNN (Zhou et al., 2016)	96.1
, ,	FitLaM (Ours)	95.4	FitLaM (ours)	96.4

Table 2: Test accuracy scores on two text classification datasets used by McCann et al. (2017).

	AG-News	DBpedia	Yelp-bi
Char-level CNN (Zhang et al., 2015)	9.51	1.55	4.88
CNN (Johnson and Zhang, 2016)	6.57	0.84	2.90
DPCNN (Johnson and Zhang, 2017)	6.87	0.88	2.64
FitLaM (ours)	5.01	0.80	2.16

Table 3: Test error rates (%) on three text classification datasets used by Johnson and Zhang (2017).

of-the-art transfer learning method for NLP.<sup>5</sup> For the AG-News, Yelp, and DBpedia datasets compiled by Zhang et al. (2015), we compare against the state-of-the-art text categorization method by Johnson and Zhang (2017).

#### 5.2 Results

We show the test accuracy scores on the IMDb and TREC-6 datasets used by McCann et al. (2017) in Table 2. Our method outperforms both CoVe, a state-of-the-art transfer learning method based on hypercolumns, as well as the state-of-theart on both datasets. On IMDb, we reduce the error dramatically by 43.9% and 22% with regard to CoVe and the state-of-the-art respectively. This is promising in particular as the existing state-of-the-art requires complex architectures (Anonymous, 2018), multiple forms of attention (McCann et al., 2017) and sophisticated embedding schemes (Johnson and Zhang, 2016), while our method employs a standard Bi-LSTM with dropout.

On TREC-6, our improvement—similar as the improvements of state-of-the-art approaches—is not statistically significant, owing to the small size of the test consisting only of 500 examples. We recommend to cease using this dataset for the evaluation of text classification algorithms. However, the competitive performance on the small TREC-6 dataset still demonstrates that fine-tuning a language model and a target task classifier is feasi-

ble even for small datasets. Note that despite pretraining on more than two orders of magnitude less data than the 7 million sentence pairs used by McCann et al. (2017), we consistently outperform their approach on both datasets.

We show the test error rates on the larger AG-News, DBpedia, and Yelp-bi datasets used by Johnson and Zhang (2017) in Table 3. Our method again outperforms the state-of-the-art significantly. On AG-News, we observe a similarly dramatic error reduction by 23.7% compared to the state-of-the-art. On DBpedia and Yelp-bi, we reduce the error by 4.8% and 18.2% respectively.

## **6** Future directions

While our method still requires some tricks and manual tuning of learning rates and dropout weights to achieve the best performance, we see it analogous to AlexNet (Krizhevsky et al., 2012) as a necessary first step that will lead to a wave of innovation. We are confident that fine-tuning language models will become more robust as more research focuses on improving transfer learning for NLP. One important step on this path will be careful ablation studies to understand the impact of each component of the models and training procedures described here.

Given that transfer learning (and particularly fine-tuning) for NLP has been under-explored, many future directions are possible. One possible direction is to improve the language model pre-training task and make it more scalable: for ImageNet, predicting far fewer classes only incurs a small performance drop (Huh et al., 2016)—

<sup>&</sup>lt;sup>5</sup>The transfer learning methods of Peters et al. (2017), Anonymous (2018), and Liu et al. (2018) were only applied to sequence tasks and it is not clear how to best use their methods for classification.

focusing on predicting the most frequent words might retain most of the performance while speeding up training. Language modeling could also be augmented with additional tasks in a multi-task learning fashion (Caruana, 1993) or enriched with additional supervision, e.g. syntax-sensitive dependencies (Linzen et al., 2016) to create a model that is more general or better suited for certain downstream tasks.

Another direction is to apply the method to novel tasks and models. While an extension to sequence labeling tasks is straightforward, other tasks such as entailment and question answering employ more complex interactions, which require novel ways to pretrain and fine-tune.

Finally, while fine-tuning is an integral component of transfer learning, it has received scarce attention, even in CV (in academia at least—it is a key foundation for commercial systems such as Clarifai). All common benchmarks still evaluate our ability to train a model from scratch, rather than fine-tuning a pretrained model. Creating benchmarks for fine-tuning will enable us to develop more sophisticated fine-tuning methods, which will allow us to unlock the full potential of pretrained models for novel tasks.

#### 7 Conclusion

We have proposed FitLaM, an effective transfer learning method for NLP, and discriminative fine-tuning, an efficient fine-tuning method that tunes different layers to different extents in order to avoid catastrophic forgetting. We have introduced BPT3C, a method to back-propagate a classifier loss to an RNN output of any sequence size as well as several techniques that are key for good fine-tuning performance and fast training. Our method significantly outperformed existing transfer learning techniques and the state-of-the-art on five representative text classification tasks. In total, we have demonstrated the benefit of transfer learning for NLP and hope that our results will catalyze new developments in transfer learning for NLP.

#### Acknowledgments

Sebastian is supported by Irish Research Council Grant Number EBPPG/2014/30 and Science Foundation Ireland Grant Number SFI/12/RC/2289.

#### References

- Anonymous. 2018. Deep contextualized word representations. In *Proceedings of ICLR 2018*.
- Jonathan Baxter. 2000. A Model of Inductive Bias Learning. *Journal of Artificial Intelligence Research* 12:149–198.
- Yoshua Bengio, Pascal Lamblin, Dan Popovici, and Hugo Larochelle. 2007. Greedy layer-wise training of deep networks. In *Advances in neural information processing systems*. pages 153–160.
- Cornelia Caragea, Nathan McNeese, Anuj Jaiswal, Greg Traylor, Hyun-Woo Kim, Prasenjit Mitra, Dinghao Wu, Andrea H Tapia, Lee Giles, Bernard J Jansen, et al. 2011. Classifying text messages for the haiti earthquake. In *Proceedings of the 8th international conference on information systems for crisis response and management (ISCRAM2011)*. Citeseer.
- Rich Caruana. 1993. Multitask learning: A knowledge-based source of inductive bias. In *Proceedings of the Tenth International Conference on Machine Learning*.
- Zhao Chen, Vijay Badrinarayanan, Chen-Yu Lee, and Andrew Rabinovich. 2017. GradNorm: Gradient Normalization for Adaptive Loss Balancing in Deep Multitask Networks pages 1–10.
- Zi Chu, Steven Gianvecchio, Haining Wang, and Sushil Jajodia. 2012. Detecting automation of twitter accounts: Are you a human, bot, or cyborg? *IEEE Transactions on Dependable and Secure Computing* 9(6):811–824.
- Alexis Conneau, Douwe Kiela, Holger Schwenk, Loïc Barrault, and Antoine Bordes. 2017. Supervised Learning of Universal Sentence Representations from Natural Language Inference Data. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*.
- Jeff Donahue, Yangqing Jia, Oriol Vinyals, Judy Hoffman, Ning Zhang, Eric Tzeng, and Trevor Darrell. 2014. Decaf: A deep convolutional activation feature for generic visual recognition. In *International conference on machine learning*. pages 647–655.
- Timothy Dozat and Christopher D. Manning. 2017. Deep Biaffine Attention for Neural Dependency Parsing. In *Proceedings of ICLR 2017*.
- Dumitru Erhan, Yoshua Bengio, Aaron Courville, Pierre-Antoine Manzagol, Pascal Vincent, and Samy Bengio. 2010. Why does unsupervised pre-training help deep learning? *Journal of Machine Learning Research* 11(Feb):625–660.
- Bjarke Felbo, Alan Mislove, Anders Søgaard, Iyad Rahwan, and Sune Lehmann. 2017. Using millions of emoji occurrences to learn any-domain representations for detecting sentiment, emotion and sarcasm. In *Proceedings of the 2017 Conference on*

- Empirical Methods in Natural Language Processing.
- Bharath Hariharan, Pablo Arbeláez, Ross Girshick, and Jitendra Malik. 2015. Hypercolumns for object segmentation and fine-grained localization. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*. pages 447–456.
- Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2016. Deep Residual Learning for Image Recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*.
- Jeremy Howard. 2018. Lesson 4: Deep learning v2. Practical Deep Learning for Coders.
- Gao Huang, Zhuang Liu, Kilian Q. Weinberger, and Laurens van der Maaten. 2017. Densely Connected Convolutional Networks. In *Proceedings of CVPR* 2017.
- Minyoung Huh, Pulkit Agrawal, and Alexei A Efros. 2016. What makes ImageNet good for transfer learning? *arXiv preprint arXiv:1608.08614*.
- Sergey Ioffe and Christian Szegedy. 2015. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning*. pages 448–456.
- Nitin Jindal and Bing Liu. 2007. Review spam detection. In *Proceedings of the 16th international conference on World Wide Web*. ACM, pages 1189–1190.
- Rie Johnson and Tong Zhang. 2016. Supervised and semi-supervised text categorization using 1stm for region embeddings. In *International Conference on Machine Learning*. pages 526–534.
- Rie Johnson and Tong Zhang. 2017. Deep pyramid convolutional neural networks for text categorization. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. volume 1, pages 562–570.
- Yoon Kim. 2014. Convolutional Neural Networks for Sentence Classification. *Proceedings of the Conference on Empirical Methods in Natural Language Processing* pages 1746–1751.
- Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. 2012. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*. pages 1097–1105.
- Tal Linzen, Emmanuel Dupoux, and Yoav Goldberg. 2016. Assessing the ability of lstms to learn syntax-sensitive dependencies. *arXiv* preprint *arXiv*:1611.01368.
- Liyuan Liu, Jingbo Shang, Frank Xu, Xiang Ren, Huan Gui, Jian Peng, and Jiawei Han. 2018. Empower sequence labeling with task-aware neural language model. In *Proceedings of AAAI 2018*.

- Jonathan Long, Evan Shelhamer, and Trevor Darrell. 2015a. Fully convolutional networks for semantic segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*. pages 3431–3440.
- Mingsheng Long, Yue Cao, Jianmin Wang, and Michael I. Jordan. 2015b. Learning Transferable Features with Deep Adaptation Networks. In *Proceedings of the 32nd International Conference on Machine learning (ICML '15)*. volume 37.
- Ilya Loshchilov and Frank Hutter. 2017. SGDR: Stochastic Gradient Descent with Warm Restarts. In *Proceedings of the Internal Conference on Learning Representations* 2017.
- Andrew L Maas, Raymond E Daly, Peter T Pham, Dan Huang, Andrew Y Ng, and Christopher Potts. 2011. Learning word vectors for sentiment analysis. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies-Volume 1*. Association for Computational Linguistics, pages 142–150.
- Bryan McCann, James Bradbury, Caiming Xiong, and Richard Socher. 2017. Learned in Translation: Contextualized Word Vectors. In *Advances in Neural Information Processing Systems*.
- Stephen Merity, Nitish Shirish Keskar, and Richard Socher. 2017a. Regularizing and Optimizing LSTM Language Models. arXiv preprint arXiv:1708.02182.
- Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. 2017b. Pointer Sentinel Mixture Models. In *Proceedings of the International Conference on Learning Representations* 2017.
- Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. 2013. Distributed Representations of Words and Phrases and their Compositionality. In *Advances in Neural Information Processing Systems*.
- Takeru Miyato, Andrew M Dai, and Ian Goodfellow. 2016. Adversarial training methods for semi-supervised text classification. arXiv preprint arXiv:1605.07725.
- Lili Mou, Hao Peng, Ge Li, Yan Xu, Lu Zhang, and Zhi Jin. 2015. Discriminative neural sentence modeling by tree-based convolution. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*.
- EWT Ngai, Yong Hu, YH Wong, Yijun Chen, and Xin Sun. 2011. The application of data mining techniques in financial fraud detection: A classification framework and an academic review of literature. *Decision Support Systems* 50(3):559–569.
- Sinno Jialin Pan and Qiang Yang. 2010. A survey on transfer learning. *IEEE Transactions on Knowledge and Data Engineering* 22(10):1345–1359.

- Jeffrey Pennington, Richard Socher, and Christopher D. Manning. 2014. Glove: Global Vectors for Word Representation. *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing* pages 1532–1543.
- Matthew E Peters, Waleed Ammar, Chandra Bhagavatula, and Russell Power. 2017. Semi-supervised sequence tagging with bidirectional language models. In *Proceedings of ACL 2017*.
- Alec Radford, Rafal Jozefowicz, and Ilya Sutskever. 2017. Learning to generate reviews and discovering sentiment. *arXiv preprint arXiv:1704.01444*.
- Marek Rei. 2017. Semi-supervised multitask learning for sequence labeling. In *Proceedings of ACL 2017*.
- Herbert L Roitblat, Anne Kershaw, and Patrick Oot. 2010. Document categorization in legal electronic discovery: computer classification vs. manual review. *Journal of the Association for Information Science and Technology* 61(1):70–80.
- Sebastian Ruder. 2016. An overview of gradient descent optimization algorithms. *arXiv* preprint *arXiv*:1609.04747.
- Ruslan Salakhutdinov and Geoffrey Hinton. 2009. Deep boltzmann machines. In *Artificial Intelligence and Statistics*. pages 448–455.
- Aliaksei Severyn and Alessandro Moschitti. 2015. UNITN: Training Deep Convolutional Neural Network for Twitter Sentiment Classification. *Proceedings of the 9th International Workshop on Semantic Evaluation (SemEval 2015)* pages 464–469.
- Ali Sharif Razavian, Hossein Azizpour, Josephine Sullivan, and Stefan Carlsson. 2014. Cnn features off-the-shelf: an astounding baseline for recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*. pages 806–813.
- Leslie N. Smith and Nicholay Topin. 2017. Super-Convergence: Very Fast Training of Residual Networks Using Large Learning Rates. *arXiv preprint arXiv:1708.07120*.
- Vladimir Naumovich Vapnik and Samuel Kotz. 1982. Estimation of dependences based on empirical data, volume 40. Springer-Verlag New York.
- Ellen M Voorhees and Dawn M Tice. 1999. The trec-8 question answering track evaluation. In *TREC*. volume 1999, page 82.
- Jason Yosinski, Jeff Clune, Yoshua Bengio, and Hod Lipson. 2014. How transferable are features in deep neural networks? In Advances in neural information processing systems. pages 3320–3328.
- Xiang Zhang, Junbo Zhao, and Yann LeCun. 2015. Character-level convolutional networks for text classification. In *Advances in neural information processing systems*. pages 649–657.

Peng Zhou, Zhenyu Qi, Suncong Zheng, Jiaming Xu, Hongyun Bao, and Bo Xu. 2016. Text classification improved by integrating bidirectional lstm with twodimensional max pooling. In *Proceedings of COL-ING 2016*.