


# Basics of Contiki

# Contiki Overview

- Based on the introduction tutorial, you already have a basic understanding of Contiki, as follows
  - Complete environment for programming sensor nodes
  - Has everything to get started in making applications
  - Includes built-in simulator named Cooja
  - Large pool of sensor compatibility, e.g., T-mote Sky, Z1
- To use Contiki for hands-on practice, it is important to understand the structure of its source code files

# Source File Structure in Contiki

- Folders and files in Contiki



# Contiki Folders

- `apps/`: Contiki applications, such as web browser, shell, etc.
- `core/`: Contiki filesystem and core components
  - `core/dev/`: Source code for devices, such as LED, sensors, buttons
  - `core/net/`: Source code for MAC, RPL routing protocol, IPv6 and IPv4, queuing packets and buffers, etc.
- `cpu/`: Source code for computation units of sensor nodes
- `dev/`: Source code files for some hardware platforms, such as cc1200, sht11, etc.
- `examples/`: Example source code files
- `platform/`: Specific device files and drivers
- `tools/`: Variety of tools for debugging, simulating, and testing applications, including Cooja

# Hello World Example


# Hello World Simulation

- The simplest way to open the simulation is to select “Hello World Simulation” in the IoTrain-Sim interface
- Alternatively, you can open it manually as follows
  - Open Cooja
  - Click File > Open simulation > Browse...
  - Go to the folder “iotrain-sim/database/fundamental\_training/single\_node/basics\_contiki/simulation”
  - Select the file “hello-world.csc”
- When the simulation control window appears, click the “Start” button to start the simulation
  - The execution will stop automatically after 5 seconds, but you can use the “Reload” button to reload the simulation

# Source Code File “hello-world.c”

```
#include "contiki.h"
#include <stdio.h>

/*-----*/
PROCESS(hello_world_process, "Hello world process");
AUTOSTART_PROCESSES(&hello_world_process);
/*-----*/
PROCESS_THREAD(hello_world_process, ev, data)
{
    PROCESS_BEGIN();
    printf("Hello, world\n");
    PROCESS_END();
}
/*-----*/
```



Part I

Part II

# Source Code Commentary: Part I

```
#include "contiki.h" /* For Contiki applications */
#include <stdio.h> /* For the printf() function*/
/*-----*/
/* Contiki application: Declare the main PROCESS */
PROCESS(hello_world_process, "Hello world process"); ❶
/* Make the process start when the module is loaded */
AUTOSTART_PROCESSES(&hello_world_process); ❷
/*-----*/
```

- ❶ hello\_world\_process is the actual name of the process, and “Hello world process” is the readable name of the process when printed to the terminal
- ❷ The AUTOSTART\_PROCESSES(&hello\_world\_process) call tells Contiki to start that process when it finishes booting



# Source Code Commentary: Part II

```
/*-----*/  
PROCESS_THREAD(hello_world_process, ev, data) ❶  
{  
    PROCESS_BEGIN(); ❷  
    printf("Hello, world\n"); ❸ /* Do what you want here */  
    PROCESS_END(); ❹  
}  
/*-----*/
```


- ❶ Declare the content of the process in the process thread, including the name of the process and callback functions (event handler and data handler)
- ❷ Begin executing the main processing thread, PROCESS; must always come first
- ❸ Put the source code corresponding to your logic here
- ❹ Ends the execution of PROCESS; must always come last

# Command-Line Execution

- To run the example via command-line, open a terminal and change to the source code directory “iotrain-sim/database/fundamental\_training/single\_node/basics\_contiki/simulation”
- The included files are as follows
  - hello-world.c: Source program in Contiki OS
  - hello-world.csc: Simulation file using Cooja simulator
  - Makefile: File that controls the compilation process
  - README.md: Basic instructions for the example

# Command-Line Execution (cont.)

- To execute the program, do as follows
  - Compile the program by running the command “make”
  - After processing finishes, run “./hello-world.native”
- The program will output the message “Hello, world” as shown below



```
user@instant-contiki: ~/IoTrain/Fundamental Training/Single Node/Basic of Contiki OS
File Edit View Search Terminal Help
user@instant-contiki:~/IoTrain/Fundamental Training/Single Node/Basic of Contiki
OS and Cooja/Simulation$ ./hello-world.native
Contiki-2.6-2450-geaa8760 started with IPV6, RPL
Rime started with address 1.2.3.4.5.6.7.8
MAC nullmac RDC nullrdc NETWORK sicslowpan
Tentative link-local IPv6 address fe80:0000:0000:0000:0302:0304:0506:0708
Hello, world
█
```

- To end the program execution, press Ctrl+C

# Makefile Explanation

- A “Makefile” contains instructions on how to compile source code into appropriate object files for execution
- The Makefile for the Hello World example is as follows

```
CONTIKI_PROJECT = hello-world ❶  
all: $(CONTIKI_PROJECT) ❷
```

```
CONTIKI = /home/user/contiki  
include $(CONTIKI)/Makefile.include ❸
```

- ❶ “hello-world” is the source code file name (more names are OK)
- ❷ The files defined above should be used to compile the project
- ❸ The additional file “Makefile.include” contains Contiki-specific compilation information