Developer-Centric User Engagement Strategies for the Smart-X Telemetry Dashboard

A research report on dashboard interactivity strategies for high-throughput IoT monitoring interfaces

Module	PROG7312
Assessment	Smart-X IoT Mesh Ecosystem POE – Part 1, Task 1 (Research Report)
Student Name	Muaaz Abdool Gaffoor
Student Number	ST10443760

1. Introduction

Smart-X - just like any high-throughput IoT system, generates a constant stream of multi-typed telemetry from thousands of different distributed nodes. An operator who finds the monitoring interface confusing and difficult to read will not use it properly. This could cause a fault that goes unnoticed, and an unnoticed fault on a bad dashboard is just as costly as one the sensors never reported. This report sets out five dashboard engagement strategies for that particular problem, each solution supported by published research, and then justifies the one that is chosen for the Smart-X gateway.

2. Five Dashboard Engagement Strategies Considered

1. **Real-time visual telemetry feedback:** continuously updating visual indicators (live charts, pulse animations, colour-coded states) that reflect the current condition of the monitored system as soon as data arrives, rather than requiring a manual refresh [1], [2].
2. **Alert prioritisation and anomaly highlighting:** separating critical, actionable alerts from routine telemetry noise so operators are not desensitised to warnings, a documented cause of alert fatigue in monitoring interfaces [2], [3].
3. **Gamification of monitoring tasks:** introducing light game-design elements (progress indicators, achievement-style feedback) into otherwise repetitive monitoring work to sustain operator attention and intrinsic motivation during low-activity periods [4].
4. **Simplified, guided onboarding flows:** structured onboarding sequences that progressively introduce a complex dashboard's components rather than exposing all functionality at once, reducing the barrier for new or occasional users [5].
5. **Interactive annotation and contextual exploration:** allowing users to directly annotate or query specific data points within a visualisation, improving data exploration and letting operators record context against anomalies as they investigate them [6].

3. Justification of Chosen Strategy: Real-Time Visual Telemetry Feedback

The strategy that I chose for the smart X gateway dashboard is real time visual telemetry and real-time feedback: it turns our static value dashboard into a lively dashboard element that updates continuously with new telemetry information and visual changes instead of a generic progress bar

Three things make this the right choice: the specific failure mode Smart-X needs to guard against, the published evidence linking real-time feedback to faster anomaly detection, and how well it fits the module's technical constraints.

The real risk in a system like Smart-X is not a shortage of data. It is an operator failing to notice the data in time. Attention to a display that is not changing degrades within minutes of sustained monitoring, so a sensor disconnect or a power spike can sit unnoticed on a dashboard that gives no visible sign anything happened [1]. A live feedback element forces a perceptible change the moment new telemetry lands, which counters that attentional decay instead of expecting the operator to keep manually re-checking a static value.

There is also evidence behind this beyond the general attention argument. Work on monitoring interfaces for industrial and cloud infrastructure shows that dashboards presenting immediate, intuitive state changes measurably cut the time between a fault occurring and an operator noticing it, and that this is one of the more reliable levers available when the underlying data itself cannot be simplified [1], [2]. That matters for Smart-X specifically: a delayed response to a critical moisture drop or a power spike has real consequences in the scenario the system models, whether that is crop damage in a hydroponic deployment or strain on equipment in a smart-grid node.

It also fits the rest of what the POE requires without adding extra work. The ingestion API is already receiving a continuous stream of simulated telemetry through the TelemetryPacket<T> pipeline, so exposing a lightweight polling or push-based feed to a dashboard widget is just a thin presentation layer on top of something that already exists. That keeps the engagement feature genuinely dynamic, updating on its own as data changes, rather than a decorative element bolted onto an otherwise static interface, which the brief specifically discourages.

And it carries forward cleanly. Part 2 adds a live command stream and priority-queued alerts, Part 3 adds network topology visualisation, and both build naturally on a dashboard element that is already designed to reflect live system state. An onboarding-flow or gamification strategy would have solved a different problem, either first-use comprehension or sustained engagement over long idle periods, neither of which is Smart-X's actual operational risk. The risk is a monitoring interface that fails to make an anomaly visible the moment it happens, and real-time visual telemetry feedback is the strategy that targets that directly.

4. Supporting Diagram

Figure 1: Real-Time Visual Telemetry Feedback Loop




Figure 1 shows the loop the strategy depends on: telemetry moves from the simulated sensor nodes through the ingestion API into a live telemetry store, which drives the dashboard's real-time element directly. An operator sees an anomalous reading the moment it is ingested, not on the next manual refresh.

References

[1] N. Alice, J. Asiimwe, U. I. Bature, M. Simon, and T. Meron, "Industrial Monitoring System with Real-time Alerts and Automated Protection Mechanisms," International Journal of Engineering and Manufacturing (IJEM), vol. 15, no. 2, pp. 56–67, 2025.

[2] "Mitigating Alert Fatigue in Cloud Monitoring Systems: A Machine Learning Perspective," Journal of Network and Computer Applications, ScienceDirect, 2024.

[3] "Alert Fatigue in Security Operations Centres: Research Challenges and Opportunities," ACM Computing Surveys, Association for Computing Machinery, 2025.

[4] "Supporting human monitoring activities in highly automated manufacturing through gamification," Applied Ergonomics, ScienceDirect, 2022.

[5] P. Dhanoa et al., "A Process Model for Dashboard Onboarding," Computer Graphics Forum, vol. 41, no. 3, Wiley Online Library, 2022.

[6] "A Survey on Annotations in Information Visualization: Empirical Insights, Applications, and Challenges," arXiv preprint, 2024.