

RaceDay — API Endpoint Plan

Part 1 routes are retained as the canonical design. The two `/api/profile/me` routes are compatibility aliases matching the Part 2 guide; they call the same own-profile actions and do not allow editing another user.

Method	Route	Description	Access
POST	<code>/api/auth/register</code>	Register Organiser/Participant	Public
POST	<code>/api/auth/login</code>	Authenticate and start session	Public
POST	<code>/api/auth/logout</code>	Clear current session	Logged in
GET	<code>/api/users/me</code>	View own profile	Any logged-in user
PUT	<code>/api/users/me</code>	Update own profile	Any logged-in user
GET	<code>/api/profile/me</code>	Compatibility alias for own profile	Any logged-in user
PUT	<code>/api/profile/me</code>	Compatibility alias for updating own profile	Any logged-in user
GET	<code>/api/events</code>	Browse/filter events	Public
GET	<code>/api/events/mine</code>	View own events	Organiser
GET	<code>/api/events/{id}</code>	View event and categories	Public
POST	<code>/api/events</code>	Create event	Organiser
PUT	<code>/api/events/{id}</code>	Update own event	Organiser owner
DELETE	<code>/api/events/{id}</code>	Delete own event	Organiser owner
GET	<code>/api/events/{id}/categories</code>	List event categories	Public
POST	<code>/api/events/{id}/categories</code>	Add category	Organiser owner
PUT	<code>/api/categories/{id}</code>	Update category	Organiser owner
DELETE	<code>/api/categories/{id}</code>	Delete category	Organiser owner
POST	<code>/api/enrolments</code>	Enrol in category	Participant
GET	<code>/api/enrolments/me</code>	View own enrolments	Participant
PUT	<code>/api/enrolments/{id}/status</code>	Update enrolment status	Organiser owner
DELETE	<code>/api/enrolments/{id}</code>	Cancel own enrolment	Participant
GET	<code>/api/events/{id}/enrolments</code>	View event enrolments	Organiser owner
POST	<code>/api/results</code>	Capture result	Organiser owner
GET	<code>/api/results/me</code>	View own results	Participant
GET	<code>/api/events/{id}/results</code>	View event results	Organiser owner
GET	<code>/api/events/{id}/weather</code>	View weather/route info	Public
POST	<code>/api/events/{id}/weather</code>	Create/update weather/route info	Organiser owner

Role enforcement: protected endpoints use the server-side session to identify UserId and Role. Organiser actions also verify ownership of the parent Event. Participant actions verify the logged-in participant owns the requested enrolment/result.