Exam-1

ST115

First name: _____ Last name: _____

I hereby state that I have not communicated with or gained information in any way from my classmates during this exam, and that all work is my own.

Signature: _____

Any potential violation of NC State's policy on academic integrity will be reported to the Office of Student Conduct & Community Standards. All work on this exam must be your own.

1. You have 75 minutes to complete the exam.
2. Every MC question is worth 3-points unless otherwise specified.
3. Every True/False question is worth 2-points unless otherwise specified.
4. You are **not** allowed a cell phone, even if you intend to use it for checking the time, music device or headphones, notes, books, or other resources, or to communicate with anyone other than the professor during the exam.
5. Please answer exactly and only what the question is asking.

Good luck!

Matching: Git and GitHub (8-points)

Match each Git/GitHub command with its correct definition. Write the corresponding number on the blank next to the correct definition.

Command	Definition
1. Push	_____ Moves changes from your local repository to GitHub.
2. Pull	_____ Selects changes to be included in the next commit.
3. Stage	_____ Downloads changes from GitHub to your local repository.
4. Commit	_____ Records a set of changes in your local Git history.

1. **True or False** (2-points): When you open a project in RSTudio, you must make sure to run `install.packages()` every time to make sure your packages are downloaded and ready to use for that specific project.

a. True

b. False

2. **True or False** (2-points): When you open a project in RStudio, you must make sure to run `library()` every time to make sure your packages are opened and ready to use for that specific project.

a. True

b. False

3. What do you use to index elements in a data frame or vector (3-points)?

a. ()

b. []

c. {}

d. |>

4. **Fill in the blank** (4-points) : When you save an R-object with the _____ operator, you can see the R-object saved in the _____ tab in RStudio.

Reading Code (Rows & Columns: 10 points)

After all the NA values are removed from the data set, the classic penguins data set has 333 rows and 8 columns. Assume that all required packages were loaded/opened correctly. The breakdown of species can be seen below.

```
# A tibble: 3 x 2
  species       n
  <fct>     <int>
1 Adelie      146
2 Chinstrap    68
3 Gentoo      119
```

The name of the columns can be seen below.

```
[1] "species"           "island"            "bill_length_mm"
[4] "bill_depth_mm"     "flipper_length_mm" "body_mass_g"
[7] "sex"               "year"
```

Using this information, read the following the code below. Next, determine how many rows and columns EACH of the three new data sets would have. Label your answers rows = and columns = . If the code would give an error, state that instead and EXPLAIN why. One of the three will give an error.

a.

```
penguins |>
select(-body_mass_g) |>
filter(species != "Adelie")
```

b.

```
penguins |>
select(island) |>
filter(species == "Gentoo")
```

c.

```
penguins |>
arrange(desc(body_mass_g))
```

Catching Errors / Sloppy Code (21-points)

You receive the following R-code chunk from an AI model that is trying to answer the following research questions using the `mtcars` dataset:

1. Do cars with more than 6 cylinders have better fuel efficiency than cars with 6 or fewer cylinders?
2. Do cars with manual transmissions have a higher average MPG than cars with automatic transmissions?

However, you notice that this code has a ton of mistakes. A mistake is defined as sloppy / unnecessary code; code that doesn't pertain to the research question; improper code that produces an error.

There are **at least** 7 mistakes in the following code-chunk that fit this criteria. Your job is to:

1. Number the mistakes you identify with a number and a circle around the number ex. (1)
2. In **ONE** sentence next to the number, explain why this is a mistake.

Here is a data table to help answer your question:

Variable	Description
`mpg`	Miles per gallon (in mpg)
`cyl`	Number of cylinders
`am`	Transmission type: `0` = automatic, `1` = manual
`hp`	Horsepower

```
# Question 1

library(tidyverse)

mtcars2 <- mtcars |>
  filter(cyl > 6) |>
  mutate(mpg = mpg * 1.609) |>
  summarize(
    mean_mpg = mean(mpg),
    n = n
  )

# Question 2

library(dplyr)

mtcars |>
  mutate(
    transmission = ifelse(am = 1, "Manual", "Automatic")
  ) |>
  group_by(transmission) |>
  summarize(
    average_mpg = mean(mpg),
    average_hp = mean(hp)
  ) |>
  arrange(desc(average_hp))
```

Miscellaneous (17-points)

1. In one sentence, define what the following code chunk options do when they are correctly used in a R-code chunk (6-points).


a. `#| echo: false` -

b. `#| eval: false` -

2. I'm claiming that the following table is a valid example of a data frame in R. Critique this claim. If you disagree, explain why AND explain how you would change/add/include with the data to make it a data frame (6-points).

Student_Name	Section_Number	Quiz_Score
John Doe	1	88
Dylan Michaels	2	94
Kyle McKee	2	93
Peverel Shipley		91
Wen Seng		

Please see the following image. In 2-3 sentences, explain when these statuses appear. Be as detailed as possible (5-points).



ifelse (10-points)

The following code chunk is from the penguins dataset and the table is an example of the possible output with some values missing.

```
penguins$size <- ifelse(penguins$body_mass_g > 50, "Big", "Small")
```

Using the above code, fill in the missing values in the table. HINT: For the last blank, fill in an example of what that body mass could be.

species	body_mass_g	_____
Adelie	40.6	_____
Gentoo	53.4	_____
Adelie	51.8	_____
Chinstrap	_____	Small

function-writing (9-points)

Please see the following function:

```
calculate_total <- function(x, y) {
  total <- x + y
  total
}

calculate_total(x = 5, y = 10)
```

Based on the code above, write the correct response in the following _____.

– Function name: _____

– Argument(s): _____

– Values of the argument(s): _____

– Returned value(s): _____

YAML (6-points)

1. **True or False**: A YAML is appropriate in either a .R file or a .qmd file.

a. True

b. False

2. **True or False**: A YAML is space-sensitive (spacing / indentation matter).

a. True

b. False

Forms and Joins (20-points)

Please see the following output for a data frame called scores:

```
  student  quiz score
1    Alex Quiz1     8
2    Alex Quiz2    10
3   Blair Quiz1     9
4   Blair Quiz2     8
5   Casey Quiz1     7
6   Casey Quiz2     9
```

First, justify if these data are wide or long format. Next, rewrite the data above to be in the other format. Include appropriate column names and all observations.

2. Now, suppose your colleague has a second data set (student_info), and they want to join it with the **original** scores data set in question 1 (not your answer to question-1).

```
  student       major
1    Alex  Statistics
2   Blair     Biology
3   Dylan Mathematics
```

To do this, they write the following code.

```
inner_join(scores, student_info)
```

Fill in the table below to match the result of the code above. Note: There may be additional rows/columns in the template. If so, leave them blank/empty for the purpose of this problem. Include the appropriate column names.
