

EL5: Reproducibility

Reproducible analysis and {targets}

Reading

- M. Baker [1] and R. de Oliveira Andrade [2] motivates why reproducible analysis is important!
- R. D. Peng and S. C. Hicks [3] introduce and elaborate more on the subject.
- A. Nguyen [4] only read section “Basic Introduction to Docker and Containers” in chapter 2 (but you do not need to install Docker for this course)

💡 Consider

- After reading papers like these, one might be tempted to conclude that nothing is trustworthy – not even our own analyses. If every result comes with assumptions, uncertainty, and potential bias, what does trust really mean? Statisticians live in a world of probabilities, but most people prefer certainty.
- Reproducibility might sound like a good thing but how much does the technical details matter if we are not allowed to freely share the underlying health care data anyway?

For reference:

- [Targets overview](#)
- [Target manual](#)

Practice

A workshop with 7 parts was given at the R Medicine conference 2025. Practice according to part 1-3 (part 4-7 are slightly outside the scope of the course and only recommended if you have additional time and interest).

Clone [this GitHub repo](#). Exercises are found in the code folder.

Follow the recording from the workshop while you are practicing: [The power of {targets} package for reproducible data science](#)

i Notes on the recording

- The full video is close to three hours long, but this includes breaks as well as the more advanced topics that are not mandatory (only the first 92 minutes, which includes several 10 min breaks is mandatory). Nevertheless, it is recommended to watch the full video (just watching part 4-7 for inspirational purposes without doing the exercises and without any expectation to fully grasp all the details).
- RStudio is used in the recording. Please try to use Positron; however, feel free to revert to RStudio this time if following the instructions in one application while working in another feels overwhelming.
- You may recognise some of the material from Part 3, as presented during the lecture

This practice is homework (no dedicated computer session is targeting targets but you should use at least some components of it in a later project, so you should practice the basics now!)

An article about computational science in a scientific publication is not the scholarship itself, it is merely advertising of the scholarship. The actual scholarship is the complete software development environment and the complete set of instructions which generated the figures. / Buckheit & Donoho

[...] importance of having a clear understanding of how data analysis was conducted when critical life and death decisions must be made. / Peng et al. 2021

Reproducible analysis


The definition of reproducible research generally consists of the following elements.

A published data analysis is reproducible if the analytic data sets and the computer code used to create the data analysis are made available to others for independent study and analysis


This is rather vague ...

Why is this a problem?

- Many, even simple, results depend on a precise record of procedures and processing and the order in which they occur.
- Many statistical algorithms have many tuning parameters that can dramatically change the results if they are not inputted exactly the same way as was done by the original investigators.
- If any of these myriad details are not properly recorded in the code, then there is a significant possibility that the results produced by others will differ from the original investigators' results.



How do we *ensure* end to end reproducibility?



Recap folder structure

```
../../my_project/
├─ README.md      - project documentation
├─ TODO           - what should be done next?
├─ .git           - handled by git (hidden folder)
├─ .gitignore     - used by git but your responsibility!
├─ data/          - your data files (not under version control!)
│   ├── cancer.csv
│   └── patients.qs
├─ R/             - your saved R functions
│   ├── function1.R
│   └── function2.R
├─ reports/
└─ _targets.R     - targets pipeline script
```

Pipeline

- A pipeline is a computational workflow that does statistics, analytics, or data science.
- A pipeline contains tasks to prepare datasets, run models, and summarize results for a business deliverable or research paper.
- Pipeline tools coordinate the pieces of computationally demanding analysis projects.

Long running processes

- Imagine you have nice R-scripts to take care of every step in your project
- You have either one very very ... very long file or a bunch of files which you execute in order
- It takes two weeks to run all the scripts (not unrealistic for a big project!)

- You report the result to your collaborators
- They ask you to update a tiny detail somewhere in the middle of your workflow
- You need to rerun everything (while you're screaming in frustration)!
- This will repeat again and again until you finally
 - a) Lose your mind and quit your job
 - b) Adapt a more reproducible workflow

Steps-wise procedure

- The default setting in R is to save the workspace to disk when you end the session
- This is usually not recommended and therefore often disabled in for example RStudio
 - (If you re-start your session at a later point you might have no idea how the restored objects relates to each other.)
- You may still want to execute things in a more step-wise fashion
 1. Convert big data files to something R-friendly
 2. Perform some data management (select relevant columns and rows), cleaning, add calculated variables etc
 3. Perform some exploratory data analysis (EDA) to get a better understanding of the data
 4. Perform some statistical analysis
 5. Report and visualize the results

Caching

- If you perform each step in different script files, you might start each file with some input and end it with some output
- The output from the previous script is used as input in the next script
- `save()` and `load()` are standard but can be very slow for large objects
- `saveRDS()` and `loadRDS()` use serialization and are nowadays much more efficient
- `qs2::qs_save()` and `qs2::qs_read()` (or `qs2::qd_save()` and `qs2::qd_read()`) from the [qs2 package](#) are currently “state-of-the-art” (but things tend to change quickly)

Benchmarking

Single-threaded

Algorithm	Compression	Save Time (s)	Read Time (s)
qs2	7.96	13.4	50.4
qdata	8.45	10.5	34.8
base::serialize	1.1	8.87	51.4
saveRDS	8.68	107	63.7
fst	2.59	5.09	46.3
parquet	8.29	20.3	38.4
qs (legacy)	7.97	9.13	48.1

Multi-threaded (8 threads)

Algorithm	Compression	Save Time (s)	Read Time (s)
qs2	7.96	3.79	48.1
qdata	8.45	1.98	33.1
fst	2.59	5.05	46.6
parquet	8.29	20.2	37.0
qs (legacy)	7.97	3.21	52.0

- qs2, qdata and qs with `compress_level = 3`
- parquet via the arrow package using `zstd compression_level = 3`
- `base::serialize` with `ascii = FALSE` and `xdr = FALSE`

Datasets used

- 1000 genomes non-coding VCF 1000 genomes non-coding variants (2743 MB)
- B-cell data B-cell mouse data, Greiff 2017 (1057 MB)
- IP location IPV4 range data with location information (198 MB)
- Netflix movie ratings Netflix ML prediction dataset (571 MB)

These datasets are openly licensed and represent a combination of numeric and text data across multiple domains. See `inst/analysis/datasets.R` on Github.

Who cares?

- Imagine you work with data for the whole population (> 10 M people)
- You have medical prescription data for everyone and lets say on average 20 prescriptions (since 2015) per person $\Rightarrow 10 * 20 = 200$ M rows of data
- You are working in a secure environment where data is stored on a network server (no HDD drive)
- The same environment is shared by 20 other researchers and you are all competing for the same band-width
- It will get increasingly frustrating just to load and save the big files
- You might need to wait for half an hour before you can start working

Automated process

- Instead of relying on individual R scripts, use a reproducible pipeline.
- This is common practice in software development
 - For example GNU Make is a build automation tool that automatically determines which parts of a program need to be rebuilt and executes the necessary commands based on rules defined in a Makefile.
- Iteration during project development (which is equally relevant for a health data project), will be much faster and reliable.
- Caching as described above is automated and you only need to read/write files to disk/network storage when actually needed.

targets package

- The {targets} package is a Make-like pipeline tool for statistics and data science in R.
- The package skips costly runtime for tasks that are already up to date, orchestrates the necessary computation with implicit parallel computing, and abstracts files as R objects.
- If all the current output matches the current upstream code and data, then the whole pipeline is up to date, and the results are more trustworthy than otherwise.
- The tasks themselves are called “targets”, and they run the functions and return R objects.
- The targets package orchestrates the targets and stores the output objects to make your pipeline efficient, painless, and reproducible.

Example

Data: survey data collected by the US National Center for Health Statistics (NCHS) which has conducted a series of health and nutrition surveys since the early 1960's. Since 1999 approximately 5,000 individuals of all ages are interviewed in their homes every year and complete the health examination component of the survey. The health examination is conducted in a mobile examination centre (MEC).

Question: Is there any association between gender and BMI?

```
# pak::pkg_install("NHANES")
str(NHANES::NHANES)
```

```
Classes 'tbl_df', 'tbl' and 'data.frame':  10000 obs. of  76 variables:
 $ ID          : int  51624 51624 51624 51625 51630 51638 51646 51647
51647 51647 ...
 $ SurveyYr    : Factor w/ 2 levels "2009_10","2011_12": 1 1 1 1 1 1 1 1
1 ...
 $ Gender      : Factor w/ 2 levels "female","male": 2 2 2 2 1 2 2 1
1 ...
 $ Age         : int   34 34 34 4 49 9 8 45 45 45 ...
 $ AgeDecade   : Factor w/ 8 levels " 0-9"," 10-19",...: 4 4 4 1 5 1 1 5
5 ...
 $ AgeMonths   : int   409 409 409 49 596 115 101 541 541 541 ...
 $ Race1       : Factor w/ 5 levels "Black","Hispanic",...: 4 4 4 5 4 4 4 4
4 4 ...
 $ Race3       : Factor w/ 6 levels "Asian","Black",...: NA NA NA NA NA NA
NA NA NA NA ...
 $ Education   : Factor w/ 5 levels "8th Grade","9 - 11th Grade",...: 3 3 3
NA 4 NA NA 5 5 5 ...
 $ MaritalStatus : Factor w/ 6 levels "Divorced","LivePartner",...: 3 3 3 NA
2 NA NA 3 3 3 ...
 $ HHIncome    : Factor w/ 12 levels " 0-4999"," 5000-9999",...: 6 6 6 5 7
11 9 11 11 11 ...
 $ HHIncomeMid  : int   30000 30000 30000 22500 40000 87500 60000 87500
```

```

87500 87500 ...
$ Poverty      : num  1.36 1.36 1.36 1.07 1.91 1.84 2.33 5 5 5 ...
$ HomeRooms    : int   6 6 6 9 5 6 7 6 6 6 ...
$ HomeOwn      : Factor w/ 3 levels "Own","Rent","Other": 1 1 1 1 2 2 1 1
1 1 ...
$ Work         : Factor w/ 3 levels "Looking","NotWorking",...: 2 2 2 NA 2
NA NA 3 3 3 ...
$ Weight       : num   87.4 87.4 87.4 17 86.7 29.8 35.2 75.7 75.7 75.7 ...
$ Length       : num   NA NA NA NA NA NA NA NA NA NA ...
$ HeadCirc     : num   NA NA NA NA NA NA NA NA NA NA ...
$ Height       : num   165 165 165 105 168 ...
$ BMI          : num   32.2 32.2 32.2 15.3 30.6 ...
$ BMICatUnder20yrs: Factor w/ 4 levels "UnderWeight",...: NA NA NA NA NA NA NA
NA NA NA ...
$ BMI_WHO      : Factor w/ 4 levels "12.0_18.5","18.5_to_24.9",...: 4 4 4 1
4 1 2 3 3 3 ...
$ Pulse        : int   70 70 70 NA 86 82 72 62 62 62 ...
$ BPSysAve     : int   113 113 113 NA 112 86 107 118 118 118 ...
$ BPDiaAve     : int   85 85 85 NA 75 47 37 64 64 64 ...
$ BPSys1       : int   114 114 114 NA 118 84 114 106 106 106 ...
$ BPDia1       : int   88 88 88 NA 82 50 46 62 62 62 ...
$ BPSys2       : int   114 114 114 NA 108 84 108 118 118 118 ...
$ BPDia2       : int   88 88 88 NA 74 50 36 68 68 68 ...
$ BPSys3       : int   112 112 112 NA 116 88 106 118 118 118 ...
$ BPDia3       : int   82 82 82 NA 76 44 38 60 60 60 ...
$ Testosterone : num   NA NA NA NA NA NA NA NA NA NA ...
$ DirectChol   : num   1.29 1.29 1.29 NA 1.16 1.34 1.55 2.12 2.12 2.12 ...
$ TotChol      : num   3.49 3.49 3.49 NA 6.7 4.86 4.09 5.82 5.82 5.82 ...
$ UrineVol1     : int   352 352 352 NA 77 123 238 106 106 106 ...
$ UrineFlow1    : num   NA NA NA NA 0.094 ...
$ UrineVol2     : int   NA NA NA NA NA NA NA NA NA NA ...
$ UrineFlow2    : num   NA NA NA NA NA NA NA NA NA NA ...
$ Diabetes      : Factor w/ 2 levels "No","Yes": 1 1 1 1 1 1 1 1 1 1 ...
$ DiabetesAge   : int   NA NA NA NA NA NA NA NA NA NA ...
$ HealthGen     : Factor w/ 5 levels "Excellent","Vgood",...: 3 3 3 NA 3 NA
NA 2 2 2 ...
$ DaysPhysHlthBad : int   0 0 0 NA 0 NA NA 0 0 0 ...
$ DaysMentHlthBad : int   15 15 15 NA 10 NA NA 3 3 3 ...
$ LittleInterest : Factor w/ 3 levels "None","Several",...: 3 3 3 NA 2 NA NA
1 1 1 ...
$ Depressed     : Factor w/ 3 levels "None","Several",...: 2 2 2 NA 2 NA NA
1 1 1 ...
$ nPregnancies  : int   NA NA NA NA 2 NA NA 1 1 1 ...
$ nBabies       : int   NA NA NA NA 2 NA NA NA NA NA ...
$ Age1stBaby    : int   NA NA NA NA 27 NA NA NA NA NA ...
$ SleepHrsNight : int   4 4 4 NA 8 NA NA 8 8 8 ...
$ SleepTrouble  : Factor w/ 2 levels "No","Yes": 2 2 2 NA 2 NA NA 1 1 1 ...
$ PhysActive    : Factor w/ 2 levels "No","Yes": 1 1 1 NA 1 NA NA 2 2 2 ...

```



```

$ PhysActiveDays : int  NA NA NA NA NA NA NA NA 5 5 5 ...
$ TVHrsDay       : Factor w/ 7 levels "0_hrs","0_to_1_hr",...: NA NA NA NA NA
NA NA NA NA NA ...
$ CompHrsDay     : Factor w/ 7 levels "0_hrs","0_to_1_hr",...: NA NA NA NA NA
NA NA NA NA NA ...
$ TVHrsDayChild  : int   NA NA NA 4 NA 5 1 NA NA NA ...
$ CompHrsDayChild: int   NA NA NA 1 NA 0 6 NA NA NA ...
$ Alcohol12PlusYr: Factor w/ 2 levels "No","Yes": 2 2 2 NA 2 NA NA 2 2 2 ...
$ AlcoholDay     : int   NA NA NA NA 2 NA NA 3 3 3 ...
$ AlcoholYear    : int   0 0 0 NA 20 NA NA 52 52 52 ...
$ SmokeNow       : Factor w/ 2 levels "No","Yes": 1 1 1 NA 2 NA NA NA NA
NA ...
$ Smoke100       : Factor w/ 2 levels "No","Yes": 2 2 2 NA 2 NA NA 1 1 1 ...
$ Smoke100n      : Factor w/ 2 levels "Non-Smoker","Smoker": 2 2 2 NA 2 NA
NA 1 1 1 ...
$ SmokeAge       : int   18 18 18 NA 38 NA NA NA NA NA ...
$ Marijuana      : Factor w/ 2 levels "No","Yes": 2 2 2 NA 2 NA NA 2 2 2 ...
$ AgeFirstMarij  : int   17 17 17 NA 18 NA NA 13 13 13 ...
$ RegularMarij   : Factor w/ 2 levels "No","Yes": 1 1 1 NA 1 NA NA 1 1 1 ...
$ AgeRegMarij    : int   NA NA NA NA NA NA NA NA NA NA ...
$ HardDrugs      : Factor w/ 2 levels "No","Yes": 2 2 2 NA 2 NA NA 1 1 1 ...
$ SexEver        : Factor w/ 2 levels "No","Yes": 2 2 2 NA 2 NA NA 2 2 2 ...
$ SexAge         : int   16 16 16 NA 12 NA NA 13 13 13 ...
$ SexNumPartnLife: int   8 8 8 NA 10 NA NA 20 20 20 ...
$ SexNumPartYear : int   1 1 1 NA 1 NA NA 0 0 0 ...
$ SameSex        : Factor w/ 2 levels "No","Yes": 1 1 1 NA 2 NA NA 2 2 2 ...
$ SexOrientation : Factor w/ 3 levels "Bisexual","Heterosexual",...: 2 2 2 NA
2 NA NA 1 1 1 ...
$ PregnantNow    : Factor w/ 3 levels "Yes","No","Unknown": NA NA NA NA NA
NA NA NA NA NA ...

```

R script

A normal R script might look like:

```

# pak::pkg_install("NHANES")
library(tidyverse)

```

```

— Attaching core tidyverse packages ————— tidyverse 2.0.0
—
✓ dplyr      1.1.4      ✓ readr      2.1.6
✓ forcats    1.0.1      ✓ stringr    1.6.0
✓ ggplot2    4.0.1      ✓ tibble     3.3.1
✓ lubridate  1.9.4      ✓ tidyr      1.3.2
✓ purrr      1.2.1
— Conflicts ————— tidyverse_conflicts()
—

```


```
* dplyr::filter() masks stats::filter()
* dplyr::lag() masks stats::lag()
i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all
conflicts to become errors
```

```
df <- as_tibble(NHANES::NHANES)
tbl <- count(df, Gender)
tst <- t.test(BMI ~ Gender, df)
gg <- ggplot(df, aes(BMI, color = Gender)) + geom_density()
```

- You must run the script in order (but might not always do that) ... if so, confusion will arise!
- objects df, tbl and tst only lives in the active session
 - No problem in this example
 - but working with big and complex data might introduce long-running processes => time consuming!

Results

```
Warning: Removed 366 rows containing non-finite outside the scale range
(`stat_density()`).
```



Welch Two Sample t-test

```

data: BMI by Gender
t = 1.4981, df = 9452.6, p-value = 0.1341
alternative hypothesis: true difference in means between group female and
group male is not equal to 0
95 percent confidence interval:
 -0.06939849  0.51940903
sample estimates:
mean in group female    mean in group male
      26.77208           26.54707

```

Pipeline

- Define steps in your analysis as targets
 - Define dependencies between targets
 - Automatically track changes and rerun only necessary parts
-

Why?

- You do not want to rerun everything all the time!
- You want to keep track of what you have done
- You want to be able to reproduce your results later
- You want to share your workflow with others

target

Reformulate from ordinary object assignment:

```
df <- as_tibble(NHANES::NHANES)
```

to a target

```
library(targets)
tar_target(df, as_tibble(NHANES::NHANES))
```

```

<tar_stem>
  name: df
  description:
  command:
    as_tibble(NHANES::NHANES)
  format: rds
  repository: local
  iteration method: vector
  error mode: stop
  memory mode: auto
  storage mode: worker

```

```

retrieval mode: auto
deployment mode: worker
priority: 0
resources:
  list()
cue:
  seed: TRUE
  file: TRUE
  iteration: TRUE
  repository: TRUE
  format: TRUE
  depend: TRUE
  command: TRUE
  mode: thorough
packages:
  targets
  lubridate
  forcats
  stringr
  dplyr
  purrr
  readr
  tidyr
  tibble
  ggplot2
  tidyverse
  stats
  graphics
  grDevices
  utils
  datasets
  methods
  base
library:
  NULL

```

Put all targets in a list

```

list(
  tar_target(df, as_tibble(NHANES::NHANES)),
  tar_target(tbl, count(df, Species)),
  tar_target(tst, t.test(BMI ~ Gender, df)),
  tar_target(gg, {
    ggplot(df, aes(BMI, color = Gender)) + geom_density()
  })
)

```

_targets.R file

Put that list into a file `_targets.R` together with some additional code:

```
library(targets)
tar_source() # Source all scripts with function stored in R folder
```

```
tar_source(): these files do not exist: R
```


```
tar_option_set(
  # Specify all needed packages here
  packages = c("tidyverse"),
  # Format used for caching (qs or actually qs2 is best for big data)
  format = "qs",
  # Additional settings ...
  seed = 123
)

list(
  tar_target(df, as_tibble(NHANES:NHANES)),
  tar_target(tbl, count(df, Species)),
  tar_target(tst, t.test(BMI ~ Gender, df)),
  tar_target(gg, {
    ggplot(df, aes(BMI, color = Gender)) + geom_density()
  })
)
```

Benefits

- execute the whole project by `tar_make()`
- intermediate steps are cached and cached objects retrieved by `tar_load()` or `tar_read()`
- dependency among individual steps can be visualized: `tar_visnetwork()`

Dependency graph



Live show

```
cd
git clone https://github.com/STA220/targets.git
cd targets
positron .
```

Or perform those steps from within Positron.

Different R-versions

- Imagine you finish your research project and you submit a manuscript to a journal
- The journal comes back one year later (they didn't have time until now) and one reviewer asks you to double check some steps of the analysis
- You make some modifications and rerun your pipelines.
- But it doesn't work!
- Half a year ago you updated your R installation and a week ago all of your installed packages.

- One package was retired from CRAN (could happen even though there was nothing wrong with the package when you used it)
- One package has deprecated one of the functions you previously used
- One package has redesigned the output format from a specific function you used
- 🤖



renv

Overview

The `renv` package¹ helps you create reproducible **environments** for your R projects. Use `renv` to make your R projects more isolated, portable and reproducible.

- **Isolated:** Installing a new or updated package for one project won't break your other projects, and vice versa. That's because `renv` gives each project its own private library.
- **Portable:** Easily transport your projects from one computer to another, even across different platforms. `renv` makes it easy to install the packages your project depends on.
- **Reproducible:** `renv` records the exact package versions you depend on, and ensures those exact versions are the ones that get installed wherever you go.

Pros and cons

- It is always a good idea to be able to reproduce exactly what you did!
- But if you never update you might miss essential bug fixes.
- If your results change, how can you know which version was the most accurate?

Best practice to rerun the analysis both with the frozen versions and with the most up-to-date versions of the packages ... because you have all the time in the world and nothing more important to do right ... 😂

Different operating systems

- R should behave similar on different operating systems.

- Exceptions nevertheless exist!
 - `parallel::mclapply()` behaves differently on Windows compared to Unix-like systems because Windows does not support forked processes.
 - `sort(c("ä", "a", "z"))` might differ due to locale settings

 **Rocker Project**

HomeCode of ConductImages ▾Use ▾



The Rocker Project

Docker Containers for the R Environment

 **Getting Started**

Ensure you have [Docker installed](#) and start R inside a container with:

```
docker run --rm -ti r-base
```

Combining all?

- you could very well use both targets + renv + git + GitHub etc
 - At some point you might start to wonder whether you are a medical statistician or a software developer ... and the more complex/esoteric tools you use, the more difficult it might be to collaborate with others
 - Try to find some middle ground ... but always be open to new ideas!
-

rix: Reproducible Environments with Nix



Links

[View on CRAN](#)

[Browse source code](#)

[Report a bug](#)

License

[Full license](#)

GPL (>= 3)

Community

[Contributing guide](#)

Citation

[Citing rix](#)

Developers

Bruno Rodrigues

Author, maintainer

Philipp Baumann

Author

- [Introduction](#)
- [Quick start for returning users](#)
- [Getting started for new users](#)
 - [Docker](#)
- [Why Nix? Comparison with Docker+renv/Conda/Guix](#)
- [Contributing](#)
- [Thanks](#)
- [Recommended reading](#)

Introduction

[rix](#) is an R package that leverages [Nix](#), a package manager focused on reproducible builds. With Nix, you can create project-specific environments with a custom version of R, its packages, and all system dependencies (e.g., GDAL). Nix ensures full reproducibility, which is crucial for research and development projects.

Use cases include running web apps (e.g., Shiny, [plumber](#) APIs) or [targets](#) pipelines with a controlled R environment. Unlike [renv](#), which snapshots package versions, [rix](#) provides an entire ecosystem snapshot, including system-level dependencies.



Bibliography

- [1] M. Baker, “1,500 scientists lift the lid on reproducibility,” *Nature*, vol. 533, no. 7604, pp. 452–454, May 2016, doi: [10.1038/533452a](https://doi.org/10.1038/533452a).
- [2] R. de Oliveira Andrade, “Huge reproducibility project fails to validate dozens of biomedical studies,” *Nature*, vol. 641, no. 8062, pp. 293–294, Apr. 2025, doi: [10.1038/d41586-025-01266-x](https://doi.org/10.1038/d41586-025-01266-x).

- [3] R. D. Peng and S. C. Hicks, “Reproducible Research: A Retrospective,” *Annual Review of Public Health*, vol. 42, no. Volume42, 2021, pp. 79–93, Apr. 2021, doi: [10.1146/annurev-publhealth-012420-105110](https://doi.org/10.1146/annurev-publhealth-012420-105110).
- [4] A. Nguyen, *Hands-on healthcare data: taming the complexity of real-world data*, First edition. Beijing Boston Farnham Sebastopol Tokyo: O'Reilly, 2022.