

TEXT MINING INTRO TO PYTHON

Mattias Villani, Johan Falkenjack

NLPLAB
Dept. of Computer and Information Science
Linköping University

OVERVIEW

- ▶ What is Python? How is it special?
- ▶ Python's objects
- ▶ If-else, loops and list comprehensions
- ▶ Functions
- ▶ Classes
- ▶ Modules

WHAT IS PYTHON?

- ▶ First version in 1991
- ▶ **High-level language**
- ▶ Emphasizes **readability**
- ▶ **Interpreted** (bytecode .py and .pyc) [can be compiled via C/Java]
- ▶ Automatic memory management
- ▶ Strongly dynamically typed
- ▶ **Functional and/or object-oriented**
- ▶ **Glue** to other programs (interface to C/C++ or Java etc)
- ▶ Popular in data science (“Prototype in R, implement in Python”)
- ▶ Two currently developed versions, 2.x and 3.x
 - ▶ This course uses Python 2.7

THE BENEVOLENT(?) DICTATOR FOR LIFE (BDFL) GUIDO VAN ROSSUM



PYTHON PECULIARITIES (COMPARED TO R/MATLAB)

- ▶ Not primarily a numerical language.
- ▶ **Indexing begins at 0**, as indexes refer to breakpoints between elements.
- ▶ It follows that `myVector[0:2]` returns the first and second element, but not the third.
- ▶ **Integer division** by default in 2.x. `from __future__ import division`.
- ▶ **Indentation matters!**
- ▶ Can import specific functions from a module.
- ▶ Assignment **by object**, **NOT by copy** or **by reference**.
 - ▶ Approximately, assignment **by copy of reference**.
- ▶ `a = b = 1` assigns 1 to both a and b.

PYTHON'S OBJECTS

- ▶ Built-in types: **numbers**, **strings**, **lists**, **dictionaries**, **tuples** and **files**.
- ▶ **Vectors**, **arrays** and **matrices** are available in the **numpy/scipy** modules.
- ▶ Python is a **strongly typed** language. `'johan' + 3` gives an error.
- ▶ Python is a **dynamically typed** language. No need to declare a variables type before it is used. Python figures out the object's type.
- ▶ Implication: Polymorphism by default:
 - ▶ “In other words, don't check whether it IS-a duck: check whether it QUACKS-like-a duck, WALKS-like-a duck, etc, etc, depending on exactly what subset of duck-like behaviour you need to play your language-games with.” - Alex Martelli

STRINGS

- ▶ `s = 'Spam'`
- ▶ `s[0]` returns first letter, `s[-2]` return next to last letter. `s[0:2]` returns first **two** letter.
- ▶ `len(s)` returns the number of characters.
- ▶ `s.lower()`, `s.upper()`, `s.count('m')`, `s.endswith('am')`,
...
- ▶ **Which methods are available for my object?** Try in Spyder: type `s.` followed by TAB.
- ▶ `+` operator **concatenates strings**.
- ▶ (behind the scenes: the string object has an `__add__` method:
`s.__add__(anotherString)`)
- ▶ `sentence = 'Guido is the benevolent dictator for life'.sentence.split()`
- ▶ `s*3` returns `'SpamSpamSpam'` supported and

THE LIST OBJECT

- ▶ A list is a **container of several variables**, possibly of different types.
- ▶ `myList = ['spam', 'spam', 'bacon', 2]`
- ▶ The list object has several associated **methods**
 - ▶ `myList.append('egg')`
 - ▶ `myList.count('spam')`
 - ▶ `myList.sort()`
- ▶ `+` operator concatenates lists: `myList + myOtherList` merges the two lists as one list.

THE LIST OBJECT

- ▶ Extract elements from a list: `myList[1]`
- ▶ Lists inside lists:
 - ▶ `myOtherList = ['monty', 'Python']`
 - ▶ `myList[1] = myOtherList`
 - ▶ `myList[1]` returns the list `['monty', 'Python']`
 - ▶ `myList[1][1]` returns the string `'Python'`

STRINGS AGAIN

- ▶ Strings are **immutable**, i.e. can't be changed after creation.
- ▶ Every “change” creates a new string.
- ▶ Try to avoid creating more strings than necessary:
 - ▶ Avoid: `my_string = 'Python ' + 'is ' + 'fun!'`
 - ▶ Instead: `' '.join(['Python', 'is', 'fun'])`
- ▶ In loops where you construct strings, add constituents to a list and join after loop finishes.

TUPLES

- ▶ `myTuple = (3,4,'johan')`
- ▶ **Like lists, but immutable**
- ▶ **Why?**
 - ▶ Faster than lists
 - ▶ Protected from change
 - ▶ Can be used as keys in dictionaries
 - ▶ Multiple return object from function
 - ▶ Swapping variable content `(a, b) = (b, a)` (`[a,b = b,a]` also works)
 - ▶ String formatting: `name = "Johan"; age = 30; "My name is %s and I am %d years old" % (name , age)`
 - ▶ Sequence unpacking `a , b, c = myTuple`
- ▶ `list(myTuple)` returns `myTuple` as a list. `tuple(myList)` does the opposite.

VECTORS AND ARRAYS (AND MATRICES)

- ▶ `from scipy import *`
- ▶ `x = array([1,7,3])`
- ▶ 2-dimensional **array** (matrix): `X = array([[2,3],[4,5]])`
- ▶ **Indexing arrays**
 - ▶ First row: `X[0,]`
 - ▶ Second column: `X[:,1]`
 - ▶ Element in position 1,2: `X[0,1]`
- ▶ Array **multiplication** (*) is element-wise, for matrix multiplication use `dot()`.
- ▶ There is also a **matrix object**: `X = matrix([[2,3],[4,5]])`
 - ▶ **Arrays are preferred** (not matrices).
- ▶ Submodule **scipy.linalg** contains a lot of **matrix-functions** applicable to arrays (`det()`, `inv()`, `eig()` etc). I recommend: `from scipy.linalg import *`

DICTIONARIES

- ▶ **Unordered** collection of objects (elements).
- ▶ `myDict = {'Sarah':29, 'Erik':28, 'Evelina':26}`
- ▶ Elements are **accessed by keyword not by index** (offset):
`myDict['Evelina']` returns 26.
- ▶ **Values can contain any object**: `myDict = {'Marcus':[23,14], 'Cassandra':17, 'Per':[12,29]}`. `myDict['Marcus'][1]` returns 14.
- ▶ Any immutable object can be a key: `myDict = {2:'contents of box2', (3, 'a'):'content of box 4', 'blackbox':10}`
- ▶ `myDict.keys()`
- ▶ `myDict.values()`
- ▶ `myDict.items()`

SETS

- ▶ **Set.** Contains objects in **no order** with **no identification**.
 - ▶ With a **sequence**, elements are ordered and identified by position.
`myVector[2]`
 - ▶ With a **dictionary**, elements are unordered but identified by some key.
`myDict['myKey']`
 - ▶ With a **set**, elements stand for themselves. No indexing, no key-reference.
- ▶ Declaration: `fib=set((1,1,2,3,5,8,13))` returns the set `([1, 2, 3, 5, 8, 13])`
- ▶ Supported methods: `len(s)`, `x in s`, `set1 < set2`, `union`, `intersection`, `add`, `remove`, `pop` ...

BOOLEAN OPERATORS

- ▶ True/False
- ▶ and
- ▶ or
- ▶ not
- ▶ `a = True; b = False; a and b` [returns False].

IF-ELSE CONSTRUCTS

IF-ELSE STATEMENT

```
a = 1
if a == 1:
    print('a is one')
elif a == 2:
    print('a is two')
else:
    print('a is not one or two')
```

- **Switch statements** via dictionaries (see Jackson's Python book).

WHILE LOOPS

WHILE LOOP

```
a =10
while a>1:
    print('bigger than one')
    a = a - 1
else:
    print('smaller than one')
```

FOR LOOPS

- ▶ **for loops** can iterate over any iterable.
- ▶ **iterables**: strings, lists, tuples

FOR LOOP

```
word = 'mattias'
for letter in word:
    print(letter)
myList = ['']*10
for i in range(10):
    myList = 'mattias' + str(i)
```

LIST COMPREHENSIONS

- ▶ As in R, loops can be slow. For small loops executed many times, try list comprehensions:
- ▶ Set definition in mathematics

$$\{x \text{ for } x \in \mathcal{X}\}$$

where \mathcal{X} is some a finite set.

$$\{f(x) \text{ for } x \in \mathcal{X}\}$$

- ▶ List comprehension in Python:
 - ▶ `myList = [x for x in range(10)]`
 - ▶ `myList = [sin(x) for x in range(10)]` (don't forget `from math import sin`)
 - ▶ `myList = [x + y for x in linspace(0.1,1,10) for y in linspace(10,100,10)]` (from `scipy import linspace`)

DEFINING FUNCTIONS AND CLASSES

DEFINING FUNCTIONS

```
def mySquare(x):  
    return x**2
```

- ▶ Calling the function: `mySquare(x)`
- ▶ Instance functions in classes are defined similarly using the `self` reference.
- ▶ Make you own module by putting several functions in a `.py` file. Then import what you need.

- ▶ Comments on individual lines starts with #
- ▶ Doc-strings can be used as comments spanning over multiple lines but this should be avoided `"""This is a looooong comment"""`