

STRETCH

CEILINGS & WALLS

STRETCH Acoustic - 495D

STRETCH BV

Gentseweg 309 A3
9120 Beveren-Waas
Belgium

VAT: BE 0675.875.709

Mail: info@stretchgroup.be
Tel: +32 3 284 68 18
www.stretchplafond.be



Acoustic classification	αs= 1; Rating: A
Composition	Polyester knitted fabric coated with polyurethane (PU)
Width	200cm / 300cm / 400cm / 515cm
Weight	245 gr/m2, +/- 10%
Thickness	0,4mm
Appearance	Matt, smooth and uniform
Colour	0001/0002/1001/9999
Strength	5 times greater than PVC film, doesn't crack CH : 5,5 daN; TR : 7,5 daN
Fire rating	B-s1,d0
Packaging	Cut to measure, In roll (50m)
Warranty	10 Year*
Reference	Net width
49521 DD or DR	200cm
49531 DD or DR	300cm
49541 DD or DR	400cm
49552 DD or DR	515cm



Anti Bacterial



Anti Static



UV Resistant



Water Resistant



Light Weight



Breathable



Long Lasting



Eco Friendly



Printable

*according to Stretch standard terms of sale

certifié / certified
zertifiziert / заверено
certificado / certificato
ISO 9001 : 2008



certifié / certified
zertifiziert / заверено
certificado / certificato



STRETCH

CEILINGS & WALLS

Acoustic performance

	THK	o.d.s. mm	α_p Pratical sound absorption coefficient						α_W	Sound absorbtion class
	mm		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz		
495AC D2040	40	200	0.30	0.80	0.80	0.75	0.75	0.65	0.75	C
495AC D2050	50	55	0.25	0.70	1.00	1.00	0.95	0.90	0.95	A
495AC D4010	10	10	0.15	0.30	0.45	0.60	0.85	0.95	0.50	D
495D D2040	40	200	0.30	0.85	0.95	0.85	0.95	0.90	0.95	A
495D D2020	20	200	0.20	0.70	0.90	0.75	0.90	0.90	0.85	B
495D	0	155	0.15	0.35	0.65	0.60	0.55	0.60	0.60	C
495D D2050	50	55	0.25	0.75	1.00	1.00	0.95	0.90	1.00	A
495D D4010	10	10	0.15	0.25	0.50	0.70	0.90	0.95	0.50	D

Maintenance

STRETCH technical fabrics are polyester fabrics coated with polyurethane, which under most circumstances protects them from absorbing odours. STRETCH fabrics are hydrophobic and require little or no maintenance.

If cleaning is required, it is recommended to use the STRETCH Cleaner and the STRETCH cleaning glove or a non-abrasive soft cloth in a white color. The method to follow is:

1. Spray some STRETCH Cleaner on the glove and dab the area immediately.
2. If the stain persists, it is possible to repeat the operation several times.
3. Alternatively, other pH-neutral cleaning agents can be used with a soft white cloth, provided it has first been tested on a scrap piece or on a non-visible area of the fabric.

Under no circumstance should sodium hypochlorite based solutions (bleach) be used.