

STRETCH

CEILINGS & WALLS

STRETCH Standard - 705S

STRETCH BV

Gentseweg 309 A3
9120 Beveren-Waas
Belgium

VAT: BE 0675.875.709

Mail: info@stretchgroup.be
Tel: +32 3 284 68 18
www.stretchplafond.be



Composition	Polyester knitted fabric coated with polyurethane (PU)
Width	200cm / 250cm / 320cm / 400cm / 450cm / 515cm
Weight	245 gr/m2, +/- 10%
Thickness	0,4mm
Appearance	Matt, smooth and uniform
Colour	Matt, smooth and uniform
Strength	5 times greater than PVC film, doesn't crack CH : 5,5 daN; TR : 7,5 daN
Fire rating	B-s1,d0
Packaging	Cut to measure, In roll (50m)
Warranty	10 Year*
Reference	Net width
721 SD or SR	200cm
726 SD or SR	250cm
733 SD or SR	320cm
741 SD or SR	400cm
746 SD or SR	450cm
752 SD or SR	515cm



Anti Bacterial



Anti Static



UV Resistant



Water Resistant



Light Weight



Breathable



Long Lasting



Eco Friendly



Printable

*according to Stretch standard terms of sale

certifié / certified
zertifiziert / заверено
certificado / certificato
ISO 9001 : 2008



certifié / certified
zertifiziert / заверено
certificado / certificato



STRETCH

CEILINGS & WALLS

Maintenance

STRETCH technical fabrics are polyester fabrics coated with polyurethane, which under most circumstances protects them from absorbing odours. STRETCH fabrics are hydrophobic and require little or no maintenance.

If cleaning is required, it is recommended to use the STRETCH Cleaner and the STRETCH cleaning glove or a non-abrasive soft cloth in a white color. The method to follow is:

1. Spray some STRETCH Cleaner on the glove and dab the area immediately.
2. If the stain persists, it is possible to repeat the operation several times.
3. Alternatively, other pH-neutral cleaning agents can be used with a soft white cloth, provided it has first been tested on a scrap piece or on a non-visible area of the fabric.

Under no circumstance should sodium hypochlorite based solutions (bleach) be used.