

STRETCH Non Flamable - Standard

VAT: BE 0675.875.709

Mail: info@stretchgroup.be
Tel: +32 3 284 68 18
www.stretchplafond.be



Composition	Glassfiber - weave structure
Width	320cm
Weight	270 gr/m2, +/- 10%
Appearance	Matt, smooth and uniform
Colour	Ral 9016
Tensile strength	DIN EN ISO 1421-1 3250 /2700 N/1 cm
Fire rating	A2-s1,d0
Packaging	Cut to measure, In roll (50m)
Warranty	10 Year*
Reference	Net width
SF-NF-A2-32-(CTM or R)	320cm



Non -
Flamable



Anti
Static



UV
Resistant



Water
Resistant



Light
Weight



Printable



Long
Lasting



Eco
Friendly

*according to Stretch standard terms of sale

certifié / certified
zertifiziert / заверено
certificado / certificato
ISO 9001 : 2008



certifié / certified
zertifiziert / заверено
certificado / certificado



STRETCH

CEILINGS & WALLS

Maintenance

STRETCH technical fabrics are glassfiber fabrics coated with polyurethane, which under most circumstances protects them from absorbing odours. STRETCH fabrics are hydrophobic and require little or no maintenance.

If cleaning is required, it is recommended to use the STRETCH Cleaner and the STRETCH cleaning glove or a non-abrasive soft cloth in a white color. The method to follow is:

1. Spray some STRETCH Cleaner on the glove and dab the area immediately.
2. If the stain persists, it is possible to repeat the operation several times.
3. Alternatively, other pH-neutral cleaning agents can be used with a soft white cloth, provided it has first been tested on a scrap piece or on a non-visible area of the fabric.

Under no circumstance should sodium hypochlorite based solutions (bleach) be used.