

STRETCH

CEILINGS & WALLS

STRETCH Standard - STD

STRETCH BV

Gentseweg 309 A3
9120 Beveren-Waas
Belgium

VAT: BE 0675.875.709

Mail: info@stretchgroup.be
Tel: +32 3 284 68 18
www.stretchplafond.be



Composition	Polyester knitted fabric coated with polyurethane (PU)
Width	200cm / 320cm / 510cm
Weight	255 gr/m2, +/- 10%
Thickness	0,4mm
Appearance	Matt, smooth and uniform
Colour	Ral 9016 / 9010 / 9005
Tensile strength	DIN EN ISO 1421-1 450/650 N/5 cm 450/650 H/5 cm
Tear strength	DIN 53363 60/350 N 60/350 H
Fire rating	B-s1,d0
Packaging	Cut to measure, In roll (50m)
Warranty	10 Year*
Reference	Net width
SF-STD-20-(CTM or R)	200cm
SF-STD-32-(CTM or R)	320cm
SF-STD-51-(CTM or R)	510cm



Anti
Bacterial



Anti
Static



UV
Resistant



Water
Resistant



Light
Weight



Printable



Long
Lasting



Eco
Friendly

*according to Stretch standard terms of sale

certifié / certified
zertifiziert / заверено
certificado / certificato
ISO 9001 : 2008



certifié / certified
zertifiziert / заверено
certificado / certificado



ASQUAL

CURRENTA
Leistung für Chemie und Industrie

STRETCH

CEILINGS & WALLS

Maintenance

STRETCH technical fabrics are polyester fabrics coated with polyurethane, which under most circumstances protects them from absorbing odours. STRETCH fabrics are hydrophobic and require little or no maintenance.

If cleaning is required, it is recommended to use the STRETCH Cleaner and the STRETCH cleaning glove or a non-abrasive soft cloth in a white color. The method to follow is:

1. Spray some STRETCH Cleaner on the glove and dab the area immediately.
2. If the stain persists, it is possible to repeat the operation several times.
3. Alternatively, other pH-neutral cleaning agents can be used with a soft white cloth, provided it has first been tested on a scrap piece or on a non-visible area of the fabric.

Under no circumstance should sodium hypochlorite based solutions (bleach) be used.