

# STRETCH

CEILINGS & WALLS

## STRETCH Acoustic - 705A

STRETCH BV

Gentseweg 309 A3  
9120 Beveren-Waas  
Belgium

VAT: BE 0675.875.709

Mail: [info@stretchgroup.be](mailto:info@stretchgroup.be)  
Tel: +32 3 284 68 18  
[www.stretchplafond.be](http://www.stretchplafond.be)



|                         |                                                                            |
|-------------------------|----------------------------------------------------------------------------|
| Acoustic classification | $\alpha_s = 0,55$ ; Rating: D<br>(with D4010 and 55 mm plenum)             |
| Composition             | Polyester knitted fabric coated with polyurethane (PU)                     |
| Width                   | 200cm / 250cm / 335cm / 410cm / 510cm                                      |
| Weight                  | 210 gr/m <sup>2</sup> , +/- 10%                                            |
| Thickness               | 0,3mm                                                                      |
| Appearance              | Matt, smooth and uniform                                                   |
| Colour                  | 3 different colors                                                         |
| Strength                | CH : 3,5 daN ; TR : 5,9 daN - 5 times greater than PVC film, doesn't crack |
| Fire rating             | B-s1,d0                                                                    |
| Packaging               | Cut to measure, In roll (50m)                                              |
| Warranty                | 10 Year*                                                                   |
| Reference               | Net width                                                                  |
| 721 AD or AR            | 200cm                                                                      |
| 726 AD or AR            | 250cm                                                                      |
| 735 AD or AR            | 350cm                                                                      |
| 741 AD or AR            | 410cm                                                                      |
| 741 AD or AR            | 510cm                                                                      |



Anti Bacterial



Anti Static



UV Resistant



Water Resistant



Light Weight



Breathable



Long Lasting



Eco Friendly



Printable

\*according to Stretch standard terms of sale

certifié / certified  
zertifiziert / заверено  
certificado / certificato  
ISO 9001 : 2008



certifié / certified  
zertifiziert / заверено  
certificado / certificato



# STRETCH

CEILINGS & WALLS

## Acoustic performance

|            | THK | o.d.s.<br>mm | $\alpha_p$ Pratical sound absorption coefficient |        |        |            |            |            | $\alpha_W$ | Sound absorbtion<br>class |
|------------|-----|--------------|--------------------------------------------------|--------|--------|------------|------------|------------|------------|---------------------------|
|            | mm  |              | 125 Hz                                           | 250 Hz | 500 Hz | 1000<br>Hz | 2000<br>Hz | 4000<br>Hz |            |                           |
| 705A D4010 | 55  | 55           | 0.05                                             | 0.20   | 0.60   | 0.80       | 0.55       | 0.45       | 0.55       | D                         |

## Maintenance

STRETCH technical fabrics are polyester fabrics coated with polyurethane, which under most circumstances protects them from absorbing odours. STRETCH fabrics are hydrophobic and require little or no maintenance.

If cleaning is required, it is recommended to use the STRETCH Cleaner and the STRETCH cleaning glove or a non-abrasive soft cloth in a white color. The method to follow is:

1. Spray some STRETCH Cleaner on the glove and dab the area immediately.
2. If the stain persists, it is possible to repeat the operation several times.
3. Alternatively, other pH-neutral cleaning agents can be used with a soft white cloth, provided it has first been tested on a scrap piece or on a non-visible area of the fabric.

Under no circumstance should sodium hypochlorite based solutions (bleach) be used.