



NOTES:

1. Material:

Magnet Wire:

Ø0.65 enamelled copper wire to IEC60317,
outer diameter 0.703 max.
temperature rating 180°C min.

Core: Ferrite

2. No. of turns: 21 ref.

[*] 3. Inductance: 4µH min at 1kHz

[*] 4. Core to be secured in coil with epoxy glue;
core push-off force to be 40N min.

C2 5.

1. COMPLY WITH DIRECTIVE 2002/95/EC(RoHS).

DO NOT SCALE DRAWING

UNIT: mm TOLERANCE: 4%

受控副本 不可私自複印

供應商用(不回收)

日期: JUN 20 2013

日期: JUN 20 2013

MATERIAL
FINISHING

SEE NOTE 1

CHIAPHUA
COMPONENTS 捷和電機

REQUIREMENT.

6/17/2013

0.6 MM; DELET NOTE 5; AAD CORE POSITION

C1-3 OFFSET THE CHOKE LEAD LENGTH ABOUT

B WAS 16±1.

8/16/2012

A INITIAL RELEASE

6/7/2012

REVISION DESCRIPTION DATE

Linear
DimensionsAngular
Dimensions

Unspecified Tolerance

0.5-3 >3-6 >6-30 >30-120 >120-400

±0.1 ±0.1 ±0.2 ±0.3 ±0.5

Permissible deviations for ranges of lengths
of shorter side of the angle concerned

-10 >10-50 >50-120 >120-400 >400

±1° ±30' ±20' ±10' ±5'

Special
CharacteristicCritical
CharacteristicControl
CharacteristicMajor
CharacteristicConformance
CharacteristicSafety
Characteristic

Level

Ppk

Cpk

TITLE: Choke

DRAWN

CHECKED

APPROVED

DRAWING NO.: 403004

SHEET: 1 OF 1

REVISION: C