

COMP1021
Introduction to Computer Science

Using Logic

David Rossiter

Outcomes

- After completing this presentation, you are expected to be able to:
 1. Understand how to use logic operators *and*, *or*, and *not*

Comparing Things

- When you do a comparison, the result is either True or False

```
x = 100  
result = x > 50  
print(result) → True
```

```
x = 10  
result = x > 50  
print(result) → False
```

Using Logical Operators

- You use the comparison operators (<, <=, >, >=, == and !=) to compare two values
- You can also use *logical operators*, also called *Boolean operators*:

a and b if both condition a and condition b are True, the result is True; otherwise, it's False

a or b if either condition a or condition b is True, the result is True; otherwise, it's False

not a if a is True, then the result is False;
if a is False, then the result is True } *The opposite*

Summary

- Here is a summary of the input and output:


<i>a</i>	<i>b</i>	<i>a and b</i>	<i>a or b</i>	<i>not a</i>
False	False	False	False	True
False	True	False	True	True
True	False	False	True	False
True	True	True	True	False


And


- and – the result is True if both inputs are True otherwise the result is False
- Let's use Python to check whether someone is a suitable girlfriend/boyfriend
- In this example, we need **both** of the two inputs to be true for the person to be suitable


```
funny = False  
friendly = False  
suitable_partner = funny and friendly  
print(suitable_partner)
```

The inputs

 *The result*


```
funny = False  
friendly = True  
suitable_partner = funny and friendly  
print(suitable_partner)       False
```

```
funny = True  
friendly = False  
suitable_partner = funny and friendly  
print(suitable_partner)       False
```


```
funny = True  
friendly = True  
suitable_partner = funny and friendly  
print(suitable_partner)       True
```


Or


- `or` – the result is False if both inputs are False otherwise the result is True
- Let's revise the previous code so only one of the two inputs has to be true for the person to be suitable

```
funny = False  
friendly = False  
suitable_partner = funny or friendly  
print(suitable_partner)  False
```



```
funny = False  
friendly = True  
suitable_partner = funny or friendly  
print(suitable_partner)     True
```

```
funny = True  
friendly = False  
suitable_partner = funny or friendly  
print(suitable_partner)     True
```

```
funny = True  
friendly = True  
suitable_partner = funny or friendly  
print(suitable_partner)     True
```

Not

- not – the output is the opposite of the input

```
very_clean = False  
need_to_shower = not very_clean  
print(need_to_shower)    → True
```

```
very_clean = True  
need_to_shower = not very_clean  
print(need_to_shower)    → False
```

Simpler Code

```
if funny == True and friendly == True:  
    suitable_partner = True  
else:  
    suitable_partner = False
```

- The code shown above works fine
but a good programmer would write this,
which does the same:

```
suitable_partner = funny and friendly
```

Multiple Inputs

- Here's an example of multiple inputs

```
funny = True  
friendly = False  
wealthy = True  
has_car = True  
cute = False
```

In this example
all of these have
to be True for the
result to be True

*This tells Python the
code continues on
the following line*


```
suitable_partner = funny and friendly and \  
    wealthy and has_car and cute  
print(suitable_partner)
```



False

Multiple Inputs

- Here's another example

```
scary_virus = True
need_internet = True
live_on_campus = False
go_to_HKUST = (live_on_campus or need_internet) \
               and not scary_virus
print(go_to_HKUST)  False
```

- The logic is: go to HKUST if you live on campus
or you need internet
but if there is a scary virus don't go

Converting Inputs into True or False

- Sometimes the inputs are not True or False, they are something else
- You may have to ‘convert’ the inputs into True or False before you can use logical operators
- The example on the next slide ‘converts’ input from the user into True or False, then uses a logical operator

if the user enters yes then response contains True

*if the user enters anything except yes then
response contains False*

```
response = input("Are you alive? (yes/no) ")
```

```
response = response == "yes"
```

```
print("response =", response)
```

```
print("Are you dead?")
```

```
print("The answer is:", not response)
```

```
Are you alive? (yes/no) yes
```

```
response = True
```

```
Are you dead?
```

```
The answer is: False
```

```
Are you alive? (yes/no) no
```

```
response = False
```

```
Are you dead?
```

```
The answer is: True
```