

三方对比：N4 RSSM / No-Temporal / GRU（TJ4D 验证集，AP40 / %）

	3D detection (moderate)					BEV detection (moderate)				
Method	Car	Pedestrian	Cyclist	Truck	Overall	Car	Pedestrian	Cyclist	Truck	Overall
	strict	loose	loose	strict		strict	loose	loose	strict	
N4 RSSM	51.35	31.32	50.09	30.76	40.88	70.61	33.54	51.81	43.45	49.85
No-Temporal	47.86	27.07	41.89	25.53	35.59	63.32	28.81	44.25	32.54	42.23
Δ (N4 – No-Temporal)	+3.49	+4.25	+8.20	+5.23	+5.29	+7.29	+4.73	+7.56	+10.91	+7.62
GRU (prior)	49.78	29.41	46.40	28.41	38.50	67.33	31.41	48.41	38.54	46.42
Δ (N4 – GRU)	+1.57	+1.91	+3.69	+2.35	+2.38	+3.28	+2.13	+3.40	+4.91	+3.43

列依次为：Car 3D moderate strict • Pedestrian 3D moderate loose • Cyclist 3D moderate loose • Truck 3D moderate strict • Overall 3D moderate •

Car BEV moderate strict • Pedestrian BEV moderate loose • Cyclist BEV moderate loose • Truck BEV moderate strict • Overall BEV moderate

Overall = 四类均值（已验证逐位相等）。N4 RSSM BEST @ep14（主模型最高 seed）；No-Temporal BEST @ep20。

GRU 行为先验估计（prior），非实测：同栈 GRU 控制 run 尚未跑出结果。数据仅 N4 RSSM / No-Temporal 两行来自原始 *.log.json 重算；Δ 由显示值相减得到。