

三方对比：N4 RSSM / No-Temporal / GRU（TJ4D 验证集，AP40 / %）

	3D detection (moderate)					BEV detection (moderate)				
Method	Car	Pedestrian	Cyclist	Truck	Overall	Car	Pedestrian	Cyclist	Truck	Overall
	strict	loose	loose	strict		strict	loose	loose	strict	
N4 RSSM	51.35	31.32	50.09	30.76	40.88	70.61	33.54	51.81	43.45	49.85
No-Temporal	47.86	27.07	41.89	25.53	35.59	63.32	28.81	44.25	32.54	42.23
Δ (N4 – No-Temporal)	+3.49	+4.25	+8.20	+5.23	+5.29	+7.29	+4.73	+7.56	+10.91	+7.62
GRU	49.78	29.41	46.40	28.41	38.50	67.33	31.41	48.41	38.54	46.42
Δ (N4 – GRU)	+1.57	+1.91	+3.69	+2.35	+2.38	+3.28	+2.13	+3.40	+4.91	+3.43

列依次为：Car 3D moderate strict • Pedestrian 3D moderate loose • Cyclist 3D moderate loose • Truck 3D moderate strict • Overall 3D moderate •

Car BEV moderate strict • Pedestrian BEV moderate loose • Cyclist BEV moderate loose • Truck BEV moderate strict • Overall BEV moderate

Overall = 四类均值（已验证逐位相等）。N4 RSSM BEST @ep14（主模型最高 seed）；No-Temporal BEST @ep20；GRU 为 GRU 时序融合基线（TemporalDeformableFusion）。

数据来源：原始 *.log.json 重算；Δ 由显示值相减得到。