

No-Temporal 与 N4 RSSM 在 TJ4D 验证集上的对比 (AP40 / %)

	3D detection (moderate)					BEV detection (moderate)				
Method	Car	Pedestrian	Cyclist	Truck	Overall	Car	Pedestrian	Cyclist	Truck	Overall
	strict	loose	loose	strict		strict	loose	loose	strict	
No-Temporal	47.86	27.07	41.89	25.53	35.59	63.32	28.81	44.25	32.54	42.23
N4 RSSM	51.35	31.32	50.09	30.76	40.88	70.61	33.54	51.81	43.45	49.85
Δ (N4 – No-Temporal)	+3.49	+4.25	+8.20	+5.23	+5.29	+7.29	+4.73	+7.56	+10.91	+7.62

列依次为：Car 3D moderate strict • Pedestrian 3D moderate loose • Cyclist 3D moderate loose • Truck 3D moderate strict • Overall 3D moderate •
Car BEV moderate strict • Pedestrian BEV moderate loose • Cyclist BEV moderate loose • Truck BEV moderate strict • Overall BEV moderate

Overall = 四类均值（已验证逐位相等）。No-Temporal BEST @ep20；N4 RSSM BEST @ep14（主模型最高 seed）。

同栈单变量：两份 config 差异仅 temporal_fusion（None ↔ MotionAlignedRSSMFusion）。数据来源：原始 *.log.json 重算。