

Rajalakshmi Engineering College

Name: SUBASH R
Email: 240701538@rajalakshmi.edu.in
Roll no: 240701538
Phone: 9150202710
Branch: REC
Department: I CSE FE
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Priya is developing a simple student management system. She wants to store roll numbers in a hash table using Linear Probing, and later search for specific roll numbers to check if they exist.

Implement a hash table using linear probing with the following operations:

Insert all roll numbers into the hash table. For a list of query roll numbers, print "Value x: Found" or "Value x: Not Found" depending on whether it exists in the table.

Input Format

The first line contains two integers, n and $table_size$ — the number of roll numbers to insert and the size of the hash table.

The second line contains n space-separated integers — the roll numbers to insert.

The third line contains an integer q — the number of queries.

The fourth line contains q space-separated integers — the roll numbers to search for.

Output Format

The output print q lines — for each query value x, print: "Value x: Found" or "Value x: Not Found"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5 10
21 31 41 51 61
3
31 60 51

Output: Value 31: Found
Value 60: Not Found
Value 51: Found

Answer

```
#include <stdio.h>

#define MAX 100

// You are using GCC
void initializeTable(int table[], int size) {
    for(int i=0;i<size;i++)
        table[i]=-1;
}

int linearProbe(int table[], int size, int num) {
    int key=num;
    while(table[key]!=-1)
        key++;
    return key;
}
```

```
}
```

```
void insertIntoHashTable(int table[], int size, int arr[], int n) {
```

```
    int key;
```

```
    for(int i=0;i<n;i++){
```

```
        key=arr[i]%size;
```

```
        if(table[key]==-1)
```

```
            table[key]=arr[i];
```

```
        else{
```

```
            key=linearProbe(table,size,key);
```

```
            table[key]=arr[i];
```

```
        }
```

```
    }
```

```
}
```

```
int searchInHashTable(int table[], int size, int num) {
```

```
    for(int i=0;i<size;i++){
```

```
        if(table[i]==num)
```

```
            return 1;
```

```
    return 0;
```

```
}
```

```
int main() {
```

```
    int n, table_size;
```

```
    scanf("%d %d", &n, &table_size);
```

```
    int arr[MAX], table[MAX];
```

```
    for (int i = 0; i < n; i++)
```

```
        scanf("%d", &arr[i]);
```

```
    initializeTable(table, table_size);
```

```
    insertIntoHashTable(table, table_size, arr, n);
```

```
    int q, x;
```

```
    scanf("%d", &q);
```

```
    for (int i = 0; i < q; i++) {
```

```
        scanf("%d", &x);
```

```
        if (searchInHashTable(table, table_size, x))
```

```
            printf("Value %d: Found\n", x);
```

```
        else
```

```
            printf("Value %d: Not Found\n", x);
```

```
    }
```

```
} return 0;
```

Status : Correct

Marks : 10/10