

# Lasso, Ridge and Elastic Net Regression

October 21, 2021

```
[29]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import statsmodels.api as sm

from sklearn.model_selection import train_test_split
from sklearn.metrics import r2_score
from sklearn.preprocessing import StandardScaler

from sklearn.linear_model import LinearRegression
from sklearn.linear_model import Ridge
from sklearn.linear_model import Lasso
from sklearn.linear_model import ElasticNet

from sklearn.linear_model import Lars
from sklearn.linear_model import SGDRegressor

from sklearn.svm import SVR
from sklearn.neighbors import KNeighborsRegressor
from sklearn.tree import DecisionTreeRegressor

from IPython.display import Image

'''
I've turned off warnings here in this Jupyter Notebook,
'''
import warnings
warnings.filterwarnings("ignore")
```

```
[30]: Image('/Users/subhasish/Documents/APPLE/SUBHASISH/Development/GIT/Interstellar/
↳SB-AI-DEV/ML/SB/LinerRegression/Images/2021-10-21_18-38-17.png')
```

[30]:

```
In [ ]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt

import statsmodels.api as sm

from sklearn.model_selection import train_test_split
from sklearn.metrics import r2_score
from sklearn.preprocessing import StandardScaler

from sklearn.linear_model import LinearRegression
from sklearn.linear_model import Lasso
from sklearn.linear_model import Ridge
from sklearn.linear_model import ElasticNet
from sklearn.linear_model import Lars
from sklearn.linear_model import SGDRegressor
from sklearn.svm import SVR
from sklearn.neighbors import KNeighborsRegressor
from sklearn.tree import DecisionTreeRegressor

import warnings
warnings.filterwarnings("ignore")
```

```
[31]: '''
We'll build all of these models in the same notebook using a few helper
functions that we'll set up first.
'''
'''
Let's go ahead and use pandas to read in our dataset that has been cleaned and
↳preprocessed earlier.
This is in the auto-mpg- processed.csv file. Here is what the dataset looks
↳like,

We'll use all of the other features, cylinders, displacement, horsepower, and
↳so on,
to predict the mileage for the cars.
'''

automobile_df =pd.read_csv('data/auto-mpg-processed.csv')
automobile_df.sample(5)
```

```
[31]:      mpg  cylinders  displacement  horsepower  weight  acceleration  age
127  14.0         8         302.0         137     4042          14.5   48
192  31.0         4          76.0          52     1649          16.5   47
41   18.0         6         250.0         105     3459          16.0   46
48   23.0         4         115.0          95     2694          15.0   46
167  37.3         4          91.0          69     2130          14.7   42
```

```
[32]: '''
I'm going to instantiate a dictionary here called result_dict that will hold the
training and test scores from the different models that we build and train.

The keys will be meaningful names for the different models that we build and the
values will be their training and test R squares.
```

*In this way, by simply doing the results stored in this dictionary, we'll be able to compare different models.*

```
'''  
result_dict = {}
```

[33]: *'''  
I'm going to define a helper function here called build\_model that will allow  
me to  
build and train the different regression models.*

```
'''  
'''  
:param regression_fn:  
    :param name_of_y_col:  
    :param names_of_x_cols:  
    :param dataset:  
    :param test_frac:  
    :param preprocess_fn:  
    :param show_plot_Y:  
    :param show_plot_scatter:
```

*The first argument here is the regression function. This is a function that  
takes in a training  
data and corresponding target values. This will instantiate a particular ML  
regression model,  
whether it's a linear regression model, a lasso model, a ridge or an elastic  
net model, anything.  
And this function will train the model on our training data.*

*The name of y\_col input argument specifies the column name in our data frame  
for the target  
values that we should use for training.*

*The names\_of\_x\_cols is a list of feature columns. These are the columns that  
we want to  
include as features when we train our model.*

*The dataset is the original data frame that contains the features, as well as  
our target values.*

*The test\_frac specifies how much of our dataset we should hold out to evaluate  
or measure our model,  
that is the fraction of our data that will be used as test data.*

*If you want the data to be preprocessed in some way, standardized or scaled  
before you feed  
it into your regression model, you can specify a preprocessed function.*

*By default, it's set to None.*

*Set show\_plot\_Y to True if you want to display a plot of actual versus predicted  
→ Y values,*

*and set show\_plot\_scatter to true if you want to see how your regression line  
→ fits on the training data.*

```
'''
def build_model(regression_fn,
                name_of_y_col,
                names_of_x_cols,
                dataset,
                test_frac=0.2,
                preprocess_fn=None,
                show_plot_Y=False,
                show_plot_scatter=False):

    '''
    Extract from the dataset the features that you want to train your model  
→ into the variable X
    and extract the target value into Y.
    '''
    X=dataset[names_of_x_cols]
    Y=dataset[name_of_y_col]

    '''
    If you've specified a function used to preprocess your model, apply this  
→ preprocessing
    function to your X values.
    The preprocessed features are stored once again in the X variable.
    '''
    if preprocess_fn is not None:
        X=preprocess_fn(X)

    '''
    Use scikit-learn's train_test_split function to split up your dataset into  
→ training and test data.
    '''
    x_train, x_test, y_train, y_test = train_test_split(X, Y,
    →test_size=test_frac)
    '''

    Once you have your training data, pass in the training data, as well as the  
corresponding labels to the regression function.
```

```

    The regression function is a wrapper that will instantiate a particular
    ↪ regression model and
    train on the dataset you've specified.

    The regression function will return the fully trained ML model, which you
    ↪ can then use
    for prediction, and store your predicted values in y_pred.
'''
model= regression_fn(x_train,y_train)
y_pred=model.predict(x_test)

'''
    You can then print out the R square values on the training data, as well as
    ↪ the test data
    for your model.
'''
print("Training_score : " , model.score(x_train, y_train))
print("Test_score : ", r2_score(y_test, y_pred))

'''
    If you've invoked the build model function with show_plot_Y is equal to
    ↪ True, plot the
    actual values versus predicted values in the form of a line chart
'''
if show_plot_Y == True:
    fig, ax = plt.subplots(figsize=(12, 8))

    plt.plot(y_pred, label='Predicted')
    plt.plot(y_test.values, label='Actual')

    plt.ylabel(name_of_y_col)

    plt.legend()
    plt.show()

'''
    if you've called it with show_plot_scatter equal to True, display a scatter
    ↪ plot in
    matplotlib with the original X and Y values of the test data and the
    ↪ predicted line.
'''
if show_plot_scatter == True:
    fig, ax = plt.subplots(figsize=(12, 8))

    plt.scatter(x_test, y_test)
    plt.plot(x_test, y_pred, 'r')

```

```

plt.legend(['Predicted line','Observed data'])
plt.show()

'''
we'll return from this build model function the training score and test Rsquare
score for this particular model.
'''
return {
    'training_score': model.score(x_train,y_train),
    'test_score': r2_score(y_test,y_pred)
}

```

```

[34]: '''
This is the compare_results function. This is the function that will quickly
print out the
training, as well as test scores for all of the regression models that we've
built so far.

This function uses a for loop to iterate through all of the keys in our result
dictionary
and then prints out the kind of regression that was performed, the training
score,
as well as the test score.
'''
def compare_results():
    for key in result_dict:
        print('Regression: ', key)
        print('Training score', result_dict[key]['training_score'])
        print('Test score', result_dict[key]['test_score'])
        print()


```

```

[35]: Image('/Users/subhasish/Documents/APPLE/SUBHASISH/Development/GIT/Interstellar/
SB-AI-DEV/ML/SB/LinerRegression/Images/2021-10-21_20-06-31.jpg')

```

[35]:



```
[36]: '''
This linear_reg function takes in training data, x_train, and target values,
↳y_train.

Within this function, we instantiate the LinearRegression estimator object with
↳normalize is equal
to True and call model.fit on this training data.

Once the model has been trained, we return an instance of this fully-trained
↳model
to the caller of this function.

This is the helper function that we'll pass in to build model
'''
def linear_reg(x_train,y_train):
    model=LinearRegression(normalize=True)
    model.fit(x_train,y_train)

    return model
```

```
[37]: '''
We invoke the build_model function that will train our regression model and
↳calculate
the training, as well as test scores and assign these results to the result
↳dictionary object.

We'll save the training and test score in the result dictionary with a
↳meaningful key.

So we have regressed to find the values of mpg, this is a single linear
↳regression.
Single linear, because we just use one feature for the regression,

and let's take a look at build_model for this.

The linear_reg function that we just defined is the first input argument,
that is our regression function.

The target value that we want to predict using this model is mpg,

the input feature that we use to train the model is just one, that is the
↳weight of the car,

the original dataset is automobile_df,
```

and we want to show Y values, actual versus predicted.


Run Shift+Enter to build and train our linear regression model using our  
→ helper function,  
and here is the training and test scores for this model.

We also have a nice little line chart here with predicted values in blue and  
→ actual values in orange.

```
'''  
result_dict ['mpg ~ single_linear'] =build_model(linear_reg,  
                                                    'mpg',  
                                                    ['weight'],  
                                                    automobile_df,  
                                                    show_plot_Y=True)
```

Training\_score : 0.6886465574759385

Test\_score : 0.7022214608274017



[38]: '''

Let's try this once again. This time we'll perform our kitchen sink linear  
→ regression with  
all of the features as input.



*The result of this regression will be present in the mpg - kitchen\_sink\_linear\_ ↪key,*

*and the features we use in our training data are cylinders, displacement, horsepower, weight, and acceleration.*


*Our kitchen sink regression performed decently well this time around, training score of 70%, test score of around the same.*

*'''*

```
result_dict ['mpg - kitchen_sink_linear'] =build_model(linear_reg,
                                                         'mpg',
                                                         ['cylinders',
                                                          'displacement',
                                                          'horsepower',
                                                          'weight',
                                                          'acceleration'],
                                                         automobile_df,
                                                         show_plot_Y=True)
```

Training\_score : 0.7118879455162679

Test\_score : 0.6875259383256004



[39]: '''

*But you don't really need to throw the kitchen sink at your linear regressor,   
→you'll find   
that a more parsimonious regression with a few selected features performs just   
→as well.*


*Here is a parsimonious regression using the same linear regressor estimator   
→object,   
we'll only use the horsepower and weight features in our training data.*

*We've dropped the number of features down from five to two, but because these   
→were the   
most significant features, we see that the training score and test scores for   
→our   
regression are still high.   
'''*

```
result_dict ['mpg - parsimonious_linear'] =build_model(linear_reg,
                                                         'mpg',
                                                         [
                                                         'horsepower',
                                                         'weight',
                                                         ],
                                                         automobile_df,
                                                         show_plot_Y=True)
```

Training\_score : 0.7044402283383003

Test\_score : 0.7127802587822276



```
[40]: '''
let's compare results and here are all of the training and testing scores for
↳all of the
regression models that we've just built and trained right here for you, set up
↳side by side.

This one screen allows us to quickly compare how the different models have done.
'''
compare_results()
```


```
Regression: mpg ~ single_linear
Training score 0.6886465574759385
Test score 0.7022214608274017
```

```
Regression: mpg - kitchen_sink_linear
Training score 0.7118879455162679
Test score 0.6875259383256004
```

```
Regression: mpg - parsimonious_linear
Training score 0.7044402283383003
Test score 0.7127802587822276
```


```
[41]: Image('/Users/subhasish/Documents/APPLE/SUBHASISH/Development/GIT/Interstellar/
↳SB-AI-DEV/ML/SB/LinerRegression/Images/2021-10-21_20-26-07.jpg')
```

[41]:



```
[42]: Image('/Users/subhasish/Documents/APPLE/SUBHASISH/Development/GIT/Interstellar/
↳SB-AI-DEV/ML/SB/LinerRegression/Images/2021-10-21_20-34-11.jpg')
```

[42]:



```
[43]: '''
The lasso regression model uses L-1 regularization to add a penalty to our loss_
↳function.
```

The objective of this penalty function is to reduce the magnitude of regression coefficients so that we don't end up with an overly complex model.

Regularization is a technique by which we prevent our models from overfitting\_
↳on the training
data and build more robust solutions.

Define a function called `lasso_reg`, which takes in the training data, as well,  
→as target values,  
and within this function instantiate and train a lasso estimator object.

An important hyperparameter that you specify when you build your lasso,  
→regression model is `alpha`.  
`Alpha` is the constant that you use to multiply the  $L_1$  regularization term.

The default value for `alpha` is set to 1, and higher values of `alpha` imply more,  
→regularization.

If you set `alpha` to 0, this completely eliminates the  $L_1$  penalty term, which,  
→means

Lasso regression defaults to ordinary linear regression, least squares,  
→regression.

```
'''  
  
def lasso_reg(x_train,y_train,alpha=0.5):  
    model=Lasso(alpha=alpha)  
    model.fit(x_train,y_train)  
  
    return model
```


```
[44]: '''  
    Let's build and train a lasso regression model by calling the build_model,  
    →function.  
    This is a kitchen sink regression, as you can see, I've passed in all 5,  
    →features here.  
  
    We've seen just a little bit earlier that kitchen sink models with linear,  
    →regression  
    don't really perform well, but if you take a look at the training and test  
    R squares for lasso regression, you'll find something interesting.  
  
    You'll find that the model performs better on the test data with a test score,  
    →of  
    almost 73%. Lasso regression models are regularized.  
  
    The penalty that we've imposed, the  $L_1$  penalty, force model coefficients to,  
    →be smaller  
    in magnitude. This results in a simpler and more robust model, which performs,  
    →well on test data.
```

*So if you're performing kitchen sink regression because you don't know which  
→ features in  
your data are significant, it's better to use a regularized model.  
'''*

```
result_dict ['mpg - kitchen_sink_lasso'] =build_model(lasso_reg,  
                                                    'mpg',  
                                                    ['cylinders',  
                                                    'displacement',  
                                                    'horsepower',  
                                                    'weight',  
                                                    'acceleration'],  
                                                    automobile_df,  
                                                    show_plot_Y=True)
```

Training\_score : 0.7000490393629422

Test\_score : 0.715147174572117



[45]: *'''  
Let's quickly call the compare\_results function here in order to see all of the  
→ training and test  
scores in one place.*

*You can see that the kitchen sink linear regression didn't really perform as well as the kitchen sink lasso regression.*

*The R square for test data was almost 69% for our regularized model, whereas it was just around 67% for our non-regularized linear regression model.*

```
'''  
compare_results()
```

```
Regression: mpg ~ single_linear  
Training score 0.6886465574759385  
Test score 0.7022214608274017
```


```
Regression: mpg - kitchen_sink_linear  
Training score 0.7118879455162679  
Test score 0.6875259383256004
```

```
Regression: mpg - parsimonious_linear  
Training score 0.7044402283383003  
Test score 0.7127802587822276
```

```
Regression: mpg - kitchen_sink_lasso  
Training score 0.7000490393629422  
Test score 0.715147174572117
```

```
[46]: Image('/Users/subhasish/Documents/APPLE/SUBHASISH/Development/GIT/Interstellar/  
↳SB-AI-DEV/ML/SB/LinerRegression/Images/2021-10-21_20-59-34.jpg')
```

[46]:



```
[47]: Image('/Users/subhasish/Documents/APPLE/SUBHASISH/Development/GIT/Interstellar/  
↳SB-AI-DEV/ML/SB/LinerRegression/Images/2021-10-21_21-03-33.jpg')
```

[47]:

```
In [ ]: def ridge_reg(x_train, y_train, alpha=0.5, normalize=True):
        model = Ridge(alpha=alpha, normalize=normalize)
        model.fit(x_train, y_train)
        return model]

In [ ]:

In [ ]:

In [ ]: Reduces the magnitude of regression coefficients
          by adding L2 regularization in the loss function

In [ ]:

In [ ]:
```

[48]: '''  
The ridge regression model is another one that imposes a penalty on an overly  
→ complex  
model by using regularization.  
  
As we've studied here, ridge regression works exactly like lasso regression, it  
→ reduces the  
magnitude of regression coefficients by adding L-2 regularization in the loss  
→ function.  
  
The L-2 regularization term is the L-2 Norm of the coefficients, which is the  
→ sum of the  
squares of the coefficients which we use to add as a penalty.  
  
Once again, the alpha parameter here is used to determine the strength of the  
→ regularization.  
larger values imply stronger or greater regularization.  
'''  
  
def ridge\_reg(x\_train,y\_train,alpha=0.5,normalize=True):  
 model=Ridge(alpha=alpha,normalize=normalize)  
 model.fit(x\_train,y\_train)  
  
 return model

[49]: '''  
This should be a positive floating point value, larger values imply stronger or  
→ greater  
regularization.  
  
Once again, because this is a regularized regression model, we'll perform  
→ kitchen sink ridge regression.




*We'll throw in all features here and see how kitchen sink regression performs,  
→using the  
ridge regularized model.*

*And you can see here from the training R square and the test R square that this,  
→particular  
model didn't really perform well for this dataset.  
'''*

```
result_dict ['mpg - kitchen_sink_Ridge'] =build_model(ridge_reg,  
                                                    'mpg',  
                                                    ['cylinders',  
                                                    'displacement',  
                                                    'horsepower',  
                                                    'weight',  
                                                    'acceleration'],  
                                                    automobile_df,  
                                                    show_plot_Y=True)
```

Training\_score : 0.6861630528478846

Test\_score : 0.6996778757024829



```
[50]: '''
For this particular dataset, the lasso model regularized using L-1 Norm
↳performed better than
the ridge regression model.

Remember that this in no way implies that in absolute terms one regression
↳model is
better than the other, it depends on your dataset, it depends on other model
↳parameters,
which we haven't really tweaked here.

Both lasso and ridge are regularized models, which impose a penalty on more
↳complex models or
higher value of coefficients.

The penalty that they impose whether it's the L-1 Norm or the L-2 Norm of
↳coefficients
is what is different.
'''
compare_results()
```

```
Regression: mpg ~ single_linear
Training score 0.6886465574759385
Test score 0.7022214608274017
```

```
Regression: mpg - kitchen_sink_linear
Training score 0.7118879455162679
Test score 0.6875259383256004
```

```
Regression: mpg - parsimonious_linear
Training score 0.7044402283383003
Test score 0.7127802587822276
```

```
Regression: mpg - kitchen_sink_lasso
Training score 0.7000490393629422
Test score 0.715147174572117
```

```
Regression: mpg - kitchen_sink_Ridge
Training score 0.6861630528478846
Test score 0.6996778757024829
```

```
[50]:
```