

# Rajalakshmi Engineering College

Name: SUBHA SRI S  
Email: 241801277@rajalakshmi.edu.in  
Roll no: 241801277  
Phone: 9884931507  
Branch: REC  
Department: I AI & DS FD  
Batch: 2028  
Degree: B.E - AI & DS

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 6\_COD\_Question 5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Jose has an array of N fractional values, represented as double-point numbers. He needs to sort these fractions in increasing order and seeks your help.

Write a program to help Jose sort the array using the merge sort algorithm.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of fractions to be sorted.

The second line consists of N double-point numbers, separated by spaces, representing the fractions array.

##### ***Output Format***

The output prints N double-point numbers, sorted in increasing order, and rounded to three decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 4

0.123 0.543 0.321 0.789

Output: 0.123 0.321 0.543 0.789

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
#define EPSILON 1e-9
```

```
int compare(double a, double b) {
    if (labs(a - b) < EPSILON) {
        return 0;
    } else if (a < b) {
        return -1;
    } else {
        return 1;
    }
}
```

```
void merge(double arr[], int l, int m, int r) {
    int n1 = m - l + 1;
    int n2 = r - m;
    double L[n1], R[n2];

    for (int i = 0; i < n1; i++)
        L[i] = arr[l + i];
    for (int j = 0; j < n2; j++)
        R[j] = arr[m + 1 + j];
```

```

int i = 0, j = 0, k = l;
while (i < n1 && j < n2) {
    if (L[i] <= R[j]) {
        arr[k] = L[i];
        i++;
    } else {
        arr[k] = R[j];
        j++;
    }
    k++;
}

while (i < n1) {
    arr[k] = L[i];
    i++;
    k++;
}

while (j < n2) {
    arr[k] = R[j];
    j++;
    k++;
}
}

void mergeSort(double arr[], int l, int r) {
    if (l < r) {
        int m = l + (r - l) / 2;
        mergeSort(arr, l, m);
        mergeSort(arr, m + 1, r);
        merge(arr, l, m, r);
    }
}

int main() {
    int n;
    scanf("%d", &n);
    double fractions[n];
    for (int i = 0; i < n; i++) {
        scanf("%lf", &fractions[i]);
    }
    mergeSort(fractions, 0, n - 1);
}

```

```
for (int i = 0; i < n; i++) {  
    printf("%.3f ", fractions[i]);  
}  
return 0;  
}
```

**Status :** Correct

**Marks :** 10/10