

# **ASSIGNMENT -5**

## **Exception and Multithreading**

a) Write a Java program to handle each of the following exception during execution. Write a suitable finally block for the selected exceptions wherever found appropriate.

i) InterruptedException

ii) ArrayIndexOutOfBoundsException

iii) IllegalArgumentException

iv) IndexOutOfBoundsException

v) NegativeArraySizeException

vi) NullPointerException

vii) IllegalAccessException

**CODE :-**

```
import java.util.Scanner;

public class ExceptionDemo {

    static void handleInterruptedException() {

        try {

            System.out.println("Thread going to sleep for 2 seconds");

            Thread.sleep(2000);

        }

        catch (InterruptedException e) {

            System.out.println("Error: Thread was interrupted");

        }

        finally {

            System.out.println("Thread operation complete\n");

        }

    }

}
```

```
static void handleArrayIndexOutOfBounds() {  
    int[] arr = {10, 20, 30};  
    try {  
        System.out.println("Accessing array element at index 3");  
        System.out.println("Value at index 3: " + arr[3]);  
    }  
    catch (ArrayIndexOutOfBoundsException e) {  
        System.out.println("Error: Cannot access element outside array bounds");  
    }  
    finally {  
        System.out.println("Array elements are:");  
        for(int i = 0; i < arr.length; i++) {  
            System.out.print(arr[i] + " ");  
        }  
        System.out.println("\n");  
    }  
}
```

```
static void handleIllegalArgument(int marks) {  
    try {  
        if(marks < 0 || marks > 100) {  
            throw new IllegalArgumentException();  
        }  
        System.out.println("Valid marks: " + marks);  
    }  
    catch (IllegalArgumentException e) {  
        System.out.println("Error: Marks should be between 0 and 100");  
    }  
}
```

```
finally {  
    System.out.println("Marks validation complete\n");  
}  
}
```

```
static void handleIndexOutOfBounds() {  
    String[] names = {"Ram", "Shyam"};  
    try {  
        System.out.println("Accessing name at index 2");  
        System.out.println("Name at index 2: " + names[2]);  
    }  
    catch (IndexOutOfBoundsException e) {  
        System.out.println("Error: Index is out of bounds");  
    }  
    finally {  
        System.out.println("Available names:");  
        for(String n : names) {  
            System.out.print(n + " ");  
        }  
        System.out.println("\n");  
    }  
}
```

```
static void handleNegativeArraySize() {  
    try {  
        System.out.println("Creating array of size -3");  
        System.out.println("Attempting to create the array...");  
        int[] arr = new int[-3];  
    }  
}
```

```
    catch (NegativeArraySizeException e) {  
        System.out.println("Error: Array size cannot be negative");  
    }  
    finally {  
        System.out.println("Array size must be positive\n");  
    }  
}
```

```
static void handleNullPointerException() {  
    String str = null;  
    try {  
        System.out.println("Getting length of null string");  
        System.out.println("String length: " + str.length());  
    }  
    catch (NullPointerException e) {  
        System.out.println("Error: Cannot perform operations on null object");  
    }  
    finally {  
        System.out.println("String operation complete\n");  
    }  
}
```

```
static void handleIllegalAccess(String name) {  
    try {  
        if(name == null || name.isEmpty()) {  
            throw new IllegalArgumentException();  
        }  
        System.out.println("Valid name: " + name);  
    }  
}
```

```
        catch (IllegalArgumentException e) {  
            System.out.println("Error: Name cannot be null or empty");  
        }  
        finally {  
            System.out.println("Name validation complete\n");  
        }  
    }  
}
```

```
public static void main(String[] args) {  
    Scanner sc = new Scanner(System.in);  
    int choice;  
    while(true){  
        System.out.println("Exception Handling Menu:");  
        System.out.println("1. InterruptedException");  
        System.out.println("2. ArrayIndexOutOfBoundsException");  
        System.out.println("3. IllegalArgumentException");  
        System.out.println("4. IndexOutOfBoundsException");  
        System.out.println("5. NegativeArraySizeException");  
        System.out.println("6. NullPointerException");  
        System.out.println("7. IllegalAccess Check");  
        System.out.println("8. Exit");  
        System.out.print("Enter your choice: ");  
        choice = sc.nextInt();  
        switch(choice) {  
            case 1:  
                handleInterruptedException();  
                break;  
            case 2:  
                handleArrayIndexOutOfBoundsException();  
                break;  
            case 3:  
                handleIllegalArgumentException();  
                break;  
            case 4:  
                handleIndexOutOfBoundsException();  
                break;  
            case 5:  
                handleNegativeArraySizeException();  
                break;  
            case 6:  
                handleNullPointerException();  
                break;  
            case 7:  
                handleIllegalAccessCheck();  
                break;  
            case 8:  
                System.out.println("Exiting...");  
                return;  
            default:  
                System.out.println("Invalid choice. Please enter a valid option (1-8).");  
        }  
    }  
}
```

```
        break;
    case 3:
        System.out.print("Enter marks (0-100): ");
        int marks = sc.nextInt();
        handleIllegalArgument(marks);
        break;
    case 4:
        handleIndexOutOfBounds();
        break;
    case 5:
        handleNegativeArraySize();
        break;
    case 6:
        handleNullPointerException();
        break;
    case 7:
        System.out.print("Enter name: ");
        sc.nextLine();
        String name = sc.nextLine();
        handleIllegalAccess(name);
        break;
    case 8:
        System.out.println("Exiting program...");
        sc.close();
        return;
    default:
        System.out.println("Invalid choice! Please try again.\n");
}
}
```

```
}  
}
```

---

**b) An user defined exception class : UserVerySmallNumException. This exception is thrown before performing a/b, on finding that a/b is very small less than 0.00001. Override toString method to display appropriate exception error message.**

**CODE :-**

```
class UseVerySmallNumException extends Exception{  
    private final double val;  
    UseVerySmallNumException(double v){  
        val = v;  
    }  
    @Override  
    public String toString(){  
        return "The Quotient " + val + " is too small";  
    }  
}  
  
public class CustomException {  
    static double divide(double a , double b) throws UseVerySmallNumException,  
    ArithmeticException{  
        if(b == 0){  
            throw new ArithmeticException();  
        }  
        double ans = a / b;  
        if(ans <= 0.000001){  
            throw new UseVerySmallNumException(ans);  
        }  
        System.out.println("Normal flow");  
        return ans;  
    }  
}
```

```

    }

    public static void main(String[] args) {
        try {
            for(int i = 0 ; i < 7 ; i ++){
                double dividend = Math.pow(10 , i);
                System.out.println("Result : " + divide(1 , dividend));
            }
        }
        catch (UseVerySmallNumException e) {
            System.out.println("Caught : " + e);
        }
    }
}

```

---

**c) Demonstrate the Shortest Job First Process Scheduling Algorithm using java multithreading. Here, assume that job size is decided by the numbers elements (n) a method is going to print from 1 to n. For example, a method called to print elements from 1 to 5 has higher priority than a method called to print from 1 to 10.**

**CODE :-**

```

import java.util.Scanner;

public class Shortest_Job_First {
    static class Job implements Runnable {
        int id;
        int n;
        Job(int id, int n) {
            this.id = id;
            this.n = n;
        }
    }
}

```



```

@Override

public void run() {
    for (int i = 1; i <= n; i++) {
        System.out.print("J" + id + ":" + i + (i == n ? "" : " "));
        try {
            Thread.sleep(20);
        }
        catch (InterruptedException ignored) {}
    }
    System.out.println();
}

}

public static void main(String[] args) throws InterruptedException {
    Scanner sc = new Scanner(System.in);
    System.out.print("Enter number of jobs: ");
    int m = sc.nextInt();
    Job[] jobs = new Job[m];
    for (int i = 1; i <= m; i++) {
        System.out.print("Enter size for job " + i + ": ");
        int n = sc.nextInt();
        jobs[i - 1] = new Job(i, n);
    }
    for (int i = 0; i < m - 1; i++) {
        int min = i;
        for (int j = i + 1; j < m; j++) {
            if (jobs[j].n < jobs[min].n) {
                min = j;
            }
        }
    }
}

```

```

    }
    if (min != i) {
        Job tmp = jobs[i];
        jobs[i] = jobs[min];
        jobs[min] = tmp;
    }
}
for (int i = 0; i < m; i++) {
    Thread t = new Thread(jobs[i]);
    t.start();
    t.join();
}
sc.close();
}
}

```

---

**d) Demonstrate the use of synchronized block for a Inventory class where one and only one thread can update the value of a stock item at a any instance of time**

**CODE :-**

```

class Inventory {
    int val = 100;
    synchronized void update(int x) {
        val += x;
        System.out.println(Thread.currentThread().getName() + ": " + val);
    }
    int get() {
        return val;
    }
}

```

```

}

class Worker implements Runnable {

    Inventory inv;

    int x;

    Worker(Inventory inv, int x) {

        this.inv = inv;

        this.x = x;

    }

    @Override

    public void run() {

        for(int i = 0; i < 5; i++) {

            inv.update(x);

            try {

                Thread.sleep(100);

            }

            catch(InterruptedException e) {

                System.out.println("Error");

            }

        }

    }

}

public class Synchronized {

    public static void main(String[] args) throws InterruptedException {

        Inventory inv = new Inventory();

        Thread t1 = new Thread(new Worker(inv, 10), "T1");

        Thread t2 = new Thread(new Worker(inv, -10), "T2");

        System.out.println("Start: " + inv.get());

        t1.start();

        t2.start();

    }

}

```

```
t1.join();  
t2.join();  
System.out.println("End: " + inv.get());  
}  
}
```

---