

The Andhra Pradesh Fire and Emergency Operations and Levy of Fee Rules, 2006

Source: <https://indiankanoon.org/doc/121917074/>

[Skip to main content](#)

[Legal Document View](#)

[Tools for analyzing structure and cite text of judgments](#)

[Unlock Advanced Research with PRISM](#)

[AI](#)

Integrated with over 4 crore judgments and laws ? designed for legal practitioners, researchers, students and institutions

-

[Know your Kanoon](#)

-

[Doc Gen Hub](#)

-

[Counter Argument](#)

-

[Case Predict AI](#)

-

[Talk with IK Doc](#)

-

...

[Upgrade to Premium](#)

[\[Cites](#)

0

, Cited by

0

]

State of Andhra Pradesh - Act

The Andhra Pradesh Fire and Emergency Operations and Levy of Fee Rules, 2006

ANDHRA PRADESH

India

The Andhra Pradesh Fire and Emergency Operations and Levy of Fee Rules, 2006

Rule THE-ANDHRA-PRADESH-FIRE-AND-EMERGENCY-OPERATIONS-AND-LEVY-OF-FEE-RULES-2006 of 2006

Published on 8 December 2006

Commenced on 8 December 2006

[This is the version of this document from 8 December 2006.]

[Note: The original publication document is not available and this content could not be verified.]

The Andhra Pradesh Fire and Emergency Operations and Levy of Fee Rules, 2006

Published vide Notification Andhra Pradesh Gazette, RS to Part 1, Extraordinary No. 74, dated 8.12.2006. G.O. Ms. No. 306, Home (Prisons-A), dated 7.12.2006.

In exercise of the powers conferred by sub-section (1) of Section 47 of the Andhra Pradesh Fire Service Act, 1999 (Andhra Pradesh Act

No. 15 of 1999

), the Government of Andhra Pradesh hereby makes the following rules in supersession of the rules issued in G.O. Ms. No. 14, Home (Prisons-A) Department, dated the 12th January, 2004.

Rules

Chapter-I

1.

Short title and extent:

(1)

These rules shall be called the Andhra Pradesh Fire and Emergency Operations and Levy of Fee Rules, 2006.

(2)

These rules shall extend to the whole of the State of Andhra Pradesh.

2.

Definitions:

- In these rules, unless there is anything repugnant to the subject or context

(a)

'Act' means the Andhra Pradesh Fire Service Act, 1999 (Andhra Pradesh Act

15 of 1999

);

(b)

'Accident' means Fire Accident, Road/Rail accident or emergency call due to collapse of a building, earthquake or any other such emergency call;

(c)

'Annexure' means an Annexure annexed to these rules;

(d)

'Authorised Officer' means any officer not below the rank of Station Fire Officer as specified by the Director General of Fire Services;

(e)

'Duty' means the duties prescribed for the members of service in these rules;

(f)

'Form' means the Form annexed to these rules;

(g)

'Jurisdiction' means the territorial jurisdiction of the Fire Station, Assistant Divisional Fire Officer or Divisional Fire Officer or Regional Fire Officer or Additional Director of Fire Services, as may be notified by the Government from time to time;

(h)

'Licence' means, a licence issued under the provisions of the Act.

(i)

'Officer-in-charge of the fire station' means a member of the Andhra Pradesh Fire Service not below the rank of Station Fire Officer and also shall include the Leading Fireman in cases where the Station Fire Officer is absent;

(j)

'Order' means the Government Order or Orders specified in the Andhra Pradesh Fire Service Manual and the General or Standing Orders issued by the Director General of Fire Services;

(k)

'Precautions' means Fire Precautions as may be specified against fire risk notified by the Government from time to time under Section 14 of the Act or any other provisions of the Act;

(l)

'Special Services' means rescue calls arising out of other accidents and such other services as are specified under the Andhra Pradesh Fire Service Manual;

(m)

'Standard' means the Standard prescribed or recommended by the Bureau of Indian Standards, Government of India, New Delhi and National Building Code of India, 1997;

(n)

"State" means the State of Andhra Pradesh.

Chapter II

(Personnel and Functioning of Service)

3.

Appointment of Members of Service:

- The members of Fire Service shall be those appointed in accordance with the special rules framed by the Government and as amended from time to time. On appointment, every member of the service shall be given a Certificate of Appointment in Form No. 1 annexed to these rules. Loss or damage of which shall render him liable for severe disciplinary action.

4.

Attending of Fire Calls:

- While at Headquarters or during inspection or visits to other fire stations, the Additional Director of Fire Services, Regional Fire Officers, Divisional Fire Officers and the Assistant Divisional Fire Officers shall attend such fire calls which are serious or which in their discretion require their presence for technical guidance.

5.

Composition of a Fire Station:

- Every fire station shall have a minimum component of One Station Fire Officer, Two Leading Firemen, Three Driver Operators and Ten Firemen and be provided with:

(1)

fire vehicles, appliances and equipment as laid down in Annexure XX of Andhra Pradesh Fire Service Manual.

(2)

The vehicles, appliances and equipment shall be replaced automatically on completion of its life period.

6.

Accommodation for Fire Station Staff:

(1)

Every fire station shall be provided with land measuring two acres and with a building and accommodation for safe custody of fire vehicles, appliances and equipment as well as for accommodation for fire staff.

(2)

The members of service are eligible for rent-free quarters. Where rent-free quarters have not been provided by the Government, the members of service shall be eligible for additional house rent allowance at the rates prescribed by the Government from time to time.

(3)

The members of service shall be entitled to free supply of uniform on such scale as may be prescribed by the Government from time to time.

7.

Drawal of water form firefighting operations:

- The Station Fire Officer shall have the authority to draw water from a water source specifically designated by the Government or the Director General of Fire Services for drawing water for firefighting purposes from any other water sources in his jurisdiction whether public or private.

8.

Rewards for assisting in firefighting and rescue operations:

- On receipt of specific recommendations from subordinate officers to be made out on plain paper, for giving rewards in firefighting and rescue operations to persons who give timely information regarding occurrence of fires and to those who effectively assist fire services on occasions of fire. The Director General of Fire Services shall examine the recommendation and issue rewards not exceeding rupees two thousand on any specific occasion.

9.

Manner of responding to fire calls:

- On receipt of any information or alarm of fire, it shall be the duty of every fire officer who is expected to respond to the said information/alarm in the manner as prescribed in Chapter XXVIII of the Andhra Pradesh Fire Service Manual.

10.

Manner of responding fire calls beyond local jurisdiction:

(1)

The Officer-in-charge of fire station shall have the powers of sending members of service with vehicle, appliances and equipment beyond the limits of any area in which the Act is in force for the purposes of firefighting falling in the immediate neighbourhood of his fire station and on such occasion shall within the shortest possible time inform his

immediate superior of his action.

(2)

Whenever so ordered, it shall be the duty of members of service to assist in any rescue, salvage or similar work as ordered by the officer-in-charge of fire station or any 'authority superior to him.

11.

The Director General to issue Orders and guidelines:

- The Director General of Fire Services shall issue such orders and lay down guidelines as he may feel appropriate and necessary for the maintenance of the service in a due state of efficiency. Copies of such orders whenever issued shall be forwarded to the Government.

12.

Manner of disposal of unlawful assembly:

- While acting under the provisions of Section 10 of the Act, the officer-in-charge of the fire station may cause disposal of an unlawful assembly in the manner prescribed in Section 129 of Criminal Procedure Code, 1973.

13.

Reporting of damage caused during firefighting operations:

- The officer-in-charge of the fire station shall report any damage done to any premises or property on the occasion of fire by members of service in the due discharge of the duties in Form No. 2 attached to these rules in triplicate to his immediate superiors and the Director General of Fire Services within 24 hours of such incident.

14.

Powers of the Director General to enter into arrangements for assistance:

- The Director General shall inform the Government the details of arrangements made with any person from whom he has obtained assistance in accordance with Section 12 of the Act.

15.

Issue of No Objection Certificate:

(1)

Any person proposing to construct a high-rise building of more than 15 mtrs. height for commercial/business purpose, 18 meters and above height for residential purpose, and buildings of public congregation like schools, cinema halls, function halls, religious places, which are more than 500 sq. meters in plot area or 6 meters and above in height shall apply to the Director General or any member of the service duly authorized by him in this behalf, for a No Objection Certificate as per the following procedure:

(a)

The applicant may obtain the prescribed application form (Form No. 16), from e-Seva or down load from Andhra Pradesh Fire Service Web Site "www.fireservices.ap.gov.in" or from any District Fire Office or Directorate of Fire Services;

(b)

The application form shall be duly filled in, after carefully reading the instructions therein and should be signed by authorized technical persons, also Seven sets of drawings i.e., site plan, cellar plan, ground floor plan, typical floor plan, sectional elevation and terrace plans duly marking fire fighting systems in Red complying with requirements mentioned in the application form shall be made;

(c)

A, non refundable Fire precaution fee @ Rs. 10/- per sq. meter of total built up area in all floors including Basements and stilt floor in the form of Challan under the Head of Account "0070- 109-SH (02) Fees of Fires-001 other receipts";

(d)

The application form along with drawings, fire precaution fee, Estimate towards the provision of required fire safety systems, 15% of the estimated cost of the fire safety installation and equipment in the form of Bank Guarantee drawn on any Nationalised Bank for a period of 5 years Guaranteeing provision and satisfactory maintenance of mandatory fire precaution and fire protection measures and an undertaking on Rs. 100/- stamp paper in (Form No. 17) shall be presented at e-Seva center. The Bank Guarantee can be invoked at any time by the Director General of Fire Services in the event of non-provision and non-maintenance of mandatory fire precautionary and fire protection measures.

(e)

The e-Seva center operator, will enter the particulars given by the applicant in the application form in their computer

Programmed to make a preliminary check, to verify whether required particulars have been, furnished properly, and if so, the application shall be processed and forwarded, along with the documents to Fire Services for necessary scrutiny and action. However if the particulars are not properly furnished, the application will be returned to the applicant at e-Seva center with computer generated details of deficiencies for rectification and resubmission.

(f)

Fire Services, will review and scrutinize the documents, call for any missing or additional information that may be required from the applicant, inspect the site and if, the projected compliance with fire safety rules appear satisfactory, within 60 days approximately communicate the "Provisional No-Objection Certificate" in Form No. 18 with conditions as it may deem fit, to Municipal authority with copy to the applicant, and others.

However, if not satisfied with the projected compliance with fire safety rules, the party shall be expeditiously advised along with clear reasons for the rejection. The applicant may, appropriately, rectify the deficiencies pointed out and reapply for the "Provisional N.O.C. at e-Seva center".

(2)

The Director General or any member of the service duly authorized by him in this behalf may himself take cognizance of any high-rise building being constructed without "Provisional No-Objection Certificate" from Fire Services, and appropriately address the Municipal Authority and the party for necessary action as per rules, to ensure compliance with fire safety requirements.

Explanation: - In case any person proposes to increase the number of floors on any Building already constructed in such a manner that it shall qualify for being termed as a high-rise building shall before construction, apply to the Director General or any member of service duly authorized by him in this behalf for "Provisional No-Objection Certificate" as per procedure stipulated vide, sub-rule 1 above.

(3)

(a)

The Provisional No Objection Certificate shall be issued giving any additional requirements in the interest of safety. These would be in addition to National Building Code of India and applicable building rules, construction safety included.

(b)

The "Provisional, as well as, Final No-Objection Certificate" shall be valid only for the occupancy class, the occupant load and the building particulars indicated in the application. Fresh No Objection Certificate will be required for change in occupancy.

(4)

During the process of construction, the Director General shall depute a member of the service to conduct such inspection of the construction and note the deviations from Provisional No-Objection Certificate or National Building Code or any other rules for the time being in force that may be observed and instruct for necessary corrections, without relaxing any rule. Such deviations shall be brought to the notice of the party, acknowledgement obtained and copy of same sent to the Director General of Fire Service. The responsibility of full compliance with the rules remains with the owners/technical persons as stipulated in National Building Code on Building rules or any other rules for the time being in force.

(5)

On completion of the construction of the high-rise building, the applicant shall apply for a "Final No Objection Certificate" as per following procedure:

(a)

Obtain prescribed application form (Form No. 19) from e-Seva or down load from APFS web site "www.fireservices.ap.gov.in" or from any District Fire Officer or Directorate of Fire Services.

(b)

Provide updated information in the above form, which shall truly reflect the as-installed and as-built status at site and shall be signed by authorized technical persons.

(c)

Make 4 copies of Provisional No-Objection Certificate drawings, clearly showing, the as-Built and corrections, if any. These must be certified by competent architect and engineer.

(d)

Certified electrical drawings, specifications of fire safety related equipment with details, as required in the application

form, to be prepared.

(e)

Present the above documents (a to d) at e-Seva center.

(f)

The e-Seva center operator, will enter the particulars given by the applicant in the application form in their computer programmed to make a preliminary check, to verify whether required particulars have been, furnished properly, and if so, the application, shall be processed and forwarded, along with the documents, to Fire Services for necessary scrutiny and action. However if the particulars are not properly furnished, the application will be returned to the applicant at e-Seva center with computer generated details of deficiencies, for rectification and resubmission.

(g)

(i)

Fire Services, will review and scrutinize the documents, call for any missing or additional information that may be required from the applicant, inspect the site to verify the correctness of information provided, witness functional test and if, compliance with all fire safety rules are found to be satisfactory, within 60 days, approximately communicate the "Final No-Objection Certificate" in Form No. 20 with conditions as it may deem fit, to Municipal authority, with copy to the applicant, and others.

Note: - The applicant/owner should ensure that technical persons have themselves conducted all tests and functional checks on all fire-safety related equipment, before the site inspection by Fire Services, so as to expedite, approvals.)

(ii)

However, if not satisfied with the projected compliance with fire safety rules, the applicant shall be expeditiously advised along with clear reasons for the rejection. The applicant may appropriately rectify the deficiencies pointed out and re-apply at e-Seva center for the "Final No-Objection Certificate".

(iii)

The occupancy class and occupant load shall be mentioned in the final No Objection Certificate and communicated to the Municipal authority, the applicant/owner and others.

(6)

The Provisional No Objection Certificate shall not be issued by the Director General, unless the person has deposited the fire precaution fund chargeable per square metre as per rates prescribed by the Government from time to time.

Chapter III

Particular Duties

16.

(1)

Station and other operational routine: - The Members of the Fire Service shall act in accordance with the procedure and attendance at Fire Station as provided under Chapter XXIX of the Andhra Pradesh Fire Service Manual; and

(2)

Fire prevention and fire precautions: - The Members of the Fire Service not below the rank of Station Fire Officer and officer-in-charge of the Fire Station and the Leading Firemen, in cases where the Station Fire Officer is absent shall act in accordance with Chapter XXVII of the Andhra Pradesh Fire Service Manual.

Chapter IV

17.

Preventive measures:

- The Members of the Fire Service authorized under Rule 3 shall report the negligence, carelessness, wilful commissions or omissions of the holders of the licence mentioned under Rule 24 and Sections 13, 14, 15, 16, 17 and 18 of the Act, to the Director General of Fire Service through proper channel. On approval of the Director General of Fire Services and after giving the owner or occupier a reasonable opportunity not exceeding thirty days of making representation, shall take action to seize, detain or remove such objectionable objects or goods under Section 14 of the Act or order the closure of the premises in Form No. 3 after conducting Panchanama in Form No. 4 annexed to these Rules. This shall be without prejudice to any prosecution that may be launched under Sections 22 and 31 of the Act.

18.

Application for grant of licence:

(1)

The owner or occupier of any place using it for any one or more of the purposes mentioned in the notification issued under Section 15 in Annexure appended to these rules, shall within 30 days from the date of notification shall submit an Application in Form No. 5 in duplicate along with plans and fees to the Authorized Officer either by delivery in person or by Registered post for the grant of licence. The prescribed fees by a challan has to be paid before issue of licence.

(2)

No place or site within any area which constitutes a fire risk shall be used unless the occupier or owner of the premises obtains a licence issued by the Authorized Officer after the payment of prescribed fee.

(3)

The occupier or owner of the premises shall pay a fee as specified in the schedule under this sub-rule for scrutiny of plans by a challan (Treasury Receipt) under the Head of Account 0070 - Other Administrative Services, 060 - Other Services, 109 - Fire Protection and Control and 081 - Other Receipts.

19.

Grant of licence:

(1)

A licence may be granted by the Authorized Officer in Form No. 6 with conditions as he may direct on an application made to him in prescribed form after inspection either by himself or by his subordinate and on payment of prescribed fee within a period of sixty days from the date of receipt of an application provided that where the Authorized Officer refuses to grant a licence, he shall record the reasons for such refusal and communicate to the occupier or owner of the premises within sixty days from the date of receipt of the application for the licence.

(2)

The Authorized Officer shall approve the plan and send to the applicant with licence. Every licence granted under this Rule shall be valid for a period of three years or for such lessor period as may be specified in the licence.

(3)

If the Authorized Officer is of the opinion that the plans submitted along with the Application are not in accordance with the requirements of the Act, the Authorized Officer may require the applicant to furnish, within thirty days of the date of receipt of application, more detailed particulars and plans which may include particulars such as lay out of site, fire safety arrangements, Means of Escape, i.e. Exits, Gangways, Corridor, etc., or any other matter that he may consider necessary in the interest of fire safety of the premises.

(4)

The Authorized Officer may, after giving the applicant a reasonable opportunity of being heard, by speaking order, refuse the grant of licence. He shall record the reasons for such refusal and communicate to the occupier within sixty days from the date of receipt of the application for the licence.

(5)

The Applicant may submit an Appeal to the Director General of Fire Services against the orders of refusal to grant the licence by an Authorized Officer within thirty days from the date of receipt of the order in Form No. 7.

(6)

If no order is communicated to the Applicant, within sixty days from the date on which the application has been delivered in person or sent by Registered Post, the licence applied for shall be deemed to have been granted subject to the application for licence in being conformity with the provisions of the Act and thereupon the licence shall be issued forthwith.

(7)

Every licence granted shall be valid for the time specified till it has been duly cancelled.

(8)

A licence granted shall be caused to be produced on demand by the officials not below the rank of Station Fire Officer of Fire Service Department.

20.

Amendment of Licence:

(1)

A licence granted may be amended by the Authorized Officer. A licensee shall get his licence amended when there is a change in the name of the premises or ownership or; in the limits specified in the licence in regard to the nature and quantity of hazardous materials to be handled.

(2)

The occupier or the owner of premises shall within thirty days of the occurrence of any change, send to the Authorized Officer an application for the amendment of the original licence stating the nature of the amendment and the reasons therefor together with the fee prescribed.

(3)

The fee for the amendment of a licence shall be the amount, if any by which the fee that would have been payable if the licence had originally been issued in the amended form exceeds the licence fee payable for the relevant calendar year but for the amendment along with an amendment fee of Rs. 200/- i.e. normal licence fee plus Rs. 200/-.

21.

Renewal of licence:

(1)

A licence may be renewed by the Authorized Officer.

(2)

The occupier or owner of the premises shall submit the licence with an application in Form No. 8 to the Authorized Officer either by delivering in person or by Registered Post for the renewal of licence not less than two months before the date on which the licence expires.

Provided that the application for renewal is not received within the time specified, the licence shall be renewed only on payment of a fee 25% in excess of the fee ordinarily payable for the licence.

(3)

The same fee shall be Charged for the renewal of a licence for one calendar year as for the grant of licence thereof. Provided that where the renewal of licence is refused, the authorized officer shall record reasons therefore and communicate to the occupier or owner within thirty days from the date of receipt of the application for renewal of licence.

(4)

The applicant may submit an Appeal to the Director General of Fire Services against the refusal orders of the Authorized Officer to renew the licence within 30 days from the date of receipt of order in Form No. 7.

22.

Procedure on death or disability of licensee:

- If a Licensee dies or becomes insolvent, the persons carrying on the business of such Licensee shall submit an application for amendment within thirty days for amendment in his own name for the un-expired portion of the original licence without any additional fee.

23.

Loss of licence:

- Where a licence granted or renewed under these rules is lost or accidentally destroyed, a duplicate may be granted by the authorized officer on submission of application on plain paper with a payment of fee of Rs. 100/-.

24.

Payment of fee:

(1)

Every Licensee shall before the commencement of any calendar year, pay the annual licence fee of such amount as is prescribed in Rule 28.

(2)

If the prescribed annual licence fee is not fully paid within the prescribed period in this Rule, simple interest at two per cent per month or part thereof shall be payable.

Provided that the Director General of Fire Services may, if satisfied that there is sufficient reason for the non-payment of the annual licence fee within the time prescribed in this Rule, by order in writing, waive the interest specified.

(3)

In case of applications for scrutiny of plans where any information is sought or revised plans are called for and if such information/revised plans are not furnished by the occupier or owner within a period of sixty days from the date of seeking such information or calling for revised plans, the correspondence shall be treated as closed and the occupier or owner if so desires may submit fresh application along with the prescribed fee.

25.

Right of inspection:

(1)

The authorized officer or any other member of the service not below the rank of Station Fire Officer (hereinafter called Inspecting Officer) may, after giving three hours notice in Form No. 9 to the occupier or if there be no occupier, to the owner of any building or premises or any place which in his opinion for reasons to be recorded, constitutes a fire risk, enter and inspect the site, building or premises at any time between sun-rise and sun-set for ascertaining the adequacy or contravention of Fire Prevention and safety measures provided that such inspection may be made at any other time if an industry is working or an entertainment is going on at such place or the inspecting officer considers it absolutely necessary for reasons to be recorded in writing, to make an immediate inspection of such place in order to ensure safety of life and property.

(2)

The inspecting officer shall be provided with all possible assistance by the owner or occupier as the case may be of the building or premises for carrying out the inspection.

(3)

When any building or premises used as a human dwelling is entered, due regard shall be paid to the social and religious sentiments of the occupiers and before any apartment in the actual occupancy of any women, who according to the custom does not appear in public, is entered, notice shall be given to her that she is at liberty to withdraw and every reasonable opportunity shall be given to her for withdrawal.

(4)

Detailed information on existing fire safety measures, i.e., Self-appraisal check list to verify their adequacy as per National Building Code or any other rules for the time being in force and to facilitate inspection, shall be provided by the owner or occupier of a building in 2 to 4 weeks as may be stipulated, by duly filling in the format provided by the inspecting officer.

26.

Inspection report and issue of notice:

(1)

The Inspecting Officer shall, after the completion of inspection of building or premises record his views on the deviation from or the contravention of the building byelaws with regard to the fire prevention and fire safety measures or the inadequacy or non-compliance of such measures provided or to be provided therein with reference to the height of the building or premises or the nature of activities carried on in such building or premises or part thereof in the Form No. 10 or 11 (Inspection Report).

(2)

The Inspecting Officer shall issue a Notice in Form No. 12 to the owner or occupier of such building or premises directing him to undertake such measures as may be specified in the Notice within 30 days.

(3)

The Inspecting Officer in case of other than Authorized Officer shall also submit a report of inspection made by him and send a copy of notice to the Authorized Officer.

27.

Steps to be taken in the event of non-compliance of notice:

- The Authorized Officer or any other member of service empowered in this behalf, in the event of non-compliance of any notice issued under Rule 26 may take such steps as may be necessary for the compliance of such notice.

28.

Fees:

(1)

The standby and pumping charges shall be collected from the owner or occupier of the premises where the fire has occurred or spread where the members of the service are sent beyond the limits of the State of Andhra Pradesh.

(2)

The fee at the rate of ten rupees per square meter of the built-up area shall be payable by the owner of every high-rise building along with the applications submitted to the Director General for approval of building plans.

(3)

The fee prescribed for grant of licence/renewal of licence to the premises/building used for any one or more of the purposes which constitute fire risk as per Sections 15, 16, 17 and 18 of the Act shall be rupees five hundred, rupees one

thousand, rupees two thousand five hundred and rupees five thousand per year is mentioned in Appendix as below:

Sl. No.

Category of Building/Material/Trade Fee prescribed per year

1.

Category-I from Sl. No. 1 to 613 of Appendix Rs. 500/-

2.

Category-II from Sl. No. 1 to 280 of Appendix Rs. 1000/-

3.

Category-III from Sl. No. 1 to 12 of Appendix Rs. 2500/-

4.

Category-IV from Sl. No. 1 to 8 of Appendix Rs. 5000/-.

29.

Penalties:

(1)

Any member of service who violates his legitimate duties shall be punishable with imprisonment for a term which may extend to three months or with fine which may extend three months' pay of such member or with both by initiating prosecution by the appointing authority concerned for the following reasons:

(a)

found guilty of any violation of duty or wilful breach of any provision of the Act, or any rules or orders made there under; or

(b)

found guilty of cowardice; or

(c)

withdraws from the duties of his office without permission; or

(d)

being absent on leave, fails without reasonable cause, to report himself for duty on expiration of such leave; or

(e)

accepts any other employment or office in contravention of the provisions of Section 37 of the Act; or

(f)

intentionally or knowingly causes or attempts to cause disaffection towards the Government amongst the members of the service; or induces or attempts to induce any member of the service to withhold his services or commit a breach of discipline.

(2)

Penalty for failure to take precautions:

The authorized officer may impose fine not exceeding Rs. 500/-(Rupees Five hundred only) on the occupier or owner of the premises who fails to comply with any of the requirements specified in the notification issued under sub-sections (1) and (2) of Section 14 of the Act.

(3)

Penalty for wilfully obstructing operations:

The Authorized Officer not below the rank of Assistant Divisional Fire Officer shall initiate prosecution against any person who wilfully and without any reasonable cause obstructs or interferes with any member of the service who is engaged in firefighting operations and shall be punishable with imprisonment for a term which may extend to three months or with fine which may extend to five hundred rupees or with both.

(4)

Penalty for false report:

The Authorized Officer not below the rank of Assistant Divisional Fire Officer shall initiate prosecution against any person who knowingly gives or causes to be given a false report of the outbreak of a fire to any person authorized to receive such report by means of a statement, message or otherwise and shall be punishable with imprisonment for a term which may extend to three months or with fine which may extend to five hundred rupees or with both.

(5)

Penalty for failure to take out licence:

(a)

The Authorized Officer shall serve a notice in Form No. 13 on the occupier or owner of the premises who is being bound to take out a licence under the provisions of the Act, fails to obtain a licence or fails to comply with any of the conditions specified in the licence, requiring him to obtain a licence or comply with any of the conditions specified in the licence as the case may be within 15 days from the date of serving notice.

(b)

If the owner or occupier of the premises/building does not comply with the notice, the authorized officer not below the rank of Assistant Divisional Fire Officer shall serve a show-cause notice in Form No. 14 and if the owner or occupier further failed to comply with the show-cause notice within 30 days shall initiate prosecution and shall be punishable with imprisonment for a term which may extend to three months or with fine which may extend to five thousand rupees or with both.

(6)

Penalty for wilful violation:

The Authorized Officer not below the rank of Assistant Divisional Fire Officer shall initiate prosecution against the owner or occupier of the premises/building who wilfully contravenes any provisions of this Act or the rules made thereunder or fails to comply with any requisition lawfully made upon him under any provisions of the Act shall, without prejudice to any other action taken against him under Section 22 of the Act and shall be punishable with imprisonment for a term which may extend to three months or with fine which may extend to Rs. 25,000/- (Rupees Twenty five thousand only) or with both; and where the offence is a continuing one, with a further fine which may extend to Rs. 3000/- (Rupees Three thousand only) for every day during which such offence continues after the conviction for the first such offence.

Provided further that in the absence of special and adequate reasons to the contrary to be mentioned in the judgment of the court, such punishment shall not be less than Rs. 5000/- (Rupees Five thousand only) or such daily fine shall be less than Rs. 100/- (Rupees One hundred only) per day for a continuing one.

(7)

Procedure to deal with offences by companies:

The Authorized Officer not below the rank of Assistant Divisional Fire Officer shall initiate prosecution or impose fine against the company (i.e. Any body corporate and includes a firm or other association of individuals) committed offence under this Act or every person who at the time the offence was committed, was in charge of and was responsible to the company of the conduct of the business of the company as well as the company shall be guilty of the offence and shall be liable to be proceeded against and punished accordingly. Where it is proved that the offence has been committed with the consent or connivance of, or is attributable to any neglect on the part of any director or partner of the firm, manager, secretary or other officer shall also be deemed to be guilty of that offence and shall be liable to be proceeded against and punished accordingly.

30.

Compounding or withdrawal of proceedings:

- The Director General or any officer authorized by him in this behalf, by general or special order may before or after the institution of the proceedings, and for reasons to be recorded in writing, compound any offence made punishable by or under this Act or the rules made thereunder or withdraw from the proceedings. The offender if in custody shall be discharged when an offence has been compounded and no further proceedings shall be taken against him in respect of the offence compounded.

31.

Prosecution procedure:

- Officers not below the rank of Assistant Divisional Fire Officer upon the records made out by the Station Fire Officer and on obtaining sanction to prosecute from the Director General of Fire Services shall lodge a complaint before the Court of Competent Jurisdiction against the Offenders under Sections 22, 27, 28, 29, 30, 31 and 32 of the Act.

Chapter V

32.

Repairs and replacement of appliances and stores:

- The Director General of Fire Services shall exercise powers in the matter of repairs and replacement of appliances, procurement of stores and maintenance of the repair squad and workshop as per procedure contemplated in Chapter XXV of the Andhra Pradesh Fire Service Manual.

Chapter VI

33.

Training:

- The Director General of Fire Services shall organize various training courses for different levels as envisaged in Annexures II and III of the Andhra Pradesh Fire Service Manual. He shall take the assistance of the Additional Director of Fire Services at Headquarters and the Divisional Fire Officer, State Training School and the Director, National Fire Service College, Nagpur. He shall also coordinate with the Government, the Administrative Department for Fire Service in the Government and organize courses on Administration and Management Training, Seminars and Conferences. He shall also coordinate with the Fire Advisor, Ministry of Home Affairs and Director, Indian Standards Institutions and the Director, Supplies and Disposals, Government of India and organize courses on quality control and purchase procedure. He shall also coordinate with the Director, Central Building Research Institute, Rurkee and Fire Advisor, Ministry of Defence and Advisor, Communications, Government of India and organize courses on Research and Development of up to date technology in the department for the betterment of service and to satisfy the safety needs of the public from the fire hazards.

Chapter VII

34.

Buildings:

- The Director General of Fire Services shall exercise his powers in the matter of construction of new fire stations providing permanent buildings for the new and old fire stations, construction of quarters for the staff and construction of static water tanks, following the procedures contemplated under Chapter XX of the Andhra Pradesh Fire Service Manual as amended from time to time. He shall also utilize the services of the Andhra Pradesh Water and Drainage Board, the Corporations and Municipalities, Revenue Department, major Panchayats and Panchayat Unions for providing Hydrant system to the required areas in the State and ensure fire protection system to the entire State of Andhra Pradesh.

Chapter VIII

35.

General:

(a)

No suit, prosecution or other legal proceeding shall lie against any person for anything which is in good faith done or intended to be done under these Rules.

(b)

The Training fee will be charged from the trainees for others for providing a course of instruction in the prevention and extinguishments of fire as prescribed by the Government from time to time.

(c)

The fire tax shall be levied on lands and buildings on which property tax is levied at the rate of one per cent of the total amount of the property tax in the form of a surcharge. The same shall be recoverable as if it were arrear of land revenue.

(d)

The membership certificate shall be issued to various ranks of the department in the format prescribed in Form No. 1 appended to these Rules;

(e)

The members of the Service shall be engaged in firefighting, rescue and relief operations on a safeguard to their safety being an award of money compensation as per the Workmen's Compensation Act, 1923 (Central Act VIII of 1923) and a Group Insurance Scheme. Further, the family members who are suitable shall be appointed to suitable ranks in the force in the event of their death in action or on duty. Further, they shall be entitled to all the benefits applicable to the Government Servants who die in harness and all other legitimate compensation announced by the Government from time to time. They shall also be entitled to receive any special awards granted by the Government or private person, company, Corporation, Boards and others;

(f)

The member of the service up to the rank of Assistant Divisional Fire Officer shall be entitled for all the "Rewards" contemplated under Chapter IV of the Andhra Pradesh Fire Service Manual;

(g)

The award amount of compensation for the member who is injured during action or while on duty or his death on the event shall be to the extent decided by the Tribunal for Workmen's Compensation or by any other Court competent to pass such an order in addition to all other benefits entitled to by the member while dying in harness;

(h)

The job such as Private Standby, pumping and others undertaken utilizing the men and machine power of the department shall be governed by the orders in the Andhra Pradesh Fire Service Manual. The Government, by any special order, may treat such paid jobs as free at their discretion; and

(i)

The members of the Service holding various ranks shall be equivalent in ranks of various other paramilitary forces in the country by a special order and they shall enjoy the status and protocol on their day to day official affairs and on National occasions. Their dress regulation shall be regulated on these lines from time to time by the Government.

Chapter IX

36.

Compensation:

(1)

The Director General of Fire Services may grant compensation to persons, who, while rendering effective service to the Fire Service in the discharge of their duties, met with accident to the extent fixed by the Government from time to time for injury and compensation to their dependants in the event of their death.

(2)

The Director General of Fire Services may grant compensation to be paid to the property to the extent of the damage caused by the members of service during the conduct of firefighting and rescue operations after receipt of report in Form No. 2 and on the basis of assessment report of Roads and Building authorities.

Chapter X

37.

Auxiliary Fire Service:

(1)

The Director General of Fire Services may organise the Auxiliary Service on the pattern developed by the Fire Advisor, Ministry of Home Affairs, Government of India and the expenditure thereof shall be borne by the Government from the State Contingent Fund. The Director General of Fire Services shall be the recruiting authority for the members of Auxiliary Service.

(2)

A Member of the auxiliary fire service on appointment, shall receive a certificate of appointment for a specified period of time as per Form No. 15 attached to these rules, loss or damage of which shall render him liable for severe disciplinary action.

Annexure

(See Under Rule 18)

Categorization of Fire hazardous Buildings/Materials/Trades under the provisions of Andhra Pradesh Fire Service Act, 1999 and prescribed fee for issuing licences

(I)

The Category of Buildings/Materials/Trades coming Under licence fee of Rs. 500/-

Sl. No.

Description of Hazard

(1)

(2)

1.

Theatres and Cinemas Non-AC irrespective of seating capacity including touring talkies.

2.

Other Halls with a closely seated audience (Stage shows and dramas)

3.

Restaurants/Hotels and Dhabas with seating capacity of 30 Nos.
to 100 Nos.

4.

Dance Halls

5.

Exhibitions and Assemblies like Industrial, Entertainment,
Political, Religious, Cultural, Professional
Conferences/Meetings, Major cultural shows and sale exhibitions.

6.

Function Halls, Circus es, Large Tent House.

7.

Non-Residential Schools and Colleges upto 500 inmates but not
below 100 inmates.

8.

Non-Residential places for using/storing more than 05 Nos. LPG
Cylinders.

9.

Transport Godowns having the floor area upto 2000 Sft.

10.

Timber depots, Coal and Oil depots

11.

Gas Cylinders (Liquefied, dissolved and cryogenic) storage

12.

Wholesale shops

13.

Commercial showrooms ? Temporary and Permanent

14.

Automobiles Service Centres

15.

Petrol?Diesel outlets having dispensing pumps of 3 Nos.
and below

16.

Bulk Kerosene storages

17.

Software centers having minimum 05 Nos. to 20 Nos. computers

18.

Bakeries and Eating houses including Ice cream parlors, Fast
food centers etc.

19.

Ice Factories

20.

Fire crackers sales outlets with temporary licence for two
weeks

21.

Carpentry and cabinet making

22.

Tyre re trading centers

23.

Leather processing units/Tanneries

24.

Warehouses and Godowns for storage of Jute, Tobacco, Chillies,

Cotton, Cashew nuts, Oils, Petrol, Gunny bags, Paper, Celluloid,
Timber, Charcoal, Furniture, Food Grains, Cloth, Paints,
Varnishes, Spirit, Rubber, Camphor, Artificial Manure and
Pesticides, Fiber and Vegetable oils with the floor area of 500
Sft. to 2000 Sft.

25.

Timber Mills, Saw Mills, Rice Mills

26.

All Small Scale/Cottage Industries

27.

Departmental Stores/Super Bazars/Super Markets

28.

Fruit Markets

29.

Commercial Show Rooms

30.

Storages of Electronic and Electrical Goods with floor area
below 2000 Sft.

31.

All Bars & Restaurants

32.

All small scale industries which are covered by Factories Act,
1948

33.

Accelerine

34.

Acitic Acid (Glacial)

35.

Acetone

36.

Acetylene (Dissolved)

37.

African Fiber

38.

Agava Fiber

39.

Aguardiente (sprits)

40.

Alcohol

41.

Alfa (Vegetable Fiber)

42.

Algerian Fiber

43.

Allyl Alcohol

44.

Aloe Fiber

45.

Alluminium Resinate

46.

Ambari Hemp (Vegetable Fiber)

47.
American Moss Fiber
48.
Ammonia
49.
Ammonia anhydrous
50.
Ammonia Bichromate
51.
Ammonia persulphate
52.
Safety cartridges and safety fuses
53.
Amorphous phosphorous
54.
Amyl Acetate
55.
Amyl Alcohol
56.
Amyl Butyrate
57.
Amyl Formate
58.
Amyl Propionate
59.
Andon Sonien Fiber
60.
Aniline
61.
Aniline Oil
62.
Aniline Black
63.
Animal Oils
64.
Anthracene
65.
Anthracene oils
66.
Ante corrosive paints
67.
Ante Foulding paints
68.
Antimony Sulphate
69.
Arca Nuts complete with husk or shell
70.
Arnica flowers
71.
Artificial silk fiber
- 72.

Artificial silk waste

73.

Asafoetida

74.

Asphalt

75.

Asphalted Felt

76.

Asphalted Paper

77.

Asphalt Saturated Felt

78.

Asphaltum

79.

Begarse

80.

Begassee (Vegetable Fiber)

81.

Bagazo

82.

Bags and Sacks

83.

Balata

84.

Balsams

85.

Bamboo Fiber

86.

Bamboo Mats

87.

Banana Fiber

88.

Barium Sulphide

89.

Bass

90.

Bassin (Vegetable Fiber)

91.

Bast (Vegetable Fiber)

92.

Battery Acid

93.

Bay leaves

94.

Beeswas

95.

Beet pulp

96.

Beliladona leaves

97.

Benjamin

98.
Benzoic Acid
99.
Benzoin
100.
Benzol
101.
Benzole
102.
Benzolene
103.
Berlin Black
104.
Bichromates of all kinds
105.
Binitrobenzene
106.
Binitrobenzol
107.
Biri leaves
108.
Bi-sulphide of Carbon
109.
Bitumen
110.
Bitumenous damp
111.
Bitumenous felt
112.
Bitumenous paint
113.
Blacking
114.
Black of all kinds
115.
Bombax cotton (Venetable Fiber)
116.
Bone Oil
117.
Borneo]
118.
Bran Oil
119.
Bratice Cloth
120.
Brewers Grains
121.
Brim Stone
122.
Bristile Fiber
- 123.

Bromelia Fiber

124.

Broom corn (Vegetable Fiber)

125.

Broom Millet (Vegetable Fiber)

126.

Brunsvick

127.

Betchu leaves

128.

Butalyde

129.

Butane

130.

Butyl Alcohol

131.

Butyl Acetate

132.

Butylamine

133.

Butylbutyrate

134.

Butyllactate

135.

Cahco Nuts

136.

Coboun Nuts

137.

Cake

138.

Calcium Cyanamide

139.

Calcium Permanganate

140.

Calcium Resinate

141.

Calcium Sulphide

142.

Canphene

143.

Camphor

144.

Camphor Oil

145.

Candles

146.

Cane Fiber

147.

Cape Palma Fiber

148.

Caraway Chaff

- 149.
Carbolic Oils
- 150.
Carbon
- 151.
Carbon Black
- 152.
Carbon Di-sulphide
- 153.
Carbonyl Chloride
- 154.
Caraube
- 155.
Cassia Leaves
- 156.
Castor Oil
- 157.
Cattle Food Cake
- 158.
Caustic Potash
- 159.
Caustic Soda
- 160.
Cello-solve Butyl
- 161.
Cello-solve Acetate
- 162.
Cerasine
- 163.
Charcoal
- 164.
Charcoal Black
- 165.
Chickle
- 166.
China Grass (Vegetable Fibre)
- 167.
Chlorobenzene
- 168.
Chlorine
- 169.
Chloromates of all kinds
- 170.
Cloth Asthalted
- 171.
Cloth Tarred
- 172.
Cloth Oiled
- 173.
Coal Gas
- 174.

Coal Pitch
175.
Coal Tar
176.
Coal Tar Dyes
177.
Coca Butter
178.
Coca Nut Fiber
179.
Coconut Oil
180.
Cod Oil
181.
Coir Dust
182.
Coir Fiber
183.
Coir Matting
184.
Coir Rope
185.
Coir Yarn
186.
Cole Nuts
187.
Collophony
188.
Common Resine
189.
Confetti
190.
Confetti Bombs
191.
Congo Fiber
192.
Copal
193.
Copal Varnish
194.
Copper Sulphide
195.
Copra
196.
Copra Cake
197.
Copra Meal
198.
Cordage sisel
199.
Cork Dust

- 200.
Cotton in fully pressed bales or otherwise
- 201.
Cotton Flock
- 202.
Cotton Grass
- 203.
Cotton Linter
- 204.
Cotton seed Cake
- 205.
Cotton seed Oil
- 206.
Cotton seed Screenings
- 207.
Cotton Straw
- 208.
Cotton Waste
- 209.
Cowrie
- 210.
Creosote
- 211.
Creosote Oil
- 212.
Cresols
- 213.
Cresilic Acid
- 214.
Crin (Vegetable fiber)
- 215.
Crotonaldehyde
- 216.
Cubra Bast
- 217.
Cumene
- 218.
Cumol
- 219.
Culed Vegetable Hair (Vegetable Fiber)
- 220.
Cus Fiber (Cus Cus Root)
- 221.
Cyanogen
- 222.
Cymene P
- 223.
Cymol
- 224.
Dammer
- 225.

Damp Course

226.

Date Palm Fiber

227.

DLT Liquid

228.

Dead Oil

229.

Dackance

230.

Decalin

231.

Dessicated Coconut Oil

232.

Diamylane

233.

Diamyl Phthalatene

234.

Diatol

235.

Dibromoacetylene

236.

Dibutyl Phthalate

237.

Dichromo Ethylene

238.

Dichloro Pentanes

239.

Diethyl Amine

240.

Diethyl Carbinol

241.

Dimethyl Ketones

242.

Dinitro Aniline

243.

Dinitro Benzene

244.

Di-Pentane

245.

Down Vegetable

246.

Dragones Blood

247.

Dried Grass

248.

Dubbin

249.

Earth Nuts (Shelled)

250.

Earth Vax

- 251.
Edible Oils
- 252.
Esparto Grass (Vegetable Fibre)
- 253.
Ethane
- 254.
Essential Oils
- 255.
Ethyl Aceto Acetate
- 256.
Gutta Jelagong
- 257.
Gutta Percha
- 258.
Hard Waste Yarn
- 259.
Health for Besoms
- 260.
Hemp of all kinds (Vegetable Fibres)
- 261.
Hemp Seed Oil
- 262.
Hemp Yarn
- 263.
Hennequem (Vegetable Fiber)
- 264.
Hessians
- 265.
Hop Fiber
- 266.
Hops spent
- 267.
Hull Fiber
- 268.
Hydro Bromic Acid
- 269.
Hydrochloric Acid
- 270.
Hydrofluoric Acid
- 271.
Hydrofluosilicic Acid
- 272.
Hydrogen
- 273.
Hydrogen Cyanide
- 274.
IFC Hemp (Vegetable Fiber)
- 275.
India Ribber
- 276.

Inflammable liquids (F.P. above 25 deg. Cent.)

277.

Inks Printing (F.P. above 25 deg. Cent.)

278.

Insecticides (F.P. above 25 deg. Cent.)

279.

Iron sulphide

280.

Isobutyl carbinol

281.

Istle Fiber

282.

Italian Hemp

283.

Italian whisk (Vegetable Fiber)

284.

Ita Palm Fiber

285.

Ivory Black

286.

Ixthe Fiber

287.

Japanese Moss

288.

Jaumaye (Vegetable Fiber)

289.

Joss Paper and sticks

290.

Juniper

291.

Junk

292.

Jute in fully pressed bales

293.

Jute cuttings

294.

Jute Yarn

295.

Kopok (Vegetable Fiber)

296.

Kopok Seed

297.

Kaur

298.

Kerosene Oil

299.

Kittol (Vegetable Fiber)

300.

Kumbi (Vegetable Fiber)

301.

Lamp Black

- 302.
Lamp Oil
- 303.
Lead Di-oxide
- 304.
Lead Respinate
- 305.
Leather pickers (Oily)
- 306.
Leaves dried
- 307.
Lechugilla (Vegetable fiber)
- 308.
Lime unslaked
- 309.
Linen Fiber
- 310.
Linters
- 311.
Medagascar Fiber
- 312.
Magnesium Bromate
- 313.
Magnesium Candles
- 314.
Magnesium Ribbon
- 315.
Magnesium Forches
- 316.
Magnesium Wire
- 317.
Magney Fiber
- 318.
Manganese Di-oxide
- 319.
Manganese Resinate
- 320.
Manila Hemp (Vegetable Fiber)
- 321.
Manila Yarn
- 322.
Manila Rope Tarred
- 323.
Manjak
- 324.
Matches of all kinds
- 325.
Mats archangel or Russian
- 326.
Matting used
- 327.

Maxphalt

328.

Methanol

329.

Mercuric Chloride

330.

Methane

331.

Methylated Spirit

332.

Methyl Cello Solve

333.

Methyl Chloride

334.

Mexican Fiber

335.

Millet Stack (Vegetable Fiber)

336.

Mineral Black

337.

Mineral Oil

338.

Mineral Turpentine

339.

Mineral Vax

340.

Molaxcuit

341.

Molasses Meal

342.

Molassine Meal

343.

Monkey Bass (Vegetable Fiber)

344.

Monkey Bread (Tree Fiber)

345.

Monkey Nuts (Shelled)

346.

Monochloro Acetic Acid

347.

Mono Nitro Line

348.

Mono Nitro Aniline

349.

Mono Nitro Naphthalene

350.

Moss dried of all kinds

351.

Mould Coats

352.

Mulberry Fiber

- 353.
Murva Fiber
- 354.
Musa Fiber
- 355.
Murrah
- 356.
Naptha (F.P. above 24.4 deg. cent.)
- 357.
Napthalene
- 358.
Nettle Fiber
- 359.
Newzeland Flax (Vegetable Fiber)
- 360.
Newzeland Hemp (Vegetable Fiber)
- 361.
Nickel Ferroxide
- 362.
Nitra Aniline
- 363.
Nitro Aniline
- 364.
Nitro Benzene
- 365.
Nitro Cellulose
- 366.
Nitro Chalk
- 367.
Nitro Methanol
- 368.
Nitro Phenol
- 369.
Nitroze Phenel
- 370.
Nitro Toluene
- 371.
Nitrous Oxide
- 372.
Oakum
- 373.
Oil Cake
- 374.
Oil Foots
- 375.
Oil Gas
- 376.
Oils (Animal, Fish and essential)
- 377.
Oils Vegetables
- 378.

Oils Mineral (F.P. above 24.4 deg. cent.)

379.

Oil Seed Cake

380.

Oil sheets

381.

Oily Bags

382.

Oily Waste

383.

Oleine

384.

Oleo

385.

Oleum

386.

Opponax

387.

Orthonitro Phenol

388.

Orthonitro Toluene

389.

Oxygen Gas (in Cylinders)

390.

Ozo Kerite

391.

Paint Removers (FP above 24.4 deg. cent.)

392.

Paints (FP above 24. 4 deg. cent.)

393.

Palm Butter

394.

Palmette Grass

395.

Palm Fibers

396.

Palm Oil

397.

Palm Kernels

398.

Palm Nuts

399.

Palmerah Fiber

400.

Pampas Plumes

401.

Paper

402.

Paper Shavings

403.

Papyrous (Vegetable Fiber)

- 404.
Paraffin Vax
- 405.
Para Matta Grass (Vegetable Fiber)
- 406.
Para Nitro Acetanylide
- 407.
Para Nitro Phenol
- 408.
Para Nitro Sodimethyl Aniline
- 409.
Peat Dust
- 410.
Peat Mould
- 411.
Permanganates of all kinds
- 412.
Peroxide of all kinds
- 413.
Persulphates of all kinds
- 414.
Petroleum Ether
- 415.
Petroleum Jelly
- 416.
Petroleum Oils
- 417.
Pharmaceutical Chemicals and Drugs
- 418.
Phenol
- 419.
Phosphorous Red
- 420.
Phosphorous Penta Chloride
- 421.
Phosphorous Sulphides
- 422.
Phosphorous Trichloride
- 423.
Photographic Powders
- 424.
Pissava of all kinds (Vegetable Fiber)
- 425.
Pine apple Grass
- 426.
Pine Bark
- 427.
Pita Fiber
- 428.
Pitch
- 429.

Plantaine Fiber

430.

Poisons and Polishing Liquids

431.

Pontionac

432.

Potassium Bichromate

433.

Potassium Hydroxide

434.

Potassium Permanganate

435.

Potassium Persulphate

436.

Potassium Sulphinde

437.

Pyrene

438.

Raffia (Vegetable Fiber)

439.

Rags (Clean)

440.

Ramie (Vegetable Fiber)

441.

Rayon Fiber

442.

Rayon Waste

443.

Rayophane Paper

444.

Rectified Spirit

445.

Red phosphorous

446.

Renovators (FP above 24.4 deg. cent.)

447.

Resins (Natural)

448.

Resinates

449.

Rhea Fiber

450.

Rhigolene

451.

Rice Root (Vegetable Fiber)

452.

Rock Gas

453.

Rope Tarred

454.

Rosin

- 455.
Rosin Oil
- 456.
Rosin Spirit
- 457.
Rubber Spirit
- 458.
Rubber Goods
- 459.
Rubber Waste
- 460.
Sacks and Bags
- 461.
Salvage Goods
- 462.
Sandarac
- 463.
Sansevieria Biores
- 464.
Saw Dust
- 465.
Shavings Wood or Paper
- 466.
Sheets Oiled
- 467.
Ships Flares
- 468.
Sisal
- 469.
Sodium Bichromate
- 470.
Sodium Hydroxide
- 471.
Sodium Permanganate
- 472.
Salvents (FP above 24.4 Deg. cent.)
- 473.
Soot
- 474.
Sorghum Stalk (Vegetable Fiber)
- 475.
Spangle Lights
- 476.
Spanish Black
- 477.
Spirits of Salts
- 478.
Stains (FP above 24. 4 deg. cent.)
- 479.
Stearic Acid
- 480.

Stearlime

481.

Straw (Vegetable Fiber)

482.

Straw developers

483.

Straw Plants

484.

String Tarred

485.

Suint

486.

Sulphide, Waste Liquor

487.

Sulphur Chlorides

488.

Sulphur Dyes

489.

Sulphur Praecip-1 LB Packets

490.

Sulphuric Acid Dilute

491.

Sunn Hemp (Vegetable Fiber)

492.

Tallow

493.

Tampico Hemp (Vegetable Fiber)

494.

Tar of all kinds

495.

Tar Oils and their liquid products

496.

Tarpaulins

497.

Tarpaulin Papers

498.

Teasles

499.

Terebene

500.

Tetra Nitro Methyl Aniline

501.

Textile Materials Oiled

502.

Thistle down (Vegetable Fiber)

503.

Thus

504.

Thyme

505.

Tow of all kinds

- 506.
Tree Cotton (Vegetable Fiber)
- 507.
Tri Cnesyl Phosphate
- 508.
Tri Sodium Phosphate
- 509.
Tula Fiber
- 510.
Turkey Red Oil
- 511.
Turpentine
- 512.
Twine Tarred
- 513.
Varnishes (FP above 24.4 deg. cent.)
- 514.
Vaseline
- 515.
Vegetable Black
- 516.
Vegetable Down
- 517.
Vegetable Fibers of all kinds
- 518.
Vegetable Horse Hair
- 519.
Vegetable Silk
- 520.
Vegetable Wool
- 521.
Wagner Lockheed
- 522.
Waste of all kinds
- 523.
Water proofed cloth using an oil based solution
- 524.
Water proofing solutions (FP above 24.4 deg. cent.)
- 525.
Wax of all kinds
- 526.
White Spirit
- 527.
Wood Fiber
- 528.
Wood flour
- 529.
Wood Meal
- 530.
Wood Wool
- 531.

Wool Grease

532.

Xylene (FP above 24.4 deg cent.)

533.

Yucca Fiber

534.

Zacaton (Vegetable Fiber)

535.

Zinc Bi-chromate

536.

Zinc Dust

537.

Acetylene Engineers

538.

Agricultural implement manufacturers

539.

Artificial flower Manufacturers

540.

Auctioneers

541.

Bag Manufacturers

542.

Bedding and Mattresses Manufacturers

543.

Bill Posters

544.

Biscuit Manufacturers (Small Scale)

545.

Blacksmiths and Farriers

546.

Bottle Merchants

547.

Brush Makers

548.

Builders and Applied Trades

549.

Cap and Hat Makers

550.

Carbide of Calcium Makers

551.

Carmen

552.

Carriers

553.

Case Makers

554.

Chemists

555.

Clothiers and Out fitters

556.

Colour Manufacturers

- 557.
Comb Manufacturers
- 558.
Coopers
- 559.
Cork Merchants
- 560.
Curriers and Tanners
- 561.
Decorators
- 562.
Drapers
- 563.
Druggists
- 564.
Dyers and Cleaners
- 565.
Electrical Suppliers
- 566.
Enamellers
- 567.
Muslin Clippers
- 568.
Envelope Makers
- 569.
Export Pakers
- 570.
Fancy Box Makers and Goods Traders
- 571.
Fish Curers and Fried Fish shops
- 572.
Floor Cloth Manufacturers
- 573.
Forage Merchants
- 574.
Founders
- 575.
French Polishers
- 576.
Furriers
- 577.
Galvanizers
- 578.
Gas Singers and Cloth Pressers
- 579.
Glass Works
- 580.
Glovers
- 581.
Glue Merchants
- 582.

Gramophone and Record Traders

583.

Grossers and Coffee Roasters

584.

Gun smiths

585.

Garment and Textile Manufacturers

586.

Hatters

587.

Hops

588.

Hossiers

589.

Hot Pressers

590.

Incandescent Mantle Makers

591.

India Rubber and Guttapercha Manufacturers

592.

Iron Founders

593.

Job Masters

594.

Joiners

595.

Lace Manufacturers

596.

Lacquer Manufacturers

597.

Launderies

598.

Litho Graphic Printers

599.

Munition Makers

600.

Milleners

601.

Mill Wrights

602.

Packing Case Makers

603.

Paper Bag and Box Makers

604.

Rag and Waste Dealers

605.

Sack and Bag Manufacturers

606.

Skin Dressers

607.

Soap Boilers

608.

Stables

609.

Upholstrers

610.

Varnish Manufacturers

611.

Water Proofers

612.

Whar Fingers

613.

Wheel Wrights

(II)

Category of Buildings/Materials/Trades coming under Licence fee of Rs. 1000/-

Sl. No.

Description of Hazard

(1)

(2)

1.

Theaters and Cinema halls?Air conditioned/Air-cooled
irrespective of seating capacity

2.

Hotels/Restaurants/Dhabas with above 100 seating capacity ?
includes Tiffin/Meal Hotel. etc.

3.

Lodgings with 50 Rooms and above

4.

All Clubs

5.

Residential Schools and Colleges with 100 to 1000 inmates

6.

All Buildings/Offices provided with Central A/C System

7.

Transport Godown having the floor area of 2000 Sft. and above

8.

Liquified Petroleum Gas Cylinders Storage Godown

9.

Major Automobile Show Rooms (Two wheelers and Three wheelers)

10.

Establishments provided with Central Air Conditioning System

11.

Petrol/Diesel outlets having Dispensing Pumps 4 Nos. and above

12.

Software Center with more than 20 Computers and Software
Training Institutes issuing Degree/Diploma Certificates

13.

Multi Level Parking Hazard

14.

Laboratories and Research Establishments

15.

Bulk Storage of Electronic and Electrical Goods with Floor

area exceeding 2000 Sft.

16.

Explosive Material Storage/Manufacture

17.

Ammunition Storage/Manufacture

18.

Non-residential Schools with above 500 inmates

19.

Manufacture/Repairing by any process of aerated water/ Mineral water

20.

Leather Processing Units

21.

Warehouses and Godowns with floor area 2000 Sft. and above

22.

Mills like Cotton/Rayon/Synthetic Mills/Jute Mills, Oil Mills, Dying and Printing Mills, Paper Mills

23.

Absolute Alcohol

24.

Accumulator Acid

25.

Accumulator cases celluloid

26.

Acetal

27.

Acetaldehyde

28.

Acetone Oils

29.

Acetylene (Liquid)

30.

Acetyloid

31.

Acid

32.

Aconite leaves

33.

Acrylenitrile

34.

Aeroplane Flares

35.

Alluminium Carbide

36.

Alluminium Dust

37.

Alluminium Paste

38.

Alluminium Powder

39.

Alluminium Sulphocyanide

40.
Ammonium Chloride
41.
Ammonium Cyanide
42.
Ammonium Nitrate
43.
Ammonium Picrate
44.
Ammonium Perchlorate
45.
Ammonium Sulphate Nitrate
46.
Ammonium Sulphocyanide
47.
Amorces (Explosives)
48.
Amyl Amine
49.
Amyl Chloride
50.
Amyl
51.
Amyl Hydrate
52.
Amyl Ether
53.
Amyl Nitrate
54.
Amyl oxide
55.
Anhydrous Denaturated Alcohol (Ansol M & Ansol PR)
56.
Antimony Potassium Tartrate
57.
Aqua Fortis (Nitric Acid)
58.
Aqua Regia
59.
Areca Nuts without husk or shell
60.
Barium Acetate
61.
Barium Binoxide
62.
Barium Bromate
63.
Baromide
64.
Barium Carbonate
- 65.

Barium Chlorate
66.
Barium Chloride
67.
Barium Chromate
68.
Barium Cyanide
69.
Barium Ethyl sulphate
70.
Barium Fluoride
71.
Barium Hydrate
72.
Barium Hydroxide
73.
Barium Iodide
74.
Barium Manganate
75.
Barium Nitrate
76.
Barium Oxide
77.
Barium Peroxide
78.
Barium Sulphocyanate
79.
Barium Sulphocyanide
80.
Bengal Lights
81.
Benzene
82.
Benzine
83.
Benzoyl Peroxide
84.
Binoxilate of Potash
85.
Blasting Powder
86.
Bon-bons (Crackers)
87.
Bromine
88.
Bronze Powder
89.
Butyl Aldehyde
90.
Butyl Chloride

91.
Butyl Nitrate
92.
Calcium Carbide
93.
Calcium Chlorate
94.
Calcium Cyanide
95.
Calcium Nitrate
96.
Calcium Peroxide
97.
Calcium Phospide
98.
Calcium Phospite
99.
Calcium Silicide
100.
Calcium Sulpho cyanide
101.
Cape for Toy Pistols
102.
Carbic Cake
103.
Carbolic Acid
104.
Carbon Bi-sulphide
105.
Cellophane Paper
106.
Celluloid
107.
Celluloid solution
108.
Cement Celluloid
109.
Ceric Ammonium Nitrate
110.
Casium
111.
Casium Nitrate
112.
Chilly Salt Petry
113.
Chlorate Mixture (Explosive)
114.
Chlorates of all kinds
115.
Chlorosulphonic Acid
- 116.

Chromic Anhydride
117.
Cleaning and Polishing liquids, creams, Pastes
118.
Coal dust
119.
Coal Pulverized
120.
Collodion
121.
Copper Chlorade
122.
Copper Nitrate
123.
Cordite (Explosive)
124.
Cymogens
125.
Detonators
126.
Diacetone Alcohol
127.
Dibutyl Oxalate
128.
Diethyl Carbonate
129.
Dimethyl Amine
130.
Dinitro Naphthalene
131.
Dinitro phenol
132.
Dinitro toluene
133.
Di-oxane
134.
Disinfectant Liquids
135.
Dynamite
136.
Enamils
137.
Ethyl Acetate
138.
Gun Powder
139.
Hexane
140.
Hydrogen Peroxide
141.
Hydrochlorous Acid

- 142.
Industrial Alcohol
- 143.
Inflammable liquids (FP below 25 deg. Cent.)
- 144.
Inks Printing (FP below 25 deg. Cent.)
- 145.
Insecticides (FP below 25 deg. Cent.)
- 146.
Isopropyl Alcohol
- 147.
Isopropyl Amine
- 148.
Lacquers
- 149.
Lubricating Oils
- 150.
Lycopodium Powder
- 151.
Lythene
- 152.
Magnesium Nitrate
- 153.
Magnesium Peroxide
- 154.
Magnesium Powder
- 155.
- 156.
Mercuric Fulminate
- 157.
Metallic Powders
- 158.
Metallic Potassium
- 159.
Methyl Acetate
- 160.
Methyl Alcohol
- 161.
Methyl Ethyl Ketone
- 162.
Methyl Formate
- 163.
Naphta (FP below 24.4 deg. cent.)
- 164.
Nitrate Mixture
- 165.
Nitrates of all kinds
- 166.
Nitre (Sweet spirit)
- 167.
Nitric Acid

- 168.
Nitrites of all kinds
- 169.
Nitro Compounds (Explosives)
- 170.
Nitro Glyserine
- 171.
Nitro Mannite
- 172.
Nitro Storch (Explosive)
- 173.
Oils Illuminating
- 174.
Oils Mineral (FP below 24.4 deg. cent.)
- 175.
Olibanum
- 176.
Paint removers (FP below 24.4 deg. cent.)
- 177.
Paints (FP below 24.4 deg. cent.)
- 178.
Para Aldehyde
- 179.
Pentane
- 180.
Perchlorate Mixtures
- 181.
Perchlorates of all kinds
- 182.
Percussion Caps
- 183.
Petrol
- 184.
Phosgene
- 185.
Phosphine
- 186.
Phosphonium Iodide
- 187.
Phosphoric Acid
- 188.
Phosphorous White
- 189.
Phosphorous sesqui sulphide
- 190.
Picramic Acid
- 191.
Picric Acid
- 192.
Picrates (Explosives)
- 193.

Poppy Seed Oil

194.

Potable spirits

195.

Potassium

196.

Potassium Chlorate

197.

Potassium Nitrate

198.

Potassium Nitrite

199.

Potassium Perchlorate

200.

Potassium Peroxide

201.

Powders Metallic

202.

Propyl Acetate

203.

Propyl Alcohol

204.

Pure Alcohol

205.

Pyridine

206.

Pyridine Base

207.

Rags (Oily or Greasy)

208.

Renovators (FP below 24.4 deg. cent.)

209.

Rockets

210.

Rubber Solution

211.

Signal (Explosive)

212.

Snaps for Crackers

213.

Sodium

214.

Sodium Amalgum

215.

Sodium Chlorate

216.

Sodium Hydro Sulphite

217.

Sodium Nitrate

218.

Sodium Nitrite

- 219.
Sodium Peroxide
- 220.
Sodium Sulphide
- 221.
Sodox
- 222.
Solvents (FP below 24.4. deg. cent.)
- 223.
Spirits Industrial
- 224.
Spirits of Wine, Rectified
- 225.
Spirits potable
- 226.
Stains (FP below 24.4 deg. cent.)
- 227.
Strontium
- 228.
Strontium chlorate
- 229.
Strontium Nitrate
- 230.
Strontium Peroxide
- 231.
Sulphuric Acid (Concentrate)
- 232.
Sulphuric Ether
- 233.
Tetralin
- 234.
Tetra Nitro Aniline
- 235.
Tetra Nitro Naphthalene
- 236.
Rhermit
- 237.
Thorium Nitrate
- 238.
Toluene
- 239.
Tri Nitro Aniline
- 240.
Tri Nitro Benzene
- 241.
Tri Nitro Naphthalene
- 242.
Tri Nitro Phenol
- 243.
Tri Nitro Toluene
- 244.

Tri Nitro Apisole

245.

Varnishes (FP below 24.4 deg. cent.)

246.

Vetriol

247.

Waste Celluloid

248.

Waste Oily or Greasy

249.

Water Proofing Solutions (FP below 24.4 deg. cent.)

250.

White Phosphorous

251.

Wood Alcohol

252.

Wood Spirit

253.

Xylene (FP below 24.4 deg. cent.)

254.

Xylonite

255.

Xylonite Solutions

256.

Yellow Phosphorous

257.

Zinc Chlorate (Metallic)

258.

Zinc Peroxide

259.

Zinc Powder

260.

Petroleum products storing, packing, Cleansing
preparing/ Manufacturing by any process of the following:

(1) Non-dangerous Petroleum like Kerosene Oil, Mineral
Turpentine, Powerine (Power Kero), Furnace Oil, Vapourising Oil,
Aviation Turbine Fuel, Mobile Power Oil etc.

(2) Heavy Petroleum like High Speed Diesel (HSD), Light diesel
oil (LDO), Tea drier oil etc.

(3) Heavy Oils like Lubricating oils, Vaseline, Petroleum
Jellies, White oils, Grease etc.

261.

Acid Manufacturers/Dealers

262.

Ammonia Manufacturers

263.

Asphalt and Bitumen Manufacturers

264.

Biscuit Manufacturers

265.

Boat Builders

266.
Boot and Shoe Factories
 267.
Brewers
 268.
Bronze Powder Manufacturers
 269.
Builders & Applied Traders
 270.
Butchers & Tripe Boilers
 271.
Celluloid Goods Manufacturers
 272.
Chemical Manufacturers
 273.
Ink (Printing) Manufacturers
 274.
Jewelers
 275.
Marine Stores
 276.
Music Instrument Makers
 277.
Oil Processing/Recycling/Extraction Units
 278.
Piano Manufacturers
 279.
Tarpaulin Makers
 280.
Turkish Baths
- (III)
Category of Buildings/Material/Trades coming under Licence fee of Rs. 2,500/-
Sl. No.
Description of Hazard
- (1)
(2)
1.
All stadiums (Indoor and Outdoor) and concert Halls
 2.
Cold Storages
 3.
Film Studio, Film Storage Hazard, Film Laboratory Colouring rooms and Film distribution companies
 4.
Fire crackers manufacturers and storage/sales outlets
(Permanent licence holders)
 5.
Cement Manufacturers
 6.
Coach Builders
 - 7.

Ship Builders

8.

Ship Handlers

9.

Garments & Textile Manufacturers

10.

Major Automobile show rooms & Authorized Service Centers

(Four Wheelers)

11.

All Residential Schools/Colleges more than 1000 inmates

12.

Aqua products processing units

(IV)

Category of Buildings/Material/Trades coming under Licence fee of Rs. 5,000/-

Sl. No.

Description of Hazard

(1)

(2)

1.

Multi-Speciality, Super Speciality Hospitals/Nursing Homes and Corporate Hospitals

2.

All Star Category Hotels

3.

All Large and Medium Scale Industries/Factories registered under Factories Act, 1948

4.

Distilleries & Breweries

5.

Power Generating Industries

6.

Underground shopping centers

7.

Petroleum Refineries

8.

I-MAX and Multiplex Theatres

Form - 1

(See Rule 3)

Andhra Pradesh Fire and Emergency Operational Services Certificate of Appointment

(Affix Photograph here)

This is to certify that Sri has been appointed as a member of Andhra Pradesh Fire Services in the rank of on under the Act and is vested with the powers, functions and privileges of a member of service as given in the Andhra Pradesh Fire Service Act and Rules.

Form - 2

(See Rule 13)

Report on damage caused to premises by members of service during firefighting and rescue operations

Name of the Fire Station:

(1)

Date and Time of call received :

(2)

Fire Report No. and Date:

- (3)
Name and Address of the premises where fire occurred :
- (4)
Description of property involved :
- (5)
Name and Address of the premises to which damage caused :
- (6)
Description and details of damage caused to the premises in the course of firefighting and rescue :
- (7)
Reasons for breaking/pulling down the structures :
- (8)
Claim of the amount by the party :
- (9)
Particulars of references to the R&B authorities :
- (10)
Remarks :
- Signature of Officer-in-charge

Form - 3

(See Rule 17)

Seizure Memorandum

To

Name: Date & Time

Address: Place of Panchanama

..... Case No.

..... Name & Address of

..... Panchas

(1)

(2)

The following property belonging to you has been seized and detained under Section 14(2) of A.P. Fire Service Act, 1999 for the reasons stated below:

Sl. No.

Place from where seized

Particulars of seized property

Quantity

Reasons for seizure and Detention

Signature of the Authority

Signature of the person from whom seized

Signature of the Panchas:

(1)

(2)

Form -4

(See Rule 17)

Panchanama

Case No.

Place :

Date :

Time :

(1)

Name and Address of the Firm

(2)

Name and Address of the person-in-charge present

(3)

Name and Address of the Panchas

1. Sri/Smt.

S/o./D/o./W/o.

Resident of

age years

Occupation

2. Sri/Smt.

S/o./D/o./W/o.

Resident of

age years

Occupation

We, the above Panchas are this day Called by Sri designation Place to witness the act of seizing certain property from address of the Firm which were possessed and exposed in the premises of the said Firm. In our presence, the said Fire Officer seized the following mentioned property which we testify to be correct.

Sl. No.

Place from where seized

Particulars of seized property

Quantity

Reasons for seizure and Detention

The Panchanama is read over and explained to us and it is correct account of when we saw.

Signature of the Fire Officer

Signature of the Panchas:

(1)

(2)

Received the copy of Panchanama

Signature of the person-in-charge of the premises

Form - 5

(See Rule 18)

Application for Grant/Transfer of Fire Service Licence

(1)

Name and Address of the premises/Building:

(2)

Name of the Firm/Company or Factory/Business :

(3)

Name of the Owner/Occupier

(4)

Full postal address for communication :

(5)

Description of :

(a)

Nature of Business, Trade or Process :

(b)

Commodities and quantities stored/handled

(c)

Position of storage in relation to No. of rooms/ Floor Area

(d)

Inflammable liquids and explosive materials

(6)

Type of Occupancy:

(a)
Residential

(b)
Educational

(c)
Institutional

(d)
Assembly

(e)
Business

(f)
Mercantile

(g)
Industrial

(h)
Storage

(i)
Hazardous

(7)
Building:-

(a)
General Constructional features:

Low Fire risk - Cement Concrete or brick-walled
Or

Medium Fire risk - brick-walled and timber
Or

High Fire risk - Mostly timber framed such as timber floors, timber roof, timber-staircase etc.

(b)
Particulars: —

(i)
No. of Storeyes and basement if any

(ii)
No. of exits

(iii)
Details of ceiling

(iv)
No. of staircases and whether enclosed or open

(v)
Verandah or balconies

(vi)
Attics, Mezzanine floor, lofts, etc.

(c)
Details of other structures within 20 metres all around

(i)
North

(ii)
South

(iii)
East

(iv)
West

(8)

Width of abutting road/street

(9)

Maximum amount of Horse Power of Machinery used

(10)

Maximum No. of persons present including (occupants, employees, visitors etc.)

(11)

Nearest means of communication:

(i)

Telephone No.

(ii)

Fire Station

(iii)

Police Station

(iv)

Any other

(12)

Details Fire fighting equipment installed

(i)

Fire buckets

(ii)

Fire Extinguishers (Foam/CO2/DCP)

(iii)

Hose Reel Hose

(iv)

Hydrant systems

(v)

Wet-risers

(vi)

Sprinklers

(vii)

Any other

(13)

Details of Fire detection and alarm system

(14)

Details of Watch and Ward, if any

(15)

Details of water sources

(i)

Inside the premises

(ii)

Nearest outside the premises

(iii)

Overhead and capacity

(16)

Details and safety measures for:

(i)

Electrical transformer

(ii)

Generator

(iii)

Control Panel

(iv)

Airconditioning and refrigeration system

(v)

Heating equipment

(vi)

Storage of cylinders

(vii)

Any other

(17)

Particulars of fee remitted

Challan No. and Date

Certified that the above particulars furnished are true to the best of my knowledge.

Signature of the applicant

Date:

Place:

Form - 6

[See Rule 19(1)]

Fire Service Licence

Date

Licence No.

(1)

Name and Address of the premises/Building:

(2)

Name of the Firm/Company or Factory/Business:

(3)

Name of the Owner/Occupier:

(4)

Full postal address for communication:

(5)

Description of:-

(a)

Nature of Business, Trade or Process:

(b)

Commodities and quantities stored/handled

(c)

Position of storage in relation to No. of rooms/Floor Area

(d)

Inflammable liquids and explosive materials

(e)

Maximum Horse Power installed

(6)

Type of Occupancy:

Licence is hereby granted under Section 17 of the A.P. Fire Service Act, 1999 to the above premises, within the jurisdiction of Fire Station, subject to the conditions prescribed under the A.P. Fire Service Rules.

This Licence is valid upto or till it has been duly cancelled.

Signature of Issuing Authority

Office Seal with date.

Form - 7

[See Rule 19(5) and 21(4)]

Form of Appeal

Before the Director General of Fire Services (Appellate Authority) Appeal No. dated of Sri S/o./D/o./ W/o.resident of

Appellant

Versus

Respondent

Authorized Officer (Designation)

Appeal under Rule framed under Section 17(2) of A.P. Fire Service Act against the notice/order of (Respondent)

Sir,

The Appellant respectfully submit as under: —

(1)

Statement of Facts

(2)

Ground of Appeal

(3)

Appeal is within time i.e. within 30 days from the date of receipt of order/notice

(4)

No other appeal or any matter relating to the subject matter to this appeal is pending in any Court of Law.

Signature of Authorized Representative if any

Signature of Appellant

Verification

1.

, the appellant do hereby declare that what is stated above is true to the best of my personal knowledge and belief and that I have not suppressed any material facts.

Verified today, the day of year

Place:

Signature of Appellant

Signature of Authorized Representative if any

Form - 8

[See Rule 21(2)]

Application for renewal of Fire Service Licence

(1)

Name and Address of the premises/Building

(2)

Name of the Firm/Company or Factory/Business

(3)

Name of the Owner/Occupier

(4)

Full postal address for communication

(5)

Description of:-

(a)

Nature of Business, Trade or Process b)Commodities and quantities stored/handled

(c)

Position of storage in relation to No. of rooms/ Floor Area

(d)

Inflammable liquids and explosive materials

(6)

Type of Occupancy:-

(a)

Residential

(b)

Educational

(c)

Institutional

(d)

Assembly

(e)

Business 1) Mercantile g) Industrial h)Storage i) Hazardous

(7)

Existing Licence No. and Date and Designation of Issuing Authority

(8)

Particulars of fee remitted Challan No. & Date

(9)

Details of modification/additions done if any

(a)

Structural

(b)

Storage

(c)

Quantity of Commodities/inflammable liquids/ Explosive materials

(d)

Business

(e)

Electrical appliances

(f)

Means of Escape

(g)

Any other, furnish details

Certified that the above particulars furnished are true to the best of my knowledge.

Signature of the Applicant

Place:

Date:

Form - 9

[See Rule 25(1)]

Form of Notice to inspect the premises

I, empowered by Section 20 of the A.P. Fire Service Act, 1999 and Rule 25(1) of A.P. Fire and Emergency Operations and Levy of Fee Rules, 2006 do hereby give you notice that on expiry of not less than three hours from the time of service of this notice upon you i.e. date and time , I shall enter and inspect your building/premises bearing No. located at for the purpose of ascertaining the adequacy or contravention of fire prevention and fire safety measures as required to be provided under Rules framed under the A.P. Fire Service Act, 1999.

Signature of the Inspecting Officer

To

..... Owner/Occupier

.....

.....

.....

Form - 10

[See Rule 26(1)]

Inspection Report

Name and Designation of the Inspecting Officer

Date of Inspection:

Time of Inspection:

(1)

Name and Address of the premises/Building

(2)

Name of the Firm/Company or Factory/Business

(3)

Name of the Owner/Occupier

(4)

Name of the person-in-charge present during the Inspection

(5)

Full postal address for communication

(6)

Description of:-

(a)

Nature of Business, Trade or Process

(b)

Commodities and quantities stored/handled

(c)

Position of storage in relation to No. of rooms/ Floor Area and adequacy of fire precautions adopted for storage of hazardous goods

(d)

Inflammable liquids and explosive materials

(e)

Raw materials

(f)

Machinery

(g)

Electric motors

(h)

Heating equipment like boilers, etc.

(i)

Commodities and quantity applied for in case of storage of chemicals with reference to Explosive and Petroleum Rules

(j)

Type of occupancy

(7)

Building:-

(a)

Constructional features:

(i)

General

Low Fire risk - Cement Concrete or brick-walled

Or

Medium Fire risk - brick-walled and timber

Or

High Fire risk - Mostly timber framed such as timber-floors, timber roof, timber-staircase etc.

(b)

Particulars:

(i)

No. of Storeys and basement if any;

(ii)

No. of exits

(iii)

Details of ceiling

(iv)

No. of staircases and whether enclosed or open

(v)

Verandah or balconies

(vi)

Attics, Mezzanine floor, lofts, etc.

(vii)

Whether prescribed distance in respect of means of escape is maintained or not.

(c)

Details of other structures within 20 metres all around the building and open spaces/approach for fire vehicle

Structures

(i)

North

(ii)

South

(iii)

East

(iv)

West

(8)

Width of abutting road/street

(9)

Maximum amount of Horse Power of Machinery used

(10)

Maximum No. of persons present including (occupants, employees, visitors etc.)

(11)

Nearest means of communication:

(i)

Telephone No.

(ii)

Fire Station

(iii)

Police Station

(iv)

Any other

(12)

Details of Firefighting equipment installed:

(i)

Fire Buckets

(ii)

Fire Extinguishers (Foam/CO2/DCP)

(iii)

Hose Reel Hose

(iv)

Hydrant systems

(v)

Wet-risers

(vi)

Sprinklers

(vii)

Any other

(13)

Details of Fire detection and alarm system

(14)

Details of Watch and Ward, if any

(15)

Details of water sources

(i)

Inside the premises

(ii)

Nearest outside the premises

(iii)

Overhead and capacity

(16)

Details of safety measures for:

(i)

Electrical transformer

(ii)

Generator

(iii)

Control Panel

(iv)

Air-conditioning and refrigeration system

(v)

Heating equipment

(vi)

Storage of cylinders

(vii)

Any other

(17)

Particulars of fee remitted

Challan No. and Date

Recommendations:

(1)

Commodities and quantity

(2)

Location

(3)

Storage arrangements

(4)

Fire precautionary measures suggested

(5)

Structural recommendations

(6)

Protective measures against exposure hazard

(7)

General

Whether issue of licence is recommended, if not, specify the reasons thereof.

Signature of Inspecting Officer

Date:

Place :

Form - 11

[See Rule 26(1)]

Periodical Inspection Report

Licence No.

Date of Inspection

Time of Inspection

Name & Designation of Inspecting Officer

(1)

Name and Address of the premises/building

(2)

Name of the Firm/Company/business/factory etc.

(3)

Type of Occupancy

(4)

Name of the Occupier/Owner

(5)

Name of the person-in-charge present during the inspection

(6)

Date of previous inspection if any

(7)

Details of notice served if any

(8)

Breach of conditions/recommendations of Fire Safety measures

(9)

Compliance details of the Owner/Occupier

(10)

Details of the accidents occurred from the last inspection

(i)

Property involved

(ii)

Property damaged

(iii)

Cause of Fire

(iv)

Particulars of insurance claimed

(11)

Observations made by the Inspecting Officer

(12)

Recommendations:

Signature of the Inspecting Officer

Date :

Place

Form - 12

[See Rule 26(2)]

Notice for violation of Fire Prevention and Fire Safety Measures

I, empowered by Section 21 of A.P. Fire Service Act, 1999 and Rule 26 of A.P. Fire and Emergency Operations and Levy of Fee Rules, 2006 on the basis of inspection conducted by me on do hereby call upon you to undertake the following fire prevention and fire safety measures in building/premises No.

(1)

- (2)
- (3)
- (4)
- (5)

.....

.....

.....

You have violated the conditions of Fire Service Licence and thereby endangering lives and property of the inmates and public in and around your premises.

Take notice hereby that you are directed to undertake the above fire safety and fire prevention measures ensuring the safety within 15/30 days from the date of receipt of this notice, failing which your Fire Service Licence shall be cancelled/your renewal application refused besides action will be taken as per the Rules.

Signature of the Inspecting Officer

Date:

Place:

Form -13

[See Rule 29(5)(a)]

Notice to obtain Fire Service Licence

Take notice that you are running trade located at premises No without obtaining Licence from the A.P. Fire Services Department under Section 30 of A.P. Fire Service Act, 1999.

Hence, you are served this Notice to obtain licence within 30 days from the date of receipt of this notice, failing which statutory action will be taken against you as per rules.

Signature of the Authorized Officer

Date:

Place:

To

Smt./Sri.

.....

.....

Form - 14

[See Rule 29(5)(b)]

Show cause notice to be served on the Defaulter

Whereas, it is necessary in public interest and safety, I hereby direct you, Sri/Smt. /M/s. (F irm/Company/ Business/Owner/Occupier) possessor of Fire Service Licence No. dated that you have violated the conditions mentioned therein by not maintaining the firefighting system in satisfactory working condition/ defective/having not provided the following thereby endangering lives and properties of the inmates and public in and around your premises.

- (1)
- (2)
- (3)
- (4)
- (5)

Take notice hereby, that you are directed to rectify the above defects and re-set the fire protection system ensuring the safety within 30 days from the date of receipt of this notice lest, Fire Service Licence issued to you shall be cancelled/your renewal application refused besides action taken against you to prosecute in the Court of Law under Section 31 of A.P. Fire Service Act, 1999.

You are directed to acknowledge receipt of this notice on its duplicate.

Signature of the Authorized Officer

Date

Place

Sri

.....

.....

Form - 15

[See Rule 37(2)]

Andhra Pradesh Fire and Emergency Operational Services

Certificate of Appointment for members of Auxiliary Fire Service

Affix photograph here

This is to certify that Sri has been appointed as a member of Auxiliary Fire Service in the rank of on under Section 8 of the Andhra Pradesh Fire Service Act and is vested with the powers, functions and privileges of a member of service as given in Rule 3 of the Andhra Pradesh Fire and Emergency Operational and Levy of Fee Rules.

(Issuing Authority)

(Director General of Fire Services)/

(Regional Fire Officer)/

(Divisional Fire Officer).

Form No. - 16

[See Rule 15(1)(a)]

Check list for issuance of No Objection Certificate for High Rise Buildings

Instructions for filling the Check List

(1)

Read explanatory notes carefully, before filling the form.

(2)

The requirements listed need to be fulfilled to comply with rules and Regulations. If an item is complied with mark 'Yes' and if an item is not complied with, Mark 'No'. If an item is not applicable to the particular building, mark 'Not Applicable' (NA).

(3)

In the pre-construction stage, the marking may be Yes/No/NA. In the post-construction stage full details in all columns should be filled in and relevant Vendor literature should be provided for fire safety systems/ items.

(4)

Portable fire extinguishers and miscellaneous fire safety measures will be checked, before issuing of final NOC for enabling the Municipal Authority issue occupancy certificate and hence the same should be envisaged in the planning stage.

(5)

The Checklist is not all-inclusive. The architect should make sure that all Applicable rules and regulations are fully complied with (A.P. Fire Service Act 1999/NBC, All applicable Building Laws.)

(6)

The items with '*' mark are mandatory.

(7)

The design and plan of the building shall be made and countersigned by a qualified civil or structural Engineer, an Architect (NBC-Part 2) and the Owner/Builder.

(8)

If more than one block is proposed, you should attach separate checklist for each block.

(9)

Submit proposed construction plan - 5 sets (site plan, Basement Floor Plans, Stilt Floor Plans, floor wise plan, terrace plan, Section and Elevation duly marking fire safety systems along with General information proforma and 5 sets of checklist duly filled in, Estimates towards the provision of fire safety systems, 15% of the estimates of Fire Safety system as Bank Guarantee, Undertaking on Rs. 100/- Stamp-paper and copy of the Challan towards the payment of Fire precaution Fee (@ Rs. 10/- per Sq. mtr. of total built-up area including basements and stilts areas).

(10)

Checklist should be neatly typed without any corrections. Checklists with overwriting, corrections and interpolations shall be summarily rejected.

I

*1.1

Name and Address of the Applicant

*1.2

Address of the Premises:

*1.3

Address for Correspondence (provide phone number, Fax and e-mail id if any)

*1.4

Designation and Address of Licensing Authority issuing building permit to whom NOC has to be sent (Tick the appropriate authority)

MCH/HUDA/APPART 2C/ VUDA/VGTUDA/KUDA/ TUDA

*1.5

Name of the Block

*1.6

Height of the Block

Enter the Height of the Building mtrs.

(Note for the buildings above 30 m. height, the builder shall submit Additional emergency plan of action, including provision and maintenance of hydraulic platform with capacity to have an access upto the terrace of the building, round the clock with officer and crew.

*1.7

Type of building occupancy (refer NBC-4, 3.1; 3.4.7, Table 23):

*1.8

Sub Occupancy Type:

*1.9

Area of the site in Sq. Mts. (minimum 1000 Sq. Mtrs.)

*1.10

(i) Total Built-up area of all floors including basements & stilts (in sqm.)

..... Sq. Mtrs.

(ii) Fire precaution fee remittance particulars

Fire Precaution Fee Payment should be made in the form of Challan only @ Rs. 10 per Sq. mtr. for the total built-up area including basement and stilt areas.

E-Seva User charges should be paid in the form of cash. Challan No. ?.....Amount.

?..... and

Date.....Name of the Bank

?.....Name of the Branch

?.....Treasury challan under

the following head of account: SM: 0070 ? Other

Administrative Services. MH: 109 ? Fire Protection and

Control SH: (02) ? Fees of Fires DH: 001 ?

Other Receipts DDO Code ? 25001005001

*1.11

Surrounding of the Premises

North ?.....South

?.....East

?.....West

?.....

***1.12**

Open space front & other 3 sides of the Block:

Open space front & other 3 sides (NBC-Part 3-4.6; 8.2.3.1, 9.4.1(a); Part 4-3.4.6)

Note: Access space vide a) NBC-Part 3-4.6, "additional" to open spaces regd. vide Part 3-8.2/ 3, as per NBC-Part 4-3.4.6.1.,) additional to parking space per Part 4-7.4.1.c. If ht. exceeds 15 mtrs. refer NBC-Part 3-8.2.3.1 for minimum open space, around the building and 9.4.1(a) for front open space.

***1.12.1**

Open space on North side

?.....Meters.

***1.12.2**

Open space on South side

?.....Meters

***1.12.3**

Open space on East side

?.....Meters

***1.12.4**

Open space on West side

?.....Meters

***1.12.5**

Front Side ?.....

Direction (East/West/North/South)

1.13

Projections into open spaces:

1.13.2

Front ?.....Meters

?.....direction

1.13.2

Side 1?.....Meters

?.....direction

1.13.3

Side 2 ?..... Meters

?.....direction

1.13.4

Rear ?..... Meters

?..... direction

Note: Projected Balcony at higher floors should not exceed 1.20 mtrs. as per clause 8.4 of Part 1 NBC and sunshades over windows/ventilators or other openings not to exceed 0.75 mtrs.

***1.14**

Block Details:

***1.14.1**

Number of floors ?.....Number

of Basements ?.....Number

of Stilts/ Ground floor ?.....

***1.14.2.1**

Capacity (aggregate width) of exits shall be based on occupant load (in the affected floor(s) and occupants that can be safely evacuated per 50 cms of exit, which is: 25/50/75 for stairs/ramp/doors, respectively, for residential educational or institutional bldgs. Corresponding figures are 50/60/ 75 for business & mercantile bldgs., for assembly occupancy 40/50/60, stairs/doors/ramps respectively.(NBC-Part 4-4.3/4.4)(Aggregate stairs width)?.....

*1.14.2.2

Whether horizontal exits are provided (Provided/Not provided)

Note: When horizontal exit is provided in buildings of mercantile, storage, industrial, business and assembly occupancies, the capacity per storey per unit width of exit of stair ways in table 21 may be increased by 50 percent and in buildings of institutional occupancy it may be increased by 100 per cent (4.4.3 Part 4 NBC)

*1.14.3

Floor

Area in Sq. Mtrs

Classification of occupancy:

No. of Occupants as declared by the Builder:

No. of Occupants based on Table 22 i.e, floor area divided by occupant load:

Total Aggregate width of Stair Case in Mtrs. (as declared by the Builder):

Basement 1

Basement 2

Stilt 1/

Ground Floor

Stilt 2

Floor 1

Floor 2

Floor 3

Floor 4

Floor 5

Floor 6

Floor 7

Floor 8

Floor 9

Floor 10

1.15

Refuge are:

Refuge area (NBC - 4 - 4.12.3 & Appendix

D-1.11)Sq. Mtrs.

*1.16

Width of the road to which the building abuts and whether it is hard surfaced and motorable:

The premises is abutting..... no of Roads.

For Minimum width of abutting street refer (NBC-Part 3-4-.6.a; 4.8; Part 4-7.4.1.a).

(Note: The Abutting Road width should be minimum 12 mtrs.)

Specify Abutting Street Details :

{|

Abutting Street Name

Abutting Street width in mtrs.

Side

Abutting Street 1Abutting Street 2

|-

|

| *1.17

| Entrances (Minimum width should be 4.5 mtrs. and head room clearance should be minimum 5.0 mtrs.)

| Proposed to provide number of entrance/exit

Specify: Entrance/Exit details

Entrance width in mtrs.

Abutting Road width

Side

Entrance 1Entrance 2Head room clearance

?.....mtrs.

|-

|

| *1.18

| Car parking:

| Car Parking Details:Basement / Stilt / Ground

Floor No. of Cars

Basement

?.....

Stilt

?.....

Ground

?.....

|-

|

| 1.19

| Ramps:

| Proposed to provide ramps (If no basement is there for the building, please enter 'NA.')

Specify Ramp Details

Width of Ramp in mtrs.

Side

Ramp 1Ramp 2

Note:-? As per cl. 12.9.3 of open ramps shall be permitted if they are constructed within the building line.

|-

|

| *1.20

| Staircase:

|

|-

| *1.20.1

| No. of Internal staircase?.....

(Minimum 1)No. of External staircase.....

(Minimum 1)All the staircases shall be designed to abut one of its sides to the external wall.

|-

| Internal Staircase

Details:

|-

|

|

| *1.20.2.1

| Internal Staircases (Minimum width 1.50 meters) for other than Assembly and Institutional Occupancy, for Assembly and Institutional Occupancy Minimum Internal staircase width should be minimum 2.0 meters

No.

Location

From.....Floor

To?.....Floor

Width of Staircase ?....mtrs.

Staircases 1Staircases 2Staircases

3Staircases 4Staircases 5

|-

| *1.20.2.2

| Travel distancemtr. distance from the farthest point and mtr. distance from the dead-end of the corridor to the staircases (1 ½ times permitted travel distance is acceptable if entire building is proposed with sprinkler system)

(Number of staircases to comply with travel distance NBC-4 - 4.5. If there are more than 1 internal staircase, one of the staircases may be extended to the basement and it should terminate at ground floor level and separate staircases shall be provided to reach the basement parking areas from ground floor and the same should be separated at ground level by ventilated lobby with discharge points to 2 different ends through enclosure.)

|-

| *1.20.2.3

| Width of the

Threads..... cm

|-

| *1.20.2.4

| Height of the riser cm

|-

| *1.20.2.5

| Number of riser per flight

|-

| *1.20.2.6

| Height of the hand rails..... mtr (should

be/mtrs)

| -

| *1.20.2.7

| The gap between two verticles cm
(should not exceed 15 cm)

| -

| *1.20.2.8

| Head room clearance..... mtr.

| -

| External Staircase details:

| -

|

|

| *1.20.3.1

| External Staircases:

No.

Location

From.....Floor

To?.....Floor

Width of Staircase ?....mtrs.

Staircases 1Staircases 2Staircases

3Staircases 4Staircases 5

(Note: External staircase shall terminate at
Ground/Stilt floor only, it should not extend to the basement.
Minimum width should be 1.25 Mtrs.)

| -

| *1.20.3.2

| Width of the Treads ?..cm

| -

| *1.20.3.3

| Height of the riser ?.. cm

| -

| *1.20.3.4

| Number of riser ? per flight

| -

| *1.20.3.5

| Height of the hand rails ?.. mtr. (should be
1. mtr.)

| -

| *1.20.3.6

| The gap between two verticals..... cm
(should not exceed 15 cm)

| -

| *1.20.3.7

| Head room clearance mtr.

| -

| *1.21

| Lifts:

|

| -

| 1.21.1

| ?..... Number of Passenger lifts

Passenger Lift DetailsPassenger Lift

1Passenger Lift 2

Capacity (kgs)

|-

| 1.21.2

| ?..... Number of Service lifts

Service Lift Details:Service Lift 1Service

Lift 2

Capacity (kgs)

|-

| 1.22

| Generator

| ?.....Number of Electrical Generators

Generators DetailsGenerator 1Generator 2

Capacity (kva)

Note:? Electrical generator with auto start

and auto changeover from normal to emergency source to supply power to staircase and corridor lighting circuits, fire lifts, the standby fire pump, pressurization fans and blowers, smoke extraction and damper systems in case of failure of normal electric supply.

|-

| *1.23

| Minimum Fixed Fire Fighting installations

| Whether minimum fixed fire fighting installations

as prescribed in table 23 of NBC-Part 4 are provided (NBC-4, Appdx - d is also applicable)

|-

| 1.23.1

| Proposed to provide..... number of Manual Call

Points in the entire building.

|-

| 1.23.2

| Proposed to provide..... number of Smoke

Detectectors, Heat detectors, ?.....number of Beam

Detectors in the entire building.(Please refer IS 2189:1999)

|-

| 1.23.3

| Proposed to provide Detection Control Panel in..... floor.

|-

| 1.23.4

| Proposed to provide..... number of automatic

sprinklers in the entire building.(Please refer IS 15105.

:2002)

|-

| 1.23.5

| Proposed to provide number of Hose Reels in the entire building.

| -

| 1.23.6

| Proposed to provide number of Wet Risers/ Wet
Riser cum Down comers.

| -

| 1.23.7

| Proposed to provide ... number of Yard Hydrants.

| -

| *1.23.8(a)

| Proposed to provide number of Underground Static
Water tank/tanks, totally ltrs. Capacity. Underground
Static Water Tank Details: Ltrs. Underground Static Water Tank
1 Underground.
Static Water Tank 2

| -

| 1.23.8(b)

| Mention Nearest Water Source ?.....
(River/ Lake/Pond/Well/ Municipal Water Works)

| -

| *1.23.9

| Proposed to provide number of Terrace tank/
tanks, totally..... ltrs. Capacity. Terrace Tank Details
Ltrs Terrace Tank 1 Terrace Tank 2

| -

| 1.23.10

| Proposed to provide the following Pumps:

| -

| *1.23.10.1

| {

| -

| Jockey Pump Details
| ltrs/min. capacity.

| -

| Jockey Pump 1 Jockey Pump 2

|

| }

| -

| *1.23.10.2

| {

| -

| Electrical Main Pump Details:
| ltrs/min. capacity.

| -

| Electrical Main Pump 1 Electrical Main Pump 2

|

| }

| -

| 1.23.10.3

| {

| -

| Standby Diesel Pump Details:

| ltrs/min. capacity

|-

| Standby Diesel Pump 1Standby Diesel Pump 2

|

|}

|-

| 1.23.10.4

| {}

|-

| Electric Pump for Sprinkler system Details:

| ltrs/min. capacity

|-

| Electric Pump for Sprinkler system 1Electric
Pump for Sprinkler system 2

|

|}

|-

| 1.23.10.5

| {}

|-

| Booster Pump Details:

| ltrs/min capacity

|-

| Booster Pump 1Booster Pump 2

|

|}

|-

| 1.23.11

| ?..... Number of Fire Lifts.

Fire Lift Details

Capacity

Fire Lift 1Fire Lif 2

(Note: Minimum one Fire Lift with capacity not less
than 545 kgs/8 persons lift for every 1200 sq. mtrs. area as per
NBC 4-Annexure C 1.5)

|-

| *1.24

| Bank Guarantee:

| 15% of the estimates of Fire Safety Systems Rs.

?.....as Bank Guarantee.

|-

| *1.25

| Nearest Fire Station:

| Nearest Fire Station and Telephone
Number.....

|-

| *1.26

| Public Address system:

|

(Provided/Not provided)

|-

| II

| Sl. No.

| Description

|

|

|

| -

|

| *2.1

| Whether Building Owner/Occupier Name and his
address is filled in and signed

| Yes

| No

|

| -

|

| *2.2

| Whether Location and Address of the Building/Site
is filled in

| Yes

| No

|

| -

|

| *2.3

| Whether Buildings plans include the following (for
filling 2.3.1 to 2.3.34, please refer NBC-Part 2-12.2.5.1)Note:
The plans should be to scale.All plans shall be not less than
1.

:100 scale

|

|

|

| -

|

|

| *2.3.1.1

| Whether 5 sets of Checklist duly filled in all
columns and signed are submitted?

| Yes

| No

|

| -

| *2.3.1.2

| Whether 5 sets of site plan duly marking open
places on all sides is submitted

| Yes

| No

|

| -

| *2.3.1.3

| Whether 5 sets of Floor wise plans including
Basements/Stilts duly marking fire safety systems are submitted.

| Yes

| No

|

| -

| *2.3.1.4

| Whether 5 sets of Terrace plans are submitted

| Yes

| No

|

| -

| *2.3.1.5

| Whether 5 sets of Section plans are submitted

| Yes

| No

|

| -

| *2.3.1.6

| Whether 5 sets of Elevation plans are submitted

| Yes

| No

|

| -

| *2.3.2.1

| Width of the abutting street (to be not less than
12. mtrs.) (NBC Part 3-4.6)

| Yes

| No

|

| -

| 2.3.2.2

| Show if it is terminating in dead end (NBC-Part
3.

-4.7; Part 4-3.4.6)

| Yes

| No

|

| -

| *2.3.3

| Area of the plot

| Yes

| No

|

| -

| *2.3.4

| Plan of all floors with stair- cases, corridors

| Yes

| No

|

| -

| *2.3.5

| Lift well, ramps, if (provided)

| Yes

| No

|

| -

| *2.3.6

| Two section dwgs, through stairs (NBC-Part 2.

-12.2.5.1.b/c)

| Yes

| No

|

| -

| *2.3.7

| Occupancy of all parts/floors of bldg. (NBC-Part 2.

-12.2.5b; 13.2.f; Part 4-3.1.12/3.1.14 & 4.3)

| Yes

| No

|

| -

| 2.3.8

| For filling item 2.3.8.1-2.3.8.4, please refer to (NBC-Part 2-12.2.5.1.j/n;-Part 4-3.4.11/12; -C1.6/7; 1.17)

|

|

|

| -

| 2.3.8.1

| Details of: air-conditioning & dampers

| Yes

| No

| NA

| -

| 2.3.8.2

| Details of: mechanical ventilation & smoke exhaust System

| Yes

| No

| NA

| -

| 2.3.8.3

| Details of: vents for smoke to minimize their spread

| Yes

| No

| NA

| -

| 2.3.8.4

| Details of: Vents which should be minimum 2.5% of

floor are of Basement

| Yes

| No

| NA

| -

| 2.3.9

| For filling item 2.3.9.1-2.3.9.2, please refer to

(NBC-Part 2-12.2.5.1.d/e/m; Part 4-3.4/4; C-1.5/16; IS 1646;

1.

E.R.)

|

|

|

| -

| *2.3.9.1

| Location of elec. sub-station, transformer,
generator, fire-lift

| Yes

| No

|

| -

| *2.3.9.2

| Location of smoke-stops in lobby/floors

| Yes

| No

|

| -

| 2.3.10

| For filling item 2.3.10.1-2.3.10.4, please refer to

(NBC- Part 2-12.2.5.p/q/r/s;- Part 4.5.1.2)

|

|

|

| -

| *2.3.10.1

| Underground static water storage tank, terrace tank
and fire pumps

| Yes

| No

|

| -

| *2.3.10.2

| Detection and fire alarm systems

| Yes

| No

|

| -

| *2.3.10.3

| Hose-reels, wet-riser/wet riser cum Down corner

(minimum one wet riser for every 1000 sq.m. covered area)

| Yes

| No

|

| -

| *2.3.10.4

| Automatic Sprinklers (basement area >200 sq.m.
automatic sprinklers should be provided)

| Yes

| No

|

| -

| *2.3.11

| Details of motorable access to & around bldg.
and turning radius at bldg. corners. (NBC-Part 2-12.2.5.1.a;-Part
3.

-4.6/7)

| Yes

| No

|

| -

| *2.3.12

| Vehicular parking spaces (NBC- Part 2-12.2.51.g,
Part 3 ? . 10/ appdx.B)

| Yes

| No

|

| -

| 2.3.13

| For filling item 2.3.13.1-2.3.13.3, please refer to
(NBC-Part 2-12.2.5.1.b/k; Part 3-12.9.3.f; Part 2-8.3 to13)
(Note: NBC-Part 4-4.2.9; 4.2.10.m; C.6.2; for
stairs from upper floors to basement. For corresponding rules for
lifts,see NBC-Part 4-appdx-C1.5.h/j)

|

|

|

| -

| *2.3.13.1

| Size (widths) of exit stair cases

| Yes

| No

|

| -

| *2.3.13.2

| Size (widths) of balcony approach, corridors

| Yes

| No

|

| -

| *2.3.13.3

| Size (widths) of ventilated lobby approach

| Yes

| No

|

| -

| 2.3.14

| Compartmentation (if any), show typical detail of fire-resistant doors/stops (NBC-4 - 4.7, 3.4.8, 3.4.9; C-9)

| Yes

| No

| NA

| -

| 2.3.15

| Site plan duly marking open spaces on all sides from the building line to boundary of the premises

| Yes

| No

| NA

| -

| 2.4

| Type of Construction (NBC-Part 4-3.3)

|

|

|

| -

| *2.4.1

| Construction to be type 1, including for external walls, load bearing elements, roof, stairs, lifts, exit routes corridors. (NBC-Part 4-3.3,3.4.7; IS-1642)

| Yes

| No

|

| -

| *2.4.2

| Specifications for all fire safety items like fire resistant doors used as "fire Cut-offs" or "fire-breaks" or for stairs/lifts, to be furnished (NBC-Part4-3.4.8.1/3/9)

| Yes

| No

|

| -

| *2.4.3

| Finishing material used for interior surfaces and decor not to generate toxic smoke/fumes (NBC-3.4.15; IS 12777 & 1642)

| Yes

| No

|

| -

| 2.5

| Access/Open space

|

|
|
|-
| 2.5.1
| Dead end in abutting street allowed only in
residential bldg. below 30 mtrs. ht., in which case, 81 sq. mtrs.
turning space regd. (NBC-Part 3-4.7;)
| Yes
| No
NA
*2.5.2
Entrance gate minimum width & head room, 4.5 &
5. mtrs. resp. (NBC-Part 4-3.4.6.1;)
| Yes
| No
|
|-
| 2.5.3
| Approach to bldg. and access space on all sides up
to 6 mtrs. width shall (refer to NBC-Part-3-4.4.2,/4.6,/8.4, 1.d,
/Part 4-3.4.6, 3.4.6.1.c/d, 5.1.6)
|
|
|
|-
| *2.5.3.1
| be hard surfaced for 45 ton fire vehicles and be
motorable
| Yes
| No
|
|-
| 2.5.3.2
| if have roof on water tank or bridge, if any in
access route, should withstand a load of 45 ton fire vehicle.
(NBC-Part 4-5.1.6)
| Yes
| No
| NA
|-
| *2.5.3.3
| This space of 6 mtrs., for access, shall be
maintained free of parking, and kept free of any obstructions,
structures or fixtures up to ht. of 4.5 mtrs., above which 1.25
mtrs. unenclosed balconies are allowed
| Yes
| No
|
|-
| 2.6

| Exit Requirements

|

|

|

| -

| 2.6.1

| General Exit Requirements (B-20/21; NBC-Part 4-4, appdx C) (Note-Lift and escalators shall not be considered as exits. (NBC-Part 4-4.2.2))

|

|

|

| -

| *2.6.1.1

| Every public place to have sufficient safe exits - without passing through another occupied unit. (NBC-Part 4-4.2.4/4.2.11

)

| Yes

| No

|

| -

| *2.6.1.2

| All escape Exit routes to have clearly visible & illuminated signs with battery backup emergency alternate power supply, (NBC-Part 4-4.2.7; 4.16.3/4/10, C1.14b)

| Yes

| No

|

| -

| *2.6.1.3

| Fire-check doors for fire resistance of two hour to prevent spread of fire/smoke, in escape routes, particularly at entrance to lifts and stairs which are prone to funnel/flue effect (NBC-Part 4-4.2.9)

| Yes

| No

|

| -

| 2.6.1.4

| Exits to suffice simultaneously for assembly and other occupancy, if any, unless Fire department determines that, condition are such that simultaneous occupancy will not occur (NBC-Part 4-6.4.4.8/9)

| Yes

| No

| NA

| -

| *2.6.2.1

| Number of persons within any floor area or occupant load shall be based on actuals, but not less than that given in

(NBC-Part 4-4.3; Table 21)

| Yes

| No

|

|-

| *2.6.2.2

| Locate exit stairs, so that travel distance does not exceed 22.5 mtrs. for residential, educational, institutional and hazardous occupancies and 30 mtrs. for assembly, business and storage and 45 m for industrial buildings. These should be remote to one another and should provide exit in different directions. For basements travel distance should not exceed 15 meters

(NBC-Part 4-4.5)

| Yes

| No

|

|-

| *2.6.2.3

| Doorways to be min. 100 cms. (200 cm. for assembly areas)

| Yes

| No

|

|-

| *2.6.2.4

| Open into corridors or through landings into enclosed staircases for continuous protected egress (NBC-Part 4.

-4.7)

| Yes

| No

|

|-

| *2.6.2.5

| Staircases shall be of enclosed type (NBC-Part 4.

-4.6)

| Yes

| No

|

|-

| *2.6.2.6

| No. of sizes of exit staircases to depend on 6b(1 to 3) above and 7A5 (NBC-Part 4-4.3/ 4/5&6)

| Yes

| No

|

|-

| *2.6.2.7

| Exit doors to be open able from served side, without keys (NBC-Part 4-4.7.5)

| Yes

| No

|

| -

| 2.6.3

| Corridors and Passageways

|

|

|

| -

| *2.6.3.1

| The width of the above shall not be less than the aggregate required width of exit doors leading in direction of egress (NBC-Part 4-4.8.1)

| Yes

| No

|

| -

| *2.6.3.2

| The above (& stairs/lifts) shall have fire/smoke resistant doors

| Yes

| No

|

| -

| *2.6.3.3

| Have adequate ventilation (NBC-Part 4-4.8.3)

| Yes

| No

|

| -

| *2.6.3.4

| Illumination required to ensure safe travel

| Yes

| No

|

| -

| 2.7

| 2.7a

| Internal Staircase

|

|

|

| -

| 2.7a.1

| For (2.7.a.1.1-2.7.a.1.4) (Refer NBC-Part

4.

-4.9.6/7/8)

|

|

|

| -

| *2.7a.1.1

| Minimum width 1.5 mtrs. for other than Assembly
buildings (For Assembly and Hospital buildings minimum width is
2.0

meters) (Net width of stairs, available between hand rails
important)

| Yes

| No

|

| -

| *2.7a.1.2

| Tread 25/30 cms. for residential/other than
assembly

| Yes

| No

|

| -

| *2.7a.1.3

| Riser max 15 cms ht.

| Yes

| No

|

| -

| *2.7a.1.4

| No. of risers not more than 15 Nos. per flight

| Yes

| No

|

| -

| *2.7a.1.5

| Construction should be with non-combustibles
material (NBC-Part 4-4.9.1)

| Yes

| No

|

| -

| *2.7a.2

| To be a self contained unit with at least one
external wall and be completely enclosed. (NBC-Part 4-4.9.2)

| Yes

| No

|

| -

| *2.7a.3

| Shall not be around lift (NBC-Part 4-4.9.3)

| Yes

| No

|

| -

| 2.7a.4

| Hand rails to be at 100 cms. height (NBC-Part

4.

-4.9.9)

| Yes

| No

|

|-

| *2.7a.5

| To be designed such that the No. of people in
between floor landings, is not less than those on each floor.

(NBC-Part 4-4.9.10)

| Yes

| No

|

|-

| *2.7a.6

| To contain no electrical shafts/ AC ducts or gas
pipes (NBC-Part 4-4.9.4/10f)

| Yes

| No

|

|-

| *2.7a.7

| Access to stairs shall be through two hr. rated
fire/ smoke door (NBC-Part 4-4.9.10.b)

| Yes

| No

|

|-

| 2.7b

| External Stairs

|

|

|

|-

| *2.7b.1

| Shall be directly connected to ground (NBC-Part

4.

-4.11.2)

| Yes

| No

|

|-

| *2.7b.2

| Minimum width 1.25 meters

| Yes

| No

|

|-

| *2.7b.3

| Entrance to be separate and remote from internal

stairs. (NBC-Part 4-4.11.3)

| Yes

| No

|

|-

| *2.7b.4

| To have no wall/window opening, close to it

(NBC-Part 4-4.11.4)

| Yes

| No

|

|-

| *2.7b.5

| Openable vents/ducts to outer air be provided at landings to facilitate venting of smoke, if any, and for rescue/fire fighting (NBC-Part 4 C.1.4)

| Yes

| No

|

|-

| *2.7b.6

| Route to be Always free of any obstructions/doors shall be openable from the served side without use of a key

(NBC=Part 4-4.11.6)

| Yes

| No

|

|-

| *2.7b.7

| Shall be of non-combustible materials and doors leading to it shall have the regd. fire resistance (NBC-Part

4.

-4.11.6)

| Yes

| No

|

|-

| *2.7b.8

| Fire escapes not to be taken into account in calculating evacuation time (NBC-Part 4 4.11.10)

| Yes

| No

|

|-

| *2.7b.9

| Width/tread, to be not less than 1.25 meters/25.0 meters respect riser not more than 19 cm. and flights/angle not more 15/45 degrees, resp. (NBC-Part 4-4.11.7/8). However, the corresponding dimensions for internal stairs i.e. width/tread/riser at 150/25/15 cm. resp. are much preferred to ensure safer evacuation.)

| Yes

| No

|

| -

| 2.8

| Miscellaneous Exit Items

|

|

|

| -

| 2.8.1

| Fire Tower

|

|

|

| -

| 2.8.1.1

| Fire Tower is the preferred escape route, being an enclosed staircase, approached from floors, through landings separated from floors and stairs by fire-resistant doors and open to outer air (NBC-Part 4-3 & 4.13)

| Yes

| No

| NA

| -

| 2.8.1.2

| For business, mercantile, institutional, theatres, if >8 stories or >24 mtr., in height, at least one fire tower is regd.

| Yes

| No

| NA

| -

| 2.8.2

| Horizontal Exits

| Yes

| No

| NA

| -

| 2.8.1.2

| To have with the same width at least one fire door of self-closing type (NBC-Part 4-4.12.1/2)

| Yes

| No

| NA

| -

| 2.8.2.2

| Doors to be openable at all times from served side(s) (NBC-Part 4 4.12.5)

| Yes

| No

| NA

| -

| 2.8.2.3

| Refuge area of 15 m² or an area equivalent to 0.3 m² per person to accommodate the occupants of two consecutive floors, whichever is higher, shall be provided as under.

(a)

For floors above 24 m. and upto 39 m ?
one refuge area immediately above 24 m.

(b)

For Floors above 39 m ?one refuge area on
the floor immediately above 39 m and soon after every 15 m

| Yes

| No

| NA

| -

| 2.8.3

| Ramps

|

|

|

| -

| 2.8.3.1

| To be not steeper than 1 in 10 and Never steeper
than 1 in 8. Surface to be skid proof NBC-Part 4-4.14)

| Yes

| No

| NA

| -

| *2.8.3.2

| To never abut the street without level space, so as
to provide safe sighting, before driving into the street.
(NBC-Part 3-10)

| Yes

| No

|

| -

| 2.8.3.3

| In plots over 2000 sq. mtrs. Ramps shall be within
bldg., line, for safety reasons

| Yes

| No

|

| -

| 2.9

| Electrical Safety

|

|

|

| -

| *2.9.1

| To comply with Indian Electrical Rules, including related Indian standards/Codes stipulated therein; NBC Part 8-2; N.E.C.-Part 3-3; and IS-4878-14; IS-1646 & 732.

| Yes

| No

|

| -

| *2.9.2

| Elec. installations shall be by licensed electrical contractor & supervised by holder of competency-certificate/permit issued by Government. Appropriate certificates reqd. (IS-732-3.5)

| Yes

| No

|

| -

| *2.9.3

| Completion drawings showing all circuits to enable functional checks to verify compliance with applicable rules (NBC-Part 8-3-9.1.5/9.2; IS 732.3.1/.4.1/.5/.9)

| Yes

| No

|

| -

| *2.9.4

| Specific Requirements

|

|

|

| -

| *2.9.4a.1

| Emergency and escape lighting powered by source independent of normal power, for stairs/ exit routes & fire alarm

| Yes

| No

|

| -

| *2.9.4a.2

| With one and half hrs. battery backup (NBC-Part 4.

-4.16; appendix-D1 .14)

| Yes

| No

| NA

| -

| *2.9.4b

| Alternate/Emergency generator fed, separate, direct power circuits for item 2 (refer NBC-Part 4-C.1.5.p; 1.6.4.3;

1.

12.

, 14, 15)

|

|

| NA

| -

| *2.9.4b.1

| Fire pumps, lifts

| Yes

| No

|

| -

| *2.9.4b.2

| Smoke Exhausters

| Yes

| No

|

| -

| *2.9.4b.3

| Emergency Lighting

| Yes

| No

|

| -

| *2.9.4b.4

| Fire Alarm/P.A. Systems (Note: Auto start and auto switch over from normal to emergency source should be ensured)

| Yes

| No

|

| -

| 2.9.4c

| Transformers, if in basement to have enclosure of 4 hr. rating (NBC-Part 4-C.1.16.C)

| Yes

| No

| NA

| -

| 2.9.4d

| Transformers room/enclosure, location and ventilation/exhaust to be such that no smoke or fumes therefrom can ingress into exit/escape routes or parking or other parts of the bldg. (NBC-Part 4-6.4.6.5)

| Yes

| No

| NA

| -

| *2.9.4e

| Transformer plinth should be at least 15 cm. above grade and if oil filled should have curbs to prevent egress of leaking oil into any parking area (NBC-Part 8-2-4.2.2.c/g.)

| Yes

| No

|

| -

| 2.9.4f

| Periodical verification of efficacy of emergency/alternate power supplies and related escape and fire safety equipment (IS-1646-3.6&11.6)

| Yes

| No

| NA

| -

| *2.9.4g

| Compliance with I.S. 1646; 732; 10028, regarding fire safety of bldg., electrical wiring & transformers resp.

|

|

|

| -

| 2.9.4h

| Indoor transformers to have auto High velocity water spray or Emulsifying system (IS-15.10.3)

| Yes

| No

| NA

| -

| 2.9.4i

| Transformer shall have soak pit, fencing and provided with 45 ltr. foam trolley

| Yes

| No

| NA

| -

| 2.9.5

| Power circuits

| Yes

| No

| NA

| -

| *2.9.5.1

| The lighting in, passageways, stairways, exits, and parts of bldg. open to public, should be divided into two halves, each half being fed by separate circuit controlled by switches, located remote from each other.(IS-1646)

| Yes

| No

|

| -

| *2.9.5.2

| Electrical fires being common cause of fires, strict compliance I.E.R. 30 (ISI, complaint electrical material) and IS-732 & NBC-Part 8-2, (for electrical wiring), is

essential

| Yes

| No

|

| -

| *2.9.6

| Lightning protection per IS-2309. (NBC-Part 3-19)

| Yes

| No

|

| -

| 2.10

| Fire Protection (The following aspects should be taken care of)

|

|

|

| -

| 2.10a

| Building Design

|

|

|

| -

| 2.10a.1

| Type of construction to comply with item 4, above, to prevent rapid spread of fire, smoke or fumes which may otherwise contribute to loss of lives and property. Fire resistance ratings to comply with NBC-Part 4 c1-3.3 Table 1. (Any deviations to be specifically, noted)

| Yes

| No

|

| -

| 2.10a.2

| If a bldg. has more than one occupancy it shall comply with requirements of the most hazardous one, unless 4 hr. rated separating wall is provided (NBC-Part 4-3.4.7)

| Yes

| No

|

| -

| *2.10a.3

| Fire resistant doors, 1 hr. rated, in escape routes, particularly at entrance to lifts, staircases, per 7.a-7, above (NBC-Part 4-4.2.4 & IS 361)

| Yes

| No

|

| -

| *2.10a.4

| Doorway or opening in separating walls/floors to limit spread of fire, smoke by use of 2 hr. rated fire resistance doors/ steel rolling shutters (NBC-Part 4-3.4.8 & 3.4.8.1; IS-12458)

| Yes

| No

|

| -

| *2.10a.5

| Openings in walls/floors for cables, plumbing etc. to be in ducts/shafts enclosure of 2 hr. fire-resistance, with 1 hr. rated inspection doors (NBC-Part 4-3.4.8.2/3 & C.1.9)

| Yes

| No

|

| -

| *2.10a.6

| Seal space between cables etc. and shaft, with fillers, to stop fire at every floor level. (NBC-Part 4-3.4.8.3)

| Yes

| No

|

| -

| *2.10a.7

| Surface finishes on walls/ ceilings/facade shall minimize the spread of fire or toxic fumes (NBC-Part 4-3.4.15.1; C.11)

| Yes

| No

|

| -

| *2.10a.8

| Use "Class 1 flame-spread", surfacing material, and fabric materials used for decor, carpets curtains etc. per IS 2777 (NBC-Part 4-3.4.15.2, 6.4.6.1, C1.2 & 11.1)

| Yes

| No

|

| -

| *2.10a.9

| Walls, partitions or floors lined with combustible material, to have surfaces conforming to IS 1642, to prevent rapid fire spread, hampering escape of occupants (NBC-Part 4.

-3.4.15.5)

| Yes

| No

|

| -

| *2.10a.10

| Openable windows, on external walls or on fully

glazed facades, to have locks which can be opened by fire-man's
axe to enable quick access for rescue of inmates, and for
fire-fighting (NBC Part 4-3.4.16,C.1.7)

(Note Accessibility of fire men into higher floors
is important)

| Yes

| No

|

| -

| 2.10b

| Air Conditioning/Ventilation

|

|

|

| -

| 2.10b.1

| To be designed to minimize spreading of fire smoke
& fumes from one fire area/floor to another or to escape/exit
path, staircases, etc. (NBC Part 4-3.4.11 & C1.17; v Part

3.

-sec.-1/3)

| Yes

| No

| NA

| -

| *2.10b.2

| In case of fire, or smoke at A.C's outlet,
Automatic dampers to close, to stop spreading of smoke

| Yes

| No

|

| -

| *2.10b.3

| In case of fire, stop fans, unless these are
arranged to remove smoke from fire area. (NBC-Part 4-3.4.11,2)

| Yes

| No

|

| -

| *2.10b.4

| From safety point of view, separate air handling
systems for various floors are preferred, to minimize hazard of
smoke spreading. Refer (NBC-Part 4-3.4.11.4)

| Yes

| No

|

| -

| 2.10c

| Smoke venting

Note: It is well established that far

greater lives are lost due to smoke (more so, if exits are

deficient), than due to fire-burns refer (NBC-Part 4-3.4.1/12,

4.2.9

, C1.6)

|

|

|

|-

| *2.10c.1

| Automatic smoke vents, with area min. 3.3% of floor area, in assembly areas and balconies, shall be installed. Refer (NBC-Part 4-3.4.6.4.2/6, 4.4, 6.4.6.11)

| Yes

| No

|

|-

| *2.10c.2

| The above, is natural draft smoke venting, opened by smoke sensitive device, automatically. To substitute this with powered exhausters, Department 's permission is regd. Refer (NBC-Part 4.

-3.4,6.4.4/6.4.5)

| Yes

| No

|

|-

| 2.10d

| Basements (Please refer 12.9.3 of Part 3 NBC and C1.6 of Part 4 NBC)

|

|

|

|-

| 2.10d.1

| Basements to be separately ventilated with grills etc. having 2.5% area of floor. Alternatively, air inlet & smoke outlet ducts at floor & ceiling level resp. be provided refer (NBC-Part 4-C.1.6.1)

| Yes

| No

| NA

|-

| 2.10d.2

| Mechanical extractors with 30 change/hr. in case of fire fed by alternate power also reqd. for lower basement, if any. Refer (NBC-Part 4-C.1.6.4)

| Yes

| No

| NA

|-

| 2.10d.3

| Smoke from basement fire shall in no case ingress

into any exit path/stairs serving upper floors. Refer (NBC-Part

4.

-C1.6.6)

| Yes

| No

| NA

| -

| 2.10d.4

| Use of LPG/Pressure stove in basements is prohibited, while allowed in other areas 4 hr, fire-resistant enclosures. Refer (NBC-Part 3-12.9;Part 4-C1.6.5)

| Yes

| No

| NA

| -

| 2.10.d.5

| Every basement shall be in every part at least 2.4 m in height from the floor to the underside of the roof slab or ceiling

| Yes

| No

| NA

| -

| 2.10d.6

| Adequate ventilation shall be provided for the basement. The ventilation requirements shall be the same as required by the particular occupancy according to bye laws. Any deficiency may be met by providing adequate mechanical ventilation in the form of blowers, exhaust fans, air-conditioning systems etc.

| Yes

| No

| NA

| -

| 2.10d.7

| The minimum height of the ceiling of any basement shall be 0.9 m and the maximum 1.2 m above the average surrounding ground level

| Yes

| No

| NA

| -

| 2.10d.8

| Adequate arrangements shall be made such that surface drainage does not enter the basement

| Yes

| No

| NA

| -

| 2.10d.9

| The walls and floors of the basement shall be

watertight and be so designed that the effects of the surrounding soil and moisture if any, are taken into account in design and adequate damp proofing treatment is given

| Yes

| No

| NA

| -

| 2.10d.10

| The access to the basement shall be separate from the main and alternative staircase providing access and exit from higher floors. Where the stair case is continuous in the case of buildings served by more than one staircase, the same shall be of enclosed type serving as a fire separation from the basement floor and higher floors. Open ramps shall be permitted if they are constructed within the building line subject to the provision of 2.10.d.8.

Note: The exit requirements in basements shall comply with the provisions of Part 4 Fire and Life Safety.

| Yes

| No

| NA

| -

| 2.10d.11

| Each Basement shall be separately ventilated. Vents with cross sectional area (Aggregate) not less than 2.5% of the floor area spread evenly round the perimeter of the basement shall be provided in the form of grills, or breakable stall board lights or pavement lights or by way of shafts. Alternatively, a system of air inlets shall be provided at basement floor level and smoke outlets at basement ceiling level. Inlets and extracts may be terminated at ground level with stall board or pavement lights as before, but ducts to convey fresh air to the basement floor level have to be laid. Stall board and pavement lights should be in positions easily accessible to the fire brigade and clearly marked. 'Smoke outlet' or air inlet with an indication of area served at or near the opening.

| Yes

| No

| NA

| -

| 2.10.d.12

| The staircase of basements, shall be of enclosed type having fire resistance of not less than 2 h and shall be situated at the periphery of the basement to be entered at ground level only from the open air and in such positions that smoke from any fire in the basement shall not obstruct any exit serving the ground and upper stores of the building and shall communicate with basement through a lobby provided with fire resisting self closing doors of 1 h resistance. For travel distance see 4.5 Part 4. NBC. If the travel distance exceeds as given in table 21, Part 4.

, Additional stair-cases shall be provided at proper places.

| Yes

| No

| NA

| -

| 2.10.d.13

| In Multi-storey basements, intake ducts may serve all basement levels, but each basement level and basement compartment shall have separate smoke outlet duct or ducts. Ducts so provided shall have the same fire resistance rating as the compartment it-self. Fire rating may be taken as the required smoke extraction time from smoke extraction ducts.

| Yes

| No

| NA

| -

| 2.10.d.14

| Mechanical extractors for smoke venting system from lower basement levels shall also be provided. The system shall be of such design as to operate on actuation of heat/smoke sensitive detectors or sprinklers, if installed, and shall have a considerably superior performance compared to the standard units. It shall also have an arrangement to start it manually.

| Yes

| No

| NA

| -

| 2.10.d.15

| Mechanical extractors shall have an internal locking arrangement, so that extractors shall continue to operate and supply fans shall stop automatically with the actuation of fire detectors.

| Yes

| No

| NA

| -

| 2.10.d.16

| Mechanical extractors shall have an alternative source of supply

| Yes

| No

| NA

| -

| 2.10.d.17

| Ventilating ducts shall be irate- grated with the structure and made out of brick masonry or reinforced cement concrete as far as possible and when this duct crosses the transformer area or electrical switch board, fire dampers shall be provided.

| Yes

| No

| NA

| -

| 2.10.d.18

| If cutouts are provided from basements to the upper floors or to the atmosphere, all sides cutout openings in the basements shall be protected by sprinkler head at close spacing so as to form a water curtain in the event of fire.

| Yes

| No

| NA

| -

| *2.10e

| First aid fire extinguishers should be provided as per IS-2190: 1992 & NBC-Part 4-5.1

Note: The following minimum number of fire extinguishers should be provided.

| Yes

| No

|

| -

| (1) One ABC powder extinguishers of 5 kgs. capacity and 2 no. of fire buckets filled with clean, dry, fine sand should be provided for every 8 cars.

| Yes

| No

|

| -

| Part (2) One extinguishers of 2 kgs. capacity should be provided near the entrance to each main switch board room

| Yes

| No

|

| -

| Part (3) 2 ABC powder extinguishers of 5 kgs. capacity should be provided near transformer, if installed

| Yes

| No

|

| -

| Part (4) 2 ABC powder extinguishers of 5 kgs. capacity should be provided inside each lift room

| Yes

| No

|

| -

| (v) 1 water pipe gas cartridge extinguisher of 9 ltrs capacity should be kept near each staircase landing on every floor

| Yes

| No

|
|-
| (vi) Scale of suitable extinguishers for other
areas shall be collected before approaching the department for
final clearance, after finalizing utility of each area
| Yes
| No
|
|-
| (vii) All the extinguishers suggested above should
be with BIS Mark and should be located at an easily accessible
position without obstructing the normal passage
| Yes
| No
|
|-
| *2.10f
| Fire service inlet (4 way) refer (NBC-Part
4.
-5.1.6.b)
| Yes
| No
|
|-
| *2.10g
| Fire lift {546 Kg capacity) @ 1 for every 1200
sq.m. floor area. Refer (NBC-Part 4-appdx-C.1.5)
| Yes
| No
|
|-
| 2.11
| Special Hazards
|
|
|
|-
| *2.11.1
| Rooms with refrigeration equipment/transformer not
to be adjacent to each other and should be vented separately to
outer air. (NBC-Part 4-6.4.6.5)
| Yes
| No
|
|-
| *2.11.2
| All rooms/areas storing combustible
material/equipment/etc. be effectively cut off from exits/
assembly areas. (NBC-Part 4.6.4.6.6)
| Yes
| No

|
|-
| *2.11.3
| Whether minimum fixed fire fighting installations
as prescribed in table 23 of NBC-Part 4 are provided (NBC-Part 4
appdx-d is also applicable)

|
|
|
|-
| (1) Proposed to provide emergency lighting with
minimum

| Yes
| No

|
|-
| 2 hrs battery backup in the escape route.

|
|
|
|-
| (2) Proposed to provide Auto glow signages in all
floors.

| Yes
| No

|
|-
| (3) Proposed to provide Public Address System

| Yes
| No

|
|-
| 2.12
| Miscellaneous

|
|
|
|-
| *2.12.1

| For building 15 m and above, NBC-Part 4, appdx-C is
applicable

|
|
|
|-
| *2.12.2

| One Fire lift with capacity of not less than 545
kg. (8 per-sons lift) for every 1200 sq. mtrs. of floor area
shall be provided (NBC-Part 4-C.1.5)

| Yes
| No

|
|-
| *2.12.3
| All floors to be compartmented into 750 sq. mtrs.
area through 2 hr rated fire separation walls (NBC-1V-C.1.8)
| Yes
| No
|
|-
| *2.12.4
| Basement ventilation and stair- cases shall be such
that smoke cannot travel to upper floors
| Yes
| No
|
|-
| *2.12.5
| For Buildings above 60 mtrs. height, whether
helipad arrangement is made (el C.10 of annexure C Part 4 NBC,
2005.
)
| Yes
| No
|
|-
| *2.12.6
| Whether compartmentation is proposed to be done to
confine the fire/smoke to the area where fire incident has
occurred (Cl C.9 Annexure C, Part 4, NBC, 2005)
| Yes
| No
|
|-
| *2.12.7
| Whether smoke mangement is strictly ensured, so
that exit route is free from smoke logging in case of fire (Cl
3.4.8
, 3.4.9, 3.4.12, 4.2.9, 4.10 Part 4 NBC, 2005)
| Yes
| No
|
|-
| 2.13
Fire pumps (Refer Table 23 of Part 4 of NBC, 2005)
*2.13.1
Whether estimates for Fire Safety System (certified
by the architect) submitted?
Yes
No

| -

| *2.13.2

| Whether 15% of the estimates of Fire Safety System
as Bank Guarantee is submitted?

| Yes

| No

|

| -

| *2.13.3

| Whether challan copy submitted?

| Yes

| No

|

| -

| *2.13.4

| Whether Undertaking on Rs. 100/-Stamp paper
submitted?

| Yes

| No

|

| -

| *2.14

| Provide name, address, licence No., signature of
technical staff

|

|

|

| -

|

| Name

| Phone Number (Land line/ Mobile) Licence No.

Signature

|

|

|

| -

| Builder

|

|

| Yes

| No

|

| -

| Architect

|

|

| Yes

| No

|

| -

| Structural Engineer

|
|
| Yes
| No
|
|-
| Electrical Contractor
|
|
| Yes
| No
|
|-
| Fire Safety Systems Contractor
|
|
| Yes
| No
|
|-
| III
Explanatory Notes
3a.1
"NBC"?National Building Code of
India (as amended in 2005 and) "PART 3"/" PART 4",
"VPART 2" etc. refer to parts of NBC.
-
3a.2
I.E.R. refers to Indian electrical rules
-
3a.3
S.P. 30-1984 is the National Electrical Code
-
3a.4
I.S. refers to Indian Standard
-
3b
NBC-Part 4-appdx-D, is mandatory for bldgs. 15 mts.
and above. However, may be referred to for other buildings Also,
depending on the degree of compliance with applicable rules or
local conditions, as determined by the fire department
-
3c
Each of the rules is sufficient provided all others
are followed. Hence, inadequate compliance with one rule may

warrant enhanced stress on others, as consented to by fire department

|-

| 3d

| Brief descriptions are given for each item. The referred rules give details

|-

| 3e

| Considering the safety scenario in most high-rise bldgs., the unreliability of power supply, and the high incidence of elec. shorts circuits, etc., resulting in fires, the manual and automatic fire-alarm are preferred for all high-rise bldgs. For the same reasons and because delays in fire reporting/quenching is often causing avoidable loss of lives and property. Hence automatic sprinklers, which have proven cost effective, are preferred for such bldgs.

|-

| 3f

| In the pre construction design provisions and commitments can be evaluated but all columns can not be filled in detail. In this case brief description with applicable I.S. can be given. However, in the post construction stage, specific details of installations, corrections in approved drawings to reflect "as-built" situations, and certificates etc., duly signed by technical persons, should be submitted and all columns filled up, to facilitate inspection, functional checks and issuance of final NOC required for occupancy certificate from Municipal authorities.

|-

| 3g

| NOC is valid for the particulars provided in the application. For any change of class of occupancy, fresh NOC for occupancy will be required. (NBC-Part 4-3.1.12 & 3.1.14 & NBC-Part 2 c1-13.2.f & B-4.2.Part 3-b)

|-

| 3h

| Most of the facilities, in fire incidents are due to

(a)

Unrestrained and avoidable spreading of Smoke/fumes due to insufficient smoke Sealing/exhaust arrangements

(b)

Smoke in escape route and in stairs make them Difficult to use

(c)

Inadequate aggregate width of stairs with insufficient ventilations If smoke exclusion from exit stair case is not ensured, then larger aggregate width of stairs would be required to ensure evacuation of inmates of affected floors within two and half minutes stipulated in NBC Part 4-cl-8.4

|-

| 3j

| In each specific case, the fire department may stipulate additional measures, as being necessary for ensuring fire safety of building inmates and public (Section 12 of A.P. Fire Service Act, 1999

|-

| 3k

| The architect and the owner of the building shall sign the checklist and plans

|-

| 3l

| This checklist does not cover cinema occupancy (sub-occupancy type 01 & 02).

|}

Form - 17

[See Rule 15(1)(d)]

Undertaking on Rs. 100/- stamp paper format

(To be typed on Rs. 100/- Stamp Paper)

Undertaking

This letter of undertaking is executed by
..... in favour of the Director
General, Fire and Emergency Services, BRKR Government , Offices/Complex, Tank Bund Road, Hyderabad-500063

1. We say that we are promoters and Developers Builders of the Multi-storeyed building at.....

2. We say that as stipulated by you we will provide all fire safety systems as per National Building Code and Multi-Storeyed Building Regulations, 1981 in the above Multi-Storeyed Building and prepared the estimate of Rs. towards the provision of all Fire Fighting Systems and submit the estimate in original along with the general information and checklist/on fire safety measures for approval.

3. We undertake to incur an expenditure of Rs. for providing Fire Safety arrangements as per details furnished in the above estimate.

4. We undertake to furnish Bank Guarantee for 15% of the total estimated cost of fire safety systems as above in favour of Director General of Fire Services, obtained from any Nationalised Bank for a period of 5 years guaranteeing to provide all fire fighting systems as per National Building Code and maintain them in good working condition round the clock.

5. We agree that the above Bank Guarantee can be invoked by Director General of Fire Services at any time in the event of non-provision or non-maintenance of fire fighting systems in our Multi-storeyed Building as per National Building Code or in the event of non-compliance of any other fire safety measures suggested in the provisional No-Objection Certificate.

6. We also agree that the provisional No-Objection Certificate shall be issued by the Director General of fire services for the construction of Multi-storeyed Building only after furnishing the above bank guarantee by us.

7. We say that as stipulated by you we will undertake to impart training to 40% of the occupants and employees working at Building in fire prevention and fire fighting at Andhra Pradesh Fire Service State Training School, Vattinagulapally, Hyderabad within 6 months from the date of occupation.

8. We undertake to maintain and keep the fire fighting equipment installed at Building.....in good working condition at all times by regularly servicing and replacing the obsolete equipment.

Place:

Date:

Signature of the Builder/Promoter/Developer

Name:.....

Designation:.....

Address for Correspondence.....

Contact Telephone number.....

Form No. 18

[See Rule 15(1)091

Government of Andhra Pradesh Fire and Emergency Services Department

From

.....

.....

.....

.....

To

.....

.....

.....

Rc. No.,

Dated.....

Sir,

Sub: - Fire and Emergency Services Department - Construction of Multi-Storeyed Building by issue of No Objection Certificate - Reg.

Ref: - (1) Application of M/s. with e-Seva Unique I.D. No.

(2)

Report of the Multi-Storeyed Building Inspection Committee, Hyderabad Rc. No.

(3)

Judgment dated 28.9.2006 of the Hon'ble High Court of A.P. in W.P. M.P. No. 21991 of 2006 in W.P. No. 26365 of 2005.

Vide reference cited (3) (copy enclosed), the Hon'ble High Court has directed that:

"Since the Department has carried out necessary inspection and has found nothing objectionable, we give liberty to the concerned authority to issue no objection certificate to the applicant subject to the condition that if the applicant makes any deviation from the sanctioned plan, then the competent authority shall be entitled to demolish the entire building irrespective of the stage of construction.

The department has in last more than six months rigorously ensured total adherence to the norms prescribed and the relevant statutory provisions made for taking fire safety measures, we deem it proper to modify order dated 21.3.2006 and direct that the competent authority shall be free to consider and decide the applications made in further for grant of No Objection Certificate under the A.P. Fire Service Act, 1999 after clearance by the Multi-storeyed Building Inspection Committee."

(2)

The Multi-Storeyed Building Inspection Committee, A.P. Fire Services Department vide reference cited (2) has recommended for the issuance of No Objection Certificate to the proposed Multi-Storeyed Building withwith a height of for Occupancy being constructed by M/s.

(3)

In pursuance of the orders of the Hon'ble High Court cited above, the No Objection Certificate is issued to the proposed Multi-Storeyed Building Block withwith a height of metres for Occupancy being constructed by M/s. as per Section 13(1) of A.P. Fire Service Act, 1999 and the building plans are forwarded herewith after countersigning the same for your approval.

(4)

The Builder may be informed of the following Act/Rules/Regulations:

1. A.P. Fire Service Act, 1999:

As per Section 31 of "whoever wilfully contravenes any provisions of this Act or the rules made thereunder or fails to comply with any requisition lawfully made upon him under any provisions of this Act shall, without prejudice to any other action taken against him under Section 22 be punishable with imprisonment for a term which may extend to three months or with fine which may extend to twenty five thousand rupees or with both; and where the offence is a continuing one, with a further fine which may extend to three thousand rupees for every day during which such offence continues

after the conviction for the first such offence.

II. Municipal Corporation Building Bye-Laws, 1981:

As per Bye-Law 12 "On completion of the building work, the licensed technical personnel shall give notice to the Authority in prescribed form in pursuance of sub-section (1) of Section 455 of the Act." The Builder, on completion of the Building and before occupation, should intimate the Director General of Fire Services for inspection and issue of "No Objection Certificate".

As per Bye-law 13.1 "No building erected, re-erected or altered materially shall be occupied in whole or in part until the issue of an Occupancy Certificate by the authority affirming that such building is fit for occupation".

III. National Building Code of India:

As per Clause 13.1 of Part-II of the National Building Code of India "neither granting of the permit nor the approval of the drawings and specifications, nor inspections made by the Authority during erection of the building shall in any way relieve the owner of such building from full responsibility for carrying out the work in accordance with the requirements of the National Building Code of India."

The building should not be occupied without "No Objection Certificate" from the Fire Services Department.

IV. As per Clause 9.3 of Part II of the National Building Code of India "the Licensed Architect/Engineer/Structural Engineer/Supervisor/Town Planner shall be responsible for supervision of the construction and for the completion certificate. In the event of violation of the provisions of the Code he shall be liable to penalties as prescribed by the Authority including cancellation of the Licence".

V. Multi-Storeyed Building Regulations, 1981:

(a)

As per Regulation 06 "in so far as the determination of sufficiency of all aspects of structural design, building services, plumbing, fire protection, practices and safety are concerned, the specifications, standard and Code of Practice recommended in the National Building Code of India shall be fully conformed to, and any breach thereof shall be deemed to be a breach of the requirement under the Multi-Storeyed Building Regulations."

(b)

As per Rule 5(2) of M.S.B. Regulations, 1981, the construction of building should be periodically inspected jointly with the representative of Chief Engineer, HUDA and Divisional Fire Officer,to ensure that the construction of Multi-storeyed Building is undertaken as per approved plans and Fire Precautionary and Fire Protection measures, as suggested earlier are implemented.

(5)

The builder has proposed the following open spaces for the Multi Storey Building.....

Side

Open space required as per NBC

Proposed to provide by the Builder

North

..... meters

.....meters

East

..... meters

.....meters

South

..... meters

.....meters

West

..... meters

.....meters

6. Means of Escape: - The proposed Multi Storeyed Building has the Allowing Means of Escape (Internal, External staircases)

Sl. No.

Detail of Escape

Means of Minimum width required as per NBC

Width of Staircases Provided

1.

Internal Staircases ... Nos.

..... mtrs

..... mtrs

2.

External Staircases ... Nos.

..... mtrs

..... mtrs

(7)

The approved plans are forwarded subject to provision of the following fire safety measures and other conditions:

i. Hose Reel

ii. Wet Riser-cum-down corner system (... Nos.)

iii. Yard Hydrant system

iv. Manually operated electrical fire alarm system

v. Automatic Detection and Alarm System in the entire building

vi. Sprinkler System in the

vii. The Underground static water tank of litres

viii. Overhead tank of litres capacity

ix. A pump house LPM Electrical and Diesel, LPM jockey and LPM Booster pump

x. Hard, levelled, open to sky open space as per the plans on all sides of the building should be provided without fail.

xi. All fire safety systems shall be provided as per the provisions of National Building Code of India.

(8)

The following are the specific details of mandatory Fire Safety measures to be provided in the Multi Storeyed Building required as per National Building Code of India, 2005.

(i)

The building shall be suitably compartmentalized so that fire/smoke remain confined to the area where fire incident has occurred and does not spread to the remaining part of the building as per Clause C-9 of National Building Code of India, 2005 Part-IV Annexure-C.

(ii)

Openings in separating walls and floors-Attention shall be paid to all such factors as they will limit fire spreading to these openings and maintain fire rating of the structural member. Every wall opening shall be protected with Fire resisting doors having fire rating of not less than two hours. All openings in the floors shall be protected by vertical enclosures extending above and below such openings, the wall of such enclosures having a fire resistance of not less than two hours and all openings therein being protected with a fire resisting assemble (Clause 3.4.8 of National Building Code of India, 2005 Part-IV).

(iii)

Every vertical opening between at the floors shall be suitably enclosed or protected, has necessary to provide the following:

(a)

Reasonable safety to the occupants while using the means of egress by preventing spread of fire, smoke, or fumes through vertical openings from floor to floor to allow occupants to complete their use of the means of egress. Further it shall be ensured to provide a clear height of 21.00 MM in the passage/escape path of the occupants.

(b)

Limitation of damage to the building and its contents (Clause 3.4.8.4) Part-IV of National Building Code of India, 2005.

(i)

Air conditioning and ventilating systems shall be so installed and maintained as to minimize the danger of spread of fire, smoke or fumes from one floor to other or from outside to any occupied building or structure (Clause 3.4.11.1) Part IV of National Building Code of India 2005. a. Effective means for preventing circulation of smoke through the AC system in case of fire in air filters are from other sources drawn into the system, and shall have smoke sensitive devices for actuation in accordance with the accepted standards (Clause 3.4.11.3) Part IV of National Building Code of India 2005.

b. Separate air handling units for each floor shall be provided to avoid the hazards arising from spread of fire and smoke through air conditioning ducts (Clause 3.4.11.4) Part IV of National Building Code of India 2005.

c. Fire Dampers shall be provided in the AC system designed so as to close automatically in case of fire and thereby preventing spread of fire or smoke.

(ii)

Pressurization of staircases shall be done as per Clause 4.10 Part IV of National Building Code of India 2005.

(iii)

Fire doors with 2 hours fire resistance shall be provided at appropriate place along the escape route and particularly at the entrance to the lift lobby and stair well to prevent spread of fire and smoke (Clause 4.2.9) Part IV of National Building Code of India 2005.

(iv)

Smoke venting facilities for safe use of exits shall be provided as per Clause 3.4.12 Part IV National Building Code of India 2005.

(v)

Flame retardant material only should be made use for interior decoration and upholstery to prevent generation of toxic smoke/ flames. The surface interior finishes shall comply (Clause 3.4.15) Part IV of National Building Code of India 2005.

(vi)

Nos. of Fire Lifts complying to Clause C 1.5 Q of Annexure-C of Part IV of National Building Code of India 2005 shall be provided i.e. one Fire Lift for 1200 sq. metres of floor area.

(vii)

Basements ventilation shall comply to Clause C 1.6 of Annexure-C Part IV of National Building Code of India 2005.

(viii)

Illumination of means of exit in staircase and corridors shall comply with Clause C.1.4 of Annexure-C Part IV of National Building Code of India 2005.

(9)

This No Objection Certificate is issued with a condition that if the builder makes any deviation from the sanctioned plan, the entire building shall be demolished irrespective of the stage of construction.

(10)

You are requested to issue necessary instructions to to undertake joint inspection of the Multi-storeyed Building along with District Fire Officer,

Yours faithfully,

(.....)

Director General of Fire Services,

Andhra Pradesh, Hyderabad.

Copies to:

(i)

M/s.

(ii)

Multi-Storeyed Building Inspection Committee, i.e. Regional Fire Officer, Central Region, District Fire Officer, and Asst. District Fire Officer, (with a set of countersigned plans).

(iii)

The Officer-in-charge of Fire Station (with a set of countersigned plans).

Form No. 19

[See Rule 15(5)(a)]

(Check List for Final N.O.C. (High Rise Buildings))

A. Applicant to give up-dated, as-built and as-installed, status for all items mentioned in Form No. 16 A fresh copy of the Form No. 16 shall be used for this purpose. It shall be signed by the competent technical persons.

B. Copy of drawings cleared earlier by Fire Services vide "Provisional N.O.C." and approved for construction by municipal authority, shall be clearly marked to reflect the ground situation particularly with respect to the following and duly signed by technical persons:

I. Open spaces and parking spaces

II. 6 mtrs. Access space with vertical clearance of 5.0 mtrs., around the building

III. Section sketch of staircases to show their enclosed construction and vents to prevent smoke logging

IV. Actual location of fire/smoke check doors for exit routes, lifts, stairs, and for compartmentation, if any

V. Location of fire detectors, manual call points, sprinklers, hose reels, 4 yard hydrants and wet-risers

VI. Basement ventilation, smoke vents/exhausters, exit stairs 4 VII. Location of transformers, generators, showing enclosures & ventilation exhaust to external air space

VIII. Location/capacity of fire water tanks and pumps

IX. Means of access to higher floors and refuge areas, specially for windowless buildings to facilitate fire fighting and rescue operations.

C. Enclose technical details, specifications, vendors literature and confirm relevant I.S. Nos. complied with, for:-

(i)

Various models of fire resistant door assemblies used to contain spread of fire and smoke

(ii)

Pumps, hose-reels, fire/smoke detectors, sprinklers, hydrant system, fire extinguishers

(iii)

Smoke exhausters, ventilation/air conditioning system installed with brief engineering write-up, (signed by the technical person) explaining as to how it will achieve compliance with clauses 4 and 5 of National Building Code-4 (Prime objective is to contain spread of fire/smoke and their ingress into exit/escape routes to ensure safety of lives)

(iv)

D.1 Electrical single line diagram showing separate circuits for:

(i)

Fire pumps, fire-alarm and P.A. system, lifts

(ii)

Smoke control/exhaust equipment, and associated ventilation

(iii)

Exit route lighting, indicating battery back-up where provided

(iv)

Emergency generator system, with associated showing change-over from normal to emergency per National Building Code and IS 1646.

2. The above diagram will be used to verify, relevant compliance with National Building Code, IS-1646 and for functional test of fire safety related equipment.

3. Certificate of compliance with Electrical Rules and the diagram, is to be signed by the electrical contractor.

E. Fire control room and fire staff:

(i)

Indicate the alarm detection and communication facilities provided to alert inmates/fire services

(ii)

Emergency plan for evacuation

(iii)

Display of Do's and Don'ts in case of fire at conspicuous places

(iv)

Instructions for fire fighting

(v)

Organization of fire-staff/trained inmates, for fire extinguishing as per Annexure-E Part-4 of NBC

(vi)

Fire drills-schedule with name of person responsible for organizing the same and maintenance of relevant records.

Name

Phone number (Land line/ Mobile)

Licence No.

Signature

Builder

Architect
Structural Engineer
Electrical Contractor
Fire Safety Systems Contractor
Form No. 20

[See Rule 15(5)(g)(1)]

Director General of Fire Services to Municipal Corporation of Hyderabad

Sub: - APF & ESD..... issue of NOC for..... of M.s.

Ref: - 1. Application of M/s. (including particulars vide Form No. 18 Certificates and Dwgs).

2. Provisional N.O.C. issued vide Rc No..... dated.....

3. Report of MSB, Rc. No. dated

4. Government Memo. No. 6828/M1/2004-2, dated 19.06.2004 of M.A. & U.D. Department

5. M.C.H. Permit No.

With reference to the application first cited and items 11 to 14 in second cited above, the MSB committee has inspected the site at with reference to the duly certified, general information, check list, certificates, as-built drawings and have given their recommendations. Accordingly the Final NOC is issued for the building subject to the following conditions:

A. Main particulars of the Bldg.

1. Address of the Building :

2. Area of Plot/Ht. of Bldg. :

3. No. of blocks/Floors :

4. Types of occupancy :

5. Floor-wise details :

Floor - Built up.....Class of

Occupant loadRemarks

Area Occupancy

.....

.....

B. Strict compliance with all fire-safety provisions of NBC and of Building rules particularly measuring.

1. A min 6 mtrs. wide access around the building abutting building line is always maintained free of any parking obstructions, structures, fixtures, balconies a ht. of 5.0 mtrs. or generators, transformers, toilets, securities, posts, misc., petty vendors, etc.

2. The aggregate width/capacity of exits stairs and shall remain compliant with NBC for safe evacuation of occupants.

3. Fire-resisting doors to limit the spread of fire and for preventing smoke and fumes from entering exit stairs, lifts which impedes safe evacuation since it is an essential pre-requisite for life safety.

4. Parking basement provided with sprinklers, and stairs/lifts thereto comply with NBC are maintained in perfect working condition.

5. Fixed and first-aid fire fighting equipment, alarms etc. shall be tested and maintained regularly as per applicable standards and Fire-Drills conducted Quarterly for first two years and thereafter half yearly.

6. Emergency power generator etc., and associated equipment it feeds, should be periodically, verified as per NBC and IS-1646.

C. Fixed fire fighting equipment as per table 23 Part-4 of NBC

1. Capacity of fire water tanks. Underground, Terrace

2. Pumps at ground level: Electrical & diesel each LPM & one electrical 180 LPM.

3. (a) Auto detection and alarm system

(b)

Manual fire Alarm system

4. (a) Auto sprinkler system

(b)

Hose reels

5. (a) Yard hydrants

(b)

Wet riser(s)

(c)

Down corner

D. First-aid fire extinguishers

1. Type No.'s 2. Type No.'s 3. Type No's.....

E. Evacuation plan showing exit routes and recommended action be displayed at conspicuous locations

6. Fresh NOC would be required for any change in occupancy as per NBC and Building bye-laws.

Yours faithfully

Director General of Fire Services

Copy to the Builder.....

Copy to M.S.B. Committee.....

RFO/DFO/ADFO.....

Related AI tags, queries and research notes

Translation