

# The Merchant Shipping (Tonnage Measurement Of Ships) Rules, 1960

Source: <https://indiankanoon.org/doc/175170794/>

[Skip to main content](#)

[Legal Document View](#)

[Tools for analyzing structure and cite text of judgments](#)

[Unlock Advanced Research with](#)

[PRISM](#)

[AI](#)

Integrated with over 4 crore judgments and laws ? designed for legal practitioners, researchers, students and institutions

-

[Know your Kanoon](#)

-

[Doc Gen Hub](#)

-

[Counter Argument](#)

-

[Case Predict AI](#)

-

[Talk with IK Doc](#)

-

...

[Upgrade to Premium](#)

[Cites

0

, Cited by

0

]

Union of India - Act

The Merchant Shipping (Tonnage Measurement Of Ships) Rules, 1960

UNION OF INDIA

India

The Merchant Shipping (Tonnage Measurement Of Ships) Rules, 1960

Rule THE-MERCHANT-SHIPING-TONNAGE-MEASUREMENT-OF-SHIPS-RULES-1960 of 1960

Published on 17 December 1960

Commenced on 17 December 1960

[This is the version of this document from 17 December 1960.]

[Note: The original publication document is not available and this content could not be verified.]

The Merchant Shipping (Tonnage Measurement Of Ships) Rules, 1960

Published vide Notification Gazette of India, 1960, Part 2, Section 3(i), page 2038.

1767.

G.S.R. 1550, dated 17th December, 1960. - In exercise of the powers conferred by clauses (a) and (b) of sub-section (2) of Section 74 of the Merchant Shipping Act, 1958 (

44 of 1958

), the Central Government hereby makes the following rules, namely---

1.

Short title, commencement and application.

(1)

These rules may be called the Merchant Shipping (Tonnage Measurement of Ships) Rules, 1960.

(2)

They shall come into force on the 1st January, 1961.

(3)

They shall apply to sea-going ships which exceed 15 tons net and which are fitted with mechanical means of propulsion.

[ Definitions.

[Substituted by G.S.R. 897, dated 24th April, 1970.]

- In these rules, unless the context otherwise requires,-

(a)

"Act" means the Merchant Shipping Act, 1958;

(b)

"break" means the space above the line of the upper deck, when the deck is cut off and continued at a higher elevation;

(c)

"continuous deck" includes a deck continuous athwartship and in a fore and aft direction, at least between peak bulkheads, with interruptions in way of propelling machinery space, openings, ladder and stairway, openings, trunks, chain lockers, cofferdams or steps which do not exceed 1220 millimetres in height :

(d)

"crew" means seamen and apprentices;

(e)

"exempted spaces" means spaces in a ship which, either by virtue of their location and usage or by nature of tonnage opening or other specified openings in their sides, are exempted and, therefore, not included in ascertaining her gross tonnage;

(f)

"gross tonnage" means the sum total of the cubic capacity of spaces below the upper deck and spaces permanently covered and closed-in spaces on or above the upper deck (other than such spaces which are exempt from measurement under these rules) and consists of-----

(i)

the tonnage below the tonnage deck;

(ii)

the tonnage of the spaces between the tonnage deck and the uppermost complete deck;

(iii)

the covered and closed-in spaces on or above the uppermost complete deck;

(iv)

the engine and light and air spaces above the upper deck; and

(v)

the excess of hatchways;

(g)

"load line rules" means the Indian Merchant Shipping (Load Line) Rules, 1934, as continued in force by sub-section (3) of section 461 of the Act;

(h)

"method" means one of the methods of determining the tonnage of a ship specified in Schedule I;

(i)

"propelling power allowance" means the deduction from the gross tonnage on account of the space occupied by the propelling power machinery;

(j)

"register tonnage" or "net tonnage" means the tonnage arrived at after making from the gross tonnage of a ship the allowances and deductions permissible under these rules;

(k)

"Schedule" means a Schedule to these rules;

(l)

"Second deck" for the purpose of tonnage mark means the deck next below the uppermost complete deck which is

continuous in a fore and aft direction at least between peak bulkheads, is continuous athwartships, and is fitted as an integral and permanent part of the ship's structure, with proper covers fitted to all main hatchways;

(m)

"Surveyor" means a surveyor appointed under section 9 of the Act;

(n)

[ "ton" means a unit of volume equal to 2.83 cubic metres (alternatively one cubic metre is equivalent to 0.353 ton);]

(o)

"tonnage deck" means the second deck except in the case of single deck ships, in which case it means the upper deck;

(p)

"trunk" means a hatch and ventilation trunks which do not extend longitudinally completely between main transverse bulkheads;

(q)

"uppermost complete deck" for the purpose of tonnage mark means the upper deck of a ship exposed to sea and weather fitted as an integral part of the ship's structure with permanent means of closing all openings in the weather portions thereof :

Provided that all openings in the sides of ship below the deck, other than openings situated abaft a transverse water-tight bulkhead, placed aft of the rudder stock, are fitted with permanent means of water-tight closing.]

3.

Gross Tonnage.

(1)

The gross tonnage of a ship shall be determined by the methods and in the circumstances specified below, namely :-

(a)

By method I, at the time of registration of a ship and in other cases to which that method is applicable;

(b)

By method II with the permission of the Central Government, where the ship has cargo on board and in other cases where method I is not applicable :

Provided that the owner of any ship the tonnage of which was determined by method II may, at any subsequent time, apply to the Central Government for the determination of its tonnage by method I.

The ship shall thereupon be re-measured and tonnage altered accordingly.

(c)

By method III, in the case of open ships.

(2)

All measurements for the purpose of ascertaining the tonnage of a ship shall be in metres or fractions of a metre.[\*\*\*]

[Omitted by G.S.R. 897, dated 24th April, 1970.]

.

4.

Deductions from Gross, Tonnage.

- [(1) From the gross tonnage of a ship determined in accordance with the provisions of rule 3, deductions shall be made on account of the following spaces, namely :-

(a)

allowance for propelling power machinery in ships propelled by steam or other mechanical power determined in accordance with rule 5;

(b)

any space used exclusively for the accommodation of master or crew :

Provided that such space conforms to the requirements of the Merchant Shipping (Crew Accommodation) Rules, 1960, but excluding the following space :

(i)

space appropriated for the storage of fresh water;

(ii)

space appropriated for the storage of provisions (other than fresh water) in excess of 15 per cent of the aggregate crew accommodation space;

- (c) the wheelhouse and chartroom, and space fitted with the appropriated for the use of radio and navigational aids;
- (d) chain lockers and space appropriated for, or for the working of the steering gear, anchor gear and capstan;
- (e) space appropriated for the storage of safety equipment or batteries;
- (f) workshop and store rooms appropriated for the use of pumpmen, electricians, carpenters and boatswains, and the lamp-room;
- (g) space occupied by the donkey engine and boilers if they area outside the propelling machinery space and connected to the main pumps of the ship;
- (h) space occupied by the main pumps of the ship if they are outside the propelling machinery space;
- (i) any space below the upper deck (other than double bottom) adapted solely for water ballast:  
Provided that no deduction shall be made on account of any space unless it has previously been included in the gross tonnage.]

[Substituted by G.S.R. 639, dated 14th May, 1975.]

- (2) No deduction on account of any space shall be made under sub-rule (1) unless--

- (a) the space has been certified by a surveyor as reasonable in extent and properly and efficiently constructed for the purpose for which it is intended;
- (b) a notice is permanently marked in or over such space stating the purpose for which it is to be applied.

5.  
Propelling Power Allowance.

- (1) The allowance for engine-room space in ships propelled by steam or other power requiring engine-room shall be ascertained in accordance with method IV specified in Schedule 1. The deductions on account of propelling power machinery shall be regulated as follows, namely :--

- (a) where the tonnage of the space occupied by and necessary for the proper working of the boilers and machinery is 13 per cent or above and under 20 percent of the gross tonnage, the deduction shall be 32 per cent of the gross tonnage;
- (b) where such space is below 13 per cent of the gross tonnage, the deduction shall be 32 per cent of the gross tonnage reduced proportionately;
- (c) where such space is 20 per cent and above of the gross tonnage, the deduction shall consist of the tonnage of the space occupied by or required to be enclosed for the proper working of the boilers and machinery with the addition of three-fourth of the tonnage of that space;
- (d) in cases falling under clauses (b) and (c), the space occupied by the shaft tunnel shall also be added to the engine-room space.

- (2) Such portion of the space above the crown of the engine-room and above the upper deck as is framed in for the machinery or for the admission of light and air shall not be included in the measurement of the spaces occupied by the propelling power machinery, unless the owner of the ship has applied in writing to the Central Government in that behalf:  
Provided that-----

- (a)

the portion is first included in the measurement of the gross tonnage;

(b)

a surveyor certifies that the portion so framed in is reasonable in extent and is so constructed as to be safe and seaworthy, and that it cannot be used for any purpose other than the machinery or for the admission of light and air to the machinery or boilers of the ship.

(3)

The allowance made under this head shall not in any case exceed fifty-five per cent of that portion of the tonnage of the ship which remains after deducting from the gross tonnage the allowance on account of the space used for the accommodation of the master and the crew provided that this shall not apply to ships constructed for the purpose of towing vessels so long as they are employed as tugs but not employed for the carriage of passengers, cargo or stores or when using dry docks, floating docks or places provided for repairing of vessels.

6.

Spaces for master and crew.

(1)

No deduction on account of any space intended for the master or the crew shall be made unless a surveyor has certified that space is used for that purpose.

(2)

The maximum space allowable on account of storage under this head shall not exceed fifteen per cent of the deductions for the master's and crew accommodation.

7.

Allowance for Water Ballast.

- The allowance on account of water ballast spaces shall be regulated in accordance with the [provisions of]  
[Substituted by G.S.R. 897, dated 24th April, 1970.]

Schedule II.

8.

Exemptions.

- [(1) The following spaces shall be measured but, save as provided in rule 8A, exempted from inclusion in the gross tonnage---

(a)

on application in writing the owner or agent of the ship-

(i)

deck shelters for deck passengers;

(ii)

spaces abreast side openings;

(iii)

open passage-ways serving other than passenger spaces above deck;

(b)

permanently closed spaces which, had they been provided with tonnage openings, would have qualified for exemption but for the coming into force of the Merchant Shipping (Tonnage Measurement of Ships) Amendment Rules, 1970

(i)

spaces, including spaces situated in the detached superstructures or deck houses, on or above the uppermost complete deck;

(ii)

spaces situated within the uppermost tween deck so long as, when the ship is in the summer zone, the upper edge of the tonnage mark referred to in rule 8B, or when the ship is in fresh water or the tropical zone, the upper edge of the additional line referred to in rule 8C, is not submerged.]

(2)

[ The following permanently closed-in spaces situated on or above the upper deck shall not be included in the Gross Tonnage provided they are reasonable in extent, namely :-

(a)

space fitted with the appropriated for the use of machinery or condensers;

- (b) the wheelhouse and chartroom, and space fitted with and appropriated for the use of radio and navigational aids;
- (c) skylights, domes and trunks which light or ventilate the space they serve;
- (d) chain lockers, and space appropriated for working the anchor gear and capstan;
- (e) space appropriated for the storage of safety equipment or batteries;
- (f) companions and access hatches serving as protection for stairways or ladderways leading to space below, and openings over such stairways and ladderways including escape trunks;
- (g) the galley, and any separate bakery fitted with ovens; provided in either case that no part thereof is appropriate for use for any other purpose;
- (h) washing and sanitary accommodation forming part of the crew accommodation or appropriated for the use of the master;
- (i) workshops and storerooms appropriated for the use of pumpmen, engineers, electricians, carpenters and boatwains, and the lamproom;
- (j) water ballast tanks not appropriated for use for any other purpose.]

(3) The Central Government may, subject to such conditions as maybe prescribed, grant further exemptions as may be deemed necessary.

[8-A. Assignments of tonnage mark.

[Inserted by G.S.R. 897, dated 24th April, 1970.]

- The spaces referred to in sub-clause (ii) of clause (b) of sub-rule 1 of rule 8 shall not be exempted from inclusion in the gross tonnage of a ship which does not have tonnage markings in accordance with these rules.

8.

-B. Form and position of tonnage mark.

(1)

The tonnage mark shall be of the form set out in Schedule IIA and shall consist of a horizontal line 380 millimetres long and 25 millimetres wide, upon which shall be placed for identification an inverted equilateral triangle, each side of which shall be 300 millimetres long and 25 millimetres wide, with its apex on the mid-point of the said horizontal line.

(2)

Such mark shall be cut or welded on each side of the ship abaft amidships, but as near thereto as practicable, but the apex of the triangle shall not be nearer than 540 millimetres to the centre of the load line disc assigned under the load line rules, nor farther than 2000 millimetres abaft the vertical centre line of such load line disc.

(3)

The upper edge of the tonnage mark shall be located below the line of the second deck, the position of which shall be determined in accordance with the Table set out in Schedule IIB.

(4)

Notwithstanding anything contained in sub-rule (3), when the free board deck, as determined under the load line rules, coincides with the second deck, the tonnage mark shall be placed on a line level with the uppermost part of the load line grid.

8.

-C. Additional line.

(1)

To indicate fresh water and tropical draught an additional horizontal line, 230 millimetres long and 25 millimetres wide, may be cut or welded above the tonnage mark (see Schedule IIA), except when the tonnage mark is assigned in

accordance with sub-rule (4) of rule 8B.

(2)

Such additional line shall be measured from a vertical line 25 millimetres wide marked at the after end of, and perpendicular to, the tonnage mark; the length of the vertical line being one forty-eighth of the moulded draught to the tonnage mark.

8.

-D. Ships having no load line markings.

- For ships to which no load line has been assigned, the line of the uppermost complete deck shall be marked amidships by a horizontal line 300 millimetres long and 25 millimetres wide.

8.

-E. Alternate gross tonnage.

(1)

Except when the tonnage mark is assigned in accordance with sub-rule (4) of rule 813, there shall be determined for every ship which has been assigned a tonnage mark, two gross tonnages for the purpose of deciding whether exemption under sub-clause (ii) of clause (b) of sub-rule (1) of rule 8 is admissible according as the tonnage mark is submerged or not.

(2)

In the case of any ship for which two tonnages have been determined in accordance with sub-rule (1) and which is in possession of a certificate of registry showing such two tonnages, the lower of the two tonnages shall be construed to be its tonnage for the time being while the ship is so loaded as not to submerge the tonnage mark assigned to it in accordance with rule 8A, for the purposes of levy of any fee or dues which are based on the gross tonnage of a ship measured in accordance with the provisions of these rules :

Provided that, for the purposes of Parts VI, VII, VIII and IX of the Act, the qualifying gross tonnage shall be the higher figure.

8.

-F. Higher tonnage in special cases.

- Notwithstanding anything contained in rule 8B, if the Central Government finds that in respect of an Indian ship possessing dual tonnage certificate any country outside India takes into account the higher tonnage for the purpose of levy of tonnage dues, whether or not the tonnage mark is submerged, the Central Government may, by notification in the Official Gazette, direct that in respect of a ship registered in that country the higher tonnage shall constitute the basis of levy of tonnage dues in India.]

[Substituted by G.S.R. 639, dated 14th May, 1975.]

9.

Register Tonnage on net tonnage.

(1)

The register tonnage of a ship shall be arrived at by deducting from the [gross tonnage or gross tonnages (referred to in rule 8F.)]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

of the ship the allowances of the nature and to the extent admissible under these rules.

[\*\*\*]

[Omitted by G.S.R. 897, dated 24th April, 1970.]

(3)

Where the tonnage of a ship has been or is deemed to have been ascertained under these rules, the tonnage shall not be altered unless the alteration is made in the form or the capacity of the ship or it is discovered that the tonnage has been erroneously computed, and in either of these cases, the ship shall be remeasured and her tonnage ascertained in accordance with these rules.

[9-A. Deck Cargo and cargo in exempted spaces.

[Inserted by G.S.R. 897, dated 24th April, 1970.]

(1)

If any ship other than a ship exclusively engaged in trading between any port or place in India--

(a)

carries cargo in the enclosed space between the uppermost complete deck and the second deck while the tonnage mark is not submerged, or

(b)

carries any deck cargo, that is to say, carries any cargo in any uncovered space upon deck or in any covered space not included in the cubical contents forming ship's register tonnage,

the tonnage of space so utilised for carrying cargo shall be measured in the manner specified in Schedule I and added to the relevant tonnage of the ship and the total tonnage so calculated shall be the basis for the levy of dues based on ship's register tonnage.

Note. -The space so occupied shall be deemed to be the space limited by straight lines enclosing a rectangular space sufficient to include the goods.

(2)

The tonnage of spaces referred to in sub-rule (1) shall be ascertained by the officer of the customs referred to in Section 3 of the Customs Act, 1962, in the manner directed in paragraph (6) of Method I in Schedule I and when so ascertained shall be entered by him in ship's official log book and also in a memorandum which he shall deliver to the Master and the Master shall, when any dues are demanded on ship's tonnage, produce that memorandum in the like manner as if it were ship's Certificate of Registry or in the case of a ship other than an Indian ship a document equivalent to a Certificate of Registry.]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

10.

Tonnage ascertained in foreign countries.

(1)

Where the tonnage of a ship has been ascertained in accordance with the rules in force in a foreign country which has adopted these rules or in accordance with the rules which are substantially similar to these rules, the Central Government may accept the tonnage specified in the certificate of registry issued by that country in the same manner, to the same extent and for the same purposes as the tonnage indicated in the certificate of registry issued under these rules.

(2)

Notwithstanding anything contained in sub-rule (1), the Central Government may, if it is of opinion that the tonnage of any foreign ship as ascertained by the rules of the country to which she belongs differs materially from the tonnage of that ship as it would be if it is measured under these rules, direct that the ship shall be re-measured and her tonnage ascertained in accordance with these rules.

11.

Suez Canal and Panama Special Tonnage Certificate.

- If a request is received from a shipowner for measurement of a ship for Suez Canal or Panama Special Tonnage Certificate, the ship may be re-measured and her tonnage ascertained in accordance with the rules issued by the Suez Canal or Panama Canal authorities.

12.

[

[Inserted by G.S.R. 639, dated 14th May, 1975.]

Notwithstanding any procedure set out in Schedule I for the measurement of tonnage of ships the volume computed in cubic metres may be multiplied by the factor 0.353 to arrive at volume in tons.]

[13]

[Re-numbered by G.S.R. 639, dated 14th May, 1975.]

. Fees.

- Fees shall be levied under these rules at the rates and for the purposes specified in Schedule III.

Rules As To The Measurement Of Tonnage

I

(See rule 2)

Method I

(1)

Measurement of ships to be registered : and other ships of which the hold is clear. - Lengths. Measure the length of the



ship in a straight line along the upper side of the tonnage deck from the inside of the inner plank (average thickness) at the side of the stem to the inside of the midship stem timber or plank there, as the case may be (average thickness), deducting from this length what is due to the rake of the bow in the thickness of the deck, and what is due to the rake of the stern timber in the thickness of the deck, and also what is due to the rake of the stem timber in one-third of the round of the beam; divide the length so taken into the number of equal parts required by the following Table, according to the class in such Table to which the ship belongs :

[Table

[Substituted by G.S.R. 897, dated 24th April, 1970.]

Class 1. - Ships of which the tonnage deck is according to the above measurement 15.24 metres long or under, into 4 equal parts;

Class 2. - Ships of which the tonnage deck is according to the above measurement above 15.24 metres long and not exceeding 36.58 metres, into 6 equal parts;

Class 3. - Ships of which the tonnage deck is according to the above measurement above 36.58 metres long and not exceeding 54.86 metres, into 8 equal parts;

Class 4. - Ships of which the tonnage deck is according to the above measurement above 54.86 metres long and not exceeding 206.74 metres, into 10 equal parts;

Class 5. - Ships of which the tonnage deck is according to the above measurement above 206.74 metres, into 12 equal parts.]

In the case of a break or breaks in a double bottom for water ballast, the length of the ship is to be taken in parts according to the number of breaks, and each part divided into a number of equal parts according to the class in the above Table to which such length belongs.

(2)

Transverse areas. - Then, the hold being first sufficiently cleared to admit of the required depths and breadths being properly taken, find the transverse area of the ship at each point of division of the length or each point of division of the parts of the length as the case may require as follows :-

Measure the depth at each point of division from a point at a distance of one-third of the round of the beam below the tonnage deck, or, in case of a break, below a line stretched in continuation thereof, to the upper side of the floor timber (upper side of the inner plating of the double bottom) at the inside of the limber strake, after deducting the average thickness of the ceiling which is between the bilge planks and limber strake; then, if the depth at the midship division of the length does not exceed [4.88 metres]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

, divide each depth, into five equal parts; then measure the inside horizontal breadth at each of the four points of division, and also at the upper point of the depth, extending each measurement to the average thickness of that part of the ceiling which is between the points of measurement; number these breadths from above, (i.e., numbering the upper breadth one, and so on down to the fifth breadth; multiply the second and fourth by four, and the third by two; add these products together, and to the sum add the first breadth and the fifth; multiply the quantity thus obtained by one-third of the common interval between the breadths, and the product shall be deemed the transverse area of the upper part of the section; then find the area between the fifth and lower point of the depth by dividing the depth between such points into four equal parts and measure the horizontal breadths at the three points of division and also at the upper and lower points, and proceed as before and the sum of two parts shall be deemed to be the transverse area; but if the midship depth exceed [4.88 metres]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

, divide each depth into seven equal parts instead of five, and measure as before directed the horizontal breadths at the six points of division, and also at the upper point of the depth, number them from above as before; multiply the second, fourth, and sixth by four, and the third and fifth by two; add these products together, and to the sum add the first breadth and the seventh; multiply the quantity thus obtained by one-third of the common interval between the breadths, and the products shall be deemed the transverse area of the upper part of the section; then find the lower part of the area as before directed, and add the two parts together, and the sum shall be deemed to be the transverse area.

In all cases, where the top of the double bottom is horizontal it will be sufficient to measure the transverse areas.

(3)

Computation from areas. - Having thus ascertained the transverse area at each point of division of the length of the ship,

or each point of division of the parts of length, as the case may require, as required by the above table, proceed to ascertain the register tonnage under the tonnage deck in the following manner :

Number the areas respectively, 1, 2, 3, etc. No.1 being at the extreme limit of the length at the bow, or of each part of the length, and the last number at the extreme limit of the length of the stern, or the extreme limit at the after end of each part of the length : then whether the length be divided according to the table into four or 12 parts, as in classes 1 and 5, or any intermediate number, as in classes 2, 3 and 4, multiply the second and every even numbered area by four, and third and every odd numbered area (except the first and last) by two; add these products together, and to the sum add the first and last if they yield anything; multiply the quantity thus obtained by one-third of the common interval between the areas, and the product will be the cubical contents of the space, or cubical contents of each part if the ship is measured in parts under the tonnage deck; divide this product, or if measured in parts the products of the several parts added together, [by 2.83]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

, and the quotient, being the tonnage under the tonnage deck, shall be deemed to be the register tonnage of the ship, subject to any additions and deductions under the rules.

(4)

In case of decks above the tonnage deck. - If the ship has a third deck, commonly called a spar deck, the tonnage of the space between it and the tonnage deck shall be ascertained as follows :-

Measure [\* \* \*]

[Omitted by G.S.R. 897, dated 24th April, 1970]

the inside length of the space at the middle of its height from the plank at the side of the stem to the lining on the timbers at the stern, and divide the length into the same number of equal parts as the length of the tonnage deck is divided as above directed; measure (also at the middle of its height) the inside breadth of the space at each of the points of division, also the breadth at the stem and the breadth at the stern : number them successively 1, 2, 3, etc., commencing at the stem; multiply the second and all the other even numbered breadths by four, and the third and all the other odd numbered breadth (except the first and the last) by two; to the sum of these products add the first and last breadths; multiply the whole sum by one-third of the common interval between the breadths, and the result will give in superficial [metres]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

the mean horizontal area of the space; measure the mean height of the space, and multiply by it the mean horizontal area, and the product will be the cubical contents of the space; divide this product by [2.83]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

and the quotient shall be deemed to be the tonnage of the space and shall be added to the tonnage of the ship ascertained as aforesaid. If the ship has more than three decks, the tonnage of each space between decks above the tonnage deck shall be severally ascertained in manner above described, and shall be added to the tonnage of the ship ascertained as aforesaid.

(5)

Poop, deck-house, forecastle, and any other closed-in space. - If there be a break, a poop or any other permanent closed-in space on the upper deck available for cargo or stores, or for the berthing or accommodation of passengers or crew, the tonnage of that space shall be ascertained as follows :

Measure the internal mean length of the space [\* \* \*]

[Omitted by G.S.R. 897, dated 24th April, 1970.]

and divide it into two equal parts; measure at the middle of its height three inside breadths, namely, one at each end and the other at the middle of the length; then to the sum of the end breadths add four times the middle breadth, and multiply the whole sum by one-third of the common interval between the breadths, the product will give the mean horizontal area of the space; then measure the mean height, and multiply by it the mean horizontal area; divide the product by [2.83]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

and the quotient shall be deemed to be the tonnage of the space and shall be added to the tonnage under the tonnage deck ascertained as aforesaid. Provided that no addition shall be made in respect of any building erected for the shelter of deck passengers, and approved by the Director General of Shipping.

(6)

[ The cubic capacity of covered or uncovered spaces upon deck, when used for carriage of cargoes, shall be determined

by multiplying the area, in square metres, of spaces occupied by cargo, as determined in accordance with the provisions of sub-rule (2) of rule 9A, by the maximum height of goods in metres. The cubic capacity in metres so arrived shall be divided by 2.83 for determining tonnage of such spaces.]

[Inserted by G.S.R. 897, dated 24th April, 1970.]

#### Method II

(1)

Measurement of ships not requiring registry with cargo on board and ships which cannot be measured under Method I Length-Breadth. - -Girthing of the ship. Measure the length on the uppermost deck from the outside of the outer plant at the stem to the aft side of the stern-post, deducting therefrom the distance between the aft side of the stern-post and the rabbet of the stern-post at the point where the counter plank crosses it; measure also the greatest breadth of the ship to the outside of the outer planking or wales, and then, having first marked on the outside of the ship on both sides thereof the height of the upper deck at the ship's sides girth the ship at the greatest breadth in a direction perpendicular to the keel from the height so marked on the outside of the ship on the one side to the height so marked on the other side by passing a chain under the keel; to half the girth thus taken add half the main breadth; square the sum; multiply the result by the length of ship taken as aforesaid; then multiply this product by the factor [0.17 (seventeen hundredths)]

[Substituted by G.S.R. 897, dated 24th April, 1970]

in the case of ships built of wood, and [0.18 (eighteen hundredths)]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

in the case of ships built of iron and the product shall be deemed the register tonnage of the ship, subject to any additions and deductions under the rules.

(2)

Poop, deck-house, forecastle, and other closed-in spaces on upper deck. - If there be a break, a poop, or other closed-in space on the upper deck, the tonnage of that space shall be ascertained by multiplying together the mean length, breadth and depth of the space, and dividing the product [by 2.83]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

and the quotient so obtained shall be deemed to be the tonnage of the space, and shall be added to the tonnage of the ship ascertained as aforesaid.

#### Method III

Measurement of open ships. - In ascertaining the tonnage of open ships the upper edge of the upper strake is to form the boundary line of measurement, and the depths shall be taken from an athwartship line, extended from upper edge to upper edge of the said strake at each division of the length.

#### Method IV

Measurement of allowance for engine room space. - (i) Measure the mean depth of the space from its crown to the ceiling at the limber strake, measure also three, or, if necessary, more than three breadths of the space at the middle of its depth, taking one of those measurements at each end, and another at the middle of the length; take the mean of those breadths; measure also the mean length of the space between the foremost and aftermost bulkheads or limits of its length, excluding such parts, if any, as are not actually occupied by or required for the proper working of the machinery; multiply together these three dimensions of length, breadth and depth, divide the product [by 2.83]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

and the result shall be deemed the tonnage of the space below the crown; then find the cubical contents of the space or spaces, if any, above the crown aforesaid, which are framed in for the machinery or for the admission of light and air, by multiplying together the length, depth, and breadth thereof; add such contents to the cubical contents of the space below the crown; divide the sum [by 2.83]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

; and the result shall (subject to the provisions hereinafter contained) be deemed to be the tonnage of the space.

(ii)

If in any ship in which the space for propelling power is to be measured the engines and boilers are fitted in separate compartments, the contents of each shall be measured severally in like manner, according to the above method, and the sum of their several results shall be deemed to be the tonnage of the said space.

(iii)

In the case of screw steamers in which the space for propelling power is to be measured, the contents of the shaft trunk

shall be ascertained by multiplying together the mean length, breadth, and depth of the trunk, and dividing the product [by 2.83]

[Substituted by G.S.R. 897, dated 24th April, 1970.]

.

(iv)

If in any ship in which the space aforesaid is to be measured any alteration be made in the length or capacity of the spaces, or if any cabins be fitted in the space, the ship shall be deemed to be a ship not registered until re-measurement.

II

(See rule 7)

Water Ballast Spaces

The maximum allowance for water ballast spaces shall not exceed 19 per cent of the gross tonnage, irrespective of the size of the ship.

In calculating such allowance, the capacity of all water ballast spaces above the double bottom may be taken into account.

IIA

[See rule 88(1)-7]

Tonnage Mark

IIB

[See Rule 8B (3)]

Tonnage Mark Table

Minimum distance front the moulded line of the second deck to the upper edge of the tonnage mark in millimetres.

Length

Lt. Lt/Dt

in

metres.

12

13

14

15

16

17

18

19

20

67

and under

51

51

51

51

51

51

51

51

51

70

81

51

51

51

51  
51  
51  
51  
51  
73  
118  
51  
51  
51  
51  
51  
51  
51  
51  
51  
76  
157  
82  
51  
51  
51  
51  
51  
51  
51  
51  
79  
201  
119  
51  
51  
51  
51  
51  
51  
51  
51  
51  
82  
246  
159  
84  
51  
51  
51  
51  
51  
51  
51  
85  
294  
200  
120  
51  
51

51  
51  
51  
51  
88  
344  
344  
158  
83  
51  
51  
51  
51  
51  
91  
398  
291  
199  
119  
51  
51  
51  
51  
51  
94  
455  
341  
243  
158  
83  
51  
51  
51  
51  
97  
515  
393  
288  
198  
119  
51  
51  
51  
51  
97  
515  
393  
288  
198  
119  
51

51  
51  
51  
100  
577  
447  
336  
240  
135  
81  
51  
51  
51  
103  
643  
506  
388  
386  
196  
117  
51  
51  
51  
106  
713  
567  
442  
334  
239  
156  
82  
51  
51  
109  
785  
631  
499  
385  
285  
196  
118  
51  
51  
112  
862  
699  
559  
438  
333  
240  
157

83  
51  
115  
943  
772  
624  
497  
386  
288  
200  
118  
52  
118  
1026  
845  
690  
556  
439  
336  
243  
161  
87  
121  
1111  
921  
758  
617  
494  
385  
288  
202  
124  
124  
1199  
1000  
829  
682  
553  
439  
338  
247  
165  
127  
1279  
1075  
900  
749  
617  
500  
397  
304



220  
130  
1362  
1154  
975  
820  
685  
566  
460  
365  
279  
133  
1450  
1237  
1054  
896  
757  
635  
527  
429  
342  
136  
1541  
1323  
1135  
974  
832  
707  
596  
496  
407  
139  
1636  
1413  
1222  
1057  
912  
784  
671  
569  
478  
142  
1732  
1504  
1309  
1140  
992  
862  
746  
642  
548

145  
1829  
1597  
1397  
1225  
1074  
941  
823  
717  
621  
148  
1926  
1688  
1485  
1309  
1555  
0119  
898  
790  
692  
151  
2020  
1778  
1570  
1390  
1233  
1095  
971  
861  
761  
154  
2112  
1865  
1653  
1470  
1309  
1168  
1042  
930  
828  
157  
2203  
1951  
1735  
1548  
1384  
1241  
1112  
998  
894  
160

2288  
2032  
1812  
1622  
1455  
1308  
1177  
1061  
955  
162  
2374  
2112  
1888  
1694  
1525  
1376  
1241  
1122  
1015  
166  
2455  
2189  
1961  
1763  
1591  
1438  
1302  
1181  
1072  
169  
2537  
2866  
2033  
1832  
1656  
1501  
1363  
1239  
1128  
172  
2616  
2340  
2103  
1899  
1720  
1562  
1421  
1295  
1182  
175  
2694

2414  
2173  
1965  
1783  
1622  
1479  
1351  
1236  
178  
2772  
2487  
2242  
2030  
1845  
1682  
1536  
1406  
1289  
181  
2350  
2560  
2312  
2096  
1907  
1741  
1593  
1461  
1342  
184  
2924  
2629  
2376  
2157  
1965  
1797  
1640  
1512  
1391  
187  
2999  
2699  
2441  
2219  
2024  
2853  
1700  
1563  
1440  
190  
3072  
2768

2506  
2280  
2083  
1909  
1753  
1614  
1489  
193  
3144  
2835  
2569  
2340  
2139  
1962  
1804  
1663  
1536  
196  
3215  
2901  
2632  
2398  
2195  
2014  
1855  
1711  
1582  
199  
3285  
2967  
2694  
2456  
2250  
2067  
1905  
1759  
1628  
202  
3356  
3032  
2754  
2513  
2304  
2118  
1953  
1805  
1672  
205  
3425  
3096  
2814

2570  
2357  
2169  
2001  
1851  
1716  
208  
3493  
3160  
2874  
2626  
2410  
2219  
2049  
1897  
1760  
211  
3561  
3223  
2933  
2682  
2462  
2263  
2096  
1942  
1803  
214  
3628  
3285  
2991  
2736  
2513  
2317  
2142  
1986  
1845  
217  
3694  
3346  
3048  
2790  
2562  
2365  
2187  
2029  
1886  
220  
3760  
3407  
3105  
2843

2613  
2412  
2232  
2072  
1927  
223  
3825  
3467  
3161  
2894  
2662  
2458  
2276  
2113  
1966  
226  
3889  
3526  
3216  
2947  
2710  
2504  
2319  
2154  
2005  
229  
3951  
3584  
3270  
2998  
2758  
2549  
2361  
2194  
2043  
232  
4013  
3642  
3323  
3047  
2805  
2593  
2402  
2233  
2080  
235  
4075  
3699  
3376  
3096  
2841

2636  
2443  
2272  
2117  
238  
4136  
3756  
3438  
3144  
2897  
2678  
2483  
1231  
2153  
241  
4197  
3810  
3479  
3192  
3941  
2720  
2523  
2347  
2188  
244  
4257  
3865  
3530  
3240  
2986  
2762  
2562  
2384  
2223

Note. - (1) Length (Lt) used in the tonnage mark table shall be the distance on the second deck between two points, of which the foremost is the point where the underside of that deck or the line thereof at the stem, meets the inner surface of the ceiling sparring or frames, and the aftermost is the point where the underside of that deck or the line thereof, meets the inner surface of the ceiling sparring or frames in the middle plan at the stem. Where the second deck is stepped an equivalent length shall be used. (See figure I)

(2)

Depth (Ds) to be used in the tonnage mark table is the moulded depth to the second deck. Where the second deck is stepped an equivalent depth shall be used.

(See figure I).

Figure I

(3)

The tonnage mark table is given for the ratios Lt/Ds from 12 to 20 for lengths at intervals of 3 metres upto 244 metres. For intermediate lengths and Lt/Ds ratios the corresponding distance should be obtained by interpolation. In other cases figures should be obtained by extrapolation.

III

(See Rule 12)

(a) Measurement



for Indian Tonnage

Rs.

P.

(i)

For measurement for one of the following  
under Method I in

Schedule I:-

First measurement

of an Indian ship

Assignment of

Tonnage Mark

Re-measurement

including under-deck tonnage

First

measurement of a foreign ship for a

certificate of

Indian tonnage

Re-measurement,

including under-deck

tonnage,

of a foreign ship for renewal of a

certificate of

Indian tonnage

Re-measurement

of a ship previously

measured under

Method U in Schedule I

Re-measurement of

under-deck tonnage

Ships not

exceeding 50 tons

80.00

Ships

exceeding 50 tons but not exceeding 100 tons

For each

additional 100 tons or part of 100 tons,

175.00

above 100 tons,

but not exceeding 20,000 tons

25.00

For

each additional 100 tons or part of 100 tons,

exceeding 20,000

tons

10.00

(ii) For

measurement under Method II and

Rs. P.

Method III in

Schedule II-First measurement of an Indian ship

First measurement

of a foreign ship for  
Certificate of  
Indian Tonnage half the fee in (a)(i)  
Re-measurement  
which includes under-deck tonnage  
(iii) For  
re-measurements not involving under-deck tonnage (Indian or  
foreign ships)  
For one of the  
following re-measurement:  
alterations on the  
upper deck;  
alterations in the  
engine room;  
light and air  
spaces;  
crew  
accommodation;  
water ballast  
spaces;  
Ships not  
exceeding 50 tons  
25.00  
Ship exceeding 50  
tons but not exceeding 100 tons  
35.00  
For each  
additional 100 tons or part of 100 tons  
exceeding 100 tons  
5.00  
Maximum fee for  
each item 215.00  
The  
fee for re-measurement for crew  
accommodation  
covers the inspection of the  
crew  
accommodation if the inspection is made  
at the same time  
as the remeasurement.  
(iv)  
For inspection made ecessasy by minor  
alterations (rig,  
engines, etc.)  
40.00  
(v)  
For the renewal of a foreign ship's certificate  
of  
Indian tonnage or for the issue of a  
certificate  
of Indian tonnage to a foreign

ship that was  
previously Indian.

When  
a Surveyor's check measurement  
shows  
that no alterations have occurred and  
re-measurement is  
unnecessary.

When  
some re-measurement is necessary although  
the  
under deck is unaltered or when  
measurement  
is necessary for the assignment  
of a tonnage mark

80.00

Plus  
the fee in (iii) for any re-measurements required.

(vi) For a copy of  
a certificate of Indian tonnage  
10.00

(b) Measurement  
for Suez and Panama Tonnage

(i) For first  
measurement of a ship when the Indian tonnage figures are  
available for a Suez Canal or a Panama Canal Certificate  
two-fifths  
of the appropriate fee in (a)(i).

For Suez Canal and  
a Panama Certificate if the measurements are made at the same  
time  
three-fifths  
of the appropriate fee in (a)(i)

(ii) For first  
measurement of a ship when the Indian tonnage figures are not  
available.

the  
fee in (a)(i) based on canal gross tonnage.

For a Suez Canal  
or a Panama Canal Certificate

For a Suez Canal  
and a Panama Canal Certificate, if the measurements are made at  
the same time  
the  
fee in (a)(i) based on canal gross tonnage plus two-fifths of the  
appropriate fee in (b)(i).

(iii) For  
re-measurement and further certificate or certificates.

These fees cover  
the re-measurement of a ship (except under deck, for Indian  
tonnage if the measurements are made at the same time, but the

fee paid must not be less than the appropriate fee in (a) (iii).

(iv) For a copy of  
a certificate

20.00

(v) For the supply  
of details of Suez Canal or  
Panama Canal

tonnage calculations to an owner

95.00

The fees for  
measurement of tonnage under (a) and (b) cover any number of  
separate visits to the ship which the surveyor may find it  
necessary to make.

(c) For inspecting  
tonnage marks made for the purposes of rules 8A and 8B,  
irrespective of the number of visits required by the surveyor for  
inspection

120.00

Note :-The expression "tons" used in the Schedule "means gross" tons and where alternate gross tonnages are  
determined, the higher figure of gross tonnage.

Related AI tags, queries and research notes

Translation