

The Central Motor Vehicles Rules, 1989

Source: <https://indiankanoon.org/doc/28072254/>

[Skip to main content](#)

[Legal Document View](#)

[Tools for analyzing structure and cite text of judgments](#)

[Unlock Advanced Research with](#)

[PRISM](#)

[AI](#)

[Integrated with over 4 crore judgments and laws ? designed for legal practitioners, researchers, students and institutions](#)

-

[Know your Kanoon](#)

-

[Doc Gen Hub](#)

-

[Counter Argument](#)

-

[Case Predict AI](#)

-

[Talk with IK Doc](#)

-

...

[Upgrade to Premium](#)

[\[Cites](#)

[0](#)

[, Cited by](#)

[160](#)

[\]](#)

[Union of India - Act](#)

[The Central Motor Vehicles Rules, 1989](#)

[UNION OF INDIA](#)

[India](#)

[The Central Motor Vehicles Rules, 1989](#)

[Rule THE-CENTRAL-MOTOR-VEHICLES-RULES-1989 of 1989](#)

[Published on 2 June 1989](#)

[Commenced on 2 June 1989](#)

[\[This is the version of this document from 16 January 2023.\]](#)

[\[Note: The original publication document is not available and this content could not be verified.\]](#)

[\[Amended by](#)

[Central Motor Vehicles \(First Amendment\) Rules, 2023 \(Rule G-S-R-29-E- of 2023\)](#)

[on](#)

[16 January 2023](#)

[\]](#)

[The Central Motor Vehicles Rules, 1989](#)

[Published vide Notification G.S.R. 590 \(E\), dated 2.6.1989, published in the Gazette of India, Extraordinary, Part, 2, Section 3, dated 2.6.1989](#)

[196.](#)

[Chapter I](#)

[Preliminary](#)

1.

Short title and commencement.

(1)

These rules may be called The Central Motor Vehicles Rules, 1989.

(2)

[Except in so far as the provisions of these rules relate to the registration of non-commercial four wheeled petrol and diesel driven vehicles in the National Capital Region, Delhi which shall come into force on and from the 1st day of June 1999, the provisions of these rules shall come into force on and from the 1st April, 2000.]

[Substituted by Notification No. G.S.R. 399(E), dated 1.6.1999 (w.e.f. 2.6.1989).]

(3)

The provisions of [rule, 9]

[Inserted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989)]

sub-rule (3) of rule 16, sub-rule (4) of rule 96, [* * *]

[The words and figures 'sub-rule (3) of rule 103 omitted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).]

sub-rule (3) of rule 105, rule 113, sub-rules (2), (3), (4) or (5) of rule 115, rules 118, 122, 124, 125, 126 and 127 shall come into force on such date as the Central Government may, by notification in the Official Gazette, appoint.

2.

Definitions.

- In these rules, unless the context otherwise requires

(a)

"Act" means the Motor Vehicles Act, 1988 (

59 of 1988

);

(b)

["agricultural tractor" means any mechanically propelled 4-wheel vehicle designed to work with suitable implements for various field operations and/or trailers to transport agricultural materials. Agricultural tractor is a non-transport vehicle;

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(c)

"agricultural trailer" means a trailer generally left uncovered with single/double axle construction which is coupled to an agricultural tractor by means of two hooks and predominantly used for transporting agricultural materials;]

(ca)

["combine harvester" means an agricultural equipment vehicle, self propelled or agricultural tractor powered type (either coupled to the trailer for header assembly or any other attachment of the machine) designed to perform more than one of the following tasks namely:-

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(i)

picking, harvesting, threshing, separating, cleaning, chopping, collecting and unloading crop or agricultural produce, such as grain, sugarcane, cotton, fodder, straw or stalk, while moving through the standing crop or agricultural produce;

(ii)

arrangement of bagging with a pick-up attachment to use it for handling crop that has been swathed.

Explanation.-For the purpose of this clause, a combine harvester shall be a non-transport motor vehicle, the driving on the road of which is incidental to the main intended use in the fields and for traveling from one field to another, for short durations, at a speed not exceeding thirty kilometer per hour;]

[[cab]]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

"construction equipment vehicle" means rubber tyred (including pneumatic tyred), rubber padded or steel drum wheel mounted, self-propelled, excavator, loader, backhoe, compactor roller, dumper, motor grader, mobile crane, dozer, fork lift truck, self-loading concrete mixer or any other construction equipment vehicle or combination thereof designed for off-highway operations in mining, industrial undertaking, irrigation and general construction but modified and manufactured with "on or off" or "on and off" highway capabilities.

Explanation. - A construction equipment vehicle shall be a non-transport vehicle the driving on the road of which is

incidental to the main off-highway function and for a short duration at a speed not exceeding 50 kms per hour, but such vehicle does not include other purely off-highway construction equipment vehicle designed and adopted for use in any enclosed premises, factory or mine other than road network, not equipped to travel on public roads on their own power;]

(cb)

["E-rickshaw" means a special purpose battery operated vehicle having three wheels and intended to provide last mile connectivity for transport of passengers for hire or reward, provided -

[Inserted by Notification No. GSR 709 (E), dated 8.10.2014 (w.e.f. 2.6.1989)]

(i)

such vehicle is constructed or adapted to carry not more than four passengers, excluding the driver, and not more than forty kilogrammes luggage in total;

(ii)

the net power of its motor is not more than 2000 W;

(iii)

the maximum speed of the vehicle is not more than twenty-five kilometer per hour;

(cc)

"E-cart" means a special purpose battery operated vehicle having three wheels and intended to provide last mile connectivity for carrying goods for hire or reward, provided -

(i)

such vehicle is constructed or adapted for carrying goods by providing a separate load body or compartment with the maximum weight three hundred and ten kilogrammes in addition to driver;

(ii)

the net power of its motor is not more than 2000 W;

(iii)

the maximum speed of the vehicle is not more than twenty-five kilometre per hour]

(d)

["financier" means a person or a title holder-cum-dealer who lets a motor vehicle on hire under an agreement of hire purchase or lease or hypothecation to the operator with a permission to get it registered in operators name as registered owner;]

[Substituted by GSR 111(E), dated 10.2.2004, for Clause (d) (w.e.f. 10.2.2004).]

(e)

□

[Clauses (b) and (c) relettered as Clauses (e) and (f), respectively by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

Form means a Form appended to these rules;

(f)

□

[Clauses (b) and (c) relettered as Clauses (e) and (f), respectively by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

section means a section of the Act;

(g)

□

[Clauses (d) and (e) relettered as Clauses (g) and (h), respectively by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

trade certificate means a certificate issued by the registering authority under rule 35;

(h)

□

[Clauses (d) and (e) relettered as Clauses (g) and (h), respectively by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

non-transport vehicle means a motor vehicle which is not a transport vehicle;

[[i) Category L-1 means a motorcycle with maximum speed not exceeding 45 Km/h and engine capacity not exceeding 50 cc if fitted with a thermic engine or motor power not exceeding 0.5 kilo watt if fitted with electric motor;]

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

]

(j)

[Category L-2 means motorcycle other than Category L-1]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

;

(k)
[Category M means a motor vehicle with at least four wheels used for carrying passengers]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

;

(l)
[Category M-1 means a motor vehicle used for carriage of passengers, comprising not more than eight seats in addition to the drivers seat.]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

Note.- Definitions of type of body work for motor vehicles of Category M1 shall be in accordance with Annexure 1 of AIS 053:2005, as amended from time to time, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986);]

(m)
[Category M-2 means a motor vehicle used for carriage of passengers, comprising nine or more seats in addition to drivers seat and having a maximum Gross Vehicle Weight not exceeding five tonnes;]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

(n)
[Category M-3 means a motor vehicle used for carriage of passengers, comprising nine or more seats in addition to drivers seat and having a Gross Vehicle Weight exceeding five tonnes;]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

(o)
[Category N means a motor vehicle with at least four wheels used for carrying goods which may also carry persons in addition to the goods subject to the conditions specified in Para 3.2 of AIS 053-2005, as amended from time to time, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986);]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

(p)
[Category N-1 means a motor vehicle used for carriage of goods and having a Gross Vehicle Weight not exceeding 3.5 tonnes;]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

(q)
[Category N-2 means a motor vehicle used for carriage of goods and having a Gross Vehicle Weight exceeding 3.5 tonnes but not exceeding 12 tonnes;]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

(r)
[Category N-3 means a motor vehicle used for carriage of goods and having a Gross Vehicle Weight exceeding 12 tonnes;

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

Note.- For the motor vehicles, additional details and definitions specified in AIS 053-2005, as amended from time to time, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986) shall be applicable;]

(s)
[Smart Card means a device capable of storing data and executing commands which is a microprocessor chip mounted on a plastic card and the dimensions of the card and chip are specified in the International Organisation for Standardisation (ISO)/International Electro Technical Commission (IEC) 7816 specifications, as may be amended from time to time, and shall be as per the specifications specified in Annexure XI.

[Substituted by GSR 513(E), dated 10.8.2004 (w.e.f. 10.9.2004).]

Explanation. - For the purposes of this clause, microprocessor chip shall have non-volatile re-writable memory capacity of minimum [64 Kilo Byte] consisting of application data, file headers, security definitions, and a maximum of 350 bytes for Operating System Interfacing, as specified by the Ministry of Road Transport and Highways from time to time for Driving License and Registration Certificate applications;]

[Note : The microprocessor chip of smart card mentioned at para I shall conform to the specification given in the Annexure for smart card based driving license and vehicle Registration documents for transport and non-transport vehicles and shall contain the information specified under these rules.]

[Inserted by G.S.R. 540(E), dated 15.6.2010.]

(t)

[International Driving Permit means the license issued by a licensing authority in India under Chapter II of the Act to an Indian National authorising the person specified therein to drive any categories of motor vehicles as specified in Form 6-A in the areas or territories of countries other than India [that are Parties to the Convention on Road Traffic signed at Geneva on 19th day of September, 1949]

[Inserted by GSR 720(E), dated 10.9.2003 (w.e.f. 10.10.2003).]

;]

(u)

[Battery Operated Vehicle means a vehicle adapted for use upon roads and powered exclusively by an electric motor whose traction energy is supplied exclusively by traction battery installed in the vehicle:

[Inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

[Provided that a two wheeled battery operated vehicle shall not be deemed to be a motor vehicle if all the following conditions are verified and authorised by any testing agency specified in rule 126, namely:-

(a)

vehicle is equipped with an electric motor having thirty minute power less than 0.25 kW;

(b)

maximum speed of the vehicle is less than 25 km/hr;

(c)

vehicle is fitted with suitable brakes and retro-reflective devices, i.e. one white reflector in the front and one red reflector at the rear;

(d)

unladen weight (excluding battery weight) of the vehicle is not more than 60 kg;

(e)

in case of pedal assisted vehicle equipped with an auxiliary electric motor, in addition to above, the thirty minute power of the motor is less than 0.25 kW, whose output is progressively reduced and finally cut off as the vehicle reaches a speed of 25 km/hr, or sooner, if the cyclist stops pedalling.]

(v)

"Power tiller" means an agricultural machinery used for soil preparation having a single axle in which the direction of travel and its control for field operation is performed by the operator walking behind it. This equipment may or may not have a riding attachment and when coupled to a trailer can be used for the transportation of goods. The maximum speed of the power tiller when coupled to a trailer, shall not exceed 22 km/h. The maximum haulage capacity of the Power tiller coupled to a trailer shall not exceed 1.5 tons;]

(w)

[National Capital Region shall have the meaning assigned to it in clause (f) of section 2 of the National Capital Region Planning Board Act, 1985 (

2 of 1985

).]

[Inserted by GSR 37(E), dated 20.1.2009 (w.e.f. 20.1.2009).]

(x)

["modular hydraulic trailer" means a trailer module intended for carrying indivisible heavy or over dimensional cargo and having the following features, namely:-

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(i)

swing axles with hydraulic suspension;

(ii)

independently steerable axles;

(iii)

two or more axle rows;

(iv)

suitable arrangement for joining such modules longitudinally or laterally or both;

(v)

suitable provision for joining such separate modules with spacer beam arrangement or by bolster arrangement or by girder bridge arrangement or by loading deck arrangement;

(vi)

suitable drawbar arrangement for being pulled or pushed or self propelled.

Explanation. - For the purpose of this clause, the expressions,-

(i)

"spacer beam arrangement" shall mean the arrangement of rigid steel frame used for joining two separate modular hydraulic trailer units to form a single rigid chassis for movement of long cargo;

(ii)

"bolster arrangement" shall mean the arrangement of two separate units of modular hydraulic trailer mounted with turn tables and the cargo rests on the turn tables, whereby cargo structure itself acts as long member of trailer chassis;

(iii)

"girder bridge arrangement" shall mean the arrangement of two separate units of modular hydraulic trailers mounted with turn tables, and cargo is placed on a steel girder, which is then mounted on modular hydraulic trailer, whereby the steel girder acts as the long member of the trailer chassis;

(iv)

"loading deck arrangement" shall mean the arrangement of two separate units of modular hydraulic trailers mounted with turn tables, and cargo is placed on a loading deck, which is then mounted on both modular hydraulic trailers, whereby the loading deck acts as the long member of the modular hydraulic trailer chassis;

(vii)

fitted with suitable braking system.

(y)

"puller tractor" means a multi-axle haulage tractor of Category N3 vehicle having-

(i)

suitable arrangement to pull or push modular hydraulic trailer or combination thereof under drawbar arrangement;

(ii)

adequate ballast weight for providing traction;

(iii)

minimum engine power of 260 hp; and

(iv)

maximum speed not exceeding twenty five kilometre per hour while pulling load;]

Chapter II

Licensing of Drivers of Motor Vehicles

General

3.

General.

- The provisions of sub-section (1) of section 3 shall not apply to a person while or gaining experience in driving with the object of presenting himself for a test of competence to drive, so long as-

(a)

such person is the holder of an effective learners license issued to him in Form 3 to drive the vehicle;

(b)

such person is accompanied by an instructor holding an effective driving license to drive the vehicle and such instructor is sitting in such a position to control or stop the vehicle; and

(c)

there is painted, in the front and the rear of the vehicle or on a plate or card affixed to the front and the rear, the letter L in red on a white background as under:

L

Note.- The painting on the vehicle or on the plate or card shall not be less than 18 centimetres square and the letter L shall not be 10 centimetres high, 2 centimetres thick and 9 centimetres wide at the bottom:

Provided that a person, while receiving instructions or gaining experience in driving a motor cycle (with or without a side-car attached), shall not carry any other person on the motor cycle except for the purpose and in the manner referred to in clause (b).

4.

[Evidence as to the correctness of address and age.]

[Rule 4 substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

- Every applicant for the issue of a license under this Chapter shall produce as evidence of his address and age, any one or more of the following documents in original or relevant extracts thereof duly [self attested], namely:-

[* * *]

[Item No. 1 '1. Ration Card' omitted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

2. Electoral Roll,

3. Life Insurance Policy,

[* * *]

[Item No. 3-A '3-A. Janta Insurance Policy' omitted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000). Earlier it was inserted by GSR 684(E), dated 15.10.1999 (w.e.f. 22.10.1999).]

4. Passport,

[* * *]

[Item No. 5 '5. Electricity or Telephone Bill' and Item No. 7 '7. House Tax Receipt' omitted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001). Before that item Nos. 5, 6 and 7 were inserted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000).]

[* * *]

[Omitted "6. Pay slip issued by any office of the Central Government or a State Government or a local body," by Notification No. G.S.R. 684(E), dated 5.8.1999 (w.e.f. 2.6.1989)]

[* * *]

[Item No. 5 '5. Electricity or Telephone Bill' and Item No. 7 '7. House Tax Receipt' omitted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001). Before that item Nos. 5, 6 and 7 were inserted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000).]

8.

School certificate,

9.

Birth certificate,

10.

Certificate granted by a registered medical practitioner not below the rank of a Civil Surgeon, as to the age of the applicant,

11.

[Any other document or documents as may be prescribed by the State Government under clause (k) of section 28.]

[Item 11 inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

12.

[Proof of legal presence in India in addition to proof of residence in case of foreigners:]

[Inserted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

Provided that where the applicant is not able to produce any of the above-mentioned documents for sufficient reason, the licensing authority may accept any affidavit sworn by the applicant before an Executive Magistrate, or a First Class judicial magistrate or a Notary Public as evidence of age and address.]

5.

Medical certificate.

- [(1) Every application for the issue of a learners license or a driving license or for making addition of another class or description of a motor vehicle to a driving license or for renewal of a driving license to drive a vehicle other than a transport vehicle shall be accompanied by an self-declaration as to the physical fitness as in Form 1 and every such application for a license to drive a transport vehicle shall be accompanied by a medical certificate in Form 1-A issued by

a registered medical practitioner referred to in sub-section (3) of section 8.]

[Sub-Rule (1) substituted by GSR 221(E), dated 28.3.2001 (28.3.2001). Before that sub-Rule (1) substituted by GSR 684(E), dated 5.10.1999 (w.e.f. 5.10.1999).]

(2)

[An application for a medical certificate shall contain a declaration in Form 1.

(3)

A medical certificate issued in Form 1-A shall be valid for a period of one year from the date of its issue. It shall be accompanied by a passport size copy of the photograph of the applicant.]

[Inserted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

6.

Exemption from production of medical certificate.

- Any person who has, after the date of commencement of these rules, produced a medical certificate in connection with the obtaining of a learners license or a driving license, whether for initial issuance or for renewal there of, or for addition of another class of motor vehicles to his driving license, shall not be required to produce a medical certificate, except where the application is made for the renewal of a driving license.

7.

Affixing of photograph to medical certificate.

- A photograph of the applicant shall be affixed at the appropriate place shown in [Form 1-A]

[Substituted by GSR 933(E), dated 28.10.1989, for 'Form 1' (w.e.f. 28.10.1989).]

and the registered medical practitioner shall affix his signature and seal to the said photograph in such a manner that the signature and the seal appear partly on the photograph and partly on the form of the medical certificate:

[* * *]

[Proviso omitted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

8. [Minimum educational qualification for driving transport vehicles.

[Inserted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

- The minimum educational qualification in respect of an applicant for obtaining a license to drive a transport vehicle shall be a pass in the eighth standard:

Provided that the minimum educational qualification specified in this rule shall not apply in the case of

(i)

renewal of a driving license to drive a transport vehicle; or

(ii)

addition of another class of transport vehicle to the driving license, already held before the commencement of the Motor Vehicles (Amendment) Rules, 2007.]

[8-A. Minimum training required for driving E-rickshaw or E-cart. - Nothing contained in rule 8 shall apply to the applicant for obtaining a license to drive E-rickshaw or E-cart provided the applicant has undergone training at least for a period of ten days and obtained a certificate of training from the registered E-rickshaw or E-cart Association, or a manufacturer producing E-rickshaw or E-cart, as the case may be.]

[Inserted by Notification No. G.S.R. 27 (E), dated 13.1.2015 (w.e.f. 2.6.1989).]

9. [Educational qualifications for drivers of goods carriages carrying dangerous or hazardous goods]

[Rule 9 substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

.

- [(1) One year from the date of commencement of Central Motor Vehicles(Amendment) Rules, 1993, any person driving a goods carriage carrying goods of dangerous or hazardous nature to human life shall, in addition to being the holder of a driving license to drive a transport vehicle, also has the ability to read and write at least one Indian language out of those [specified in the VIII Schedule of the Constitution]

[Sub-Rule(1) substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

and English and also possess a certificate of having successfully passed a course consisting of following syllabus and periodicity connected with the transport of such goods.]

Period of training

3 days

Place of training

At any institute recognized by the State Government

Syllabus

-

A.

Defensive driving

Questionnaire

Cause of accidents

Accidents statistics

Drivers personal fitness

Car condition

Braking distance

Highway driving

Road/Pedestrian crossing

Railway crossing

Adapting to weather

B.

Advanced driving skills and training

(i) Discussion

Before starting

Check list

outside/below/near vehicle

product side

inside vehicle

During driving

correct speed/gear

signaling

lane control

overtaking/giving side

speed limit/safe distance

driving on slopes

Before stopping

Safe stopping place, signaling, road width, condition

After stopping

preventing vehicle movement

wheel clocks

vehicle attendance

[Night driving

[Substituted by G.S.R. 214(E), dated 18.3.1999 (w.e.f. 18.3.1999)]

mandatory lighting requirements

[Substituted by G.S.R. 214(E), dated 18.3.1999 (w.e.f. 18.3.1999)]

headlamp alignment

[Substituted by G.S.R. 214(E), dated 18.3.1999 (w.e.f. 18.3.1999)]

use of dipped beam]

[Substituted by G.S.R. 214(E), dated 18.3.1999 (w.e.f. 18.3.1999)]

(ii) Field test/training

1 driver at a time

C.

Product safety UN Panel

UN classification

Hazchem code

Toxicity, flammability, other definitions

Duration of training for (C) Third day.

Product information

Tremcards

CIS/MSDS

Importance of temperature pressure, level

Explosive limits

Knowledge about equipment

Emergency procedure

Communication

Spillage handling

Use of PPE

Fire fighting

First Aid

Toxic release control

Protection of wells, rivers, lakes, etc.

Use of protective equipment

Knowledge about valves, etc.

(2)

The holder of a driving license possessing the minimum educational qualification or the certificate referred to in sub-rule (1), shall make an application in writing on a plain paper along with his driving license and the relevant certificate to the licensing authority in whose jurisdiction here sides for making necessary entries in his driving license and if the driving license is in Form 7, the application shall be accompanied by the fee [as specified in the Table in rule 32]

[Substituted 'as is referred to in Serial No. 8 of the Table to rule 32' by Notification No. G.S.R. 1183(E), dated 29.12.2016 (w.e.f. 2.6.1989).]

.

(3)

The licensing authority, on receipt of the application referred to in sub-rule (2), shall make an endorsement in the driving license of the applicant to the effect that he is authorised to drive a goods carriage carrying goods of dangerous or hazardous nature to human life.

(4)

A licensing authority other than the original licensing authority making any such endorsement shall communicate the fact to the original licensing authority.

Learners license

10. Application for learners license.

- An application for the grant [* * *]

[The words 'or renewal' omitted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.1989).]

of a learners license shall be made in Form 2 and shall be accompanied by,

(a)

save as otherwise provided in rule 6, a medical certificate in [Form 1-A]

[Substituted by GSR 933(E), dated 28.10.1989, for 'Form 1' (w.e.f. 28.10.1989).]

,

(b)

three copies of the applicants recent [passport size photograph]

[Substituted by G.S.R. 933(E), dated 28.10.1989, for 'photograph of the size of five centimeters' (w.e.f. 28.10.1989).]

,

(c)

appropriate fee as specified in rule 32,

(d)

[in the case of an application for transport vehicle excluding E-rickshaw or E-cart, the driving license held by the applicant;]

[Substituted by Notification No. G.S.R. 27 (E), dated 13.1.2015 (w.e.f. 2.6.1989).]

(e)

[proof of residence,

[Inserted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

(f)

proof of age,

(g)

proof of citizenship.]

11. Preliminary test.

(1)

Save as otherwise provided in sub-rule (2), every applicant for a learners license shall present himself before the licensing authority on such date, place and time, as the licensing authority may appoint, for a test and satisfy such authority that the applicant possesses adequate knowledge and understanding of the following matters, namely:

(a)

the traffic signs, traffic signals and the rules of the road regulations made under section 118;

(b)

the duties of a driver when his vehicle is involved in an accident resulting in the death or bodily injury to a person or damage to property of a third party;

(c)

the precautions to be taken while passing an unmanned railway crossing; and

(d)

the documents he should carry with him while driving a motor vehicle.

[(1-A) In determining as to whether an applicant possesses adequate knowledge and understanding of the matters referred to in sub-rule (1), the licensing authority shall put to the applicant questions of objective type such as specified in Annexure VI.

Explanation. - For the purpose of this sub-rule, adequate knowledge means answering correctly at least 60 percent of the questions put to him.]

[Inserted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

(2)

Nothing contained in sub-rule (1) shall apply to the following class of applicants, namely:

(a)

the holder of an effective driving license,

(b)

the holder of a driving license which has expired but five years have not elapsed,

(c)

the holder of a learners license issued or renewed after the commencement of these rules,

(d)

[the holder of a certificate to the effect of the possession of adequate knowledge and understanding of the matters referred to in sub-rule (1), issued by any institution recognised and notified in this regard by the State Government.]

[Inserted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001). Earlier Clause (d) was omitted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000). Before that it was inserted by GSR 684(E), dated 5.10.1999 (w.e.f. 22.10.1999).]

12. Consent of parent or guardian, in the case of application by minor.

- In the case of an application for a learners license to drive a [motorcycle without gear]

[Substituted by GSR 76(E), dated 31.1.2000, for 'motor cycle with engine capacity not exceeding 50cc' (w.e.f. 31.1.2000). Earlier these words were substituted by GSR 684(E), dated 5.10.1999 (w.e.f. 22.10.1999).]

by an applicant under the proviso to sub-section (1) of section 4, the application shall be signed by the parent or guardian of the applicant.

13.

Form of learners license.

- Every learners license issued by the licensing authority shall be in Form 3.

Driving license

14.

Application for a driving license.

- [(1)]

[Rule 14 renumbered as sub-Rule (1) thereof by GSR 720(E), dated 10.9.2003 (w.e.f. 10.10.2003).]

An application for a driving license shall be made in Form 4 and shall be accompanied by,

(a)
an effective learners license to drive the vehicle of the type to which the application relates;

(b)
[appropriate fee as specified in rule 32, for the test, or the subsequent test, as the case may be, of competence to drive for each class and for issue of licence;]

[Substituted by Notification No. G.S.R. 1183(E), dated 29.12.2016 (w.e.f. 2.6.1989).]

(c)
three copies of the applicants recent [passport size photograph]

[Substituted by GSR 933(E), dated 28.10.1989, for 'photograph of the size of five centimetres by six centimetres' (w.e.f. 28.10.1989).]

;

(d)
save as otherwise provided in rule 6, a medical certificate in [Form 1-A]

[Substituted by GSR 933(E), dated 28.10.1989, for 'Form 1' (w.e.f. 28.10.1989).]

;

(e)
a driving certificate in Form 5 issued by the school or establishment from where the applicant received instruction, if any;

(f)
[proof of residence;

[Inserted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

(g)
proof of age;

(h)
[proof of citizenship.]]

(2)
[An application for an International Driving Permit shall be made in Form 4-A and shall be accompanied by

(a)
valid driving license issued by the licensing authority under these rules;

(b)
appropriate fee as specified in rule 32;

(c)
three copies of the applicants recent passport photograph;

(d)
a medical certificate in Form 1-A;

(e)
valid proof of Indian Nationals;

(f)
valid proof of passport; and

(g)
valid proof of visa, wherever applicable.]

15.
Driving test.

(1)
No person shall appear for the test of competence to drive unless he has held a learners license for a period of at least [thirty days]

[Substituted by GSR 933(E), dated 28.10.1989, for 'six weeks' (w.e.f. 28.10.1989).]

.

(2)

The test of competence to drive referred to in sub-section(3) of section 9 shall be conducted by the licensing authority or such other person as may be authorized in this behalf by the State Government in a vehicle of the type to which the application relates.

(3)

The applicant shall satisfy the person conducting the test that he is able to

(a)

adjust rear-view mirror;

(b)

take suitable precautions before starting the engine;

(c)

move away safely and smoothly straight ahead at an angle, while at the same time engaging all gears until the top gear is reached;

(d)

to change to the lower gears quickly from the top gear when the traffic conditions warrant such change;

(e)

change quickly to lower gears when driving downhill;

(f)

stop and re-start the vehicle on a steep upward incline making proper use of the hand-brake or of the throttle and the foot-brake without any rolling back, turn right and left corners correctly and make proper use of the rear-view mirror before signalling;

(g)

overtake, allow to be overtaken, meet or cover the path of other vehicles safely and take an appropriate course of the road with proper caution giving appropriate signals;

(h)

give appropriate traffic signals at the appropriate time, in clear and unmistakable manner by hand or by electrical indicators fitted to the vehicle;

(i)

change the lanes with proper signals and with due care;

(j)

stop the vehicle in an emergency or otherwise, and in the latter case, bring it to rest at an appropriate course on the road safely, giving appropriate signals;

(k)

in the case of vehicle having a reverse gear, driving the vehicle backwards, reverse it into a limited opening either to the right or left under control and with reasonable accuracy;

(l)

cause the vehicle to face in the opposite direction by means of forward and reverse gears;

(m)

take correct and prompt action on the signals given by traffic signs, traffic lights, traffic controllers, policemen and take appropriate action on signs given by other road users;

(n)

act correctly at pedestrian crossings, which is not regulated by traffic lights or traffic police, by giving preference to persons crossing the roads;

(o)

keep well to the left in normal driving;

(p)

regulate speed to suit varying road and traffic conditions;

(q)

demonstrate general control of the vehicle by confident steering and smooth gear changing and braking as and when necessary;

(r)

make proper use of the rear-view mirror before signalling, beginning maneuvering, moving away, altering the course to overtake, turning right or stopping;

(s)

use proper side when driving straight, turning right, turning left and at junction of the road;

(t)

make proper use of accelerator, clutch, gears, brakes (hand and foot) steering and horn;

(u)

anticipate the actions of pedestrians, drivers of other vehicles and cyclists;

(v)

take precautions at cross roads and on road junctions with regard to:

(i)

adjustment of speed on approach,

(ii)

proper use of rear-view mirror,

(iii)

correct positioning of the vehicle before and after turning to the right or left,

(iv)

avoidance of cutting right hand corners,

(v)

looking right, left and right again before crossing or emerging;

(w)

concentrate in driving without his attention being distracted and to demonstrate the presence of mind;

(x)

show courtesy and consideration for the safety and convenience of other road users, such as pedestrians, drivers of other motor vehicles or cyclists.

16.

Form of driving license.

(1)

Every driving license issued or renewed by a licensing authority shall be in Form 6.

(2)

Where the licensing authority has the necessary apparatus, [for the issue of a laminated card type or Smart Card type driving license, such card type or Smart Card type driving license, as may be specified in the Notification issued by the concerned State Government or Union Territory Administration,]

[Substituted by GSR 400(E), dated 31.5.2002, for 'for the issue of a laminated card type driving license, such card type driving license' (w.e.f. 31.5.2002).]

shall be in Form 7.

(3)

On and from the date of commencement of this sub-rule, every driving license issued or renewed by the licensing authority shall be in Form 7.

(4)

[Every International Driving Permit issued by a licensing authority shall be in Form 6-A and shall be valid for a period of not more than one year from the date of issue, as the case may be, or till the validity of the driving license, whichever is earlier.

(5)

The automobile associations authorised by the State Government/Union Territory Administration shall be allowed to issue International Driving Permit to their own members as also others subject to counter-signature by competent authority.]

[Inserted by GSR 720(E), dated 10.9.2003 (w.e.f. 10.10.2003).]

(6)

[Every driving license issued or renewed by a licensing authority to drive an E-rickshaw or E-cart shall be valid for a period of not more than three years from the date of issued, as the case may be, or till the validity of the driving license,

whichever is earlier.]

[Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

17.

Addition to driving license.

(1)

An application for addition of another class or description of motor vehicle to the driving license shall be made in Form 8 to the licensing authority and shall be accompanied by

(a)

an effective learners license and driving license held by the applicant;

(b)

[in the case of an application for transport vehicle excluding E-rickshaw or E-cart, the driving license held by the applicant;]

[Inserted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

[* * *]

[Clause (c) omitted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

(d)

appropriate fee as specified in rule 32.

(2)

The provisions of sub-section (1), sub-section (3) and sub-section (4) of section 9 shall, insofar as may be, apply in relation to an application under sub-section (1) as they apply in relation to an application for the grant of a driving license.

18.

Renewal of driving license.

(1)

An application for the renewal of a driving license shall be made in Form 9 to the licensing authority having jurisdiction over the area in which the applicant ordinarily resides or carries on business and shall be accompanied by

(a)

appropriate fee as specified in rule 32;

(b)

three copies of the applicants recent [passport size photograph]

[Substituted by GSR 933(E), dated 28.10.1989, for 'photograph of the size of five centimetres by six centimetres' (w.e.f. 28.10.1989).]

, if renewal is to be made in Form 6,

(c)

the driving license,

(d)

the medical certificate in [Form 1-A]

[Substituted by GSR 933(E), dated 28.10.1989, for 'Form 1' (w.e.f. 28.10.1989).]

.

(2)

Where the driving license authorises the holder of such license to drive a transport vehicle as well as any other vehicle, then the licensing authority shall, subject to the production of medical certificate, renew such license for the appropriate period as specified in sub-section (2) of section 14.

(3)

[Where the licensing authority renewing the driving license is not the licensing authority who issued the driving license the fact of the renewal shall be intimated to the licensing authority who issued the driving license :

Provided that in case the application is for issuance of a duplicate driving license which has been lost, torn or mutilated such that the identification or authenticity of the document cannot be reasonably established, the licensing authority receiving such application shall on confirmation from the original issuing authority, issue the duplicate driving license.

Provided also that if such confirmation is not received within 60 days, duplicate license shall be issued, without waiting for the confirmation.]

[Inserted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

19.

Refund of fee.

- Where the licensing authority rejects an application for the renewal of a driving license under sub-section (5) of section 15, it shall refund half of the fee paid for such renewal to the applicant, on an application made by him in that behalf not later than thirty days from the date of receipt of the order rejecting the application.

20.

Driving license to drive motor vehicle belonging to the Defence Department.

- The authorities for the purpose of sub-section (1) of section 18 shall be

(i)

all the officers-commanding of Units of Army of and above the rank of Major;

(ii)

all the officers-commanding of Units of Navy of and above the rank of Lieutenant Commander;

(iii)

all the officers-commanding of Units of Air Force of and above the rank of Squadron Leader.

Disqualification

21.

Powers of licensing authority to disqualify.

- For the purpose of clause (f) of sub-section (1) of section 19, the commission of the following acts by holder of a driving license shall constitute nuisance or danger to the public, namely:

(1)

Theft of motor vehicle.

(2)

Assault on passengers.

(3)

Theft of personal effects of passengers.

(4)

Theft of goods carried in goods carriages.

(5)

Transport of goods prohibited under any law.

(6)

[Driver, while driving a transport vehicle, engages himself in activity which is likely to disturb his concentration.]

[Clause (6) substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

(7)

Abduction of passengers.

(8)

Carrying overload in goods carriages.

(9)

Driving at speed exceeding the specified limit.

(10)

Carrying persons in goods carriage, either inside the drivers cabin in excess of its capacity or on the vehicle, whether for hire or not.

(11)

Failing to comply with the provisions of section 134.

(12)

Failure to stop when signalled to do so by any person authorised to do so.

(13)

Misbehaviour with and showing discourtesy to passengers, intending passengers or consignors and consignees of goods.

(14)

Smoking while driving public service vehicles.

(15)

Abandoning vehicle in a public place causing inconvenience to other road users or to passengers in the vehicle.

(16)

Driving vehicle while under the influence of drink or drugs.

(17)

Interfering with any person mounting or preparing to mount upon any other vehicle.

(18)

Allowing any person to sit or placing things in such away as to impede the driver from having a clear vision of the road or proper control of the vehicle.

(19)

Not stopping a stage carriage at approved stopping places for a sufficient period of time in a safe and convenient position upon demand or signal of the conductor or any passenger desiring to alight from the vehicle and unless there is no room in the vehicle, upon demand or signal of any person desiring to becoming a passenger.

(20)

Loitering or unduly delaying any journey and not proceeding to the destination as near as may be in accordance with the timetable pertaining to the vehicle, or, where there is no such time table, with all reasonable dispatch.

(21)

Not driving a contract carriage, in the absence of a reasonable cause, to the destination named by the hirer by the shortest route.

(22)

The driver of a motor cab not accepting the first offer of hire which may be made to him irrespective of the length of the journey for which such offer is made.

(23)

The driver of a motor cab demanding or extracting any fare in excess to that to which he is legally entitled or refusing to ply motor cab.

(24)

[Abandoning a transport vehicle as a mark of protest or agitation of any kind or strike in a public place or in any other place in a manner causing obstructions and inconvenience to the public or passengers or other users of such places.]

[Clause (24) substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

(25)

[Using mobile phone while driving a vehicle.]

[Inserted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).]

Endorsement in Driving License

22.

Endorsement by Courts.

- A Court convicting a holder of a license, for any one of the offences specified hereunder, shall endorse or cause to be endorsed in the driving license, the particulars of such conviction, namely :

(a)

Driving without a license, or without a license which is effective, or without a license applicable to the vehicle driven (section 3).

(b)

Allowing a license to be used by another person (section 6(2)).

(c)

Driving when disqualified (section 23).

(d)

Driving an unregistered vehicle (section 39).

(e)

Driving a transport vehicle not covered by a certificate of fitness (section 56).

(f)

Driving a transport vehicle in contravention of section 66.

(g)

Driving in contravention of rule 118.

(h)

Failure to comply with provisions of section 114.

(i)

Refusing or failing within specified time to produce license or certificate of registration (section 130).

(j)

Failing to stop vehicle as required under section 132.

(k)

Obtaining or applying for a license without giving particulars of endorsement (section 182).

(l)

Driving at excessive speed (section 183).

(m)

Driving dangerously (section 184).

(n)

Driving while under the influence of drink or drugs (section 185).

(o)

Driving when mentally or physically unfit to drive (section 186).

(p)

Abetment of an offence punishable under section 183 or 186.

(q)

Abetment of offence specified in section 188.

(r)

Taking part in an unauthorised race or trial of speed (section 189).

(s)

Using vehicle in unsafe condition (section 190).

(t)

Driving vehicle exceeding permissible limit or weight (section 194).

(u)

Altering a license or using an altered license.

(v)

An offence punishable with imprisonment in the commission of which a motor vehicle was used.

State Register

23.

State Register of driving licenses.

(1)

Each State Government shall maintain a State Register of driving licenses in respect of driving licenses issued and renewed by the licensing authorities in the State in Form 10.

(2)

Each State Government shall send to the Director (Transport Research), Ministry of Surface Transport, New Delhi, a printed copy of the register referred to in sub-rule (1).

Driving Schools And Establishments

24.

Driving schools and establishments.

(1)

No person shall establish or maintain any driving school or establishment for imparting instructions for hire or reward in driving motor vehicles without a license in Form 11 granted by the licensing authority.

(2)

An application for the grant or renewal of a license under sub-rule (1) shall be made in Form 12 or Form 13, as the case may be, to the licensing authority having jurisdiction in the area in which the school or establishment is situated and shall be accompanied by appropriate fee as specified in rule 32.

Explanation. - For the purposes of this rule and rules 25 to 28 licensing authority means an officer not below the rank of

the Regional Transport Officer of the Motor Vehicles Department established under section 213.

(3)

The licensing authority shall, when considering an application for the grant or renewal of a license under this rule, have regard to the following matters, namely :-

(i)

the applicant and the staff working under him are of good moral character and are qualified to give driving instructions;

(ii)

the premises where the school or establishment is proposed to be conducted is either owned by the applicant or is taken on lease by him or is hired in his name and it has adequate provision for [conducting lecture and demonstration of models]

[Substituted by GSR 933(E), dated 28.10.1989, for 'a lecture hall, room for demonstration of models, administrative section, reception room and sanitary block' (w.e.f. 28.10.1989).]

besides adequate parking area for the vehicles meant to be used for imparting instructions in driving :

Provided that in respect of schools or establishments imparting instructions in driving of motor vehicles or matters connected therewith immediately before the commencement of these rules, the licensing authority may permit the conducting of instruction facilities in the same premises where the school or establishment is housed for a period of six months, notwithstanding the fact that the premises do not satisfy the conditions laid down in this clause;

(iii)

the financial resources of the proposed school or establishment are sufficient to provide for its continued maintenance;

(iv)

the applicant owns and maintains a minimum of one motor vehicle each of the type in which instruction is imparted in the school or establishment;

(v)

the vehicles are available exclusively for purposes of imparting instruction and all such vehicles, except motor cycles, are fitted with dual control facility to enable the instructor to control or stop the vehicle;

(vi)

the applicant maintains the following apparatus, equipment and other requirements, namely:

(a)

a blackboard,

(b)

a road plan board with necessary model signals and charts,

(c)

traffic signs chart,

(d)

chart on automatic signals and signals given by traffic controllers where there are no automatic signals,

(e)

a service chart depicting a detailed view of all the components of a motor vehicle,

(f)

engine gear box, [brake shoe and drums]

[Substituted by GSR 933(E), dated 28.10.1989, for certain words (w.e.f. 28.10.1989).]

(except where the applicant desires to impart instruction in the driving of motor cycles only),

(g)

puncture kit with tyre lever, wheel brace, jack and tyre pressure gauge,

(h)

spanners (a set each of fix spanners, box spanners, pliers, screw drivers, screw spanners, and hammer),

(i)

driving instructions manual,

(j)

benches and tables for trainees and work bench,

[* * *]

[Clauses (k) and (l) omitted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

[* * *]

[Clauses (k) and (l) omitted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

(m)

a [collection]

[Substituted by G.S.R. 933(E), dated 28.10.1989, for 'library consisting' (w.e.f. 28.10.1989).]

of books on automobile mechanism, driving, road safety, traffic regulations, laws relating to motor vehicles and related subjects [* * *]

[The words 'both in English and the regional languages' omitted by G.S.R. 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

(n)

a fully equipped first-aid box for use in emergency at the premises;

[* * *]

[Clause (vii) omitted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989)]

(viii)

The applicant or any member of the staff employed by him for imparting instructions possesses the following qualifications, namely:

(a)

a minimum educational qualification of a pass in the 10th standard,

(b)

a minimum driving experience of five years in addition to a certificate in a course in motor mechanics or any other higher qualification in mechanical engineering from an institution established by the Central or a State Government or from an institution recognised by the Board of Technical Education of a State Government,

(c)

thorough knowledge of traffic signs specified in the Schedule to the Act and the regulations made under section 118,

(d)

ability to demonstrate and to explain the functions of different components, parts of the vehicles,

(e)

adequate knowledge of English or the regional language of the region in which the school or establishment is situated:

Provided that any person who has served as an instructor for a period of not less than five years immediately before the commencement of these rules, is exempted from the requirements of this sub-clause.

(4)

The licensing authority may, on receipt of an application under sub-rule (2) and after satisfying that the applicant has complied with the requirements of sub-rule (3), grant or renew a license in Form 11 [within a period of ninety days from receipt of such an application]

[Inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.10.2005).]

.

(5)

No application for license shall be refused by the licensing authority unless the applicant is given an opportunity of being heard and reasons for such refusal are given in writing by the licensing authority.

25.

Duration of a license and renewal thereof.

- A license granted in Form 11 shall be in force for a period of five years and may be renewed on an application in Form 13 made to the licensing authority which granted the license not less than sixty days before the date of its expiry:

[Provided that the validity of the said license shall be subject to fulfilling the criteria as prescribed by the State Government, which shall be certified by the licensing authority or any other authority as may be prescribed for the purpose by the State Government on an annual basis.]

[Proviso added by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

26.

Issue of duplicate license.

(1)

If at any time a license granted under sub-rule (4) of rule 24 is lost or destroyed, the holder of the license shall forth with

intimate the loss to the licensing authority which granted the license and shall apply in writing to the said authority, for a duplicate.

(2)

On receipt of an application along with the appropriate fee as specified in rule 32, the licensing authority shall issue a duplicate license clearly marked Duplicate.

(3)

If after the issue of a duplicate license, the original is found, the same shall be surrendered forthwith to the licensing authority by which it was issued.

27.

General conditions to be observed by the holder of a license.

- The holder of a license granted under rule 24 shall,

(a)

maintain on an annual basis, a register in Form 14 and an alphabetical list of the names of the students admitted during the year;

(b)

conduct the training course according to the syllabus specified in rule 31;

[* * *]

[Clause (c) omitted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

(d)

issue to every student who has completed the course a certificate in Form 5;

(e)

submit to the licensing authority which granted the license such information or return as may be called for by it from time to time for the purposes of this Chapter;

(f)

not shift the school or establishment from the premises mentioned in the license without the prior approval in writing of the licensing authority, which granted the license;

(g)

keep the premises of the school or establishment and the record and registers maintained by it at all reasonable times open for inspection by the licensing authority or by any person authorised in this behalf by the licensing authority;

(h)

exhibit in a conspicuous manner on all the motor vehicles used for imparting instructions the name, full address of the school or establishment and the telephone number, if any, in bold letters;

(i)

maintain a record separately for each trainee showing the number of driving hours spent every day in Form 15;

(j)

display at a prominent place in its office the following:

(i)

the license in original issued to the school or establishment by the licensing authority, and

(ii)

the names and addresses of instructors employed by the school or establishment;

(k)

not act in a manner calculated to mislead any person making an application to receive instructions from the school or establishment as to his ability to procure a license for such person other than in accordance with these rules or to connive with any person in acts of commission or omission with a view to circumventing the provisions of this Chapter.

28.

Power of the licensing authority to suspend or revoke license.

(1)

If the licensing authority which granted the license is satisfied, after giving the holder of the license an opportunity of being heard, that he has

(a)

failed to comply with the requirements specified in sub-rule (3) of rule 24; or

- (b)
failed to maintain the vehicles in which instructions are being imparted in good condition; or
- (c)
failed to adhere to the syllabus specified in rule 31 in imparting instruction; or
- (d)
violated any other provision of rule 27, it may, for reasons to be recorded in writing, make an order,
 - (i)
suspending the license for a specified period; or
 - (ii)
revoking the license.

(2)
Where the license is suspended or revoked under sub-rule (1), the license shall be surrendered to the licensing authority by the holder thereof.

29.

Appeal.

- Any person aggrieved by any order of the licensing authority under sub-rule (5) of rule 24, rule 25 or rule 28 may, within thirty days of the date of receipt of such order, appeal to the Head of the Motor Vehicles Department established under section 213.

30.

Procedure for appeal.

(1)

An appeal under rule 29 shall be preferred in duplicate in the form of a memorandum, setting forth the grounds of objections to the order of the licensing authority and shall be accompanied by a certified copy of the order appealed against and appropriate fee as specified in rule 32.

(2)

The appellate authority, after giving an opportunity to the parties to be heard and after such further enquiry, if any, as it may deem necessary, pass appropriate orders [within a period of forty five days from the date of receipt of such an appeal]

[Inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.10.2005).]

.

31.

Syllabus for imparting instructions in driving of motor vehicles.

(1)

The syllabus for imparting instructions in driving of motor vehicles of the schools or establishments shall be as follows (see tables below):

A. Driving Theory-I

1.

Know your vehicle

Simple introduction to automobile engines and their working.

2.

Vehicle control

Foot controls

Foot brake, accelerator, clutch-dipper (not in present models)

Hand controls

Steering wheel, hand brake, horn, light, wipers, ignition switch, starter, dipper and indicators

Other controls

Rear-view mirror (right and left side), instrument cluster, gauges, dials, windscreen-their purpose

3.

Pre-driving checks

(i) Before sitting on driver's seat and

(ii) After sitting on driver's seat.

4.

Beginning to drive

Precautions just before moving,

While moving Bitting point,

Moving, Steering control, Changing of gear, Stopping, Braking, Accelerator
(gradual, sudden)

Traffic sense, road sense, judgment, parking and positioning according to road users, Reversing.

5.

Driving on the road

Anticipation, judgment and road positioning according to other road users.

6.

Driving at inter-sections

Mirror Signal and Manoeuvre (MSM) and Position Speed and Look (PSL)

7.

Manoeuvres

Merging and diverging manoeuvres-turning manoeuvres to left, right, about, 3-point turn, 5-point turn and U-turn,
overtaking stationary vehicle, moving vehicle in left side and right side

8.

Reversing

Locating reverse gear in sitting position, speed control, steering in reverse gear, weaving the 'S' bend and common errors.

9.

Parking

Parallel, angular, perpendicular, parking facing uphill, parking facing downhill, common errors.

10.

Driver's responsibility on the road

Driving behaviour, consideration for other road-users, courtesy and competitiveness, over-confidence, impatience and defensive driving.

Distance between cars while driving at Railway crossing.

11.

Priority for certain vehicles

Emergency vehicles Fire engines, and Ambulance

B. Traffic Education-I

1.

Driving regulations

Road use regulations made under section 118 of the Motor Vehicles Act, 1988

2.

Hand signals

3.

Traffic signals

Schedule to the Motor Vehicles Act, 1988

4.

Hand signals of Traffic constables/Traffic warden

5.

Introduction to automatic light signals

6.

Introduction to road markings

7.

Speed regulations on highways and city roads

8.

Parking at objectionable places

9.

Some important provisions of the Motor Vehicles Act, 1988

- Sections 122, 123, 125, 126 and 128 of the Motor Vehicles Act, 1988.

10.

Test of competence to drive

Sub-rule (3) of rule 15 of the Central Motor Vehicles Rules, 1989

C. Light Vehicles Driving Practice

1.

Identification of various parts of the vehicles

2.

Pre-driving checks

(i) Before sitting on driver's seat, and

(ii) After sitting on driver's seat.

3.

Steering practice

Push and pull method

4.

Braking point

5.

Moving and gear changing

6.

Stopping

Normal stopping

Emergency stopping

7.

Developing judgment and anticipation to drive on road

8.

Reversing

In straight

In 'S' bends.

9.

Turning about and parking

10.

Licensing

D. Vehicle Mechanism And Repairs

1.

Layout of vehicle

2.

Function of diesel and petrol engines

3.

Fuel system

Fuel lines

Fuel injection pump

Automiser

Air lock

Oil block

4.

Cooling system

Purpose

Radiator

Water pump

Fan leaf/fan belt

Radiator water boiling

Rectification

5.

Lubrication system

Purpose

Engine lubrication

Chassis lubrication

Oil grade number unit wise.

6.

Transmission system

(a)Clutch:

Function

Slip

Rising

Linkages

(b)Gear box:

Function

Purpose

Parts

(c)Propeller shaft:

Function/purpose

Yoke joint

C.J.bearing slip

"U" joint

Lubrication

(d)Differential:

Purpose

Function/Noise.

7.

Suspension system

Purpose

Springs

Shackle, shackle pin bushes

Shock absorber and its bushes.

8.

Steering system

Purpose

Steering geometry

Steering linkages

Steering box

9.

Brake system

Purpose

Hydraulic brake and its know-how

Air assisted hydraulic brake and its know-how

Air brake and its know-how

Brake adjustment of the entire system

10.

Electrical system

Battery and its condition

Dynamo/Alternator

Self-motor-Starter motor regulators

Lights-Knowledge to read the charging rate in the Ampere meter.

11.

Tyres

Study of tyres

Maintenance

Effect of defective tyres and wheel alignment.

12.

Instruments cluster, dash board meters and their purposes and functions.

E. Medium And Heavy Vehicle Driving:

Driving Theory-II

1.

Qualities of a good driver

Patience, responsibility, self-confidence, anticipation, concentration, courtesy, defensive driving, knowledge of road rules/regulations, knowledge of vehicle controls, maintenance and simple mechanism.

2.

Knowledge of vehicle controls

Major controls

Minor controls

3.

Response to controls

Accelerator

Brake-Gradual/Sudden/Sudden fierce

Clutch

Steering

4.

Pre-driving checks

(i)Before sitting on driver's seat, and

(ii)After sitting on driver's seat.

5.

Holding steering wheel

Push and pull method practice

On the move

While gear changing

While turning

While sounding horn

While operating dash board switches

While signaling

On emergency

6.

Gear changing

Double de-clutching, importance and procedure single clutching.

Gear up procedure, shifting to lower gears

Gear down procedure, shifting to higher gears.

7.

Beginning to drive

I gear

II gear

III gear

IV gear

V gear
Reverse gear
Over drive/optional.
8.
M.S.M and P.S.L Routines
9.
Manoeuvres
Passing
Merging
Diverging
Overtaking
Crossing
Turning
Cornering
Reversing
Parking
10.
Stopping
Normal stopping
Emergency stopping
Use of engine brake/exhaust brake.
11.
Stopping distance
Reaction distance
Braking distance
12.
Following distance
Meaning
Distance method
Car length method
2 seconds time rule method
13.
Identification, prediction, decision and execution (IPDE) principle
14.
Defensive driving techniques
Judgment
Anticipation
Escape route
15.
Night driving
Location of head light switch
Procedure
Obligation to light the lamps, restriction on lighting the lamps.
16.
Hill driving
Starting in hill using the parking brake method
Slipping the clutch method
Driving uphill
Driving downhill.
17.
Emergency manoeuvres

Prevention is better than cure in case of skidding, horn struck

Fire, wheels coming out

Brake failure

Broken stub axle

Burst of front tyre

Steering wobbling

Snapping of steering linkages

Jamming of accelerator pedal

Snapping of clutch rod

Under special circumstances like chances of collision with a disabled vehicle

Brake failure during downhill

Sudden obstruction in front of the vehicle

18.

Driving under special conditions

In wet weather

In dawn, dusk and misty roads

In dense traffic.

19.

Towing (trailer driving)

Procedure

On tow board

Speed of towing

Reversing and positioning the vehicle with trailers.

20.

Fuel saving methods

21.

Reports-Discussions.

F. Traffic Education-II

1.

Know your road

Functional classification

Design speeds

Road geometrics

Surface types and characteristics

Slopes and elevation

2.

Sight distance

At bends

At intersections.

3.

Road junctions

Principles and types

T junctions

Y junctions

4-Arm junctions

Staggered junctions

Controlled junctions

Uncontrolled junctions

4.

Traffic islands

Types of roundabouts

Channelisers, median

5.

Bye-pass, subway, over-bridge and fly-overs

Driving procedures.

6.

Bus stop, bus terminus, bus stand

Ingress

Egress

Method

7.

Road markings

White line: continuous and broken

Yellow line

Land marking

Zebra crossing

Stop line

Parking markings

Sense of road signals.

8.

Lane selection and lane discipline

9.

Automatic light signals

10.

Road users characteristics

Pedestrian, drunkards, children and blind, deaf and dumb

Youth, aged women with children

Slow-moving vehicles

Mopeds and motor cycles

Autos, tempos, vans

Buses and trucks

VIP, ambulance, fire engine

Animals.

11.

Accidents

Types of accidents

Causes of accidents

Preventive methods

Driver's duties and responsibilities on the occurrence of accident.

12.

Important provisions in Motor Vehicles Act, 1988 (

59 of 1988

), Central Motor Vehicles Rules, 1989, and the State Motor Vehicles Rules

Certain definitions

Driving license and its renewal

Carrying driving license, certificates of registration, fitness and insurance, permit taxation card or tax token and production of such document on demand by checking officers.

Traffic offences and penalties stipulated under the Act and Rules

Relevant Extracts of Petroleum Act, 1934

City Police Act

Indian Penal Code, 1860

.

G. Public Relations For Drivers

Some basic aspects about ethical and courteous behaviour with other road users

H. Heavy Vehicle Driving Practice

1.

Introduction of various instruments

Dial gauges and controls.

2.

Pre-driving checks

(i) Before sitting on driver's seat, and

(ii) After sitting on driver's seat.

3.

Beginning to drive

Bitting point, moving, changing gear including double de-clutch steering, stopping, hand signals.

4.

Rural road driving

Application of IBDE-principle

5.

Development of judgment

Passing, overtaking, merging, diverging, M.S.M and P.S.L. routine method of practice, defensive driving technique, proper following.

6.

Development of anticipation

Turning, meeting, entering and emerging in junctions, lane selection and lane discipline, intersection, observation.

7.

Developing skill to drive in crowded streets

8.

Night driving

9.

Cross country practice and hill driving

10.

Internal-trade test.

11.

Reversing and parking practice

12.

Licensing

I. Fire Hazards

Fire-fighting and prevention methods on vehicle

J. Vehicle Maintenance

1.

Factors affecting the vehicle parts due to bad and negligent driving

2.

General day-to-day maintenance and periodical maintenance.

3.

Battery maintenance

4.

Tyre maintenance and tube vulcanizing

5.

Engine tune up

6.

Checking wheel alignment

7.

Brake adjustment

8.

Accelerator, brake, clutch-pedal adjustment

9.

Fan belt adjustments.

10.

Observation of dash-board meters.

11.

Lubrication.

12.

Removal of air lock and oil block.

K. First-Aid

1.

Introduction to first-aid

2.

Outline of first-aid

3.

Structure and functions of the body.

4.

Dressings and bandages

5.

The circulation of the blood.

6.

Wounds and haemorrhage

7.

Haemorrhage from special regions.

8.

Shock.

9.

Respiration

10.

Injuries to bones

11.

Burning scales

12.

Unconsciousness (insensibility)

13.

Poisons

(2)

[The lessons for training drivers of non-transport vehicles shall cover Parts A, B, C, F, G and K of the syllabus referred to in sub-rule (1) and the training period shall not be less than twenty-one days:

Provided that in case of motor cycles, it shall be sufficient compliance with the provisions, if portion of Part C of syllabus as applicable to such vehicles are covered.

(3)

The lessons for training drivers of transport vehicles shall cover Parts E, F, G, H, I, J and K of the syllabus referred to in sub-rule (1) and the training period shall not be less than thirty days:

Provided that this sub-rule shall not apply in respect of drivers holding driving license to drive medium goods vehicle or medium passenger motor vehicle who had undergone the lessons after the commencement of this rule, and desiring to obtain a driving license to drive heavy goods vehicle or heavy passenger motor vehicle.

(4)

The actual driving hours for trainees in driving non-transport vehicles shall not be less than ten hours and actual driving

hours for trainees in driving transport vehicles shall not be less than fifteen hours:

Provided that in the case of drivers holding driving license to drive medium goods vehicle or medium passenger motor vehicles undergoing training for heavy motor vehicles, it shall be sufficient if they undergo training in driving for a period of not less than five hours.

(5)

[Nothing in this rule shall apply in the case of an applicant whose driving license authorises him to drive a motor cycle or a three-wheeler non-transport vehicle or a motor car, applying for a license to drive a motor cab of the respective type, or in the case of an applicant holding a driving license to drive a tractor, applying for a license to drive a tractor-trailer combination.]

[Substituted by G.S.R. 933(E), dated 28.10.1989, for sub-Rules (2), (3) and (4) (w.e.f. 28.10.1989)]

(6)

Where any trainee possesses first-aid certificate issued by St. John Ambulance Association, he need not undergo Part K of the syllabus referred to in sub-rule (1).]

[Inserted by GSR 720(E), dated 10.9.2003 (w.e.f. 10.10.2003).]

[31A. Temporary license. - (1) Where there is no school or establishment as is referred to in sub-section (4) of section 12 or granted a license under sub-rule (4) of rule 24, in any Taluk within the jurisdiction of the licensing authority, the licensing authority may, notwithstanding anything contained in sub-rules (3) and (4) of rule 24 or rule 25, grant a temporary license to any establishment or any person for imparting instructions in the driving of a transport vehicle, subject to the following conditions, namely:

(a)

the temporary license shall be valid for a period of one year from the date of its issue:

Provided that as long as the Taluk does not have any school or establishment, the licensing authority may renew a temporary license granted under this sub-rule for a further period not exceeding one year at a time;

(b)

the person imparting instructions in the driving of a transport vehicle shall possess the following qualifications, namely :

(i)

a minimum driving experience of five years in the class of vehicles in which instructions are proposed to be imparted;

(ii)

adequate knowledge of the regional language of the region in which the school or establishment is situated;

(iii)

thorough knowledge of traffic signs specified in the Schedule to the Act and the Regulations made under section 118;

(iv)

ability to demonstrate and explain the functions of different components and parts of a vehicle;

(c)

the applicant shall maintain a motor vehicle each of the type in which the instruction is imparted and also the following apparatus, namely:

(i)

a blackboard;

(ii)

traffic sign chart;

(iii)

a service chart depicting a detailed view of all the components of a motor vehicle;

(iv)

puncture kit with tyre lever, wheel brace, jack;

(v)

spanners (a set each of fixed spanners, box spanners, screw driver, screw spanners and hammer).

(2)

The driving schools run by a State Transport Undertaking or an Industrial Training Institute set up by the Central Government or any State Government and other establishments run by the Central Government or a State Government which have facilities for imparting training for drivers, shall be authorised to issue driving certificates in Form 5, subject to the condition that the training imparted in these schools shall be in accordance with the syllabus referred to in rule 31.]

[Inserted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

[32. Fees. - The fees which shall be charged under the provisions of this Chapter shall be as specified in the table below:

Provided that the States may levy [fee lower than the amount specified in the table and may also levy]

[Substituted by Notification No. G.S.R. 1183(E), dated 29.12.2016 (w.e.f. 2.6.1989).]

additional amounts to cover the cost of automation and technology utilised for conducting the testing or providing value added services.

Table

Sl. No.

Purpose

Amount

Rule

Section

(1)

(2)

(3)

(4)

(5)

1.

Issue of learner's licence in Form 3 for each class of vehicle

One hundred and fifty rupees

10

8

2.

Learner's licence test fee or repeat test fee, as the case may

be

Fifty rupees

27(q)

3.

For test, or repeat test, as the case may be, of competence to

drive (for each class of vehicle)

Three hundred rupees

14 (1)(b)

9

4.

Issue of a driving licence Two hundred rupees 14 (1)(b) 9

5.

Issue of International Driving Permit One thousand rupees

14(2)(b) 9

6.

Addition of another class of vehicle to driving licence

Five hundred rupees

17(1)(d)

11

7.

Endorsement or renewal of authorisation for vehicle carrying

hazardous goods

One hundred rupees

9

27(q)

8.

Renewal of driving licence

Two hundred rupees

18(1)(a)

15

9.

Renewal of a driving licence for which application is made

after the grace period

Three hundred rupees.

Note.:- Additional fee at the rate of one

thousand rupees for delay of each year or part thereof reckoned

from the date of expiry of the grace period shall be levied.

15

10.

Issue or renewal of licence to a school or establishment for

imparting instructions in driving

Ten thousand rupees

24(2)

12

11.

Issue of duplicate licence to a school or establishment for

imparting instructions in driving

Five thousand rupees

26(2)

12

12.

An appeal against the orders of licensing authority referred

to in rule 29

Five hundred rupees

30(1)

17

13.

Any application for change in address or any other particulars

recorded in the driving licence e.g. address etc.

Two hundred rupees

27(q)

Note. 1. Where a Smartcard Type driving licence is issued in Form 7, an additional fee of two hundred rupees shall be levied.

2. The fees specified at serial numbers 1, 2 and 3 of the Table above shall be paid collectively at the time of submission of application for issue of learner's licence or driving licence or for endorsement of another class of vehicle, as the case may be.]

32. Fees.- The fees which shall be charged under the provisions of this Chapter shall be as specified in the Table below:
[Table]

[Substituted by G.S.R. 221(E), dated 28.3.2001 (w.e.f. 28.3.2001). Earlier the Table was substituted by G.S.R 76(E), dated 31.1.2000 (w.e.f. 31.1.2000). Before that the Table was substituted by G.S.R. 684(E), dated 5.10.1999 (w.e.f. 22.10.1999).]

{|

Serial No.

Purpose

Amount

Rule

Section

- (1)
- (2)
- (3)
- (4)
- (5)

1.

In respect of issue[***]

[The words 'or renewal' omitted by G.S.R. 276 (E), dated 10-4-2007 (w.e.f. 10-4-2007)]
of learner's license for each class of vehicle

Thirty rupees

10

8

2.

In respect of issue of a driving license in Form 6

Forty rupees

14(b)

9

[2-A.

[Inserted by G.S.R. 720(E), dated 10.9.2003 (w.e.f. 10.10.2003)]

In respect of issue of International Driving Permit in Form 6-A

[Inserted by G.S.R. 720(E), dated 10.9.2003 (w.e.f. 10.10.2003)]

Five hundred rupees

[Inserted by G.S.R. 720(E), dated 10.9.2003 (w.e.f. 10.10.2003)]

14(2)(b)

[Inserted by G.S.R. 720(E), dated 10.9.2003 (w.e.f. 10.10.2003)]

9]

[Inserted by G.S.R. 720(E), dated 10.9.2003 (w.e.f. 10.10.2003)]

3.

In respect of issue of driving license in Form 7.

[Two hundred rupees]

[Substituted by G.S.R. 400(E), dated 31.5.2002, for 'One hundred and fifty rupees; (w.e.f. 31.5.2002)]
including the cost of computerized chip

14(b)

9

4.

For test of competence to drive

Fifty rupees

14(b)

9

5.

In respect of addition of another class of vehicle to driving license in Form 6

Thirty rupees

17(1)(d)

11

6.

In respect of renewal of driving license in Form 6.

[Fifty rupees]

[Substituted by G.S.R. 400(E), dated 31.5.2002, for 'Thirty rupees' (w.e.f. 31.5.2002)]

18(1)(a)

15

7.

In respect of renewal of a driving license in Form 6 to drive a motor vehicle for which application is made after the grace period

[Hundred rupees and an additional fee at the rate of fifty rupees for a period of delay of one year or part thereof reckoned from the date of expiry of the grace period]

[Substituted by G.S.R. 720(E) dated 10.9.2003, for 'Thirty rupees' (w.e.f. 10.10.2003).]

15

8. [

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

In respect of addition of another class of motor vehicle to the driving license in Form 7

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

Two hundred rupees including the cost of computerised chip

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

17(1)(d)

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

11

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

8-A

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

In respect of renewal of driving license in Form 7

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

Two hundred fifty rupees including the cost of Smart Card

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

18(1)(d)

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

11

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

8-B.

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

In respect of renewal of driving license in Form 7 for which application is made after the grace period.

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

Two hundred rupees including the cost of computerised chip and additional fee at the rate of fifty rupees for a period of delay of one year or part thereof reckoned from the date of expiry of the grace period

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

18(1)(d)

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

15]

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007)]

9.

In respect of issue and renewal of license to a school or establishment for imparting instructions in driving

Two thousand and five hundred rupees

24(2)

12

10.

In respect of issue of duplicate license to the school or establishment imparting instructions in driving

Two thousand and five hundred rupees

26(2)

12

11.

In respect of an appeal against the orders of licensing authority referred to in rule 30.

One hundred rupees

30(1)

17]

l}

Chapter III

Registration of Motor Vehicles

Trade certificate

33.

Condition for exemption from registration.

- For the purpose of the proviso to section 39, a motor vehicle in the possession of a [dealer or manufacturer of automobiles or automobile ancillaries or a test agency specified in rule 126]

[Substituted by Notification No. 291 (E) dated 24.4.2014]

shall be exempted from the necessity of registration subject to the condition that he obtains a trade certificate from the registering authority having jurisdiction in the area in which the [dealer or manufacturer of automobiles or automobile ancillaries or a test agency specified in rule 126]

[Substituted by Notification No. 291 (E) dated 24.4.2014]

has his place of business in accordance with the provisions of this Chapter.

34.

Trade certificate.

(1)

An application for the grant or renewal of a trade certificate shall be made in Form 16 and shall be accompanied by the appropriate fee as specified in rule 81.

(2)

Separate application shall be made for each of the following classes of vehicles, namely:

(a)

motor cycle;

(b)

invalid carriage;

(c)

light motor vehicle;

(d)

medium passenger motor vehicle;

(e)

medium goods vehicle;

(f)

heavy passenger motor vehicle;

(g)

heavy goods vehicle;

(h)

[E-rickshaw;

[Inserted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

(i)

E-cart;

(j)

any other motor vehicle of a specified description.]

35.

Grant or renewal of trade certificate.

(1)

On receipt of an application for the grant or renewal of a trade certificate in respect of a vehicle, the registering authority may, if satisfied that the applicant is a bona fide [dealer or manufacturer of automobile or automobiles ancillary or a test agency specified in rule 126]

[Substituted by Notification No. 291 (E) dated 24.4.2014]

and requires the certificates specified in the application, issue to the applicant one or more certificates, as the case may

be, in Form 17 [within thirty days from the date of receipt of such an application]

[Inserted by G.S.R. 589(E), dated 16.9.2005 (w.e.f. 16.10.2005)]

and shall assign in respect of each certificate a trade registration mark consisting of the registration mark referred to in the notification made under sub-section (6) of section 41 and followed by two letters and a number containing not more than three digits for each vehicle, for example:

AB Represent State Code.

12Registration.

District Code.

TC1Trade certificate number for the vehicle.

(2)

No application for trade certificate shall be refused by the registering authority unless the applicant is given an opportunity of being heard and reasons for such refusal are given in writing.

36.

Refund.

- Where the registering authority refuses to issue or renew a trade certificate, it shall refund to the applicant fifty per cent of the fee paid along with the application.

37.

Period of validity.

- A trade certificate granted or renewed under rule 35 shall be in force for a period of twelve months from the date of issue or renewal thereof and shall be effective throughout India.

38.

Issue of duplicate certificate.

(1)

If at any time the trade certificate is lost or destroyed, its holder shall report to the police station in the jurisdiction of which the loss or destruction has occurred and intimate the fact in writing to the registering authority by whom the certificate was issued and apply in Form 18 to the said authority for a duplicate certificate accompanied by the appropriate fee as specified in rule 81.

(2)

On receipt of an application along with the fee, the registering authority may issue a duplicate Trade Certificate clearly marked Duplicate.

(3)

If after the issue of a duplicate certificate the original is traced, the same shall be surrendered forthwith to the registering authority by which it was issued.

39.

Use of trade registration mark and number.

(1)

A trade registration mark and number shall not be used upon more than one vehicle at a time or upon any vehicle other than a vehicle bona fide in the possession of the [dealer or manufacturer of automobile or automobile ancillaries or a test agency specified in rules 126]

[Substituted by Notification No. 291 (E) dated 24.4.2014]

in the course of his business or on any type of vehicle other than the one for which the trade certificate is issued.

(2)

The trade certificate shall be carried on a motor vehicle in a weather-proof circular folder and the trade registration mark shall be exhibited in a conspicuous place in the vehicle.

40.

Restrictions on use of trade certificate or trade registration mark and number.

- A trade certificate shall be used only by the person to whom it is issued and such person shall not allow or offer or cause the certificate or the number assigned in connection therewith to be used by any other person:

Provided that the provision of this rule shall not apply where the person to whom the certificate is granted, or a person bona fide in his employment and acting under his authority, or any other person bona fide acting on behalf of the holder of a trade certificate is present in the vehicle, or if such vehicle is designed for use by only one person and is being used

by a prospective purchaser of that vehicle for the purpose of reasonable test or trial.

41.

Purposes for which motor vehicle with trade certificate may be used.

- The holder of a trade certificate shall not use any vehicle in a public place under that certificate for any purpose other than the following:

(a)

for test, by or on behalf of the holder of a trade certificate during the course of, or after completion of, construction or repair; or

(b)

for proceeding to or returning from a weigh bridge for or after weighment, or to and from any place for its registration; or

(c)

for a reasonable trial or demonstration by or for the benefit of a prospective purchaser and for proceeding to or returning from the place where such person intends to keep it; or

(d)

for proceeding to or returning from the premises of the dealer or of the purchaser or of any other dealer for the purpose of delivery; or

(e)

for proceeding to or returning from a workshop with the objective of fitting a body to the vehicle or painting or for repairs; or

(f)

for proceeding to and returning from airport, railway station, wharf for or after being transported; or

(g)

for proceeding to or returning from an exhibition of motor vehicles or any place at which the vehicle is to be or has been offered for sale; or

(h)

for removing the vehicle after it has been taken possession of by or on behalf of the financier due to any default on the part of the other party under the provisions of an agreement of hire-purchase, lease or hypothecation.

42.

Delivery of vehicle subject to registration.

- No holder of a trade certificate shall deliver a motor vehicle to a purchaser without registration, whether temporary or permanent.

43.

Register of trade certificate.

(1)

Every holder of a trade certificate shall maintain a register in Form 19 in duplicate which shall be in a bound book, with pages numbered serially.

(2)

The particulars referred to in Form 19 except the time of return under column 7, shall be entered in the register before the commencement of each trip by the holder of the trade certificate or his representative and a duplicate copy of Form 19 made prior to the commencement of each trip shall be carried during the trip by the driver of the vehicle and shall be produced on demand by any officer empowered to demand production of documents by or under the Act.

(3)

The holder of a trade certificate shall, at the end of a trip, fill in column 7 of Form 19 (both original and duplicate), and the register and the duplicate shall be open for inspection by the registering authority.

44.

Suspension or cancellation of trade certificate.

- If the registering authority has reason to believe that the holder of any trade certificate has not complied with the provisions of rules 39 to 43, it may, after giving the holder an opportunity of being heard, suspend or cancel the trade certificate held by him.

45.

Appeal.

- Any person aggrieved by an order of the registering authority under rule 35 or rule 44 may, within thirty days of the receipt of any such order, appeal to the head of the Motor Vehicles Department established under section 213.

46.

Procedure for appeal.

(1)

The appeal referred to in rule 45 shall be preferred in duplicate in the form of a memorandum, setting forth the grounds of objections to the order of the registering authority and shall be accompanied by appropriate fee as specified in rule 81 and a certified copy of the order appealed against.

(2)

The appellate authority, after giving an opportunity to the parties to be heard and after such enquiry, if any, as it deems necessary, pass appropriate orders [within the period of thirty days from the date of receipt of such an appeal]

[Inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.10.2005).]

.

Registration

47.

Application for registration of motor vehicles.

(1)

An application for registration of a motor vehicle shall be made in Form 20 to the registering authority within a period of [seven days]

[Substituted by GSR 933(E), dated 28.10.1989, for 'two days'(w.e.f. 28.10.1989).]

from the date of taking delivery of such vehicle, excluding the period of journey and shall be accompanied by

(a)

sale certificate in Form 21;

(b)

valid insurance certificate;

(c)

[copy of the proceedings of the State Transport Authority or Transport Commissioner or such other authorities as may be prescribed by the State Government for the purpose of approval of the design in the case of a trailer or a semi-trailer]

[Clause (c) substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(d)

original sale certificate from the concerned authorities in Form 21 in the case of ex-army vehicles;

(e)

proof of address by way of any one of the documents referred to in rule 4;

(f)

temporary registration, if any;

(g)

road-worthiness certificate in Form 22 from the manufacturers, [Form 22-A from the body builders]

[Added by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

;

(h)

[customs clearance certificate in the case of imported vehicles along with the license and bond, if any:

[Clause (h) substituted by GSR 83(E), dated 5.2.2003 (w.e.f. 5.2.2003).]

Provided that in the case of imported vehicles other than those imported under the Baggage Rules,1998, the procedure followed by the registering authority shall be same as those procedure followed for registering of vehicles manufactured in India; and]

(i)

appropriate fee as specified in rule 81;

(j)

[proof of citizenship;

[Inserted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

(k)

proof of legal presence in India in addition to proof of residence in case of foreigners.]

(l)

[technical specifications and any other document as may be required by the registering authority in respect of the modular hydraulic trailer.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

[Provided that upto 31st December, 2016, on and from the date of publication of the Central Motor Vehicles (Amendment) Rules, 2015 published on 13th January, 2015, in respect of the models of the E-rickshaws and E-carts existing prior to publication of the Central Motor Vehicles (Sixteenth Amendment) Rules, 2014 and the notification published vide S.O. 2590(E) dated the 8th October, 2014, the application for registration under this sub-rule shall be made in Form 20 to the registering authority within a period of seven days from the date of issue of Form-21 and Form-22 and shall be accompanied by -

(i)

road worthiness certificate in Form-22 to be issued by the manufacturer or dealer or registered E-rickshaw or E-cart Association or any agency authorised by State Government; and

(ii)

sale certificate in Form 21 to be issued by manufacturer or dealer or registered E-rickshaw or E-cart Association or any agency authorised by State Government for presentation along with the application for registration.]

(2)

In respect of vehicles temporarily registered,application under sub-rule (1) shall be made before the temporary registration expires.

[[(4) The modular hydraulic trailers registered under these rules]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall ply in public place in laden condition subject to such other conditions as may be determined by the Central Government from time to time.]

[Substituted by Notification No. G.S.R. 903 (E) dated 23.9.2016 (w.e.f. 2.6.1989)]

(5)

[All types of trailers and semitrailers covered under rule 125D, shall be registered independently.

Provided that, if the owner or registering party, requests to register the trailer or semitrailer jointly with compatible towing vehicle as a single vehicle, the registering authority shall register them as a single vehicle.]

[Inserted by Notification No. G.S.R. 1482(E), dated 7.12.2017 (w.e.f. 2.6.1989).]

48.

Issue of certificate of registration.

- On receipt of an application under rule 47 and after verification of the documents furnished therewith, the registering authority shall, subject to the provisions of section 44, issue to the owner of the motor vehicle a [certificate of registration in Form 23 or Form 23-A, as may be specified in the Notification issued by the concerned State Government or Union Territory Administration]

[Substituted by GSR 400(E), dated 31.5.2002, for 'certificate of registration in Form 23'(w.e.f. 31.5.2002).]

[within the period of thirty days from the receipt of such an application]

[Added by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

:

[Provided that where the certificate of registration pertains to a transport vehicle it shall be handed over to the registered owner only after recording the certificate of fitness in Form 38 [within the period of thirty days from the date of receipt of such an application]

[Added by G.S.R. 338(E), dated 26-3-1993 (w.e.f. 26-3-1993).]

.]

49.

Registration records to be kept by the registering authority.

- Every registering authority shall keep in Form 24 a permanent register of motor vehicles registered by it under section 41 and of motor vehicles of other States for which new registration marks are assigned by it under sub-section (2) of section 47 and shall also enter in such record under the respective registration numbers, all changes made with reference to the provisions of sub-section (10) or sub-section (14) of section 41,sub-section (5) of section 49,

sub-section (6) of section 50, sub-sections (1),(2),(3) and (5) of section 51, sub-section (4) of section 52, orders of suspension under section 53 and order of cancellation under sections 54 and 55.

50.

[Form and manner of display of registration marks on the motor vehicles]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

- [(1) On or after commencement of this rule, the registration mark referred to in sub-section (6) of section 41 shall be displayed both at the front and at the rear of all motor vehicles clearly and legibly in the form of security license plate of the following specifications, namely:

(i)

the plate shall be a solid unit made of 1.0mm aluminium conforming to DIN 1745/DIN 1783 or ISO 7591. Border edges and corners of the plate shall be rounded to avoid injuries to the extent of approx. 10 mm and the plates must have an embossed border. The plate shall be suitable for hot stamping and reflective sheet has to be guaranteed for imperishable nature for minimum five years. The fast colouring of legend and border to be done by hot stamping;

(ii)

the plate should bear the letters IND in blue colour on the extreme left center of the plate. The letter should be one-fourth of the size of letters mentioned in rule 51 and should be buried into the foil or applied by hot stamping and should be integral part of the plate;

(iii)

each plate shall be protected against counterfeiting by applying chromium-based hologram, applied by hot stamping. Stickers and adhesive labels are not permitted. The plate shall bear a permanent consecutive identification number of minimum seven digits, to be laser branded into the reflective sheeting and hot stamping film shall bear a verification inscription;

(iv)

apart from the registration marks on the front and rear, the third registration mark in the form of self-destructive type, chromium based hologram sticker shall be affixed on the left-hand topside of the windshield of the vehicle. The registration details such as registration number, registering authority, etc., shall be printed on the sticker. The third registration mark shall be issued by the registering authorities/approved dealers of the license plates manufacturer along with the regular registration marks, and thereafter if such sticker is destroyed it shall be issued by the license plate manufacturer or his dealer;

(v)

the plate shall be fastened with non-removable/non-reusable snap lock fitting system on rear of the vehicle at the premises of the registering authority;

The license plates with all the above specifications and the specified registrations for a vehicle shall be issued by the registering authority or approved the license plates manufacturers or their dealers. The Central Road Research Institute, New Delhi or any of the agency authorised by the Central Government shall approve the license plates manufacturers to the above specification;

(vi)

the size of the plate for different categories of vehicles shall be as follows:

For two and three-wheelers

200 x 100 mm

For Light Motor Vehicles/Passenger cars

340 x 200 mm/500 x 120 mm

For medium commercial vehicles, heavy commercial vehicles and

Trailer/combination

340 x 200 mm:

Provided that this sub-rule shall apply to already registered vehicles two years from the date of commencement:]

[Sub-Rule(1) substituted by GSR 221(E), dated 28.3.2001 as amended by S.O. 938(E), dated 24.9.2001, S.O. 499(E), dated 9.5.2002 and S.O. 59(E), dated 21.1.2003 (w.e.f. 1.1.2004).]

[Provided further that the size of the registration plates for agricultural tractors shall be as follows]

[Inserted by GSR 720(E), dated 10.9.2003 (w.e.f. 10.10.2003).]

:-

Front -

285x45 mm

Rear -

200x100mm]:

[Provided also that the size of registration plate for combine harvester shall be 340mm X 200 mm and exhibited at the front and at the rear of combine harvester and at the rear of trailer for header assembly used during transport:]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

[Provided also that the size of registration plate for power tiller shall be 285x45 mm and shall be exhibited at the front. Further, in case of trailer coupled to power tiller, the size of registration plate shall be 200x100 mm and shall be exhibited on its rear:]

[Third proviso inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

[Provided also that in case of a motor cycle, the size of 285x45 mm for front registration plate shall also be permitted.]

[Fourth proviso inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

(2)

In the case of motor cycles the registration mark in the front shall be displayed parallel to the handle bar or on any part of the vehicle including mudguard facing the front instead of, on a plate in line with the axis of the vehicle:

Provided that

(a)

the registration mark exhibited at the rear of a transport vehicle shall be affixed to the vehicle on the right hand side at a distance not exceeding one metre from the ground as may be reasonably possible having regard to the type of the body of the vehicle;

(b)

the registration mark shall also be painted on the right and left side on the body of the vehicle in the case of a transport vehicle;

(c)

the registration mark shall also be painted and exhibited on the partition provided between the driver and the passengers, facing the passengers seats or, where there is no such partition, on the front interior of the vehicle near the roof to the left side of the drivers seat facing the passengers seats in the case of a stage carriage or a contract carriage and in the case of a motor cab or a taxi cab it shall be sufficient if the registration mark is painted on the dash-board;

(d)

[the letters of the registration mark shall be in English and the figures shall be in Arabic numerals and shall be shown:

[Clause (d) substituted by GSR 901(E), dated 13.12.2001 (w.e.f. 13.12.2001). Earlier Clause (d) was substituted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).]

(A)

in the case of transport vehicles in black colour on yellow background; and

(B)

in other cases, in black colour on white background, the registration mark on the trailer shall be exhibited on the left hand side in black colour on yellow background. In addition, the registration mark on the drawing vehicle shall be exhibited on the trailer also and this shall be done on the right hand side at the rear of the trailer or the last trailer as the case may be, in black colour on retro-reflective type yellow background:

Provided that where provisions of this clause have not been complied with in respect of motor vehicle, on or before the commencement of the Central Motor Vehicles (8th Amendment) Rules, 2001, then the provisions shall be complied with,

(i)

in respect of transport vehicle, on or before 1st February, 2002; and

(ii)

in other cases, on or before 1st July, 2002.]

(3)

[The registration mark shall be exhibited in two lines, the State code and registering authority code forming the first line and the rest forming the second line, one below the other:

[Provided that the registration mark in the front may be exhibited in one line in case, in 200mm x 100mm size plate,

there is no sufficient space to exhibit the registration mark in one line, the alpha numeric of the registration mark shall be displayed as under:]

[Added by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(i)

where the total number of alpha numeric characters in the registration mark is even, then, equal number of alpha numeric character in each line; and

(ii)

where the total number of alpha numeric characters in the registration mark is odd, then any extra alpha numeric character shall be exhibited on the second line,

and all dimensions shall be maintained as per rule 51 without disturbing security features in the plate:

Provided further that in models of vehicles having no sufficient provision at the rear to exhibit the registration mark in two lines, it shall be sufficient if in such vehicles registration mark is exhibited in a single line:

Provided further that registration mark on a light motor vehicle may be in the centre with illumination.

(4)

Every motor vehicle, except motor cab and motor car, manufactured on and from the date of commencement of the Central Motor Vehicles(Amendment) Rules, 1993, shall be provided with sufficient space in the rear for display of registration mark in two lines.

(5)

In case of agricultural tractors, the registration mark need not be inclined to the [vertical plane by more than 45 degrees]

[Substituted by GSR 111(E), dated 10.2.2004, for 'vertical by more than 30 degrees'(w.e.f. 10.8.2004).]

.

(6)

The registration mark of the drawing agricultural tractor may not be exhibited on the agricultural trailer or trailers.].

(7)

[The registration mark of the modular hydraulic trailer may not be exhibited on the puller tractor.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

51.

[Size of letters and numerals of the registration mark.

[Substituted by G.S.R. 338(E), dated 26-3-1993 (w.e.f. 26-3-1993).]

- The dimension of letters and figures of the registration mark and the space between different letters and numerals and letters and edge of the plain surface shall be as follows:]

Sl.No.

Class of vehicle

Dimensions not less than

Height

Thickness

Space between

(1)

(2)

(3)

(4)

(5)

1

All motor cycles and three-wheeled invalid

carriages

Rear-letter

35

7

5

2

All motor cycles and three-wheeled invalid

carriages

Rear-numeral

40

7

5

3

Motor cycles with engine capacity less than 70cc

Front-letters and numerals

15

2.5

2.5

4

Other motor cycles

Front-letters and numerals

30

5

5

[5

[Substituted by G.S.R. 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

Three-wheelers of engine capacity not exceeding

500 cc[E-rickshaws and E-carts]

[Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

Rear and Front numerals and letters

35

7

5

6

Three-wheelers of engine capacity exceeding 500

cc

Rear and Front numerals and letters

40

7

5]

7

All other motor vehicles

Rear and Front numerals and letters

65

10

10

[8

[Inserted by G.S.R. 589(E), dated 16.9.2005 (w.e.f. 16.9.2005)]

Power tillers

Front numerals and letters

15

2.5

2.5

9

Trailers coupled to power tillers

Rear letters and numerals

30

5

5]

[10

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

Combine harvester

Font and rear letters and numerals

65

10

10

11

Trailer for header assembly of combine harvesters

Rear letters and numerals

65

10

10]

52.

Renewal of certificate of registration.

(1)

An application by or on behalf of the owner of a motor vehicle, other than a transport vehicle, for the renewal of a certificate of registration, shall be made to the registering authority in whose jurisdiction the vehicle is, in Form 25 not more than sixty days before the date of its expiry, accompanied by the appropriate fee as specified in rule 81.

(2)

On receipt of an application under sub-rule (1), the registering authority shall refer the vehicle to the authority referred to in sub-section (1) of section 56 and after obtaining a certificate of fitness from that authority, renew the certificate of registration:

Provided that in a case where the certificate of fitness is granted on a date after the expiry of a certificate of registration, the renewal shall be made from the date of grant of the certificate of fitness for a period of five years.

(3)

A motor vehicle other than a transport vehicle shall not be deemed to be validly registered for the purposes of section 39, after the expiry of the period of validity entered in the certificate of registration and no such vehicle shall be used in any public place until its certificate of registration is renewed under sub-rule (2).

52A.

. Renewal of certificate of registration of Government vehicles .

(1)

Notwithstanding anything contained in rule 52 ,the certificate of registration in respect of a motor vehicle owned by -

(i)

the Central Government ;or

(ii)

the State Government or Union Territory administrations ;or

(iii)

any Municipal Corporation or Municipality or Panchayat ;or

(iv)

a State transport undertaking established under the Road Transport Corporation Act ,1950 (64 of 1950)and the Companies Act ,2013 (18 of 2013);or a Public sector undertaking ;or an autonomous body owned or controlled by the Central Government or the State Government , shall expire after the lapse of fifteen years , as provided in sub -section (7) of section 41 , from the date of initial registration of the vehicle :

Provided that the certificate of registration of government vehicle if already renewed before lapse of fifteen years from the date of initial registration ,such certificate shall be treated as cancelled on completion of fifteen years from the date of initial registration of the vehicle :

Provided further that ,this rule shall not apply to the special purpose vehicles (armoured and other specialised vehicles) used for operational purposes for defense of the country and for the maintenance of law and order and internal security .

(2)

Disposal of such vehicles shall ,after the expiry of the fifteen years from the date of initial registration of the vehicle , be ensured through the Registered Vehicle Scrapping Facility set up in accordance with the Motor Vehicles (Registration and Functions of Vehicle Scrapping Facility)Rules ,2021 ,as amended from time to time .

53.

Issue of duplicate certificate of registration.

(1)

If at any time, the certificate of registration is lost or destroyed the owner shall report to the police station in the jurisdiction of which the loss or destruction has occurred and intimate that fact in writing to the registering authority by whom the certificate of registration was issued.

(2)

An application for the issue of a duplicate certificate of registration shall be made to the [last registering authority] [Substituted by GSR 221(E), dated 28.3.2001, for 'original registering authority' (w.e.f. 28.3.2001). Earlier these words were substituted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000).]

in Form 26 and shall be accompanied by the appropriate fee as specified in rule 81.

53A.

Application for temporary registration. - An application for temporary registration in case the motor vehicle is being registered in a state other than the state in which the dealer is situated or in case of a purchased chassis on which the body has to be fabricated separately, shall be made electronically on the Portal by the owner to any registering authority or other authority as may be prescribed by the State Government, in Form 20, and shall be accompanied by the documents required to be submitted along with an application for registration of motor vehicles as per sub-rule (1) of rule 47 along with the appropriate fee as specified in rule 81.

53B.

Issue of temporary certificate of registration. - (1) The temporary registration certificate shall be generated electronically in Form 23B immediately on receipt of application for temporary registration along with requisite fees.

(2)

Any temporary registration granted under sub-rule (1) shall be valid for an initial period of six months from the date of its issue:

Provided that where the motor vehicle registered under sub-rule (1), is a chassis to which a body has not been attached and the same is detained in a workshop beyond the said period of six months for being fitted with a body or due to any unforeseen circumstances beyond the control of the owner, the registering authority may, on submission of application in Form 20B and payment of appropriate fee as specified in rule 81 by the owner, extend the initial period of validity one or more times by 30 days each, as the registering authority may deem fit.

(3)

Upon granting an extension of the initial period of validity of certificate of temporary registration by any further period or periods under sub-rule (2), the registering authority shall make an appropriate entry in Form 23B.

53C.

Assignment of temporary registration marks. -

(1)

The authority granting a temporary certificate of registration shall assign a temporary registration mark to the vehicle, for example:-

T- Represent temporary certificate;

08.

- Month of issuance of temporary certificate of registration 20- Year of issuance of temporary certificate of registration;

AB- Represent State Code;

1234.

- Serial Number of Temporary Registration;

AB- Alphabet of Temporary Registration (Except O and I).

(2)

The owner shall ensure that the said mark is affixed to the front and rear of the motor vehicle.]

[Inserted by 2021 amendment rules]

54.

Assignment of new registration mark.

(1)

An application for the assignment of a new registration mark under sub-section (1) of section 47 shall be made in Form 27 and shall be accompanied by a no objection certificate in Form 28 along with the appropriate fee as specified in rule 81, within a period of thirty days from the date of expiry of the period specified in the said section:

Provided that where a motor vehicle is intended to be kept in a State for a period exceeding twelve months and the owner of such vehicle makes a declaration to that effect, the application may be made at any time within the said period of twelve months.

(2)

On receipt of an application under sub-rule (1), the registering authority shall, subject to the provision of section 44, assign to the vehicle the registration mark.

55.

Transfer of ownership.

(1)

Where the ownership of a motor vehicle is transferred, the transferor shall report the fact of transfer in Form 29 to the registering authorities concerned in whose jurisdiction the transferor and the transferee reside or have their places of business.

(2)

An application for the transfer of ownership of a motor vehicle under sub-clause (i) of clause (a) of sub-section (1) of section 50 shall be made by the transferee in Form 30, and shall be accompanied by

(i)

the certificate of registration;

(ii)

the certificate of insurance; and

(iii)

the appropriate fee as specified in rule 81.

(3)

An application for transfer of ownership of a motor vehicle under sub-clause (ii) of clause (a) of sub-section (1) of section 50 shall be made by the transferee in Form 30 and shall, in addition to the documents and fee referred to in sub-rule (2), be accompanied by one of the following documents, namely :-

(a)

a no objection certificate granted by the registering authority under sub-section (3) of section 48; or

(b)

an order of the registering authority refusing to grant the no objection certificate under sub-section (3) of section 48; or

(c)

where the no objection certificate or the order, as the case may be, has not been received, a declaration by the transferor that he has not received any such communication together with

(i)

the receipt obtained from the registering authority under sub-section (2) of section 48; or

(ii)

the postal acknowledgement received from the registering authority where the application for no objection certificate has been sent by post.

56.

Transfer of ownership on death of owner of the vehicle.

(1)

Where the owner of a motor vehicle dies, the person succeeding to the possession of the vehicle may for a period of three months, use the vehicle as if it has been transferred to him where such person has, within thirty days of the death of the owner informs the registering authority of the occurrence of the death of the owner and of his own intention to use the vehicle.

(2)

The person referred to in sub-rule (1) shall apply in Form 31 within the period of three months to the said registering

authority for the transfer of ownership of the vehicle in his name, accompanied by

(a)

the appropriate fee as specified in rule 81;

(b)

the death certificate in relation to the registered owner;

(c)

the certificate of registration; [* * *]

[Omitted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

(d)

the certificate of insurance; [and]

[Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

(e)

[driving license and permit in case of E-rickshaw and E-cart.]

57.

Transfer of ownership of vehicle purchased in public auction.

(1)

The person who has acquired or purchased a motor vehicle at a public auction conducted by or on behalf of the Central Government or a State Government shall make an application in Form 32 within thirty days of taking possession of the vehicle to the registering authority accompanied by

(a)

the appropriate fee as specified in rule 81;

(b)

the certificates of registration and insurance;

(c)

the certificate or order confirming the sale of the vehicle in his favour duly signed by the person authorised to conduct the auction; [* * *]

[Omitted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

(d)

the certified copy of the order of the Central Government or State Government authorising the auction of the vehicle; [and]

[Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

(e)

[driving license and permit in case of transfer of ownership of E-rickshaw and E-cart.]

(2)

Where the vehicle auctioned is a vehicle without any registration mark, or with a registration mark which on verification is found to be false, the registering authority shall, subject to the provisions of section 44, assign a new registration mark to the vehicle in the name of the Department of the Central Government or State Government auctioning the vehicle and thereafter record the entries of transfer of ownership of the vehicle giving the name and address of the person to whom the vehicle is sold:

[Provided that motor vehicle in the name of the Central Government or State Government shall not be transferred by the concerned registering authority without verifying the proceeding of the auction or disposal of the concerned vehicle.]

[Inserted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.2.2004).]

58.

No objection certificate.

(1)

An application for the issue of no objection certificate under section 48 in respect of a motor vehicle shall be made in Form 28 to the registering authority by which the vehicle was previously registered, accompanied by

(a)

the certified copy of the certificate of registration;

(b)

the certified copy of the certificate of insurance;

(c)

evidence of payment of motor vehicle tax up-to-date;

(d)

where no tax is payable for a certain period a certificate from the tax collecting authority that no tax is due from the vehicle for the said period.

(2)

In the case of a transport vehicle, in addition to the documents referred to in sub-rule (1), documentary evidence in respect of the following matters shall also be furnished, namely:

(a)

that the vehicle is not covered by any permit issued by any transport authority;

(b)

that the sum of money agreed upon to be paid by the holder of the permit under sub-sections (5) and (6) of section 86, if any, is not pending recovery;

(c)

evidence of payment of tax on passengers and goods under any law for the time being in force up to the date of application for no objection certificate.

(3)

On receipt of an application under sub-rule (1), the registering authority shall fill Part III of Form 28 and return that part to the applicant duly signed.

(4)

Where the registering authority grants or refuses to grant the no objection certificate, it shall return the duplicate copy of the said Form to the applicant and the triplicate copy to the other registering authority after duly filling and signing Part II thereof.

59.

Change in residence.

- An application for recording a change in the residence in the certificate of registration of a motor vehicle shall be made by the owner of the vehicle in Form 33 accompanied by the certificate of registration and proof of address in the manner specified in rule 4 and the appropriate fee as specified in rule 81.

60.

Endorsement of hire-purchase agreements, etc.

- An application for making an entry of hire-purchase, lease or hypothecation agreement in the certificate of registration of a motor vehicle required under sub-section (2) of section 51 shall be made in Form 34 duly signed by the registered owner of the vehicle and the financier and shall be accompanied by the certificate of registration and the appropriate fee as specified in rule 81.

61.

Termination of hire-purchase agreements, etc.

(1)

An application for making an entry of termination of agreement of hire purchase, lease or hypothecation referred to in sub-section (3) of section 51 shall be made in Form 35 duly signed by the registered owner of the vehicle and the financier, and shall be accompanied by the certificate of registration and the appropriate fee as specified in rule 81.

(2)

The application for the issue of a fresh certificate of registration under sub-section (5) of section 51 shall be made in Form 36 and shall be accompanied by a fee as specified in rule 81.

(3)

Where the registered owner has refused to deliver the certificate of registration to the financier or has absconded then the registering authority shall issue a notice to the registered owner of the vehicle in Form 37.

Certificate of fitness

62.

Validity of certificate of fitness.

(1)

A certificate of fitness in respect of a transport vehicle granted under section 56 shall be in Form 38 and such certificate

when granted or renewed shall be valid for the period as indicated below:

(a) new transport
vehicle

two years

(b) renewal of

certificate of fitness in respect of vehicles mentioned in (a)

above[***]

[Certain words omitted by G.S.R. 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

one year

(ba) renewal of

certificate of fitness in respect of E-rickshaw and E-cart

three years

(c) [renewal of

certificate of fitness in respect of vehicles covered under rule

82 of these rules

[Substituted by G.S.R. 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

One year]

(d) fresh

registration of imported vehicles

Same period as in

the case of vehicles manufactured in India having regard to the

date of manufacture:

[Provided that the renewal of a fitness certificate shall be made only after an [Inspecting Officer or authorized testing stations as referred to in sub-section (1) of section 56 of the Act]

[Proviso added by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001). Earlier the Proviso was omitted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000). Before that the Proviso was added by GSR 684(E), dated 5.10.1999 (w.e.f. 22.10.1999).]

has carried the tests specified in the Table given below, namely:]

[Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

[Table]

[Substituted by Notification No. GSR 345 (E) dated 19.5.2014 (w.e.f. 2.6.1989)]

Sl.No.

Item

Check

Fitment

Check

make/type/rating etc. as per original equipment recommendations

Check

conditions

Check

Functioning

Test

Remarks

1.

2.

3.

4.

5.

6.

7.

8.

(1)

Spark Plug/

Suppressor cap/ High Tension cable

Yes

Yes

Yes

No

No

-

(2)

Head Lamp Beams

Yes

No

Yes

Yes

Check

(a)

Beam focus as per Annexure VII;(b) in case of authorised testing station using headlight tester, testing procedure and requirement shall be as per AIS-128:2014.

(3)

Other Lights

Yes

No

Yes

Yes

No

Also

ensure that unauthorised lights are not fitted.

(4)

Reflectors

Yes

No

Yes

No

No

Ensure

colour of reflectors and reflective tapes are as per rule 104

(5)

Bulbs

Yes

Yes

Yes

No

No

Ensure

that head light bulbs wattage, especially halogen, is not higher than those indicated in IS 1606-1993 and also ensure that halogen bulbs with P45t caps are not used in all vehicles

(6)

Rear View Mirror

Yes

No

Yes

No

No

-

(7)

Safety Glass

Yes

Yes

Yes

No

No

Laminated

windscreen glass is used for vehicles manufactured from April,
1996 onwards

(8)

Horn

Yes

No

Yes

Yes

No

-

(9)

Silencer

Yes

No

Yes

Yes

No

Ensure no leakage

(10)

Dash Board

Equipment

Yes

No

Yes

Yes

No

-

(11)

Wind shield wiper

Yes

No

Yes

Yes

No

-

(12)

Exhaust emission

No

No

No

No

Yes

Pollution Under

Control Certificate .

(13)

Braking System

Yes

No

Yes

Yes

Yes

(a)

As per rule 96 (8);(b) in case of authorized testing station using roller brake tester, testing procedure, and requirements shall be as per AIS-128:2014.

(14)

Speedometer

Yes

No

Yes

Yes

No

As per rule 117.

(15)

Steering gear

Yes

No

Yes

Yes

Check

free play

Check

free play as per rule 98 for vehicles with steering wheel.

(16) [

[Inserted by Notification No. G.S.R. 677 (E), dated 3.9.2015 (w.e.f. 2.6.1989).]

Rear Under run Protecting Device For N2, N3, T3 and T4 gear

Yes

No

Yes

No

No

As per rule 124 (1A)

(17)

Lateral Side Protection Device For N2, N3, T3 and T4

Yes

No

Yes

No

No

As per rule 124 (1A)]

[Provided further that in case of E-rickshaw and E-cart, the renewal of fitness certificate shall be made only after carrying out tests specified out tests specified in the Table given below :-

Items

Check Fitment

Check make or Type rating, etc., as per original equipment recommendation

Check conditions

Check functioning

Test

Remarks

Maximum speed

No

No

No

No

Yes

The vehicle shall be driven in unladen condition (with full charge and at full accelerator position) on straight or flat road and when the vehicle attains full speed, the maximum speed shall be calculated by measuring time taken to travel fixed distance (say 50 metres).]

[Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

[Provided also that if the tests specified in the Table under the first proviso are conducted by an Inspecting Officer or authorized testing station in a State/ Union Territory other than the State/ Union Territory where the vehicle is registered, the Inspecting Officer who conducted the tests shall, on the same day or on the following working day, upload his inspection report in Form 38A at the portal <http://parivahan.gov.in/vahan> and also send the inspection report signed under his hand and seal to the registering authority by speed post for issue of certificate of fitness by the registering authority within fifteen days from the date of the inspection report, if the vehicle is found by the Inspecting Officer to be in compliance with the provisions of the Act and rules and a copy shall be given to the driver of the vehicle:

[Inserted by the Notification No. G.S.R. 1096, dated 28.11.2016 (w.e.f. 2.6.1989).]

Provided also that the next fitness certificate is obtained from the inspecting officer or an authorized testing station in the State/ Union Territory of the registering authority where the vehicle is registered.]

[Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

Explanation. - Inspecting Officer means an Officer appointed by a State Government under section 213 of the Act.

(2)

The fee for the grant or renewal of a certificate of fitness shall be as specified in rule 81.

(3)

[The fee for testing of a vehicle when tested by an Inspecting Officer or authorised testing station, other than the Inspecting Officer in the office of the registering authority, shall be as specified in rule 81.]

[Inserted by the Notification No. G.S.R. 1096, dated 28.11.2016 (w.e.f. 2.6.1989).]

63.

Regulation and control of authorized testing stations.

(1)

No operator of an authorised testing station shall issue or renew a certificate of fitness to a transport vehicle under section 56 without a letter of authority in Form 39 granted by the registering authority.

(2)

An application for grant or renewal of a letter of authority under sub-rule (1) shall be made in Form 40 to the registering authority having jurisdiction in the area in which the service station or garage is situated and shall be accompanied by,

(a)

the appropriate fee as specified in rule 81;

(b)
a security deposit of [rupees one lakh]
[Substituted by GSR 338(E), dated 26.3.1993, for 'rupees ten thousand'(w.e.f. 26.3.1993).]
in such manner as may be specified by the State Government.

Explanation. - For the purpose of this rule and rules 64 to 72, the registering authority means an officer not below the rank of the regional transport officer of the Motor Vehicles Department established under section 213.

(3)
A registering authority shall, when considering an application for the grant or renewal of a letter of authority, have regard to the following matters, namely:

(a)
the applicant or at least one of the members of the staff employed by him for the inspection of transport vehicles for the purpose of issue or renewal of certificate of fitness possesses the following minimum qualifications:

(i)
a [three years]
[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]
diploma in automobile engineering or mechanical engineering or an equivalent qualification;

(ii)
experience of minimum service of five years in an automobile workshop undertaking repairs of heavy goods vehicles, heavy passenger motor vehicles, medium motor vehicles and light motor vehicles;

(iii)
a driving license to drive motor cycle, heavy passenger motor vehicle and heavy goods vehicle with a minimum driving experience of not less than five years;

(iv)
thorough knowledge of the Act and the rules made thereunder, especially the Chapters relating to registration of motor vehicles and construction, equipment and maintenance of motor vehicles;

(b)
the premises where the authorised testing station is to be housed is either owned by the applicant or is taken on lease by him or is hired in his name and it has [minimum of one acre of land]
[Certain words substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]
for administrative section, reception room and [sanitary block and space for erection]
[Certain words substituted by G.S.R. 338(E), dated 26-3-1993 (w.e.f. 26-3-1993).]
of testing equipments and other apparatus;

(c)
inspection lanes are provided adjacent to the building in the same compound or at other places approved by the registering authority;

(d)
testing equipments and apparatus are installed in such manner that vehicles may pass through with ease and speed;

(e)
[the applicant maintains in good condition, the equipment and apparatus for undertaking test pertaining to [exhaust gas, engine tuning, engine analysis]

[Clause (e) substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]
,smoke emission, brake system, head-lights, wheel alignments, compressors, speedometers and other like components;]

(f)
the financial resources of the applicant are sufficient to provide for its continued maintenance;

(g)
the applicant maintains an up-to-date copy of the Act, these Rules and the concerned State Motor Vehicles Rules.

(4)
The registering authority shall also, when considering an application under this rule, take into consideration the fact that the setting up of the authorised testing station will improve the availability of testing facilities in the area both in relation to the number of vehicles and proximity to such facilities.

(5)

The registering authority may, on receipt of an application under sub-rule (2) and after satisfying himself that the applicant has complied with the requirements of sub-rules (3) and (4), grant or renew the letter of authority in Form 39: Provided that no application for a letter of authority shall be refused by the registering authority unless the applicant is given an opportunity of being heard and reasons for such refusal are given in writing by the registering authority.

64.

Duration of letter of authority.

- A letter of authority granted or renewed shall be effective for a period of five years from the date of grant or renewal.

65.

General conditions to be observed by the holder of letter of authority.

- The holder of a letter of authority shall

(a)

maintain a register with a separate page for each vehicle containing the registration number of the vehicle for which the certificate of fitness is granted or renewed, the make and model of the vehicle, the engine number and the chassis number of the vehicle along with the pencil print of the chassis number, the name and address of the owner of the vehicle, particulars of any permit of such vehicle, period of validity of certificate of fitness granted or renewed and the signature of the owner of the vehicle or his authorised representative;

(b)

forward the particulars of the transport vehicles for which certificates of fitness have been granted or renewed and the period of validity of such certificate, within two days of grant or renewal of the certificate of fitness, to the authority which has granted the permit and where the transport vehicle is not covered by a permit, to the transport authority in whose jurisdiction the vehicle is kept;

(c)

issue to every transport vehicle satisfying the requirements of section 56, a certificate of fitness in accordance with the provisions of rule 62;

(d)

not shift the place of business mentioned in the letter of authority without the prior approval in writing of the registering authority which granted the letter of authority;

(e)

keep the premises of the testing station and the records and registers maintained by it and all the machinery, equipment and apparatus in the premises at all reasonable time open for inspection by the registering authority or any person of the Motor Vehicles Department of the State Government established under section 213 authorised in this behalf by the registering authority;

(f)

display at a prominent place in its main office the following:

(i)

the letter of authority in original issued to the authorised testing station by the registering authority;

(ii)

the name and address of the person authorised to issue or renew the certificate of fitness;

(iii)

the qualifications of the persons referred to in clause (a) of sub-rule (3) of rule 63;

(g)

not charge a fee for inspection of a vehicle for the purpose of issue or renewal of the appropriate certificate of fitness in excess of the fee specified in rule 81;

(h)

surrender to the Regional Transport Authority having jurisdiction over the area, the register referred to in clause (a) as soon as entries in all the pages in the register are completed and in any case not later than two days after such completion.

66.

Issue of duplicate letter of authority.

(1)

If at any time the letter of authority granted or renewed under sub-rule (5) of rule 63 is lost or destroyed, the holder of the letter of authority shall report to the police station in the jurisdiction of which the loss or destruction has occurred and intimate the fact in writing to the registering authority which granted or renewed the letter of authority and shall apply for a duplicate.

(2)

On receipt of an application along with the appropriate fee as specified in rule 81, the registering authority may issue a duplicate letter of authority clearly marked Duplicate.

(3)

If after the issue of a duplicate letter of authority, the original is traced, the same shall be surrendered forthwith to the registering authority by which it was issued.

67.

Supervision of authorised testing stations.

- The registering authority or any officer of the Motor Vehicles Department of the State Government duly authorised in this behalf by the registering authority may, at any time, conduct test checks at the premises of the authorised testing station with a view to ensure that the vehicles are properly tested by the authorised testing station.

68.

Power of registering authority or Regional Transport Authority to call for information.

- The authorised testing station shall submit to the registering authority or the Regional Transport Authority having jurisdiction in the area, such information or returns as maybe called for by such authority from time to time.

69.

Power of registering authority to suspend or cancel the letter of authority or forfeit security deposit.

(1)

If the registering authority is satisfied after giving the holder of a letter of authority an opportunity of being heard, that he has

(a)

failed to maintain the equipment, machinery and apparatus referred to in sub-clause (e) of sub-rule (3) of rule 63 in good condition; or

(b)

failed to comply with the other requirements laid down in sub-rule (3) of rule 63; or

(c)

failed to observe correct standards of testing before granting or renewing certificates of fitness as noticed at the time of test-checking referred to in rule 67 or the frequency of accidents involving transport vehicles covered by certificates of fitness granted or renewed by the authorised testing station attributable to any mechanical defect of the vehicle, it may

(i)

suspend the letter of authority for a specified period; or

(ii)

cancel the letter of authority; or

(iii)

order forfeiture of the security deposit furnished by the authorised testing station.

(2)

Where the letter of authority is suspended or cancelled under sub-rule (1), the holder of the letter of authority shall surrender the same to the registering authority forthwith.

(3)

Where the security deposit is forfeited under sub-rule(1), the holder of the letter within thirty days of the receipt of the order of forfeiture, remit to the registering authority the amount ordered to be forfeited so that the requirement of sub-rule (2) of rule 63 in relation to deposit of security is complied with.

70.

Appeal.

- Any person aggrieved by an order of the registering authority under sub-rule (5) of rule 63 or sub-rule (1) of rule 69, may, within thirty days of the receipt of the order, appeal to the Head of the Motor Vehicles Department of the State Government established under section 213.

71.

Procedure for appeal.

(1)

An appeal under rule 70 shall be preferred in duplicate in the form of a memorandum, setting forth the grounds of objections to the order of the registering authority and shall be accompanied by the appropriate fee as specified in rule 81 and a certified copy of such order.

(2)

The appellate authority may, after giving an opportunity to the parties to be heard and after such enquiry as it may deem necessary, pass appropriate orders.

72.

Voluntary surrender of letter of authority.

(1)

The holder of a letter of authority may, at any time, surrender the letter of authority issued to him, to the registering authority which has granted the letter of authority and on such surrender, the registering authority shall cancel the letter of authority forthwith.

(2)

On cancellation of the letter of authority under sub-rule (1), the registering authority shall refund to the holder of the letter of authority, the amount of security deposit referred to in sub-rule (2) of rule 63 in full and without any interest.

73.

Tax clearance certificate to be submitted to the testing station.

- No authorised testing station shall accept an application for the grant or renewal of a certificate of fitness unless the same is accompanied by a tax clearance certificate in such form as may be specified by the State Government, from the Regional Transport Officer or motor vehicle inspector having jurisdiction in the area to the effect that the vehicle is not in arrears of motor vehicle tax or any compounding fee referred to in sub-sections (5) and (6) of section 86.

Registration of vehicles belonging to the Central Government used for defence purposes

74.

Assignment of registration marks to the vehicles belonging to the Central Government used for defence purposes.

- The authority referred to in sub-section (1) of section 60 shall assign registration marks to the vehicles belonging to the Central Government and used for defence purposes in the following manner, namely:

A group of figures followed by a single capital letter, a broad arrow, not more than six figures and a capital letter or a group of letters. The registration mark shall be in English letters and Arabic numerals.

State Register of Motor Vehicles

75.

State register of motor vehicles.

(1)

Each State Government shall maintain a State register of motor vehicles in respect of motor vehicles registered in the State in Form 41.

(2)

Each [State Government shall, if so desired by the Central Government]

[Substituted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001). Earlier these words were omitted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000). Before that words were inserted by GSR 684(E), dated 5.10.1999 (w.e.f. 22.10.1999).]

send to the Director (Transport Research), Ministry of Surface Transport, New Delhi, a printed copy of the register referred to in sub-rule (1).

Special provision for registration of motor vehicles of diplomatic officers, etc.

76.

Registration of vehicles of diplomatic and consular officers.

(1)

Every application for registration of a motor vehicle under sub-section (1) of section 42 by or on behalf of any diplomatic officer or consular officer shall be made in triplicate by the head of the mission or consular officer in Form 42 and be addressed to the registering authority through the Competent Authority accompanied by the relevant documents and fees referred to in rule 47.

(2)

The Competent Authority shall forward one copy of the application to the registering authority concerned together with a statement certifying the status of the person applying for registration and shall return one copy of the application to the applicant. The third copy of the application may be retained by the Competent Authority for record.

(3)

The registering authority shall, on receipt of the application duly endorsed under sub-rule (2), register the vehicle, subject to the provision of section 44.

(4)

The registering authority shall issue to the owner of a motor vehicle registered by it under sub-rule (3), a certificate of registration in Form 43 and shall enter in a register to be kept by it, particulars of such certificate.

(5)

The registering authority shall assign to the motor vehicle for display thereon in the manner specified in rule 77, the registration mark in accordance with sub-rule (6) or sub-rule (7), as the case may be.

(6)

[A motor vehicle belonging to a diplomatic mission in Delhi or to any of its diplomatic officer shall be assigned a registration mark consisting of the letters CD preceded by the number allotted to the mission by the Ministry of External Affairs of the Government of India and followed by a number allotted to the vehicle by the registering authority in the following manner, namely :

(i)

an official vehicle meant for the use of the head of a mission shall be allotted the number 1;

(ii)

personal vehicles of the head of the mission shall be allotted the number 1, followed consecutively, in alphabetical order, by a letter beginning with the letter A;

(iii)

official vehicles, other than those referred to in clause (i), shall be allotted consecutive numbers beginning with the number 2;

(iv)

vehicles belonging to other officers of the mission shall be allotted numbers in consecutive order after the last number allotted under clause (iii);

(v)

vehicles acquired by a mission or by its diplomatic officer other than heads of missions, shall be allotted numbers in consecutive order after the last number allotted under clause (iv) irrespective of whether such vehicle is for official or personal use of the mission or any of its officers;

(vi)

a number allotted to a vehicle under any of the clauses (i) to (iv), which is lying unutilised due to sale or export of such vehicle or cancellation of its number may be allotted to another vehicle under the same clause in respect of which an application has been made under sub-rule (1).]

(7)

A motor vehicle belonging to a consular post [headed by a Carrier Counsellor Officer]

[Substituted by GSR 221(E), dated 28.3.2001, for 'outside Delhi'(w.e.f. 28.3.2001).]

or to any of its officers shall be assigned a registration mark consisting of the letters CC preceded by the number of the post allotted to it by the Ministry of External Affairs of the Government of India and followed by a number allotted to the vehicle by the registering authority out of a block of numbers allotted for that post in the following manner, namely:

(i)

an official vehicle meant for the use of the head of a consular post shall be allotted the first number from the block of numbers allotted to that post;

(ii)

personal vehicles of the Consul-General shall be allotted the number referred to in clause (i), followed consecutively in alphabetical order, by a letter beginning with the letter A;

(iii)

official vehicles other than those referred to in clause (i), shall be allotted consecutive numbers beginning with the

second number from the block of numbers allotted to the post;

(iv)

vehicles belonging to other officers of the post shall be allotted numbers in consecutive order after the last number allotted under clause (iii);

(v)

vehicles acquired by a post, or by its consular officers, other than the head of the post shall be allotted numbers in consecutive order after the last number allotted under clause (iv) irrespective of whether such vehicle is for official or personal use of the post or any of its officers;

(vi)

a number allotted to a vehicle under any of the clauses (i) to (v), which is lying unutilised due to sale or export of such vehicle or cancellation of its number, may be allotted to another vehicle under the same clause in respect of which an application has been made under sub-rule (i).

[Explanation. - For the purposes of this rule and rules 77, 78 and 79, competent authority means:

(i)

in relation to a diplomatic officer or a consular officer who has his residence in Delhi, the Chief of Protocol to the Government of India in the Ministry of External Affairs; and

(ii)

in relation to a diplomatic officer or a consular officer who has his residence at any other place, the Secretary (Transport) to the State Government.]

(8)

[Consular posts headed by Honorary Consular Officers shall use standard size number plates bearing ordinary registration number provided by the concerned registration authorities. They may, however, use the word name of the country followed by CC (Honorary) in the same font and colour (i.e., the numbers and letters in white colour on black background) but in letters smaller than the registration number on a maximum of two of their vehicles.]

[Inserted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).]

[76-A. Application of rules 76 to 80 to organisations notified under the United Nations (Privileges and Immunities) Act, 1947.

[Inserted by GSR 644, dated 25.9.1995.]

- The provisions of rules 76 and 77 to 80 shall apply to the motor vehicles of diplomatic officers of the organisations notified under the United Nations (Privileges and Immunities) Act, 1947 (46 of 1947) as they apply to a diplomatic officer or consular officer with the modification that in rule 76,

(a)

in sub-rule (6), for the letters CD, the letters UN shall be substituted; and

(b)

in sub-rule (7), for the letters CC, the letters UN shall be substituted.]

[76-B. Registration of vehicles of home-based non-diplomatic officials of diplomatic missions or consular posts.

[Inserted by GSR 395(E), dated 16.7.1997 (w.e.f. 16.7.1997).]

(1)

A motor vehicle belonging to a non-diplomatic official of a diplomatic mission or a consular post in Delhi shall be assigned a registration mark consisting of letters CDP preceded by the number allotted to the mission or post by the Ministry of External Affairs of the Government of India and followed by a number allotted to the vehicle by the registering authority.

(2)

A motor vehicle belonging to a home-based non-diplomatic official of a consular post outside Delhi shall be assigned a registration mark consisting of the letters CCP preceded by the number of the post allotted to it by the Ministry of External Affairs of the Government of India and followed by the number allotted to the vehicle by the registering authority.]

[Substituted by GSR 129(E), dated 16.2.2000 (w.e.f. 16.2.2000).]

77.

Exhibition of registration mark.

(1)

The registration mark assigned under sub-rules (5) to (7) of rule 76 shall be clearly exhibited in reflecting colour both at the front and rear of the vehicle on the plain surface of a plate or part of the vehicle and the size of which shall be 41 centimetres by 14 centimetres

(i)

with deep blue background, the registration mark and the number being in white in the case of motor vehicles referred to in sub-rule (6) of rule 76;

(ii)

[with deep blue background, the registration mark and the number being in yellow]

[Substituted 'with yellow background, the registration mark and the number being in black' by Notification No. G.S.R. 633(E), dated 23.6.2017 (w.e.f. 2.6.1989).]

, in the case of motor vehicles referred to in sub-rule (7) of rule 76;

(iii)

[with light green background, the registration mark and the number being in white in case of motor vehicles referred to in rule 76-B.]

[Inserted by GSR 395(E), dated 16.7.1997 (w.e.f. 16.7.1997).]

(2)

The registration mark shall be in English letters and Arabic numerals and

(i)

save in the case of a motor cycle or an invalid carriage, the letters shall be not less than 6 centimetres high and 2centimetres thick at any part, the numerals shall be not less than 9centimetres high and 2 centimetres thick at any part, and there shall be as pace between any letter and any numeral and between any letter or any numeral and the edge of the plain surface of not less than 1 centimetre and a space between any two letters and between any two numerals of not less than 1centimetre; and

(ii)

in the case of a motor cycle or an invalid carriage, the dimensions of the letters and figures shall not be less than two-thirds of those specified in clause (i).

(3)

The plain surface referred to in sub-rule (2) shall not be inclined from the vertical by more than thirty degrees. The letters and numerals shall be exhibited as follows:

(i)

in the case of a transport vehicle, the registration mark shall be exhibited in two separate horizontal lines, the number allotted to the mission or post and the letters forming the first line followed by the number allotted by the registering authority in the second line; and

(ii)

in all other cases, the registration mark may exhibit the letters and numerals either in two horizontal lines as aforesaid or in one horizontal line.

(4)

Notwithstanding anything contained in sub-rule (1), the registration mark exhibited at the front of a motor cycle or an invalid carriage may be displayed on a plate in line with the axis of the vehicle and shall, in such a case, be displayed on both sides of the plate.

(5)

In the case of a trailer

(i)

the registration mark shall be exhibited on a plate or surface on the left hand side of the trailer, the dimensions of the letters and figures being not less than two-thirds of the dimensions specified in sub-rule (2);

(ii)

the registration mark of the drawing motor vehicle to be affixed to the rear of the trailer shall be in conformity with the provisions of these rules relating to the registration mark affixed to the rear of the motor vehicle.

(6)

The registration mark shall also be painted on the right and left side of the body of a transport vehicle.

78.

Assignment of new registration mark on removal of vehicle to another State.

(1)

Every application for assignment of new registration mark on removal to another State under sub-section (1) of section 47 by or on behalf of a diplomatic officer or consular officer shall be made in triplicate in Form 44 and shall be addressed to the registering authority through the competent authority accompanied by the relevant documents and fees referred to in rule 54.

(2)

The provisions of sub-rules (2) to (7) of rule 76 shall apply to an application made under sub-rule (1) as they apply to an application made under sub-rule (1) of rule 76.

79.

Suspension and cancellation of registration of vehicle registered under rule 76.

- If, under the provisions of section 53, section 54 or section 55, the registration of a motor vehicle made in accordance with rule 76 is suspended or cancelled, then a copy of the order of suspension or cancellation shall be sent to the competent authority in addition to each of the authorities or persons to whom a copy has to be sent under the said sections.

80.

Transfer or disposal of motor vehicle registered under rule 76.

(1)

Where a motor vehicle registered in accordance with rule 76 is transferred by way of sale or otherwise, the transferor shall, within fourteen days, report the fact of the transfer along with the full name and address of the person to whom the vehicle is transferred to the registering authority within whose jurisdiction the transfer is effected and shall simultaneously send copies of the said report to:

(a)

the transferee;

(b)

the competent authority;

(c)

the Collector of Customs of the port of importation of the vehicle and where it is not possible to locate the port of importation, to the Collector of Central Excise and Customs nearest to the headquarters of the transferee; and

(d)

the original registering authority in whose records the registration of the vehicle is recorded, if the transfer is effected in the jurisdiction of another registering authority,

and shall also surrender the number plate in respect of the vehicle to the registering authority in whose records the registration of the vehicle is recorded, when the transfer is to a person other than a diplomatic officer or a consular officer.

(2)

Where the transferee is a diplomatic officer or a consular officer, an application by him or on his behalf shall be made to the registering authority for registration of the vehicle in accordance with the provision of rule 76.

Fees

81.

[Fees.

[Substituted by Notification No. G.S.R. 1183(E), dated 29.12.2016 (w.e.f. 2.6.1989).]

- The fees which shall be charged under the provisions of this Chapter shall be as specified in the Table below:

Provided that the States may levy [fee lower than the amount specified in the table and may also levy]

[Sub-Rule(6) substituted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).]

additional amounts to cover the cost of automation and technology utilized for conducting the testing or providing value added services.

Table

Sl. No.

Purpose

Amount

Rule

Section

(1)

(2)

(3)

(4)

(5)

1.

Grant or renewal of trade certificate in respect of each class
of vehicle:

34(1)

(a) Motorcycle

Five hundred rupees

(b) Invalid Carriage

Five hundred rupees

(c) Others

One thousand rupees

2.

Duplicate trade certificate:

38(1)

(a) Motorcycle

Three hundred rupees

(b) Invalid Carriage

Three hundred rupees

(c) Others

Five hundred rupees

3.

Appeal under rule 46

One thousand rupees

46(1)

4.

Issue or renewal of certificate of registration and assignment
of new registration mark:

47(1)

52(1)

54(1)

76(1)

and

78(1)

(a) Invalid Carriage

(b) Motor cycle

Fifty rupees

(c) Three wheeler/ Quadricycle/ Light Motor Vehicles:

Three hundred rupees

i) Non transport;

Six hundred rupees

ii) Transport

One thousand rupees

(d) Medium goods vehicle

One thousand rupees

(e) Medium passenger motor vehicle

One thousand rupees

(f) Heavy goods vehicle

One thousand and five hundred rupees

(g) Heavy passenger motor vehicle

One thousand and five hundred rupees

(h) Imported motor vehicle

Five thousand rupees

(i) Imported motor cycle

Two thousand and five hundred rupees

(j) Any other vehicle not mentioned above

Three thousand rupees

Note 1: Additional fee of two hundred rupees shall be levied if the certificate of registration is a smart card type issued or renewed in Form 23A.

Note 2: In case of delay in applying for renewal of certificate of registration, an additional fee of three hundred rupees for delay of every month or part thereof in respect of motor cycles and five hundred rupees for delay of every month or part thereof in respect of other classes of non-transport vehicles shall be levied.

5.

Issue of duplicate certificate of registration

Half of the fee mentioned against Serial No.4

53(2)

6.

Transfer of ownership

Half of the fee mentioned against

Serial No.4.

Note: In case of delay in submission of 'No Objection Certificate', an additional fee of rupees three hundred for delay of each month or part thereof in case of motor cycles and five hundred rupees for each month of delay or part thereof for other vehicles shall be levied.

55(2)(iii), 55(3), 56(2)(a) and 57(1)(a)

7.

Change of residence

Half of the fee mentioned against

Serial No.4.

Note: In case of delay in submitting 'No Objection Certificate' for change of residence, an additional fee of rupees three hundred for delay of each month or part thereof in case of motor cycles and five hundred rupees for each month of delay or part thereof for other vehicles shall be levied.

59

8.

Recording alteration in the certificate of registration

Half of the fee mentioned against Serial No.4

9.

Endorsing hire purchase/ lease/ hypothecation agreement-

60

(a) Motorcycle

Five hundred rupees

(b) Three wheeler/quadracycle/light motor vehicle

One thousand and five hundred rupees

(c) Medium or heavy vehicle

Three thousand rupees

Note: No separate fee will be levied for cancellation

of lease, etc, or for issue of fresh Certificate of Registration thereafter.

10.

Conducting test of a vehicle for grant or renewal of certificate of fitness

62(2)

(a) Motorcycle

(i) Manual: Two hundred rupees

(ii) Automated: Four hundred rupees

(b) Three wheeled or light motor vehicle or quadracycle

(i) Manual : Four hundred rupees

(ii) Automated: Six hundred rupees

(c) Medium or heavy motor vehicle

(i) Manual: Six hundred rupees

(ii) Automated: One thousand rupees

11.

Grant or renewal of certificate of fitness for motor vehicle

Two hundred rupees.

Note: Additional fee of fifty rupees for each day of delay after expiry of certificate of fitness shall be levied.

62(2)

12.

Grant or renewal of letter of authority

Fifteen thousand rupees

63(2)(a)

13.

Issue of duplicate letter of authority

Seven thousand and five hundred rupees

66(2)

14.

Appeal under rule 70

Three thousand rupees

71(1)

15.

Any application not covered under entries at Serial Nos. 1 to 14 above

Two hundred rupees

64(p)

Note 1: For the removal of doubts, it is hereby clarified that medium passenger motor vehicles, heavy goods vehicles, imported motor vehicles or any other vehicles not mentioned against Serial No.4 of the above Table include both transport and non-transport vehicles.

Note 2: Where the certificate of registration issued is in the form of any Smart Card Type, an additional fee of rupees two hundred shall be charged except in the case of issue of fresh certificate of registration after cancellation of hire purchase or lease or hypothecation agreement.]

81. Fees.- The fee which shall be charged under the provisions of this Chapter shall be as specified in the table below:

[Table]

[Substituted by G.S.R. 221(E), dated 28.3.2001(w.e.f. 28.3.2001). Earlier the Table was substituted by G.S.R. 76(E), dated 31.1.2000 (w.e.f. 31.1.2000). Before that the Table was substituted by G.S.R 684 (E), dated 5.10.1999 (w.e.f. 22.10.1999).]

{|

Sl.No.

Purpose

Amount

Rule

Section

1.

Grant or renewal of trade certificate in respect of each vehicle

34(1)

-

Motor cycle

Fifty rupees

Invalid carriage

Fifty rupees

Others

Two hundred rupees

2.

Duplicate trade certificate

38(1)

-

Motor cycle

Thirty rupees

Invalid carriage

Thirty rupees

Others

One hundred rupees

3.

Appeal under rule 46

One hundred rupees

46(1)

-

4.

Issue, renewal of certificates of registration and assignment of new registration mark:

47(1),52(1),54(1),76(1)and78(1)

Invalid carriage

Twenty rupees

Motor cycle

Sixty rupees

Light motor vehicle:

(i) Non-Transport

Two hundred rupees

(ii) Light Commercial Vehicle

Three hundred rupees

[E-rickshaw or E-cart

[Susbstituted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

Three hundred rupees]

Medium goods vehicle

Four hundred rupees

Medium passenger motor vehicle

Four hundred rupees

Heavy goods vehicle

Six hundred rupees

Heavy passenger motor vehicle

Six hundred rupees

Imported motor vehicle

Eight Hundred rupees

Imported motor cycle

Two hundred rupees

Any other vehicle not mentioned above

Three hundred rupees

5.

Issue of duplicate certificate of registration

Half of the fee mentioned in Serial No. 4

53(2)

-

6.

Transfer of ownership

Half of the fee mentioned in Serial No. 4

55(2)(iii),55(3),56(2)(a)and57(1)(a)

-

7.

Change of residence

Twenty rupees

59

8.

Recording alteration in the certificate of registration

Fifty rupees

52(4)

-

9.

Endorsing hire-purchase/ lease/ hypothecation agreement

One hundred rupees

60

-

10.

Cancellation of hire-purchase/ lease/ hypothecation agreement

or issue of fresh certificate of registration

One hundred rupees

61(1) and (2)

-

11.

Conducting test of a vehicle for grant and renewal of

certificate of fitness:

(i) Two/ three-wheeled vehicle

One hundred rupees

62(2)

-

(ii) Light motor vehicle

Two hundred rupees

(iii) Medium motor vehicle

Three hundred rupees

(iv) Heavy motor vehicle

Four hundred rupees

11A. [

[Inserted by Notification No. G.S.R. 1096 (E), dated 28.11.2016 (w.e.f. 2.6.1989).]

Conducting test of a vehicle by an Inspecting Officer or

Authorized testing station other than the Inspecting Officer in

the office of the registering authority for grant or renewal of

certificate of fitness by the registering authority

Manual: Two hundred rupees

62(2)

Motorcycle

Automated : Four hundred rupees

Three wheeled or light motor vehicle or quadricycle

Manual : Four hundred rupees Automated : Six hundred rupees

Medium or heavy motor vehicle

Manual : Six hundred rupees Automated : One thousand rupees]

12.

Grant or renewal or certificate of fitness for motor vehicle

One hundred rupees

62(2)

-

13.

Grant or renewal of letter of authority

Five thousand rupees

63(2)(a)

-

14.

Issue of duplicate letter of authority

Five thousand rupees

66(2)

-

15.

Appeal under rule 70

Four hundred rupees

71(1)

-

Note.- For the removal of doubts, it is hereby declared that medium passenger motor vehicle, heavy goods vehicle, imported motor vehicle and any other vehicle not mentioned in Serial No. 4 of this Table include both transport and non-transport vehicles:

{}

[Provided that in case for any purpose referred to in Serial Numbers 4, 5, 6, 7, 8, 9 and 10 of this Table is issued on any Smart Card, an additional amount of fee of Rupees Two hundred shall be charged for each such card.]

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

Chapter IV

Control of Transport Vehicles

Tourist permits

82.

Tourist permits.

(1)

An application for the grant of permit in respect of a tourist vehicle (hereinafter referred to in these rules as a tourist permit) shall be made in Form 45 to the State Transport Authority.

(2)

[* * *]

[Clause (a) of sub-Rule(2) omitted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(a)

[A tourist permit shall be deemed to be invalid from the date on which the motor vehicle covered by the permit completes 9 years in the case of a motor cab and 8 years where the motor vehicle is other than a motor cab, unless the motor vehicle is replaced;]

[Clause (b) of sub-Rule(2) renumbered as Clause (a) and Clause (a) as so renumbered substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(b)

[]

[Clause (c) of sub-Rule(2) renumbered as Clause (b) by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

Where a vehicle covered by a tourist permit is proposed to be replaced by another, the latter vehicle shall not be more than two years old on the date of such replacement.

Explanation. - For the purposes of this sub-rule, the period of [9 years or 8 years]

[Substituted by GSR 338(E), dated 26.3.1993, for '2 years, 5 years or 7 years'(w.e.f. 26.3.1993).]

shall be computed from the date of initial registration of the motor vehicle.

83.

Authorisation fee.

(1)

An application for the grant of authorisation for a tourist permit shall be made in Form 46 and shall be accompanied by a fee of Rs. 500 per annum in the form of a bank draft.

(2)

[Every authorisation shall be granted in Form 23-A, in case the certificate of registration is issued on Smart Card or shall be granted in Form 47, in case the authorisation is in paper document mode subject to the payment of taxes or fees, if any, levied by the concerned State. The authority which grants the authorisation shall issue to the permit holder separate receipts for such taxes or fees in respect of each bank draft and such receipts shall be security printed watermark paper carrying such hologram as may be specified by the concerned State/Union Territory:

Provided that the bank drafts received in respect of taxes or fees shall invariably be forwarded by the authority which grants the authorisation to the respective States:

Provided also that the use of such security printed watermark paper carrying such hologram shall come into force on or before six months from the date of commencement of the Central Motor Vehicles (Third Amendment) Rules, 2002.]

[Sub-Rule(2) substituted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

[(2-A) The authority which grants the authorisation shall inform the State Transport Authorities concerned the registration number of the motor vehicle, the name and address of the permit holder and the period for which the said authorisation is valid:]

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[Provided that where the permit holder undertakes to pay the tax direct to the concerned State Transport Authority at the time of entry in his jurisdiction, the authorisation shall expressly state that it has been issued subject to payment of taxes to the concerned State Transport Authority.]

[Inserted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000). Earlier Proviso was omitted by GSR 684(E), dated 5.10.1999 (w.e.f. 22.10.1999).]

(3)

The period of validity of an authorisation shall not exceed one year at a time [* * *]

[The words 'and shall expire on the 31st day of March of the year' omitted by GSR 933(E), dated 28.10.1989 (w.e.f.

28.10.1989).]

.

84.

Right of operation.

- No tourist permit shall be deemed to confer the right of operation in any State not included in the authorisation referred to in rule 83 nor shall it exempt the owner of a vehicle from the payment of tax or fee, if any, leviable in any State.

85.

Additional conditions of tourist permit.

- The following shall be the additional conditions of every tourist permit granted to a tourist vehicle other than a motor cab under sub-section (9) of section 88, namely:

(1)

The permit holder shall cause to be prepared in respect of each trip a list in triplicate of tourist passengers to be carried in the vehicle, [***]

[Certain words omitted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

giving full particulars as under :-

(a)

name of the passengers,

(b)

address of the passengers,

(c)

age of the passengers,

(d)

starting point and the point of destination.

(2)

[One copy of the list referred to in sub-rule (1) shall be carried in the tourist vehicle and shall be produced on demand by the officers authorised to demand production of documents by or under the provisions of the Act and the Rules, and the second copy shall be preserved by the permit holder.]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(3)

The tourist vehicle shall either commence its journey, or end its journey, circular or otherwise, in the home State, subject to the condition that the vehicle shall not remain outside the home State for a period of more than [three months.]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

The permit holder shall see that every return of the tourist vehicle to the home State is reported to the authority which issued the permit:

Provided that where the contracted journey ends outside the home State, the vehicle shall not be offered for hire within that State or from that State to any other State except for the return journey to any point in the home State.

(4)

The tourist vehicle may operate circular tours of places lying exclusively in the home State or in the home State and outside the State if such circular tours are in the list approved by the tourist department of the home State to visit places of tourist, historical or religious importance and the tour is duly advertised before hand:

[Provided that where such tourist vehicle is registered in the National Capital Region, it shall not operate circular tours of places lying exclusively in the National Capital Region unless it conforms to the mass emission standards [(Bharat Stage-IV) specified in sub-rule (15) of rule 115]

[Inserted by GSR 37(E), dated 20.1.2009 (w.e.f. 20.1.2009).]

.]

(5)

The permit holder or his authorized agent shall issue a receipt to the hirer and the counterfoil of the same shall be kept available with him and produced on demand to the officers empowered to demand documents by or under the Act.

(6)

The tourist vehicle shall not be parked on any bus stand used by stage carriage and shall not operate from such bus stand.

(7)

[The tourist vehicle shall exhibit the word "Tourist" within a circle of sixty centimetres diameter in a contrast colour on both sides of the vehicle, so as to be visible clearly.]

[Substituted by Notification No. G.S.R. 586 (E) dated 25.7.2012 (w.e.f. 2.6.1989)]

(8)

The permit holder shall display in the front top of the tourist vehicle a board in yellow with letters in black with the inscription Tourist permit valid in the State(s) of in English and Hindi and also, if he so prefers, in regional language of the home State.

(9)

The permit holder shall not operate the tourist vehicle as a stage carriage.

(10)

The permit holder shall maintain a day-to-day logbook indicating the name and address of the permit holder and the registration mark of the vehicle, name and address of the driver with the particulars of his driving license and the starting and destination points of the journey with the time of departure and arrival and the name and address of the hirer.

(11)

The permit holder shall furnish once in every 3 months the information contained in condition (10) to the State Transport Authority which granted the permit and the logbook shall be preserved for a period of 3 years and shall be made available to the said authority on demand along with the records referred to in conditions (2) and (4).

Explanation. - In this rule, home State means the State which has granted the permit under sub-section (9) of section 88. 85.

-A. The following shall be the additional conditions of every tourist permit in respect of motor cabs.

(1)

The words "Tourist vehicle" shall be painted on both the sides of the vehicle within a circle of twenty-five centimetres diameter.

(2)

A board with the inscription "Tourist permit valid in the State(s) of....." in black letters in yellow background shall be displayed in the front of the vehicle above the registration number plates:

[Provided that this rule shall not apply to motor cabs covered under the Rent a Cab Scheme, 1989.]

[Added by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

National permits

86.

Application for national permit.

- An application for the grant of a national permit shall be made in Form 48 to the authority referred to in section 69.

87.

Form, contents and duration of authorisation.

(1)

An application for the grant of an authorisation for a national permit shall be made in Form 46 and shall be accompanied by a fee of [Rs. 1000]

[Substituted by G.S.R. 386(E), dated 7th May, 2010.]

per annum in the form of a bank draft.

[(2) Every authorisation shall be granted in Form 23-A, in case the certificate of registration is issued on Smart Card or in Form 47, in case the authorisation is in paper document, subject to payment of a consolidated fee of rupees fifteen thousand per annum to be deposited in the national permit account for the permit granted to operate throughout the territory of India;

[Substituted by GSR 386 (E), dated 7.5.2010.]

(2A)

The consolidated fee deposited in the national permit account shall be distributed by the Central Government among the States and Union territories on pro rata basis as per the following specification, namely :-

Percentage share of nth State/ Union territory = $\frac{\text{Total consolidated fee received by nth State/ Union territory in the base year}}{\text{Total consolidated fee received by all the State Union territories in the base year where national permit is in operation}} \times 100$

Note:- The base year shall be the average of the latest three financial years and the share of the States and Union territories shall be notified by the Central Government from time to time.

Explanation. - For the purpose of sub-rule (2) and sub-rule (2A), the "national permit account" means an account established by the Central Government and notified in the Official Gazette.]

(3)

The period of validity of an authorisation shall not exceed one year at a time [* * *]

[The words 'and shall expire on the 31st day of March of the year' omitted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

88.

[Age of motor vehicle for the purpose of national permit.

[Rule 88 substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(1)

No national permit shall be granted in respect of a goods carriage, other than multiaxle vehicle, which is more than [twelve years] old at any point of time.

(2)

No national permit shall be granted for a multiaxle goods carriage which is more than fifteen years old at any point of time.

(2A)

[No national permit shall be granted for a puller tractor which is more than fifteen years old at any point of time:

Provided that the national permit may be extended for another period of five years subject to certificate of fitness granted by the manufacturer or a chartered engineer, in case the manufacturer ceases to operate in India.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(3)

A national permit shall be deemed to be invalid from the date on which a goods carriage covered by the permit completes fifteen years in case of a multiaxle goods carriage and [twelve years]

[Substituted by G.S.R. 799(E), dated 30-12-1993, for 'nine years' (w.e.f. 30-12-1993).]

where the vehicle is other than a multiaxle goods carriage, unless such goods carriage is replaced.

Explanation. - For the purpose of this rule, the period of [twelve years]

[Substituted by G.S.R. 799(E), dated 30-12-1993, for 'nine years' (w.e.f. 30-12-1993).]

or fifteen years, as the case may be, shall be computed from the date of initial registration of the motor vehicle covered under its permit or the prime mover in case of an articulated vehicle.]

(4)

[No national permit shall be granted in respect of a multiaxle trailer approved to carry a gross vehicle weight of more than 50 tonnes, which is more than 25 years old at any point of time, the period of 25 years being computed from the date of initial registration of the said trailer.

Explanation. - For the purpose of this rule, multiaxle trailer means a trailer having more than two axles.]

[Inserted by G.S.R. 221(E), dated 28-3-2001 (w.e.f. 28-3-2001)]

(4A)

[No national permit shall be granted in respect of a modular hydraulic trailer, which is more than twenty five years old at any point of time, the period of twenty five years being computed from the date of initial registration of the said modular hydraulic trailer:

Provided that the national permit may be extended for another period of five years subject to certificate of fitness granted by the manufacturer or a chartered engineer or approving authority, in case the manufacturer ceases to operate in India:

Provided further that the national permit shall be valid irrespective of the combination of modular hydraulic trailers subject to the condition that each individual modular hydraulic trailer is having valid national permit.

Explanation. - For the purposes of this section, "national permit" means a permit issued to ply the motor vehicle under this section, throughout the territory of India.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(5)

[A national permit shall be in such security printed watermark paper and shall carry such hologram as the State Government or the State Transport Authority, as the case may be, issuing such permit, may specify:

Provided that the use of such security printed watermark paper carrying such hologram shall come into force on or before six months from the date of commencement of the Central Motor Vehicles (Third Amendment) Rules, 2002.]

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

89.

[* * *]

[Rule 89 omitted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001). Earlier Rule 89 was inserted GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000). Before that Rule 89 was omitted by GSR 684(E), dated 5.10.1999 (w.e.f. 22.10.1999).]

90.

Additional conditions for national permit.

- The national permit issued under sub-section(12) of section 88 shall be subject to the following additional conditions, namely:

(1)

[All motor vehicles other than a trailer or modular hydraulic trailer]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

plying under a national permit shall be painted in dry leaf brown colour with thirty centimetres broad white borders and the words National permit shall be inscribed on both sides of the vehicle in bold letters within a circle of sixty centimetres diameter:

Provided that the body of a tanker carrying dangerous or hazardous goods shall be painted in white colour with a dry leaf brown ribbon of 5 centimetres width around in the middle at the exterior and that of the drivers cabin in orange colour.

(2)

A board with the inscription National permit valid in the State(s) of with blue letters on white background shall be carried in front top of [such vehicles other than a trailer or modular hydraulic trailer for which the same shall appear on both sides of the vehicle]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

.

(3)

No such vehicle shall carry any goods without a bill of lading in Form 50.

(4)

The vehicle shall have a minimum of two drivers and shall be provided with a seat across its full width behind the drivers seat providing facility for the spare driver to stretch himself and sleep:

[Provided that this sub-rule shall apply to light motor vehicle and medium goods vehicles only from a date to be notified by the Central Government.]

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(5)

The vehicle shall at all times carry the following documents and shall be produced on demand by an officer empowered to demand documents by or under the Act, namely:

(i)

Certificate of fitness,

(ii)

Certificate of insurance,

(iii)

Certificate of registration,

(iv)

National permit,

(v)

Taxation certificate,

(vi)

Authorisation.

(6)

The vehicle shall be subject to all local rules or restrictions imposed by a State Government.

(7)

The vehicle shall not pick up or set down goods between two points situated in the same State [other than the home State]

[Inserted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

:

[Provided that where such vehicle is registered in the National Capital Region, it shall not pick up or set down goods between two points situated in the National Capital Region unless it conforms to the mass emission standards [(Bharat Stage-IV) specified in sub-rule (15) of rule 115]

[Inserted by GSR 37(E), dated 20.1.2009 (w.e.f. 20.1.2009).]

.]

Chapter V

Construction, Equipment and Maintenance of Motor Vehicles

Preliminary

91.

Definitions.

- In this Chapter, unless the context otherwise requires,

(a)

class label, in relation to any dangerous or hazardous goods, means the class label specified in column 3 of the Table to rule 137;

(b)

consignor, in relation to dangerous or hazardous goods intended for transportation by a goods carriage, means the owner of such dangerous or hazardous goods;

(c)

dangerous or hazardous goods, means the goods of dangerous or hazardous nature to human life specified in Tables I, II, and III to rule 137;

(d)

emergency information panel, means the panel specified in rule 134;

(e)

primary risk, in relation to any dangerous or hazardous goods, means the most potent risk which such goods give rise to;

(f)

subsidiary risk, in relation to any dangerous or hazardous goods, means the subsidiary risk which such goods are likely to give rise to in addition to the primary risk.

92.

General.

(1)

No person shall use or cause or allow to be used in any public place any motor vehicle which does not comply with the provisions of this Chapter:

[Provided that nothing contained in this rule shall apply to vehicles manufactured prior to the coming into force of the Central Motor Vehicles (Amendment) Rules, 1993.]

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(2)

Nothing in this rule shall apply to a motor vehicle

(a)

which has been damaged in an accident or to a vehicle stopped or impeded owing to shortage of fuel or other temporary defects while at the place at which the accident or defect occurred;

(b)

which is defective or damaged and is being removed to the nearest place of repair or disposal; or

(c)

which is more than fifty years old from the date of its registration and is being driven for taking part in a vintage car rally:

Provided that where a motor vehicle can no longer remain under the effective control of the person driving, the same

shall not be used in a public place except by towing.

[Explanation.

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

- For the purposes of this rule, motor vehicle includes construction equipment vehicle.]

(3)

[Testing of components conforming to standards in lieu of Indian Standards: Whenever apart, component or assembly is used in a vehicle complying with standards in lieu of those notified in these rules such as an international standard (for example, EEC/ECE/IEC/ISO or such other standards) or a foreign national standard, permission for use of such parts, component or assembly complying with such standards shall be approved by the Central Government.

In such cases, the compliance of parts, components or assemblies to such international or foreign national standards will be established for the purpose of rule 126, by a certificate of compliance issued by an authorised certifying agency or by an accredited certifying agency of the country of origin for such international or foreign national standards and vetted by a testing agency as referred to in rule 126.]

[Inserted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

Overall dimension

93.

Overall dimension of motor vehicles.

(1)

The overall width of a motor vehicle, measured at right angles to the axis of the motor vehicle between perpendicular planes enclosing the extreme points, [shall not exceed 2.6 metres.]

[Substituted by GSR 221(E), dated 28.3.2001, for 'shall not exceed'(w.e.f. 28.3.2001).]

[* * *]

[Clauses. (i) and (ii) omitted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).]

[* * *]

[Clauses. (i) and (ii) omitted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).]

Explanation. - For purposes of this rule, a rear-view mirror, or guard rail or a direction indicator [rub-rail(rubber beading) having maximum thickness of 20 mm on each side of the body]

[Substituted by GSR 221(E), dated 28.3.2001, for '(when in operation)'(w.e.f. 28.3.2001).]

shall not be taken into consideration in measuring the overall width of a motor vehicle.

[(1-A) The overall width of a construction equipment vehicle, measured at right angles to the axis of the construction equipment vehicle between perpendicular planes enclosing the extreme points, shall not exceed 3 metres while in the travel mode and such construction equipment vehicle [shall be painted by yellow and black zebra stripes on the portion of the width that exceeds 2.6 metres]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

on the front and rear sides duly marked for nighttime driving/parking suitably by red lamps at the front and rear:]

[Provided that the zebra stripes need not be used on attachments.]

[Inserted by GSR 116(E), dated 27.2.2002 (w.e.f. 27.8.2002).]

(1B)

[The overall width of a combine harvester measured at right angles to the axis of the combine harvester between perpendicular planes enclosing the extreme points shall not exceed 3.3 meters while in the travel mode; and such combine harvesters shall be painted by yellow and black zebra stripes on the portion of the width that exceeds 2.6 meters on the front; and rear sides duly marked for night time driving and parking suitably by white or amber lamps at the front and red lamps at the rear:

Provided that the zebra stripes need not be used on attachments, if any.

(1C)

The overall width of modular hydraulic trailer, measured at right angles to the axis of the modular hydraulic trailer between perpendicular planes enclosing the extreme points shall not exceed three metres.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(2)

[The overall length of a motor vehicle other than a trailer shall not exceed

(i)

in the case of motor vehicle other than transport vehicle having not more than two axles, 6.5 metres;

(ii)

in the case of transport vehicle with rigid frame having two or more axles, 12 metres;

(iii)

in the case of articulated vehicles having more than two axles, 16 metres;

[Provided that on and after the 1st April 2017, in case of articulated vehicles, engaged by automobile manufacturers to carry motor vehicles from their factories to different sale outlets in the country, 18.75 meters;]

[Sub-Rule(2) substituted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).]

(iv)

in the case of truck-trailer or tractor-trailer combination, 18 metres;

[Provided that, on and after the 1st April 2017, in case of truck-trailer or tractor-trailer vehicles engaged by automobile manufacturers to carry motor vehicles from their factories to different sale outlets in the country, 18.75 meters:

Provided further that on and after the 1st April 2017, articulated or truck-trailer or tractor-trailer vehicles engaged by automobile manufacturers to carry motor vehicle from their factories to different sale outlets in the country, shall be provided with a sliding inspection window on the container body, to allow verification of motor vehicles carried in the container and the sliding inspection window shall be minimum of 400 millimeters in length and 300 millimeters in height and at least one sliding inspection window shall be fitted to the middle third of the vehicle, the foremost sliding inspection window being not further than 3 meters from the front and in the case of trailers, account shall be taken of the length of the drawbar for the measurement of this distance and the distance between two adjacent sliding inspection windows shall not exceed 4 meters and the height of the upper edge of the sliding inspection window shall not be more than 1.8 meters from the ground;]

[Inserted by Notification No. G.S.R. 963 (E), dated 7.10.2016 (w.e.f. 2.6.1989).]

(v)

in the case of 3axle passenger transport vehicles, 15 metres;

(va)

[in the case of a puller tractor having three or more axles, ten meters;

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(vb)

in the case of a modular hydraulic trailer, any single module with maximum eight axle rows shall not exceed nineteen metres;]

(vi)

in the case of single articulated (vestibule type) passenger transport vehicle, 18 metres (Please see the conditions given in note below);

(vii)

in the case of double articulate passenger transport vehicles, 25 metres (Please see the conditions given in note below).

Note .In the case of single articulated passenger transport vehicles of 18 metres length and double articulated passenger transport vehicles up to 25 metres, permission of the State Government shall be obtained regarding their plying on selected routes depending upon local road conditions, width, manoeuvrability of the vehicle in traffic, as deemed fit. These passenger transport vehicles will also be required to have a closed circuit TV system for proper visibility in and around the passenger transport vehicle by the driver to maintain safety. Intercom system shall also be provided in such passenger transport vehicle. In addition,the standing passenger will be allowed only on the lower deck of double articulated passenger transport vehicle.]

(viii)

[in the case of E-rickshaw and E-cart, shall not exceed 1.8 metres.]

[Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

(3)

In the case of an articulated vehicle or a tractor-trailer combination specially constructed and used for the conveyance of individual load of exceptional length,

(i)

if all the wheels of the vehicle are fitted with pneumatic tyres,or

(ii)

if all the wheels of the vehicle are not fitted with pneumatic tyres, so long as the vehicle is not driven at a speed exceeding twenty-five kilometres per hour, the overall length shall not exceed 18 metres.

Explanation. - For the purposes of this rule overall length means the length of the vehicle measured between parallel planes passing through the extreme projection points of the vehicle exclusive of

- (i)
a starting handle;
- (ii)
any hood when down;
- (iii)
any fire-escape fixed to a vehicle;
- (iv)
any post office letter-box, the length of which measured parallel to the axis of the vehicle, does not exceed 30 centimetres;
- (v)
any ladder used for loading or unloading from the roof of the vehicle or any tail or indicator lamp or number plate fixed to a vehicle;
- (vi)
any spare wheel or spare wheel bracket or bumper fitted to a vehicle;
- (vii)
any towing hook or other fitment which does not project beyond any fitment covered by clauses (iii) to (vi).

[(3-A) [The overall length of the construction equipment vehicle and combine harvester]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

, in travel shall not exceed 12.75 metres :

Provided that in the case of construction equipment vehicle with more than two axles, the length shall not exceed 18 metres.

[Provided further that in case of combine harvester exclusively used for harvesting sugarcane, the overall length in travel shall not exceed 15 metres.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

Explanation. - For the purposes of this sub-rule overall length means the length of the vehicle measured between parallel planes through the extreme projection points of the vehicle, exclusive of

- (i)
any fire-escape fixed to a vehicle;
- (ii)
any ladder used by the operator to board or alight the vehicle;
- (iii)
any tail or indicator lamp or number plate fixed to a vehicle;
- (iv)
any sphere wheel or sphere wheel bracket or bumper fitted to a vehicle;
- (v)
any towing hook or other fitments;
- (vi)
any operational attachment on front, rear or carrier chassis of construction equipment vehicle in travel mode.]

(3B)
[The overall length of puller tractor and modular hydraulic trailer combination shall not exceed 29 metres:

Provided that movement of larger combinations with more than eight axle lines shall be subject to prior approval of the concerned authorities.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(4)
The overall height of a motor vehicle measured from the surface on which the vehicle rests,

- (i)

in the case of a vehicle other than a double-decked [transport vehicle]

[Substituted by GSR 589(E), dated 16.9.2005, for 'motor vehicle'(w.e.f. 16.9.2006).]

, shall not exceed 3.8 metres;

(ii)

[in the case of a double decked transport vehicle, shall not exceed 4.75 metres;

[Clause (ii) substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

(ii-a) in the case of tractor-trailer goods vehicle, shall not exceed 4.20 metres;]

(iib)

[in the case of modular hydraulic trailer or combination of such modular hydraulic trailers, shall not exceed 4.75 metres;]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(iii)

[in the case of a laden trailer carrying ISO series 1 Freight Container or in the case of fabricated containerised motor vehicle, shall not exceed 4.52 metres]

[Clause (iii) substituted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

:

Provided that the provisions of clauses (i) to (iii) shall not apply to fire-escape tower wagons and other special purpose vehicles exempted by general or special order of registering authority.

[(4-A) The overall height of a construction equipment vehicle [or combine harvester]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

measured from the surface on which the vehicle rests shall not exceed 4.75 metres, while in the travel mode:

Provided that the provisions of this sub-rule shall not apply to any other special purpose attachment to the construction equipment vehicle [or combine harvester]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

exempted by general or special order of the registering authority.]

(5)

The overhang of a tractor [or puller tractor]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall not exceed 1.85 metres.

(6)

[The overhang of the motor vehicle [other than a tractor and construction equipment vehicle]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[tractor, construction equipment vehicle and combine harvester]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall not exceed 60% of the wheel base.

Explanation I. - For the purpose of this rule wheel base means,

(a)

in the case of vehicles with only two axles, the distance measured horizontally and parallel to the longitudinal axis of the vehicle, between the centre points of the front axle and rear axle;

(b)

in case of a vehicle having only three axles, and the front axle is only the steered axle, the distance measured horizontally and parallel to longitudinal axis of the vehicle between the centre of the front axle and centre point between the two rear axles;]

(c)

[in case of vehicles having more than three axles, and fitted with or without retractable axle, wheelbase shall be the distance measured between the centre of the front-most axle and the centre point of rear combination of non-steered axles.

[Substituted by Notification No. G.S.R. 625 (E) dated 8.8.2012 (w.e.f. 2.6.1989)]

Note:

(i)

'retractable axle' means an axle which can be raised or lowered by the axle-lift device in accordance with first indent;

(ii)

'axle-lift device' means a device permanently fitted to a vehicle for the purpose of reducing or increasing the load on the axle(s), according to the loading conditions of the vehicle, either by raising the wheels clear off the ground or lowering them to the ground or without raising the wheels off the ground (e.g., in the case of air suspension systems, or other systems), in order to reduce the wear on the tyres when the vehicle is not fully laden, or make starting (moving off) on slippery ground easier for motor vehicles or vehicle combinations, by increasing the load on the driving axle.];

[Explanation II]

[Renumbered by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

. - For the purpose of this rule, overhang means the distance measured horizontally and parallel to the longitudinal axis of the vehicles between two vertical planes at right angles to such axis passing through the two points specified hereunder:

(A)

The rearmost point of the vehicle exclusive of

(i)

any hood when down;

(ii)

any post office letter-box, the length of which measured parallel to the longitudinal axis of the vehicle, does not exceed thirty centimetres;

(iii)

any ladder forming part of a turn-table fire-escape fixed to a vehicle;

(iv)

any ladder used when the vehicle is at rest for loading or unloading from the roof of the vehicle, or any tail lamp or number plate fixed to a vehicle;

(v)

any spare wheel or spare wheel bracket fitted to a vehicle;

(vi)

any luggage carrier fitted to a motor vehicle constructed solely for carriage of passengers and their effects and adapted to carry not more than seven passengers exclusive of the driver;

(vii)

any towing hook or other fitment which does not project beyond any fitment mentioned in clauses (ii) to (vi);

(viii)

[any mounted implement on a 3-point linkage of a tractor:]

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

Provided that in the case of a stage carriage:

(a)

the projection of any bumper or advertisement panel fitted at the rear of the vehicle shall not exceed fifteen centimetres;

(b)

the projection in respect of an advertisement panel shall not be such as to obstruct either the vision from the rear view mirror or project through the emergency exit at the rear or both;

(B)

(i)

In the case of a vehicle having only two axles, one of which is not a steering axle, the centre point of that axle; or

(ii)

[in the case of a vehicle having only three axles and the front axle is the only steering axle, the centre point of the rearmost axle, irrespective of rear axle(s) being 'fixed' or 'retractable (lift axle)'.]

[Substituted by Notification No. G.S.R. 625 (E) dated 8.8.2012 (w.e.f. 2.6.1989)]

;

(iii)

in the case of any vehicle registered in India before the commencement of these rules it shall suffice if the overhang does not exceed 7/24ths of the overall length of the vehicle;

(iv)

[in the case of a vehicle having only three axles where two front axles are steering axles, the centre point of the

rearmost axle, irrespective of rear axle(s) being 'fixed' or 'retractable (lift axle)'.]
[Substituted by Notification No. G.S.R. 625 (E) dated 8.8.2012 (w.e.f. 2.6.1989)]

;

(v)

[in the case of a vehicle having four or more than four axles; the centre point of the rearmost axle, irrespective of rear axle(s) being 'fixed 'or 'retractable (lift axle)'.]

[Substituted by Notification No. G.S.R. 625 (E) dated 8.8.2012 (w.e.f. 2.6.1989)]

(vi)

in any other case, a point situated on the longitudinal axis of the vehicle such that a line drawn from it at right angle to that axis will pass through the centre of the minimum turning circle of the vehicle.

[(6-A) The overhang of the construction equipment vehicle [or combine harvester]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

shall not exceed 7.5 metres in front or rear while in the travel mode.

[Provided that in case of a combine harvester exclusively used for harvesting sugarcane, the overhang shall not exceed 8.5 meters in rear while in travel mode.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

Explanation. - For the purpose of this sub-rule, overhang means the length/height measured horizontally and parallel to the longitudinal axis of the construction equipment vehicle [or combine harvester]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

between two vertical planes at right angles to such axis passing through

(i)

the front most point of the vehicle and the centre point of the front axle, for the front overhang,

(ii)

the rearmost point of the vehicle and centre point of the rear axle, for the rear overhang, exclusive of the parts or fitments mentioned at items (i) to (vi)of the Explanation to sub-rule (3-A).]

(7)

□

[Renumbered by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

No part of the vehicle other than a direction indicator, when in operation, or a driving mirror, shall project laterally more than 355 millimetres beyond the centre line of the rear wheels, in the case of a single rear wheels or more than 152 millimetres beyond the extreme outer edge of the outer tyres, in the case of dual rear wheels:

[* * *]

[Proviso omitted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004). Earlier proviso was added by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

Provided that the State Government or any authority authorised in this behalf by the State Government, if it is satisfied that it is necessary because of the nature of any road or bridge or in the interest of public safety, may prohibitor restrict the operation of a motor vehicle in a specified route or area unless such vehicle complies with the requirements specified by the State Government for such route or area.

[(7-A) No part of the construction equipment vehicle [or combine harvester]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

in travel mode other than a direction indicator, or a driving mirror, shall project laterally more than 300 millimetres beyond the extreme outer edge of the tyres or wheel drums regardless of single or dual tyres or rollers.]

(8)

□

[Renumbered by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

No motor vehicle shall be loaded in such a manner that the load or any part thereof extends,

(i)

laterally beyond the side of the body;

(ii)

to the front beyond the foremost part of the load body of the vehicle;

(iii)

to the rear beyond the rear most part of the vehicle;

(iv)

to a height beyond the limits specified in sub-rule (4):

Provided that clause (iii) shall not apply to a goods carriage when loaded with any pole or rod or indivisible load so long as the projecting part or parts do not exceed the distance of one metre beyond the rear most point of the motor vehicle.

[93-A. Overall dimension for agricultural tractors.

[Inserted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

(1)

The overall width of the agricultural tractor shall not exceed 2.6 metres.

(2)

The overall length of the agricultural tractor shall not exceed 6.5 metres.

(3)

The overall height of the agricultural tractor shall not exceed 3.8 metres.

(4)

The overhang of the agricultural tractor shall not exceed 1.85 metres :

Provided that lateral projection up to 700 millimetres beyond the central line of the rear wheel shall be permitted.]

[93-B. Overall dimension for power tillers.

[Rule 93-B inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

(1)

The overall length of the power tiller with a riding attachment shall not exceed 3.5 metres.

(2)

The overall width of the power tiller with a riding attachment including case wheelers shall not exceed 1.5 metres.

(3)

The maximum overall height of the power tiller shall not exceed 2.0 metres.

(4)

The overall length of the power tiller when coupled to a trailer shall not exceed 6.0 metres.

(5)

The maximum overall width of the power tiller when coupled to a trailer shall not exceed 1.7 metres.

(6)

The maximum overall height of the power tiller when coupled to a trailer shall not exceed 2.0 metres.]

93C.

[Overall dimension for Airport Passenger Bus (Tarmac Bus).

[Inserted by Notification No. G.S.R. 594(E), dated 13.6.2016 (w.e.f. 2.6.1989).]

- (1) The Overall Length of the Airport Passenger Bus shall not exceed fifteen meters.

(2)

The Overall Width of the Airport Passenger Bus shall not exceed 3.2 meters.

Explanation. - For the purposes of this rule, the term "Airport Passenger Bus (Tarmac Bus)" means the Bus having doors on both sides which is exclusively used for the carrying the passengers from airport terminal to and from the aircraft and plying on the air side on the Air port terminal with maximum speed not exceeding thirty kilometre per hour.]

Size, nature and condition of tyres

94.

Condition of tyres.

- [(1) [Every motor vehicle including agricultural tractor and its trailer]

[Substituted by G.S.R 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

[and the combine harvester and modular hydraulic trailers]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall be fitted with pneumatic tyres and every construction equipment vehicle, other than steel drum rollers of vibratory compactors or compactor rollers or road roller or a track laying vehicle, shall be fitted with pneumatic tyres or solid rubber tyres.]

(2)

The pneumatic tyres of [a motor vehicle including agricultural tractor and its trailer]

[Substituted by GSR 111(E), dated 10.2.2004, for 'a motor vehicle' (w.e.f. 10.8.2004).]
[and the combine harvester]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall be kept properly inflated and in good and sound condition.

(3)

For the purpose of sub-rule (2), a tyre shall not be deemed to be of good and sound condition if

(i)

any of the fabric of its casing is exposed by wear of the tread or by any unvulcanised cut or abrasion in any of its parts;
or

(ii)

it shows signs of incipient failure by local deformation or swelling; or

(iii)

it has been patched or repaired by an outside gaiter or patch other than a vulcanised repair;

(iv)

[the Non-Skid Depth (NSD), shall not be less than 0.8 mm in the case of two-wheeler and three-wheeler and 1.6 mm in the case of other motor vehicles, below the Tread Wear Indicator (TWI) embedded in tyres at the time of manufacture:]

[Inserted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.9.2001).]

Provided that the requirement specified in clause (iii) shall not apply to a temporary repair effected to enable the vehicle to be moved to the nearest place where the tyre can be repaired or replaced:

Provided further that where a motor vehicle, other than road roller or track laying vehicle, is not fitted with pneumatic tyres, it shall not be used in a public place unless it is fitted with shoes or other suitable device so that plying of such vehicle does not damage the road:

[Provided also that the requirements of the Non-Skid Depth (NSD) and Tread Wear Indicator (TWI) specified in clause (iv) shall not be applicable for the agricultural tractor tyres.]

[Inserted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

95.

Size and ply rating of tyres.

- [(1) The tyres including radial tyres used on all motor vehicles manufactured or imported on and after the 1st day of April, 2006, other than agricultural tractors, construction equipment vehicles [or a combine harvester]

[Sub-Rule (1) substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

and power tillers shall comply with the requirements specified in is: 15627-2005 or [IS: 15633-2005 or IS: 15636-2005 applicable]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 1.4.2009).]

:

Provided that the selection and fitment of tyres for motor vehicles manufactured or imported on and from the 1st day of April, 2006 shall be in accordance with AIS:050:2004 in the case of two and three-wheelers and AIS:051:2004 in the case other motor vehicles, till such time the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986):

Provided further that Central Institute of Road Transport, Pune and any other agency which may be authorised by Central Government from time to time can carry tests for verification against AIS:044:2004 for tyres for the purposes of rule 126.]

[* * *]

[Sub-rule (2) Omitted by Notification No. G.S.R. 76(E), dated 31.1.2000 (w.e.f. 2.6.1989).]

[[(2-A) The size of the tyres of a construction equipment vehicle]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

specified in column (1) of the Table below shall have a ply rating specified in the corresponding entry in column (2) of the said Table in respect of maximum weight permitted to be carried by such tyre specified in the corresponding entry in column (3) thereof:

Provided that the maximum safe load for single axle with two or more tyres shall not exceed 10.2 tonnes.]

Off-The-Road Service Conventional and

Wide Base Diagonal Ply Tyres

Table

AGRICULTURAL TRACTOR DRIVE WHEEL

Tyre size Designation

Ply rating

Maximum weight permitted to be carried (Kgs.)

8.3/8-24

4

6

630

825

8.3/8-32

4

6

730

925

11.2/10-28

4

6

8

900

1120

1320

12.4/11-24

4

6

8

950

1215

1450

12.4/11-28

4

6

8

10

12

1030

1285

1550

1600

1650

12.4/11-36

4

6

1150

1450

12.4/11-38

4

6

8

1180

1500

1750

13.6/12-28

4

6

8

10

12

1120

1450

1650

1750

1800

16.9/14-28

6

8

10

12

1850

2180

2430

2725

ROAD GRADER

Tyre size Designation

Ply rating

Maximum weight permitted to be carried (Kgs.)

13.00-24

8

12

2040

2485

14.00-24

12

3015

OFF THE ROAD HAULAGE SERVICE TYRES

Tyre size Designation

Ply rating

Maximum weight permitted to be carried (Kgs.)

12.00-20

14

16

2650

2900

12.00-24/25

14

16

3000

3250

13.00-24/25

18

3875

14.00-24/25

16
20
24
4000
4625
5150
16.00-24/25

20
24
28
5450
6000
6700
18.00-24/25

12
16
20
24
28
32
4750
5600
6500
7300
8000
8750

WIDE BASE

Tyre size Designation

Ply rating

Maximum weight permitted to be carried (Kgs.)

23.5-25

12
16
20
24
5300
6150
7300
8000

Note.- [1.]

[The existing note numbered as '1' by GSR 116(E), dated 27.2.2002 (w.e.f. 27.8.2002).]

The load rating for tyres not covered by the above Table may be notified by the Central Government as and when such tyres are introduced on construction equipment vehicles, and until these are notified, the provisional load rating declared by the construction equipment vehicle manufacturer may be certified by the certifying test agency referred to in rule 126.]

2. [The maximum axle loading capacities shall be verified based on the safe loading capacities of the tyres. In cases where the axle load exceed 10.2 tonnes, the vehicle manufacturer shall ask the user to seek the prior permission of the concerned Regional or State Transport Authorities in whose jurisdiction the construction equipment vehicle is expected to ply depending upon the conditions of roads/bridges, where deemed fit. Such construction equipment vehicles whose axle load exceeds 10.2 tonnes shall display permanently on the vehicle a placard indicating NOT FOR PLYING ON ROADS. These conditions shall be mentioned in the certificate, issued by the testing agencies referred to in the rule

126, where the axle load exceeds 10.2 tonnes.]

[Inserted by GSR 116(E), dated 27.2.2002 (w.e.f. 27.8.2002).]

(3)

No tyre shall have a ply rating more than 20, for applications of on-highway and such ply rating shall not be prescribed by either vehicle manufacturer or employed by vehicle user on this class of vehicle.

(4)

Check on sub-rule (3) of rule 95 on commercial vehicles will be conducted by the authority indicated in sub-rule (1) of rule 126, while conducting the checks.

(5)

[Every tyre manufacturer shall, in addition to any trade mark or size of the tyre, also emboss on it the following, namely:

(i)

Week and year code or month and year code of manufacture; and

(ii)

maximum load carrying capacity.]

(6)

[In the case of Indian manufactured vehicles and imported vehicles (new and old), the size of tyres if included in the International Standards, namely, ECE, JATMA, ETRTO and T RA besides Bureau of Indian Standards may also be accepted under this rule:

Provided that the following conditions shall be complied with :

(i)

that testing agencies referred to in rule 126 shall satisfy themselves about the load and speed rating of the tyre with reference to the Indian conditions;

(ii)

that the test report/certificate issued by the testing agency of the country of origin shall be verified for acceptance by the testing agency referred to in rule 126;

(iii)

that for tubeless tyres fitted on imported vehicles confirming to conditions (i) and (ii) shall also be allowed.]

(7)

[Temporary use spare wheel or tyre and Run Flat Tyre for vehicles of categories M1 and N1, if they are different from the normal tyre used on the vehicle shall conform to AIS 110: 2009, as amended from time to time, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

[Inserted by Notification No. G.S.R. 625 (E) dated 8.8.2012 (w.e.f. 2.6.1989)]

[95-A. Size and ply rating of tyres for agricultural tractor.

[Inserted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

(1)

The tyre of the agricultural tractor shall have load carrying capacity as may be specified by the tyre manufacturer, subject to the condition that the maximum load specified by the agricultural tractor manufacturer shall not be greater than the load permitted by the tyre manufacturer.

(2)

The agricultural tractor manufacturer shall select only that rim size as recommended by the tyre manufacturer.

Note.- For compliance to the above two sub-rules, the following shall be referred to IS:13154-1991 as amended from time to time Tyres for agricultural tractor, implements and power tillers. In case a particular size of tyre is not listed in IS: 13154-1991, any equivalent International Standard like Economic Commission of Europe (ECE), Japanese Automotive Tyre Manufacturers Association (JATMA), European Tyre and Rim Technical Organisation (ETRTO), The Tyre and Rim Association Inc. (T RA) and Indian Tyre Technical Advisory Committee (ITTAC), etc., shall be accepted.]

[95-B. Size and ply rating of tyres for power tillers.

[Rule 95-B inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

(1)

The tyre should have load carrying capacity as specified by the tyre manufacturer, however, the maximum load specified by the power tiller manufacturer shall not be greater than that permitted by the tyre manufacturer.

(2)

The power tiller manufacturer shall select there commended/preferred rim sizes only, as suggested by the tyre manufacturer.

Note.- For compliance to this rule, the following standards shall be referred to, namely:

(i)

IS:13154 -1991,as amended from time to time-Tyre for agricultural tractor, implement and power tillers.

(ii)

In case a particular size of tyre is not listed in IS:13154 -1991, as amended from time to time, any equivalent International Standard like ECE, JATMA, ETRTO, TNRA,ITTAC, etc.]

[95C. Size and ply rating of tyres for modular hydraulic trailers - (1) The tyres including radial tyres used on modular hydraulic trailers shall be in accordance with IS 15636: 2005 as amended from time to time.

(2)

The tyre of modular hydraulic trailers shall have load carrying capacity as specified by the tyre manufacturer, however, the maximum load specified by the modular hydraulic trailers manufacturer shall not be greater than that permitted by the tyre manufacturer.

(3)

The modular hydraulic trailer manufacturer shall select the recommended or preferred rim sizes only, as suggested by the tyre manufacturer and the wheel rims shall confirm to IS 9438:1980.

Note:- For compliance to this rule, any equivalent national or international standards such as Indian Standards (IS), Automotive Industry Standard (AIS), ECE (Economic Commission of Europe), Japan Automobile Tyre Manufacturers Association (JATMA), European Tyre and Rim Technical Organisation (ETRTO), Tyre and Rim Association Inc. (TRA), Indian Tyre Technical Advisory Committee (ITT'AC), etc., may be referred.

95D.

Limited road trials.

- The Hydraulic Modular Trailer with specified Gross Vehicle Weight or maximum load carrying capacity shall be subjected to minimum hundred kilometres run preferably on plain roads with speed less than ten kilometres per hour.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

Brakes, steering gears,safety glass and windscreen wipers

96.

Brakes.

- [(1) Every motor vehicle, other than a motor cycle, three-wheeled invalid carriage, trailer or a road roller shall be equipped with two independent and efficient braking systems, namely, the parking brake and foot operated service brake:

Provided that a motorcycle and three-wheeled invalid carriage shall be equipped with the independent and efficient braking systems, either both hand operated or one foot operated and the other hand operated.]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(2)

The braking system shall be of strength capable of stopping the vehicle within the distance specified in sub-rule (8) and of holding it at rest in all conditions and all such brakes at all time be properly connected and maintained in efficient condition.

[* * *]

[Proviso omitted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(3)

In every motor vehicle [other than agricultural tractors,]

[Added by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

the brakes operated by one of the means of operation shall act directly upon the wheel and not through the transmission gear.

(4)

[Every motor vehicle manufactured on and after the 1st day of April, 2006 shall have a braking system whose performance shall conform to the following Indian Standard, namely :

(i)

for [two wheelers, three wheelers, E-rickshaw and E-cart] IS:14664:1999, as amended from time to time.

(ii)

all motor vehicles, other than two-wheelers, three-wheelers, trailers, semi-trailers, construction equipment vehicles, [two wheelers, three wheelers, E-rickshaw and E-cart]

[Substituted for the words 'agricultural tractors and power tillers' by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

, IS:11852 (Part 1): 2001, 11852 (Part 2): 2001, 11852 (Part 3): 2001, 11852 (Part 4): 2001, 11852 (Part 5): 2001, 11852 (Part 6): 2001, 11852 (Part 7): 2001 and 11852 (Part 8): 2001, as amended from time to time:

[(4 A). Notwithstanding anything contained in clause (i) of sub-rule (4),-

(a)

New vehicle models of category L2 with;

(i)

engine capacity ? 125 cc;

(ii)

maximum continuous rated or net power ? 11kw; and

(iii)

power/weight ratio ? 0.1 kw/kg,

manufactured on and after the 1st April, 2018 shall be fitted with anti-lock braking system or combined braking system conforming to IS: 14664: 2010;

(b)

Existing vehicle models of category L2 with :

(i)

engine capacity ? 125 cc;

(ii)

maximum continuous rated or net power ? 11kw; and

(iii)

power/weight ratio ? 0.1 kw/kg,

manufactured on and after the 1st April, 2019 shall be fitted with anti-lock braking system or combined braking system conforming to IS: 14664: 2010:

Provided that all other category of two wheeled vehicles which does not fall in the criteria as mentioned above in clause (a) and (b) shall be fitted with anti-lock braking system conforming to IS: 14664: 2010 on and after the 1st April, 2018 for new vehicle models and on and after the 1st April, 2019 for existing vehicle models.]

[Inserted Notification No. G.S.R. 310(E), dated 16.3.2016 (w.e.f. 2.6.1989).]

[* * *]

[Omitted Proviso by Notification No. G.S.R. 225(E), dated 1.4.2015 (w.e.f. 2.6.1989)]

[Provided that]

[Substituted by Notification No. G.S.R. 225(E), dated 1.4.2015 (w.e.f. 2.6.1989)]

IS: 11852:2003 (Part 9) shall be applicable for vehicles manufactured on and after the 1st day of October, 2006 fitted with Anti-Lock Braking System.]

[Sub-Rule(4) substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

(4B)

[The motor vehicles of category M1 and M2 shall-

(i)

on and after the 1st April 2018, in the case of new models; and

(ii)

on and after the 1st April 2019, in the case of all models.

be fitted with Anti-lock braking systems as per IS: 15986:2015, specifications in case of Category M1 vehicles and per IS: 11852:2003 (Part -9), specifications in case of Category M2 vehicles.]

[Inserted by Notification No. G.S.R. 120 (E), dated 10.2.2017 (w.e.f. 2.6.1989).]

(5)

Except in the case of a motor cycle, the braking system or one of the braking systems of a motor vehicle shall be so constructed and maintained that it can be so set as effectively to prevent at least two, or in the case of a motor vehicle

having three wheels, at least one of the wheels from revolving when the vehicle is left unattended.

(6)

The braking system or part thereof which functions in the aforesaid manner shall be known as parking brake and where such a parking brake is designed to be operated by hand, it shall be known as hand-brake.

(7)

[(a) In the case of motor vehicles, other than three-wheelers of gross vehicle weight not exceeding 1000 kgs. and motor cycles, the service brake shall be acting on all the wheels of the vehicle.

(b)

In case of three-wheelers of gross vehicle weight not exceeding 1000 kgs. if the foot operated brake does not act on all the wheels, the following conditions shall be fulfilled, namely:

(i)

the foot operated brake shall act on the two wheels which are on the same axle, and

(ii)

in addition to the parking brake, there shall be an independent brake acting on the other wheel of the vehicle with an independent hand-operated control.

(c)

In the case of motor cycles, the braking system operated with the foot or left hand shall act at least on the rear wheel and the brake operated by right hand at least on the front wheel.

(d)

In the case of agricultural tractors, the braking system shall act as on both the rear wheels, either directly or through the transmission gear.]

(8)

[The service braking system in the case of vehicle other than three-wheelers and motorcycles, and the braking system operated by one of the means of operation other than the parking brake in the case of three-wheelers and motor cycles shall be capable to bring the vehicles to halt within the distance specified in the following Table when tested in accordance to the condition prescribed correspondingly in the Table. The test shall be conducted on a dry level hard road in good condition. During the test the accelerator control shall be fully released and in the case of vehicles with manual gear shifting control, the top gear and the clutch shall be engaged.]

[Substituted by G.S.R. 338(E), dated 26-3-1993 (w.e.f. 26-3-1993).]

Sl. No.

Type of vehicle

Load

Test speed (The speed at which the brake should be applied)(Kmph)

Type of brake

Stopping distance (m)

1.

All vehicles other than motor cycles, three-wheelers and agricultural tractors

Laden to the registered GVW or unladen

or Laden or Unladen

30

30

40

40

Foot operated service

"

"

"

13

21

21

21

2.
Motor cycles
Unladen
30
Foot or hand operated
21
3.
Three-wheelers including three-wheeler tractors for trailers
Unladen
30
Foot operated (brakes operating on at least two wheels)
13
4.
Agricultural tractors
Laden to test mass
25
Foot operated service
10
5.
All other than three-wheelers of engine capacity not exceeding 500cc, motor cycles and agricultural tractors
Laden to the registered GVW or unladen

30
40
30
40
-do-
-do-
-do-
-do-
12.7
15.0
9.3
12.0
6. [

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

Puller Tractors

GVW

20

Foot operated service

13]

For the purpose of this test for vehicles other than motor cycles the unladen means the vehicle is without any load and shall carry only the driver and another person for specific purpose of supervising the test, and the instruments, if any. In the case of motor cycles, the unladen means that vehicle will carry only the single rider and the measuring instrument, if any.

(9)

[The following category of vehicles shall be fitted with Anti-Lock Braking System conforming to IS:11852:2003 (Part 9):]

[Sub-Rule (9) inserted by G.S.R. 589(E), dated 16-9-2005 (w.e.f. 16-9-2005)]

(i)

N2 [***]

[omitted by notification no. 389(E) dated by 9.6.2014 (w.e.f. 1.10.2014)]

category of vehicles other than tractor-trailer combination manufactured on and after the 1st day of October, 2006 meant

for carrying hazardous goods and liquid petroleum gas;

(ii)
[new models of M3 and N3 categories of vehicles manufactured on and after the 1st April, 2015;]
[substituted by notification no. 389(E) dated by 9.6.2014 (w.e.f. 1.10.2014)]

(iii)
[existing models of M3 and N3 categories of vehicles manufactured on and after the 1st October, 2015]
[substituted by notification no. 389(E) dated by 9.6.2014 (w.e.f. 1.10.2014)]

(iv)
[the following categories of vehicles manufactured prior to the dates specified in clauses (ii) and (iii) shall be fitted with Anti-lock Braking System conforming to IS: 11852:2003 (Part 9)-
[Substituted by Notification No. G.S.R. 52 (E) dated 23.1.2015 (w.e.f. 2.6.1989)]

(a)
N3 categories of vehicles other than tractor-trailer combination manufactured on and after the 1st day of October, 2006 meant for carrying hazardous goods and liquid petroleum gas;

(b)
N3 categories of vehicles manufactured on and after the 1st day of October, 2007, that are double decked transport vehicles;

(c)
N3 categories of vehicles manufactured on and after the 1st day of October, 2007, that are used as tractor-trailer combinations;

(d)
M3 categories of buses that ply on All India Tourist Permit, manufactured on and after the 1st day of October, 2007.]
[96-A. Brakes for construction equipment vehicle.

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

(1)
Construction equipment vehicle with hydrostatic transmission shall employ either hand or foot operated hydrostatic braking system both for service and parking brake system acting at least on two wheels on the same axle or drum.]
[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(2)
The braking system shall be of a strength capable of stopping the vehicle within the distance specified in sub-rule (8) and of holding it at rest in all conditions, and all such brakes shall at all times be properly conducted and maintained in efficient condition.

(3)
In every construction equipment vehicle, other than those having hydrostatic transmission, the brakes operated by any of the means of operation shall act directly upon the wheel or at a suitable location in the power train provided that such an action does not dis couple, disengage or isolate the braking action from the wheels.

(4)
Every construction equipment vehicle which manufactured on or after the commencement of the Motor Vehicles (Sixth Amendment) Rules, 2000, shall have a braking system whose performance shall [conform to the test and stopping distance formula as specified in sub-rule (7)]
[Substituted by GSR 116(E), dated 27.2.2002 (w.e.f. 27-8-2002)]

·
(5)
The braking system or one of the braking systems of construction equipment vehicle, shall be so constructed and maintained that it can effectively prevent at least two wheels or drums from revolving when the vehicle is left unattended and it shall be designed to be applied through hand or foot or automatically when engine is not running.

(6)
In the case of construction equipment vehicles with four or more than four wheels, the service brake shall work on at least two wheels of the vehicle.

(7)
[The service braking system of the construction equipment vehicle shall be capable of bringing the vehicle to a halt

within the stopping distance as calculated by the formula given below, when tested in unladen condition and attachment carry position at a speed corresponding to 80 percent. of the design maximum speed. The test shall be conducted in the forward direction of travel on a dry level hard road in good condition and during the test the acceleration control or travel shall be fully released and in the case of vehicle with manual gear shifting control, the top gear and the clutch shall be engaged.]

[Substituted by GSR 116(E), dated 27.2.2002 (w.e.f. 27.8.2002).]

Stopping Distance Formula

$S \geq 0.15v + (V^2/130)$,

Where S is the Stopping distance in metres,

V is the test speed corresponding to 80% of design maximum speed in Km/h.,

Control force F - 700 Newtons.

Explanation. - For the purposes of this sub-rule, unladen means the construction equipment vehicle in travel mode without any load except the driver and another person for the specific purpose of supervising the test and the instruments, if any:

Provided that while the stopping distance formula mentioned above remain unchanged, the construction equipment using hydrostatic transmission, the brake test shall be performed by positioning the gear change lever to the neutral position.

[96-B. High Speed Braking Requirements]

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

- For high speed braking, the following test procedure shall be followed, namely:

(a)

in the case of Category M-1, the P type, service brake test as defined under IS : 11852-2001 Part 3, shall be carried out in the engine connected mode at a test speed of 120 km/h or at 80% of the design maximum speed of the vehicle, whichever is lower.

(b)

the stopping distance requirements shall be according to the following formula, namely:

$S \geq 0.1 V + (V^2/130)$:

where, S is the Stopping Distance in mtrs.

V is the test speed in km/h, and

Control force - 500 Newtons.

Provided that this sub-rule shall be applicable in case of new vehicles yet to be type approved after six months, and in case of already type approved vehicles, twelve months, from the date of the commencement of the Central Motor Vehicles (Third Amendment) Rules, 2002.]

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

[96-C. Brakes for agricultural tractor.

[Inserted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

- The braking system of the agricultural tractor shall conform to IS: 12061-1994 and IS: 12207-1999, as amended from time to time.]

[Inserted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.9.2001).]

[96-D. Braking requirements for power tillers.

[Rule 96-D inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

- The power tillers when coupled to a trailer shall meet the following requirements, namely :-

(i)

the brake test for the power tiller coupled to a trailer shall be carried out with a gross combination weight not exceeding 1.5 tons as declared by the manufacturer;

(ii)

The brake test shall be conducted at a speed of 15 km/h to meet the stopping distance requirement of 7.5 metres with the pedal effort not exceeding 600N;

(iii)

The trailer coupled to the power tiller shall be fitted with a parking brake capable of holding the combination on

anup-slope and down-slope gradient of 12%.]

[96-E. Brakes for combine harvester. - (1) The brake test shall be conducted in forwarded direction on dry hard road in good condition with the clutch disengage and cutter bar trailer with header assembly attached to reel of combine harvester.

(2)

The service braking system of the unladen combine harvester shall be capable of bringing the vehicle to a halt within a specified stopping distance when brake is applied at the standard test speed as mentioned in the Table below:

Table

S.No.

Type of

Combine

Load

(Unloader)

Test Speed

Stopping

Distance

1.

Self

Propelled Combine harvester

-

20 km/h or

max speed whichever is less

10 meter

2.

Tractor

Powered Combine harvester

-

24 km/h or

max speed whichever is less

10 meter

Maximum pedal force should not be more than 600 N.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

97.

Brakes for trailers.

(1)

[[Every trailer including modular hydraulic trailer]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

, other than a tractor-drawn trailer, having five hundred kilogrammes and more of weight] shall have an efficient braking system which are capable of being applied when it is being drawn,

(i)

in the case of trailer having not more than two axles, to at least all the wheels of one axle; or

(ii)

in the case of a trailer having more than two axles, to at least all the wheels of two axles:

Provided that the braking system shall be so constructed that it is not rendered ineffective by the non-rotation of the engine of the drawing vehicle.

(2)

The provision of sub-rule (1) shall not apply to,

(i)

any land implement drawn by a motor vehicle;

(ii)

any trailer designed for use and used by a local authority for street cleansing or by the fire service for fire fighting, which

does not carry any load other than its necessary gear and equipment;

(iii)
any disabled vehicle which is being drawn by a motor vehicle in consequence of its disablement.

(3)
[***]
[Omitted by Notification No. GSR 1464(E), dated 27.11.2017 (w.e.f. 2.6.1989).]
[Provided that every agricultural trailer manufactured on or after the 1st February, 2016 shall meet the following requirements for compliance to agricultural trailer brake system as per AIS:043-2005 specification, as amended from time to time, namely:-

(a)
fitment of the hydraulic braking system or inertia over-run braking system such as foundation brake (drum or disc, etc.) actuation systems on the the trailer including the proportional or control valve;

(b)
type approval of agricultural trailer braking system requirements as per AIS-043-2005, as amended from time to time.]
98.

Steering gears.

(1)
The steering gear of every motor vehicle shall be maintained in good and sound condition, free from back-lash exceeding 30 degrees on the steering wheel, [all ball joints connecting the steering linkage,]
[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]
shall be protected by rubber caps and where the connections are secured with bolts or pins, the bolts or pins shall be effectively locked.

(2)
[On and after the 1st day of April 2019, the steering gear of motor vehicles of categories L, M and N, shall conform to the Indian Standard IS: 12222-2011, as amended from time to time.]
[Substituted by Notification No. G.S.R 1463(E), dated 27.11.2017 (w.e.f. 2.6.1989).]

(3)
[[On and after 1st May, 2003]
[Sub-Rule(3) substituted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]
, the steering effort of all motor vehicles other than three-wheelers not fitted with steering wheel, motor cycles, [and invalid carriages]
[Substituted by GSR 111(E), dated 10.2.2004, for 'invalid carriages and agricultural tractors' (w.e.f. 10.8.2004).]
manufactured shall conform to the Indian Standard IS: 11948-1999, as amended from time to time.]

[Inserted by Notification No. G.S.R. 492(E), dated 15.6.2015 (w.e.f. 2.6.1989)]
[Provided that on and after the 1st day of April, 2019 the steering effort of all motor vehicles other than three wheelers not fitted with steering wheel, motor cycles and invalid carriages manufactured, shall conform to the Indian Standard IS: 11948-2010, as amended from time to time]
[Inserted by Notification No. G.S.R. 1463(E), dated 27.11.2017 (w.e.f. 2.6.1989)]

(4)
[Every heavy passenger motor vehicle manufactured after expiry of six months from the date of commencement of the Central Motor Vehicles (Amendment) Rules, 2000(including the date of such commencement), shall be fitted with power steering gears.]
[Inserted by GSR 65(E), dated 25.1.2000 (w.e.f. 25.1.2000).]

(5)
[The power steering shall be fitted in,
(a)
the Category N3 multi-axle vehicles on and from 1st May, 2004; and
(b)
other than multi-axle vehicles of Category N3 on and from 1st December, 2004.]

[98-A. Steering gears for construction equipment vehicles.
[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

(1)

The steering system of every construction vehicle shall be maintained in good and sound condition, with backlash not exceeding 30 degrees on the steering wheel when tested with the engine running; ball-joints connecting the steering linkage of the mechanical steering system shall be protected by rubber caps and where the connections are secured with bolts or pins, the bolts or pins shall be effectively locked; in the case of hydrostatic steering system the moving parts shall be effectively sealed and protected from dust ingress.

(2)

The steering system of the construction equipment vehicle shall be adequately designed to ensure efficient and effective control of the vehicle under all the driving conditions and shall be so constructed as to conform to the Indian Standards IS: 12222-(1987), as modified from time to time.

(3)

The steering effort of the construction equipment vehicles during normal unladen operation shall not exceed 11.7 kg push/pull for hydrostatic steering system and 20 kg for manual steering wheel system when evaluated as per clauses 5.1 to 5.4 of Indian Standards IS: 11948-(1986) as specified by the Bureau of Indian Standards.]

[Sub-Rule(5) substituted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004). Earlier sub-Rule(5) was inserted by GSR 845(E), dated 27.12.2002 (w.e.f. 27.12.2002).]

[98-B. Steering Gears for agricultural tractors.

[Inserted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

(1)

The steering gear of agricultural tractor shall be maintained in good and sound condition, free from backlash exceeding 30 degrees on the steering wheels. All ball joints connecting the steering linkage shall be protected by rubber caps and where the connections are secured with bolts, or pins, the bolts or pins shall be effectively locked.

(2)

The turning circle diameter and turning circle clearance diameter of every agricultural tractor shall conform to IS: 11859-1986, as amended from time to time.

(3)

The steering effort requirement of agricultural tractor shall conform to Automotive Industry Standard (AIS): 042 as amended from time to time, till such time the corresponding BIS standard is notified.]

[98-C. Steering gear for power tillers.

[Rule 98-C inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

- The turning circle diameter and the turning clearance circle diameter of power tillers coupled to trailers, when measured as per IS:12222:1987, as amended from time to time, shall not exceed 10 metres.]

[98-D. Steering gears for combine harvester. - (1) The turning clearance circle diameter of combine harvester, coupled to the trailer for header assembly, if any, when measured as per IS: 11859-2004, as amended from time to time, shall not exceed 20 meters, without brake condition.

(2)

The steering effort requirement of combine harvester shall conform to AIS : 042-2004, as amended from time to time, till such time the corresponding Bureau of Indian Standard is notified.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

99.

Forward and backward motion.

- Every [motor vehicle including [construction equipment vehicle, agricultural tractor and combine harvester]

[Substituted by GSR 116(E), dated 27.2.2002, for 'motor vehicle' (w.e.f. 27.8.2002).]

and agriculture tractor] other than a motor cycle and three-wheeled invalid carriages, shall be capable of moving under its own power [in the reverse direction also]

[Substituted by GSR 338(E), dated 26.3.1993, for 'either forwards or backwards' (w.e.f. 26.3.1993).]

:

[Provided that power tillers with a riding attachment and power tillers coupled to trailers shall be capable of moving under its own power in the reverse direction also.]

[Proviso inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

100.

Safety glass.

(1)

The glass of windscreens and the windows of every motor vehicle [other than agricultural tractors]

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

shall be of safety glass:

Provided that in the case of three-wheelers and vehicles with hood and side covers, the windows maybe of [acrylic or plastic transparent sheet.]

[Substituted by GSR 338(E), dated 26.3.1993, for 'acrylic transport sheet' (w.e.f. 26.3.1993).]

Explanation. - For the purpose of this rule,

(i)

safety glass means glass [conforming to the specifications of the Bureau of Indian Standards or any International Standards [* * *]

[Substituted by GSR 933(E), dated 28.10.1989, for 'approved by' (w.e.f. 28.10.1989).]

] and so manufactured or treated that if fractured, it does not fly or break into fragments capable of causing severe cuts;

(ii)

any windscreen or window at the front of the vehicle, the inner surface of which is at an angle [more than thirty degrees]

[Substituted by GSR 214(E), dated 18.3.1999, for 'extending to thirty degrees' (w.e.f. 18.3.1999).]

to the longitudinal axis of the vehicle shall be deemed to face to the front.

(2)

[The glass of the windscreen and rear window of every motor vehicle shall be such and shall be maintained in such a condition that the visual transmission of light is not less than 70%. The glasses used for side windows are such and shall be maintained in such condition that the visual transmission of light is not less than 50%,and shall conform to Indian Standards [IS : 2553 Part 21992]

[Sub-Rule(2) Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

:]

(3)

[The glass of the front windscreen of every motor vehicle [other than two-wheelers and agricultural tractors]

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

manufactured after three years from the coming into force of the Central Motor Vehicles (Amendment) Rules, 1993 shall be made of laminated safety glass :

[Provided that on and from three months after the commencement of the Central Motor Vehicles (Amendment)Rules, 1999, the glass of the front windscreen of every motor vehicle other than two-wheelers and agricultural tractors shall be made of laminated safety glass conforming to the Indian Standards IS: 2553Part 21992.]

[Inserted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

Explanation. - For the purpose of these sub-rules laminated safety glass shall mean two or more pieces of glass held together by an intervening layer or layers of plastic materials. The laminated safety glass will crack and break under sufficient impact, but the pieces of the glass tend to adhere to the plastic material and do not fly, and if a hole is produced, the edges would be less jagged than they would be in the case of an ordinary glass.

[(3-A) The glass of the front windscreen of a construction equipment vehicle manufactured after 3years from the date of commencement of the Central Motor Vehicles (Sixth Amendment) Rules, 2000 shall be made of laminated safety glass.]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

(3B)

[The glass of the front wind screen of a combine harvester shall be made of laminated safety glass.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(4)

Notwithstanding anything contained in this rule if the Central Government is of the opinion that it is necessary and expedient to do so in public interest, it may, by order published in the Official Gazette,exempt [any motor vehicle including construction equipment vehicle]

[Substituted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

for use by any person, from the provisions of this rule.]

101.

[Wind screen wiper.

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(1)

An efficient power operated [* * *] windscreen wiper shall be fitted to every motor vehicle having a windscreen, other than three-wheeled invalid carriage [and motor cycles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'motor cycles and three-wheelers of engine capacity not exceeding 500 cc' (w.e.f. 1.4.2006).]

.]

(2)

One year from the date of commencement of Central Motor Vehicles (Amendment) Rules, 1993, [all motor vehicles other than three-wheelers, motor cycles and invalid carriages [manufactured on and after 1st January, 2003 in respect of Category M1 vehicles, and in respect of other vehicles, on and after 1st May, 2003]

[Substituted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

, having a wind screen shall be fitted with a wind screen wiping system which shall conform to the requirements laid down in the following standards, as amended from time to time, till such time the corresponding Bureau of Indian Standards specifications are notified :

(i)

[IS: 15804-2008]

[Substituted by GSR 291 (E), dated 24.4.2014]

, in the case of M-1 category of vehicles

(ii)

[IS: 15802-2008]

[Substituted by GSR 291 (E), dated 24.4.2014]

, in the case of other vehicles.]

[(2-A) [All construction equipment vehicles and combine harvesters]

[Sub-Rule (2-A) substituted by GSR 116(E), dated 27.2.2002 (w.e.f. 27.8.2002). Earlier sub-Rule (2-A) was inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

having windscreen shall be fitted with an efficient power operated windscreen wiping system. The windscreen wiping system shall conform to the requirements of the standards as may be specified from time to time under these rules.]

(2B)

[On and after 1st April, 2015, all agricultural tractors having wind screen shall conform to AIS 011/2001, as amended from time to time till such time the corresponding Bureau of Indian Standards specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

[Inserted by GSR 291 (E), dated 24.4.2014]

[* * *]

[Sub-Rule (3) omitted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

102.

[Signalling devices, direction indicators and stop lights.]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

- [(1) The signal to turn to the right or to the left shall be given by electrically operated direction indicator lamps on all motor vehicles including [construction equipment vehicles and the combined harvester, and such construction equipment vehicles and combined harvester]

[Sub-Rule (1) substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 1.4.2006).]

be fitted and maintained so that the following conditions are met, namely :

(i)

The direction indicator lamps shall be of amber colour which are illuminated to indicate the intention to turn, by a light flashing at the rate of not less than 60 and not more than 120 flashes per minute.

(ii)

The light emitted by the lamp when in operation shall be clearly visible from both front and rear of the vehicle.

(iii)

The minimum illuminated area of each direction indicator shall be 60 square centimetres:

Provided that nothing contained in this sub-rule shall apply to L1 category of motor cycles.]

(2)

[On all vehicles other than motor cycles, [the intention to stop the vehicle (other than construction equipment [and the combined harvester]

[Sub-Rule (2) substituted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

vehicle having hydrostatic brakes)] shall be indicated by two electrical stop lamps which shall be red in colour and shall be fitted one on each left and right-hand sides at the rear of the vehicle. The stop lamps shall light up on the actuation of the service brake control. In the case of motor cycle, the intention to stop the vehicle shall be indicated by one stop lamp at the rear which shall light up on the actuation of the control operating the brakes on the rear wheels.]

(3)

One year from the date of commencement of the Central Motor Vehicles (Amendment) Rules, 1993, the stop lamp of every motor cycle shall be so designed and fitted that it will light up on actuation of any of the controls which actuate the brakes on any wheel.

(4)

[In the case of modular hydraulic trailer,-

(i)

the intention to stop shall be indicated by two electrical stop lamps which shall be red in color and shall be fitted one each on left and right hand sides at the rear of the vehicle;

(ii)

the stop lamps shall light up on the actuation of the service brake control of the puller tractor;

(iii)

at least two direction indicators of amber colour shall be fitted, which are illuminated to indicate intention to turn by a light and the minimum illuminated area of each indicator shall be 60 sq.cm.]

103.

Position of the indicator.

(1)

A direction indicator shall be fitted and every direction indicator shall be so designed and fitted that [the driver of the vehicle including a construction equipment vehicle]

[Substituted by GSR 116(E), dated 27.2.2002, for 'driver of the vehicle' and 'every motor vehicle' respectively (w.e.f. 27.8.2002).]

[and combine harvester]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

when in his driving seat is aware that it is operating correctly.

(2)

[One year from the date of commencement of the Central Motor Vehicles (Amendment) Rules, 1993, [every motor vehicle including a construction equipment vehicle]

[Substituted by G.S.R. 338(E), dated 26-3-1993 (w.e.f. 26.3.1993)]

[and combine harvester]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

other than [* * *]

[The words 'three wheelers of engine capacity not exceeding 500 cc and' omitted by GSR 589(E), dated 16.9.2005 (w.e.f. 1.4.2006).]

motor cycles shall be equipped with such a device that when the vehicle is in an immobilised condition all the direction indicators flash together giving hazard warning to other road users.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

104.

[Fitment of reflectors.]

[Substituted by G.S.R. 338(E), dated 26-3-1993 (w.e.f. 26-3-1993).]

- [(1) Every motor vehicle manufactured on and after the 1st day of April,2006, including trailers and semi-trailers, other than three-wheelers and motorcycles shall be fitted with two red reflectors, one each on both sides at their rear. Every motor cycle shall be fitted with at least one red reflex reflector at the rear :]

[Sub-Rule (1) and the proviso substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

[Provided that in respect of the vehicles of-

(i)

Category N-1 and Category N-2, 3.5 tonnes and above but less than 7.5 tonnes Gross Vehicle Weight, manufactured on and after 1st day of April, 2009, shall be affixed at the front with a white-reflective tape and at the rear with a red reflective tape running across the width of the body and the tapes affixed at front and rear shall be not less than 20 mm width and shall conform to the requirement of Annexures 4, 5 and 6 of AIS:090-2005 till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(ii)

Category N-3 and Category N-2, 7.5 tonnes and above Gross Vehicle Weight, manufactured on and after 1st day of April, 2009, shall be affixed at the front with a white reflective tape running across the width of the body and the tape affixed at the front shall not be less than 50 mm width and shall conform to the requirement of Annexures 4, 5 and 6 of AIS:090-2005 till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(iii)

Category N-3 including trailers or semi-trailers and Category N-2, 7.5 tonnes and above GVW along with trailers or semi-trailers, manufactured on and after 1st day of April, 2009, shall be affixed with reflective contour marking at the rear and side in accordance with AIS:090 -2005 till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(iv)

Category M-2 and M-3, manufactured on and after 1st October, 2009, shall be affixed at the front with white reflective tape and at the rear with red reflective tape running across the width of the body and the sides of M3 category vehicles shall be affixed with yellow reflective tape running across the length of the body but tapes so affixed shall not be less than 50 mm width and shall conform to Annexures 4, 5 and 6 of AIS: 090-2005, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

(2)

Every goods carriage vehicle including trailers and semi-trailers other than three-wheeler [* * *]

[The words 'of engine capacity not exceeding 500 cc' omitted by GSR 589(E), dated 16.9.2005 (w.e.f. 1.4.2006).]

shall be fitted with two white reflectors one each at the extreme right and left bottom corners in the front of the vehicle and facing to the front. The reflecting area of each reflector shall not be less than 28.5 sq. centimetres, in the case of vehicles with overall length of more than 6 metres, and not less than 7 sq. centimetres in case of other vehicles.

(3)

[All trailers including semi-trailers, other than those drawn by three-wheeled tractors [* * *]

[Substituted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

shall be fitted with the following reflex reflectors, namely,

(i)

two white reflex reflectors in the front, one each at the right and left corners at a height not exceeding 1500 mm above the ground,

(ii)

two red reflex reflectors in the rear, one each at the right and left corners at a height not exceeding 1500 mm above the ground, and

(iii)

the area of the reflectors referred to above shall not be less than 28.5 sq. cm. in the case of trailers with overall length exceeding 6 metres and shall not be less than 7 sq.cm. in case of other trailers.]

(4)

[On and after expiry of one year from the date of commencement of the Central Motor Vehicles(Amendment) Rules, 1999, the reflectors referred to in this rule and in rule 110 shall be of reflex type conforming to [AIS:057:2005 till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986(63 of 1986)]

[Substituted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999). Earlier sub-Rule(4) was substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

.]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

(5)

[On and from the date of commencement of the Central Motor Vehicles Rules, 1993, every motor vehicle and trailer of length exceeding 6 metres shall be fitted with two amber coloured reflex reflectors on each left hand and right hand of the vehicle, one set as close to the front end as possible and the other set as close to the rear end as possible. The height of the side reflectors above the ground shall not be more than 1500 mm. The area of each reflector shall not be less than 28.5 sq. cm.:

Provided that in case the distance between the two side reflectors is more than 3 metres, additional intermediate side reflectors shall be fitted so that the distance between any adjacent side reflector is not more than 3 metres.]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[[104A. Fitment of reflectors on construction equipment vehicles and combine harvester.

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

- All construction equipment vehicles and combine harvester shall be fitted with]

(i)

two white reflex reflectors in the front of the vehicle on each side and visible to on-coming vehicles from the front at night;

[Provided that in case of combine harvester, the height of front white reflex-reflector shall not be more than 2100 mm above the ground in the case of unobstructed vision from the front and the implement or device shall not obstruct the visibility of the front reflex-reflectors to the oncoming vehicles;]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(ii)

two red reflectors in the rear of the vehicle, one each at right and left corners, at a height not exceeding 1500 mm above the ground in the case of unobstructed vision from the rear and the implement or device shall not obstruct the visibility of the reflectors to the following vehicle;

[Provided that in case of combine harvester, the height shall not exceed 2100 mm above the ground;]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(iii)

two sets of amber coloured side reflex reflectors, one each on left hand and right hand sides of the vehicle, one set as close to the front end and the other set as close to the rear end as possible to the basic machine without attachments and if the distance between the two amber side reflex reflectors is more than 3 metres, additional intermediate amber side reflex reflectors shall be fitted so that the distance between any adjacent amber side reflex reflector is not more than 3 metres :

[Provided that the fitment of reflex reflectors on the implements such as booms of cranes and arms of shovels, shall not be mandatory. However, wherever possible the fitment of these reflectors may be done considering the working environment/nature of these machines in the fields;]

[Substituted by GSR 116(E), dated 27.2.2002, for the proviso (w.e.f. 27.8.2002).]

(iv)

the reflecting area of each reflex reflector shall not be less than 28.5 sq. cms;

(v)

the construction equipment vehicle [and combine harvester]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall be fitted with a retro-reflective tape or retro-reflective paint of not less than 20 millimetres width, running across the width of the body at the front and rear, and the colour of the reflective tape or reflective paint shall be white at the front and red at the rear;

(vi)

the reflectors referred to in this sub-rule, shall be of reflex type conforming to Indian Standards IS:8339 specified by the Bureau of Indian Standards;

(vii)

the retro-reflective tape and paint shall be as per clause 801 and 803 of Ministry of Surface Transport (Roads Wing) specifications for Road and Bridge works (3rd Revision, 1995) as amended from time to time.]

[104-B. Fitment of reflectors for agricultural tractors.

[Rule 104-B inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

(1)

Every agricultural tractor manufactured on and after the 1st day of April, 2006 shall be fitted with two non-triangular red reflectors of not less than 7 sq. cm reflecting area one each on both sides at the rear.

(2)

The reflectors referred in sub-rule (1) of this rule shall be of the reflex type conforming to AIS:057:2005 till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

104.

-C. Fitment of reflectors on power tillers.

(1)

On and from one year from the date of commencement of the Central Motor Vehicles (Fifth Amendment) Rules, 2005, every power tiller shall be fitted with two white reflex reflectors of not less than 7 sq. cm reflecting area in the front of the vehicle one on each side and visible to oncoming vehicles from the front at night, conforming to AIS : 057 : 2005 till corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(2)

In the case of trailers attached to power tillers, two red reflectors of not less than 7 sq.cm reflecting area in the rear side, one each at right and left corners, at a height not exceeding 1500 mm above the ground shall also be fitted.]

104D.

[Fitment of retro-reflective tapes or reflectors and rear marking plate on modular hydraulic trailer.

[Inserted by Notification No. G.S.R. 212(E), dated 20.3.2015 (w.e.f. 1.4.2015)]

- Every modular hydraulic trailer shall be fitted with two red reflective tapes having width not less than 50 mm at the rear and front and amber reflective tape having width not less than 50 mm on the sides, conforming to AIS: 090:2005, as amended from time to time, till the corresponding Bureau of Indian Standard specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(2)

Every modular hydraulic trailer shall be fitted with two red reflective tapes having area not less than 28.5 sq. cm on the sides one set as close to the front end and the other set as close to the rear end as possible, conforming to AIS:057:2005, as amended from time to time till the corresponding Bureau of Indian Standard specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(3)

Every modular hydraulic trailer shall be fitted with rear marking plate confirming to AIS-089.]

105.

Lamps.

- [(1) Save as hereinafter provided, every motor vehicle, while being driven in a public place, during the period half an hour after sunset and at any time when there is no sufficient light, shall be lit with the following lamps which shall render clearly discernible persons and vehicles on the road at a distance of one hundred and fifty five metres ahead:

[Sub-Rule (1) substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 1.4.2006).]

(a)

in the case of motor vehicle other than three-wheelers, three-wheeled invalid carriages and motor cycles, two or four head lamps;

(b)

in the case of [* * *], three-wheelers and three-wheeled invalid carriages one or two headlamps;

(bb)

[(bb) every two wheeler manufactured on and after the 1st April, 2017, shall have one or two head lamps, conforming to the applicable standards in force for performance and installation requirements as notified by the Central Government from time to time vide according to sub-rule (1) of rule 124, which shall automatically switch on when the engine is running:

[Inserted by Notification No. G.S.R. 188(E), dated 22.2.2016 (w.e.f. 2.6.1989).]

Provided that, the above condition of the head lamp being lit when the engine is running is deemed to be satisfied if daytime running lamp is provided, conforming to the applicable standards in force for performance and installation requirements as notified by the Central Government from time to time, which shall be lit automatically if the engine is

running:

Provided further that the daytime running lamp shall be lit off automatically if the engine is running and the head lamp is switched on.]

(c)

in the case of a sidecar attached to a motor cycle one lamp showing a white light to the front;

(d)

in the case of construction equipment vehicle [and combine harvesters]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

, two or four lamps showing to the front white light visible from a distance of one hundred and fifty five metres ahead.]

(2)

Every such motor vehicle other than a [* * *]

[The words 'a motor cycle and' omitted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

three-wheeler shall also carry -

(i)

[two lamps (hereinafter referred to as the rear lamp) showing to the rear a red light visible in the rear from a distance of one hundred and fifty-five metres; and in the case of a motor cycle one lamp showing a red light to the rear visible from a distance of seventy-five metres]

[Substituted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

; and

(ii)

lamp, which may be the rear lamp or some other device, illuminating with a white light the whole of the registration mark exhibited [[on the rear of the vehicle including construction equipment vehicle]

[Substituted by GSR 642(E), dated 28.7.2000, for 'on the rear of the vehicle' (w.e.f. 28.7.2000).]

, [and combine harvesters]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

and on the side in the case of construction equipment vehicle] [and combine harvesters]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

so as to render it legible from a distance of fifteen metres to the rear :

Provided that when a motor vehicle is drawing another vehicle or vehicles and the distance between such vehicles does not exceed 1.5 metres, it shall be sufficient if the last drawn vehicle carries a rear lamp or a lamp illuminating the rear registration mark :

[Provided further that every construction equipment vehicle shall also carry two lamps showing to the rear red lights visible in the rear from a distance of one hundred and fifty-five metres.]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

(3)

[On and from the commencement of the Central Motor Vehicles (Amendment) Rules, 1993, all the obligatory front head lamps of a motor vehicle other than motor cycles shall be as nearly as possible of the same power and fixed at a height as specified in Indian Standards [IS: 8415-1977]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(clause 4.1):

Provided that in the case of four-wheel drive cross country vehicles, the maximum height of the said front head lamps may be as per limits specified in Indian Standards [IS:8415-1977]

[Substituted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

(clause 4.1.1):

[* * *]

[Proviso omitted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

Provided further that on and from the commencement of the Central Motor Vehicles(Amendment) Rules, 1993, all vehicles other than three-wheelers of engine capacity less than 500 cc, motor cycles and three-wheeled invalid carriages manufactured shall be fitted with two rear lamps showing red light to the rear.]

[(3-A) On and from the commencement of the Central Motor Vehicles (Sixth Amendment) Rules, 2000, all the obligatory front head lamps of a construction equipment vehicle shall be as nearly as possible of the same power and fixed at a

height so that front visibility is maintained and farthestmost point of equipment/attachment is clearly seen by on-coming traffic.]

[Inserted by G.S.R. 642(E), dated 28-7-2000 (w.e.f. 28-7-2000).]

(3B)

[All the obligatory front head lamps of a combine harvester shall be as nearly as possible of the same power and fixed at a height so that front visibility is maintained and farthestmost point of equipment or attachment is clearly seen by oncoming traffic.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(4)

The rear lamp shall be fixed either on the centre line of the vehicle or to the right hand side, and save in the case of a transport vehicle, at a height of not exceeding one metre above the ground:

[* * *]

[Proviso omitted by G.S.R. 111(E), dated 10-2-2004 (w.e.f. 10-8-2004).]

(5)

In the case of a transport vehicle, the rear light maybe fixed at such level as may be necessary to illuminate the registration mark.

(6)

Every heavy goods carriage [including trailers]

[Added by G.S.R. 642 (E), dated 28.7.2000 (w.e.f.28.7.2000).]

shall be fitted with a red indicator lamp of size of thirty centimetres by ten centimetres on the extreme rear most body cross beam and in the case of a vehicle not constructed with body in the rear,the indicator lamp shall be fitted near the right rear light above the rear number plate:

[Provided that every construction equipment vehicle of an unconventional or extraordinary type in travel mode shall be fitted or installed with a red indicator lamp of size of not less than 100 square centimetres on the extreme rearmost point of the body.]

[Added by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

(7)

[On and from the date of commencement of the Central Motor Vehicles (Amendment) Rules, 1999, every motor vehicle manufactured shall be fitted with at least one lamp which shall automatically be operated, throwing a white light to the rear, when the vehicle is being driven in the reverse gear.]

[Substituted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999). Earlier sub-Rule (7) was inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(8)

[In the case of vehicles, other than three-wheelers of engine capacity not exceeding 500 CC, which are attached with trailers, all the lamps required to be fitted on the rear of the vehicle shall be fitted at the rear of the trailer.]

[Inserted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

[(8-A) On the commencement of the Central Motor Vehicles (Sixth Amendment) Rules, 2000, every construction equipment vehicle shall be fitted with two lamps at the rear throwing light to the rear when the vehicle is being driven in the reverse gear and there shall also be an audible warning system operating when the vehicle is being driven in the reverse gear, the audible warning system and the light being automatically operated when the vehicle is in reverse gear.]

[Added by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000). Previously inserted by GSR 214(E), dated 18.3.1999. [There seems to be some confusion/mistake in the language of Clause 13(f) of GSR 214(E), dated 18.3.1999 and Clause 13(e) of GSR 642(E), dated 28.7.2000-Ed.].]

(8B)

[Every combine harvester shall be fitted with two lamps at the rear throwing light to the rear when the vehicle is being driven in the reverse gear and there shall also be an audible warning system operating when the vehicle is being driven in the reverse gear so that the audible warning system and the light are automatically operated when the vehicle is in reverse gear.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

106.

Deflection of lights.

- [(1) No head lamp showing a light to the front shall be used on any motor vehicle including agricultural tractor and construction equipment vehicle [and combine harvester]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

(whether fitted with single or dual head lamp) unless such lamp is so constructed, fitted and maintained that the beam of light emitted there from meet the requirements of respective safety standards notified under rule 124 and 124A.]

[* * *]

[Sub-Rule (2) omitted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(2)

[]

[Sub-Rule(3) renumbered as sub-Rule (2) by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[***]

[Omitted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

[107. Top lights.

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

- Every goods vehicle including trailer and semi-trailer other than three-wheelers and vehicles with overall width not exceeding 2.1 metres shall be fitted with two white lights at the top right and left corners [showing white light to the front] and two red lights at the top right and [showing red light to the rear]

[Substituted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

. The lights shall remain lit when the vehicle is kept stationary on the road during night and at the time of poor visibility: Provided that in the case of goods carriage without a full body in the rear, provision for fitting of the top light at the rear shall not be necessary.]

[107-A. Implement lights for construction equipment vehicle.

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

- Construction equipment vehicle having implements with front overhang greater than 60% of wheelbase shall be fixed with additional implement light of amber colour at a location nearest to the extreme edge of the implement without affecting the functions of showing light in all directions and where the implement is more than 3 metres in length, additional amber coloured lamps shall be fixed at a distance of not exceeding 3 metres for the entire length of the implement:

Provided that in case of rear overhang the additional implement lights shall be in red colour.]

108.

[Use of red,white or blue light.

[Substituted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

(1)

No motor vehicle shall show a red light to the front or light other than red to rear:

Provided that the provisions of this rule shall not apply to

(i)

the internal lighting of the vehicle; or

(ii)

[the amber light, if displayed by any direction indicator or as top light used on vehicle for operating within the premises such as airports, ports, mines and project sites, without going outside the said premises on to public roads;]

(iii)

[* * *]

[Omitted 'a vehicle carrying high dignitaries as specified by the Central Government or the State Government,as the case may be, from time to time;' by Notification No. G.S.R. 423(E), dated 1.5.2017 (w.e.f. 2.6.1989).]

(iv)

[the blinker type of red light with purple glass fitted to an ambulance van used for carrying patients or the warning lamps fitted on Road Ambulance in accordance with Annexure-1 of AIS-125 (Part-1)-2014;]

[Substituted by Notification No. G.S.R. 868(E), dated 1.4.2018 (w.e.f. 2.6.1989).]

(v)

[* * *]

[Omitted 'to a vehicle having a lamp fitted with an electrical bulb, if the power of the bulb does not exceed seven watts and the lamp is fitted with frosted glass or any other material which has the effect of diffusing the light;' by Notification No. G.S.R. 423(E), dated 1.5.2017 (w.e.f. 2.6.1989).]

(vi)

white light illuminating the rear number plate;

(vii)

white light used while reversing;

(viii)

plough light provided in agricultural tractors for illuminating the implements working area on the ground in agricultural field operations.

[* * *] [[Omitted '(2) Use of blue light with flasher shall be determined and notified by the State Governments at their discretion.

(3)

Use of blue light with or without flasher shall be permitted as top light on vehicles escorting high dignitaries entitled to the use of red light.' by Notification No. G.S.R. 423(E), dated 1.5.2017 (w.e.f. 2.6.1989).]]

(4)

Use of multi-coloured red, blue and white light shall be permitted only on vehicles specifically designated for [such emergency and disaster management duties as may be specified by the Central Government]

[Substituted 'emergency duties and shall be specifically specified by State Governments' by Notification No. G.S.R. 423(E), dated 1.5.2017 (w.e.f. 2.6.1989).]

.

[* * *] [[Omitted '(5) The State Government shall inform the Central Government regarding publication of notifications issued by the concerned State Government under sub-rule (2) and under clause (e) of the Notification No. S.O. 52(E), dated 11th January, 2002, published in the Gazette of India, Ministry of Road Transport and Highways, regarding use of red light on top of vehicle being used by dignitaries.

(6)

In case vehicle is not carrying dignitaries, red or blue light, as the case may be, light shall not be used and be covered by black cover.' by Notification No. G.S.R. 423(E), dated 1.5.2017 (w.e.f. 2.6.1989).]]]

(7)

[On and after the 1st April, 2018, the top lights (warning lamps) fitted on Road Ambulances shall be in accordance with AIS:125 (Part1)- 2014, as amended from time to time, for all types of ambulances specified therein, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

[Inserted by Notification No. G.S.R. 868(E), dated 1.4.2018 (w.e.f. 2.6.1989).]

[[108A. Use of red or white light on construction equipment vehicles and combine harvesters.]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

- No construction equipment vehicle [and combine harvesters]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall show a red light to the front or light other than red to the rear:

Provided that the provision of this rule shall not apply to:

(i)

the internal lighting of the vehicle;

(ii)

the amber light, if displayed by any direction indicator or top light;

(iii)

white light illuminating the rear or side registration number plate;

(iv)

white light used while reversing;

(v)

light provided for illuminating the implements working area on the ground in off-highway or construction operations.]

108B.

[Use of beacon or blinking lamp on puller tractor. - The puller tractor shall be fitted with two beacon or blinking lamps,

which are amber in color, one each on left and right hand side on top of the cabin.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

109.

[Parking light.

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

- [[Every construction equipment vehicle, combine harvester and motor vehicle] other than] [* * *]

[The words 'three wheelers of engine capacity not exceeding 500 cc' omitted by GSR 589(E), dated 16.9.2005 (w.e.f. 1.4.2006).]

motor cycles and three-wheeled invalid carriages shall be provided with one white or amber parking light on each side in the front. In addition to the front lights, two red parking lights one on each side in the rear shall be provided. The front and rear parking lights shall remain lit even when the vehicle is kept stationary on the road:

Provided that these rear lamps can be the same as the rear lamps referred to in rule 105, sub-rule (2):

[* * *]

[Proviso omitted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

]

[Provided also that construction equipment vehicle [and combine harvester]

[Substituted by G.S.R. 642(E), dated 28.7.2000 (w.e.f. 2.6.1989).]

, which are installed with flood light lamps or spot lights at the front, rear or side of the vehicle for their off-highway or construction operations, shall have separate control for such lamps or light sand these shall be permanently switched off when the vehicle is travelling on the road.]

110.

[[Lamps on three-wheelers]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

.

- Every [three-wheeler]

[Substituted by GSR 589(E), dated 16.9.2005, for 'auto-rickshaws and three-wheelers of engine capacity not exceeding 500 cc' (w.e.f. 1.4.2006).]

shall be fitted with one front head lamp and [two side white or amber lights]

[Substituted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

or two front lamps on the body. In addition to the front lamp or side lights, it shall be fitted with [two rear lamps showing to the rear red light]

[Substituted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

visible from a distance of 75 metres and a white light illuminating the registration mark exhibited on the rear of the vehicle so as to render it legible from a distance of 15 metres; and also two red reflex reflectors each having a reflecting area of not less than seven square centimetres :

Provided in case where these vehicles are attached with trailers, the rear fitments mentioned in this rule and direction indicator system mentioned in rule 102 shall also be provided at the rear of the trailer:]

[Provided further that fitment of one head lamp shall be applicable only in case of three-wheelers with overall width not exceeding 1400 mm and in such cases the side lights shall be amber in colour.]

[Proviso inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 1.4.2006).]

111.

Prohibition of spot lights, etc.

- No spot light or search light shall be carried on the front of any vehicle except in exceptional circumstances with the prior approval of the registering authority.

Smoke, vapour, spark, ashes, grit and oil

112.

Exhaust gases.

- Every motor vehicle shall be so constructed or equipped that the exhaust gases from the engine are discharged neither downward nor to the left side of the vehicle and shall be so fitted as to allow the gases to escape to the right side or rear of the vehicle:

Provided that in the case of tankers carrying explosives and inflammable goods, the fitment of exhaust pipe shall be

according to the specification of the Inspector of Explosives:

[Provided further that in the vehicles where the exhaust gases are discharged to the right of the vehicle, slight downward angle shall be permitted, provided the exhaust gases do not kick up any dust when the vehicle is stationary and engine running and in any case the angle of the pipe to the horizontal should not be more than 30degrees:

Provided also that where the exhaust gases are discharged to the left of the vehicle the inclination of exhaust pipe should not cross 30 degrees in downward and 30 degrees in left direction against the vertical plane which includes the vehicle centre line,provided the exhaust gases do not take up any dust when the vehicle is stationary and engine running:

[Provided further that in the case of agricultural tractors, vertical or horizontal]

[Substituted by G.S.R. 338(E), dated 26-3-1993 (w.e.f. 26-3-1993).]

exhaust pipe may be provided and outlet of this pipe should be so directed that the driver of the tractor is not exposed to exhaust gases by locating the outlet over or to the side of head-level of the driver as per Indian Standards IS: 12239 (Part1)1988:]

[Provided also that in the case of construction equipment vehicle [and combine harvester]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

vertical exhaust pipe may be fitted and outlet of this pipe shall be so directed that the driver of the vehicle is not exposed to exhaust gases.]

113.

Location of exhaust pipes.

- On and from the date of commencement of this sub-rule, [no exhaust pipe of a motor vehicle including construction equipment vehicle]

[Substituted by GSR 116(E), dated 27.2.2002, for 'no exhaust pipe' (w.e.f. 27.8.2002).]

[and combine harvester]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall be located within a distance of 35 millimetres from the fuel line connecting to the fuel tank and engine.

114.

Exhaust pipes of public service vehicles.

- The exhaust pipe of every public service vehicle shall be so fitted or shielded that no inflammable material is thrown upon it from any other part of the vehicle and that it is not likely to cause a fire through proximity to any inflammable material on the vehicle.

Emission of smoke, vapour, etc., from motor vehicles

115.

Emission of smoke, vapour, etc. from motor vehicles.

- [(1) Every motor vehicle other than motor cycles of engine capacity not exceeding 70 cc, manufactured prior to the first day of March 1990, shall be maintained in such condition and shall be so driven so as to comply with the standards prescribed in these rules.]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(2)

[On and after 1st October, 2004, every motor vehicle operating on

(i)

Petrol/CNG/LPG shall comply with the idling emission standards for Carbon monoxide (CO) and Hydrocarbon (HC) given in the Table below] :-

[Table]

[Substituted by Notification No. 277 (E) dated 11.4.2014 (w.e.f. 1.10.2014)]

Petrol/CNG/LPG Driven Vehicles

S.No.

Vehicle

Type and Applicability

CO%

*HC(n-hexane

equivalent) ppm

1.
Two Wheelers
(2/4 ? Stroke) (Vehicles manufactured on and before 31st March, 2000)
4.5
9,000
2.
Two Wheelers
(2 ? Stroke) (Vehicles manufactured between 31st March, 2000 and 31st March 2010)
3.5
6,000
3.
Two Wheelers
(4 ? Stroke) (Vehicles manufactured between 31st March, 2000 and 31st March 2010)
3.5
4,500
4.
Two Wheelers
(2 ? Stroke) (Vehicles manufactured after 31st March, 2010)
3.0
4,000
5.
Two wheelers (4-Stroke) (Vehicles manufactured manufactured after 31st March, 2010)
3.0
3,000
6.
Three
Wheelers (2/4 ? Stroke) (Vehicles manufactured on and before 31st March, 2000)
4.5
9,000
7.
Three
Wheelers (2 ? Stroke) (Vehicles manufactured after 31st March, 2000)
3.5
6,000
8.
Three
Wheelers (4 ? Stroke) (Vehicles manufactured after 31st March, 2000)
3.5
4,500
9.
Four
Wheelers manufactured as per pre-Bharat Stage II emission norms
3.0
1,500
- 10.

Four

Wheelers manufactured as per Bharat Stage-II or Bharat Stage-III

Emission norms

0.5

750?

Note.- The test shall be carried out using the instrument type approved as per rule 116(3) of the Central Motor Vehicles Rules, 1989 (CMVR) with the vehicle engine warmed up after 4 run of minimum 15 minutes on a variable course under normal traffic condition. During the test the vehicle engine shall be running at idling speed and the sampling probe shall be inserted into the vehicle exhaust system to a depth not less than 300mm. In case CO and/or HC emission values recorded during the test are not within the limits, the testing shall be discontinued and the vehicle owner shall be advised to resubmit the vehicle after repair/service.

*The idling emission standards for vehicles when operating on Compressed Natural Gas (CNG), shall contain Non-Methane Hydrocarbon (NMHC) in place of Hydrocarbon (HC) and shall be estimated by the following formula:

$NMHC = 0.3 \times HC$

Where HC= Total Hydrocarbon measured as n-hexane equivalent

Similarly idling emission standards for vehicles when operating on Liquefied Petroleum Gas (LPG) shall contain Reactive Hydrocarbon (RHC) in place of Hydrocarbon (HC) and shall be estimated by the following formula:

$RHC = 0.5 \times HC$

Where HC= Total Hydrocarbon measured as n-hexane equivalent:

Provided that in case of Petrol vehicles fitted with three-way closed loop catalytic converters operating in a specific city or area, the Government of the respective State or Union Territory Administration, as the case may be, may, by notification in the Official Gazette, specify the introduction of measurement of LAMBDA" (dimensionless value representing burning efficiency of an engine in terms of the air/fuel ratio in the exhaust gases) and tighter emission norms for in-use vehicles with such periodicity as may be warranted, after ensuring that gas analysers capable of measuring the values, duly approved by the testing agencies, are available in such city or area, as the case may be:

Provided further that testing procedures are prescribed in TAP documents Nos. 115 and 116 as amended from time to time:

Provided also that the compliance to the limits prescribed in the above proviso shall be included in the certificate issued by the vehicle manufacturer in Form 22 or Form 22-A, as applicable for the vehicle manufactured on or after 1st October, 2004:"

[Provided that in the case of CNG/LPG motor vehicles operating on bi-fuel mode, the test shall be conducted only on CNG/LPG mode.]

[Inserted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

[Provided that every motor vehicle operating on Petrol/Compressed Natural Gas/Liquefied Petroleum Gas, manufactured as per [Bharat Stage-IV or Bharat Stage-VI]

[Inserted by Notification No. G.S.R. 103 (E) dated 23.2.2012 (w.e.f. 2.6.1989)]

norms shall comply with the idling and high idling applicable emission standards for carbon Monoxide (CO), Hydro Carbon (HC) and Lambda given in the following Table, namely:-

Table

(Petrol/Compressed Natural Gas/Liquefied Petroleum Gas driven vehicles, manufactured as per Bharat Stage-IV norms)

Sr.No.

Type of vehicle

Idle emission

limits

High idle

emission limits

(1)

(2)

(3)

(4)

CO%

HC (n hexane
equivalent) ppm

CO%

Lambda (RPM-2500

200) + _

1.

Compressed

Natural Gas/Liquefied Petroleum Gas driven 4-wheelers

manufactured as per Bharat Stage-IV norms.

0.3%

200 ppm.

-

-

2.

Petrol driven

4-wheelers manufactured as per Bharat Stage-IV norms.

0.3%

200 ppm

0.2

1 + _ 0.03 or as

declared by the vehicle manufacturer;]

(ii)

Smoke density for all diesel-driven vehicles shall be as follows:-

[Table

(Diesel vehicles)

Sr.No.

Method of test

Maximum smoke density

(1)

(2)

(3)

Light

absorption coefficient (1/metre)

Hartidge

units

1.

Free

acceleration test for turbo charged engine and naturally

aspirated engine for vehicles manufactured as per pre-[Bharat Stage-IV or Bharat Stage-VI]

[Substituted by Notification No. G.S.R. 889(E), dated 16.9.2016 (w.e.f. 2.6.1989).]

norms.

2.45

65

2.

Free

acceleration test for turbo charged engine and naturally

aspirated engine for vehicles manufactured as per[Bharat Stage-IV or Bharat Stage-VI]

[Substituted by Notification No. G.S.R. 889(E), dated 16.9.2016 (w.e.f. 2.6.1989).]

norms.

1.62

50]

[Substituted by Notification No. G.S.R. 103 (E) dated 23.2.2012 (w.e.f. 2.6.1989)]

[The free acceleration test shall be carried out using the instrument type-approved under sub-rule (3) of rule 116 as given under:-

(a)

three times flushing by free acceleration to be undertaken with or without the sampling probe in the vehicle exhaust, and average maximum rpm of the three flashing's to be recorded;

(b)

thereafter, with sample probe inserted in vehicle exhaust during each free acceleration, maximum no load rpm reached shall be within bandwidth of ± 500 rpm of the average value in respect of 3-wheeler vehicles and ± 300 rpm of the average value for all other categories of vehicles;

(c)

the free acceleration test, mentioned in (b) above, shall be repeated minimum three times

(d)

the smoke density to be recorded shall be arithmetic mean of these three readings;

(e)

In case the smoke density recorded is not within the limits, then, the test may be repeated with engine oil temperature measured by a probe in the oil level dipstick tube to be at least 600 C:

Provided that the above test shall not be carried out if the On Board Diagnostic (OBD) Malfunction Indicator Lamp (MIL) of BS-IV vehicles is switched on; in such cases, the vehicle shall be re-submitted for the above test after repair or servicing:

Provided further that only for Type Approval purposes, all new models type approved on or before the commencement of the Central Motor Vehicles (Tenth Amendment) Rules, 2015 and complying with the requirements of free acceleration smoke as provided in the Central Motor Vehicles (Amendment) Rules, 2012, published vide notification number GSR 103(E) dated 23rd February 2012, need not be re type-approved for compliance to this sub-rule.]

[Substituted by Notification No. G.S.R. 498 (E), dated 16.6.2015 (w.e.f. 2.6.1989)]

(3)

On and from the [date]

[Brought into force on 1st day of April, 1991 vide S.O. 869(E), dated 27.10.1989.]

of commencement of this sub-rule, all petrol-driven vehicles shall be so manufactured that they comply with the mass emission standards as specified at Annexure I. The breakdown of the operating cycle used for the test shall be as specified at Annexure II, and the reference fuel for all such tests shall be specified in Annexure III to these rules.

(4)

On and from the [date]

[Brought into force on 1st day of April, 1991 vide S.O. 869(E), dated 27.10.1989.]

of commencement of this sub-rule, all diesel-driven vehicles shall be so manufactured that they comply with the standards based on exhaust gas opacity as specified at Annexure IV to these rules.

(5)

On and from the [date]

[Brought into force on 1st day of April, 1992 vide S.O. 869(E), dated 27.10.1989.]

of commencement of this sub-rule, all petrol-driven vehicles shall be so manufactured that they comply with the following levels of emissions [when tested as per test cycle specified in Annexure V]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

:-

Mass of Carbon Monoxide

(CO)

Mass of Hydrocarbons

(HC)

Mass of Nitrogen Oxides

(NO)

Maximum grams per KWH

Maximum grams per KWH

Maximum grams per KWH

14

3.5

18

[Provided the standards for exhaust gas emissions applicable to agricultural tractors shall be notified separately.]

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(6)

Each motor vehicle manufactured on and after the dates specified in sub-rule (2), (3), (4) or (5), shall be certified by the manufacturers to be conforming to the standards specified in the said sub-sections, and further certify that the components liable to effect the emission of gaseous pollutants are so designed, constructed and assembled as to enable the vehicle, in normal use, despite the vibration to which it may be subjected, to comply with the provisions of the said sub-rule.

(7)

[After the expiry of a period of one year from the date on which the motor vehicle was first registered, every such vehicle shall carry a valid "Pollution under control" certificate issued by an agency authorized for this Purpose by the State Government. The validity of the certificate shall be for [six months]

[Added by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

and the certificate shall always be carried in the vehicle and produced on demand by the officers referred to in sub-rule (1) of rule 116.

[Provided that the validity of the certificate shall be twelve months for the vehicles manufactured as per [Bharat Stage-IV or Bharat Stage-VI]

[Inserted by Notification No. G.S.R. 103 (E) dated 23.2.2012 (w.e.f. 2.6.1989)]

norms.]

(8)

The certificate issued under sub-rule (7) shall, while it remains effective, be valid throughout India.]

(9)

[Mass emission standard for diesel vehicles]

[Substituted by GSR 163(E), dated 29.3.1996 (w.e.f. 1.4.1996). Earlier sub-Rule (9) was added by GSR 609(E), dated 15.9.1993 (w.e.f. 15.9.1993).]

Type approval tests

Vehicle Category

HC*(g/KWH)

CO*(g/KWH)

NO_x g/KWH

Smoke

Medium and Heavy over 3.5 Ton/GVW

Light diesel up to 3.5 Ton/GVW

or

2.4

2.4

11.2

11.2

14.4

14.4

Reference mass R(kg)

CO**

g/KM

HC+NO_x**

g/KM

R<1020

5.0

2.0

1020<R<1250

5.7

2.2

1250<R<1470

6.4

2.5

1470<R<1700

7.0

2.7

1700<R<1930

7.7

2.9

1930<R<2150

8.2

3.5

R<2150

9.0

4.0

Note:

*The test cycle is as per 13 mode cycle on dynamometer.

** The test should be as per Indian driving cycle with cold start.

***The emissions of visible pollutants (smoke) shall not exceed the limit value to smoke density. When expressed as light absorption coefficient given below for various nominal flows when tested as constant speeds over full load. (As indicated at Annexure I).

Cop Standards

*10% relaxation in the standards for HC, CO and NO_x would be given.

**10% relaxation in the standards for CO and combined HC+NO_x would be given.

[Mass emission standard for petrol-driven vehicles-Effective from 1st April, 1998

(i)

Passenger Cars

Type approval tests

Cubic Capacity (cm³)

Carbon Monoxide (gm/km)

HC+NO_x (gm/km)

Passengers cars fitted with catalytic converter

Passenger cars not fitted with catalytic converter

Passenger cars fitted with catalytic converter

Passenger cars not fitted with catalytic converter

<1400

4.34

8.68

1.50

3.00

>1400<2000

5.60

11.20

1.92

3.84

>2000

6.20

12.40

2.18

4.36

Notes.- 1. The tests will be as per Indian driving cycle with warm start. However, with effect from 1st April, 1998, the test will be as per Indian driving cycle with cold start for catalytic converter fitted vehicles as:-

Soak Temperature

20°-30°C

Soak Period

6.30 hrs

Preparatory running before sampling

4 cycles

Number of test cycles

6

Break down of cycles

Indian driving cycle as per

Annexure II

2. For passenger cars not fitted with catalytic converters, the test will continue to be with warm start as per existing procedure, till 1-4-2000.

3. There should be no crankcase emission.

4. Evaporative emission should not be more than 2.0g/test.

5. COP standards: 20% relaxation in the standards for Carbon Monoxide and combined HC + NOx would be given.

6. For vehicles fitted with catalytic converter a deterioration factor of 1.2 on Type Approval Limits will be applicable for durability.]

(ii)

Three-Wheelers (for all categories)-

CO

gms/km

6.75

HC +

NOx

gms/

km

5.40

Note:

1. The test will be as per Indian driving cycle with warm start. However, with effect from 1st April, 1998, the test will be as per Indian driving cycle with cold start.

2. COP standards: 20% relaxation in the standards for Carbon Monoxide and combined HC + NOx would be given.

(iii)

Two-Wheelers (for all categories)

CO

gms/Km

4.50

HC +

NOx

gms/

Km

3.60

Note:

1. The test will be as per Indian driving cycle with warm start. However, with effect from 1st April, 1998, the test will be

as per Indian driving cycle with cold start.

2. COP standards: 20% relaxation in the standards for Carbon Monoxide and combined HC+NOx would be given.

Annexure I

Nominal Flow

G(1/2)

Light Absorption

(K(1/m))

Nominal Flow

G(1/2)

Light Absorption

(K(1/m))

42

2.26

120

1.37

45

2.19

125

1.345

50

2.08

130

1.32

55

1.985

135

1.30

60

1.90

140

1.27

65

1.84

145

1.25

70

1.775

150

1.205

75

1.72

160

1.19

80

1.665

165

1.17

85

1.62

170

1.155

90

1.575

175

1.14

95

1.535

180

1.125

100

1.495

185

1.11

105

1.465

190

1.095

110

1.425

195

1.08

115

1.395

200

1.065]

[(10) Mass Emission Standards for vehicles manufactured on and after 1st June, 1999 in case of National Capital Region of Delhi and in other cases on and after 1st April, 2000]

[Sub-Rule (10) inserted by GSR 493(E), dated 28.8.1997 (w.e.f. 1.4.2000).]

.]

[Substituted by GSR 46(E), dated 21.1.1998 (w.e.f. 1.4.1998).]

A. For Petrol-Driven Vehicles

(1) Passenger Cars

CO(g

/kin)

Type Approval

2.72

Conformity of Production

3.16

Notes.-The test shall be as per the modified Indian driving cycle, with cold start, as specified in Annexure N-B, on Chassis Dynamometer.

There should be no crankcase emission.

Evaporative emission should not be more than 2.0g/test.

For vehicles fitted with catalytic converter, a deterioration factor of 1.2 on Type Approval Limits will be applicable for durability.

Commercial fuel shall be as notified by the Ministry of Environment and Forests vide Notification No. G.S.R. 176(E), dated the 2nd April, 1996.

Reference test fuel shall be as specified in Annexure IV-C.

2-Wheelers and 3-Wheelers

CO(g/km)

HC+NO_x(g/km)

2-Wheeler

3-Wheeler

2-Wheeler

3-Wheeler

Type Approval

2.0

4.0

2.0

2.0

Conformity of Production

2.4

4.8

2.4

2.4

Notes.-The test shall be as per the Indian driving cycle, with cold start, on Chassis Dynamometer as specified in Annexure IV-B to the principal rules.

Commercial fuel shall be as notified by the Ministry of Environment and Forests vide Notification No. G.S.R. 176(E), dated the 2nd April, 1996.

Reference test fuel shall be as specified in Annexure IV-C.

[For 2-wheelers and 3-wheelers fitted with catalytic converter, a deterioration factor of 1.2 on Type Approval Limits, will be applicable for durability:

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

Provided that the vehicle manufacturers may opt for an ageing test of 30,000 kms for evaluating deterioration factor, as per procedure that may be laid down by the Central Government.]

B. For Diesel Vehicles (Including Two and Three-Wheelers)

I. Vehicles with GVW exceeding 3.5 ton

Pollutants

Limits for

Type Approval

Conformity of Production

CO(g/kWh

4.5

4.9

HC(g/kWh)

1.1

1.23

NOx g/kWh

8.0

9.0

PM(g/k Wh) for engines with power exceeding 85kW

0.36

0.4

PM(g/k Wh) for engines with power exceeding 85kW

0.36

0.4

II. Vehicles with GVW equal to or less than 3.5 ton

Pollutants

Limits for

Type Approval

Conformity of Production

CO(g/kWh

4.5

4.9

HC(g/kWh)

1.1

1.23

NOx g/kWh

8.0

9.0

PM(g/k Wh) for engines with power exceeding 85kW

0.36

0.4

PM(g/k Wh) for engines with power exceeding 85kW

0.61

0.68

Or Chasis Dynamometer Test

Reference Mass (kg)

Limits for Type Approval gm/km

Limits for conformity of Production gm/km

CO

HC+NOx

PM

CO

HC+NOx

PM

R?1250

2.72

0.97

0.14

3.16

1.13

0.18

1250<R?1700

5.17

1.40

0.19

6.0

1.60

0.22

1700<R

6.90

1.70

0.25

8.0

2.0

0.29

Notes.-The test for vehicles with GVW equal to or less than 3.5 ton shall be as per the 13 mode cycle on engine dynamometer specified in Annexure N-A to the principal rules.

The test shall be as per the Indian driving cycle, for 2-Wheelers and 3-Wheelers and modified Indian driving cycle for 4-Wheelers with cold start, as specified in Annexure IV-B on Chassis Dynamometer.

For vehicles fitted with catalytic converters a deterioration factor 1.1 of CO; 1.0 for HC+NOx and 1.2 for PM on type approval limits will be applicable for durability.

The emission of visible pollutants (smoke) shall not exceed the limit value to smoke density, when expressed as light absorption co-efficient for various nominal flows as in Annexure I to rule 115(9), (Notification No. G.S.R. 163(E), dated

29th March, 1996), when tested at constant speeds over full load. These smoke limits are without correction factor and engines are to be tested with conditioned air supplied to the engine to maintain atmospheric factor of 0.98 to 1.02. Commercial fuel shall be as notified by the Ministry of Environment and Forests vide Notification No. G.S.R. 176(E), dated the 2nd April, 1996.

Reference test fuel shall be as specified in Annexure IV-D.]

[For 2-wheelers and 3-wheelers fitted with catalytic converter, the deterioration factor shall be as follows:

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

CO

=1.1

HC

+ NO_x =1.0

PM

=1.2:

Provided that the vehicle manufacturers may opt for an ageing test of 30,000 kms for evaluating deterioration factor, as per procedure that may be laid down by the Central Government:

Provided further that the above provisions shall come into force after six months from the publication of the notification.]

(11)

[Mass Emission Standards (Bharat Stage II):

(A)

Motor Cars with seating capacity of and up to 6 persons (including driver) and Gross Vehicle Mass (GVM) not exceeding 2500 kg.

Vehicles with

Standards (Type Approval=COP)(g/kin)

CO

(HC+NO_x)

PM

Gasoline engine

2.2

0.5

-

Diesel engine

1.0

0.7

0.08

(B)

Four-Wheeler Passenger Vehicles with GVW equal to or less than 3500kg and designed to carry more than 6 persons (including driver) or maximum mass of which exceeds 2500 kg.

|

Limit Values for Type Approval (TA) as well as COP

Class

Ref. Mass(rw) kg

Mass of CO(g/km)

Mass of HC+NO_x (g/km)

Mass of PM(g/km)

Gasoline

Diesel

Gasoline

Diesel

Diesel

|

rw<1250

2.2
1.0
0.5
0.7
0.08

II

1250<rw<1700

4.0
1.25
0.6
1.0
0.12

III

1700<rw

5.0
1.5
0.7
1.2
0.17

Notes:-

1. The test including driving cycle shall be as per sub-rule (10), with the modifications that:

(i)

there shall be no relaxation of norms for COP purposes,

(ii)

the tests shall be on Chassis dynamometer,

(iii)

the driving cycle shall be at a maximum speed of 90 kmph, and

(iv)

the reference fuel shall be of a maximum of 0.05% sulphur content.

2. Commercial fuel for meeting above norms shall be up to 0.05% mass maximum sulphur content.

3. There shall be no crankcase emissions for petrol-driven vehicles.

4. Evaporative emission shall not be more than 2.0g/test from petrol-driven vehicles.

5. For the above vehicles when fitted with catalytic converter deterioration factor shall be as follows:

Gasoline engines: CO=1.2; (HC+NO_x)=1.2;

Diesel engines: CO=1.1; (HC+NO_x)=1.0; PM=1.2:

Provided that the vehicle manufacturers may opt for an ageing test of 80,000 laps for evaluating deterioration factor, as per procedure that may be laid down by the Central Government.

6. For diesel engine vehicles, the emission of visible pollutants (smoke) shall not exceed the limit value to smoke density, when expressed as light absorption coefficient for various nominal flows as in Annexure I to rule 115(9) when tested at constant speeds over full load.]

(C)

Four-Wheeled Vehicles (other than passenger vehicles) with GVW equal to or less than 3500 kg shall conform the following norms:

Engine Dynamometer Test

Limit Values for Type Approval (TA) as well as (COP)

CO (g/kWh)

HC (g/kWh)

NO_x (g/kWh)

PM (g/kWh)

4.0

1.1

7.0

0.15

Or Chassis Dynamometer Test

Class

Ref. Mass (RM) Kg

Mass of CO (g/km)

Mass of HC+NO_x (g/km)

Mass of PM (g/km)

RM

Gasoline

Diesel

Gasoline

Diesel

I

RM?1250

2.2

1.0

0.5

0.7

0.08

II

1250<RM?1700

4.0

1.25

0.6

1.0

0.12

III

1700<RM

5.0

1.5

0.7

1.2

0.17

Notes:

1. (a) There shall be no relaxation for COP purposes.

(b)

The tests shall be carried out on the engine dynamometer operation as specified in Annexure IV-A of the rules. The tests on Chassis dynamometer shall be as per the driving cycle given in Note of clause (B) of sub-rule (11) of rule 115.

(c)

The reference fuel shall be of a maximum of 0.05% mass sulphur content.

2. Commercial fuel for meeting above norms shall be up to 0.05% maximum mass sulphur content.

3. For diesel engined vehicles the emission of visible pollutants (smoke) shall not exceed the limit value to smoke density, when expressed as light absorption coefficient for various nominal flows as in Annexure I to sub-rule (9) of rule 115 when tested at constant speeds over full load. These smoke limits are without correction factor and engines are to be tested with conditioned air supplied to the engine to maintain atmospheric factor of 0.98 to 1.02.

4. For diesel engined vehicles, the free acceleration smoke for naturally aspirated and turbo-charged engines shall not exceed the smoke density limit value as in clause (c) of sub-rule (2) of rule 115.]

5. There shall be no crankcase emissions for petrol engined vehicles.

6. Evaporative emission shall not be more than 2.0g/test from petrol engined vehicles.

(D)

Vehicles with GVW exceeding 3500kg shall conform the following norms:

Limit Values for Type Approval (TA) as well as (COP)

CO (g/kWh)

HC (g/kWh)

NOx (g/k Wh)

PM (g/kWh)

4.0

1.1

7.0

0.15

Notes:

1. (a) There shall be no relaxation for COP purposes.

(b)

The tests shall be carried out on the engine dynamometer operation as specified in Annexure IV-A of the rules.

(c)

The reference fuel shall be of a maximum of 0.05% mass sulphur content.

2. Commercial fuel for meeting above norms shall be up to 0.05% mass maximum sulphur content.

3. For diesel engined vehicles, the emission of visible pollutants (smoke) shall not exceed the limit value to smoke density, when expressed as light absorption coefficient for various nominal flow as in Annexure I to sub-rule (9) of rule 115 when tested at constant speeds over full load. These smoke limits are without correction factor and engines are to be tested with conditioned air supplied to the engine to maintain atmospheric factor of 0.98 to 1.02.

4. For diesel engined vehicles, the free acceleration smoke for naturally aspirated and turbo-charged engines shall not exceed the smoke density limit value as in clause (c) of sub-rule (2) of rule 115.

[Inserted by GSR 77(E), dated 31.1.2000. Brought into force in the National Capital Region w.e.f. 1.4.2000 vide GSR 77(E), dated 31.1.2000, in Mumbai (including Greater Mumbai) w.e.f. 1.1.2001) and in Calcutta and Chennai w.e.f. 1.7.2001 vide GSR 779(E), dated 29.8.2000.]

Inserted by GSR 286(E), dated 24.4.2001 published in the Gazette of India, dated 24.4.2001, Extraordinary, Part II, Section 3(i), Serial No. 198. In the National Capital Territory of Delhi in respect of Vehicles manufactured on or after six months from the date of publication in the Official Gazette, i.e., 24.4.2001 and in respect of the 'Four-Wheeled Transport Vehicles' which are playing on Inter-State Permits or on National Permits or on All India Tourist Permits within the jurisdiction of National Capital Territory of Delhi, and in respect of any Vehicles in other areas of country, from such date as the Central Government may, by notification appoint in the Official Gazette, and different dates may be appointed for different areas.

(12)

[Mass emission standards (Bharat Stage II) for two-wheeler and three-wheeler manufactured on and from 1st April, 2005 shall be as follows, namely:

Table

Vehicle Category

Pollutants

TA = COP

Norms g/km

TA=COP

D.F.(*)

(1)

(2)

(3)

(4)

Two-wheeler

(Petrol)

CO

1.50

1.2
 HC+NO_x
 1.50
 1.2
 Three-wheeler (Petrol)
 CO
 2.25
 1.2
 HC+NO_x
 2.00
 1.2
 Two-wheeler and three-wheeler (Diesel)
 CO
 1.00
 1.1
 HC+NO_x
 0.85
 1.0
 PM
 0.10
 1.2
 Deterioration Factor, see para (c) below.

(a)

The test shall be as per the Indian Driving Cycle with cold start on chassis dynamometer as specified in the Table given below by testing agencies, namely:

Table

Test Cell Conditions

Petrol two-wheeler and three-wheeler

Diesel two-wheeler and three-wheeler

(1)

(2)

(3)

Soak Temperature

20-30° C

20-30° C

Soak period

6-30 hours

6-30 hours

Preparatory running before sampling

Idling of 40 seconds and 4 cycles

Idling of 40 seconds

No. of test cycles

6

6

Breakdown of cycles

Indian Driving Cycle as per Annexure II to principal rule

Indian Driving Cycle as per Annexure II to principal rule

(b)

Reference fuel for testing shall be in line with that in the ECE;

(c)

(i)

For all types of two-wheeler and three-wheeler petrol vehicles, a deterioration factor as specified in column (4) in the Table in this sub-rule shall be applicable for durability:

Provided that the vehicle manufacturer may opt for an ageing test of 30,000 kins for evaluating deterioration factor, as per procedure that may be laid down by the Central Government from time to time;

(ii)

For all types of two-wheeler and three-wheeler diesel vehicles, a deterioration factor as specified in column (4) in the Table in this sub-rule shall be applicable for durability.

Provided that the vehicle manufacturer may opt for an ageing test of 30,000kins for evaluating deterioration factor, as per procedure that may be laid down by the Central Government from time to time;

(d)

For diesel engine vehicles, the emission of visible pollutants (smoke) shall not exceed the limit value to smoke density, when expressed as light absorption co-efficient for various nominal flow as indicated in Annexure I to sub-rule (9) of rule 115 when tested at constant speed over full load;

(e)

COP frequency and samples:

Sl.

No

Type of Vehicle

. Annual Production

COP Frequency

No.

Exceeding

Up to

(1)

(2)

(3)

(4)

(5)

1.

Two-wheeler and three-wheeler

250 per 6 months

10000 per year

Once every year

2.

Two-wheeler

10000 per year

150000 per 6 months

Once every 6 months

3.

Two-wheeler

150000 per 6 months

-

Once every 3 months

4.

Three-wheeler

1000 per year

75000 per 6 months

Once every 6 months

5.

Three-wheeler

75000 per 6 months

-

Once every 3 months

For production volumes of less than 250 per 6 months the method as prescribed in the proviso to rule 126-A shall apply;

(f)

Testing procedures shall be in accordance with the reference document MOST/CMVR/TAP-115/116 as amended from time to time by the Government of India in the Ministry of Road Transport and Highways:]

[Provided that Mass Emission Standards (Bharat Stage II) for diesel driven two-wheeler and three-wheeler shall come into force on the dates specified against each of the States in Table below:

Table

Sl.

No

State

Date

(1)

(2)

(3)

1.

Rajasthan

1stJune, 2005

2.

Uttar Pradesh, Mathura, Kannauj, Muzaffamagar, Aligarh, Farukkabad, Saharanpur, Badaun, Barreily, Moradabad, Hathras, Rampur, Bijnor, Agra, Pilibhi.t, J.P.

Nagar, Mainpuri, Lalitpur, Hardoi, Firozabad, Jhansi, Shahjahanpur, Etawah, Jalon, Lakhimpur Kheri, Etah, Mahoba and Sitapur

1stJune, 2005

3.

Uttaranchal

1stJuly, 2005

4.

Madhya Pradesh

1stSeptember, 2005

5.

Himachal Pradesh

1stOctober, 2005

6.

Jammu and Kashmir

1stOctober, 2005

7.

Punjab

1stOctober, 2005]

[Inserted by GSR 200(E), dated 1.4.2005 (w.e.f. 1.4.2005).]

(13) [Without prejudice to the provisions contained in clause (a) of sub-rule (2) of rule 1 of the Central Motor Vehicles (3rd Amendment) Rules, 2000 and clause (a) of sub-rule (ii) of rule I of the Central Motor Vehicles (2nd Amendment) Rules, 2001, notifications number S.O. 779(E), dated 29th August, 2000 and number S.O. 90(E), dated 27th January, 2003, issued under clause (b) of sub-rule (2) of rule 1 of the Central Motor Vehicles (3rd Amendment) Rules, 2000, notifications number S.O. 731(E), dated 21st July, 2001, number S.O. 801(E), dated 26th July, 2002 and number S.O. 940(E), dated 4th September, 2002, issued under clause (b) of sub-rule (ii) of rule 1 of the Central Motor Vehicles (2nd Amendment) Rules, 2001 and notification number S.O. 91(E), dated 27th January, 2003, issued under clause (b) of sub-rule (2) of rule 1 of the Central Motor Vehicles (3rd Amendment) Rules, 2000 and clause (b) of sub-rule (ii) of rule 1 of the Central Motor Vehicles (2nd Amendment) Rules, 2001, the provisions of sub-rule (11-)` shall, in respect of four-wheeled vehicles manufactured on and from the 1st April, 2005, come into force in all States and Union Territories

on the 1st day of April, 2005:]

[Inserted by GSR 927(E), dated 5.12.2003.]

[Provided that provisions of sub-rule (11) shall, in respect of four-wheeled vehicles to be registered in Sholapur and Lucknow, come into force in Sholapur and Lucknow from the 1st June, 2004:

Provided further that the above said provision shall not apply in respect of four-wheeled transport vehicles plying from Sholapur to other parts of the State of Maharashtra or from Lucknow to the other parts of the State of Uttar Pradesh; or on inter-State or National Permit or on the All India Tourist Permit, within the territorial jurisdiction of the said cities:]

[Inserted by GSR 200(E), dated 18.3.2004 (w.e.f. 1.6.2004).]

[Provided that Mass Emission Standards (Bharat Stage II) for diesel driven four wheeled vehicles shall come into force on the dates specified against each of the States in Table below :

Table
Sl.
No
State
Date
(1)
(2)
(3)
1.
Rajasthan
1stJune, 2005
2.
Uttar Pradesh, Mathura, Kannauj, Muzaffamagar, Aligarh, Farukkabad, Saharanpur, Badaun, Barreily, Moradabad, Hathras, Rampur, Bijnor, Agra, Pilibhi.t, J.P.
Nagar, Mainpuri, Lalitpur, Hardoi, Firozabad, Jhansi, Shahjahanpur, Etawah, Jalon, Lakhimpur Kheri, Etah, Mahoba and Sitapur
1stJune, 2005
3.
Uttaranchal
1stJuly, 2005
4.
Madhya Pradesh
1stSeptember, 2005
5.
Himachal Pradesh
1stOctober, 2005
6.
Jammu and Kashmir
1stOctober, 2005
7.
Punjab
1stOctober, 2005]

[Inserted by GSR 200(E), dated 1.4.2005 (w.e.f. 1.4.2005).]

(14)

Mass Emission Standards (Bharat Stage III).-The Mass Emission Standards for Bharat Stage III shall be as under:

(A)

Motor cars with seating capacity of and up to six persons (including driver) and Gross Vehicle Weight not exceeding 2500 kg.

Vehicles with

Limit Values for Type Approval (TA) as well as COP (g/km)

CO

HC
NOx
HC+NOx
PM

Gasoline

2.30

0.20

0.15

--

--

Diesel engine

0.64

--

0.50

0.56

0.05

(B)

Four-Wheeler Passenger Vehicles with Gross Vehicle Weight equal to or less than 3500 kg and designed to carry more than six persons (including driver) or 3000 kg.

and

(C)

Four-wheeled Vehicle (other than passenger vehicles) with Gross Vehicle Weight equal to or less than 3500 kg. shall conform.to the following norms:

| Limit Values for Type Approval (TA) as well as COP (g/km)

CO

HC

NOx

HC+NOx

PM

Class

Ref.Mass

(rw)kg

Gasoline

Diesel

Gasoline

Diesel

Gasoline

Diesel

Gasoline

Diesel

Diesel

I

rw?1305

2.30

0.64

0.20

--

0.15

0.50

--

0.56

0.05

II

1305<rw?1760

4.17

0.80

0.25

--

0.18

0.65

--

0.72

0.07

III

1760<rw

5.22

0.95

0.29

--

0.21

0.78

--

0.86

0.10

Notes.-

1. The test shall be on Chassis Dynamometer.

2. The test including driving cycle shall be as per sub-rule (10), with the modifications that

(i)

the exhaust gas sampling should start at the initiation of the engine start up procedure (refer Annexure IV-E);

(ii)

the driving cycle shall be at a maximum speed of 90 kmph (refer Annexure IV-E for the detailed cycle).

3. There shall be no relaxation of norms for COP purposes.

4. In case of vehicles operating on CNG or LPG all the provisions prescribed in rules 115-B and 115-C shall be applicable except that the norms to be complied with shall be as per these rules.

5. The reference fuel shall be as specified in Annexure IV-F, Annexure IV-G, Annexure IV H and Annexure IVI for diesel, petrol, LPG and CNG, respectively.

6. There shall be no crankcase emissions for petrol driven vehicles.

7. Evaporative emission shall not be more than 2.0 0-/test from petrol-driven vehicles. The Evaporative Emission test procedure for vehicles with positive-ignition engines shall be as described in Annexure VI of European Economic Community (EEC) Directive 70/220/EEC last amended by 98/69/EC.

8. The Conformity of Production (COP) testing procedure shall be as described in section 7 of Annexure I of EEC Directive 70/220/EEC (Refer Appendix I or Appendix 2 as applicable) last amended by 98/69/EC.

9. The COP frequency and samples:

(i)

The COP period for each vehicle model including its variants shall be once in a year.

(ii)

For production volume of less than 250 for six months, the method as prescribed in the provisos to rule 126-A shall apply.

10. The vehicles meeting the above norms shall use commercial fuel as per BIS specification IS:1460-2000 (Amendment No. I-January, 2003) (Fourth Revision) for Diesel and IS:2796-2000 (Amendment No. II-February, 2003) (Third Revision) for Gasoline.

11. For the vehicles described in clauses (A), (B) and (C) of this sub-rule, deterioration factor shall be as given below:

Engine category

Deterioration factors

CO

HC

NOx

HC+NOx

PM

Gasoline/Gas Engine

1.2

1.2

1.2

--

--

Diesel Engine

1.1

1.0

1.0

1.2

(i)

Alternatively, the vehicle manufacturers may opt for an ageing test of 80,000 kms for evaluating deterioration factor, as described in Annexure VII of European Economic Community Directive 70/220/EEC last amended by 98/69/EC with the following exceptions:

(a)

The maximum lap speed at 10th lap will be 72 km/h

(b)

The maximum lap speed at 11th lap will be 90 km/h

(ii)

The above ageing test should be carried out by the approved test agency.

12. For diesel vehicles, the emission of visible pollutants (smoke) shall not exceed the limit-value to smoke density, when expressed as light absorption co-efficient for various nominal flows as given in Annexure I of sub-rule (9) when tested at constant speeds over full load. These smoke limits are without correction factor and engines are to be tested with conditioned air supplied to the engine to maintain atmospheric factor of 0.98 to 1.02.

13. In case of diesel vehicles, the engine power shall be measured on engine dynamometer and the measured power shall not differ from the specified power as given below:

(i)

For Type approval: $\pm 5\%$ at maximum power point and $\pm 10\%$ at other measurement points for single cylinder engines. $\pm 2\%$ at maximum power point and $+ 6\%$, and $\pm 2\%$ at other measurement points for all other engines.

(ii)

Testing procedures shall be in accordance with Chapter 6 of Part IV of the reference document MOST/CMVR/TAP-115/116 as amended from time to time by the Government of India in the Ministry of Shipping, Road Transport and Highways.

14. The vehicles described in clauses (A), (B) and (C) of this sub-rule should comply with rule 115(2).

(D)

Diesel vehicles with GVW exceeding 3500 kg. shall conform to the following norms:

Limit Values for Type Approval (TA) as well as (COP)

Engine Steady State Cycle (ESC) test

Engine Load Response (ELR) test

CO

(g/kWh)

HC

(g/kWh)

NOx

(g/kWh)

PM

(g/kWh)(2)

Smoke

(m-1)(2)

2.1

0.66

5.0

0.10/0.13(1)

0.8

(1)

For engines having swept volume of less than 0.75 litre per cylinder and a rated power speed of more than 3000 rpm.

(2)

For diesel engines only.

Notes.

1. The test shall be on engine dynamometer.

2. There shall be no relaxation of norms for COP purposes.

3. The gaseous and particulate emissions are to be determined on the ESC test as described in EEC document 1999/96/EC.

4. The smoke opacity is to be determined on the ELR test as described in EEC document 1999/96/EC.

5. In case of vehicles operating on CNG or LPG mode all the provisions prescribed in rules 115-B and 115-C shall be respectively applicable, except that limiting value shall be as per clause (D) above.

6. The reference fuel shall be as specified in Annexure IV-F, Annexure IV-H and Annexure N-I for diesel, LPG and CNG, respectively.

7. The Conformity of Production (COP) testing procedure shall be as described in section 9 of Annexure I of EEC Directive 88/77/EEC last amended by 1999/96/EC.

8. The COP frequency and samples:

(i)

The COP period for each engine model including its variants shall be once in a year.

(ii)

For production volume of less than 250 for six months, the method as prescribed in the provisos to rule 126-A shall apply.

9. For diesel engine vehicles, the emission of visible pollutants (smoke) shall not exceed the limit value of smoke density, as per Annexure I to rule 115(9). These smoke limits are without correction factor and engines are to be tested with conditioned air supplied to the engine to maintain atmospheric factor of 0.98 to 1.02.

10. The vehicles meeting the above norms shall use commercial fuel as per BIS specification IS:1460-2000 (Amendment No. I-January, 2003) (Fourth Revision) for Diesel and IS:2796-2000 (Amendment No. II-February, 2003) (Third Revision) for Gasoline.,

11. In case of diesel vehicles, the engine power shall be measured on engine dynamometer and the measured power shall not differ from the specified power as given below:

(i)

For Type approval: +2% at maximum power point and +6% and ?2% at other measurement points.

(ii)

For conformity of production: ?5%/+8% at maximum power point.

(iii)

Testing procedures shall be in accordance with Chapter 6 of Part IV of the reference document MOST/CMVR/TAP-115/116 as amended from time to time by the Government of India in the Ministry of Shipping, Road Transport and Highways.

12. The vehicles mentioned in clause (D) shall also comply with rule 115(2).]

(E)

Diesel vehicles with GVW exceeding 3500 kg. and fitted with advanced exhaust after treatment system including De-NOx catalyst and/or particulate trap shall additionally conform to the following norms:

Limit Values for Type Approval (TA) as well as (COP)

Engine Transient Cycle (ETC)

CO (g/kWh)

HC (g/kWh)

NOx (g/kWh)

PM (g/kWh)

5.45

0.78

5.0

0.16/0.21(3)

(3)

For engines having swept volume of less than 0.75 litre per cylinder and rated power speed of more than 3000 rpm.

Notes.-

1. The test shall be on engine dynamometer.

2. There shall be no relaxation for COP purposes.

3. The gaseous and particulate emissions are to be determined on the ETC test as described in EEC document 1999/96/EC and comply with the norms given above.

4. In addition, the gaseous and particulate emissions are to be determined on the ESC test as described in EEC document 1999/96/EC and meet the prescribed gaseous and particulate emissions norms as given in clause (D).

5. In addition, the smoke opacity is to be determined on the ELR test as described in EEC document 1999/96/EC and meet the prescribed smoke density norms as given in clause (D).

6. The reference fuel shall be as specified in Annexure N-F.

7. The Conformity of Production (COP) testing procedure shall be as described in section 9 of Annexure I of EEC Directive 88/77/EEC last amended by 1999/96/EC.

(8)

The COP frequency and samples:

(i)

The COP period for each engine model including its variants shall be once in a year.,

(ii)

For production volume of less than 250 for six months, the method as prescribed in the provisos to rule 126-A shall apply.

(9)

For diesel engine vehicles, the emission of visible pollutants (smoke) shall not exceed the limit value of smoke density, as per Annexure I to rule 115(9). These smoke limits are without correction factor and engines are to be tested with conditioned air supplied to the engine to maintain atmospheric factor of 0.98 to 1.02.

10. The vehicles meeting the above norms shall use commercial fuel as per BIS specification IS:1460-2000 (Amendment No. I-January, 2003) (Fourth Revision) for Diesel.

11. In case of diesel vehicles, the engine power shall be measured on engine dynamometer and the measured power shall meet the requirements as given below:

(i)

For Type approval: $\pm 2\%$ at maximum power point and $+6\%$ and -2% at other measurement points.

(ii)

For conformity of production: $\pm 5\%$ $+8\%$ at maximum power point.

(iii)

Testing procedures shall be in accordance with Chapter 6 of Part IV of the reference document MOST/CMVR/TAP-115/116 as amended from time to time by the Government of India in the Ministry of Shipping, Road Transport and Highways.

12. The vehicles mentioned in clause (E) shall also comply with rule 115(2).

[Inserted by GSR 720(E), dated 10.9.2003.]

Inserted by GSR 686(E), dated 20.10.2004. Brought into force- (a) in the National Capital Region and the cities of Mumbai, Kolkata, Chennai, Bangalore, Hyderabad including Secunderabad, Ahmedabad, Pune, Surat, Kanpur and Agra in respect of four-wheeled vehicles manufactured on and from 1st April 2005, except in respect of four-wheeled transport vehicles playing on Inter-State Permits or National Permits or All India Tourist Permits within the jurisdiction of these cities; and (b) in other areas of the country, from such date as may be notified by the Central Government. Here 'National Capital Region' shall have the same meaning as assigned to it in clause (f) of section 2 of the National Capital Region Planning Board Act, 1985 (

2 of 1985

).

(F)

[Mass Emission Standards (Bharat Stage III) as specified in sub-clause (iii) shall be applicable in the National Capital Region and the cities of Mumbai, Kolkata, Chennai, Bangalore, Hyderabad including Secunderabad, Ahmedabad, Pune, Surat, Kanpur, Agra, Sholapur and Lucknow in respect of two and three wheeler vehicles manufactured on or after 1st April, 2010.:

[Substituted by G.S.R. 443 (E), dated 21.5.2010.]

(ii)

the Mass Emission Standards (Bharat Stage-III) as specified in sub clause (iii) shall be applicable in all the States and the Union Territories except* National Capital Region and the cities of Mumbai, Kolkata, Chennai, Bangalore, Hyderabad including Secunderabad, Ahmedabad, Pune, Surat, Kanpur, Agra, Solahpur and Lucknow in respect of two and three wheeler vehicles manufactured on or after 1st October, 2010.

(iii)

the Mass Emission Standards (Bharat Stage-III) for two and three wheeler vehicles shall be as under :-]

Vehicle Category

Pollutants

T A=COP norms

(g/km)

(Deterioration Factor)

(1)

(2)

(3)

(4)

Two-wheelers

(Gasoline)

CO

HC+NO_x

1.0

1.0

1.2

1.2

Three-wheelers

(Gasoline)

CO

HC+NO_x

1.25

1.25

1.2

1.2

Two-wheelers and Three-wheelers (Diesel)

CO

HC+NO_x

PM

0.50

0.50

0.50

1.1

1.0

1.2

Notes.-

1. (a) For vehicles operating on CNG mode, the provisions of rule 115-B shall be applicable.

(b)

For vehicles operating on LPG mode, the provisions of rule 115-C shall be applicable.

2. The reference fuel for Diesel and Gasoline vehicle shall be as specified in Annexure IV-F and Annexure IV-G respectively and reference fuel for CNG and LPG shall be as available commercially.

3. The commercial fuel for Gasoline and Diesel vehicle shall be as per BIS Specification IS: 1460-2005 (Fifth revision) for Diesel and IS: 2796-2008 (Amendment No. I-January, 2008) (Forth Revision) for Gasoline, Specification for Commercial CNG and LPG shall be as notified from time to time.

4. The provisions of clauses (a), (c), (d), (e) and (f) of sub-rule (12) of rule 115, except the proviso therein, shall be applicable to the said vehicles.

5. In case of diesel vehicles, the engine power shall be measured on engine dynamometer and the measured power shall conform to the power specified in Chapter 1 of Part IV of MoSRTTH/CMVR/TAP-115/116 as amended from time to time, when tested as per the procedures laid down in Chapter 6 of Part IV of MoSRTTH/CMVRIT AP - 115/116 as amended from time to time

6.

(i)

Gasoline/CNG/LPG vehicles specified herein shall comply with the provisions of clause (i) of sub-rule (2) of rule 115.

(FA)

[Alternate Mass Emission Standards (Bharat Stage III) for two wheeler gasoline vehicles, with engine capacity exceeding 50cc or a maximum design speed exceeding 50 km/hour, based on Worldwide Harmonised Motorcycle Emissions Certification (WMTC) Procedure shall be as under:-

Class

Pollutants

TA

= COP norms Including Deterioration Factor (g/km)

(1)

(2)

(3)

Class

1 and

Sub

Class 2.1

Co

1.87

HC+NO_x

1.08

Sub

Class 2.2

CO

2.62

HC+NO_x

0.92

Sub

Class 3.1

CO

2.62

HC+NO_x

0.55

Sub

Class 3.2

CO

2.62

HC+Nox

0.55

Explanatory Notes:-

For the purpose of this clause,-

1. Classification of vehicles and weighting factor for final emission result shall be as given below:-

Definition of

Class

Cycles

Weighting

factors for final emission results

Class

1

Engine

capacity above 50 CC but less than 150 cc and vehicle maximum speed equal or less than 50 km/h or engine capacity less than 150 CC and vehicle maximum speed more than 50 km/h but less than 100 km/h.

Part

1 Reduced Speed cold followed by Part 1 Reduced Speed Hot

Part 1 Reduced

Speed cold shall be 50% and Part 1 reduced Speed Hot shall be 50%

Sub

Class 2.1

Engine capacity

less than 150 cc and vehicle maximum speed equal to or more than 100 km/h but less than 115 km/h or engine capacity 150 cc and above and vehicle maximum speed less than 115 km/h

Part 1 Reduced

Speed cold followed by Part 1 reduced Speed Hot

Part Reduced Speed

cold shall be 50% and part 1 reduced Speed Hot shall be 50%

Sub

Class 2.2

Any

engine capacity and vehicle maximum speed equal to or more than 115 km/h but less than 130 km/h

Part 1 cold

followed by Part 2 Hot

Part 1 cold shall

be 30% and Part 2 Hot shall be 70%

Sub

Class 3.1

Any

engine capacity, vehicle maximum speed equal to or more than 130 km/h but less than 140 km/h

Part 1 cold

followed by Part 2 Hot followed by Part 3 Reduced Speed

Part 1 cold shall

be 25% Part 2 Hot Shall be 50% and Part 3 Reduced shall

be 25%

Sub

Class 3.2

Any

engine capacity and vehicle maximum speed equal to or more than 140 km/h

Part 1 cold

followed by Part 2 Hot followed by Part 3

Part 1 Cold shall

be 25% Part 2 Hot shall be 50% and Part 3 shall be 25%

2. The test procedure and driving cycles shall be as per United Nations Economic Commission for Europe (UNECE) Global Technical Regulation (GTR)- 2 incorporating Amendment 2, with preconditioning, soaking and cold start on chassis dynamometer as specified above.

3. Vehicle preconditioning: Operated through the cycles prescribed as above.

4. Vehicle soaking: The vehicle shall be stored for not less than six hours and not more than thirty-six hours prior to the cold start Type I test or until the engine oil temperature (T_o) or the coolant temperature (T_e) or the spark plug seat/gasket temperature (T_p), only for air cooled engine, equals the air temperature of the soak area.

5. Preparatory running before sampling is not required, sampling starts at $T=0$ second.

6. Break down of different parts of Worldwide Harmonised Motorcycle Emissions Certification (WMfC) shall be as per the details given in Annexure 5 of Chapter XIII A of Ministry of Road Transport and Highways/Central Motor Vehicles Rules/Type Approval Procedure-115/116 (MoRTH/CMVR/TAP-115/116).

7. Reference fuel shall be as specified in Annexure IV-G of the said rules.

8. Requirements of durability have been built in the mass emission standards specified above.

9. Conformity of Production (COP) frequency and sampling shall be as per clause (e) of sub-rule 12 of rule 115 of the said rules.

10. Test procedure shall be in accordance with Ministry of Road Transport and Highways/Central Motor Vehicles Rules/Type Approval Procedure-115/116 (MoRTH/CMVR/TAP-115/116).

11. The vehicles shall comply with the provisions of clause (i) of sub-rule (2) of rule 115 of the said rules.

12. The commercial fuel for gasoline vehicle shall be as per Bureau of Indian Standards specification IS: 2796-2008 for gasoline.]

(ii)

Diesel vehicles specified herein shall comply with clause (ii) of sub-rule (2) of rule 115.

(G)

[The provisions of this sub-rule in respect of four wheeler vehicles manufactured on and from the 1st October, 2010 shall apply to all the State and the Union Territories except* National Capital Region and the cities of Mumbai, Kolkata, Chennai, Bangalore, Hyderabad including Secunderabad, Ahmedabad, Pune, Surat, Kanpur, Agra, Sholapur and Lucknow.]

[Substituted by G.S.R. 443 (E), dated 21.5.2010]

(15)

Mass Emission Standards (Bharat Stage IV) for M and N Category vehicles:-

(a)

the Mass Emission Standards for Bharat Stage IV shall come into force in the National Capital Region and the cities of Mumbai, Kolkata, Chennai, Bangalore, Hyderabad including Secunderabad, Ahmedabad, Pune, Surat, Kanpur and Agra in respect of four-wheeled vehicle manufactured on or after the 1st April, 2010, except the four-wheeled transport

vehicles plying on Inter-State permits or National permits or All India Tourist permits, within the jurisdiction of these cities.

[Provided that the Mass Emission Standards (Bharat Stage-IV) shall be applicable in the cities of Sholapur and Lucknow in respect of four wheeler vehicles manufactured on or after 1st June, 2010 except the four wheeler transport vehicles plying on Inter-State Permits or National Permits or All India Tourist Permits, within the jurisdiction of the said cities]

[Inserted by G.S.R. 443(E), dated 21.5.2010.]

Explanation. - For the purposes of sub-rules (14) and (15), the "National Capital Region" shall have the same meaning as assigned to it in clause (J) of section 2 of the National Capital Region Planning Board Act, 1985 (

2 of 1985

);

(aa)

[without prejudice to the provisions contained in the provisos to clause (a), the Mass Emission Standards for Bharat Stage IV shall come into force all over the the country in respect of four wheeled vehicles manufactured on or after the 1st April, 2017.]

[Inserted by Notification No. G.S.R. 643(E), dated 19.8.2015 (w.e.f. 2.6.1989).]

(b)

the Mass Emission Standards for Bharat Stage IV shall be as under:-

(i)

the mass emission standards for Bharat Stage-IV, Category M and Category N vehicles manufactured on or after the 1st April, 2010, with Gross Vehicle Weight not exceeding 3,500 kg, shall be as under;

Limit Values for TA and COP

Category

Class

Reference Mass (RW) (kg)

Mass of Carbon Monoxide (CO) (g/km)

Mass of Hydro Carbon (HC) (g/km)

Mass of Oxides of Nitrogen (NOx)(g/km)

Combined mass of Hydro-carbons and Oxides of Nitrogen (HC+NOx) (g/km)

Mass of Particulates (PM) (g/km)

Gasoline

Diesel

Gasoline

Gasoline

Diesel

Diesel

Diesel

M*

-

All

1.00

0.50

0.10

0.08

0.25

0.30

0.025

N1 and M**

I

RW?1305

1.00

0.50
0.10
0.08
0.25
0.30
0.025

II

1305<RW?1760

1.81
0.63
0.13
0.10
0.33
0.39
0.04

III

1760<RW

2.27
0.74
0.16
0.11
0.39
0.46
0.06

*These limits are not applicable for vehicles designed to carry more than six persons including driver or vehicles whose gross vehicle weight exceeds 2,500 kg.

**These limits are applicable for vehicles designed to carry more than six persons including driver or vehicles whose gross vehicle weight exceeds 2,500 kg.

Notes.-

1. The test shall be on Chassis Dynamometer.
2. The test including driving cycle shall be as provided in sub-rule (10) with the modifications that

(i)

The exhaust gas sampling should start at the initiation of the engine start up procedure referred to in Annexure IV-E.

(ii)

The driving cycle shall be at a maximum speed of 90 km/hour referred to in Annexure IV-E.

3. There shall be no relaxation of norms for Conformity of Production (COP) purposes.

4.

(i)

In case of vehicles operating on CNG, the provisions in rule 115-B shall be applicable.

(ii)

In case of vehicles operating on LPG, the provisions in rule 115-C shall be applicable.

5. The reference fuel shall be as specified in Annexure IV-J for Gasoline vehicles, Annexure IV-K for Diesel vehicles, Annexure IV-L for CNG (G20 and G25) vehicles and Annexure IV-M for LPG (Fuel A and Fuel B) vehicles respectively. Reference Fuel as per Annexure IV-L and IV-M shall be used for Type Approval and Conformity of Production one year after the same is available to the test agencies. Till then, Commercial CNG/LPG fuel shall be used.

6. There shall be no crankcase emissions for Gasoline driven vehicles.

7. Evaporative emission shall not be more than 2.0 g/test from Gasoline driven vehicles. The evaporative emission test procedure for gasoline driven vehicles shall be as per the procedure specified in MoSRT/CMVR/TAP-115/116 and as amended from time to time.

8. The Conformity of Production (COP) testing procedure shall be as described in MoSRT/CMVR/TAP-115/116 as amended from time to time.

9. The COP frequency and samples:

(i)

The Conformity of Production period for each vehicle model including its variant(s) shall be once in a year;

(ii)

Where production volume in six months is less than 250 per model including its variants, the provisions contained in the provisos to rule 126-A shall apply.

10. The commercial Gasoline and Diesel fuel shall be as per Annexure IV-N and IV-O in respect of the places mentioned in clause (a) of this sub-rule and in respect of all other places, the commercial fuel shall be Bharat Stage-III as per BIS specification IS : 1460-2005 (fifth revision) for Diesel and IS : 2796-2008 (Amendment No. 1, January 2008) (forth revision) for Gasoline Specification for commercial CNG and LPG shall be as notified from time to time.

11. For the vehicles of the Category M and Category N with Gross Vehicle Weight not. exceeding 3,500 kg.

(i)

Deterioration factor shall be as given below :

Engine Category

Deterioration Factor

CO

HC

NOx

HC+NOx

PM

Gasoline/Gaseous Fueled engines

1.2

1.2

1.2

Not applicable

Diesel Engines

1.1

Not applicable

1.0

1.0

1.2

(ii)

Alternatively, the vehicle manufacturers may opt for an ageing test of 80,000 km for evaluating deterioration factor as per MoSRTTH/CMVR/TAP-115/116 and as amended from time to time.

(iii)

The maximum lap speed at 10th lap and at 11th lap shall be 72 km/hour and 90 km/hour respectively.

(iv)

The above ageing test should be carried out by the approved test agency specified in rule 126.

12. For Diesel Vehicles, the emission of visible pollutants (smoke) shall not exceed the limit value of smoke density, when expressed as light absorption co-efficient for various nominal flows as given in Annexure I to sub-rule (9) of rule 115 when tested at constant speeds over the full load. These smoke limits are without correction factor and engines are to be tested with conditioned air supplied to the engine to maintain atmospheric factor at 0.98 to 1.02.

13. In the case of Diesel vehicles, the engine power shall be measured on engine dynamometer and the measured power shall conform to the power specified in Chapter 1 of Part IV of MoSRTTH/CMVR/TAP-115/116 as amended from time to time, when tested as per the procedures laid down in Chapter 6 of Part IV of MoSRTTH/CMVR/TAP -115/116 as amended from time to time.

14.

(i)

All Gasoline/CNG/LPG vehicles specified in this sub-clause shall comply with the provisions of clause (i) of sub-rule (2) of rule 115.

(ii)

All Diesel Fueled Vehicles specified in this sub-clause shall comply with the provisions of clause (ii) of sub-rule (2) of rule 115.

15. The vehicles of the Category M and Category N with Gross Vehicle Weight not exceeding 3,500 kg: shall be equipped with On-Board Diagnostic (OBD) systems for emission control which shall have the capability of identifying the likely area of malfunction by means of fault codes stored in computer memory for vehicles manufactured on and from 1st April 2010 as per the procedure laid down in MoSRT/CMVR/TAP-115/116 and as amended from time to time. The On-Board Diagnostic (OBD) systems for emission control shall be as specified in the Tables below:

TABLE I

On-Board Diagnostic

(OBD)

systems for emission control:

Sl.No.

Engine Type

Category of Vehicles

Year

OBD I Vehicles manufactured on and from

OBD II vehicles manufactured on and from

1.

Gasoline Fueled Engines

M1 and M2 (less than 3,500 kg GVW)

1stApril 2010

1stApril 2013

2.

Gasoline Fueled Engines

N1

1stApril 2010

1stApril 2013

3.

LPG or CNG fueled Engines

M1 and M2 (less than 3,500 kg GVW)

-

1stApril 2013

4.

LPG or CNG fueled Engines

N1

-

1stApril 2013

5.

Compression Ignition Engines

M1 and M2 (less than 3,500 kg GVW)

1stApril 2010

1stApril 2013

6.

Compression Ignition Engines

N1

1stApril 2010

1stApril 2013

7.

All

Vehicles above 3,500 kg GVW

-

1stApril 2013

TABLE II

All Positive Ignition Vehicles

OBD Monitoring Items

Monitoring Items

OBD I Vehicles manufactured on and from

OBD II vehicles manufactured on and from

Catalyst

-

1stApril 2013

Misfire

-

1stApril 2013

O(Oxygen) sensor

1stApril 2010

1stApril 2013

Secondary Air system (if provided)

1stApril 2010

1stApril 2013

Coolant temperature

1stApril 2010

1stApril 2013

EGR, (Exhaust Gas Recirculation) (if provided)

1stApril 2010

1stApril 2013

Fuel tank leakage and evaporation

-

1stApril 2013

Fuel system

-

1stApril 2013

Emission Control systems/components

(Comprehensive Components)

1stApril 2010

1stApril 2013

Circuit continuity for all emission related power train components

1stApril 2010

1stApril 2013

Distance traveled since MIL (Malfunction Indicator Lamp) ON

1stApril 2010

1stApril 2013

TABLE III

All Compression Ignition Vehicles

OBD Monitoring Items

Monitoring Items

OBD I Vehicles manufactured on and from

OBD II vehicles manufactured on and from

Catalyst

-

1stApril 2013

Electronic fuel Injection system

1stApril 2010

1stApril 2013

Particulate Trap (if provided)

-

1stApril 2013

Coolant temperature

1stApril 2010

1stApril 2013

EGR, (Exhaust Gas Recirculation) (if provided)

1stApril 2010

1stApril 2013

Fuel system

-

1stApril 2013

Emission Control systems/components

(Comprehensive Components)

1stApril 2010

1stApril 2013

Circuit continuity for all emission related power train components

1stApril 2010

1stApril 2013

Distance travelled since MIL (Malfunction Indicator Lamp) ON

1stApril 2010

1stApril 2013

16. For vehicles manufactured on and from 1st April 2013, the On-Board Diagnostic-II (OBD-II) systems for emission control must indicate the failure of an emission-related component or system, as per the procedure laid down in MoSRT/CMVR/TAP-115/116 and as amended from time to time, when that failure results in an increase in emissions above the limits given in the Table below:

| Reference Mass

Mass of Carbon Monoxide

Mass of Hydrocarbons

Mass of oxides of Nitrogen (g/km)

Mass of Particulates

(RW)

(CO)

(HC)

(NOx)

(PM)

(kg)

(g/km)

(g/km)

(g/km)

(g/km)

Category

Class

| Petrol

Diesel

Petrol

Diesel

Petrol

Diesel

Diesel

M*

-

All

3.2

3.2

0.4

0.4

0.6

1.2

0.18

N1 and M**

I

RW?1305

3.2

3.2

0.4

0.4

0.6

1.2

0.18

| II

1305<RW?1760

5.8

4.0

0.5

0.5

0.7

1.6

0.23

| III

176<RW

7.3

4.8

0.6

0.6

0.8

1.9

0.28

*These limits are not applicable for vehicles designed to carry more than six persons including driver or vehicles whose gross vehicle weight exceeds 2,500 kg.

**These limits are applicable for vehicles designed to carry more than six persons including driver or vehicles whose gross vehicle weight exceeds 2,500 kg.

(ii)

Vehicles with Gross Vehicle Weight exceeding 3,500 kg manufactured on or after the 1st April, 2010 and equipped with either the diesel engines or the CNG Engines or the LPG Engines shall conform to the following norms: ^

(A)

For Diesel engines

Limit values for Type Approval (TA) as well as (COP)

Engine Steady State Cycle (ESC) test

Engine Load Response (ELR) test

CO (g/kWh)

HC (g/kWh)

NOx(g/kWh)

PM (g/kWh)

Smoke(m-1)

1.5

0.46

3.5

0.02

0.5

(B)

For diesel engines, CNG Engines or LPG Engines

Engine Transient Cycle (ETC) test

CO(g/kWh)

NMHC(1)(g/kWh)

CH4(2)

NOx(g/kWh)

PM(3)

4.0

0.55

1.1

3.5

0.03

(1)

A manufacturer may choose to measure the mass of total hydrocarbons (THC) instead of measuring the mass of non-methane hydrocarbon (NMHC). In this case, the limit for mass of THC should be same as for the NMHC.

(2)

For CNG engines only.

(3)

For Diesel engines only.

Notes.

1. The test shall be done on engine dynamometer.

2. There shall be no relaxation of norms for Conformity of Production (COP) purposes.

3. In case of vehicles operating on diesel fueled engines, the gaseous and particulate emissions shall be as per Engine Steady State Cycle (ESC) and Engine Transient Cycle (ETC) and smoke test shall be as per Engine Load Response (ELR) as specified in MoSRTTH/CMVR/TAP-115/116 and as amended from time to time.

4. In case of vehicles operating on CNG or LPG fueled engines, the gaseous emissions are to be determined only on the Engine Transient Cycle (ETC) test as specified in MoSRTTH/CMVR/TAP-115/116 as amended from time to time.

5. The smoke opacity is to be determined on the Engine Load Response (ELR) test as specified in Part XII of MoSRTTH/CMVR/TAP-115/116 as amended from time to time.

6. In case of vehicles operating on CNG or LPG mode, the provisions of rules 115-B and 115-C shall be applicable respectively.

7. The reference fuel shall be as specified in Annexure IV-K for Diesel vehicles, Annexure IV-L for CNG (G20, G23 and G25) vehicles and Annexure IV-M for LPG (Fuel A and Fuel B) vehicles respectively. Reference Fuel as per Annexure IV-L and IV-M shall be used for Type Approval and Conformity of Production, one year after the same is available to the test agencies. Till then, Commercial CNG/LPG fuel shall be used.

8. The Conformity of Production (COP) testing procedure shall be as specified in MoSRTTH/CMVR/TAP-115/116 as amended from time to time.

9. The Conformity of Production (COP) frequency and samples:

(i)

The Conformity of Production period for each engine model including its variant(s) shall be once a year;

(ii)

Where production volume in six months is less than 250 per model including its variants, the provisions contained in the provisos to rule 126-A shall apply.

10. For diesel engine vehicles, the emission of visible pollutants (smoke) shall not exceed the limit value of smoke density, as per Annexure I to sub-rule (9) of rule 115. These smoke limits are without correction factor and engines are to be tested with conditioned air supplied to the engine to maintain atmospheric factor of 0.98 to 1.02.

11. The commercial Diesel fuel shall be as per Annexure IV-O in respect of the places mentioned in sub-clause (i) of clause (a) of this sub-rule and in respect of all other places, the commercial fuel shall be as per BIS specification IS : 1460-2005 (fifth revision) for Diesel. Specification for Commercial CNG and LPG shall be as notified from time to time.

12. For vehicles with Gross Vehicle Weight exceeding 3,500 kg manufactured on or after the 1st April, 2010,-

(i)

deterioration factor shall be as given in the Table below:

Engine type

Test cycle

CO

HC

NMHC

CH₄

NO

PM

Diesel engine

ESC

1.1

1.05

-

-

1.05

1.1

ETC

1.1

1.05

-

-

1.05

1.1

CNG,LPG or Gaseous Fueled engine

ETC

1.1

1.05

1.05

1.2

1.05

-

(ii)

alternatively, the vehicle manufacturers may opt for evaluation of deterioration factor as specified in MoSRTTH/CMVR/TAP-115/116 as amended from time to time.

Category of Vehicle in which engine will be installed

Minimum Service accumulation period

Category N1 vehicles

100,000km

Category N2 Vehicles

125,000 km

Category N3 Vehicles with GVW equal to or less than 16,000 kg

125,000 km

Category N3 Vehicles with GVW above 16,000 kg

167,000 km

Category M2 Vehicles

100,000 km

Category M3 Vehicles with GVW equal to or less than 7,500 kg

125,000 km

Category M3 Vehicles with GVW above 7,500 kg

167,000 km

The above ageing test should be carried out by the approval test agency.

13. In the case of Diesel vehicles, the engine power shall be measured on engine dynamometer and the measured power shall not differ from the specified power as given in Chapter 1 of Part IV of MoSRTTH/CMVR/TAP-115/116 as amended from time to time when tested as per procedures laid down in Chapter 6 of Part IV of MoSRTTH/CMVR/TAP-115/116 as amended from time to time.

14.

(i)

The CNG and LPG vehicles specified in this sub-clause shall comply with the provisions of clause (i) of sub-rule (2) of rule 115;

(ii)

All Diesel Fueled Vehicles specified in this sub-clause shall comply with the provisions of clause (ii) of sub-rule (2) of rule 115.

15. The extension of type approval to engine family and engine after treatment system family shall be as described in MoSRTTH/CMVR/TAP-115/116 as amended from time to time.

16. The vehicles specified in this sub-clause shall be equipped with an On Board Diagnostic systems for emission control which shall have the capability of identifying the likely area of malfunction by means of fault codes stored in computer memory for vehicle manufactured on and from 1st April 2013, as per procedure laid down in MoSRTTH/CMVR/TAP-115/116 and as amended from time to time.

17. The Diesel engine NOx reduction agent AUS 32 (Aqueous Urea Solution) shall conform to Part 1 and Part 2 of ISO 22241-2006.

Inserted by G.S.R. 84(E), dated 9.2.2009 (w.e.f. 1.4.2010)

(16)

[Mass emission standards (Bharat Stage IV) for two wheelers, - The following mass emission standards (Bharat Stage IV) shall come into force for two wheelers manufactured on and after the 1st April, 2016 for new types of vehicle models and from the 1st April, 2017 for existing types of vehicle models -

A. Two wheeled vehicles fitted with gasoline engines -

I. Mass emission standards (Bharat Stage IV) for two wheelers, with engine capacity exceeding 50 cc and a maximum design speed exceeding 50 km per hour; Based on World-wide Harmonized Motorcycle Test Cycle (WMTC)-

Table 1

Class

TA=COP norms (g/km)

CO

NOx

HC + NOx

If the evaporative emission commission with 2

g/test

If the evaporative emission complies with 6 g/test

(1)

(2)

(3)

(4)

(5)

Class 1 and Sub-class 2-1

1.403

0.39

0.79

0.59

Sub-class 2-2

1.970

0.34

0.67

0.47

Sub-class 3-1 and Sub-class 3-2

1.970

0.20

0.40

0.20

Explanatory Notes :- For the purpose of this clause, -

1. Classification of vehicles and weighting factor for the final emission result shall be as given below :-

Definition of class

Cycles

Weighting factors for final emission results

Class 1

Vehicles that fulfill the following specifications belong to

class 1 : $50 \text{ cm}^3 < \text{engine capacity} < 150 \text{ cm}^3$ and $V_{\text{max}} >$

50 km/h and $\text{engine capacity} < 150 \text{ cm}^3$ and 50

$\text{km/h} < V_{\text{max}} < 100 \text{ km/h}$

Part 1 Reduced Speed cold followed by Part 1

Reduced Speed Hot

Part 1 Reduced Speed cold shall be 50% and Part 1

Reduced Speed Hot shall be 50%

Sub-Class 2.1

Vehicles that fulfill the following specifications belong to

class 2-1: $\text{Engine capacity} < 150 \text{ cm}^3$ and $100 \text{ km/h} > V$

$\text{max} < 115 \text{ km/h}$ and $\text{Engine capacity} > 150 \text{ cm}^3$ and V

$\text{max} < 115 \text{ km/h}$

Part 1 Reduced Speed cold followed by Part 1 Reduced

Speed Hot

Part 1 Reduced Speed cold shall be 50% and Part 1

Reduced Speed Hot shall be 50%

Sub-Class 2.2

Vehicles that fulfill the following specifications belong to

class 2-2 : $115 \text{ km/h} > V \text{ max} < 130 \text{ km/h}$

Part 1 cold followed by Part 2 Hot

Part 1 cold shall be 30% Part 2 hot shall be 70%

Sub-Class 3-1

Vehicles that fulfill the following specifications belong to

class 3-1: $130 \text{ km/h} < V \text{ max} < 140 \text{ km/h}$

Part 1 cold followed by Part 2 Hot followed by Part

3 reduced speed

Part 1 cold shall be 25% Part 2 Hot shall be 50%

and Part 3 reduced shall be 25%

Sub-Class 3-2

Vehicles that fulfill the following specifications belong to

class 3-2: V max $\leq$ 140 km/h

Part 1 cold followed by Part 2 Hot followed by Part

3

Part 1 cold shall be 25% Part 2 Hot shall be 50%

and Part 3 reduced shall be 25%

2. The test procedure and driving cycles shall be as per United Nations Economic Commission for Europe (UN ECE) Global Technical Regulation (GTR)-2 incorporating Amendment 2, with preconditioning soaking and cold start on chassis dynamometer as specified above.

3. Vehicle preconditioning: Operated through the cycles prescribed as above.

4. Vehicle soaking: The vehicle shall be stored for not less than six hours and not more than thirty six hours prior to the cold start Type 1 test or until the engine oil temperature (TO) or the coolant temperature (TC) or the spark plug seat/gasket temperature (TP), only for air cooled engine, equals the air temperature of the soak area.

5. Preparatory running before sampling is not required, sampling starts at T=0 second.

6. Break down of different parts of Worldwide Harmonised Motorcycle Emission Certification (WMTC) shall be as per the details given in Annexure 5 of Chapter XIII A of Ministry of Road Transport and Highways or Central Motor Vehicles Rules or Type Approval Procedure -115/116 (MoRTH/CMVR/TAP-115/116) as amended from time to time.

7. The reference fuel for gasoline vehicle shall be as specified in Annexure-IV-J of the said rules and reference fuel for Compressed Natural Gas (CNG) and for Liquefied Petroleum Gas (LPG) shall be as commercially available.

8. The specification of commercial gasoline shall be as specified in Annexure IV-N of the said rules. For the areas other than those specified in Para (a) of sub-rule 15 of rule 115 of principal rules commercial gasoline shall be as per Bureau of Indian Standards specification IS: 2796-2008 for gasoline. Specification for commercial CNG and LPG shall be as notified from time to time.

9. Requirements of durability (for CO - 1.2, NO_x - 1.2 & HC+NO_x - 1.2 considering 30,000 km. durability run) have been built into the mass emission standards specified above.

10. For vehicles operating on CNG mode, the provisions of rule 115-B shall be applicable.

11. For vehicles operating on LPG mode, the provisions of rule 115-C shall be applicable.

12. Gasoline or CNG or LPG vehicles specified herein shall comply with the provisions of clause (i) of sub-rule (2) of rule 115.

13. Crankcase ventilation system shall not permit the emission of any of the crankcase gases into the atmosphere.

14. Evaporative emission for gasoline driven vehicles shall not be more than 2g/test or 6 g/test, depending on whether the norm for HC + NO_x adopted by manufacturer is from Column (4) or Column (5) respectively of table 1 of mass emission norms and the test procedure shall be as per MoRTH/CMVR/ TAP-115/116, as amended from time to time.

15. Conformity of production (COP) frequency and sampling shall be as per clause (e) of sub-rule (12) of rule 115 of the said rules.

II. Mass emission standards (Bharat Stage IV) for two wheelers with Spark Ignition engines, other than those specified in para A.I above: (Vehicles with cc $\leq$ 50 and Vmax $\leq$ 50 km/hr):

The mass emission standards

Table 2

Pollutant

TA=COP norms (g/km)

Deterioration Factor(D.F.)

(1)

(2)

(3)

CO

0.75

1.2

HC + Nox

0.75

1.2

Notes : - 1. For vehicles operating on CNG mode, the provisions of rule 115-B shall be applicable.

2. For vehicles operating on LPG mode, the provisions of rule 115-C shall be applicable.

3. Gasoline or CNG or LPG vehicles specified herein shall comply with the provisions of clause (i) of sub-rule (2) of rule 115.

4. The reference fuel for gasoline vehicle shall be as specified in Annexure IV-J of the said rules and reference fuel for CNG and LPG shall be as available commercially.

5. The specification of commercial gasoline shall be as specified in Annexure IV-N of the said rules and for the areas other than those specified in clause (a) of sub-rule 15 of rule 115 of principal rules commercial gasoline shall be as per Bureau of Indian Standards specification IS: 2796-2008 for gasoline. The Specification for commercial CNG and LPG shall be as notified from time to time.

6. The provision of clauses (a), (c), (i), (e) and (f) of sub-rule 12 of rule 115, except the proviso therein, shall be applicable to the said vehicle.

B. Two wheeled vehicles fitted with diesel engines -

The mass emission standards shall be same as those applicable for diesel three-wheelers.]

[Inserted by Notification No. G.S.R. 431(E), dated 4.7.2014 (w.e.f. 2.6.1989)]

(17)

[Mass emission standards (Bharat Stage IV) for three wheelers: - Mass emission standards (Bharat Stage IV) for new vehicle models of three wheelers manufactured on or after the 1st April, 2016 and for existing vehicle models of three wheelers manufactured on or after 1st April, 2017:

A. Three wheelers fitted with gasoline engine:

Table 1

CO

HC

+ Nox

If

the evaporative emission complies with 2.0 g/test

If

the evaporative emission complies with 6.0 g/test

(1)

(2)

(3)

(4)

TA

= COP norms (g/km)

0.94

0.94

0.74

D.F.

(Deterioration Factor)

1.2

1.2

1.2

B. Three wheelers fitted with Compressed Natural Gas (CNG) or Liquefied Petroleum Gas (LPG) engine:

Table 2

CO

HC

+ NOx

(1)

(2)

(3)

TA = COP

norms (g/km)

0.940

0.940

D.F.

(Deterioration Factor)

1.2

1.2

C. Three wheelers fitted with compression ignition engine:

Table 3

CO

HC

+ Nox

PM

(1)

(2)

(3)

(4)

TA

= COP norms (g/km)

0.380

0.380

0.0425

D.F.

(Deterioration Factor)

1.1

1.0

1.2

Explanation. - For the purpose of this clause, it is clarified that, -

(i)

for vehicles operating on compressed natural gas mode, the provisions of rule 115B shall be applicable;

(ii)

for vehicles operating on liquefied petroleum gas mode, the provisions of rule 115C shall be applicable;

(iii)

the provisions of clauses (a), (c), (d), (e) and (f) of sub-rule (12), except the proviso therein at the end of that sub-rule, shall be applicable;

(iv)

the reference fuel shall be as specified in Annexure IV-J for vehicles equipped with gasoline and Annexure IV-K for vehicles equipped with diesel engines and reference fuel for compressed natural gas and liquefied petroleum gas shall be as available commercially;

(v)

the specification of commercial gasoline and diesel shall be as specified in Annexure IV-N and Annexure IV-O, respectively and for the areas other than those specified in clause (a) of sub-rule 15, commercial fuel shall be as per the Bureau of Indian Standards specification IS: 2796-2008 (Amendment No. 1- January 2008) for gasoline and IS 1460:2005 (fifth revision) for diesel;

(vi)

specification for commercial compressed natural gas and liquefied petroleum gas shall be as notified from time to time;

(vii)

conformity of production (COP) test procedure shall be as described in MoRTH/CMVR/TAP-115/116 as amended from time to time;

(viii)

gasoline or compressed natural gas or liquefied petroleum gas vehicles specified herein shall comply with the provisions of clause (i) of sub-rule (2);

(ix)

diesel vehicles specified herein shall comply with the provisions of clause (ii) of sub-rule (2);

(x)

crank case ventilation for gasoline driven vehicles system shall not permit the emission of any of the crank case gases into the atmosphere;

(xi)

evaporative emission for gasoline driven vehicles shall not be more than 2.0 g/test or 6.0g/test, depending on whether the norm for HC+NO_x adopted by manufacturer is from column (3) or column (4), respectively, of Table 1 of mass emission norms and the test procedure shall be as per MoRTH/CMVR/TAP-115/116, as amended from time to time.]

(18)

[(i)The Emission Standards for Bharat Stage VI (BS-VI) for category M and N vehicles having Gross Vehicle Weight not exceeding 3500kg, manufactured on or after 1st April 2020 for all models, shall be as under :-

Table 1

Limit Values for M and N Category vehicles fitted with PI & CI Engines: BS VI

Reference Mass (RM) (kg)

Mass of Carbon Monoxide (CO)

Mass of Total Hydrocarbons (THC)

Mass of Non-Methane Hydrocarbons (NMHC)

Mass of Oxides of Nitrogen (NO_x)

Combined Mass of Hydrocarbons and Oxides of Nitrogen (THC + NO_x)

Mass of Particulate Matter (PM)

Number of Particles (PN)

L1 (mg/km)

L2 (mg/km)

L3 (mg/km)

L4 (mg/km)

L2 + L3 (mg/km)

L5 (mg/km)

L6 (numbers/km)

Category

Class

PI

CI

PI

CI

PI

CI

PI

CI

PI

CI

PI(1)

CI

PI(1)(2)

CI

M(M1 & M2)

-

All
1000
500
100
-
68
-
60
80
-
170
4.5
4.5
6.0 X 1011
6.0 X 1011
N1
I
RM? 1305
1000
500
100
-
68
-
60
80
-
170
4.5
4.5
6.0 X 1011
6.0 X 1011
II
1305 < RM?1760
1810
630
130
-
90
-
75
105
-
195
4.5
4.5
6.0 X 1011
6.0 X 1011
III
1760?RM
2270

740
160
-
108
-
82
125
-
215
4.5
4.5
6.0 X 10¹¹
6.0 X 10¹¹
N2
-

All
2270
740
160
-
108
-

82
125
-
215
4.5
4.5
6.0 X 10¹¹
6.0 X 10¹¹

PI = Positive Ignition, CI =
Compression Ignition

(3) For positive ignition, particulate mass and number of particles limit shall apply only to vehicles with direct injection engines.

(4) Until three years after date of implementation for new type approvals and new vehicles, particle number emission limit of 6.0 X 10¹²#/km shall apply to BS VI gasoline direct injection vehicles upon choice of the manufacturer.

Note: This Regulation shall apply to vehicles of categories M1, M2, N1 and N2 with a reference mass not exceeding 2,610 kg.

At the manufacturer's request, type approval granted under this Regulation may be extended from vehicles mentioned above to M1, M2, N1 and N2 vehicles with a reference mass not exceeding 2,840 kg and which meet the conditions laid down in this notification.

Table 2

Application of Test Requirements for Type-Approval - BS VI Vehicles with Positive Ignition Engines including Hybrids

Vehicles with Compression Ignition Engines

including Hybrids

Mono Fuel

Bi- Fuel(1)

Flex Fuel(1)

Flex Fuel

Mono Fuel

Dual Fuel

Reference Fuel

Gasoline (E5)

LPG

CNG/ Bio- Methane/ Bio-Gas/ LNG

Hydrogen (ICE) 3

H2 CNG (Hydrogen + CNG)

Gasoline (E5)

Gasoline (E5)

Gasoline (E5)

Gasoline (E5)

Diesel (B7)

Diesel (B7)

Diesel + CNG

LPG

CNG/ Bio- Methane

Hydrogen (ICE)3

Ethanol (E85)/ (E100)

Bio-Diesel up to 100%(5)

Gaseous Pollutants (Type 1 Test)

Yes

Yes

Yes

Yes2

Yes

Yes (Both Fuels)

Yes (Both Fuels)

Yes (Both Fuels)2

Yes (Both Fuels)

Yes

Yes

Yes

Particulate Mass and Particulate Number (Type 1 Test)

Yes4

-

-

-

-

Yes(Gasoline only)

Yes (Gasoline only)

Yes (Gasoline Only)

Yes(Both Fuels)

Yes

Yes

Yes

Idle Emissions (Type II Test)

Yes

Yes

Yes

-

Yes

Yes (Both Fuels)

Yes (Both Fuels)

Yes (Gasoline Only)

Yes (Both Fuels)

-

-

-

Crankcase Emissions (Type III Test)

Yes

Yes

Yes

-

-

Yes

Yes (Gasoline only)

Yes (Gasoline only)

Yes (Gasoline only)

Yes(Gasoline only)

-

-

-

Evaporative Emissions (Type IV test)

Yes

-

-

-

-

Yes (Gasoline only)

Yes (Gasoline only)

Yes (Gasoline Only)

Yes (Gasoline only)

-

-

-

Durability (Type V Test)

Yes

Yes

Yes

Yes

Yes

Yes (Gasoline only)

Yes (Gasoline only)

Yes (Gasoline Only)

Yes (Gasoline only)

Yes (B7 only)

Yes

Yes

In-Service Conformity

Yes

Yes

Yes

Yes

Yes

Yes (both fuels)

Yes (both fuels)

Yes (gasoline only)

Yes (both fuels)

Yes(B7 only)

Yes

Yes

On-Board Diagnostics and IUPRm

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

(6)CO₂emission and fuel
consumption

Yes

Yes

Yes

Yes

Yes

Yes (Both fuels)

Yes (Both fuels)

Yes (Both fuels)

Yes (Both fuels)

Yes (Both fuels)

Yes

Yes

Smoke Opacity

--

--

--

--

--

--

--

--

--

Yes

Yes

--

Engine Power

Yes

Yes

Yes

Yes

Yes

Yes (Both fuels)

Yes (Both fuels)

Yes (Both fuels)

Yes (Both fuels)

Yes

Yes

Yes

(1) When a bi-fuel vehicle has flex fuel option, both test requirements are applicable. Vehicle tested with E100 need not to be tested for E85.

(2) Only NOx emissions shall be determined when the vehicle is running on Hydrogen.

(3) Reference Fuel is ?Hydrogen for Internal Combustion Engine? as Specified in Annexure IV-W.

(4) For Positive ignition, particulate mass and number limits for vehicles with positive ignition engines including hybrids shall apply only to vehicles with direct injection engines.

(5) Vehicle fueled with Bio diesel blends up to 7% will be tested with reference diesel (B7) & vehicles fueled with Bio diesel blends above 7% will be tested with respective blends.

(6) CO₂ emission and fuel consumption shall be measured as per procedure laid down in AIS 137 and as amended time to time.

Notes.-

(1)

The test shall be on Chassis Dynamometer.

(2)

The test including driving cycle shall be as provided in sub-rule (10) with the modifications that-

(i)

the exhaust gas sampling should start at the initiation of the engine start up procedure referred to in Annexure IV-E and as amended from time to time as per AIS-137;

(ii)

the driving cycle shall be at a maximum speed of 90 km/hour referred to in Annexure IV-E and as amended from time to time as per AIS-137.

(3)

There shall be no relaxation of norms for Conformity of Production (COP) purposes and procedure for compliance shall be as per AIS137 as amended from time to time.

(4)

Specifications for Reference Fuels shall be as below:-

(a)

Reference natural gas fuel used in Natural Gas or Bio-Methane mono-fuel or bi-fuel vehicles shall be as per Annexure

IV-L (G20, G23 and G25).

(b)

Reference LPG fuel used in LPG mono-fuel or bi-fuel vehicles shall be as per Annexure IV M (Fuel A and Fuel B), however, in case of non-availability of reference fuels for CNG/ LPG, the commercially available CNG as per BIS 15958:2012 and LPG as per BIS 14861:2000 as amended from time to time shall be used for the purpose of Type Approval and Conformity of Production.

(c)

The reference ethanol fuel (E85) shall be as per the Annexure IV-Q.

(d)

The Reference Gasoline fuel (E5) shall be as specified in Annexure IV-X.

(e)

The Reference Diesel fuel (B7) shall be as specified in Annexure IV-T.

(f)

Hydrogen Fuel vehicles shall be tested with reference fuel specified in the Annexure IV-W to said rules.

(g)

The reference fuel Biogas (Bio-methane) shall be as per IS 16087:2013 and as amended time to time.

(5)

Crankcase ventilation system shall not permit the emission of any of the crankcase gases in to the atmosphere.

(6)

Evaporative emission shall not be more than 2.0g/test from Gasoline fuelled vehicles. The evaporative emission test procedure for gasoline fuelled vehicles shall be as per the procedure specified in AIS 137 and as amended from time to time.

(7)

The Conformity of Production (COP) testing procedure shall be as described in AIS 137 and as amended from time to time.

(8)

Conformity of Production (COP) frequency and samples as under :-

(i)

The Conformity of Production period for each vehicle model including its variant(s) shall be once a year.

(ii)

Where production volume in six months is less than 250 per model including its variants, the provisions contained in the provisos to rule 126-A shall apply.

(iii)

All these tests shall be conducted with the reference fuel as specified in this sub-rule. However, at the manufacturer's request, test may be carried out with commercial fuel.

(iv)

For vehicles approved as per this sub-rule, at least 50% of Vehicle models, rounded to nearest integer value, produced from particular plant per year shall be selected randomly from dealer's location or warehouse.

(9)

Specifications for Commercial Fuels as under :-

(i)

The Commercial Gasoline fuel shall be as per Annexure IV-U and as amended from time to time.

(ii)

Specification for commercial CNG and commercial LPG shall be in accordance with BIS 15958:2012 and as per BIS 14861:2000 respectively and as amended from time to time.

(iii)

Biodiesel used in commercial Diesel shall be as per IS 15607 as amended from time to time.

(iv)

Specification for Commercial Diesel fuel shall be as per Annexure IV-V and as amended from time to time.

(v)

Specifications for commercial E85 shall be as specified in accordance with the Indian Standards as amended from time

to time.

(vi)

Specification for commercial Biogas (Bio-methane) shall be as per IS 16087:2013 and as amended time to time.

(10)

Specifications of NO_x reduction agent AUS 32 (Aqueous Urea Solution) shall conform to Part 1 and Part 2 of ISO 22241-2006 or DIN standard - DIN V 70070.

(11)

For Diesel vehicles, the emission of visible pollutants (smoke) shall not exceed the limit value of smoke density, when expressed as light absorption coefficient for various nominal flows as given in Annex I to sub-rule (9) of rule 115 when tested at constant speeds over the full load. These smoke limits are without correction factor and engines are to be tested with conditioned air supplied to the engine to maintain atmospheric factor at 0.98 to 1.02.

(12)

The engine power shall be measured on engine dynamometer and the measured power shall conform to the power specified in AIS 137 as amended from time to time, when tested as per the procedures laid down in AIS 137 as amended from time to time.

(13)

Type II Test: Vehicles fitted with PI engines specified in this sub-clause shall comply with the provisions of clause (i) of sub-rule (2) of rule 115 as applicable.

(14)

Free Acceleration Smoke: Vehicles fitted with CI engines specified in this sub-clause shall comply with the provisions of clause (ii) of sub-rule (2) of rule 115 as applicable.

(15)

Deterioration Factor shall be as given in the following Table :-

Table

Deterioration Factor shall be as given below: BS VI

Engine Category

Assigned Deterioration Factor

CO

THC

NMHC

NO_x

HC+NO_x

Particulate Matter (PM)

Particle Number (PN)

Positive Ignition

1.5

1.3

1.3

1.6

-

1.0

1.0

Compression Ignition

1.5

-

-

1.1

1.1

1.0

1.0

(i)

Alternatively, the vehicle manufacturer may opt for a vehicle ageing test of 1,60,000 km or bench ageing durability test, for evaluating the Deterioration factor as per AIS 137 and as amended from time to time.

(ii)

This test may be performed by driving vehicle on a test track, on the road, or on a chassis dynamometer or Engine Test Bench as per AIS 137

(iii)

The maximum lap speed at 10th lap and at 11th lap shall be 72 km/hour and 90 km/hour respectively.

(iv)

The above ageing test should be carried out by the approved test agency specified in rule 126.

(16)

The vehicles shall be equipped with On-Board Diagnostic (BS VI - OBD) systems for emission control which shall have the capability of identifying the likely area of malfunction by means of fault codes stored in computer memory as per the procedure laid down in AIS 137 and as amended from time to time when that failure results in an increase in emission above the limits given in the following Tables below:-

(i)

OBD Threshold for BS VI vehicles manufactured on or after 1st April 2020:

Table 1

On-Board Diagnostic (BS VI- OBD-I) Threshold: BS VI

Reference mass (RM) (kg)

CO (mg/km)

NMHC (mg/km)

NOx (mg/km)

PM (mg/km)

Category

Class

PI

CI

PI

CI

PI

CI

PI(1)

CI

M (M1 & M2)

-

All

1900

1750

170

290

150

180

25

25

N1

I

RM?1305

1900

1750

170

290

150
180
25
25
II
1305 < RM?1760
3400
2200
225
320
190
220
25
25
III
1760 < RM
4300
2500
270
350
210
280
30
30
N2
-
All
4300
2500
270
350
210
280
30
30

(1)For positive ignition, particulate mass limits
apply only to vehicles with direct injection engines

(ii)
OBD Threshold for BS VI vehicles manufactured on or after 1st April 2023:

Table 2

On-Board Diagnostic (BS VI OBD-II) Threshold: BS VI

Reference mass (RM) (kg)
CO (mg/km)
NMHC (mg/km)
NOx (mg/km)
PM (mg/km)
Category
Class
PI
CI
PI

CI
PI
CI
PI(1)
CI
M (M1 & M2)
-
All
1900
1750
170
290
90
140
12
12
N1
I
RM?1305
1900
1750
170
290
90
140
12
12
II
1305 < RM?1760
3400
2200
225
320
110
180
12
12
III
1760 < RM
4300
2500
270
350
120
220
12
12
N2
-
All
4300

2500

270

350

120

220

12

12

(1) For positive ignition, particulate mass limits apply only to vehicles with direct injection engines

(17)

In-use performance ratio (IUPR) for BS VI vehicles manufactured on or after 1st April 2023, the in-use performance ratio (IUPR) of a specific monitor M of the OBD systems shall be:

$IUPRM = \text{Numerator} / \text{Denominator}$

(i)

Comparison of Numerator and Denominator gives an indication of how often a specific monitor is operating relative to vehicle operation. Detailed requirements for tracking IUPR are given in AIS 137.

(ii)

If, according to the requirements specified in AIS 137, the vehicle is equipped with a specific monitor M, IUPRM shall be greater or equal to 0.1 for all monitors M.

(18)

In service compliance of vehicles shall be as per procedure laid down in AIS137 and as amended time to time.

(19)

During type approval and COP applicable from 1st April, 2020, real world driving cycle emission measurement using PEMS shall be carried out for data collection and from 1st April, 2023 real world driving cycle emission conformity shall be applicable. The detailed procedure is laid down in AIS137 and as amended from time to time.

(ii)

The Emission Standards for Bharat Stage VI (BS-VI) for category M and N vehicles having Gross Vehicle Weight exceeding 3500kg., manufactured on or after 1st April 2020 for all models, shall be as under :-

Table 1

Limit values for M&N category vehicles: BS-VI

Limit values

CO (mg/kWh)

THC (mg/kWh)

NMHC (mg/kWh)

CH₄(mg/kWh)

NOX(mg/kWh)

NH₃(ppm)

PM mass (mg/kWh)

PM number (numbers/kWh)

WHSC (CI)

1500

130

400

10

10

8.0×10^{11}

WHTC (CI)

4000

160

460

10

10

6.0 x 10¹¹

WHTC (PI)

4000

160

500

460

10

10

6.0 x 10¹¹

Notes:

PI = Positive Ignition

CI = Compression Ignition

For M1, N1, M2 & N2 category vehicles with a reference mass not exceeding 2840 kg., at the manufacturer's request, type approval may be granted as per the sub-rule (18) (i) of this rule.

If a vehicle is tested for type approval on Chassis Dynamometer having Reference Mass up to 2610 kg, manufacturer may seek type approval extensions up to reference mass of 2840 kg for its variants exceeding GVW of 3500 kg. In such cases mass emission testing on Engine Dynamometer shall not be required.

Table 2

Applicability of Test Requirements for BS-VI

Positive-ignition engines

Compression-ignition engines

Dual fuel engines

Gasoline (E5)

CNG/ Bio-methane/ Bio-Gas/ LNG

LPG

E85

HCNG (Hydrogen + CNG)

Diesel (B7)

Ethanol (ED95)

Bio-diesel blends up to 100%(1)

Diesel +(CNG/LNG)

Gaseous pollutants

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes(2)

Particulate Mass

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes(2)

PM number

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes(2)

Durability

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes(2)

OBD

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes(2)

Off Cycle Emissions (WNTE)

--

--

--

--

--

Yes

Yes

Yes

Yes(2)

PEMS Demonstration test at Type Approval

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes(2)

In-Service Conformity

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes(2)

(1)

The vehicles/ engines fuelled with bio diesel blends up to 7% shall be tested with reference diesel (B7) and vehicles fuelled with Bio diesel blends above 7% will be tested with respective blends.

(2)

The test applicability requirements for dual fuel engine is depending on the Gas Energy Ratio (GER) measured over the hot part of the WHTC test-cycle. GER classification shall be as per AIS 137 and as amended from time to time.

Notes.-

(1)

The test shall be done on engine dynamometer.

(2)

In case of vehicles equipped with Compression Ignition engines, the gaseous and particulate emissions shall be measured as per WHSC and WHTC cycles as per procedure described in AIS 137 as amended from time to time.

(3)

In case of vehicles equipped with positive Ignition engines, the gaseous and particulate emissions shall be measured as per WHTC cycle as per procedure described in AIS 137 and as amended from time to time.

(4)

Specifications for Reference fuels are as below:-

(a)

Reference natural gas fuel used in Natural Gas or Bio-Methane mono-fuel or bi-fuel vehicles shall be as per Annexure IV-L (G20, G23 and G25)

(b)

Reference LPG fuel used in LPG mono-fuel or bi-fuel vehicles shall be as per Annexure IV M (Fuel A and Fuel B). However, in case of non-availability of reference fuels for CNG/ LPG, the commercially available CNG as per BIS 15958:2012 and LPG as per BIS 14861:2000 as amended from time to time shall be used for the purpose of Type Approval and Conformity of Production.

(c)

The reference ethanol fuel (ED95) shall be as specified in Annexure IV-R.

(d)

The Reference Gasoline fuel (E5) shall be in Annexure IV-X.

(e)

The Reference Diesel fuel (B7) shall be as specified in Annexure IV-T.

(f)

The reference fuel Biogas (Bio-methane) shall be as per IS 16087:2013 and as amended time to time.

(5)

The Conformity of Production (COP) testing procedure shall be as described in AIS 137 as amended from time to time.

(6)

The Conformity of Production (COP) frequency and samples shall be as under:-

(i)

The conformity of Production period for each engine model including its variant(s) shall be once a year.

(ii)

Where production volume in six month is less than 250 per model including its variant(s), the provisions contained in the provisos to rule 126-A shall apply.

(7)

Specifications for Commercial fuels shall be as under:-

a. The Commercial Gasoline fuel shall be as per Annexure IV-U and as amended from time to time.

b. Specification for commercial CNG and commercial LPG shall be in accordance with BIS 15958:2012 and as per BIS 14861:2000 respectively and as amended from time to time.

c. Biodiesel used in commercial Diesel shall be as per IS 15607 as amended from time to time.

d. Specification for Commercial Diesel fuel up to 7% of bio diesel blend shall be as per Annexure IV-V and as amended from time to time.

e. Specifications for commercial E85 and ED95 shall be as specified in accordance with the Indian Standards as amended from time to time.

f. Specification for commercial Biogas (Bio-methane) shall be as per IS 16087:2013 and as amended time to time.

(8)

For CI engine vehicles, the emission of visible pollutants (smoke) shall not exceed the limit value of smoke density, as per Annexure I to sub-rule (9) of rule 115. These smoke limits are without correction factor and engines are to be tested with conditioned air supplied to the engine to maintain atmospheric factor of 0.98 to 1.02.

(9)

The engine power shall be measured on engine dynamometer and the measured power shall conform to the power specified and tested as per procedures prescribed in AIS 137 as amended time to time.

(10)

Idle emissions and Smoke Density shall be as under:-

a. The vehicles equipped with PI engine specified in this sub-rule shall comply with the provisions of clause (i) of sub-rule (2) of rule 115.

b. The Vehicles equipped with CI engine specified in this sub-rule shall comply with the provisions of clause (ii) of sub-rule (2) of rule 115.

(11)

Deterioration Factors.-

(i)

Deterioration factors shall be as given in the Table below:

Table 1

Deterioration Factors for BS-VI

Test cycle

CO

THC1

NMHC2

CH42

NOx

NH3

PM mass

PM number

WHTC

1.3

1.3

1.4

1.4

1.15

1.0
1.05
1.0
WHSC

1.3
1.3

1.15
1.0
1.05
1.0

(1)
Applies in case of a compression ignition engine.

(2)
Applies in case of a positive ignition engine.

(ii)
Alternatively, the vehicle manufacturers may opt for evaluation of deterioration factor over normal useful life period as per procedure described in AIS 137 and as amended time to time.

Useful life period and minimum service accumulation period for evaluation of deterioration factor given in Table below:-

Table 2

Minimum service accumulation period - BS-VI

Category of vehicle in which engine will be installed

Useful Life Period

Minimum service accumulation period

Category N1 vehicles

1,60,000 km or 5 years

1,60,000 km

Category N2 vehicles

3,00,000 km or 6 years

1,88,000 km

Category N3 Vehicles with GVW equal to or less than 16,000 kg

3,00,000 km or 6 years

1,88,000 km

Category N3 Vehicles with GVW above 16,000 kg

7,00,000 km or 7 years

2,33,000 km

Category M2 vehicles

1,60,000 km or 5 years

1,60,000 km

Category M3 Vehicles with GVW equal to or less than 7,500 kg

3,00,000 km or 6 years

1,88,000 km

Category M3 Vehicles with GVW above 7,500 kg

7,00,000 km or 7 years

2,33,000 km

The evaluation of deterioration factor test shall be carried out by the approved test agency specified in rule 126.

(12)

(a)

During type approval and COP applicable from 1st April, 2020, emission measurement on vehicles using PEMS shall be carried out on road for data collection and from 1st April, 2023 in-service conformity factor shall be applicable. The

detailed procedure is laid down in AIS137 and as amended from time to time

(b)

The type approval vehicle used for the PEMS demonstration test shall be representative for the vehicle category intended for the installation of the engine system. The vehicle may be a prototype vehicle or an adapted production vehicle.

(c)

For PEMS demonstration test at type approval, vehicle shall meet the requirements of in-service compliance from 1st April, 2023.

(13)

The vehicles specified in this sub-clause shall meet the following World Not-To-Exceed (WNTe) Off-cycle laboratory testing limits for gaseous and particulate exhaust emissions, and as per procedure laid down in AIS 137 and as amended time to time:-

Test cycle

COmg/kWh

THCmg/kWh

Noxmg/kWh

PMmg/kWh

WNTe

2000

220

600

16

(14)

The vehicles specified in this sub-clause manufactured on or after 1st April, 2023 shall have the capability of assessing the in-use performance of on-board diagnostic, as per procedure laid down in AIS 137 and as amended time to time.

(15)

The vehicles specified in this sub-clause fitted with engine, which rely on the use of a reagent in order to reduce emissions, shall ensure the correct operation of NOx control measures, as per procedure laid down in AIS 137 and as amended time to time.

(16)

The vehicles specified in this sub-rule shall be equipped with an On-Board Diagnostic system (BS VI OBD-I and BS-VI OBD-II) for emission control which shall have the capability of identifying the likely area of the malfunctions by means of fault codes stored in computer memory and communicating that information off-board, as per procedure described in AIS 137, when that failure results in an increase in emission above the limits given in the following Tables below:-

(a)

BSVI- OBD-I threshold for BS VI vehicles manufactured on or after 1st April 2020 shall be as given below:-

Table 1

OBD threshold Limits: (BS-VI OBD-I)

Limit in mg/kWh

NOx

PM Mass

Compression ignition engines

1500

Performance Monitoring(1)

Positive Ignition engines

1500

--

(1)

Performance monitoring for wall-flow diesel particulate filter shall be as per AIS-137 and as amended time to time.

(b)

BS-VI-OBD-II threshold for BS VI vehicles manufactured on or after 1st April 2023 shall be as given below:-

Table 2

OBD threshold Limits: (BS-VI OBD-II)

Limit in mg/kWh

NOx

PM Mass

CO

Compression ignition engines

1200

25

Positive Ignition engines

1200

--

7500

At the manufacturer's request type approval may be granted for compliance to BS-VI OBD-II requirements before its implementation

(19)

(i)

The Emission Standards for Bharat Stage-VI (BS-VI) for two wheelers vehicle models manufactured on or after 1st April 2020 shall be as per Tables below:-

Table 1

Limit Values for Two wheelers fitted with PI & CI engines: BSVI

Vehicle Class

BS VI Emission Norms

CO mg/km

HC mg/km

NOx mg/km

NMHC mg/km

PM mg/km

EVAP mg/test

OBD

Durability mileage (km) Type V

PI Vehicles

1 & 2-1

1000

100

60

68

4.5*

1500

STAGEII

20000

2-2

1000

100

60

68

4.5*

3-1 & 3-2

1000

100

60
 68
 4.5*
 35000
 CI Vehicles
 All
 500
 100
 90
 68
 4.5*
 -
 35000
 DF (for all classes)
 1.3
 1.3 (SI) 1.1 (CI)
 1.3 (SI) 1.1 (CI)
 1.3 (SI) 1.1 (CI)
 1.0 (CI)
 300**

* Applicable to gasoline direct injection (DI) engines only.

**Fixed DF of 300 mg/test shall be added to SHED test results. Alternative to fixed DF, manufacture may opt for ageing of evaporative emission control devices as per procedure specified in AIS 137 and as amended time to time.

Table 2

Application of Test Requirements for Type-Approval: BS-VI

Vehicle with SI engines including hybrids

Vehicles with CI engines including hybrids

Mono-fuel

Bi-fuel(3)

Flex-fuel

Flex-fuel

Mono-fuel

Dual Fuel

Gasoline (E5)

LPG

CNG/ Bio-methane/ Bio-Gas/ LNG

H2

HCNG (Hydrogen + CNG)

Gasoline (E5)

Gasoline (E5)

Gasoline (E5)

Gasoline (E5)

Diesel (B7)

Diesel (B7)

Diesel + CNG

LPG

CNG/ Bio-methane

H2

Ethanol (E85)/ E100

Up to 100%(1)Bio-diesel

Gaseous pollutant Type I test

Yes

Yes

Yes

Yes

Yes

Yes (both fuels)

Yes (both fuels)

Yes (Both fuels)

Yes (both fuels)

Yes (Both fuels)

Yes

Yes

(2)Type I test Particulate mass

Yes

No

No

No

No

Yes (gasoline only)

Yes (gasoline only)

Yes (gasoline only)

Yes (gasoline only)

Yes

Yes

Yes

Idle emission (Type II)

Yes

Yes

Yes

No

Yes

Yes (both fuels)

Yes (both fuels)

Yes (gasoline only)

Yes (both fuels)

Yes (B7 only)

Yes

Yes

Crankcase emission (Type III test)

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Evaporative emission (Type IV test)

Yes

No

No

No

No

Yes (gasoline only)

Yes (gasoline only)

Yes (gasoline only)

Yes (gasoline only)

No

No

No

Durability (Type V test)

Yes

Yes

Yes

Yes

Yes

Yes (gasoline only)

Yes (gasoline only)

Yes (gasoline only)

Yes (gasoline only)

Yes (B7 only)

Yes

Yes

(4)CO₂& Fuel consumption

Yes

Yes

Yes

Yes

Yes

Yes (both fuels)

Yes (both fuels)

Yes (Both fuels)

Yes (both fuels)

Yes (Both fuels)

Yes

Yes

On board diagnosis OBD

Yes

Yes

Yes

Yes

Yes

Yes (gasoline only)

Yes (gasoline only)

Yes (gasoline only)

Yes (gasoline only)

Yes (B7 only)

Yes

Yes

Smoke Opacity

No

No

No

No

No

No

No

No

No

Yes (B7 Only)

Yes

No

(1)

Vehicles fuelled with bio diesel blends up to 7% shall be tested with reference diesel (B7) and vehicles fuelled with Bio diesel blends above 7% will be tested with respective blends.

(2)

In case of PI engines, applicable only to vehicles with direct Injection engines.

(3)

Vehicles models and variants having option for Bi-fuel operation and fitted with limp-home gasoline tank of capacity not exceeding two litres on two wheelers shall be exempted from test in gasoline mode.

(4)

CO₂ emission and fuel consumption shall be measured as per procedure laid down in AIS 137 and as amended time to time.

When bi-fuel vehicle is combined with a flex fuel vehicle, both test requirements are applicable. Vehicle tested with E100 need not to be tested with E85.

Notes. -

(1)

The test shall be on Chassis Dynamometer.

(2)

Classification of vehicles and weighting factor for the final emission result shall be as given below:-

Table

Classification of vehicles and weighting factor

Definition of class

WMTC Cycles

Weighting factors for final emission results

Class 1

Vehicles that fulfill the following specifications belong to

class 1: $50 \text{ cm}^3 < \text{engine capacity} < 150 \text{ cm}^3$

and $v_{\text{max}} 50 \text{ km/h}$ or engine capacity $< 150 \text{ cm}^3$ and 50

$\text{km/h} < v_{\text{max}} < 100 \text{ km/h}$

Part 1 Reduced Speed cold followed by Part 1 Reduced Speed

Hot

Part 1 Reduced Speed cold shall be 50% and Part 1 Reduced

Speed Hot shall be 50%

Sub Class 2-1

Vehicles that fulfill the following specifications belong to

class 2-1: Engine capacity $< 150 \text{ cm}^3$ and 100 km/h

$V_{max} < 115 \text{ km/h}$ or Engine capacity 150 cm^3 and $V_{max} < 115 \text{ km/h}$

Part 1 Reduced Speed cold followed by Part 2 Reduced Speed Hot

Part 1 Reduced Speed cold shall be 50% and Part 2 Reduced Speed Hot shall be 50%

Sub Class 2.2

Vehicles that fulfill the following specifications belong to class 2-2: $115 \text{ km/h} < V_{max} < 130 \text{ km/h}$

Part 1 cold followed by Part 2 Hot

Part 1 cold shall be 50% and Part 2 hot shall be 50%.

Sub Class 3-1

Vehicles that fulfill the following specifications belong to class 3-1: $130 \text{ km/h} < V_{max} < 140 \text{ km/h}$

Part 1 cold followed by Part 2 Hot followed by Part 3 reduced speed

Part 1 cold shall be 25% Part 2 Hot shall be 50% and Part 3 reduced shall be 25%

Sub Class 3-2

Vehicles that fulfill the following specifications belong to class 3-2: $V_{max} \geq 140 \text{ km/h}$ subclass 3-2.

Part 1 cold followed by Part 2 Hot followed by Part 3

Part 1 cold shall be 25% Part 2 Hot shall be 50% and Part 3 shall be 25%

(3)

The test procedure and driving cycle for all test types including alternative durability and OBD shall be as per AIS 137 and as amended time to time.

(4)

Specification of Reference Fuels shall be as under:-

a) The Reference Gasoline fuel (E5) shall be as specified in Annexure IV-X.

b) The reference ethanol fuel (E85) shall be as per Annexure IV-Q.

c) The Reference Diesel fuel (B7) shall be as specified in Annexure IV-T.

d) The reference ethanol fuel (E100) shall be as per Annexure IV-S

e) Reference natural gas fuel used in Natural Gas or Bio-Methane mono-fuel or bi-fuel vehicles shall be as per Annexure IV-L (G20, G23 and G25).

f) Reference LPG fuel used in LPG mono-fuel or bi-fuel vehicles shall be as per Annexure IV M (Fuel A and Fuel B). However, in case of non-availability of reference fuels for CNG/ LPG, the commercially available CNG as per BIS 15958:2012 and LPG as per BIS 14861:2000 as amended from time to time shall be used for the purpose of Type Approval and Conformity of Production.

g) Hydrogen Fuel vehicles shall be tested with reference fuel specified in the Annexure IV-W to said rules.

h) The reference fuel Biogas (Bio-methane) shall be as per IS 16087:2013 and as amended time to time.

(5)

Specifications of Commercial Fuels shall be as under:-

a) The Commercial Gasoline fuel blend shall be as per Annexure IV-U.

b) Specification for commercial CNG and commercial LPG shall be in accordance with BIS 15958:2012 and as per BIS 14861:2000 respectively.

c) Bio-diesel used in commercial Diesel shall be as per IS 15607.

d) Specification for Commercial Diesel fuel shall be as per Annexure IV-V.

e) Specifications for commercial E85 shall be as specified in accordance with the Indian Standards.

f) Specification for Biogas (Bio-methane) shall be as per IS 16087:2013 and as amended time to time.

(6)

Gasoline/CNG/LPG vehicles specified herein shall comply with the provisions of clause (i) of sub-rule (2) of rule 115. The Vehicle equipped with CI engine specified in sub rule shall comply with the provision of clause (ii) of sub-rule (2) of rule 115. For vehicles fitted with CI engine, the emission of visible pollutants (smoke) shall not exceed the limit value of smoke density, as per Annexure I to sub-rule (9) of rule 115. These smoke limits are without correction factor and engines are to be tested with conditioned air supplied to the engine to maintain atmospheric factor of 0.98 to 1.02.

(7)

Crankcase ventilation system shall not permit the emission of any of the crankcase gases in to the atmosphere.

(8)

Alternatively, to the fixed DF mentioned in Table 1 of this sub-rule, the vehicle manufacturers may opt for evaluation of deterioration factor as per procedure described in AIS 137 and as amended time to time.

(9)

Conformity of Production (COP) test procedure shall be as per clause (e) of sub-rule (12) of rule 115. For 2W vehicles, at least 50% of Vehicle models produced from particular plant shall be selected randomly from dealer's location or warehouse.

(10)

The engine power shall be measured on engine dynamometer and measured power shall conform to the power specified and tested as per procedure prescribed in AIS 137 and as amended time to time.

(11)

The vehicle presented for Type approval shall have been run for at least 1000 km before the test.

(12)

The Two wheeler vehicles shall be equipped with On-Board Diagnostic (OBD) systems for emission control which shall have the capability of identifying the likely area of malfunction by means of fault codes stored in computer memory as per the procedure laid down in AIS 137.

The On-Board Diagnostic (OBD) systems for emission control shall be as specified in the following Tables:

Table 1

OBD Functions and associate

Monitoring Items

OBD Stage I (BS VI) 1st April,
2020

OBD Stage II (BS VI) 1st April,
2023

Circuit continuity for all emission related power train
component (if equipped)

?

?

Distance traveled since MIL (Malfunction indicator lamp) ON

?

?

Electrical disconnection of Electronic evaporative purge
control device (if equipped and if active)

?

?

Catalytic converter monitoring

X

?

EGR system monitoring

?

?

Misfire detection

X

?

Oxygen sensor deterioration

X

?

(13)

In-use performance ratio (IUPR) for BS VI vehicles manufactured on or after 1st April 2023, the in-use performance ratio (IUPR) of a specific monitor M of the OBD systems shall be:

$IUPRM = \text{Numerator} / \text{Denominator}$

Comparison of Numerator and Denominator gives an indication of how often a specific monitor is operating relative to vehicle operation. Detailed requirements for tracking IUPR are given in AIS 137.

If, according to the requirements specified in AIS 137, the vehicle is equipped with a specific monitor M, IUPRM shall be greater or equal to 0.1 for all monitors M.

Table 2

On-board (OBD) diagnostics emission thresholds for BSVI

Applicable from 1st April, 2023

Vehicle Class

OBD Stage II/ Gasoline

CO mg/km

NMHC mg/km

NOx mg/km

PM mg/km

1 & 2-1

1900

250

300

50(1)

2-2

1900

250

300

50(1)

3-1 & 3-2

1900

250

300

50(1)

Vehicle Class

OBD Stage II/ Diesel

CO mg/km

NMHC mg/km

NOxmg/km

PM mg/km

All

1900

320

540

50

(1)

In case of P.I. engines, applicable only to vehicles with direct injection engines.

(ii)

The Emission Standards (Bharat Stage VI) for two wheelers with Spark Ignition engines other than those specified in

para (19), (i) above: (Vehicles with cc $\geq$ 50 and Vmax $\geq$ 50 km/hr) shall be as per the below table:

Table

Pollutant

TA=COP norms mg/km

Deterioration Factor (D.F.)

Test Cycle (Cold Start at T=0 sec)

CO

500

1.2

IDC as per AIS137

HC

350

1.2

NOx

150

1.2

Notes:

(1)

Gasoline/ CNG/ LPG vehicles specified herein shall comply with the provisions of clause (i) of sub-rule (2) of rule 115

(2)

The Reference Gasoline fuel (E5) shall be as specified in Annexure IV-X.

(3)

Reference natural gas fuel used in Natural Gas or Bio-Methane mono-fuel or bi-fuel vehicles shall be as per Annexure IV-L (G20, G23 and G25).

(4)

Reference LPG fuel used in LPG mono-fuel or bi-fuel vehicles shall be as per Annexure IV M (Fuel A and Fuel B). However, in case of non-availability of reference fuels for CNG/ LPG, the commercially available CNG as per BIS 15958:2012 and LPG as per BIS 14861:2000 as amended from time to time shall be used for the purpose of Type Approval and Conformity of Production. The reference fuel Biogas (Bio-methane) shall be as per IS 16087:2013 and as amended time to time.

(5)

The provision clause (a) sub-clause (i) of clause (c), clause (e) and clause (f) of sub-rule (12) of clauses (a), (c)(i), (e) and (f) for sub-rule 12 of rule 115, except the proviso therein, shall be applicable to the said vehicle.

(6)

The driving cycle for Vehicles with cc $\geq$ 50 and Vmax $\geq$ 50 km/hr shall be Indian Driving Cycle (IDC) and the exhaust gas sampling shall start at the initiation of cycle in case of gasoline two wheeler vehicles.

(7)

The engine power shall be measured on engine dynamometer and the measured power shall conform to the power specified and tested as per procedure prescribed in AIS 137 and as amended time to time.

(20)

The Emission Standards Bharat Stage VI (BS VI) for Three wheelers vehicle models manufactured on or after 1st April 2020 shall be as under:-

Table 1

Three wheelers fitted with PI and CI Engines: BS VI

Vehicle with PI engines

CO mg/km

HC+NOx mg/km

NOx mg/km

EVAP mg/test

OBD

Durability mileage (km) Type V

Test Cycle (Cold Start at T=0 sec)

Limit

440

435

130

1500

Stage II

35000

IDC AIS137

D.F.

1.20

1.2

1.2

--

--

--

Vehicle with CI engines

CO mg/km

HC+NOx mg/km

NOx mg/km

PM mg/test

OBD

Durability mileage (km) Type V

Test Cycle (Cold Start at T=0 sec)

Limit

220

200

160

25

Stage II

35000

IDC AIS137

D.F.

1.10

1.0

1.00

1.20

--

--

Table 2

Application of Test Requirements for Type-Approval : BS-VI

Vehicle with PI engines including hybrids

Vehicles with CI engines including hybrids

Mono-fuel

Bi-fuel(3)

Flex-fuel

Flex-fuel

Mono-fuel

Dual Fuel

Gasoline (E5)

LPG

CNG/Bio-methane/ Bio-Gas/LNG

H2

HCNG (Hydrogen + CNG)

Gasoline (E5)

Gasoline (E5)

Gasoline (E5)

Diesel (B7)

Diesel (B7)

Diesel + CNG

LPG

CNG/ Bio-methane

Ethanol (E85)

Bio-diesel up to 100% (1)

Gaseous pollutant (Type I test)

Yes

Yes

Yes

Yes

Yes

Yes (both fuels)

Yes (both fuels)

Yes (both fuels)

Yes (Both fuels)

Yes

Yes

(2)Type I test Particulate mass

Yes

No

No

No

No

No

No

No

Yes (Both fuels)

Yes

Yes

Idle emission (Type II test)

Yes

Yes

Yes

Yes

Yes

Yes (both fuels)

Yes (both fuels)

Yes (both fuels)

Yes (Both fuels)

Yes

Yes

Crankcase emission (Type III test)

Yes

Yes
Yes
Yes
Yes
Yes
Yes
Yes
Yes
Yes
Yes
Evaporative emission (Type IV test)
Yes
No
No
Yes
Yes
Yes (gasoline only)
Yes (gasoline only)
Yes (gasoline only)
No
No
No
Durability (Type V test)
Yes
Yes
Yes
Yes
Yes
Yes (gasoline only)
Yes (gasoline only)
Yes (gasoline only)
Yes (B7 only)
Yes
Yes
(4)CO2& Fuel consumption
Yes
Yes
Yes
No
No
Yes (both fuels)
Yes (both fuels)
Yes (both fuels)
Yes (both fuels)
Yes
Yes
OBD Stage II
Yes
Yes
Yes
Yes (gasoline only)

Yes (gasoline only)

Yes (gasoline only)

Yes (B7 only)

Yes

Yes

Smoke Opacity

No

No

No

No

No

No

No

No

Yes (B7 only)

No

No

(1)

Vehicles fuelled with bio diesel blends up to 7% shall be tested with reference diesel (B7) and vehicles fuelled with Bio diesel blends above 7% will be tested with respective blends.

(2)

In case of PI engines, applicable only to vehicles with direct Injection engines.

(3)

Vehicles models and variants having option for Bi-fuel operation and fitted with limp-home gasoline tank of capacity not exceeding three litres on three wheelers shall be exempted from test in gasoline mode.

(4)

CO₂ emission and fuel consumption shall be measured as per procedure laid down in AIS 137 and as amended time to time.

When bi-fuel vehicle is combined with a flex fuel vehicle, both test requirements are applicable. Vehicle tested with E100 need not to be tested with E85.

Notes -

1. The test shall be on Chassis Dynamometer.

2. The test including driving cycle shall be as provided in CMV sub-rule (12) with the modifications that

i) The exhaust gas sampling should start at the initiation in case of gasoline and diesel three wheeler as per the engine start up procedure referred to in Annexure II.

3. The provision of clauses (a), (c), (d), (e) and (f) of sub-rule (12) of rule 115, except the proviso therein at the end of this sub rule, shall be applicable to the said vehicles.

4. Specifications of Reference Fuels:

(a)

The Reference Gasoline fuel (E5) shall be as specified in Annexure IV-X. The reference Ethanol fuel (E85) shall be as per the Annexure IV-Q.

(b)

The Reference Diesel fuel (B7) shall be as specified in Annexure IV-T.

(c)

Reference natural gas fuel used in Natural Gas or Bio-Methane mono-fuel or bi-fuel vehicles shall be as per Annexure IV-L (G20, G23 and G25).

(d)

Reference LPG fuel used in LPG mono-fuel or bi-fuel vehicles shall be as per Annexure IV M (Fuel A and Fuel B), however, in case of non-availability of reference fuels for CNG/ LPG, the commercially available CNG as per BIS 15958:2000 and LPG as per BIS 14861:2012 as amended from time to time shall be used for the purpose of Type Approval and Conformity of Production.

(e)

Reference fuel Biogas (Bio-methane) shall be as per IS 16087:2013 and as amended time to time.

5. Specifications of Commercial Fuels shall be as under:-

i) The Commercial Gasoline fuel shall be as per Annexure IV-U.

ii) Specification for commercial CNG and commercial LPG shall be in accordance with BIS 15958:2012 and as per BIS 14861:2000 respectively.

iii) Bio-diesel used in commercial Diesel shall be as per IS 15607.

iv) Specification for Commercial Diesel fuel shall be as per Annexure IV-V.

v) Specifications for commercial E85 shall be as specified in accordance with the Indian Standards as amended from time to time.

vi) Specification of commercial Biogas (Bio-methane) shall be as per IS 16087:2013 and as amended time to time.

6. There shall be no relaxation of norms for Conformity of Production (COP) purposes.

7. The Conformity of Production (COP) testing procedure shall be as described in AIS 137 and as amended time to time. For 3W vehicles, at least 50% of Vehicle models produced from particular plant shall be selected randomly from dealer's location or warehouse.

8. Alternative to fixed DF mention in Table 1, the vehicle manufacturers may opt for evaluation of deterioration factor as per procedure described in AIS 137.

9. The engine power shall be measured on engine dynamometer and the measured power shall confirm to the power specified and tested as per procedure prescribed in AIS 137 and as amended time to time.

10. The vehicle presented for Type approval shall have been run for 1000km before the test.

11. (a) C.I. vehicles specified herein shall comply with the provisions of clause (ii) of sub-rule(2) of rule 115.

(b)

S.I. Vehicles specified herein shall comply with the provision of clause (i) of sub-rule (2) of rule 115.

12. Crank case ventilation system shall not permit the emission of any of the crankcase gases into the atmosphere. Test procedure shall as per AIS 137.

13. Evaporative emission for gasoline driven vehicles shall not be more than 1.5 g/test. Test procedure shall as per AIS 137.

14. The Three wheeler vehicles shall be equipped with On-Board Diagnostic (OBD) systems for emission control which shall have the capability of identifying the likely area of malfunction by means of fault codes stored in computer memory as per the procedure laid down in AIS 137.

The On-Board Diagnostic (OBD) systems for emission control shall be as specified in the below Tables:-

Table 1

OBD Functions and associate

Monitoring Items

OBD Stage I (BS VI)1stApril,
2020

OBD Stage II (BS VI)1stApril,
2023

Circuit continuity for all emission related power train
component (if equipped)

?

?

Distance traveled since MIL (Malfunction indicator lamp) ON

?

?

Electrical disconnection of Electronic evaporative purge
control device (if equipped and if active)

?

?

Catalytic converter monitoring

X

?

EGR system monitoring

X

?

Misfire detection

X

?

Oxygen sensor deterioration

X

?

Table 2

On-board (OBD) diagnostics emission thresholds for BSVI

Applicable from 1st April, 2023

Vehicle

OBD Stage II Gasoline

CO mg/km

NOx mg/km

Gasoline

880

425

OBD Stage II Diesel Vehicles

Diesel

CO mg/km

NOx mg/km

440

300]

[Inserted by Notification No. G.S.R. 889, dated 16.9.2016 (w.e.f. 2.6.1989).]

[[115A. Emission of smoke and vapour from agricultural tractors, power tillers, construction equipment vehicles and combine harvesters driven by diesel engines.

[Inserted by GSR 627(E), dated 8.9.1999 (w.e.f. 1.10.1999).]

]

[Inserted by Notification No. G.S.R. 487(E), dated 12.6.2015 (w.e.f. 2.6.1989)]

] - (1)Every [agricultural tractor and construction equipment vehicles and combine harvester]

[Substituted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

manufactured on and from the date of commencement of this rule shall be maintained by its owner in such condition and shall be so used that visible and gaseous pollutants emitted by them comply with the standards as prescribed in this rule.

(2)

Every manufacturer of an [agricultural tractor and construction equipment vehicle]

[Substituted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

shall comply with the standards for visible pollutants, emitted by it, when tested as per the procedure described in Indian Standards IS: 12062: 1987.

(3)

The emission of visible pollutants shall not exceed the limit values given below when tested on engine dynamometer at eighty per cent load at six equally spaced speeds, namely:

(a)

Fifty-five per cent of rated speed declared by the manufacturer or one thousand r.p.m., whichever is higher; or

(b)

rated speed declared by the manufacturer.

Maximum Smoke Density

Light absorption coefficient (1m)

Hartridge units

3.25

75

(4)

Every diesel driven [construction equipment vehicles]

[Substituted by GSR 83(E), dated 5.2.2003, for 'agricultural tractor and construction equipment vehicle'(w.e.f. 1.6.2003).] shall be so manufactured and produced by its manufacturer that it complies with the following standards of gaseous pollutants, emitted by them in addition to those of visible pollutants as provided in sub-rule (2) when tested as per the procedures described in ISO 8178-4 CI 8 mode cycle,namely:

The weighted average Mass of Carbon Monoxide (CO), Hydrocarbons (HC) and Mass Oxides of Nitrogen (NOx) in gram or [per]

[<SPAN]

kilo watt. hr. emitted during the test shall not exceed the limits given below, both for type approval and Conformity On Production tests, namely:

Mass of Carbon Monoxide (CO)

14.0 gram or[per]

[Substituted by G.S.R. 83(E), dated 5.2.2003, for 'agricultural tractor and construction equipment vehicle]

kilo watt.hr.

Mass of Hydrocarbon (HC)

3.5 gram or[per]

[Substituted by G.S.R. 83(E), dated 5.2.2003, for 'agricultural tractor and construction equipment vehicle]

kilo watt.hr.

Mass of Oxides of Nitrogen (NOx)

18.0 gram or[per]

[Substituted by G.S.R. 83(E), dated 5.2.2003, for 'agricultural tractor and construction equipment vehicle]

kilo watt.hr.]

(5)

[Every diesel driven agriculture tractor and power tiller shall be so manufactured and produced by the manufacturer that it complies with the following standards of gaseous pollutants emitted by them in addition to those of visible pollutants as provided in sub-rule (2) when tested as per the procedure prescribed in ISO8178-4 C1 8 mode cycle, namely:

The weighted average Mass of Carbon Monoxide (CO), Hydrocarbon (HC) and Oxides of Nitrogen (NOx) and Particulate Matter (PM) in gram per kilo watt hour emitted during the test shall not exceed the limits given below in the Table for Type Approval (TA) and Conformity of Production (COP) tests, namely:

TABLE

Bharat (Term)

Stage II norms

Bharat (Term)

Stage III norms

(1)

(2)

(3)

TA=COP

TA=COP

Mass of Carbon Monoxide (CO)

9.0

5.5

Mass of Hydro-carbons (HC)

Mass of Oxides of Nitrogen (NOx)

15.0

9.5

Mass of Particulate Matter (PM)

1.0

0.8]

Notes :

(1)

The norms mentioned in column (2) of the said Table which are applicable for agricultural tractor with effect from the 1st day of June, 2003, shall be applicable for power tillers from the 1st day of October, 2006.

(2)

The norms mentioned in column (3) of the said Table shall be applicable for agricultural tractor with effect from the 1st day of October, 2005 and for power tillers from the 1st day of April, 2008.]

(6)

[Every diesel driven construction equipment vehicle [and self propelled combine harvesters]

[Inserted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

shall be so manufactured that it complies with the following standards of gaseous pollutants emitted by them in addition to those of visible pollutants as provided in sub-rule (2), when tested as per the procedure described in ISO 8178 Part-4(1996) CI 8 mode cycle for variable speed engines and ISO 8178 Part-4(1996) D2 5 mode cycle for constant speed engines, namely:

The weighted average Mass of Carbon Monoxide (CO), Hydrocarbon (HC) and Oxides of Nitrogen (NO_x), and Particulate Matters (PM) in grams per kilo Watt hour emitted during the test shall not exceed the limits given below in the TABLE for Type Approval (TA) and Conformity of Production (COP) tests, namely:

TABLE

Limit Values for Type Approval (TA) as well as for Conformity of Production (COP)

Bharat Stage II (CEV)

Applicable with effect from the

CO

HC

NO_x

PM

Category

g/kWh

kW<8

1st October, 2008

8.00

1.30

9.20

1.0

8?kW<19

1st October, 2008

6.60

1.30

9.20

1.0

19?kW<37

1st October, 2007

6.50

1.30

9.20

0.85

37?kW<75

1st October, 2007

6.50

1.30

9.20
0.85
75?kW<130
1stOctober, 2007
5.0
1.30
9.20
0.70
130?kW<560
1stOctober, 2007
5.0
1.30
9.20.
0.54
Bharat Stage III (CEV)
Applicable with effect from the
CO
HC+NOx
PM
Category
q/kWh
kW<8
1stApril, 2011
8.00
7.50
0.80
8?kW<19
1stApril, 2011
6.60
7.50
0.80
19?kW<37
1stApril, 2011
5.50
7.50
0.60
37?kW<75
1stApril, 2011
5.0
4.70
0.40
75?kW<130
1stApril, 2011
5.0
4.00
0.30
130?kW<560
1stApril, 2011
3.50
4.00
0.20

|||||||

Notes :

1. The test shall be on Engine Dynamometer.
2. The Test-Procedure for measurement of Gross Power -(without Fan) shall be as per Part IV of MoSRTTH/CMVR/TAP-115/116 Issue No. 3.
3. The Test-Procedure for measurement of emission of visible and gaseous pollutants and Particulate Matter shall be as per MoSRTTH/CMVR/TAP-115/116 Part X (Sub-part B).
4. The emission of visible pollutants shall not exceed the limit values given in sub-rule (3) of rule 115-A when tested on engine dynamometer at eighty per cent load at six speeds as per sub--rule (3) of rule 115-A.
5. To meet Bharat Stage III (CEV) norms with effect from 1st April, 2011, Engine manufacturer may opt for an engine test as mentioned in Table 1 below for evaluating deterioration factors as per Annexure V of Part X, Sub-part B of MoSRTTH/CMVR/TAP-115/116 Issue No. 3

Category

(power band)

Useful life (hours)

(Emission Durability Period)

<19 kW

3000

19<kW<=(constant speed)

3000

19<kW<=37 (variable, speed)

5000

>37 kw

8000

OR

Fixed Deterioration factors shall be used as per table 2 below.

TABLE-2

TABLE-2

CO

HC

NOx

PM

1.1

1.05

1.05

1.1

[Substituted by G.S.R. 589(E), dated 16.9.2005.]

6. There shall be no relaxation of norms for COP purposes.

7. COP Selection Procedure shall be as per MoSRTTH/CMVR/TAP--115/116 Part VI.

8. COP Frequency:-

(a)

for equipment with annual production up to 200 Nos. shall be once in two years per Engine Family;

(b)

for equipment with annual production exceeding 200 Nos. shall be once in every year per Engine Family.]

9. [Bharat Stage III (CEV) norms shall be applicable to self propelled combine harvester on and from the commencement of the Central Motor Vehicles (Fourth Amendment) Rules, 2015.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(7)

[Every diesel driven [agricultural tractor operated combine harvester]

[Inserted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

manufactured on and from the date specified in column (2) of the Table 1 shall comply with the Bharat (Trem) Stage-III A norms and the weighted average mass of Carbon Monoxide (CO), Hydrocarbon (HC) and Oxides of Nitrogen (NOx) and Particulate Matters (PM) in grams per kiloWatt/hour emitted by them in addition to those of visible pollutants as provided in sub-rule (2), when tested for Type Approval (TA) and Conformity of Production (COP) in accordance with the procedure specified in ISO 8178 Part-4(1996) C1 8 mode cycle, shall not exceed the limits given in columns (3), (4)and (5) respectively, of the said Table.

Limit Values for Type Approval (TA) and Conformity of Production (COP)

TABLE-1

Category

Applicable from

CO

HC+NO_x

PM

(1)

(2)

(3)

(4)

(5)

<8kW

5.5

8.5

0.8

8<=kW<19

5.5

8.5

0.8

19<=kW<37

5.5

7.5

0.6

37<=kW<56

5.0

4.7

0.4

56<=kW<75

5.0

4.7

0.4

75<=kW<130

5.0

4.0

0.3

130<=kW<560

3.5

4.0

0.2

Notes:-

1. The test shall be on Engine Dynamometer.

2. The test procedure for measurement of Gross Power (without Fan) shall be as per Part IV of MoSRTTH/CMVR/TAP-115/116 Issue No.3.

3. The test procedure fro measurement of emission of visible and gaseous pollutants and Particulate matter shall be as

per MoSRTTH/CMVR/RAP-115/116 Part X (Sub-part A).

4. Test fuel shall be the reference fuel as specified in Annexure IV-P.

5. The emission of visible pollutants, when tested as provided in sub-rule (3) of rule 115-A, shall not exceed the limit values given therein.

6. To meet Bharat (Trem) Stage-III A norms with effect from the date specified in column (2) of Table 1, the engine manufacturer may opt for an aging test as specified in Table 2 for evaluating deterioration factors as per Annexure V of Part X (Sub-part B) of MoSRTTH/CMVR/TAP/115-116 Issue No. 3 or fixed deterioration factors as per Table 3.

Table-2

Category

(power band)

Useful life (hours)

(Emission Durability Period)

$\leq 19\text{kW}$

3000

$19 < \text{kW} \leq 37$

5000

$> 37\text{kW}$

8000

TABLE-3

CO

HC

NOx

PM

1.1

1.05

1.05

1.1

7. There shall be no relaxation of norms for Conformity of Production (COP) purposes.

8. Conformity of Production (COP) Selection Procedure Shall be as per MoSRTTH/CMVR/TAP-115/116 Part VI.

9. Conformity of Production (COP) Frequency shall be as per Part X (Sub-part A) of MoSRTTH/CMVR/TAP-115/116.

10. The extension of Type Approval (TA) to engine family and engine after-treatment system family shall be specified in MoSRTTH/CMVR/TAP-115/116 as amended from time to time.

Explanation 1. The term "engine family" includes a range of engines having similar design parameters from emission levels.

Explanation 2. The term "engine after-treatment system family" means if same after-treatment system consisting of catalyst, particulate traps, etc., is used on a series of engines, then the deterioration factor based on one engine test shall be applicable to the entire series.]

(8)

[Every gasoline driven power tiller manufactured on and from 01/07/2013, shall comply with the Bharat Stage III norms and the weighted average mass emission of Carbon Monoxide (CO), Hydrocarbon (HC) and Oxides of nitrogen (Nox) in grams per kilo watt hour emitted by them, when tested for Type Approval (TA) and Conformity of Production (COP) in accordance with the eight mode test cycle given in the following Table 1, shall not exceed the limits given in the following Table 2:-

Table 1

Mode

Engine Speed

Percent

LOAD

Weighting

Load

(1)
 (2)
 (3)
 (4)
 1.
 Rated
 100
 0.15
 2.
 Rated
 75
 0.15
 3.
 Rated
 50
 0.15
 4.
 Rated
 10
 0.1
 5.
 Intermediate speed
 100
 0.1
 6.
 Intermediate speed
 75
 0.1
 7.
 Intermediate speed
 50
 0.1
 8.
 Idle

 0.15

Table 2

Limit value for Type Approval (TA) and Conformity of Production (COP)

CO(g/Kwhr)

HC+Nox(g/Kwhr)

(1)

(2)

14

24

Notes:

1. Test shall be on engine dynamometer.
2. The Test procedure for measurement of gross power (without fan) shall be as per 15:14599.
3. The reference fuel for Gasoline power tiller engine shall be as specified in Annexure IV G of the said rules.
4. The test procedure for measurement of emission gaseous pollutants shall be as per procedure laid down in Ministry of Road Transport and Highways/Central Motor Vehicles Rules/Type Approval Procedure-115/116 (MoRTH/CMVR/TAP-115/116).]

115B.

[Mass emission standards for Compressed Natural Gas Driven Vehicles.

[Rule 115-B substituted by GSR 853(E) dated 19.11.2001 (w.e.f. 19.5.2002).]

- [1] [Mass emission standards for vehicles when operating on Compressed Natural Gas (hereinafter in this rule referred to as CNG) shall be the same as are applicable for gasoline vehicles with the exception that HC shall be replaced by Non-Methane Hydrocarbon (NMHC), where NMHC = 0.3 x HC.]

[Substituted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

[Provided that bio-compressed natural gas (bio-CNG) shall be permitted for motor vehicles as an alternate composition of the compressed natural gas (CNG):

Provided further that the mass emission standards applicable to compressed natural gas (CNG) vehicles under these rules shall be applicable to respective vehicles when they use bio-compressed natural gas (bio-CNG):

Provided also that the bio-compressed natural gas (bio-CNG) as per IS 16087 and meets the requirement of Siloxanes max 0.1 ppm (calculated as Si)]

[Inserted by Notification No. G.S.R. 498 (E), dated 16.6.2015 (w.e.f. 2.6.1989)]

A. Original Equipment/Converted Gasoline Vehicles:

(I)

For gasoline vehicles with Original Equipment(hereinafter in this rule referred to as O.E.) fitment.

(a)

In case of CNG fitments by vehicle manufacturers on new petrol vehicles, each model manufactured by vehicle manufacturers shall be type approved as per the prevailing mass emission norms as applicable for the category of new vehicles in respect of the place of its use;]

[Clause (a) substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

(b)

Base model and variants of such vehicle shall conform to these rules as applicable and type approval emission norms in petrol mode as specified in these rules. In the case of CNG mode, it shall meet mass emission norms as specified in rule 115, excluding crankcase and evaporative emission norms.

(c)

[vehicle models and variants having option for bi-fuel operation and fitted with limp-home Gasoline tank of capacity not exceeding two litres, three litres and five litres respectively on two-wheeler, three-wheeler and four-wheeler shall be exempted from mass emission tests including all tests specified under sub-rule (2),Notes 6 and 7 mentioned below clause (C) of sub-rule (14) and Notes 6, 7, 15and 16 of sub-clause (i) of clause (b)of sub-rule (15) of rule 115 in Gasoline mode;

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

(d)

prevalent conformity of production procedure shall also be applicable.]

(II)

For in-use gasoline vehicles.

(a)

The in-use vehicles fitted with CNG kits shall meet the type approval emission norms on CNG operation, as specified in these rules for gasoline vehicles as applicable to the corresponding year of manufacture of such vehicles, subject to a minimum norms as under:

(i)

for the vehicles manufactured up to 31st March, 2000, the type approval norms equivalent to India 2000 (India Stage I)norms as applicable under these rules; and

(ii)

[for the vehicles manufactured on or after 1st April, 2000, and up to the 30th September, 2010, the type approval norms as specified in the Bharat Stage II norms;]

[Substituted by Notification No. G.S.R. 498 (E), dated 16.6.2015 (w.e.f. 2.6.1989)]

(iii)

[for the vehicles manufactured on and after the 1st day of April, 2005, the type approval norms as applicable subject to minimum of Bharat Stage III emission norms in case of four-wheelers and Bharat Stage II emission norms for two and

three-wheelers;]

[Clause (iii) inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

(iv)

[for the vehicles manufactured on and after the 1st day of April 2010, the type approval norms as applicable, subject to minimum of Bharat Stage-IV emission norms for Category M and Category N Vehicles with Gross Vehicle Weight not exceeding 3,500 kg and Bharat Stage-III emission norms for two and three wheelers.]

[Inserted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

(b)

For purposes of CNG kit approval, kit manufacturer or supplier shall obtain the certificate from any of the test agencies authorized under rule 126 based on engine capacity of vehicle, in the following manner, namely:

(i)

CNG kit for the vehicle shall be type approved for vehicles irrespective of make and model. Such a kit shall be considered fit for retro fitment in any vehicle within a specified range of engine capacity of c.c. within a range of 125% tolerance.

(ii)

Separate type approval shall be necessary for the following types of vehicles, namely:

(a)

Two stroke;

(b)

Four stroke;

(c)

Carburetted;

(d)

Single point fuel injected; and

(e)

Multi point fuel injected.

Explanations. In the case of O.E. or conversion of In-Use Gasoline Vehicles,

(a)

For the purposes of granting Type Approval to a CNG kit, the tests shall be carried out as per the Table below by the test agencies.

Test

Reference Document

(1)

(2)

(i) Mass emission tests

MOST

/CMVR/TAP-115/116 and notifications issued by the Government of India in this respect

(ii) Engine performance tests on engine dynamometer applicable for OE only

IS

: 14599-1999

(iii) [Fuel Consumption test]

SI

. No. 31 of the notification number S.O. 1365(E), dated the 13th December, 2004]

(b)

The test procedure and safety guidelines for CNG vehicles, kit components including installation thereof, shall be as per AIS024, as amended from time to time, till such time as corresponding BIS specifications are notified.

(c)

For OE fitment and retro fitment on in-use vehicles, the responsibility to Type Approval shall be that of the vehicle manufacturer and kit manufacturer or supplier respectively.

(d)

The Type Approval of CNG kit for retro fitment shall be valid for three years from the date of issue of such approval and

shall be renewable for three years at a time.

(e)

The retro fitment of CNG kits on in-use vehicles shall be carried out by workshops authorized by the kit manufacturer/supplier or vehicle manufacturers, as the case may be.

(f)

The test agency shall complete the test and give necessary certificate within a period of three months from the date of receiving the kits.

(g)

The kit manufacturer/supplier shall provide a layout plan for retro fitment of CNG kit in the respective models on which any approved kit is to be installed, to the test agency for vetting and approval. The retro fitment of the kit shall be on the basis of such approved layout plan only. Testing agencies will be required to indicate specifically, the models and their variants on which the certificate will be valid.]

[* * *]

[Item A, Clause by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

B. O.E. CNG Vehicles/Converted Diesel Vehicle:

(I)

For O.E. CNG Dedicated Vehicle (including drive-away chassis) made by vehicle manufacturers.

(a)

[In case of CNG fitments by vehicle manufacturers on new diesel vehicles, each model manufactured by vehicle manufacturers shall be type approved as per the prevailing mass emission norms as applicable for the category of new vehicle sin respect of the place of its use;]

[Substituted by G.S.R. 589(E), dated 16.9.2005.]

(b)

O.E. CNG engine approved for specific engine capacity can be installed on the base model and its variants complying with the requirements under these rules as applicable;

(c)

Tests for particulate matter and emission of visible pollutants (smoke) under these rules shall not be applicable;

(d)

Prevailing COP procedure will also be applicable.

(II)

For conversion by modification of engines of In-use Diesel Vehicles .

(a)

Type approval for diesel vehicle retrofitted/modified for dedicated CNG operation shall be given for specific make and model of the vehicle, in view of major changes or modifications involved in the CNG kit and diesel engine depending upon make and model of the vehicle;

(b)

CNG kit approved on the vehicle for specific engine capacity can be installed on the base model and its variants fitted with the same capacity engine;

(c)

[The in-use vehicles when converted to operate on CNG shall meet the type approval norms of diesel vehicles corresponding to the year of their manufacture subject to the following minimum norms:

[Substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

(i)

for the vehicles manufactured up to the 31st day of March, 2000, the type approval norms equivalent to India-2000(India Stage I) norms as applicable under these rules;

(ii)

[for the vehicles manufactured on and after the 1st day of April, 2000, and up to the 30th September, 2010, the type approval norms as specified in the Bharat Stage II norms;]

(iii)

for the vehicles manufactured on and after the 1st day of April, 2005, the type approval norms as applicable subject to minimum of Bharat Stage III emission norms in case of four-wheelers and Bharat Stage II emission norms for two and

three-wheelers till the validity of these norms;]

(iv)

[for the vehicles manufactured on and after 1st April 2010, the type approval norms as applicable, shall be subject to minimum of Bharat Stage-IV emission norms in case of four wheelers and Bharat Stage--III emission norms in case of two end three wheelers till the validity of these norms;]

[Inserted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

(d)

Vehicles offered for Type Approval to the testing agency referred in rule 126 of the Central Motor Vehicles Rules, 1989 shall have to comply with fitness requirement, as applicable under these rules;

(e)

Tests for particulate matter and emission of visible pollutants (smoke) under these rules shall not be applicable;

(f)

Separate Type Approval is required for mechanically controlled and electronically controlled diesel fuel injected vehicles when retrofitted/modified for CNG operation.

Explanations. In the case of O.E. or conversion of In-Use vehicles by modification

(a)

for the purpose of granting Type Approval to the vehicle fitted with CNG engine (converted from diesel engine) as O.E., or conversion by modification of In-Use diesel vehicles, performance tests shall be carried out as per the :

Test

Reference Document

(As amended from time to time)

(1)

(2)

(i) Mass emission tests

MOST

/CMVR/TAP-115/116 and notifications issued by the Government of India in this respect

(ii) Engine performance tests on engine dynamometer applicable for OE only

IS

: 14599-1999

(iii) Grade ability

In accordance with notification issued under rule 124 of Central Motor Vehicles Rules, 1989

(iv) [Fuel Consumption test

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

Sl.

No. 31 of the notification number S.O. 1365(E), dated the 13th December, 2004]

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

(v) Electro-Magnetic Interference (EMI)

In accordance with notification issued under rule 124 of Central Motor Vehicles Rules, 1989

(vi) Range Test of at least 250 km for buses

-

(vii) Cooling Performance

IS

: 14557, 1998

Note .The mass emission tests shall be carried out either on engine dynamometer or chassis dynamometer, as applicable.

(b)

Test procedure and safety guidelines for CNG vehicles, kit components including installation thereof, shall be as per AIS024, as amended from time to time, till such time as corresponding BIS specifications are notified;

(c)

For O.E. fitment and retro fitment/modification on In-Use vehicles, the responsibility of Type Approval shall be that of the vehicle manufacturer and kit manufacturer or supplier respectively;

(d)

The Type Approval of CNG kit for retro fitment shall be valid for 3 years from the date of issue and shall be renewable for three years at a time;

(e)

The retro fitment of CNG kits on in-use vehicles shall be carried out by workshops authorized by the kit manufacturer/supplier or vehicle manufacturers, as the case may be;

(f)

The test agency shall complete the test and give necessary certificate within a period of three months from the date of receiving the kits.

[* * *]

[Item B, Clause (III) omitted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

C. Replacement of In-use Diesel Engine by New CNG Engine.

[Part C substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

- For Type Approval of in-use vehicle having diesel engine replaced by new Compressed Natural Gas engine, it shall meet prevailing emission norms as applicable to the category of vehicles in respect of its place of use subject to tests mentioned in the Table given below.]

[Inserted by Notification No. G.S.R. 515 (E) dated 29.7.2012 (w.e.f. 2.6.1989)]

Test

Reference Document

(As amended from time to time)

(1)

(2)

(i) Mass emission tests

MOST

/CMVR/TAP-115/116 and notifications issued by the Government of India in this respect

(ii) Engine performance tests

IS

: 14599-1999

(iii) Grade ability test

In accordance with notification issued under rule 124 of Central Motor Vehicles Rules, 1989

(iv) Electro-Magnetic Interference (EMI)

In accordance with notification issued under rule 124 of Central Motor Vehicles Rules, 1989

(v) Range Test of at least 250 km for buses

-

(vi) Cooling Performance

IS

: 14557, 1998

(vii) Fuel Consumption test

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

Sl.

No. 31 of the notification number S.O. 1365(E), dated the 13th December, 2004]

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

Explanation. -

(a)

Vehicles offered for Type Approval to the testing agency referred in rule 126 shall have to comply with fitness requirement, as applicable under these rules.

(b)

Test procedure and safety guidelines for such CNG vehicles, kit components including installation thereof shall be as per AIS024, as amended from time to time, till such time as corresponding BIS specifications are notified.

(c)

The test agency shall complete the test and give necessary certificate within three months of the same being submitted

for tests.

(d)

Testing agencies will be required to indicate specifically, the models and their variants on which the replacement of new engine will be valid.

D. Applicable Emission Norms

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

Category of Engines

Applicable Emission Norms

(i)OC CNG Category M and Category N Vehicles with GVW equal to or less than 3,500 kg, three wheelers and two wheelers.

Prevailing gasoline norms

(ii)CNG Category M and Category N vehicles with GVW equal to or less than 3,500 kg, three and two wheelers retro fitment from gasoline vehicles

Prevailing gasoline norms

(iii)CNG Category M and Category N vehicles with GVW equal to or less than 3,500 kg, three and two wheelers retro fitment from diesel vehicles

Prevailing diesel norms

(iv)CNG engines Category M and Category N vehicles with GVW greater than 3,500 kg manufactured up to 1stApril 2010

Prevailing diesel engine norms based on 13-mode steady-state engine dynamometer test or 13-mode Engine Steady State Cycle as applicable

(v)CNG engines for Category M and Category N vehicles with GVW greater than 3,500 kg manufactured on and from 1stApril 2010

Prevailing diesel engine emission norms.]

[E. [CNG/ bio-CNG/ LNG]

[substituted by Notification No. G.S.R. 534(E) dated 24.7.2014 (w.e.f. 2.6.1989)]

vehicle/s kit components, including their installation, shall conform to the Safety Checks given in the Annexure IX.]

F. Testing agencies shall issue every Type Approval certificate containing the Safety and Procedural Requirements for Type Approval of CNG and LPG Operated Vehicles for CNG vehicles and conversion kits, as mentioned in Annexure X.

Note :

1. For the purpose of these rules, O.E. fitment means the vehicles which are manufactured for CNG operation by the vehicle manufacturer prior to their first registration.

2. Conversion of In-use Gasoline Vehicle means a vehicle already registered as a gasoline vehicle and is subsequently converted for operation on CNG by fitting the conversion kit and carrying out the other necessary changes.

3. O.E. CNG Dedicated Vehicles means the vehicles which are manufactured for CNG operation by the vehicle manufacturer prior to their first registration.

[3(a) "O.E. LNG Dedicated Vehicle" means the vehicles which are manufactured for LNG operation by the vehicle manufacturers prior to their first registration;]

[Inserted by Notification No. G.S.R. 643(E), dated 27.6.2017 (2.6.1989).]

4. Converted diesel vehicle means a vehicle already registered as a diesel vehicle and is subsequently converted for operation on CNG by modifying the diesel engine fitted on that vehicle by fitting the conversion kit and carrying out the other necessary changes.

5. Retro fitment (or replacement)of diesel vehicle means a vehicle already registered as a diesel vehicle and is subsequently converted for operation on CNG fitting a new engine adapted to operate on CNG.

6. The AIS or IS specifications may be amended from time to time.

7. [In case of conversion kits on in-use gasoline vehicles or converted diesel vehicles, the validity of the type approval certificate issued by the testing agencies shall cover vehicles manufactured between the year of manufacture of the vehicle, on which such kit has been tested and date of the validity of the applicable norms prescribed for such category of vehicles as per clause (a) of Item (II) of part A of rule 115-B. Testing agencies shall be required to indicate specifically the model and their variants for diesel vehicles and capacity range of gasoline vehicles on which the certificate shall be valid for conversion.]

[Substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

(2)

[The mass emission standards applicable to Original Equipment CNG Dedicated Vehicles under sub-rule (1) shall be applicable to Original Equipment manufactured vehicle having GVW $\leq$ 3.5 T, when Liquefied Natural Gas is used as fuel.

(3)

The Liquefied Natural Gas composition used for carrying out emission shall meet the fuel specification as notified by the Government of India in the Ministry of Petroleum and Natural Gas, or Bureau of Indian Standard, as the case may be, for automotive application from time to time:

Provided that till such time the Liquefied Natural Gas fuel complying to the requirements as provided in Annexure IV-LA shall be used for the purpose of type approval and conformity of production.

(4)

The Original Equipment manufactured Liquefied Natural Gas dedicated vehicle having GVW $\leq$ 3.5 T shall meet the safety requirements as laid down in AIS-024 and AIS- 028 as amended from time to time.]

[Inserted by Notification No. G.S.R. 643(E), dated 27.6.2017 (w.e.f. 2.6.1989).]

[115-C. Mass emission standards for Liquefied Petroleum Gas (hereinafter in this rule referred to as LPG), driven vehicles.

[Inserted by GSR 284(E), dated 24.4.2001 (w.e.f. 24.5.2001).]

- [(1) Mass emission standards for vehicles when operating on Liquefied Petroleum Gas (hereinafter in this rule referred to as LPG) shall be same as are applicable for gasoline vehicles with the exception that HC shall be replaced by Reactive Hydrocarbon(RHC), where $RHC = 0.5 \times HC$.]

(2)

For gasoline vehicles with Original Equipment(hereinafter in this rule referred to as O.E.) Fitment,

(a)

[in case of LPG fitments done by vehicle manufacturers on new gasoline vehicles, each model manufactured by vehicle manufacturers shall be type approved as per the prevailing mass emission norms as applicable for the category of new vehicles in respect of the place of its use.]

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

(b)

base model and variants of such vehicle shall conform to these rules as applicable and type approval emission norms in petrol mode as specified in these rules. In the case of LPG mode, it shall meet mass emission norms as specified in rule 115 only excluding crankcase and evaporative emission norms;

(c)

vehicle models and variants having option for bi-fuel operation and fitted with limp-home Gasoline tank of capacity not exceeding two litres, three litres and five litres respectively on two-wheeler, three-wheeler and four-wheeler shall be exempted from mass emission tests including all tests specified under sub-rule (2), Notes 6 and 7 mentioned below clause (c) of sub-rule (14) and Notes 6, 7, 15 and 16 of sub-clause (i) of clause (b) of sub-rule (15) of rule 115 in Gasoline mode;

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

(d)

prevalent conformity of production procedure shall also be applicable.]

(3)

For in-use gasoline vehicles,

(a)

[On and after expiry of one year from the date of publication of the Central Motor Vehicles (Fifth Amendment) Rules, 2005 in the Official Gazette, the in-use vehicles fitted with LPG kits shall meet the type approval emission norms specified in these rules for gasoline vehicles as applicable to the corresponding year of manufacture of such vehicle, subject to the following minimum norms:

[Substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

(i)

for the vehicles manufactured up to the 31st day of March, 2000, the type approval norms equivalent to India-2000(India Stage I) norms as applicable under these rules;

(ii)

[for the vehicles manufactured on and after the 1st day of April, 2000, and up to the 30th September, 2010, the type approval norms as specified in the Bharat Stage II norms;]

(iii)

for the vehicles manufactured after the 1st day of April, 2005, the type approval norms as applicable subject to minimum of Bharat Stage III emission norms in case of four-wheelers and Bharat Stage II emission norms for two and three-wheelers:

Provided that in respect of vehicle model/conversion kits/engine replacements type approved and certified under rule 115-C prior to commencement of these rules (as per notification number G.S.R. 284(E), dated the 24th April, 2001), such certificates shall cease to be valid after one year from the date of publication of the Central Motor Vehicles (Fifth Amendment) Rules, 2005, in the Official Gazette notwithstanding the period of validity specified in such certificates. Such certificates need to be revalidated by testing agencies in terms of these rules:

Provided further that respective kit manufacturer/retro fitter/converters shall be free to obtain from testing agencies type approval in terms of new rules even prior to commencement of these rules;]

(iv)

[for the vehicles manufactured on and after the 1st day of April 2010, the type approval norms as applicable, subject to minimum of Bharat Stage-IV emission norms for Category M and Category N Vehicles with Gross Vehicle Weight not exceeding 3,500 kg and Bharat Stage-III emission norms for two and three wheelers.]

[Inserted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

(b)

for purposes of LPG kit approval, kit manufacturer or supplier shall obtain the certificate from any of the test agencies authorized under rule 126 based on capacity of vehicle, in the following manner, namely:

(i)

LPG kit for the vehicles shall be type approved for vehicles irrespective of make and model based on engine capacity in cubic cm. Such a kit shall be considered fit for retro fitment in any vehicle having engine capacity within a range of $\pm 25\%$ tolerance;

(ii)

[separate type approval shall be necessary for the following types of vehicles

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

(a)

two stroke

(b)

four stroke

(c)

carburetted

(d)

single point fuel injected; and

(e)

multi point fuel injected.]

(4)

(a)

For the purpose of granting type approval to LPG kit the following performance tests shall be carried out by the test agencies:

(i)

Mass emission tests.

(ii)

Engine performance tests.

(iii)

Constant speed fuel consumption test;

(b)

the tests specified under sub-clause (ii) of clause (a) shall be carried out either on engine dynamometer or chassis

dynamometer as applicable under these rules. However, in case of vehicle above 100 HP the tests shall be only on engine dynamometer;

(c)

the safety checks for such kit components including installation shall be as per the norms and standards given in the Annexure VIII, apart from detailed test procedure or safety guidelines contained in AIS 025 D1, as approved by the Central Government from time to time;

(d)

for OE fitment and retro fitment on in-use vehicles, the responsibility of Type Approval shall be that of the vehicle manufacturer and kit manufacturer or supplier, respectively;

(e)

the Type Approval of LPG kit for retro fitment shall be valid for three years from the date of issue of such approval and shall be renewable for three years at a time;

(f)

the retro fitment of LPG kits on in-use vehicles, shall be carried out by workshops authorized by the kit manufacturer/kit supplier or vehicle manufacturers, as the case may be;

(g)

the test agency shall complete the test and give necessary certificate within a period of three months from the date of receiving the kits;

(h)

the kit supplier/manufacturer shall provide a layout plan for retro fitment of LPG kit in the respective models on which any approved kit is to be installed, to the test agency for vetting and approval. The retro fitment of the kit shall be on the basis of such approved layout plan only.

[* * *]

[Sub-rule (5) omitted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

(6)

[For Diesel Vehicles with Original Equipment fitment. [(i) In case of LPG fitments by vehicles manufacturers on new diesel vehicles, each model manufactured by vehicle manufacturers shall be type approved as per the prevailing mass emission norms as applicable for the category of new vehicles in respect of the place of its use;]

[Inserted by GSR 788(E), dated 27.11.2002 (w.e.f. 2.6.2003).]

(ii)

O.E. fitment LPG engine approved for specific appropriate engine capacity can be installed on the vehicle base model and its variants complying with the other requirements under these rules as applicable;

(iii)

Tests for particulate matter and emission of visible pollutants (smoke) under these rules shall not be applicable; and

(iv)

Prevailing COP procedures shall also be applicable;

(v)

In case of limits for Hydrocarbons, the mass emission standards formula as specified in sub-rule (1) shall be applicable.]

Explanation. - In the case of O.E. fitment vehicles:

(a)

For the purpose of granting Type Approval to the vehicle manufactured by O.E., in addition to the tests as specified in Central Motor Vehicles Rules, 1989, following performance tests shall be carried out, as per the Table given below by the test agency, namely:

SL.NO.

Test

Reference Document

(as amended from time to time)

(1)

(2)

(3)

1.

Mass emission tests

MOST/CMVR/TAP-115/116 and notification issued by the Government of India in this respect

2.

Engine performance test

IS: 14599-1999

3.

Grade ability test

In accordance with notification issued under rule 124 of Central Motor Vehicles Rules, 1989

4. [

[Substituted by G.S.R. 84(E), dated 9.2.2009(w.e.f. 9.2.2009)]

[Fuel Consumption test

[Sub-R (7) substituted by G.S.R. 589(E), dated 16.9.2005(w.e.f. 16.9.2006).]

[Sl.

No. 31 of the notification number S.O. 1365(E), dated the 13thDecember, 2004]

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

5.

Electro-Magnetic Interference (EMI)

In accordance with notification issued under rule 124 of Central Motor Vehicles Rules, 1989

6.

Range test of at least 250 km for buses. For other vehicle categories range test to be carried out and test results to be reported

AIS 055

7.

Cooling performance

IS: 14557-1998

Note :The mass emission tests shall be carried out either on engine dynamometer or chassis dynamometer, as applicable;

(b)

Test procedure and safety guidelines for LPG vehicles, kit components including installation thereof, shall be as per AIS025, AIS 026, AIS 027 as amended from time to time, till such time as corresponding BIS specifications are notified and shall be as given in Annexure-VIII in addition to the detailed procedure of Safety Checks contained in AIS 025, AIS 026, AIS 027;

(c)

For O.E. fitment manufactured vehicles, the responsibility of Type Approval shall be that of the vehicle manufacturer;

(d)

The test agency shall complete the test and give necessary certificate within a period of three months from the date of receiving the kits.

(7)

[Replacement of In-use Diesel Engine by new LPG Engine.For type approval of in-use vehicle having diesel engine replaced by new Liquefied Petroleum Gas engine it shall meet the prevailing emission norms as applicable to the category of vehicles in respect of its place of use subject to the tests mentioned in the Table given below]

[Sub-Rule(7) substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

:

TABLE

SL.NO.

Test

Reference Document

(as amended from time to time)

(1)

(2)

(3)

1.

Mass emission tests

MOST/CMVR/TAP-115/116 and notification issued by the Government of India in this respect

2.

Engine performance test

IS: 14599-1999

3.

Grade ability test

In accordance with notification issued under rule 124 of Central Motor Vehicles Rules, 1989

4. [

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

Fuel Consumption test

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

Sl.

No. 31 of the notification number S.O. 1365(E), dated the 13th December, 2004]

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

5.

Electro-Magnetic Interference (EMI)

In accordance with notification issued under rule 124 of Central Motor Vehicles Rules, 1989

6.

Range test of at least 250 km for buses. For other vehicle categories range test to be carried out and test results to be reported

AIS 055

7.

Cooling performance

IS: 14557-1998

Explanation. - (a) In case of in-use vehicles offered for Type Approval to the test agency referred to in rule 126, it shall have to comply with fitness requirement, as applicable under these rules and the said test agency may, if it thinks so, verify the same;

(b)

In case of non-transport vehicles offered for retro fitment as per the tests mentioned in the Table, it shall be the responsibility of the retro fitter to make necessary inspection/checks regarding fitness of the such vehicles as applicable under these rules: In the case of retro fitment of in-use transport vehicles offered for the tests mentioned in the Table, the certificate of fitness granted under section 56 of the Act, shall be essential before the vehicle is accepted for retro fitment/conversion;

(c)

Test procedure and safety guidelines for such LPG vehicles, kit components including installation thereof shall be as per AIS025, as amended from time to time, till such time as corresponding BIS specifications are notified and shall be as given in Annexure VIII in addition to the detailed procedure or Safety checks contained in AIS 025;

(d)

The test agency shall complete the test and give necessary certificate within a period of three months from the date of the vehicle being submitted for tests; and

(e)

The test agency shall be required to indicate specifically, the models and their variants on which the replacement of new engine shall be valid.

(8)

Applicable emission norms. The emission norms as mentioned in column (3) of the Table below excluding particulate matter shall be applicable to the corresponding categories of engines as mentioned against them in column (2) of the said Table.

Sl.No.

Category of Engines

Applicable Emission Norms

13a[(i)

[Substituted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

[OE LPG Category M and Category N Vehicles with GVW equal to or less than 3,500 kg, three wheelers and two wheelers.

Prevailing gasoline norms

(ii)

LPG Category M and Category N vehicles with GVW equal to or less than 3,500 kg, three and two wheelers retro fitment from gasoline vehicles

Prevailing diesel norms

(iii)

LPG Category M and Category N vehicles with GVW equal to or less than 3,500 kg, three and two wheelers retro fitment from diesel vehicles

Prevailing diesel norms

(iv)

LPG engines Category M and Category N vehicles with GVW greater than 3,500 kg manufactured up to 1stApril 2010.

Prevailing diesel engine norms based on 13-mode steady state engine dynamometer test or 13-mode Engine Steady State Cycle as applicable

(v)

LPG engines fro Category M and Category N vehicles with GVW greater than 3,500 kg manufactured on and from 1stApril 2010

Prevailing diesel engine emission norms.]

(9)

LPG vehicle/kit components including installation shall comply with the Safety Checks as given in Annexure VIII.

(10)

The test agency shall, in addition to the Type Approval Certificate, issue Safety and Procedural Requirements for Type Approval Certificate containing the Safety and Procedural Requirements for Type Approval of CNG and LPG Operated Vehicles, for LPG vehicles and conversion kits, as mentioned in Annexure X.

Note :For the purposes of these rules,

(1)

OE fitment means the vehicle engines which are manufactured for LPG operation by the vehicle manufacturer prior to their first registration;

(2)

Conversion of In-use gasoline vehicle means a vehicle already registered as a gasoline vehicle and subsequently converted for operation on LPG by fitting the conversion kit and carrying out the other necessary changes;

(3)

O.E. fitment LPG dedicated vehicle means a vehicle which is manufactured for LPG operation by the vehicle manufacturer prior to their first registration;

(4)

Type approval of In-use vehicle having diesel engine replaced by new LPG engine means a vehicle already registered as a diesel vehicle and is subsequently converted for operation on LPG by fitting a new engine adapted for operation on LPG;

(5)

The AIS or IS specifications may be as amended and notified from time to time.]

(6)

[In case of conversion kits on in-use gasoline vehicles or replacement of in-use diesel engines by new LPG engines, the validity of the type approval certificates issued by the testing agencies shall cover vehicles manufactured between the year of manufacture of the vehicle, on which such kit had been tested and the date of validity of the norms prescribed for such category of vehicles as per clause (a)of sub-rule (3) of rule 115-C. Testing agencies shall be required to indicate specifically, the model and their variants for diesel vehicles and capacity range of gasoline vehicles on which the certificate shall be valid for conversion.]

[Note 6 inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

115D.

[Retro-fitment of hybrid electric system or electric kit to vehicles.

[Substituted by Notification No. G.S.R. 629(E), dated 24.6.2016 (w.e.f. 2.6.1989).]

(1)

The Retro-fitment of hybrid electric system kit to vehicles having Gross Vehicle Weight not exceeding 3500 kg. shall be permitted if---

(a)

the vehicle intended for retro-fitment complies with following conditions, namely:-

(i)

it conforms to Bharat Stage-II or subsequent emission norms;

(ii)

it belongs to category M1 or category M2 or category N1 with Gross Vehicle Weight not exceeding 3500 kg.;

(iii)

it is fueled by either gasoline or diesel fuel;

(iv)

it was not retrofitted earlier;

(v)

it shall not be fueled by any other alternate fuel;

(b)

the mass emission standards for vehicles so retrofitted shall be the same as prevalent for corresponding petrol or diesel vehicles as applicable for the year of manufacture of the said vehicle;

(c)

the vehicle, after retro-fitment, shall meet the requirement of AIS-123 (Part 1): 2013 as amended from time to time till such time as corresponding Bureau of Indian Standard specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986):

Provided that for the purpose of hybrid electric system kit approval, kit manufacturer or supplier shall obtain the type approval certificate from a test agency specified in rule 126 and the validity of such certificate shall be three years from the date of its issue;

(d)

the installation of type approved hybrid electric system kit shall be done only by an installer authorized by the hybrid electric system kit manufacturer or supplier, and the installer shall adhere to the installer's responsibilities and the Code of Practice detailed in the AIS-123 (Part 1): 2013, as amended from time to time, till such time as corresponding Bureau of Indian Standards (BIS) specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986):

(e)

the vehicle is manufactured in the period of manufacture of the prototype retrofitted vehicle on which kit has been tested, type approved and the date of validity of applicable emission norms prescribed for such category of vehicles:

Provided that responsibility of vehicle retro-fitted with Hybrid Electric System Kit shall be transferred from OEM to kit manufacturer or supplier, for the parts added or affected by Hybrid Electric System kit retro-fitment , except in case of zero kilometer fitment.

(2)

The Retro-fitment of hybrid electric system kit to vehicles having Gross Vehicle Weight exceeding 3500 kg. shall be permitted if---

(a)

the vehicle intended for retro-fitment complies with following conditions, namely:-

(i)

it conforms to Bharat Stage-II or subsequent emission norms;

(ii)

it belongs to category M & N with Gross Vehicle Weight exceeding 3500 kg.;

(iii)

it was not retrofitted earlier;

(iv)

it is not provided with permits for carrying dangerous or hazardous good, as defined in Central Motor Vehicle Rules, 1989;

(b)

the vehicle, after retro-fitment, shall meet the requirement of AIS-123 (Part 2): 2016, as amended from time to time, till such time as corresponding Bureau of Indian Standard specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986):

Provided that for the purpose of hybrid electric system kit approval, kit manufacturer or supplier shall obtain the type approval certificate from a test agency specified in rule 126 and the validity of such certificate shall be three years from the date of its issue;

(c)

the installation of type approved hybrid electric system kit shall be done only by an installer authorized by the hybrid electric system kit manufacturer or supplier, and the installer shall adhere to the installer's responsibilities and the Code of Practice detailed in the AIS-123 (Part 2): 2016, as amended from time to time, till such time as corresponding Bureau of Indian Standards (BIS) specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(d)

The vehicle is manufactured after the year of manufacture of the prototype retrofitted vehicle on which such kit has been tested and type approved.

Provided that responsibility of vehicle retro-fitted with Hybrid Electric System Kit shall be transferred from OEM to kit manufacturer or supplier, for the parts added or affected by Hybrid Electric System kit retro-fitment, except in case of zero kilometer fitment.

(3)

The conversion of vehicles for pure electric operation with fitment of electric kit shall be permitted if-

(a)

The vehicle intended for conversion complies with following conditions, namely:-

(i)

It belongs to category L5 or category M or category N1 or category N2;

(ii)

It was manufactured on or after 1st January 1990;

(iii)

It is not provided with permits for carrying dangerous or hazardous goods, as defined in CMV Rules, 1989;

(b)

the vehicle, after retro-fitment, shall meet the requirement of AIS-123 (Part 3): 2016, as amended from time to time, till such time as corresponding Bureau of Indian Standard specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986):

Provided that for the purpose of electric kit approval, kit manufacturer or supplier shall obtain the type approval certificate from a test agency specified in rule 126 and the validity of such certificate shall be three years from the date of its issue;

(c)

the installation of type approved electric kit shall be done only by an installer authorized by the electric kit manufacturer or supplier, and the installer shall adhere to the installer's responsibilities and the Code of Practice detailed in the AIS-123 (Part 3): 2016, as amended from time to time, till such time as corresponding Bureau of Indian Standards (BIS) specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986):

(d)

the vehicle is manufactured after the year of manufacture of the prototype converted vehicle on which such kit has been tested and type approved.

Provided that the responsibility of vehicle converted with Electric Propulsion Kit shall be transferred from OEM to kit manufacturer/ supplier for the parts added or affected by Electric Propulsion Kit, except in case of zero kilometer fitment.]

115D. [Retro fitment of hybrid electric system kit to in-use vehicles.

[Inserted by G.S.R. 364(E), dated 28.5.2014 (w.e.f. 2.6.1989).]

- Retro fitment of hybrid electric system kit to in-use vehicles registered in India shall be permitted if-

(a) the in-use vehicle intended for retro fitment complies with following conditions, namely:-

(i) it conforms to Bharat Stage-II or subsequent emission norms;

(ii) it belongs to category M1 or category M2 or category N1 with Gross Vehicle Weight not exceeding 3500 kg.

(iii) it is fueled by either gasoline or diesel fuel;

(iv) it was not retrofitted earlier;

(v) it will not be fueled by any other alternate fuel;

(b) mass emission standards for vehicles so retrofitted shall be the same as prevalent for corresponding petrol or diesel vehicles as applicable for the year of manufacture of the said vehicle;

(c) the vehicle, after retro fitment, shall meet the requirement of AIS-123 : 2013 as amended from time to time till such time as corresponding Bureau of Indian Standard specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986):

Provided that for the purpose of hybrid electric system kit approval, kit manufacturer or supplier shall obtain the type approval certificate from a test agency specified in rule 126 and the validity of such certificate shall be three years from the date of its issue;

(d) the installation of type approved hybrid electric system kit shall be done only by an installer authorized by the hybrid electric system kit manufacturer or supplier, and the installer shall adhere to the installer's responsibilities and the Code of Practice detailed in the AIS-123 : 2013, as amended from time to time, till such time as corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986.]

115E.

[[Mass emission standards for flex-fuel ethanol (E85) or E100 and ethanol (ED95) vehicles.]

[Inserted by Notification No. G.S.R. 412(E), dated 19.5.2015 (w.e.f. 2.6.1989)]

-

(1)

[The newly manufactured gasoline vehicles fitted with spark ignition engine compatible to run on gasoline or a mixture of gasoline and ethanol up to 85 per cent. Ethanol blend (E85) or mixture of gasoline and ethanol up to 100 per cent (E100), (hereinafter referred to as flex-fuel ethanol vehicle), shall be type approved as per prevailing gasoline emission norms.]

[Substituted by Notification No. G.S.R. 682 (E), dated 12.7.2016 (w.e.f. 2.6.1989).]

(2)

The newly manufactured ethanol vehicle with Gross Vehicle Weight above 3.5 tonnes compatible to run on ethanol fuel (ED95), shall be type approved as per prevailing diesel emission norms, as applicable for that category.

(3)

[The compatibility of vehicle to level of ethanol blend of E85 or E100 or ED95 shall be defined by the vehicle manufacturer and the same shall be displayed on vehicle by putting a clearly visible sticker.]

[Substituted by Notification No. G.S.R. 682 (E), dated 12.7.2016 (w.e.f. 2.6.1989).]

(4)

Test requirements for the type approval and extension for different classes of vehicles are specified in Table 1, Table 2 and Table 3 below, respectively:

[Table 1

[Substituted by Notification No. G.S.R. 682 (E), dated 12.7.2016 (w.e.f. 2.6.1989).]

Test requirements for type approval and extension

For four wheeled vehicles with Gross Vehicle Weight less than or equal to 3,500 kg

S. No.

Test

Flex-fuel ethanol vehicle

1

Gaseous pollutants (Type I test)

On both gasoline and E85 or E100 fuel

2

Idle and high idle emission (Type II test)

On both gasoline and E85 or E100 fuel

3

Crank case emission (Type III)

Only on gasoline fuel

4

Evaporative emissions (Type IV)

Only on gasoline fuel

5

Durability (Type V)

Only on gasoline fuel

6

On-board diagnostics (OBD II)

On both gasoline and E85 or E100 fuel

Table 2

Test requirements for type approval and extension

For two or three wheeled vehicles

S. No.

Test

Flex-fuel ethanol vehicle

1

Gaseous pollutants (Type I test)

On both gasoline and E85 or E100 fuel

2

Idle and emission (Type II test)

On both gasoline and E85 or E100 fuel

3

Crankcase emission (Type III)

Only on gasoline fuel

4

Evaporative emissions (Type IV)

Only on gasoline fuel

5

Durability (Type V)

Only on gasoline fuel]

Table 3

Test requirements for type approval and extension for four wheeled vehicles with Gross Vehicle Weight greater than 3,500 kg

S. No.

Test

Applicability

1

Gaseous pollutants

Test on ED95 fuel (as per prevailing emission norms BSIII or BIV)

2

Free acceleration smoke

Test on ED95

3

Durability, if opted for, instead of fixed deterioration factor

Test on ED95

4

On-board diagnostics (OBD)

Test on ED95

Notes. - (i) Mass emission tests shall be carried out as per MoRTH/CMVR/TAP-115/116 Issue 4 and its subsequent issues or amendments, as applicable and suitable updation of the ratios of gas component densities to exhaust gas density, hydrogen-carbon-oxygen ratio and fuel consumption formula shall be done in type approval procedure.

(ii)

Vehicle manufacturer shall submit the vehicle to any of the test agencies specified in rule 126, for type approval.

(iii)

Flex fuel vehicles with Gross Vehicle Weight less than or equal to 3.5 tonnes shall be tested on chassis dynamometers using the prevailing gasoline vehicle emission driving cycle; and ED95 fuel vehicles with Gross Vehicle Weight greater than 3.5 tonnes shall be tested on engine dynamometers using the prevailing diesel engine emission driving cycle.

(iv)

Flex fuel vehicles shall be tested with reference fuel specified in Annexures IV-J and IV-Q and pure ethanol fuel vehicle shall be tested with reference fuel specified in Annexure-IV-R to these rules.

(v)

For Conformity of Production test applicability, refer to MoRTH/CMVR/TAP-115/116 Issue 4 and its subsequent issues or amendments, as applicable; and fuel requirement for applicable tests, refer to above Table 1, Table 2 and Table 3.

(vi)

The reference fuel shall be as specified in Annexure IV-J for gasoline; Annexure IV Q for E85 vehicles and in Annexure-IV-R for ED95 vehicles.

(vii)

For commercial fuel specifications for gasoline IS 2796:2008 and its subsequent amendments may be referred.

(viii)

For base ethanol specifications refer IS 15464:2004 and for E85 and ED95 commercial fuel, oil marketing companies shall use suitable additives to produce and dispense such grade of fuel. Specification for commercial E85 and ED95 shall be prepared by Bureau of Indian Standards.

(ix)

The Conformity of Production frequency and sampling shall be as per requirements given in MoRTH/CMVR/TAP-115/116 Issue 4 and its subsequent issues or amendments, as applicable, according to category of vehicle.

(x)

Deterioration factors shall be as per prevailing emission norms, according to the vehicle categories, where durability test is applicable.

(xi)

For spark ignition vehicle, where measurement of net power is specified in the case of normal gasoline vehicles, it shall be carried out on engine dynamometer as per IS: 14599-1999, with gasoline, as amended from time to time.]

(xii)

[The reference fuel shall be as specified in Annexure IV-J for gasoline; Annexure S for E100 vehicles.]

[Inserted by Notification No. G.S.R. 682 (E), dated 12.7.2016 (w.e.f. 2.6.1989).]

115F.

[Fuel consumption standard.

[Substituted by Notification No. G.S.R. 954 (E), dated 4.10.2016 (w.e.f. 2.6.1989).]

(1)

Every manufacturer or importer of M1 motor vehicles which are type approved under rule 126, with at least four wheels, other than quadricycles, used for carriage of passengers and their luggage and comprising not more than nine seats including driver's seat, and of gross vehicle weight not exceeding 3,500 kilograms, manufactured or imported for sale in India, shall on and from the 1st day of April, 2017, comply with the Average Fuel consumption Standard, notified under the Energy Conservation Act, 2001 vide notification of the Government of India in the Ministry of Power number 1072 (E), dated the 23rd April, 2015.

(2)

The procedure for ensuring compliance under sub-rule (1) shall be as laid down in Document No. MoRTH/CMVR/TAP-115/116, as amended from time to time.

(3)

The procedure specified under sub-rule (2) shall be evaluated annually by the International Centre for Automotive Technology (ICAT), Manesar.]

115F. [Mass emission standards for bio-diesel (B100).

[Inserted by Notification No. G.S.R. 412(E), dated 11.4.2016 (w.e.f. 2.6.1989).]

- (1) The newly manufactured vehicles fitted with compression ignition engine compatible to run on diesel or mixture of bio-diesel up to hundred per cent bio-diesel (B100) (hereinafter referred to as flex-fuel bio-diesel vehicle), shall be type approved as per prevailing diesel emission norms.

(2) The compatibility of vehicle to level of bio-diesel blend or B100 shall be specified by the vehicle manufacturer and the same shall be displayed on vehicle by putting a clearly visible sticker.

(3) Test requirements for the type approval and extension for different classes of vehicles are specified in Table 1, Table 2 and Table 3 below, respectively:

Table 1

Test requirements for type approval and extension for four wheeled vehicles with Gross Vehicle Weight less than or equal to 3,500 kilogramme

{|

S. No.

Test

Flex-fuel bio-diesel vehicle

1.

Gaseous pollutants (type I test)

On both diesel and B100 fuel

2.

Free acceleration smoke (type II Test)

On both diesel and B100 fuel

3.

Durability (Type V), if opted for instead of fixed

Deterioration Factor (DF)

Only on diesel fuel

4.

On-board diagnostics (India OBD II)

On both diesel and B100 fuel

Table 2

Test requirements for type approval and extension for three wheeled vehicles

S. No.

Test

Flex-fuel bio-diesel vehicle

1.

Gaseous pollutants (Type I test)

On both diesel and B100 fuel

2.

Free acceleration smoke (Type II test)

On both diesel and B100 fuel

3.

Durability (Type V test), if opted for instead of fixed

Deterioration Factor

Only on diesel fuel

Table 3

Test requirements for type approval and extension for four wheeled vehicles with Gross Vehicle Weight greater than 3,500 kg

S. No.

Test

Flex-fuel bio-diesel vehicle

1.

Gaseous pollutants

On both diesel and B100 fuel

2.

Free acceleration smoke

On both diesel and B100 fuel

3.

Durability, if opted for instead of fixed DF

Only on diesel fuel

4.

On-board diagnostics (OBD)

On both diesel and B100 fuel

Diesel vehicles which are declared as compatible to run on bio diesel up to 20 per cent blend shall be tested only with Reference Diesel Fuel for prevailing emission norms.

Notes- 1. Mass emission tests shall be carried out as per MoRTH/CMVR/TAP-115/116 Issue 4 and its subsequent issues or amendments, as applicable, and suitable updation of the ratio of gas component densities to exhaust gas density, hydrogen-carbon-oxygen ratio and fuel consumption formula shall be done in type approval procedure.

2. Vehicle manufacturer shall submit the vehicle to any of the test agencies specified in rule 126, for type approval.

3. Bio-diesel vehicles with Gross Vehicle Weight less than or equal to 3.5 tonne shall be tested on chassis dynamometer using the prevailing diesel vehicle emission driving cycle. B100 fuel vehicles with Gross Vehicle Weight greater than 3.5 tonne shall be tested on engine dynamometers using the prevailing diesel engine emission driving cycle.

4. Bio-diesel vehicles shall be tested with reference fuel (as per IS 15607:2005) specified in Annexure IV-S to these rules.

5. For Conformity of Production test applicability, refer to MoRTH/CMVR/TAP-115/116 Issue 4 and its subsequent issues or amendments, as applicable; and for fuel requirement for applicable tests, refer to above Table 1, Table 2 and Table 3.

6. The Conformity of Production frequency and sampling shall be as per requirements given in MoRTH/CMVR/TAP-115/116 Issue 4 and its subsequent issues or amendments, as applicable, according to category of vehicle.

7. Deterioration factors shall be as per prevailing emission norms, according to the vehicle categories.]

]}

116.

Test for smoke emission level and carbon monoxide level for motor vehicles.

- [(1) Notwithstanding anything contained in sub-rule (7) of rule 115 any officer not below the rank of Sub-Inspector of Police or the Inspector of Motor vehicles who has reason to believe that a motor vehicle is not complying with the provisions of sub-rule (2) or sub-rule (7) of rule 115, may, in writing, direct the driver or any person in charge of the vehicle to submit the vehicle for conducting the test to measure the standards of emission in any one of the authorized testing stations, and produce the certificate to an authority at the address mentioned in the written direction within 7 days from the date of conducting the check.

(2)

The driver or any person in charge of the vehicle shall upon such direction by the officer referred to in sub-rule(1) submit the vehicle for testing for compliance of the provisions of [sub-rule(2) and sub-rule (7) of rule 115]

[Substituted by G.S.R 338(E), dated 26-3-1993 (w.e.f. 26-3-1993).]

, at any authorized testing station.

(3)

The measurement for compliance of the provisions of [sub-rule (2) and sub-rule (7) of rule 115]

[Substituted by GSR 111(E), dated 10.2.2004, for 'sub-rule (2) of rule 115'(w.e.f. 10.8.2004).]

shall be done with a meter of the type approved by any agency referred to in rule 126 of the principal rules or by the National Environmental Engineering Research Institute, Nagpur-440 001:

[Provided that such a testing agency shall follow MoSRTTH/CMVR/TAP--115/116 for approval of measuring metres.]

[Substituted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

(4)

If the result of the tests indicate that the motor vehicle complies with the provisions of [sub-rule (2) and sub-rule (7) of rule 115]

[Substituted by GSR 111(E), dated 10.2.2004, for 'sub-rule (2) of rule 115'(w.e.f. 10.8.2004).]

, the driver or any person in charge of the vehicle shall produce the certificate to the authority specified in sub-rule (1) within the stipulated time-limit.

(5)

If the test results indicate that the motor vehicle does not comply with the provisions of the sub-rule (2) and [sub-rule (2) and sub-rule (7) of rule 115]

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

, the driver or any person in charge of the vehicle shall rectify the defects so as to comply with the provisions of the sub-rule(2) of rule 115 within a period of 7 days and submit the vehicle to any authorized testing station for re-check and produce the certificate so obtained from the authorized testing station to the authority referred to in sub-rule (1).

(6)

If the certificate referred to in sub-rule (1) is not produced within the stipulated period of seven days or if the vehicle fails to comply with the provisions of [sub-rule (2) and sub-rule (7) of rule 115]

[Substituted by G.S.R 276 (E), dated 10.4.2007 (w.e.f. 10.4.2007).]

within a period of seven days, the owner of the vehicle shall be liable for the penalty prescribed under sub-section (2) of section 190 of the Act.

(7)

If the driver or any person in charge of the vehicle referred to in sub-rule (1) does not produce the said certificate within the said period of 7 days, such vehicle shall be deemed to have contravened the provisions of the sub-rule (2) of rule 115 and the checking officer shall report the matter to the registering authority.

(8)

The registering authority shall on receipt of the report referred to in sub-rule (7), for reasons to be recorded in writing suspend the certificate of registration of the vehicle, until such time the certificate is produced before the registering authority to the effect that the vehicle complies with the provisions of [sub-rule (2) and sub-rule (7) of rule 115]

[Substituted by G.S.R. 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

.

(9)

On such suspension of the certificate of registration of the vehicle, any permit granted in respect of the vehicle under Chapter V or under Chapter VI of the Motor Vehicles Act, 1988 (59 of 1988

) shall be deemed to have been suspended until a fresh Pollution under control certificate is obtained.]

Speed governors

117.

Speedometer.

(1)

[Every motor vehicle (including construction equipment vehicle)],

[Substituted by GSR 642(E), dated 28.7.2000, for 'Every motor vehicle, other than an invalid carriage'(w.e.f. 28.7.2000).]

[other than an invalid carriage or an E-rickshaw or E-cart or a vehicle]

[Substituted for the words 'other than an invalid carriage or a vehicle, the designed speed of which does not exceed thirty kilometres per hour'by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

, shall be fitted with an instrument(hereinafter referred to as speedometer) so constructed and fixed in such a position as to indicate to the driver of the vehicle the speed at which the vehicle is travelling :

[Provided that every agricultural tractor [and combine harvester]

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

shall be fitted with an Engine RPM-cum-Hour Meter:]

[Provided further that the requirement of provision of speedometer is exempted for construction equipment vehicle in which the drivers cabin rotates about a vertical axis.]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

(2)

[On and after the 1st April, 2015 (in the case of new models) and 1st April 2016 (in the case of existing models), every motor vehicle shall be fitted with a speedometer conforming to the requirements of IS:11827-2008, specified by the Bureau of Indian Standards, as amended from time to time.]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

(3)

[On and after 1st April, 2015 every construction equipment vehicle manufactured shall be fitted with a speedometer that shall conform to the requirements of IS 11827-2008 specified by the Bureau of India Standards concerning the speedometer]

[Inserted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

118.

[Speed governor.

[Substituted by Notification No. G.S.R. 290 (E) dated 15.4.2015 (w.e.f. 2.6.1989)]

(1)

Every transport vehicle notified by the Central Government under sub-section (4) of section 41 of the Motor Vehicles Act, 1988 (

59 of 1988

) save as provided herein, and manufactured or on after the 1st October, 2015 shall be equipped or fitted by the vehicle manufacturer, either in the manufacturing stage or at the dealership stage, with a speed governor (speed limiting device or speed limiting function) having maximum pre-set speed of 80 kilometre per hour conforming to the Standard AIS 018/2001, as amended from time to time:

Provided further that the transport vehicles that are -

(i)

two wheelers;

(ii)

three wheelers;

(iii)

quadricycle's;

(iv)

[* * *]

(v)

fire tenders;

(vi)

ambulances;

(vii)

police vehicles;

(viii)

verified and certified by a testing agency specified in rule 126 to have maximum rated speed of not more than 80 kilometre per hour;

Provided further that the transport vehicles manufactured on or after 1st October, 2015 that are dumpers, tankers, school buses, those carrying hazardous goods or any other category of vehicle, as may be specified by the Central Government by notification in the Official Gazette from time to time, shall be equipped or fitted by the vehicle manufacturer, either in the manufacturing stage or at the dealership stage, with a speed governor (speed limiting device or speed limiting function) having maximum speed of 60 kilometre per hour conforming to the Standard AIS 018/2001, as amended from time to time.

[Provided also that on and from 1st April 2017, articulated or truck-trailer or tractor-trailer vehicles engaged by

automobile manufacturers to carry motor vehicles from their factories to different sale outlets in the country, shall be equipped or fitted by the vehicle manufacturer, either in the manufacturing stage or at the dealership stage, with a speed governor (speed limiting device or speed limiting function) having maximum speed of 60 kilometers per hour conforming to AIS 018/2001, as amended from time to time, till such time the corresponding Bureau of Indian Standards specifications are notified.]

[Inserted by Notification No. G.S.R. 963 (E), dated 7.10.2016 (w.e.f. 2.6.1989).]

(2)

The State Government shall, by notification in the Official Gazette, specify on or before 1st October, 2015, the categories of transport vehicles registered prior to the 1st October, 2015 which are not already fitted with a speed governor (speed limiting device or speed limiting function), and are not covered under the first proviso to sub-rule 1 above, that such transport vehicles shall be equipped or fitted by the operators of those vehicles on or before 1st April, 2016 with a speed governor (speed limiting device or speed limiting function), having maximum pre-set speed of 80 kilometre per hour or such lower speed limit as specified by the State Government from time to time, conforming to the Standard AIS: 018/2001, as amended from time to time:

Provided that the categories of transport vehicles carrying hazardous goods and those transport vehicles that are dumpers, tankers or school buses, registered prior to the 1st October, 2015 and not already fitted with a speed governor (speed limiting device or speed limiting function), shall be equipped or fitted by the operator of such vehicle, with a speed governor (speed limiting device or speed limiting function) having maximum pre-set speed of 60 kilometre per hour or such other lower speed limit as may be specified by the State Government, conforming to the Standard AIS: 018/2001, as amended from time to time".]

(3)

[. An Airport Passenger Bus, referred to in rule 93C, shall be equipped or fitted with a speed governor (speed limiting device or speed limiting function) having maximum pre-set speed of thirty kilometer per hour or such lower speed limit as specified by the State Government from time to time, conforming to the standard AIS: 018/2001 as amended from time to time.]

[Inserted by Notification No. G.S.R. 594(E), dated 13.6.2016 (w.e.f. 2.6.1989).]

Reduction of noise

119.

Horns.

(1)

[On and after expiry of one year from the date of commencement of the Central Motor Vehicles(Amendment) Rules, 1999, [every motor vehicle, agricultural tractor, power tiller and construction equipment vehicle]

[Substituted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

manufactured shall be fitted with an electric horn or other devices conforming to the requirements of IS: 18841992,specified by the Bureau of Indian Standards] for use by the driver of the vehicle and capable of giving audible and sufficient warning of the approach or position of the vehicle:

[Provided that vehicles manufactured on and from the 1st October, 2014, the horn installation requirements for motor vehicles shall be as per IS:15796-2008, specified by the Bureau of Indian Standards, as amended from time to time.]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

(1A)

[Every combine harvester shall be fitted with an electric horn or other devices confirming to the requirements of IS 1884 : 1993 specified by the Bureau of Indian Standards for use by the driver of the vehicle and capable of giving audible and sufficient warning of the approach or position of the vehicle:

Provided that the horn installation requirement for combine harvester shall be as per IS 15796:2008 specification as amended from time to time.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(2)

No [motor vehicle including agricultural tractor]

[Substituted by GSR 111(E), dated 10.2.2004, for 'motor vehicle'(w.e.f. 10.8.2004).]

[and combine harvester]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall be fitted with any multi-toned horn giving a succession of different notes or with any other sound-producing device giving an unduly harsh, shrill, loud or alarming noise.

(3)

Nothing contained in sub-rule (2) shall prevent the use on vehicles used as ambulance or for fire fighting or salvage purposes or on vehicles [used by police officers or operators of construction equipment vehicles or officers of the Motor Vehicles Department]

[Substituted by GSR 116(E), dated 27.2.2002 (w.e.f. 27.8.2002).]

[in the course of their duties or on construction equipment vehicles,]

[Substituted by GSR 642(E), dated 28.7.2000, for 'in the course of their duties'(w.e.f. 28.7.2000).]

of such sound signals as may be approved by the registering authority in whose jurisdiction such vehicles are kept.

[Provided that requirements for sirens of Road Ambulances shall be in accordance with AIS:125 (Part 1)-2014, as amended from time to time, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

[Inserted by Notification No. G.S.R. 868(E), dated 1.4.2018 (w.e.f. 2.6.1989).]

120.

Silencers.

(1)

[Every motor vehicle including agricultural tractor]

[Substituted by GSR 111(E), dated 10.2.2004, for 'Every motor vehicle'(w.e.f. 10.8.2004).]

[and combine harvester]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall be fitted with a device(hereinafter referred to as a silencer) which by means of an expansion chamber or otherwise reduces as far as practicable, the noise that would otherwise be made by the escape of exhaust gases from the engine.

(2)

[Noise standards

[Substituted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

.Every motor vehicle shall be constructed and maintained so as to conform to noise standards specified in Part E of the Schedule VI to the environment (Protection) Rules, 1986, when tested as per IS:3028-1998, as amended from time to time]:

[Provided that on and from the 1st day of April, 2006, where different noise levels are prescribed for vehicles, the lowest limits prescribed for vehicles of such category, shall apply to Battery Operated Vehicles.]

[Proviso added by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

(3)

[In the case of agricultural tractor, the measurement test for driver perceived noise level and permissible sound level at bystander shall be carried out as per AIS-115 (Part 1)-2009 and AIS-115 (Part 2)-2009 respectively, as amended from time to time till such time the corresponding Bureau of Indian Standards specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986) and shall conform to the levels as specified in the Table 1 and Table 2 below :-]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

[TABLE 1]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

serial

number

Agriculture

Tractor

Date

of Implementation

Driver-perceived

noise level

(1)

All

1st

April, 2015

96

dB(A)* 92 dB (A)*

[* As per Annexure I of AIS-115 (Part 1)-2009

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

** As per Annexure II of AIS-115 (Part 1)-2009]

[TABLE 2]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

Serial

number

Agriculture

Tractor

Date

of Implementation

By

stander's position

(1)

>

1.5 TG/VW

1st

April, 2015

88 dB

(A)

(2)

<

1.5 TG/VW

1st

April, 2015

85 dB

(A)'

(4)

[In the case of power tiller with a riding attachment or power tiller coupled to trailer, the noise level when tested as per IS:12180:2000, as amended from time to time, shall not exceed 88dB(A) at the bystander position and 98dB(A) at the operators ear level.]

[Sub-Rule(4) inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 1.10.2006).]

(5)

[In the case of combine harvester, the noise level at operator's ear level shall be measured as per Annex B of IS 12180 (Part-1): 2000, whereas the noise level at bystander's position shall be measured as per IS 12180 (Part-2): 2000:

Provided that the noise level shall not exceed 98 dB (A) at operator's ear level and 88 dB (A) at bystander position.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

121.

Painting of motor vehicles.

(1)

[No motor vehicle including [agricultural tractor and construction equipment vehicle and combine harvester]

[Substituted by GSR 642(E), dated 28.7.2000, for 'No motor vehicle'(w.e.f. 28.7.2000).]

] shall be painted in olive green colour except those belonging to the Defence Department.

(2)

No contract carriage other than a tourist vehicle covered by permit under sub-section (9) of section 88 shall be painted in the manner specified in sub-rule (11) of rule 128.

(3)

No goods carriage other than a goods carriage covered by national permit shall be painted in the manner specified in

sub-rule (1) of rule 90.

Chassis number and engine number

122.

[[Embossment of the chassis number and engine number or in the case of battery operated vehicles, motor number and month of manufacture.]

[Rule 122 substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

- [(1) Every L, M and N categories of Motor vehicles, manufactured on and after 1st day of April, 2009, shall bear the identification number including month and year of manufacture, embossed or etched or punched on it, in accordance with AIS 065:2005 till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986(63 of 1986):]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 1.4.2009).]

Provided that every N category vehicle, manufactured on and after the 1st day of April, 2009 shall bear manufacturers plate as prescribed in AIS 065:2005 till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986(63 of 1986).]

(1A)

[Every [agricultural tractor, construction equipment vehicle, hydraulic modular trailer and combine harvester]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

shall bear the identification number including month and year of manufacture, embossed or etched or punched on it:

[Provided further that on and from the 1st day of April, 2016 in case of the construction equipment vehicles the identification number including month and year of manufacture, embossed or etched or punched on it shall be in accordance with AIS-136:2015, as amended from time to time, till the corresponding Bureau of Indian Standards specification are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

[Inserted by Notification No. G.S.R. 133(E), dated 29.1.2016 (w.e.f. 2.6.1989).]

Provided that in case of agricultural tractor the identification number including month and year of manufacture, embossed or etched or punched on it shall be in accordance with AIS 117- 2011, as amended from time to time till the corresponding Bureau of Indian Standards specifications are notified under Bureau of Indian Standards Act, 1986 (63 of 1986)]

[Provided further that on and from 1st day of April, 2016 in case of the construction equipment vehicles the identification number including month and year of manufacture, embossed or etched or punched on it shall be in accordance with AIS - 136:2015, as amended from time to time till the corresponding Bureau of Indian Standards specification are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

[Inserted by Notification No. G.S.R. 913(E), dated 18.11.2015 (w.e.f. 2.6.1989).]

(1B)

[Every combine harvester and hydraulic modular trailer shall bear the identification number plate including the following information embossed or etched or punched on it:

(i)

Name of manufacturer

:

(ii)

Model name

:

(iii)

Chassis number

:

(iv)

Engine/Tractor make & model

:

(v)

Engine Sl. No. (in case of Self propelled combine)

:

(vi)

Month & year of manufacture

:]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(2)

[The vehicle manufacturer shall intimate to the certifying testing agency regarding the place where the numbers shall be embossed or etched or punched including code for the year and month of production in respect of each model and such testing agency shall include these details in the certificate of compliance granted by that agency under rule 126.No manufacturer shall change the place of embossing, etching or punching and the code for the month and year of production without prior intimation by registered post to the testing agency which granted the certificate of compliance to these rules:]

[Substituted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).]

[* * *]

[Proviso omitted by GSR 784(E), dated 12.11.2008 (w.e.f. 1.4.2009).]

(3)

[In case of E-rickshaw or E-cart, the registered E-rickshaw or E-cart Association or manufacturer producing E-rickshaw or E-cart shall intimate to the State Transport Authority regarding the place where the number shall be embossed or etched or punched including the code for the year and month of production for each model of E-rickshaw or E-cart.]

[Inserted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

Safety Devices

Safety devices for drivers, passengers and road users

123.

Safety devices in motor cycle.

- No motor cycle, [which has provision for pillion rider]

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

shall be constructed without provision for a permanent hand grip on the side or behind the drivers seat and a foot rest and a protective device covering not less than half of the rear wheel so as to prevent the clothes of the person sitting on the pillion from being entangled in the wheel:

[Provided that on and from 1st January, 2003, the pillion hand holds shall be governed by IS: 14495-1998 specifications, as may be amended from time to time.]

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

[Provided that on and after 1st October, 2016, a light weight container may be fitted on a motorcycle provided it meets the following requirements:

(i)

the dimensions of the container shall not exceed 550 mm in length, 510 mm in width and 500 mm in height;

(ii)

weight of the container including its mounting and the load carried in the container shall not exceed 30 kgs;

(iii)

if such container is fitted on the pillion rider space, then no pillion rider shall be allowed:

Provided that the weight of container including its mounting and the load carried in the container, shall be within the permissible Gross Vehicle Weight in kg, specified by the vehicle manufacturer and also approved by the test agency referred to in rule 126;

(iv)

if such container is fitted behind the pillion rider space then no pillion rider should be allowed to be seated:

Provided that the weight of the pillion rider, and weight of the container including its mounting and the load carried in the container, shall be within permissible Gross Vehicle Weight in kg, specified by the vehicle manufacturer and also approved by the test agency referred to in rule 126.]

[Inserted by Notification No. G.S.R. 473(E), dated 2.5.2016 (w.e.f. 2.6.1989.).]

[Provided further that on and after the 1st day of April, 2016, a box not exceeding 550 mm in length, 510 mm in width and 500 mm in height may be fitted on a motor cycle for carriage of any items:

Provided also that no pillion rider shall be allowed on a motor cycle on which a box as specified in the above proviso has been fitted.]

[Inserted by Notification No. G.S.R. 789(E), dated 19.10.2015 (w.e.f. 2.6.1989).]

124.

[Safety standards of components.

[Rule 124 substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

- [(1) The Central Government may, from time to time, specify, by notification in the Official Gazette, the standards or the relevant standards specified by the Bureau of Indian Standards of any part, component or assembly to be used in the manufacture of a vehicle including construction equipment vehicle and the date from which such parts, components or assemblies are to be used in the manufacture of such vehicle and on publication of such notification every manufacturer shall use only such of these parts, components or assemblies in manufacture of the vehicle:

[Provided that any notification issued under this sub-rule before the commencement of the Central Motor Vehicles (6th Amendment) Rules, 2001, shall not be applicable after such commencement up to and including [26th August, 2002]

[Inserted by GSR 675(E), dated 17.9.2001 (w.e.f. 17.9.2001).]

in respect of any construction equipment.]

(1A)

[the general requirements of vehicle rear under run protecting device and the technical requirements of vehicle lateral protection side shall be as per IS:14812-2005 and as per IS:14682-2004, specified by Bureau of Indian standards, respectively, as amended from time to time, for the motor vehicles of categories mentioned therein.]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

[Provided that the vehicle manufacturers shall ensure the fitment of the rear under run protective device in vehicles of categories N2, N3 and their trailers except special purpose vehicles namely tractors and tippers at their end and lateral under run protective device either at their factory or at their dealers end. Vehicle not fitted with such devices shall not be registered under these rules. They shall also ensure to supply necessary kits if the fitment is not done by them in the case of lateral under-run protective device:

Provided further that the rear under run protective device shall also be painted with yellow and white zebra stripes on the entire rear face of the device.] [[Provisos inserted by GSR 589(E), dated 16.9.2005 (w.e.f.

16.3.2006

).]]

(1B)

[There shall not be any requirement regarding fitment of rear under run protection device and lateral protection device in modular hydraulic trailers.

(1C)

"T" signs, wherever used on modular hydraulic trailers, shall comply with IS : 9942 : 1981.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(2)

[Every manufacturer shall get the prototype of the part, component or sub-assembly for which standards have been notified, approved from any agency as referred to in rule 126 [and in the case of tyre and rubber components from the Indian Rubber Manufacturers Research Association, Thane]

[Substituted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

, or in case of compliance with notified Indian Standards from any laboratory duly authorized by the Bureau of Indian Standards. On the basis of such approval, every manufacturer shall also certify compliance with the provisions of this rule in Form 22.]

[(2-A) In case of E-rickshaw or E-cart, the registered E-rickshaw or E-cart Association or manufacturer producing E-rickshaw or E-cart shall get the prototype of the part, component or sub-assembly for which standards have been notified, approved from any agency as referred to in rule 126 or the Central Institute of Road Transport, Pune, or in case of compliance with notified Indian Standards from any laboratory duly authorized by the Bureau of Indian Standards, and on the basis of such approval, the E-rickshaw or E-cart association or manufacturer shall also certify compliance with the provisions of this rule in Form 22.]

[Inserted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

(3)

[The Central Government may, by notification in the Official Gazette, frame a scheme for marking to be affixed on any part or component or assembly to be used in the manufacture of the vehicle and specify the date from which such parts,

components or assemblies are to be used in the manufacture of the vehicle.]

[Inserted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).]

(4)

[The procedure for type approval and establishing conformity of production for components, listed in table below, shall be in accordance with AIS:037-2004 till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986(63 of 1986).

TABLE

Sl. No.

Component

Reference Rule

Effective for vehicles manufactured on and from

1.

2.

3.

4.

1.

Safety Glass

Rule 100(2), (3) and (3-A)

1stApril, 2009

2.

Brake hose

Sl.No.2 of Table of S.O. 1365 (E), dated 13-12-2004 and Sl.No. 3 of 124-A

1stApril, 2009

3.

Horn

Rule 199(1)

1stApril, 2009

4.

Tyre

Rule 95(1)

1stApril, 2009

5.

CNG Regulator

Sl.No.

3 of Annexure IX

1stApril, 2009

6.

LPG vaporizer/regulator

Sl.

No. 3 of Annexure VIII

1stApril, 2009

7.

Bulb

Sl.

No. 1 of Table of S.O. 1365 (E), dated 13-12-2004 and Sl.No. 1 of 124-A

1stOctober, 2009

8.

Rear view mirror

Rule 125(2)

1stOctober, 2009

9.

Speed limiting devices

Rule 118(1)

1stOctober, 2009

10.

Safety Belt

Rule 125(1-A)

1stOctober, 2009

11.

Wheel rims for M and N category

Sl.

No. 8 of Table of S.O. 1365(E), dated 13-12-2004

1stOctober, 2009

12.

Lighting and light signalling devices for M and N Category

Sl.No.

20 of Table of S.O. 1365(E), dated 13-12-2004

1stOctober, 2009

13.

Retro-reflectors for M and N Category

Rule 104(4) and 104-A(vi)

1stOctober, 2009

14.

Warning triangle

Rule 138(4)(c)

1stOctober, 2009

15.

Lighting and light signalling devices for L category

Sl.No.

32 of Table of S.O. 1365(E), dated 13-12-2004

1stApril, 2010

16.

Retro-reflectors for L category

Rule 104(4) and 104-A(vi)

1stApril, 2010

17.

Retro-reflector for Agricultural Tractors and Constructional Equipment Vehicles

Rule 104-A and Rule 104-B

1stApril, 2010

18.

Lighting and signalling devices for Agricultural Tractors and Constructional Equipment Vehicles

Sl.No.2 of Rule 124-A

1stApril, 2010

19.

Door locks and Door retention components

Sl.No.

16 of Table of S.O. 1365(E), dated 13-12-2004

1stApril, 2010

20.

Fuel tanks

Sl.No.

7 and 25 of Table of S.O. 1365(E), dated 13-12-2004. Sl. No.6 of Rule 124-A

1st April, 2010

21.

Reflective tapes

Rule 104(1)

1st April, 2010

Provided that the component manufacturers shall comply with the requirements six months prior to the date mentioned in column (4) above.]

[Inserted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

[[124-A. Safety standards of components for agricultural tractors and combine harvesters.]

[Inserted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004) and as corrected by vide GSR 176(E), dated 53.2004.]

(1)

The bulbs of the following lamps used on agricultural tractors [and combine harvesters]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall conform to [AIS:034-2010]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

, as amended from time to time.

(a)

Head light main and dip;

(b)

Parking light;

(c)

Direction indicator lamp;

(d)

Tail lamp;

(e)

Reversing lamp;

(f)

Stop lamp;

(g)

Rear Registration mark indicating lamp; and

(h)

Top light.

(2)

The lighting and light signalling devices for agricultural tractor [and combine harvesters]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall be in accordance with AIS:030, as amended from time to time, till such time the corresponding BIS standard is notified:

Provided that the performance requirements of the lighting, light signalling and indicating systems of agricultural tractor [and combine harvesters]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

manufactured on and from [1st October, 2005]

[Substituted by GSR 206(E), dated 1.4.2005, for '1st April, 2005'(w.e.f.1.4.2005).]

shall be in accordance with safety standard AIS:062, as amended from time to time, till such time corresponding BIS standards are notified:

[Provided further that the performance requirements of the lighting and light-signaling devices of agricultural tractors manufactured on and after the 1st day of April, 2017 shall be in accordance with AIS:062 (Rev.1): 2014, as amended from time to time, till such time corresponding BIS standards are notified:]

[Inserted by Notification No. G.S.R. 880(E), dated 14.9.2016 (w.e.f. 2.6.1989).]

[[Provided also]

[Inserted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

that the performance of rear warning triangle fitted on agricultural tractors manufactured on and after the 1st day of April,

2009, shall be in accordance with AIS:088-2005, except for clause 1.4.3 of Annexure 6 therein till such time corresponding BIS standards are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

[Provided also that in case of combine harvesters, if the shape of body work makes it impossible to comply with the height requirement of installation of the following lighting and light-signalling devices, it shall be allowed at a height not exceeding 3000 mm:

(i)

Dipped-beam headlamp (Ref. clause 6.2.4.2)*

(ii)

Front direction indicator lamp (Ref. clause 6.5.4.2.3)*

(iii)

Front position lamp (Ref. clause 6.9.4.2)*

(iv)

Front parking lamp (Ref. clause 6.12.4.2)*

*Note :Reference clause numbers of AIS-030:2001:

Provided also that the performance requirements of the lighting, light signalling and indicating systems of combine harvester shall be in accordance with safety standards AIS:062-2004, as amended from time to time, till such time as the corresponding Bureau of Indian Standards are notified:

Provided also that the performance of rear warning triangle fitted on combine harvester shall be in accordance with AIS:088-2005, except clause 1.4.3 of Annexure 6 therein, as amended from time to time, till such time the corresponding Bureau of Indian Standards are notified.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(3)

The hydraulic brake hoses wherever used in agricultural tractor [and combine harvesters]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

and its trailer shall be in accordance with [IS:7079-2008]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

, as amended from time to time.

(4)

The vegetable, non-mineral based hydraulic fluids wherever used in agricultural tractor [and combine harvesters]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall be in accordance with IS:8654 -1986, as amended from time to time.

(5)

The tow hook wherever used in agricultural tractor [and combine harvesters]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall be in accordance with IS:12362 (Part 2), as amended from time to time.

(6)

[The fuel tank of agricultural tractors shall conform to AIS: 104-2008, as amended from time to time:]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

Provided that the clause 3.2.1 of IS:12056 -1987 be exempted for agricultural tractor that have a gravity feed fuel flow system.

(7)

The wheel nuts and hub caps used in agricultural tractor [and combine harvesters]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall be in accordance with IS:13941 -1994, as amended from time to time.]

(8)

[On and after the 1st October, 2012, the ballast mass, wherever used in agriculture tractor, shall conform to AIS 105: 2008, as amended from time to time, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(9)

On and after the 1st October, 2012, the protective structures, wherever provided in agriculture tractor, shall conform to IS:11821 (Part 1)- 1992 or IS:11821 (Part 2)-1992, as the case may be.

(10)

On and after the 1st October, 2012, the load platform, wherever used in agriculture tractors, shall conform to AIS:106-2009, as amended from time to time, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(11)

On and after the 1st October, 2012, the attendant's seat, wherever used in agricultural tractors, shall conform to AIS:111-2009, as amended from time to time, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(12)

On and after the 1st October, 2012, for agricultural tractors, the driver's field of vision shall conform to AIS:107-2009, as amended from time to time, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

(13)

[On and after 1st April, 2015, for agricultural tractors, the maximum design speed shall be in accordance with AIS-116-2009.]

[Inserted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

[124-B. Safety standards of components for power tillers.

[Rule 124-B inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

(1)

The lamps and bulbs used on power tillers for

(a)

the head light main and dip;

(b)

the parking light;

(c)

the direction indicator lamp;

(d)

the tail lamp;

(e)

the reversing lamp;

(f)

the stop lamp;

(g)

the rear Registration mark illuminating lamp,

shall be in accordance with AIS:034:2004 as amended from time to time till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(2)

The lighting and signalling devices shall be in accordance with AIS:062:2004 as amended from time to time, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(3)

The safety and comfort of the operator of a power tiller shall be in accordance with IS:12239 (Part3):1996, as amended from time to time.

(4)

The grade ability of a power tiller coupled to a trailer under the declared combination weight by the manufacturer shall be in accordance with IS:9980:1988, as amended from time to time.]

[Inserted by Notification No. G.S.R. 625 (E) dated 8.8.2012 (w.e.f. 2.6.1989)]

125.

[Safety belt, collapsible steering column, auto dipper and padded dash boards.

[Rule 125 substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

- [(1)] One year from the date of commencement of the Central Motor Vehicles(Amendment) Rules, 1993, the manufacturer of every motor vehicle other than motor cycles and three-wheelers [* * *]

[The words, figures and letters 'of engine capacity not exceeding 500 cc' omitted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

, shall equip every such vehicle with a seat belt for the driver and for the person occupying the front seat.

[(1-A) The manufacturer of every motor vehicle of M-1 category shall equip every motor vehicle with a seat belt for a person occupying the front facing rear seat:

Provided that the specifications of Safety Belt Assemblies and Safety Belt Anchorages in Motor vehicles shall conform to [IS: 15140-2003 and IS: 15139-2002 respectively]

[Sub-Rule(1-A) substituted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

:

Provided further that on and after 1st October, 2002, the specification of Safety Belt Assemblies and safety Belt Anchorages in motor vehicles shall conform to [IS:15140-2003 and IS:15139-2002 respectively]

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 1.4.2009).]

.]]

[(1-B) On and after the 1st day of October, 2009, the front under run protective n (sic) after 1st day of October, 2009 shall comply with the requirements specified in AIS: 069-2006, till the corresponding HIS specifications are devices fitted on N2 and N3 categories of motor vehicles, manufactured o (sic) notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).

(1-C) On and after the 1st day of April, 2009, the temporary cabin fitted on drive away chassis vehicles of Category M and N, manufactured on and after the 1st day of October, 2008 that are driven off from the factory premises for purposes of body building, shall comply with the requirements specified in AIS: 070-2004 till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

[Inserted by GSR 784(E), dated 12.11.2008 (w.e.f. 12.11.2008).]

[Provided that this sub-rule is applicable only to those drive away chassis vehicles driven on road, whenever and wherever, by its own wheels using own power and not applicable to those drive away chassis vehicles that are transported upon trailers or by any other mode of transportation.]

[Inserted by Notification No. G.S.R. 121 (E), dated 10.2.2017 (w.e.f. 2.6.1989).]

(2)

Six months from the date of commencement of the Central Motor Vehicles (Amendment) Rules 1993, all motor vehicles shall be equipped with rear view mirror.

[Provided that [on and from 1st May, 2003]

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

, the rear view mirror specifications and installation requirements shall be as specified by AIS: 001-2001 and AIS: 002-2001 respectively, as may be amended from time to time, till such time as corresponding Bureau of Indian Standards specifications are notified.]

[Provided further that on and after the 1st October, 2012, for agricultural tractors, the rear view mirror specifications and installation requirements shall conform to AIS: 001-2001 and AIS:114- 2009 respectively, as amended from time to time, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

[Inserted by Notification No. G.S.R. 625 (E) dated 8.8.2012 (w.e.f. 2.6.1989)]

[* * *]

[Sub-Rule(3) omitted by GSR 29(E), dated 15.1.1998 (w.e.f. 15.1.1998).]

[* * *]

[Sub-Rule(4) omitted by GSR 659(E), dated 12.9.2001 (w.e.f. 12.9.2001).]

(5)

[On and after 1st January, 2003, the size and specifications on seats, their Anchorages and Head Restraints(excluding luggage retention) on M-1 vehicle category shall conform to [IS: 15546-2005]

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

.

(6)

[On and from the 1st day of October,2007, the seats, their anchorages and their head restraints for M2, M3, N1, N2and N3 category of vehicles, shall be in accordance with AIS:023:2005 as amended from time to time till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).] [[Sub-Rule(6) inserted by

GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]]

[[(8) Motor vehicles of category M1]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

excluding transport vehicles and special purpose vehicles manufactured on and after 1st April, 2015, shall have a provision for installation of at least one category of child restraint system for all weight groups on at least one of the seating positions, as specified in AIS: 072-2009, as amended from time to time, till the corresponding Bureau of Standards specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986):

Provided that the manufacturer or importer or dealer of the child restraint system shall provide the guidelines for fitment and use of such system to the buyer of such vehicles:

Provided further that for such vehicles, vehicle manufacturer or importer or dealer of the motor vehicle shall provide the guidelines for recommended position in the vehicle.]

(9)

[Motor vehicles of category M1, manufactured on and after the 1st day of July, 2019, shall comply with the additional safety features and its requirements stipulated in AIS-145-2017, as amended from time to time.]

[Inserted by Notification No. G.S.R. 1483(E), dated 7.12.2017 (w.e.f. 2.6.1989).]

[[125-A. Safety belt, etc., for construction equipment vehicles and combine harvesters.]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

- One year from the date of commencement of the Central Motor Vehicles (Sixth Amendment) Rules, 2000, the manufacturer of every construction equipment vehicle other than an agriculture tractor shall equip every such vehicle with a seat belt for the driver and for the person occupying the front seat, and with a rear view mirror.]

[Provided that every combine harvester fitted with a cabin, shall be equipped with a seat belt for the driver and with a rear view mirror.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

[125-B. Special requirements for transport vehicles that are driven on hills.

[Rule 125-B and 125-C inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2005).]

(1)

On and from the 1st day of October, 2006, such four wheeled transport vehicles as may be notified by State Governments in the Official Gazette plying on such routes or areas in hilly terrains shall be fitted with fog lamp, power steering, defrosting and demisting system and that the State Government would provide a lead time of six months for this purpose.

(2)

Anti-Lock Braking System shall be introduced in all M-2category buses including those plying on All India Tourist Permit on and from the 1st day of October, 2007 in hill areas.

125.

-C. Bodybuilding and approval.

- [(1) On and after the 1st day of October, 2014, the testing and approval for body building of new models of buses with seating capacity of 13 or more passengers excluding driver shall be in accordance with AIS:052 (Revision 1)-2008, as amended from time to time, for vehicles mentioned therein, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986)]

[Substituted by Notification No. G.S.R. 287 (E) dated 22.4.2014 (w.e.f. 2.6.1989)]

[Provided that the provision of this rule shall be implemented in two phases.

[Substituted by Notification No. G.S.R. 895 (E) dated 20.9.2016 (w.e.f. 2.6.1989)]

In first phase, the provisions of AIS 052 (Rev. 1) - 2008, excluding the parameters and requirements given in Table-1 below, shall be applicable on and after 1st day of January, 2017.

In second phase, the provisions of AIS-052 (Rev. 1) - 2008, as amended from time to time, and the parameters and requirements given in (Table-1) below, shall be applicable on and after 1st day of January, 2018.

(Table -1)

(Additional Technical Provisions of AIS: 052(Rev-1))

Sr. No.

Nature of Test/ Parameters

Requirements of Specific Clauses of AIS-052

(Rev.1)

(1)

(2)

(3)

1.

Scope and Definitions (As applicable)

1.0

2.

Body Structure Strength

3.1

3.

Body Structure Stability

3.2

4.

Window Retention

3.6

5.

Window Frames

3.6.5.5

6.

Wind Screen Wiping System and Driver's field of Vision

3.10

7.

Test Methods (As applicable)

Chapter 6

8.

Vertical orientation for dipped beam - head lamp

Annexure I, Table with title "Details about Safety

Critical Components"

9.

Seat Anchorages/ Systems.]

[Provided further that the operation of the airport passenger bus shall be restricted within the airport premises, for movement of passengers and such buses shall be provided with a marking "Restricted Use: Within Airside Operations Only" with a letter size of not less than 50mm in height on each side of the bus.]

[Inserted by Notification No. G.S.R. 594(E), dated 13.6.2016 (w.e.f. 2.6.1989).]

(2)

The testing and approval for the body building of school buses shall be in accordance with AIS:063:2005 as amended from time to time for vehicles mentioned therein, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

(3)

[All goods vehicles of Category N2 and of Category N3, either manufactured by a vehicle manufacturer or a body builder on drive away chassis vehicles shall, till the corresponding BIS specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986) comply with the provisions of AIS-093 (Rev. 1)-2015, as specified in Table I and Table II below, namely:-

Table I

Sr. No.

Test Parameters

Requirements of Specific Clauses of AIS-093

(Rev.1)

(1)

(2)

(3)

1.

Overall Dimensions

2.1.1

2.

External Projections for cabin

2.1.2

3.

Driver/ Co-passenger Door

2.1.3

4.

Climb Facility

2.1.4

5.

Hand Holds

2.1.5

6.

Window on Cab Door

2.1.6

7.

Driver Seat/ Co passenger seat

2.1.7

8.

Safety Belt Assemblies and Anchorages

2.1.8

9.

Sleeper Berth

2.1.9

10.

Mudguards/ Spray suppression devices

2.1.10

11.

Driver Work Area

2.1.11

12.

Steering Wheel

2.1.12

13.

Placement of Instrument Panel

2.1.13

14.

Position of Controls

2.1.14

15.

Stowage Space

2.1.15

16.

First Aid Box

2.1.16

- 17.
Truck Cab Structural Strength
 - 2.2.1
- 18.
Front Under run Protective Device (FUPD)
 - 2.2.2
- 19.
Cab Mounting Arrangement and Strength Requirements
 - 2.2.3
- 20.
Protection of the Occupants in the Event of a Lateral Collision
 - 2.2.4
- 21.
Installation requirements for Lighting & Signaling devices (except for the vertical orientation of the dipped beam)
 - 2.2.5
- 22.
Rear view mirror
 - 2.2.6
- 23.
Driver's Work Area
 - 2.2.7
- 24.
Door Locks & Hinges
 - 2.2.8
- 25.
Window
 - 2.2.9
- 26.
Wind Screen and Wind Screen Wiping System
 - 2.2.11
- 27.
Fire extinguishers
 - 2.2.12
- 28.
Cab and Body gap
 - 3.2.2
- 29.
Stowage Space/ Luggage Carrier
 - 3.2.3
- 30.
Mudguards/ Spray Suppression Devices
 - 3.2.4
- 31.
Protection of the Occupants of Goods-carrying Power-driven Vehicles against the Shifting of Loads
 - 3.4.1
- 32.
Retro-Reflective Markings for Heavy and Long Vehicles
 - 3.4.5

- 33.
Lateral Protective device
- 3.4.6
- 34.
Rear Under run Protective Device (RUPD)
- 3.4.7
- 35.
Internal Lighting
- 4.1.2
- 36.
Position of illumination devices
- 4.1.3
- 37.
Driver Cab lighting
- 4.2
- 38.
Electrical cables
- 4.3.1
- 39.
Fuse
- 4.3.2
- 40.
Terminals, Connectors and Elements
- 4.3.3
- 41.
Safety requirements
- 4.4
- 42.
Batteries
- 4.5
- 43.
Technical Provisions for Base Vehicles
- 5.3
- 44.
Manner of Display of Class Labels and Identification Marks
- 5.5
- Table II
- Sr. No.
- Nature of Test/ Parameters
- Requirements of Specific Clauses of AIS-093
(Rev.1)
- 1.
Categorization of Truck Load Bodies
- 3.1
- 2.
General Requirements
- 3.2
- 3.
Overall Dimensions
- 3.2.1
- 4.

Rope Hooks and other Provisions

3.2.5

5.

Working Stability

3.3.1

6.

Mounting of the Body or Load Platform of Commercial Vehicles

3.3.2

7.

Body Construction requirements

3.3.3

8.

Securing the Load on the Load body

3.4.2

9.

External Projection

3.4.3

10.

Installation requirements for Lighting & Signaling devices

(except for the vertical orientation of the dipped beam)

3.4.4

11.

External Lighting

4.1.1

12.

Type of Bulbs for lamp Assemblies

4.1.4

13.

Technical Provisions for Bodies

5.4

14.

Container Size Designations and Sizes Codes

6.4

15.

Recommendations for Stacking of Load

6.5

16.

Twist Locks

6.6

17.

Container securing arrangements

6.7

18.

Attaching Sub-frames and Bodies

6.8

19.

Tanker Mounting

6.9

20.

Stability Criteria

7.5

21.

Modification of the Vehicle Type and Extension of Approval

7.6

22.

Roll Over Stability/ Tilt Table Test Procedure

Annexure - 1

23.

Lateral Stability Calculation

Annexure - 2]

[Substituted by Notification No. G.S.R. 1034 (E) dated 2.11.2016 (w.e.f. 2.6.1989)]

(4)

[On and after expiry of six months from the date of commencement of the Central Motor Vehicles (14th Amendment) Rules, 2016, the testing and approval for body building of sleeper coaches shall be in accordance with AIS-119 (Rev.1): 2016, as amended from time to time, for vehicles mentioned therein, till the corresponding Bureau of Indian Standards specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

[Inserted by Notification No. G.S.R. 905 (E), dated 23.9.2016 (w.e.f. 2.6.1989).]

(5)

[On and after the expiry of six months from the date of commencement of the Central Motor Vehicles (Third Amendment) Rules, 2017, the testing and approval for body building of double decked buses shall be in accordance with AIS-139:2016, as amended from time to time, till the corresponding Bureau of Indian Standard specifications are notified under the Bureau of Indian Standards Act, 1986 (63 of 1986).]

[Inserted by Notification No. G.S.R. 240(E), dated 14.3.2017 (w.e.f. 2.6.1989).]

126.

[Prototype of every motor vehicle to be subject to test.

[Rule126 substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

- On and from the date of commencement of central Motor Vehicles (Amendment) Rules, 1993, every [manufacturer or importer] of motor vehicles [including trailers, semi-trailers and modular hydraulic trailer]

[Substituted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

shall submit the prototype of the vehicle [to be manufactured or imported by him]

[Substituted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

for test by the vehicle Research and Development Establishment of the Ministry of Defence of the Government of India or Automotive Research Association of India, Pune, [or the Central Farm Machinery Testing and Training Institute, Budni (MP).]

[Substituted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

or the Indian Institute of Petroleum, Dehradun, [or the Central Institute of Road Transport Pune, or the International Centre for Automotive Technology, Manesar]

[Added by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

,[or the Northern Region Farm Machinery Training and Testing Institute, Hissar (for testing of combine harvester)]

[Inserted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

[or the Global Automotive Research Centre, Chennai]

[Inserted by Notification No. G.S.R. 247(E), dated 15.3.2017 (w.e.f. 2.6.1989).]

and such other agencies as may be specified by the Central Government for granting a certificate by that agency as to the compliance of provisions of the Act and these rules:]

[Provided that the procedure for type approval of certification of motor vehicles for compliance to these rules shall be in accordance with the AIS: 017-2000, as amended from time to time]

[Inserted by GSR 400(E), dated 28.7.2000 (w.e.f. 2.6.1989).]

[and information on technical specifications shall be submitted by the vehicle manufacturer in accordance with AIS-007(Rev.5):2014.]

[Inserted by Notification No. G.S.R. 880(E), dated 14.9.2016 (w.e.f. 2.6.1989).]

[Provided further that in respect to the vehicles imported into India as completely built units (CBU), the importer shall submit a vehicle of that particular model and type to the testing agencies for granting a certificate by that agency as to

the compliance to the provisions of the Act and these rules.]

[Inserted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

[Provided also that prototype of bus bodies and truck bodies may be submitted for testing and type approval to engineering colleges specified by the State Government or the State Road Transport Undertakings duly approved by the State Government.]

[Inserted by Notification No. G.S.R. 247(E), dated 15.3.2017 (w.e.f. 2.6.1989).]

126A.

[

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

The testing agencies referred to in rule 126 shall, in accordance with the procedures laid down by the Central Government, also conduct tests on vehicles drawn from the production line of the manufacturer to verify whether these vehicles conform to the provisions of [rules made under section 110 of the Act:]

[Provided that in case the number of vehicles sold in India for a given base model and its variants(manufactured in India or imported to India) are less than 250 in any consecutive period of six months in a year, then such base model and its variants need not be subjected to the above test, if at least one model or its variants manufactured or imported by that manufacturer or importer, as the case may be, is subjected to such tests at least once in a year:

Provided further that,in case the number of base models and its variants manufactured/imported is more than one and if the individual base model and its variants are less than 250 in any consecutive period of six months in a year, then the testing agencies can pick up one of the vehicles out of such models and their variants once in a year for carrying out such test.]

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

[[126-B. Prototype of every construction equipment vehicle and combine harvester to be subject to test.]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

(1)

On and from the date of commencement of the Central Motor Vehicles (Sixth Amendment) Rules,2000, every manufacturer of construction equipment vehicle shall submit the prototype of the construction equipment vehicle to be manufactured by him for test by any of the agencies referred to in rule 126 for granting a certificate by that agency as to the compliance of provisions of the Act and these rules.

(1A)

[On and from the date of commencement of Central Motor Vehicle (Fourth Amendment) Rules, 2015, every manufacturer of combine harvester shall submit the prototype of the combine harvester to be manufactured by him for test by any of the agencies referred to in rule 126 for granting a certificate by that agency as to the compliance of the provisions of the Act and these rules.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

(2)

The testing agencies referred to in rule 126 shall in accordance with the procedure laid down by the Central Government conduct tests on vehicles drawn from the production line of the manufacturer to verify whether the vehicles conform to the provisions of the Act, or rules or orders issued thereunder shall be renumbered as sub-rule (1)thereof and after sub-rule (1) as so, renumbered:]

[Provided that the provisions of this sub-rule shall not be applicable in respect of any construction equipment up to and including [26th August, 2002]

[Inserted by GSR 675(E), dated 17.9.2001 (w.e.f. 17.9.2001).]

.]

(2A)

[The testing agencies referred to in rule 126 shall, in accordance with the procedure laid down by the Central Government, conduct tests on combine harvesters drawn from the production line of the manufacturer to verify whether the combine harvesters conform to the provisions of the Act, or rules, or orders issued there under:

Provided that the provisions of this sub-rule shall not be applicable in respect of any combine harvester up to and including the 1st day of April, 2015.]

[Inserted by Notification No. G.S.R. 212 (E) dated 20.3.2015 (w.e.f. 1.4.2015)]

127.

Quality certificate by manufacturer.

- [(1)]

[Rule 127 renumbered as sub-Rule (1) thereof by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

On and from the [date]

[1st day of April, 1991 vide Section O.941(E), dated 11th December, 1990.]

of commencement of this rule, the sale of every motor vehicle manufactured shall be accompanied by a certificate of road-worthiness issued by the manufacturer in Form 22.

(1A)

[On and from the date of commencement of the Central Motor Vehicles (Amendment) Rules, 2015, the sale of every E-rickshaw or E-cart manufactured shall be accompanied by a certificate of road worthiness issued by the E-rickshaw or E-cart manufacturer or the registered E-rickshaw or E-cart Association, in Form 22.]

[Inserted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

(2)

[On and from the date of commencement of the Central Motor Vehicles (Sixth Amendment) Rules, 2000, the sale of every construction equipment vehicle manufactured shall be accompanied by a certificate of road-worthiness issued by the manufacturer in Form 22.]

[Inserted by GSR 642(E), dated 28.7.2000 (w.e.f. 28.7.2000).]

Special provisions

128.

Tourist vehicles other than motor cabs, etc.

- A tourist vehicle other than motor cab, taxicab, campers van house trailer, shall conform to the following specifications, namely:

(1)

[The dimension shall conform to the dimensions specified in rule 93.]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

(2)

Structure. Structure of the tourist vehicle should be sturdy and strong structural frame work using suitable material of adequate sectional area and an aerodynamical shape. For exterior panelling, aluminium sheet or good quality panelling material should be used. As regards interior panelling it should cover the entire interior roof, sides, back and bulk head portions. The body should be made completely leak proof and dustproof. The vehicle should also be rattle proof. Sound deadening should also be done for all panelling including the floor.

(3)

[Passenger entrance and exit. The passenger entrance-cum-exit door shall be located on the left side of the vehicle and minimum door width shall be 685 millimetres. The door handle should be capable of being handled from inside as well as from outside. The door may be operated pneumatically or hydraulically or electrically with suitable locking devices.]

[Sub-Rule (3) substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(4)

[Emergency exit. The emergency exit provided on the tourist vehicle shall meet the following requirements, namely:

(i)

be clearly marked Emergency Exit in bold letters on the inside and the outside of the tourist vehicle;

(ii)

be so designed as to open from inside and the outside of the tourist vehicle;

(iii)

be equipped with a fastening device which can be quickly released but so designed as to offer protection against accidental release;

(iv)

be easily accessible to persons of normal height standing on the ground outside the vehicle;

(v)

be easily accessible to the passengers;

(vi)

be such that no seat or other object placed in the vehicle shall restrict the passage to the emergency door;

(vii)

be located either at the back or on to the right hand side of the vehicle; and

(viii)

emergency exist may be provided in the form of a window with breakable glass. In such cases, a suitable device shall be provided at a convenient place to break open the glass in the event of an emergency.]

(5)

Driver entry and exit. A separate door with suitable sliding window shall be provided for the driver near the driver seat.

(6)

Windscreen. (i) The front windscreen shall be of clear view and distortion free, with safety glass and shall be of full width of the tourist vehicle. If made in two halves, the width of the centre vertical joint, inclusive of the rubber glazing fitment of the front windshield shall be such as to enhance the elegance of the tourist vehicle.

(ii)

Rear windscreen shall be of safety glass or laminated safety glass. It shall match with the windows provided on the vehicle. Sliding curtains shall be provided on the rear windscreen.

(7)

Windows. Windows of tourist vehicles should have a minimum space of 14.25 millimetres and shall be of safety or laminated safety glass.

Windows shall be of double sliding type slider running smoothly in channels without rattle. All safety or laminated safety glasses used for windows should conform to standards laid down by the Bureau of Indian Standards. Windows shall be provided with sliding curtains.

(8)

Ventilation. Adequate arrangements shall be provided for ventilation for the passenger compartment as well as the driver compartment. All ventilators and windows shall be such that when closed they will not permit ingress of rain water or dust in the passenger or driver compartment.

(9)

Luggage. (i) Luggage holds shall be provided at the rear or at the sides, or both, of the tourist vehicle with sufficient space and size, and shall be rattle proof, dustproof and waterproof with safety arrangements;

(ii)

The light luggage racks, on strong brackets shall be provided inside the passenger compartment running along the sides of the tourist vehicle. Except where nylon netting is used, the under side of the rack shall have padded upholstery to protect the passengers from an accidental hit. The general design and fitment of the rack shall be so designed as to avoid sharp corners and edges.

(10)

Seats and seating arrangements. [* * *]

[Sub-Clause (i) omitted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

(ii)

Seating layout shall be [two and two or one and two or one and one]

[Substituted by GSR 933(E), dated 28.10.1989, for 'two and two'(w.e.f. 28.10.1989).]

on either side, all seats facing forward, with a clear gangway of at least 355 millimetres width at the centre. Each passenger seat shall have a minimum area of 447 millimetres × 457 millimetres and an arm rest on both sides and seat back of full height.

(iii)

The seat frames shall be sturdy, properly finished and so mounted as to transfer the weight directly to the structural members of frame-work. The seats shall be of reclining type and adjustable.

(iv)

The seats shall be so mounted as to provide at least 280 millimetres legroom from the front of the rear seat to the back of the front seat. A foot rest at suitable location and height shall be provided for every passenger.

(11)

Painting and finishing. The tourist vehicle shall be painted in a manner referred to in sub-rules (7) and (8) of rule [85]

[Substituted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

in white colour with a blue ribbon of five centimetres width at the centre of the exterior of the body.

(12)

Lighting.(i)(a) The passenger compartment shall be adequately illuminated.

(b)

Arrangement shall be provided to eliminate reflection of the light from the passenger compartment on the windscreen.

(c)

In addition to the lights in passenger compartment, at least two night-lights with coloured domes, shall be provided in the passenger compartment.

(ii)

Front and rear destination boxes, if provided, shall be illuminated.

(iii)

One independently operated light fitting shall be provided for illumination of the drivers or attendants seat area.

(iv)

A light fitting shall be provided for illuminating the steps at the passenger entrance door.

(v)

Each luggage hold shall have a light fitting for illumination of that hold.

(vi)

Wiring in the passenger compartment shall be with low tension cable conforming to IS: 2465 of size commensurate with the estimated current loading. The wires shall be carried in PVC sleeveings or conduit or casing of adequate size. When any wire passes through a hold in a panel or sheet metallic components, a rubber grommet of adequate size shall be provided for protection of the insulation.

(13)

Fittings and accessories.A tourist vehicle shall be equipped with the following, namely:

(i)

Convex rear view mirrors one on each side, universally adjustable and of adequate dimensions.

(ii)

First-aid box with glazed front, with necessary medicines for first-aid.

(iii)

Fire extinguisher, dry powder type located near the engine compartment.

(iv)

Insulation on interior or exterior of the engine bonnet for reducing the noise and heat from the engine.

(v)

Provision for locating vehicle tools securely.

(vi)

Heavy duty windscreen wiper system.

(vii)

Adjustable sun visors of adequate size for the driver and for the attendant.

(viii)

Electrically operated wide indicators or blinkers, stop lights and parking lights.

(ix)

Dual head lamps.

(x)

Suitable illumination for the registration number plate at the rear.

(xi)

Horn.

(xii)

Electric fans, of 8 inches* sweep adjustable, at least eight in number, suitably spaced in the passenger compartment and controlled by switches located near the seat.

(xiii)

Electric bell or buzzer located near the seat of driver or attendant and operated by at least four push button controls placed at suitable location in the passenger compartment.

(xiv)

Ash trays near passenger seats of a design convenient for cleaning them at intermediate stops of the tourist vehicle.

(xv)

Drinking water and ice-box.

(xvi)

Rack for magazines and other reading material.

(xvii)

Back pockets and numbers for each seat.

(xviii)

Public address system with at least four speakers suitably located in the passenger compartment.

(xix)

Document frame, located near the seat of driver, for carrying vehicle documents, tax token, license and permit.

(xx)

Mud flaps for front and rear wheels:

[Provided that the provisions of clauses (2) and (7), sub-clause (iv) of clause (12), sub-clauses (ix), (xii) and (xiii) of clause (13), of this rule shall not apply to the vehicles of integral construction.]

[Added by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

[Provided further that provisions of this rule shall not apply to tourist buses which comply with the provisions of AIS:52, AIS:119 or AIS:139.]

[Inserted by Notification No. G.S.R. 1462(E), dated 27.11.2017 (w.e.f. 2.6.1989).]

128A.

[Special provision for M3 category of vehicles.

[Rule 128A inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2007).]

- The provisions of sub-rule (4) of rule 128 shall apply to all M3 category of vehicles.]

[Sub-Rule(4) substituted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.9.2006).]

129.

Transportation of goods of dangerous or hazardous nature to human life.

(1)

Every owner of a goods carriage transporting any dangerous or hazardous goods shall, in addition to complying with the provisions of any law for the time being in force in relation to any category of dangerous or hazardous goods, comply with the following conditions, namely:

(i)

every such goods carriage, carrying the same type of dangerous or hazardous goods (whether in bulk or in packages), shall display a distinct mark of the class label appropriate to the type of dangerous or hazardous goods specified in column 3 of the Table I to rule 137;

(ii)

every package containing dangerous or hazardous goods shall display the distinct class labels appropriate to the type of dangerous or hazardous goods specified in column 3 of the Table I to rule 137;

(iii)

in the case of packages containing goods listed in Table III in rule 137 and which represents two hazards as given in column 2 thereof, such packages shall display distinct labels to indicate both the hazards;

(iv)

[every goods carriage carrying any dangerous or hazardous goods shall be equipped with safety equipments for preventing fire, explosion or escape of hazardous or dangerous goods.]

[Added by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(2)

[One year from the date of commencement of Central Motor Vehicles (Amendment) Rules, 1993, every goods carriage carrying goods of dangerous or hazardous nature to human life, shall be fitted with tachograph (an instrument to record the lapse of running time of the motor vehicle; time speed maintained, acceleration, deceleration, etc.) conforming to the specifications of the Bureau of Indian Standards.]

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[129-A. Spark arrester.

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

- Six months from the date of commencement of Central Motor Vehicles (Amendment) Rules, 1993, every goods carriage carrying goods of dangerous or hazardous nature to human life shall be fitted with a spark arrester.]

130.

Manner of display of class labels.

(1)

Where a class label is required to be displayed on a vehicle, it shall be so positioned that the size of the class label is at an angle of 45 degrees to the vertical and the size of such label shall not be of less than twenty-five millimetres square which maybe divided into two portions, the upper half portion being reserved for the pictorial symbol and the lower half for the text:

Provided that in the case of smaller packages a suitable size of the label may be adopted.

(2)

Where the class label consists of adhesive material, it shall be waterproof and where it consists of metal or other substance on which the pictorial symbol and the text are printed, painted or affixed, they shall be affixed directly on such material and in every case, the surface of the vehicle surrounding the label shall be of a colour that contrasts vividly with the background of the class label.

(3)

Every class label displayed on a vehicle shall be positioned in such a manner that it does not obscure other markings required to be displayed under any other law.

(4)

Every goods carriage carrying any dangerous or hazardous goods shall display the class label on the places shown in the Table in rule 134.

131.

[Responsibility of the consignor for safe transport of dangerous or hazardous goods.

[Rule 131 substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(1)

It shall be the responsibility of the consignor intending to transport any dangerous or hazardous goods listed in Table III, to ensure the following, namely:

(a)

the goods carriage has a valid registration to carry the said goods;

(b)

the vehicle is equipped with necessary first-aid, safety equipment and antidotes as may be necessary to contain any accident;

(c)

that the transporter or the owner of the goods carriage has full and adequate information about the dangerous or hazardous goods being transported; and

(d)

that the driver of the goods carriage is trained in handling the dangers posed during transport of such goods.

(2)

Every consignor shall supply to the owner of the goods carriage, full and adequate information about the dangerous or hazardous goods being transported as to enable such owner and its driver to,

(a)

comply with the requirements of rules 129 to 137 (both inclusive) of these rules; and

(b)

be aware of the risks created by such goods to health or safety of any person.

(3)

It shall be the duty of the consignor to ensure that the information is accurate and sufficient for the purpose of complying with the provisions of rules 129 to 137 (both inclusive) of these rules.]

132.

[Responsibility of the transporter or owner of goods carriage.

[Rule 132 substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(1)

It shall be the Responsibility of the owner of the goods carriage transporting any dangerous or hazardous goods to ensure the following, namely:

(a)

that the goods carriage has a valid registration to carry the said goods and the said carriage is safe for the transport of the said goods; and

(b)

the vehicle is equipped with necessary first-aid, safety equipment, tool box and antidotes as may be necessary to contain any accident.

(2)

Every owner of a goods carriage shall, before undertaking the transportation of dangerous or hazardous goods in his goods carriage, satisfy himself that the information given by the consignor is full and accurate in all respects and correspond to the classification of such goods specified in rule 137.

(3)

The owner of a goods carriage shall ensure that the driver of such carriage is given all the relevant information in writing as given in Annexure V of these rules in relation to the dangerous or hazardous goods entrusted to him for transport and satisfy himself that such driver has sufficient understanding of the nature of such goods and the nature of the risks involved in the transport of such goods and is capable of taking appropriate action in case of an emergency.

(4)

The owner of the goods carriage carrying dangerous or hazardous goods, and the consignor of such goods shall lay down the route for each trip which the driver shall be bound to take unless directed or permitted otherwise by the Police Authorities. They shall also fix a time table for each trip to the destination and back with reference to the route so laid down.

(5)

It shall be the duty of the owner to ensure that the driver of the goods carriage carrying dangerous or hazardous goods holds a driving license as per provisions of rule 9 of these rules.

(6)

Notwithstanding anything contained in rules 131 and 132, it shall be sufficient compliance of the provisions of these rules if the consignor transporting dangerous or hazardous goods and the owner of the goods carriage or the transporter, abides by these conditions within six months after the date of coming into force of the Central Motor Vehicles (Amendment) Rules, 1993.]

133.

[Responsibility of the driver.

[Rule 133 substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(1)

The driver of a goods carriage transporting dangerous or hazardous goods shall ensure that the information given to him in writing under sub-rule (3) of rule 132 is kept in the drivers cabin and is available at all time while the dangerous or hazardous goods to which it relates, are being transported.

(2)

Every driver of a goods carriage transporting any dangerous or hazardous goods shall observe at all times all the directions necessary for preventing fire, explosion or escape of dangerous or hazardous goods carried by him while the goods carriage is in motion, and when it is not being driven he shall ensure that the goods carriage is parked in a place which is safe from fire, explosion and any other risk, and at all times the vehicle remains under the control and supervision of the driver or some other competent person above the age of 18 years.]

134.

Emergency information panel.

(1)

Every goods carriage used for transporting any dangerous or hazardous goods shall be legibly and conspicuously marked with an emergency information panel in each of the three places indicated in the Table below so that the emergency information panel faces to each side of the carriage and to its rear and such panel shall contain the following information, namely:

- (i)
the correct technical name of the dangerous or hazardous goods in letters not less than 50 millimetres high;
- (ii)
the United Nations class number for the dangerous or hazardous goods as given in Column 1, Table 1 appended with rule 137, in numerals not less than 100 millimetres high;
- (iii)
the class label of the dangerous or hazardous goods of the size of not less than 250 millimetres square;
- (iv)
the name and telephone number of the emergency services to be contacted in the event of fire or any other accident in letters and numerals that are not less than 50 millimetres high and the name and telephone number of the consignor of the dangerous or hazardous goods or of some other person from whom expert information and advice can be obtained concerning the measures that should be taken in the event of an emergency involving such goods.

(2)
[The information contained in sub-rule (1) shall also be displayed on the vehicle by means of a sticker relating to the particular dangerous or hazardous goods carried in that particular trip.]

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(3)
[
[Sub-Rule(2) renumbered as sub-Rule(3) by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]
Every class label and emergency information panel shall be marked on the goods carriage and shall be kept free and clean from obstructions at all times.

135.

Driver to be instructed.

- The owner of every goods carriage transporting dangerous or hazardous goods shall ensure to the satisfaction of the consignor that the driver of the goods carriage has received adequate instructions and training to enable him to understand the nature of the goods being transported, by him, the nature of the risks arising out of such goods, precautions he should take while the goods carriage is in motion or stationary and the action he has to take in case of any emergency.

136.

[Driver to report to the police station about accident.

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

- The driver of a goods carriage transporting any dangerous or hazardous goods shall, on the occurrence of an accident involving any dangerous or hazardous goods transported by this carriage, report forthwith to the nearest police station and also inform the owner of the goods carriage or the transporter regarding the accident.]

137.

Class labels.

- In respect of the dangerous or hazardous goods specified in column (2) of the Table below, the labels specified in the corresponding entry in column (3) shall be the class labels, namely:

Table

I
Class
of Labels
UN
Class No.
Classification
of goods
Class
labels

(1)

(2)

(3)

1.

Explosive

Symbol

(exploding bomb) Background

:

Black

:

Orange

2.

Gases, compressed, liquefied, dissolved under pressure or deeply refrigerated.

2.1

Non-flammable gases

Symbol

(gas cylinder) Background

:

Black or White

:

Green

2.2

Inflammable gases

Symbol

(Flame) Background

:

Black or White

:

Red

2.3

Poison (toxic) gases

Symbol

(skull and crossbones)

Background

:

Black

:

White

3.

Inflammable Liquids

Symbol

(flame)

Background

:

Black or White

:

Red

4.

Inflammable solids, substance liable to spontaneous combustion; substances which, on contact with water, emit inflammable gases.

4.1

Inflammable solids

Symbol

(flame)

Background

:

Black or white

:

Red

4.2

Substances liable to spontaneous combustion

Symbol

(flame)

Background

:

Black

:

Upper half white

and

lower half red

4.3

Substances which, on contact with water, emit inflammable gases

Symbol

(flame)

Background

:

Black or White

:

Blue

5.

Oxidizing substances and organic peroxides.

5.1

Oxidizing substances

Symbol

(flame over circle)

Background

:

Black

:

Yellow

5.2

Organic peroxides

Symbol

(flame over circle)

Background

:

Black

:

Yellow

6.

Poisonous (toxic) substances and infectious substances.

6.1

Poisonous (toxic) substances

Symbol

(skull and crossbones)

Background

:

Black

:

White

6.2

Harmful substances

The

bottom half of the label should bear the inscription : Harmful :

Stow away from food-stuffs

Symbol

(St. Andrew's cross over and ear of wheat)

:

Background

:

White

6.3

Infectious substances

The

bottom half of the label should bear: Infectious substances

(optional) and the inscription ? In the case of damage or

leakage immediately notify Public Health Authority (optional)

Symbol

(three crescents superimposed on a circle) and inscription

Background

:

Black

:

Right

7.

Radioactive substances

Symbol-3

segments of a circle ? a number and lettering of the class

label) shall be black on a white background and the parallel

lines bordering the class label shall be black and shall be 5mm
thick

8.

Corrosives

Symbol

(liquids spilling from two glass vessels and attaching a hand and
a metal) : Black Lower half black with white border

[TABLE II]

[Substituted by G.S.R. 349(E), dated 1.6.2005, for Table II (w.e.f. 1.6.2005).]

Indicative criteria

(A)

Explosives:

An explosive means a solid or liquid or pyrotechnic substance (or a mixture of substances) or an article,

(i)

which is in itself capable by chemical reaction of production of gas at such a temperature and as such a speed as to
cause damage to the surroundings;

(ii)

which is designed to produce an effect, by heat, light, sound, gas or smoke or a combination of these, of non-detonative self-sustaining exothermic chemical reaction.

(B)

Gas:

(1)

A gas is a substance which

(i)

at 50°C has a vapour pressure greater than 300 kPa; or

(ii)

is completely gaseous at 20°C at a standard pressure of 101.3 kPa.

(2)

Substances of gas are assigned to one of three following divisions based on the primary hazard of the gas during transport;

(a)

Flammable gases:

Gases which at 20°C and a standard pressure of 101.3 kPa,

(i)

are ignitable when a mixture of 13 per cent or less by volume with air; c..

(ii)

have a flammable range with air of at least 12 percentage point, regardless of the lower flammable limit. Flammability shall be determined by tests or by calculation in accordance with methods adopted by International Standards Organisation [ISO: 10156: 1996] or by Bureau of Indian Standards [IS: 1446-1985]-

(b)

Non flammable, non-toxic gases:

Gases which are transported a pressure not less than 280 kPa at 20°C, or as refrigerated liquids and which,

(i)

are asphyxiant-gases which dilute or replace the oxygen normally in the atmosphere;

(ii)

are oxidizing-gases which may, generally by providing oxygen, cause or contribute to the combustion of other material more than air does; or

(iii)

do not come under the other divisions;

(c)

Toxic gases:

Gases which are known to be so toxic or corrosive to humans as to pose a hazard to health.

Note.-Gases meeting the above criteria owing to their corrosivity are classified as toxic with a subsidiary corrosive risk.

(C)

Flammable chemicals:

(i)

Flammable gases.-Gases which at 20°C and at standard pressure of 101.3 kPa are:

(a)

ignitable when a mixture of 13 per cent or less by volume with air, or

(b)

have a flammable range with air of at least 12 percentage points regardless of the lower flammable limits.

Note.-The flammability shall be determined by tests or by calculation in accordance with methods adopted by International Standards Organisation (ISO: 10156: 1996) or by Bureau of Indian Standards (IS: 1446-1985).

(ii)

Extremely flammable liquids.-Chemicals which have flash point lower than or equal to 23°C and boiling point less than 35°C.

(iii)

Very high/flammable liquids.-Chemicals which have a flash point lower than or equal to 23°C and initial boiling point

higher than 35°C.

(iv)

Highly flammable liquids.-Chemicals with a flash point lower than or equal to 60°C but higher than 23°C.

(v)

Flammable liquids.-Chemicals which have a flash point higher than 60°C: but lower than 90°C.

(D)

Reactive Substances:

Reactive substances are those substances which start reacting chemically with any other material and reducing gases through their own decomposition. Such substances are Inorganic Alkalies (for example NaOH, Iodine and the like) and Acids (for example H₂SO₄, HNO₃, HCl and the like)

(E)

Oxidizing Substances:

(a)

Oxidizing substances:Substances which, while in themselves not necessarily combustible, may generally by yielding oxygen, cause or contribute to the combustion of other material. Such substances maybe contained in an article;

(b)

Organic peroxides:Organic substances which contain the bivalent-O-O- structure and may be considered derivative of hydrogen peroxide, where one or both of the hydrogen atoms have been replaced by organic radicals. Organic peroxides are thermally unstable substances which may undergo exothermic self-accelerating decomposition. In addition, they may have one or more of the following properties,

(i)

be liable to explosive decomposition;

(ii)

burn rapidly;

(iii)

be sensitive to impact or friction;

(iv)

react dangerously with other substances;

(v)

cause damage to the eyes.

(F)

Toxic:

Toxic chemicals:-Chemical having the following values of acute toxicity and which owing to their physical and chemical properties, are capable of producing major accident hazards:

Sl.No.

Toxicity

Oral toxicity (mg/kg)

Dermal toxicity (mg/kg).

Inhalation toxicity (mg/l)

1

Extremely toxic

>5

<40

<0.5

2.

Highly toxic

>5-50

>40-200

<05-2.0

3.

Toxic.

>50-200.

>200-1000.

>2-10

1. LD50 oral in rats

2. LD50 coetaneous in rats or rabbits

3. LC50 by inhalation (four hours) in rats.

(G)

Radioactive:

Radioactive materials mean any material containing radionuclide where both the activity concentration and the total activity in the consignment exceed the values specified, depending on the type of material by the Atomic Energy Commission of India.

(H)

Corrosive:

Corrosive substances are substances which by chemical action will cause severe damage when in contact with living tissue or in the case of leakage will materially damage or even destroy other goods or the means of transport. They may also cause other hazards.

]

[TABLE III]

[Substituted by G.S.R. 349(E), dated 1.6.2005, for Table III (w.e.f. 1.6.2005).]

List of Hazardous Goods

E ? Explosive,

F ? Flammable,

O ? Oxidising,

R ? Reactive,

C ? Corrosive,

Ra ? Radioactive,

T ? Toxic,

G - Gas

Sr. No.

Name

E

F

O

R

C

Ra

T

G

1.

1 Hexene

E

F

2.

1Methylpiperidine

F

3.

1, I-Difluoroethylene (Refrigerated GasR 1132a)

G

4.

1,

2-Dichloro- 1, 1, 2, 2-Tetrafluoroethane(Refrigerated Gas R 114)

G

5.

1, 1,

1, 2-Tetrafluoroethane (Refrigerant GasR 134a)

G

6.

1, 1,

1 -Trifluoroethane (Refrigerant Gas R 143a)

G

7.

1, 1; Trichloroethane

T

8.

1, 1

-Dichloro-l-Nitroethane

T

9.

1,

1-Dichloroethane

F

10.

1,1-Difluoroethane

G

11.

1,1-Dimethoxyethane

F

12.

1, 2,

3, 6-Tetrahydrobenzaldehyde

F

13.

1, 2,

3, 6-Tetrahydropyridine

F

14.

1,

2-Butylene Oxide, Stabilized

F

15.

1,

2-Di-(Dimethylamino) Ethane

F

16.

1,

2-Dibromobutan 3-one

T

17.

1,

2-Dichloroethylene

F

18.

1,
2-Dichloropropane
F
19.
1,
2-Dimethoxyethane
F
20.
1,
2-Epoxy-3-Ethoxypropane
F
21.
1,
2-Propylenediamine
C
22
1, 3,
5-Trimethylbenzene
F
23
1,
3-Dichloroacetone
T
24
1,
3-Dichloropropanol-2
T
25
1,
3-Dimethylbutylamine
F
26
1,
4-Butynediol
T
27
1, 5,
9-Cyclododecatriene
T
28
1-Bromo-3-chloropropane
T
29
1-Bromo-3-Methylbutane
F
30
1-Chloro-1,1-Difluoroethane(Refrigerant Gas R 142b)
G
31
1-Chloro-2,
2, 2-Trifluoroethane(Refrigerant Gas R 133a)

G

32

1-Ethylpiperidine

F

33

1-Methoxy-2-Propanol

F

34

1-Pentol

C

35

2-(2-Aminoethoxy) Ethanol

C

36

2,

2-Dimethylpropane

G

37

2,

4-Toluylenediamine

T

38

2,

2'-Dichlorodiethyl Ether

T

39

2,3 Dihydropyran

F

40

2,3-Dimethylbutane

F

41

2-Amino-4,

6-Dinitrophenol Wetted

F

42

2-Amino-4-Chlorophenol

T

43

2-Amino-5-Diethylaminopentane

T

44

2-Bromo-2-Nitropropane-1,

3-Diol

F

45

2-Bromoethyl Ethyl Ether

F

46

2-Bromopentane

F

47

2-Chloroethanal

T

48

2-Chloropropane

F

49

2-Chloropropene

F

50

2-Chloropropionic Acid, Solid

T

51

2-Chloropropionic Acid, Solution

C

52

2-Chloropyridine

T

53

2-Diethylaminoethanol

C

54

2-Dimethylaminoacetonitrile

F

55

2-Dimethylaminoethanol

C

56

2-Dimethylaminoethyl Acrylate

T

57

2-Dimethylaminoethyl Methacrylate

T

58

2-Ethylaniline

T

59

2-Ethylbutanol

F

60

2-Ethylbutyraldehyde

F

61

2-Ethylhexyl Chloroformate

T

62

2-Ethylhexylamine

F

63

2-Iodobutane

F

64

2-Methyl-1-Butene

F

65

2-Methyl-2-Butene

F

66

2-Methyl-2-Heptanethios

T

67

2-Methyl-5-Ethylpyridine

T

68

2-Methylfuran

F

69

2-Methylpentan-2-OL

F

70

2-Trifluoromethylaniline

T

71

3, 3-Diethoxypropene

F

|

||-

72

3,

3'-Iminodipropylamine

C

73

3-Bromopropyne

F

74

3-Chloro-4-Methylphenyl Isocyanate

T

75

3-Chloropropanol-1

T

76

3-Methyl-1-Butene

F

77

3-Methylbutan-2-One

F

78

3-Nitro-4-Chlorobenzotrifluoride

C

79

3-Trifluoromethylaniline

T

80

4 Methoxy-4-Methylpentan 2-one

F

81

4,

4'-Diaminodiphenylmethane

T

82

4-Chloro-o-Toluidine Hydrochloride

T

83

4-Methylmorpholine

(N-Methylmorpholine)

F

84

4-Thiapentanal

T

85

5-Methylhexan-2-one

F

86

5-Nitrobenzotriazol

E

87

5-tert-Butyl-2,

4, 6-Trinitro-m-Xylene(Musk Xylene)

F

88

9-Phosphabicyclononanes

(CyclooctadienePhosphines

F

89

Acetaldehyde

F

T

90

Acetaldehyde Ammonia

T

91

Acetic Acid

C

92

Acetic Acid Solution

C

93

Acetic Acid, Glacial or Acetic Acid Solution

C

94

Acetic Anhydride

C

95

Acetic Cyanothyrin

T

96

Acetone

F

97

Acetone Cyanohydrin

T

98

Acetone Cyanohydrine (2-Cyanopropan-2-OL)

T

99

Acetone Oils

F

100

Acetone Thiosemicarbazide

T

101

Acetonitrile

F

T

102

Acetyl Bromide

C

103

Acetyl Chloride

F

C

T

104

Acetyl Iodide

C

105

Acetyl Methyl Carbinol

F

106

Acetylene

T

G

107

Acetylene

(Ethyne)

F

108

Acetylene Tetra Chloride

T

109

Acridine

T

110

Acrolein

(2-Propenal)

F

T

111

Acrolein Dimer, Stabilized

F

112

Acrylamide

T

113

Acrylic Acid, Stabilized

C

114

Acrylonitrile

F

T

115

Adiponitrile

T

116

Aerosols

G.

117

Aircraft Hydraylic Power Unit Fuel Tank

F

118

Alcoholates Solution, N.O.S.

F

119

Alcoholic Beverages

F

120

Alcohols, Flammable, Toxic, N.O.S.

F

121

Alcohols, N.O.S.

F

122

Aldehydes, Flammable, Toxic, N.O.S.

F

123

Aldehydes, N.O.S.

F

124

Aldicarb

T

125

Aldol

T

126

Alkali Metal Alloy, Liquid, N.O.S.

F

127

Alkali Metal Amalgam

F

128

Alkali Metal Amides

F

129

Alkali Metal Dispersion or AlkalineEarth Metal Dispersion

F

130

Alkaline Earth Metal Alcoholates, N.O.S.

F

131

Alkaline Earth Metal Amalgam

F

132

Alkaline Metal Alcoholates, Self-I-leating,Corrosive, N.O.S.

F

133

Alkaloids, Liquid, N.O.S. or AlkaloidSalts, Liquid, N.O.S.

T

134

Alkyl Phthalate

C

135

Alkylphenols, Liquid, N.O.S.

C

136

Alkylphenols, Solid, N.O.S.

C

137

Alkylsulphuric Acids

C

138

Alkysulphonic Acids, LiquidArkysulphonic Acids, Liquid

C

139

Alkylsulphonic Acids, Liquid or ArylsulphonicAcids, Liquid

C

140

Alkysulphonic Acids, Solid or ArylsulphonicAcids, Solid

C

141

Allyl Alcohol

F

T

142

Allyl Alcohol (2-Propen-I-OL)

F

T

143

Allyl Amine

T

144

Allyl Bromide

F

T

145

Allyl Chloride

F

T

146

Allyl Chloroformate

T

147

Allyl]

Glycidyl Ether

F

148

Allyl Iodide

F

149

Allylamine

T

150

Allyltrichlorosilane, Stabilized

C

151

Alpha Naphthyl Thiourea

C

152

Alpha-Methylbenzyl Alcohol

T

153

Alpha-Methylvaleraldehyde

F

154

Alpha-Naphthylamine

T

155

Alpha-Pinene

F

156

Aluminium

(Powder)

T

157

Aluminium Alkyl Haldies, Liquid/Solid

F

158

Aluminium Alkyl Hydrides

F

159

Aluminium Alkyls

F

160

Aluminium Azide

F

T

161

Aluminium Borohydride

F

T

162

Aluminium Bromide Solution

C.

163

Aluminium Bromide, Anhydrous

C

164

Aluminium Carbide

F

T

165

Aluminium Chloride

C

166

Aluminium Chloride Solution

C

167

Aluminium Chloride, Anhydrous

C

168

Aluminium Fluoride

C

169

Aluminium Hydride

F

170

Aluminium Nitrate

O

171

Aluminium Phosphide

F

172

Aluminium Phosphide Pesticide

T

173

Aluminium Resinate

F

174

Aluminium Smelting By-Products or Aluminium Remelting By-Products

F

175

Amines, Flammable, Corrosive, FlammableN.O.S. Polyamines, Liquid, Corrosive, Flammable,N.O.S.

C

176

Amines, Flammable, Corrosive, N.O.S. orPolyamines, Flammable, Corrosive, N.O.S.

F

177

Amines, Liquid, Corrosive, N.O.S. orPolyamines, Flammable, Liquid, Corrosive, N.O.S.

C

178

Amines, Solid, Corrosive, N.O.S. orPolyamines, Solid, Corrosive, N.O.S.

C

179

Amino Diphenyl

T

180

Amino Pyridine

T

181

Aminodiphenyl,

-4

T

182

Aminophenol-2

T

183

Aminophenols

(o-, m-, p-)

T

184

Aminopyridines

T

185

Aminopterin

T

186

Amiton

T

187

Amiton Dialate

T

188

Ammonia

T

189

Ammonia Solution

T

G

190

Ammonium Arsenate

T

191

Ammonium Chloro Platinate

T

192

Ammonium Dichromate

O

193

Ammonium Dinitro-o-Cresolate

T

194

Ammonium Fluoride

T

195

Ammonium Fluorosilicate

T

196

Ammonium Hydrogen difluoride Solution

C

197

Ammonium Hydrogen difluoride, Solid

C

198

Ammonium Metavanadate

T

199

Ammonium Nitrate Fertilizer

O

200

Ammonium Nitrate Fertilizer, N.O.S.

O

201

Ammonium Nitrate Fertilizers

O

202

Ammonium Nitrate, Liquid

O

203

Ammonium Nitrates

O

R

204

Ammonium Nitrates in Fertilizers

O

R

205

Ammonium Perchlorate

O

206

Ammonium Persulphate

O

207

Ammonium Picrate

E

Ra

208

Ammonium Picrate, Wetted

F

209

Ammonium Polysulphide Solution

C

210

Ammonium Polyvanadate

T

211

Ammonium Sulfamate

T

212

Ammonium Sulphide Solution

C

213

Ammunition, Tear-Producing, Non-Explosive

T

214

Ammunition, Toxic, Non-Explosive

T

215

Ammonium Hydrogen Sulphate

C

216

Amyl Acetates

F

T

217

Amyl Acid Phosphate

C

218

Amyl Butyrates

F

219

Amyl Formates

F

220

Amyl Nitrate

F

221

Amylamine

F

222

Amyltrichlorosilane

C

223

Anabesine

T

224

Aniline

T

225

Aniline 2,4, 6-Trimethyl

T

226

Aniline Hydrochloride

T

227

Anisidine-P

T

228

Anisidines

T

229

Anisole

F

230

Anisoyl Chloride

C

231

Anthraquinone

T

232

Anthrawuinone

T

233

Antimony and Compounds

C

T

234

Antimony Hydride (Stibine)

F

T

235

Arasenous Trichloride

T

236

Argon, Refrigerated Liquid

G

237

Arsenic and All Arsenic Compounds in any Form

T

238

Arsenic Hydride (Arsene)

T

239

Arsenic Pentoxide, Arsenic (V) Acid and Salts

T

240

Arsenic Trioxide, Arsenious (III) Acids and Salts

T

241

Asbestos

T

242

Aviation Regulated Liquid, N.O.S./Solids, N.O.S.

E

F

243

Azinphos-Ethyl

T

244

Azinphos Methyl

T

245

Azoidic Arbonamide

F

||

246

Barium Azide

E

247

Barium Bromate

O

||

248

Barium Chlorate

O

249

Barium Cyanide

T

250

Barium Hypochlorite

O

251

Barium Nitrate

C

252

Barium Nitride

C

253

Barium Oxide

T

254

Barium Perchlorate

O

255

Barium Permanganate

O

256

Barium Peroxide

O

257

Batteries Fluid, Alkali

C

258

Batteries Wet, Filled with Acid

C

259

Batteries Wet, Filled with Alkali

C

260

Batteries Wet, Non-Spillable

C

261

Batteries, containing Sodium, or Cells,containing Sodium

F

262

Batteries, Dry, containing PotassiumHydroxide Solid

C

263

Benxoyl Peroxide

O

264

Benzal Chloride

O

265

Benzaldehyde

O

266

Benzenamine,
3-Trifluoromethyl

C

267

Benzene

F

T

268

Benzene Arsenic Acid

T

269

Benzene Chloride

T

270

Benzene Sulfonyl Chloride

T

271

Benzene,
1-(Chloromethyl)-4 Nitro

T

272

Benzene,

1-(Chloromethyl) 4-Nitro

T

273

Benzenesulphonyl Chloride

F

C

274

Benzidine

T

275

Benzidine Salts

T

276

Benzimidazole,

4, 5-Dichloro-2(Trifluoromethyl)

T

277

Benzonitrile

T

278

Benzoquinone

T

279

Benzoquinone-P

T

280

Benzotrichloride

C

281

Benzoyl Chloride

C

282

Benzoyl Peroxide

E

T

283

Benzyl Bromide

T

284

Benzyl Chloride

T

285

Benzyl Chloroformate

C

286

Benzyl Cyanide

T

287

Benzyl Iodide

T

288

Benzyl dimethylamine

C

289

Benzylidene Chloride

T

290

Beryllium

(Powder)

T

291

Beryllium

(Powders, Compounds)

T

292

Beryllium Compound, N.O.S.

T

293

Beryllium Nitrate

O

294

Beryllium Powder

T

295

Bibrydiliium Pesticide Solid, Toxic

T

296

Bibrydiliium Pesticide, Liquid, Flammable, Toxic

F

297

Bicyclo

(2,2,1) Heptane-2-Carbonitrile

T

298

Bicylco

(2.2.1) Hepta-2, 5-Diene, Stabilized(2, 5-Norbornadiene, Stabilized)

F

299

Biphenyl

T

300

Bipyridiliium Pesticide, Liquid, Toxic

T

301

Bipyridiliium Pesticide, Liquid, Toxic, Flammable

T

302

BIS

(2,4, 6-Trinitrophenylamine)

C
303
BIS
(2, 4, 6-Trinitrophenyl) Amine
E
T
304
BIS
(2-Chloromethyl) Sulphide
T
305
BIS
(2-Chloromethyl) Ketone
T
306
BIS
(Chloromethyl) Ether
T
307
BIS
(Chloromethyl) Ketone
T
308
BIS
(Terbutylperoxy) Butane
F
T
309
BIS
(Tert-Butyl Peroxy) Cyclohexane
C
T
310
BIS
(Tert-Butylperoxy Butane, -2,2)
C
T
311
BIS
(Tert-Butylperoxy) Cyclohexane, 1, 1
C
T
312
BIS
(Tert-Butylperoxy) Cyclohexane-1,1
R
313
BIS
(Teri-Butylperoxy, Butane, 2, -2)
R
314

BIS,
1, 2 Tribromophenoxy-Ethane
T
315
Bismuth
& Compounds
Ra
T
316
Bisphenol
T
317
Bi sulphates, Aqueous Solution
C
318
Bisulphites, Aqueous Solution, N.O.S.
C
319
Bitoscanate
O
|
320
Blue Asbestos or Brown Asbestos
T
321
Bombs, Smoke, Non-Explosive
C
322
Boron and Compounds
T
323
Boron Powder
T
324
Boron Tribyomide
C
325
Boron Trichoride
G
326
Boron Trifluoride
T
327
Boron Trifluoride Acetic Acid Complex
C
328
Boron Trifluoride Comp. with Methyl-Ether 1:1
T
329
Boron Trifluoride Diethyl Etherate
C

330

Boron Trifluoride Dihydrate

C

331

Boron Trifluoride Dimethyl Etherate

F

332

Boron Trifluoride Propionic Acid Complex

C

333'

Boron Trifluoride, Compressed

G

334

Boron Trichloride

T

335

Bromates, Inorganic, Aqueous Solution, N.O.S.

O

336

Bromates, Inorganic, N.O.S.

O

337

Bromine

T

338

Bromine Chloride

G

339

Bromine or Bromine Solution

C

340

Bromine Pentafluoride

O

341

Bromine Trifluoride

O

342

Bromo Chloro Methane

C

343

Bromoacetic acid

C

344

Bromoacetyl Bromide

C

345

Bromobenzene

F

C

346

Bromobenzyl Cyanides, Liquid/Solid

T
347
Bromochloromethane
T
348
Bromoform
T
349
Bromomethylpropanes
F
350
Bromopropanes
F
351
Bromotrifluoroethylene
G
352
Bromotrifluoromethane
G
353
Butadiene
T
354
Butadiene-1,
3
R
T
355
Butadienes, Stabilized
G
356
Butane
G
357
Butanedione
F
358
Butanone-2
R
T
359
Butoxy Ethanol
T
360
Butyl Acid Phosphate
C
361
Butyl Acrylates, Stabilized
F
362
Butyl Alcohol

F
R
363
Butyl Glycidal Ether
T
364
Butyl Mercaptan
F
365
Butyl Methyl Ether
F
366
Butyl Nitrites
F
367
Butyl Peroxy Isolpropyl Carbonate, Tert
R
368
Butyl Peroxyacetate, Tert
R
369
Butyl Peroxyisobutyrate, Tert
R
370
Butyl Peroxymaleate, Tert
R
371
Butyl Peroxymaleme Tert
O
372
Butyl Peroxypivalate Tert
C
373
Butyl Propionates
F
374
Butyl Vinyl Ether
C
375
Butyl Vinyl Ether, Stabilized
F
376
Butylamine
R
C
377
Butylbenzenes
F
378
Butylene
G

379

Butylglycidal Ether

T

380

Butyl-N-Mercaptan

T

381

Butyltoluenes

T

382

Butyltrichlorosilane

C

383

Butyraldoxime

F

384

Butyric Acid

C

385

Butyric Anhydride

C

386

Butyronitrile

F

387

Butyryl Chloride

F

388

C. I.

Basic Green

T

389

C9 Aromatic Hydrocarbon Fraction

T

390

Cadmium and Compounds

T

391

Cadmium Carbide

T

392

Cadmium Compound

T

393

Cadmium Cyanide

T

394

Cadmium Oxide

O

395

Cadmium Oxide (Fumes)

T
396
Cadmium Stearate
T
397
Caesium Hydroxide
C
398
Caesium Nitrate
O
399
Calcium Arsenate
T
400
Calcium Carbide
F
401
Calcium Chlorate, Aqueous Solution
O
402
Calcium Cyanamide
F
403
Calcium Cyanide
T
404
Calcium Dithionite (Calcium Hydrosulphite)
F
405
Calcium Hydride
F
406
Calcium Hypochloride, Dry or CalciumHypochloride Mixture, Dry
O
407
Calcium Hypochlorite Mixture
O
408
Calcium Hypochlorite, Hydrated or CalciumHypochlorite, Hydrated Mixture
O
409
Calcium Manganese Silicon
F
410
Calcium Oxide
C
411
Calcium Perchlorate
O
412
Calcium Permanganate

O

413

Calcium Peroxide

O

414

Calcium Resinate

F

415

Calcium Silicide

F

416

Calcium, Pyrophoric or Calcium Alloys, Pyrophoric

F

417

Camphor

F

418

Camphor Oil

F

419

Caprioc Acid

C

420

Carbamate Pesticide, Liquid, Toxic

T

421

Carbamate Pesticide, Liquid, Toxic

F

422

CarbamatePesticide,Liquid,Toxic,Flammable

T

423

Carbamatc Pesticide, Solid, Toxic

T

424

Carbaryl

(Sevin)

T

425

Carbofuran

T

426

Carbofuran

(Furadan)

T

427

Carbon Dioxide Refrigerated Liquid

G

428

Carbon Disulphide

F

T

429

Carbon Monoxide

F

T

430

Carbon Monoxide and Hydrogen Mixture, Compressed

T

G

431

Carbon Tetrabromide

T

432

Carbon Tetrachloride

T

433

Carbon, Activated

F

434

Carbonyl Fluoride, Compressed

G

435

Carbonyl Sulphide

T

436

Carbophenothion

T

437

Cartridges

E

438

Caustic Alkali Liquid, N.O.S.

C

439

Celulose Nitrate

E

F

440

Celluloid

F

441

Celluloid, Scrap

F

442

Cellulose Nitrate

E

F

443

Cerium

F

444

Chemical Sample, Toxic

T

445

Chloral, Anhydrous, Stabilized

T

446

Chlorates

(Used in Explosives)

E

447

Chlorates, Inorganic, Aqueous Solution, N.O.S.

O

448

Chlorfenvinphos

T

449

Chloric Acid, Aqueous

O

450

Chlorinated Benzenes

T

451

Chlorine

T

G

452

Chlorine Dioxide

T

453

Chlorine Oxide

T

454

Chlorine Pentafluoride

G

455

Chlorine Trifluoride

G

456

Chlorite Solution

C

|

457

Chlorites, Inorganic, N.O.S.

O

458

Chlorites, Inorganic, N.O.S.

O

459

Chlormephos

T

460

Chlormequat Chloride

T

461

Chloroacetal Chloride

C

T

462

Chloroacetaldehyde

T

463

Chloroacetic Acid

T

464

Chloroacetic Acid Solution

O

465

Chloroacetic Acid, Molten

T

466

Chloroacetic Acid, Solid

T

467

Chlnoacetone, Stabilized

T

468

Chloroacetonitrile

T

469

Chloroacetophenone

T

470

Chloroacetyl Chloride

C

T

-471

Chloroaniline,

-2

T

472

Chloroaniline,

-4 -

T

473

Chloroaniline-2

T

474

Chloroaniline-4

T

475

Chloroanilines, Liquid

T

476

Chloroanilines, Solid

T

477-

Chloroanisidines

T

478

Chlorobenzene

F

T

479

Chlorobenzotrifluorides

F

480

Chlorobenzyl Chlorides

T

481

Chlorobutanes

F

482

Chlorocresols

T

483

Chlorodifluorobromomethane

(Refrigerant GasR 12B1)

G

484

Chlorodifluoromethane andChloropentafluoroethane Mixture

G

485

Chlorodifluoromethane

G

486

Chlorodinitrobenzenes, Liquid

T

487

Chlorodinitrobenzenes, Solid

T

488

Chlorodiphenyl

T

489

Chloroepoxypropane

T

490

Chloroethanol

T

491

Chloroethyl Chloroformate

T

492

Chlorofenvinphos

T

493

Chlorofluorocarbons

T

494

Chloroform

T

495

Chloroformates, Toxic, Corrosive, N.O.S.

T

496

Chloroformyl Morploline

T

497

Chloroformyl,
-4 Morpholine

T

498

Chloromethane

T

499

Chloromethyl Chloroformate

T

500

Chloromethyl Ether

T

501

Chloromethyl Ethyl Ether

F

502

Chloromethyl Methyl Ether

T

503

Chloromormates, Toxic, Corrosive, Flammable,N.O.S.

T

504

Chloronitroanilines

T

505

Chloronitrobenzene

E

T

506

Chloronitrobenzenes

T

507

Chloronitrotoluenes, Liquid/Solid

T

508

Chloropentafluoroethane

G

509

Chlorophacinone

T

510

Chlorophenolates, Liquid or Phenolates, Liquid

C

511

Chlorophenolates, Solid or Phenolates, Solid

C

512

Chlorophenols, Liquid

T

513

Chlorophenyltrichloro-Silane

C

514

Chloropicrin

T

515

Chloropicrin Mixture, N.O.S.

T

516

ChloroplatinicAcid,Solid

C

517

Chloroprene

F

T

518

Chloroprene, Stabilized

F

519

Chlorosilanes, Corrosive, Flammable, N.O.S.

C

520

Chlorosilanes, Corrosive, N.O.S.

C

521

Chlorosilanes, Flammable, Corrosive, N.O.S.

F

522

Chlorosulphonic Acid

C

523

Chlorothiophos

T

524

Chlorotoluenes

F

525

Chlorotoluidines

T

526

Chlorotrifluoromethane

G

527

Chlorotrifluoromethane and Trifluoromethane Azeotropic Mixture

G

528

Chlorotrinitrobenzene

E

T

529

Chloroxuron

T

530

Chlorophenols, Solid

T

531

Chloroethyl Chloroformate

T

532

Chromic Acid

| O

| C

T

533

Chromic Acid Solution

C

534

Chromic Chloride

O

| C

T

535

Chromic Fluoride Solution

C

536

Chromic Fluoride, Solid

C

537

Chromium and Compounds

T

538

Chromium Nitrate

O

539

Chromium Oxychloride

C

540

Chromium Powder

T
541
Chromium Trioxide, Anhydrous
O
542
Chromosulphuric Acid
C
543
Clinical Waste, Unspecified, N.O.S. or (bio)Medical Waste, N.O.S. or Regulated Medical Waste, N.O.S.
T
544
Chlorine
T
545
Coal Tar Distillates, Flammable
F
546
Cobalt
& Compounds
T
547
Cobalt
(Powder)
T
548
Cobalt Carbonyl
T
549
Cobalt Naphthenates, Powder
F
550
Cobalt Nitrilmethyldyne Compound
T
551
Cobalt Resinate, Precipitated
F
552
Coloured Fire
E
553
Compressed Gas, Flammable, N.O.S.
G
554
Compressed Gas, Toxic, Flammable Corrosive, N.O.S.
F
C
T
555
Copper Acetoarsenite
T
556

Copper and Compounds

T

557

Copper Arsenite

T

558.

Copper Based Pesticide, Liquid, Flammable, Toxic

F

559

Copper Based Pesticide, Liquid, Toxic

T

560

Copper Based Pesticide, Liquid, Toxic, Flammable

T

561

Copper Based Pesticide, Solid, Toxic

T

562

Copper Chlorate

O

563

Copper Chloride

C

564

Copper Cyanide Copperoxychloride

T

565

Coroformyl,

-4 Niorpholine

T

566

Corrosive Liquid, Acidic, Inorganic, N.O.S.

C

567

Corrosive Liquid, Acidic, Organic, N.O.S.

C

568

Corrosive Liquid, Basic, Inorganic, N.O.S.

C

569

Corrosive Liquid, Basic, Organic, N.O.S.

C

570

Corrosive Liquid, Flammable, N.O.S.

C

571

Corrosive Liquid, Oxidizing, N.O.S.

C

572

Corrosive Liquid, Self-Heating, N.O.S.

C

573

Corrosive Liquid, Toxic, N.O.S.

C

574

Corrosive Liquid, Water-Reactive, N.O.S.

C

575

Corrosive Solid, Acidic, Inorganic, N.O.S.

C

576

Corrosive Solid, Acidic, Organic, N.O.S.

C

577

Corrosive Solid, Basic, Inorganic, N.O.S.

C

578

Corrosive Solid, Basic, Organic, N.O.S.

C

579

Corrosive Solid, Oxidizing, N.O.S.

C

580

Corrosive Solid, Toxic, N.O.S.

C

581

Corrosive Solid, Water-Reactive, N.O.S.

C

582

Coumarin Derivative Pesticide, Liquid, Flammable, Toxic

F

583

Coumarin Derivative Pesticide, Liquid, Toxic

T

584

Coumarin Derivative Pesticide, Liquid, Toxic, Flammable

T

585

Coumarin Derivative Pesticide, Solid, Toxic

T

586

Coumatetrallyl

T

587

Cresols

T

588

Cresols, Liquid/Liquid

T

589

Cresylic Acid

T

590

Crimidine

T

591

Crotonaldehyde

F

T

592

Crotonic Acid

C

593

Cumene

T

594

Cupriethylenediamine Solution

C

595

Cyanide Solution, N.O.S.

T

596

Cyanides, Inorganic, Solid, N.O.S.

T

597

Cyanogen

G

598

Cyanogen Bromide

T

599

Cyanogen Chloride, Stabilized

T

G

600

Cyanogen Iodide

T

601

Cyanothoate

T

602

Cyanuric Chloride

C

603

Cyanuric Fluoride

T

604

Cyclobutane

G

605

Cyclobutyl Chloroformate

T

606

Cycloheptane

F

607

Cycloheptene

F

608

Cyclohetatriene

F

609

Cyclohexane

F

610

Cyclohexanone

F

T

611

Cyclohexene

F

612

Cyclohexenyltrichlorosilane

C

613

Cycloheximide

T

614

Cyclohexyl Acetate

F

615

Cyclohexyl Isocyanate

T

616

Cyclohexyl Mercaptan

F

617

Cyclohexylamine

C

618

Cyclohexyltrichlorosilane

C

619

Cyclooctadienes

F

620

Cyclooctatetraene

F

621

Cyclopentadiene

F

T

622

Cyclopentane

F

623

Cyclopentanol

F

624

Cyclopentanone

F

625

Cyclopentene

F

626

Cyclopropane

G

627

CyclotetramethyleneTetranitramine

E

628

Cyclotetramethylenetetranitramine

(HMX,Octogen), Wetted

E

629

Cyclotrimethylenetrinitramine

&CyclotetramethylenetetranitramineMixture Wetted or Cydotrimethyle

E

630

Cymens

F

631

DDT

T

632

Decaborane

T

633

Decaboraneo

F

634

Decabromodiphenyl Oxide

T

635

Decahydronaphthalene

F

636

Deglagrating Metal Salts of AromaticNitroderivatives, N.O.S.

E

637

Demeton

T

638

Demeton S-Methyl

T

639

Detonators

E

640

Deuterium, Compressed

G

641

Devices, Small, Hydrocarbon Gas Powered or Hydrocarbon Gas Refills for small Devices

G

642

Dihydroxybutylamine

F

|

|

643

Diacetone Alcohol

F

644

Dialifos

T

645

Diallyl Ether

F

646

Diallylamine

F

647

Diazodinitrophenol

E

648

Diazodinitrophenol, Wetted

E

F

649

Diazomethane

T

650

Dibenzyl Peroxydicarbonate

R

651

Dibenzyl Peroxydicarbonate (CONC >= 90%)

T

652

Dibenzyl dichlorosilane

C

653

Diborane

T

654

Diborane, Compressed

G

655

Dibromochloropropanes

T

656

Dibromodifluoromethane

T

657

Dibromomethane

T

658

Dibutyl Ethers

F

659

Dibutylaminoethanol

T

660

Dichloro Obenzene-O

T

661

Dichloroacetic Acid

C

662

Dichloroacetyl Chloride

C

663

Dichloroacetylene

T

664

Dichloroacetylene-O

T

665

Dichloroanilines, Liquid

T

666

Dichlorobenzalkonium Chloride

T

667

Dichlorobenzene-P

T

668

Dichlorodifluoromethane

G

669

Dichlorodifluoromethane and Difluoroethane Azeotropic Mixture

G

670

Dichlorodimethyl Ether, Symmetrical

T

671

Dichloroethane

T

672

Dichloroethyl Ether

T

673

Dichloroisocyanuric Acid, Dry or Dichloroisocyanuric Acid Salts

O

674

Dichloroisopropyl Ether

T

675

Dichloromethane

T

676

Dichloromethyl Phenylsilane

T

677

Dichloropentanes

F

678

Dichlorophenol,

-2,4 & -2.6

T

679

Dichlorophenoxy Acetic Acid

T

680

Dichlorophenoxy Acetic Acid, -2,4 (2, 4-D)

T

681

Dichlorophenyl Isocyanates

T

682

Dichlorophenyl Trichlorosilane

C

683

Dichloropropane 2, 2

T

684

Dichloropropane,

-1, 2

T

685

Dichloropropens

F

686

Dichlorosalicylic Acid-3,5

T

687

Dichlorosalicylic Acid-3,5

T

688

Dichlorosilane

G

689

Dichlorvos

(DDVP)

T

690

Dicrotophos

T

691

Dicyclohexylamine

C

T

692

Dicyclohexylammonium Nitrite

F

693

Dicyclopentadiene

F

694

Didymium Nitrate

O

695

Diepoxy Butane

T

696

Diepoxy Butane

T

697

Diethleneglycol Butyl Ether

T

698

Diethoxymethane

F

699

Diethye Peroxijdicarbonate

R

700

Diethyl Carbamazaine Citrate

R

701

Diethyl Carbamazaine Citrate

R

702

Diethyl Carbonate

F

703

Diethyl Chlorophosphate

T

704

Diethyl Ethanolamine

T

705

Diethyl Ether (Ethyl Ether)

F

706

Diethyl Glycol Dinitrate

T

707

Diethyl Ketone

F

708

Diethyl Peroxydicarbonate

T

709

Diethyl Peroxydicarbonate (CONC=30%)

T

710

Diethyl Phenylene Diamine

T

711

Diethyl Sulphate

T

712

Diethyl Sulphide

F

713

Diethylamine

R

714

Diethylamine Ethanol

T

715

Diethylaminopropylamine

F

716

Diethylbenzene

F

717

Diethyldichlorosilance

C

718

Diethylene Glycol

T

719

Diethylene Glycol Butyl Ether

T

720

Diethylene Glycol Dinitrate

T

721

Diethylene Triamine

T

722

Diethyleneglycol Butyl Ether/DiethyleneglycolButyl Acetate

T

723

Diethyleneglycol, Dinitrate, Desensitized

E

C

724

Diethylenetriamine

C

725

Diethylenetriamine

(DETA)

C

726

Diethylthiophosphoryl Chloride

C

727

Difluoromethane

(Refrigerant Gas R 32)

G

728

Difluorophosphoric Acid, Anhydrous

C

729

Digitoxin

C

730

Diglycidyl Ether

T

731

Dihlorofluoromethane

G

732

Dihydroperoxypropane

(CONC>=30%)

T

733

Dihydroperoxypropane,

-2,2

E

734

Diisobutyl Ketone

F

735

Diisobutyl Peroxide

R

736

Di-isobutyl Peroxide

T

737

Diisobutylene, Isomeric Compounds

F

738

Di-isobutyryl Peroxide

T

739

Diisooctyl Acid Phosphate

C

740

Diisopropyl Ether

F

741

Diisopropylamine

R

742

Diketene, Stabilized

T

743

Dimefox

F

C

744

Dimethcaebonyl Chloride

T

745

Dimethylcarbonyl Chloride

T

746

Dimethoate

T

747

Dimethyl Carbonate

F

T

748

Dimethyl Dichlorosilane

T

749

Dimethyl Disulphide

F

750

Dimethyl Ether

G

751

Dimethyl Hydrazine

C

752

Dimethyl Nitrosoamine

C

753

Dimethyl P Phenylene Diarnine

T

754

Dimethyl Phosphoramidi Cyanidic Acid (Tabum)

T

755

Dimethyl Phosphoramidocyanidic Acid

T

756

Dimethyl Phosphorochloridothioate

T

757

Dimethyl Phthalate

T

758

Dimethyl Sufolane (DMS)

T

759

Dimethyl Sulphate

T

760

Dimethyl Sulphide

F

761

Dimethyl Thiophosphoryl Chloride

T

762

Dimethylamine

T

763

Dimethylamine Aqueous Solution

F

764

Dimethylamine, Anhydrous

T

765

Dimethylaniline

T

766

Dimethylcarbamoyl Chloride

C

T

767

Dimethylcarbomyl

T

768

Dimethylcarbonyl Chloride

T

769

Dimethylcyclohexanes

F

770
Dimethylcyclohexylamine
C

771
Dimethyldichlorosilane
F

772
Dimethyldiethoxysilane
F

773
Dimethyldioxanes
F

774
Dimethyl Formamide
T

775
Dimethylhydrazine, Symmetrical
T

776
Dimethylhydrazine, Unsymmetrical
T

777
Dimethylnitrosamine
T

778
Dimethyl-N-Propylamine
F

779
Dimetilan
T

780
Di-n-Amylamine
F

781
Di-n-Butylamine
C

782
Dinitro O-Cresol
T

783
Dinitrobenzene
T

784
Dinitrobenzenes, Liquid
T

785
Dinitrobenzenes, Solid
T

786
Dinitrogen Tetroxide (Nitrogen Dioxide)
G

787

Dinitro-O-Cresol

T

788

Dinitrophenol

E

O

C

789

Dinitrophenol Solution

T

790

Dinitrophenol, Salts

E

T

791

Dinitrophenol, Wetted

F

792

Dinitrophenolates, Wetted

F

793

Dinitroresorcinol

E

794

Dinitroresorcinol, Wetted

F

795

Dinitrosobenzene

E

796

Dinitrotoluene

T

797

Dinitrotoluenes, Liquid/Solid

T

798

Dinitrotoluenes, Molten

E

T

799

Di-N-Propyl Ether

F

800

Di-n-Propyl Peroxidicarbonate

R

801

Di-n-Propyl Peroxydicarbonate (CONC=80%)

R

802

Dioxane

F
T
803
Dioxane-P
T
804
Dioxathion
T
805
Dioxine N
T
806
Dioxolane
F
807
Dipentene
F
808
Diphacinone
T
809
Diphenyl Methane Di-Isocynate (MDI)
T
810
Diphenylamine Chloroarsine
T
811
Diphenylchloroarsine, Liquid/Solid
T
812
Diphenyldichlorosilane
C
813
Diphenylmethyl Bromide
C
814
Diphosphoramidate Octamethyl
T
815
Dipicryl Sulphide
E
816
Dipicryl Sulphide, Wetted
F
817
Dipropyl Ketone
F
818
Dipropylamine
F
819

Dipropylene Glycol Butyl Ether

F

820

Dipropylene Glycolmethylether

F

821

Dischlorophenoxy Acetic Acid

F

822

Discrotophos

F

823

Di-sec-Butyl Peroxidicarbonate

R

824

Disec-Butyl Peroxydicarbonate (CONC>80%)

R

T

825

Disinfectant, Liquid, Corrosive, N.O.S.

C

826

Disinfectant, Liquid, Toxic, N.O.S.

T

827

Disinfectant, Solid, Toxic, N.O.S.

T

828

Disobutyl Peroxide

T

829

Disodium Trioxosilicate

C

830

Disulfoton

T

831

Dithiazamine Iodide

T

832

Dithiobiurate

T

833

Dithydroperoxypropane,

-2,2

T

834

Divinyl Ether, Stabilized

T

835

Dodecyltrichlorosilane

C
836
Dry, Liquid, Corrosive, N.O.S. or Dye IntermediateLiquid, Corrosive, N.O.S.
C
837
Dye, Solid, Corrosive, N.O.S. or Dye Intermediate,Solid, Corrosive, N.O.S.
C
838
Dye, Solid, Toxic, N.O.S. or Dye Intermediate,Solid, Toxic, N.O.S.
T
839
Ear Gas Substance, Liquid/Solid, N.O.S.
T
840
Elevated Temperature Liquid, Flammable
F
841
Epibromohydrin
T
842
Epichlorohydrin
F
T
843
EPN
T
844
Epoxypropane,
1, 2
T
845
Ergocalciferol
T.
846
Ergotamine Tartarate
T
847
Esters, N.O.S.
F
848
Ethane
G
849
Ethane, Refrigerated Liquid
G
850
Ethanesulfenyl Chloride, 2 Chloro
G
851
Ethanol 1-2 Dichloracetate
T

852

Ethanol or Ethanol Solution

F

853

Ethanolamine or Ethanolamine Solution

C

854

Ethers, N.O.S.

F

855

Ethion

T

856

Ethoprophos

T

857

Ethyl2-Chloropropionate

F

858

Ethyl Acetate

F

859

Ethyl Acrylate, Stabilized

F

860

Ethyl Alcohol

F

861

Ethyl Amine

T

G

862

Ethyl Amyl.Ketone

F

863

Ethyl Benzene

T

G

864

Ethyl Bis Amine

T

G

865

Ethyl Borate

F

866

Ethyl Bromide

T

867

Ethyl Bromoacetate

T

868

Ethyl Butyl Ether

F

869

Ethyl Butyrate

F

870

Ethyl Carbamate

T

871

Ethyl Chloride

T

G

872

Ethyl Chloroacetate

T

873

Ethyl Chloroformate

T

874

Ethyl Chlorothioformate

C

875

Ethyl Crotonate

F

876

Ethyl Ether

F

877

Ethyl Fluoride (Refrigerant Gas R 161)

G

878

Ethyl Isobutyrate

F

879

Ethyl Isocyanate

F

880

Ethyl Lactate

F

881

Ethyl Mercaptan

F

T

882

Ethyl Mercuric Phosphate

T

883

Ethyl Methacrylate

F

884

Ethyl Methyl Ether

G

885

Ethyl Methyl Ketone (Methyl Ethyl Ketone)

F

886

Ethyl Nitrate

E

R

T

887

Ethyl Orthoformate

F

888

Ethyl Oxalate

T

889

Ethyl Propionate

F

890

Ethyl Propyl Ether

F

891

Ethyl Thiocyanate

T

892

Ethylacetylene, Stabilized

G

893

Ethylamine

G

894

Ethylamine, Aqueous Solution

F

895

Ethylbenzene

F

896

Ethyldichloroarsine

T

897

Ethyldichlorosilane

F

898

Ethylene

G

899

Ethylene Chlorohydrin

T

900

Ethylene Chlorohydrine

T
901
Ethylene Di Chloride
T
902
Ethylene Diamine
F
C
903
Ethylene Diamine Hydrochloride
T
904
Ethylene Dibromide
T
905
Ethylene Dibromide (1, 2-Dibromomethane)
T
906
Ethylene Dichloride
F
907
Ethylene Flourohydrine
T
908
Ethylene Glycol
T
909
Ethylene Glycol Dinitrate
E
T
910
Ethylene Glycol Monoethyl Ether
F
911
Ethylene Glycol Monoethyl Ether Acetate
F
912
Ethylene Glycol Monomethyl Ether
F
913
Ethylene Glycol Diethyl Ether
F
914
Ethylene Oxide
E
R
T
915
Ethylene Oxide and Carbon Dioxide Mixture
G
916

Ethylene Oxide and Carbon Dioxide Mixture

G

917

Ethylene Oxide and Chlorotetrafluoroethane Mixture

G

918

Ethylene Oxide and Dichlorodifluoromethane Mixture

G

919

Ethylene Oxide and Pentafluoroethane Mixture

G

920

Ethylene Oxide and Propylene Oxide Mixture

F

921

Ethylene Oxide and Tetrafluoroethane Mixture

G

922

Ethylene Oxide or Tetrafluoroethane with Nitrogen

G

923

Ethylene, Acetylene and Propylene Mixture, Refrigerated Liquid

G

924

Ethylene, Compressed

G

925

Ethylene, Refrigerated Liquid

G

926

Ethyleneamine

F

T

927

Ethylenediamine

C

928

Ethylphenyldichlorosilane

C

929

Ethylthiocyanate

T

930

Ethyltrichlorosilane

F

931

Explosive, Blasting, Type E

E

932

Explosive, Blasting, Type A

E

O

933

Explosive, Blasting, Type B

E

C

Ra

934

Ferric Arsenate

T

935

Ferric Arsenite

T

936

Ferric Chloride Solution

C

937

Ferric Chloride, Anhydrous

C

938

Ferric Nitrate

O

939

Ferrous Arsenate

T

940

Ferrous Metal Borings, Shavings, Turnings or Cuttings

F

941

Fire Extinguisher Charges

R

T

942

Firelighters, Solid

F

943

Fireworks

E

944

Flammable Liquid, Corrosive, N.O.S.

F

945

Flammable Liquid, Corrosive, Organic, N.O.S.

T

946

Flammable Liquid, Toxic, Corrosive, N.O.S.

F

947

Flammable Solid, Corrosive, Inorganic, N.O.S.

F

948

Flammable Solid, Corrosive, Organic, N.O.S.

F

949

Flammable Solid, Inorganic, N.O.S. '

F

950

Flammable Solid, Organic, N.O.S.

F

951

Flammable Solid, Oxidizing, N.O.S.

F

952

Flammable Solid, Toxic, Inorganic, N.O.S.

F

953

Flammable Solid, Toxic, Organic, N.O.S.

F

954

Flueneetil

T

955

Fluoride

T

956

Fluorine

T

957

Fluorine, Compressed

G

958

Fluoro 2-Hydroxy Butyric Acid Amid Salt Ester

T

959

Fluoro,

-4, -2-Hydroxybutyric Acid & Salts Esters, Amides

T

960

Fluoroacetic Acid

T

961

Fluoroanilines

T

962

Fluorobenzene

F

963

Fluoroboric Acid

C

964

Fluorocobutyric Acid & Salts, Esters, Amides

T

965

Fluorophosphoric Acid, Anhydrous

C

966

Fluorosilic Acid

C

967

Fluorosilicates, N.O.S.

T

968

Fluorosulphonic Acid

C

969

Fluorotoluenes

F

970

Fluroacetic Acide and Salts, Esters and Amides

T

971

Flurobutyric Acid, -4 and Salts, Esters and Amides

T

972

Flurocrotonic Acid, -4 and Salts, Esters and Amides

T

973

Fog-Signals

E

974

Formaldehyde

T

975

Formaldehyde Solution

C

976

Formaledehyde Solution, Flammable

F

977

Formatenate Hydrochloride

T

978

Fuel, Aviation, Turbine Engine

F

979

Fumaryl Chloride

C

980

Furaldehydes

T

981

Furan

F

982

Furfural

T

983

Furfuryl Alcohol

T

984

Furfurylamine

F

985

Fusel Oil

F

986

Fuses

E

987

Gallium

C

988

Gallium Trichloride

T

989

Gas Oil or Diesel Fuel or Heating Oil Light

F

990

Gas, Refrigerated Liquid, Flammable, N.O.S.

G

991

Gas, Refrigerated Liquid, N.O.S.

G

992

Gas, Refrigerated Liquid, Oxidizing, N.O.S.

G

993

Glycerol alpha-Monochlorohydrin

T

994

Glycidaldehyde

F

995

Glyconitrile

(Hydroxyacetonitrile)

T

996

Guanidine Nitrate

O

997

Guanyl Nitrosaminoguanylidene Hydrazine, Wetted

E

998

Guanyl Nitrosaminoguanyltetrazene (Tetrazene) Wetted

E

999

Guanyl,

-1, -4 Nitrosaminogunyl-I-Tetrazene

E

1000

Gun-Cotton

E

1001

Gunpowder

E

1002

Hafnium Power, Dry

F

1003

Helium, Refrigerated Liquid

G

1004

Heptachlor

E

T

1005

Heptafluoropropane

(Refrigerant Gas R 227)

G

1006

Heptanes

F

1007

Hexa Methyl Terta-Oxyacyclononate (CONC 75%)

T

1008

Hexabutrodiphenylamine

E

1009

Hexachloro Cyclopentadiene

T

1010

Hexachloroacetone

T

1011

Hexachlorobenzene

T

1012

Hexachlorobutadiene

T

1013

Hexachlorodibenzo-P-Dioxin,-1,2,3,7,8,9,Hexamethylphosphoramide

T

1014

Hexachlorophene

T

1015

Hexadecyltrichlorosilane

C

1016

Hexadiene

F

1017

Hexaethyl Tetraphosphate

T

1018

Hexafluoropropylene

G

1019

Hexamethyl Phosphoroarmide

T

1020

Hexamethyl,

-3,3,6,6,9,9,-1,2,4,5,-Tetroxacyclononane

R

1021

Hexamethylene Diisocyanate

T

1022

Hexamethylenediamine Solution

C

1023

Hexamethylenediamine, Solid

C

1024

Hexamethyleneimine

F

1025

Hexamethylenetetramine

F

1026

Hexamethylphosphoramide

T

1027

Hexanes

F

1028

Hexanitrostilbene

E

1029

Hexanitrostilbene-2,

2, 4, 6, 6

E

1030

Hexanols

F

1031

Hexavalent Chromium

T

1032

Hexene

F

1033

Hexotonal

E

1034

Hexyltrichlorosilane

C

1035

Hydrazine

F

T

1036

Hydrazine Nitrate

E

1037

Hydrazine, Anhydrous

C

1038

Hydrazine, Aqueous Solution

T

1039

Hydrazine, Hydrate or Hydrazine, Aqueous Solution

C

1040

Hydriodic Acid

C

1041

Hydrobromic Acid

C

1042

Hydrocarbon Gas Mixture, Compressed, N.O.S.

G

1043

Hydrocarbon Gas Mixture, Liquefied, N.O.S.

G

1044

Hydrocarbons, Liquid, N.O.S.

F

1045

Hydrochloric Acid

C

1046

Hydrochloric Acid (Gas)

T

1047

Hydrocyanic Acid, Aqueous Solution (Hydrogen Cyanide, Aqueous Solution)

T

1048

Hydrofluoric Acid

C

T

1049

Hydrofluoric Acid and Sulphuric Acid Mixture

C

1050

Hydrogen

F

R

1051

Hydrogen Bromide, Anhydrous

G

1052

Hydrogen and Methane Mixture, Compressed

G

1053

Hydrogen Bromide

T

1054

Hydrogen Bromide (Hydrobromic Acid)

C

T

1055

Hydrogen Chloride (Liquified Gas)

C

T

1056

Hydrogen Chloride, Anhydrous

G

1057

Hydrogen Chloride, Refrigerated Liquid

G

1058

Hydrogen Cyanide

T

1059

Hydrogen Cyanide, Solution in Alcohol

T

1060

Hydrogen Cyanide, Stabilized

T

I-

1061

Hydrogen Fluoride

C

T

1062

Hydrogen Fluoride, Anhydrous

C

1063

Hydrogen Iodide, Anhydrous

| G

1064

Hydrogen Peroxide

O

1065

Hydrogen Peroxide and Peroxyacetic Acid Mixture

O

1066

Hydrogen Peroxide, Adeous Solution

O

1067

Hydrogen Peroxide, Aqueous Solution

O

1068

Hydrogen Peroxide, Stabilized or Hydrogen Peroxide, Adeous Solution, Stabilized

O

1069

Hydrogen Selenide

T

1070

Hydrogen Selenide, Anhydrous

G

1071

Hydrogen Sulphide

F

T

G

1072

Hydrogen, Refrigerated Liquid

G

1073

Hydrogen difluorides, N.O.S.

C

1074

Hydroquinone

T

1075

Hydroxylamine Sulphate

C

1076

Hypochlorite Solution

C

1077

Hypochlorites, Inorganic, N.O.S.

O

1078

Indene

T

1079

Infectious Substance, Affecting Animals

T

1080

Infectious Substance, Affecting Humans

T

1081

Insecticide Gas, Flammable, N.O.S.

G

1082

Insecticide Gas, N.O.S.

G

1083

Insecticide Gas, Toxic, Flammable, N.O.S.

G

1084

Insecticide Gas, Toxic, N.O.S.

G

1085

Iodine

T

1086

Iodine Monochloride

C

1087

Iodine Pentafluoride

O

1088

Iodomethylpropanes

F

1089

Iodopropanes

F

1090

Iridium Tetrachloride

T

1091

Iron Pentacarbonyl

T

1092

Isobenzan

T

1093

Isobutane

G

1094

Isobutanol

(Isobutyl Alcohol)

F

1095

Isobutyl Chloride

F

1096

Isobutyl Acetate

F

1097

Isobutyl Acrylate, Stabilized

F

1098

Isobutyl Alcohol

T

1099

Isobutyl Formate

F

1100

Isobutyl Isobutyrate

F

1101

Isobutyl Isocyanate

F

1102

Isobutyl Methacrylate, Stabilized

F

1103

Isobutyl Propane

F

1104

Isobutylene

G

1105

Isobutyraldehyde

(Isobutyl Aldehyde)

F

1106

Isobutyric Acid

F

1107

Isobutyro Nitrile

T

1108

Isobutyro Nitrile

F

1109

Isocyanates, Flammable, Toxic, N.O.S. or Isocyanate Solution, Flammable, Toxic, N.O.S.

F

1110

Isocyanates, Toxic, Flammable, N.O.S. or Isocyanate Solution, Toxic, Flammable, N.O.S.

T

1111

Isocyanates, Toxic, N.O.S. or Isocyanate Solution, Toxic, N.O.S.

T

1112

Isocyanatobenzotrifluorides

T

1113

Isocyanic Acid 3 4-Dichlorophenyl Ester

T

1114

Isodrin

T

1115

Isofluorophosphate

T

1116

Isoheptene

F

1117

Isohexene

F

1118

Isooctene

F

1119

Isopentenes

F

1120

Isophorone Diisocyanate

T

1121

Isophorone Disocylanate

T

1122

Isophoronediamine

C

1123

Isopropenyl Acetate

F

1124

Isopropenyl Benzene

F

1125

Isopropyl Formate

T

1126

Isopropyl 2-Chloropropionate

F

1127

Isopropyl Acetate

F

1128

Isopropyl Acid Phosphate

C

1129

Isopropyl Alcohol

F

1130

Isopropyl Butyrate

F

1131

Isopropyl Chloroacetate

F

1132

Isopropyl Chlorocarbonate

C

1133

Isopropyl Chloroformate

T

1134

Isopropyl Ether

F

1135

Isopropyl Isobutyrate

F

1136

Isopropyl Isocyanate

F

1137

Isopropyl Methyl Pyrazolyl Dimethyl Carbonate

T

1138

Isopropyl Propionate

F

1139

Isopropylarnine

F

C

1140

Isopropylbenzene

F

1141

Isoprpanle

(Isopropyl Alcohol)

F

1142

Isosorbide Dinitrate Mixture

F

1143

Isosorbide-5-Mononitrate

F

1144

Juglone

(5-I-lydroxynaphthalene-1,4-Dione)

T

1145

Juglone

(5-Hydroxy Napthalene-Dione)

T

1146

Kerosene

F

1147

Ketene

T

1148

Ketones, Liquid, N.O.S.

F

1149

Krypton, Refrigerated Liquid

G

1150

Lactonitrile

T

1151

Lead

(Inorganic Fumes & Dusts)

T

1152

Lead 2,4, 6-Trinitroresorcinoxide (Lead Styphnate)

E

1153

Lead Acetate

T

1154

Lead Arsenates

T

1155

Lead Arsenite

T

1156

Lead Arsenites

T

1157

Lead Azide

T

1158

Lead Azide, Wetted

E

1159

Lead Compound, Soluble, N.O.S.

T

1160

Lead Cyanide

T

1161

Lead Dioxide

O

1162

Lead Nitrate

O

1163

Lead Perchlorate

O

1164

Lead Phosphite, Dibasic

F

1165

Lead Styphnate (Lead Trinitroresorcinate), Wetted

E

1166

Lead Sulphate

C

1167

Lindane

T

1168

Liquefied Gas, Flammable, N.O.S.

G

1169

Liquefied Gas, N.O.S.

G

1170

Liquefied Gas, Oxidizing, N.O.S.

G

1171

Liquefied Gas, Toxic, Flammable, N.O.S.

G

1172

Liquefied Gas, Toxic, N.O.S.

G

1173

Liquefied Petroleum Gas

F

1174

Liquified Gas, Toxic, Corrosive, N.O.S.

G

1175

Liquefied Gas, Toxic, Flammable, Corrosive, N.O S.

G

1176

Liquefied Gas, Toxic, Oxidizing, Corrosive, N.O.S.

G

1177

Liquefied Gas, Toxic, Oxidizing, N.O.S.

G

1178

Lithium

F

1179

Lithium Alkyls

F

1180

Lithium Aluminium Hydride

F

1181

Lithium Aluminium Hydride, Ethereal

F

1182

Lithium Borohydride

F

1183

Lithiurn Ferrosilicon

F

1184

Lithium Hydride

F

1185

Lithium Hydride, Fused Solid

F

1186

Lithium Hydroxide Monohydrate

C

1187

Lithium Hydroxide Solution

C

1188

Lithium Hypochlorite, Dry or LithiumHypochlorite Mixture

O

1189

Lithium Nitrate

O

1190

Lithium Nitride

F

1191

Lithium Peroxide

O

1192

Lithium Silicon

F

1193

London Purple

T

1194

Magnesium Alkyls

F

1195

Magnesium Aluminium Phosphide

F

1196

Magnesium Arsenate

T

1197

Magnesium Bromate

O

1198

Magnesium Chlorate

O

1199

Magnesium Diamide

F

1200

Magnesium Diphenyl

F

1201

Magnesium Fluorosilicate

T

1202

Magnesium Granules, Coated

F

1203

Magnesium Hydride

F

1204

Magnesium Nitrate

O

1205

Magnesium or Magnesium Alloys

F

1206

Magnesium Perchlorate

O

1207

Magnesium Peroxide

O

1208

Magnesium Phosphide

F

1209

Magnesium Powder or Magnesium Alloys Powder

F

1210

Magnesium Powder or Ribbon

| O

||

1211

Magnesium Silicide

F

1212

Maleic Anhydride

C

1213

Maleit Anhydride

T

1214

Malononitrile

T

1215

Maltel Anhydride

T

1216

Manganese and Compounds

T

1217

Maneb or Maneb Preparation

F

1218

Maneb, Stabilized or Maneb Preparation, Stabilized

F

1219

Manganese Nitrate

O

1220

Manganese Resinate

F

1221

Manganese Tricarbonyl Cyclopentadiene

C

1222

Mannitol Hexanitrate (Nitromannite) Wetted

E

1223

Matches, Fusee

F

1224

Matches, Safety

F

1225

Matches, Strike Anywhere

F

1226

Matches, Was 'Vesta'

F

1227

Mechlor Ethamine

T

1228

Medicine, Liquid, Flammable, Toxic, N.O.S.

F

1229

Medicine, Liquid, Toxic, N.O.S.

T

1230

Medicine, Solid, Toxic, N.O.S.

T

1231

Mephospholan

T

1232

Mercaptans, Liquid, Flammable, N.O.S. or Mercaptan Mixture, Liquid, Flammable, N.O.S.

F

1233

Mercaptans, Liquid, Flammable, Toxic, N.O.S. or Mercaptan Mixture

F

1234

Mercaptans, Liquid, Toxic, Flammable, N.O.S. or Mercaptan, Mixture, Liquid, Toxic, Flammable, N.O.S.

T

1235

Mercapto Benzothiazole

T

1236

Mercuric Acetate

T

1237

Mercuric Arsenate

T

1238

Mercuric Chloride

T

1239

Mercuric Nitrate

T

1240

Mercuric Oxide

T

1241

Mercuric Potassium Cyanide

T

1242

Mercurous Nitrate

T

1243

Mercury

C

1244

Mercury Acetate

T

1245

Mercury Alkyl

O

T

1246

Mercury Ammonium Chloride

T

1247

Mercury Based Pesticide, Liquid, Flammable, Toxic

F

1248

Mercury Based Pesticide, Liquid, Toxic

T

1249

Mercury Based Pesticide, Liquid, Toxic, Flammable

T

1250

Mercury Based Pesticide, Solid, Toxic

T

1251

Mercury Benzoate-

T

1252

Mercury Bromides

T

1253

Mercury Compound, Liquid, N.O.S.

T

1254

Mercury Compound, Solid, N.O.S.

T

1255

Mercury Cyanide

T

1256

Mercury Fulminate

E

1257

Mercury Gluconate

T

1258

Mercury Iodide

T

1259

Mercury Methyl

T

1260

Mercury Methyl Chloride

T

1261

Mercury Nucleate

T

1262

Mercury Oleate

T

1263

Mercury Oxide

T

1264

Mercury Oxycyanide, Desensitized

T

1265

Mercury Potassium Iodide

T

1266

Mercury Salicylate

T

1267

Mercury Sulphate

T

1268

Mercury Thiocyanate

T

1269

Metal Alkyl Haldies, Water-Reactive, N.O.S.or Metal Aryl Haldies, Water-Reactive, N.O.S.

F

1270

Metal Alkyl Hydrides, Water-Reactive, N.O.S.or Metal Aryl Hydrides, Water-Reactive, N.O.S.

F

1271

Metal Alkyls, Water-Reactive, N.O.S. or MetalAryls, Water-Reactive, N.O.S.

F

1272

Metal Carbonyls, N.O.S.

T

1273

Metal Catalyst, Dry

F

1274

Metal Catalyst, Wetted

F

1275

Metal Hydrides, Flammable, N.O.S.

F

1276

Metal Hydrides, Water-Reactive, N.O.S.

F

1277

Metal Powder, Flammable, N.O.S.

F

1278

Metal Powder, Self-Heating, N.O.S.

F

1279

Metal Salts of Organic Compounds, Flammable,N.O.S.

F

1280

Metaldehyde

F

1281

Metallic Substance, Water-Reactive, N.O.S.

F

1282

Methacrolein Diacetate

F

1283

Methacrylaldehyde, Stabilized

F

1284

Methacrylic Acid, Stabilized

C

1285

Methacrylic Anhydride

C

1286

Methacrylonitrile

C

1287

Methacrylonitrile, Stabilized

F

1288

Methacryloyl Chloride

T

1289

Methacryloyl Oxyethyl Isocyanate

T

1290

Methallyl Alcohol

F

1291

Methamidophos

T

1292

Methane

G

1293

Methane, Compressed or Natural Gas, Compressed

G

1294

Methane, Refrigerated Liquid or Natural Gas, Refrigerated Liquid

G

1295

Methanesulphonyl Chloride

T

1296

Methanesulphonyl Fluoride

T

1297

Methanidophos

T

1298

Methanol

F

1299

Methanthiol

T

1300

Methidathion

T

1301

Methiocarb

T

1302

Methonyl

T

1303

Methoxy Ethanol

T

1304

Methoxy Ethanol (2-Methyl Cellosolve)

T

1305

Methoxyethyl Mercuric Acetate

T

1306

Methoxymethyl Isocyanate

F

1307

Methyarylol Chloride

T

1308

Methyl 2-Chloroacrylate

T

1309

Methyl2-Chloropropionate

F

1310

Methyl Acetate

F

1311

Methyl Acrylate

F

T

1312

Methyl Acrylate, Stabilized

F

1313

Methyl Alcohol

F

1314

Methyl Amine

F

1315

Methyl Amylketone

C

1316

Methyl Bromide

G;

1317

Methyl Bromide (Bromomethane)

T

1318

Methyl Bromide and Ethylene Dibromide Mixture, Liquid

T

1319

Methyl Bromoacetate

F

1320

Methyl Butyrate

F

1321

Methyl Chloride

T

G

1322

Methyl Chloride and Methylene Chloride Mixture

G

1323

Methyl Chloroacetate

T

1324

Methyl Chloroform

F

T

1325

Methyl Chloroformate

T

1326

Methyl Chloromethyl Ether

T

1327

Methyl Cyclohexane

F

1328

Methyl Cyclohexene

F

1329

Methyl Dichloroacetate

T

1330

Methyl Disulphide

T

1331

Methyl Ethyl Ketone Peroxide

R

1332

Methyl Ethyl Ketone Peroxide (CONC. 60%)

T

1333

Methyl Formate

F

1334

Methyl Gluoride (Refrigerant Gas R 41)

G

1335

Methyl Hydrazine

O

1336

Methyl Iodide

T

1337

Methyl Isobutyl Carbinol

F

1338

Methyl Isobutyl Ketone

F

1339

Methyl Isobutyl Ketone Peroxide

R

1340

Methyl Isocyanate

F

T

1341

Methyl Isopropenyl Ketone, Stabilized

F

1342

Methyl Isothiocyanate

T

1343

Methyl Isovalerate

F

1344

Methyl Magnesium Bromide in Ethyl Ether

F

1345

Methyl Mercuric Dicyanamide

T

1346

Methyl Mercaptan

G

1347

Methyl Methacrylate

F

1348

Methyl Methacrylate Monomer, Stabilized

F

1349

Methyl-N,

2, 4, 6, 6-Tetranitroaniline

T

1350

Methyl Nitrite

G

1351

Methyl Orthosilicate

T

1352

Methyl Parathion

T

1353

Methyl Phencapton

T

1354

Methyl Phoshonic Dichloride

T

1355

Methyl Phosphonic Dichloride

T

1356

Methyl Propionate

F

1357

Methyl Propyl Ether

F

1358

Methyl Propyl Ketone

F

1359

Methyl Styrene

F

T

1360

Methyl tert-Butyl Ether

F

1361

Methyl Thiocyanate

T

1362

Methyl Trichloroacetate

T

1363

Methyl Trichlorosilane

T

1364

Methyl Vinyl Ketone

T

1365

Methyl Vinyl Ketone, Stabilized

T

1366

Metylally Chloride

F

1367

Methylamine, Anhydrous

G

1368

Methylamyl Acetate

F

1369

Methylchlorosilane

G

1370

Methylcyclohexane

F

1371

Methylcylohexano,S

F

1372

Methylcyclohexanone

F

1373

Methylcyclopentane

F

1374

Methyldichlorosilane

F

1375

Methylene Bis (2-Chloroaniline)

T

1376

Methylene Chloride

T

1377

Methylenebis,

-4,4,(2, -Chloroaniline)

T

1378

Methylhydrazine

T

1379

Methylisobutyl Ketone

T

1380

Methylpentadiene

F

1381

Methylphenyldichlorosilane

C

1382

Methyl Tetrahydrofuran

F

1383

Methyltrichlorosilane

F

1384

Methyol Isodyanate

F

T

1385

Mevinphos

T

1386

Molybdenum and Compounds

T

1387

Molybdenum Pentachloride

C

1388

Molybdenum Powder

T

1389

Monocrotophos

T

1390

Morpholine

F

C

1391

Motor Fuel Anti-Knock Mixture

T

1392

Motor Spirit or Gasoline or Petrol

F

1393

Mustard Gas

T

1394

N, N-Diethylethylenediamine

|| C

1395

N, N-Dimethylformamide

F

1396

N, N-Dimethylaniline

T

1397

N-Aminoethylpiperazine

C

1398

Naphtha

E

F

1399

Naphtha Solvent

E

F

1400

Naphthalene, Crude or Naphthalene, Refined

F

1401

Naphthalene, Molten

F

1402

Naphthyl Amine

T

1403

Naphthylurea

T

1404

Naptha

(Coal Tar)

F

1405

Napthalene

T

1406

Napthylamine,-2

T

1407

N-Butyl Acetate

T

1408

N-Butyl Alcohol

F

T

1409

N-Butyl Chloroformate

T

1410

N-Butyl Formate

F

1411

N-Butyl Isocyanate

T

1412

N-Butyl Methacrylate, Stabilized

F

1413

N-Butylaniline

T

1414

N-Butylimidazole

T

1415

N-Decane

F

1416

N-Diethylaniline

T

1417

N-Dinitrobenzene

T

1418

Neon, Refrigerated Liquid

G

1419

N-Ethylaniline

T

1420

N-Ethylbenzyltoluidines, Liquid/Solid

T

1421

N-Ethyl-N-Benzylaniline

T

1422

N-Ethyltoluidines

T

1423

N-Heptaldehyde

F

1424

N-Heptene

F

1425

N-Hexane

F

1426

Nickel and Compounds

T

1427

Nickel Carbonyl/Nickel Tetracarbonyl

T

1428

Nickel Cyanide

T

1429

Nickel Nitrate

O

1430

Nickel Nitrite

O

1431

Nickel Powder

T

1432

Nickel Tetracarbonyl

F

T

1433

Nicotine

T

1434

Nicotine Compound, Liquid, N.O.S. or Nicotine Preparation, Liquid, N.O.S.

T

1435

Nicotine Compound, Solid, N.O.S. or Nicotine Preparation, Solid, N.O.S.

T

1436

Nicotine Hydrochloride, Liquid or Nicotine Hydrochloride Solution

T

1437

Nicotine Hydrochloride, solid

T

1438

Nicotine Salicylate

T

1439

Nicotine Sulphate

T

1440

Nicotine Sulphate, Solid

T

1441

Nicotine Sulphate, Solution

T

1442

Nicotine Tartrate

T

1443

Nitric Oxide, Compressed

G

1444

Nitrates, Inorganic, Aqueous Solution, N.O.S.

O

|||-

1445

Nitrates, Inorganic, N.O.S.

O

1446

Nitrating Acid Mixture

C

1447

Nitrating Acid Mixture, Spent

C

1448

Nitric Acid

C

1449

Nitric Acid and Dinitrogen Tetraoxide Mixture(Nitric Oxide and Nitrogen Dioxide Mixture)

G

1450

Nitric Acid, Red Fuming

C

1451

Nitric Oxide

T

1452

Nitriles, Flammable, Toxic, N.O.S.

F

1453

Nitriles, Toxic, Flammable, N.O.S.

T

1454

Nitriles, Toxic, N.O.S.

T

1455

Nitrites, Inorganic, Aqueous Solution, N.O.S.

O

1456

Nitrites, Inorganic, N.O.S.

O

1457

Nitro Urea

E

1458

Nitroaniline-O

T

1459

Nitroaniline-P

T

1460

Nitroanilines

T

G

1461

Nitroanisoles, Liquid/Solid

T

1462

Nitrobenzene

T

1463

Nitrobenzenesulphonic Acid

C

1464

Nitrobenzotrifluorides

T

1465

Nitrobromobenzenes, Liquid

T

1466

Nitrocellulose

E

1467

Nitrocellulose Membrane Filters

F

1468

Nitrocellulose Mixture with or without plasticizer, with or without pigment

F

1469

Nitrocellulose Solution, Flammable

F

1470

Nitrocellulose with Alcohol

F

1471

Nitrocellulose with Water

F

1472

Nitrocellulose

(Dry)

E

1473

Nitrochlorobenzene

T

1474

Nitrochlorobenzene-P

T

1475

Nitrocresols

T

1476

Nitrocyclohexane

T

1477

Nitroethane

F

T

1478

Nitrogen

G

1479

Nitrogen Dioxide

T

1480

Nitrogen Oxide

T

G

1481

Nitrogen Oxides

T

1482

Nitrogen Trifluoride

T

G

1483

Nitrogen Trifluoride, Compressed

G

1484

Nitrogen Trioxide

G

1485

Nitrogen, Refrigerated Liquid

G

1486

Nitroglycerin Mixture, Desensitized Solid, N.O.S.

F

1487

Nitroglycerin Mixture, Desensitized Liquid, Flammable, N.O.S.

F

1488

Nitroglycerin Mixture, Desensitized, Liquid, N.O.S.

F

1489

Nitroglycerin Solution in Alcohol

E

1490

Nitroglycerin Solution in Alcohol

F

1491

Nitroglycerin

E

T

1492

Nitroguanidine

(Picrite)

F

1493

Nitroglycerin Solution in Alcohol

F

1494

Nitrohydrochloric Acid

C

1495

Nitromethane

F

1496

Nitronaphthalene

F

1497

Nitrophenol-P

T

1498

Nitrophenols

T

1499

Nitropropane-1

F

1500

Nitropropane-2

F

1501

Nitropropanes

F

1502

Nitroso Dimethyl Amine

T

1503

Nitrostarch

E

1504

Nitrostarch, Wetted

F

1505

Nitrosyl Chloride

G

1506

Nitrosylsulphuric Acid, Liquid/Solid

C

1507

Nitrotoluene

T

1508

Nitrotoluenes, Liquid

T

1509

Nitrotoluidines

(Mono)

T

1510

Nitrous Oxide

G

1511

Nitrous Oxide, Refrigerated Liquid

G

1512

Nitroxyls, Liquid

T

1513

N-Methylaniline

T

1514

N-Methylbutylamine

F

1515

N-Methyl-N,
2, 4, 6-Tetranitroaniline

E

1516

Nonanes

F

1517

Nonyltrichlorosilane

C

1518

n-Propanol
(Propyl Alcohol, Normal)

F

1519

n-Propyl Acetate

F

1520

n-Propyl Chloroformate

T

1521

n-Propyl Isocyanate

T

1522

n-Propylnitrate

F

1523

n-Propylbenzene

F

1524

Octadecyltrichlorosilane

C

1525

Octadiene

F

1526

Octafluorobut
(Refrigerant Gas R218)

G

1527

Octafluorobut-2-Ene

(Refrigerant Gas R 1318)

G

1528

Octafluorocyclobutane

(Refrigerant Gas RC 318)

G

1529

Octanes

F

1530

Octyl Aldehydes

F

1531

Octyltrichlorosilane

C

1532

o-Dichlorobenzene

T

1533

Oleum

C

1534

O-Nitro Toluene

E

1535

00 Diethyl S Ethyl Suph. Methyl Phos

T

1536

00 Diethyl S Ethylsulphinylmethylphosphorothioate

T

1537

OO Diethyl S Ethylthiomethyl Phosphorothioate

T

1538

OO-Diethyl S-IsopropylthiomethylPhosphorothioate

T

1539

Organic Peroxide Type B, Liquid

O

1540

Organic Peroxide Type B, Liquid, TemperatureControlled

O

1541

Organic Peroxide Type B, Solid

O

1542

Organic Peroxide Type B, Solid, TemperatureControlled

O

1543

Organic Peroxide Type C, Liquid

O

1544

Organic Peroxide Type C, Liquid, TemperatureControlled

O

1545

Organic Peroxide Type C, Solid

O

1546

Organic Peroxide Type C, Solid, TemperatureControlled

O

1547

Organic Peroxide Type D, Liquid

O

1548

Organic Peroxide Type D, Liquid, TemperatureControlled

O

1549

Organic Peroxide Type D, Solid

O

1550

Organic Peroxide Type D, Solid, Temperature,Controlled

O

1551

Organic Peroxide Type E, Liquid

O

1552

Organic Peroxide Type E, Liquid, Temperature,Controlled

O

1553

Organic Peroxide Type E, Solid

O

1554

Organic Peroxide Type E, Solid, TemperatureControlled

O

1555

Organic Peroxide Type F, Liquid

O

||

1556

Organic Peroxide Type F, Liquid, TemperatureControlled

O

1557

Organic Peroxide Type F, Solid

O

1558

Organic Peroxide Type F, Solid, TemperatureControlled

O

1559

Organic Pigments, Self-Heating

F

1560

Organo Rhodium Complex

T

1561

Organoarsenic Compound, N.O.S.

T

1562

Organochlorine Pesticide, Liquid, Flammable, Toxic

F

1563

Organochlorine Pesticide, Liquid, Toxic

T

1564

Organochlorine Pesticide, Liquid, Toxic, Flammable

T

1565

Organochlorine Pesticide, Solid, Toxic

T

1566

Organometallic Compound or Compound Solution or Compound Dispersion, Water-Reactive, Flammable, N.O.S.

F

1567

Organometallic Compound, Toxic, N.O.S.

T

1568

Organophosphorus Compound, Toxic, Flammable, N.O.S.

T

1569

Organophosphorus Compound, Toxic, N.O.S.

T

1570

Organophosphorus pesticide Liquid, Flammable, Toxic

F

1571

Organophosphorus Pesticide Solid, Toxic

T

1572

Organophosphorus Pesticide Liquid, Toxic

T

1573

Organophosphorus Pesticide, Liquid, Toxic, Flammable

T

1574

Organotin Compound Liquid, N.O.S.

T

1575

Organotin Compound, Solid, N.O.S.

T

1576

Organotin Pesticide, Liquid, Flammable, Toxic

F

1577

Organotin Pesticide, Liquid, Toxic

T

1578

Organotin Pesticide, Liquid, Toxic, Flammable

T

1579

Organotin Pesticide, Solid, Toxic

T

1580

Orotic Acid

T

1581

Osmium Tetroxide

T

1582

O-Toludine

T

1583

Oxetane,

3, 3-Bis (Chloromethyl)

T

1584

Oxidiphenoxarsine

T

1585

Oxidizing Liquid, Corrosive, N.O.S.

O

1586

Oxidizing Liquid, N.O.S.

O

1587

Oxidizing Liquid, Toxic, N.O.S._

O

1588

Oxidizing Solid, Corrosive, N.O.S.

O

1589

Oxidizing Solid, Flammable, N.O.S.

O

1590

Oxidizing Solid, N.O.S.

O

1591

Oxidizing Solid, Self Heating,N.O.S.

O

1592

Oxidizing Solid, Toxic, N.O.S.

O

1593

Oxidizing Solid, Water Reactive, N.O.S.

O

1594

Oxvdisulfoton

T

1595

Oxygen

(Liquid)

O

G

1596

Oxygen Difluoride

T

1597

Oxygen Difluoride, Compressed

G

1598

Oxygen Generator, Chemical

O

1599

Oxygen

(Liquid)

O

1600

O-Xylene

F

C

1601

Ozone

O

R

T

1602

Paint or Paint Related Material

C

1603

Paraffin

F

1604

Paraformaldehyde

F

T

1605

Paraoxon

(Diethyl 4 Nitrophenyl Phosphate)

T

1606

Paraquate Methosulphate

T

1607

Parathion

T

1608

Parathion Methyl

T

1609

Paris Green

T

1610

Paroxon

(Diethyl 4-Nitrophenyl Phosphate)

T

1611

Pensulfothion

T

1612

Penta Borgne

F

T

1613

Penta Chloro Ethane

T

1614

Penta Chloro Phenol

T

1615

Pentaborane

T

1616

Pentabromodiphenyl Oxide

T

1617

Pentabromophenol

T

1618

Pentachloro Naphthalene

T

1619

Pentachloro Napthalene

T

1620

Pentachloroethane

T

1621

Pentachlorophenol

T

1622

Pentadecyl-Amine

C

1623

Pentaerythaiotol Tetranitrate

T

1624

Pentaerythrite Tetranitrate (PentaerythritolTetranitrate; Petn) Wetted

E

1625

Pentaerythrite Tetranitrate Mixture, Desensitized,Solid, N.O.S.

F

1626

Pentaerythritol Tetranitrate

E

T

1627

Pentafluoroethane

(Refrigerant Gas R 125)

G

1628

Pentachlorophenol

T

1629

Pentamethylheptane

F

1630

Pentane

T

1631

Pentane-2,4-Dion

F

1632

Pentanes, liquid

F

1633

Pentanone,

2,4-Methyl

T

1634

Peracetic Acid

R

C

1635

Peradetic Acid

T

1636

Perchlorates, Inorganic, Aqueous Solution, N.O.S.

O

1637

Perchlorates, Inorganic, N.O.S.

O

1638

Perchloric Acid

C

1639

Perchloroethylene

T

1640

Perchloromethyl Mercaptan

T

1641

Perchloryl Fluoride

G

1642

Percussion Caps

E

1643

Perfluoro

(Ethyl Vinyl Ether)

G

1644

Perfluoro

(Methyl Vinyl Ether)

G

1645

Permanganates, Inorganic, Aqueous Solution, N.O.S.

O

1646

Permanganates, Inorganic, N.O.S.

O

1647

Peroxides, Inorganic, N.O.S.

O

1648

Peroxyacetic Acid

T

1649

Persulphates, Inorganic, Aqueous Solution, N.O.S.

O

1650

Persulphates, Inorganic, N.O.S.

O

1651

Pesticide, Liquid, Toxic, Flammable, N.O.S.

T

1652

Pesticide, Liquid, Toxic, Flammable, N.O.S.

F

1653

Pesticide, Liquid, Toxic, N.O.S.

T

1654

Pesticide, Solid, Toxic, N.O.S.

T

1655

Pentanone,

2, -4, -Methyl

F
T
1656
Petroleum Crude Oil
F
1657
Petroleum Gases, Liquefied
G
1658
Phenacyl Bromide
T
1659
Phenetidines
T
1660
Phenol
T
1661
Phenol Solution
T
1662
Phenol, Molten
T
1663
Phenol, Solid
T
1664
Phenol,
2, 2-Thiobis (4 Chloro 6 Methyl Phenol)
T
1665
Phenol,
2, 2-Thiobis (4, 6-Dichloro)
T
1666
Phenol,
3-(1-Metnol Ethyl)-Methyl carbonate
T
1667
Phenolsulphonic Acid, Liquid
C
1668
Phenoxyacetic Acid Deriavative Pesticide, Liquid,Flammable, Toxic
F
1669
Phenoxyacetic Acid Deriavative Pesticide,Liquid, Toxic
T
1670
Phenoxyacetic Acid Deriavative Pesticide,Liquid, Toxic, Flammable
T
1671

Phenoxyacetic Acid Derivative Pesticide, Solid, Toxic

T

1672

Phenyl Chloroformate

T

1673

Phenyl Glycidyl Ether

F

T

1674

Phenyl Hydrazine Hydrochloride

T

1675

Phenyl Isocyanate

T

1676

Phenyl Mercury Acetate

T

1677

Phenyl Silatrane

T

1678

Phenyl Thiourea

T

1679

Phenylacetonitrile, Liquid

T

1680

Phenylacetyl Chloride

C

1681

Phenylcarbylamine Chloride

T

1682

Phenylene P-Diamine

T

1683

Phenylenediamines

T

1684

Phenylhydrazine

T

1685

Phenylmercuric Acetate

T

1686

Phenylmercuric Compound, N.O.S.

T

1687

Phenylmercuric Hydroxide

T

1688

Phenylmercuric Nitrate

T

1689

Phenylmercury Acetate

T

1690

Phenylphosphorus Dichloride

C

1691

Phenylphosphorus Thiodichloride

C

1692

Phenyl Trichlorosilane

C

1693

Phorate

T

1694

Phorothioc Acid, 00 Dimethyl S-(2-Methyl)

T

1695

Phosacetim

T

1696

Phosalone

T

1697

Phosaoetin

T

1698

Phosazetin

T

1699

Phosfolan

T

1700

Phosgene

G

1701

Phosgene

(Carbonyl Chloride)

F

T

1702

Phosmet

T

1703

Phosphamidon

T

1704

Phosphine

|

|

G

1705

Phosphine

(Hydrogen Phosphide)

F

|

T

1706

Phosphoric Acid

O

C

1707

Phosphoric Acid & Esters

C

T

1708

Phosphoric Acid Dimethyl (4-Methyl Thio) Phenyl

T

1709

Phosphoric Acid, Bromoethyl Bromo (2,2-Dimethylpropyl) Bromoethyl Ester

T

1710

Phosphoric Acid, Liquid/Solid

C

1711

Phosphorothioc Ethyl-Methyl Ester

C

1712

Phosphorothioic Acid, Methyl-Ethyl Ester

C

1713

Phosphorothioic Acid Methyl (Ester)

C

1714

Phosphorous

F

1715

Phosphorous Pentaoxide

F

O

1716

Phosphorous and Compounds

F

T

1717

Phosphorous Oxychloride

T

1718

Phosphorous Penta Chloride

T

I-

1719

Phosphorous Trichloride

T

1720

Phosphorus Acid

C

1721

Phosphorus Heptasulphide

F

1722

Phosphorus Oxybromide

C

1723

Phosphorus Oxybromide, Molten

C

1724

Phosphorus Oxychloride

C

1725

Phosphorus Pentabromide

C

1726

Phosphorus Pentachloride

C

1727

Phosphorus Pentafluoride, Compressed

G

1728

Phosphorus Pentasulphide

F

1729

Phosphorus Pentaoxide

C

1730

Phosphorus Sesquisulphide

F

1731

Phosphorus Tribromide

C

1732

Phosphorus Trichloride

T

1733

Phosphorus Trioxide

C

1734

Phosphorus Trisulphide

F

1735

Phosphorus, Amosphous

F

1736

Phosphorus, White or Yellow, Dry or UnderWater or in Solution

F

1737

Phosphorus, White, Molten

F

1738

Phthalic Anhydride

C

T

1739

Phylloquinone

T

1740

Physostigmine

T

1741

Physostigmine Salicylate (1:1)

|||

T

1742

Picolines

F

1743

Picric Acid (2, 4, 6-Trinitrophenol)

E

T

1744

Pine Oil

F

1745

Piperazine

C

1746

Piperdine

T

1747

Piperidine

C

1748

Plastics, Nitrocellulose-Based, Self-Heating, N.O.S.

F

1749

Platinous Chloride

T

1750

Platinum Tetrachloride

T

1751

P-Nitrophenol

T

1752

p-Nitrosodimethylaniline

F

1753

Polybrominated Biphenyls

T

1754

Polychlorinated Biphenyls

T

1755

Polyester Resin Kit

F

1756

Polyhalogenated Biphenyls, Liquid or Polyhalogenated Terphenyls, Liquid

T

1757

Polymeric Beads, Expandable

F

1758

Potassium

F

1759

Potassium Nitride

C

1760

Potassium Peroxide

F

C

1761

Potassium Silver Cyanide

T

1762

Potassium Arsenate

T

1763

Potassium Arsenite

T

1764

Potassium Bromate

O

1765

Potassium Chlorate

O

1766

Potassium Chlorate, Aqueous Solution

O

1767

Potassium Cuprocyanide

T

1768

Potassium Cyanide

T

1769

Potassium Dithionite (Potassium Hydrosulphite)

F

1770

Potassium Fluoride

T

1771

Potassium Fluoroacetate

T

1772

Potassium Fluorosilicate

T

1773

Potassium Hydrogen Sulphate

C

1774

Potassium Hydrogendifluoride

C

1775

Potassium Hydroxide

C

1776

Potassium Hydroxide, Solid

C

1777

Potassium Hydroxide, Solution

C

1778

Potassium Metavanadate

T

1779

Potassium Monoxide

C

1780

Potassium Nitrate

O

1781

Potassium Nitrate and Sodium Nitrite Mixture

O

1782

Potassium Nitride

O

C

1783

Potassium Nitrite

O

1784

Potassium Perchlorate

O

1785

Potassium Permanganate

O

1786

Potassium Peroxide

O

1787

Potassium Persulphate

O

1788

Potassium Phosphide

F

1789

Potassium Sulphide, Anhydrous or Potassium Sulphide

F

1790

Potassium Sulphide, Hydrated

C

1791

Potassium Superoxide

O

1792

Potassium Arsenite

T

1793

Powdered Metals and Mixtures

T

1794

Promurit

(1-(3,4-Dichlorophenyl)-3-Triazenethiocarboxamide)

T

1795

Propadiene, Stabilized

G

1796

Propane

G

1797

Propanesultone-1,

3

T

1798

Propanethiols

F

1799

Propargyl Alcohol

T

1800

Propargyl Bromide

T

1801

Propen-1,

-2-Chloro-1, 3, Diol-Diacetate

T

1802

Propen-2-Chloro 1, 3-Diou Diacetate

T

1803

Prophyl Alcohol

F

1804

Propylene Oxide

R

1805

Propiolactone Beta

R

1806

Propionic Acid

C

1807

Propionic Anhydride

C

1808

Propionitrile

F

T

1809

Propionitrile,

3-Chloro

T

1810

Propionyl Chloride

F

1811

Propiophenone,4-Amino

T

1812

Propyl Acetate-N

F

1813

Propyl Chloride

F

1814

Propyl Chloroformate

T

1815

Propyl Formates

F

1816

Propylamine

F

1817

Propylene

G

1818

Propylene Chlorohydrin

T

1819

Propylene Dichloride

T

1820

Propylene Glycol, Allyether

T

1821

Propylene Oxide

F

1822

Propylene Tetramer

F

1823

Propyleneamine

T

1824

Propyleneimine, Stabilized

F

1825

Propyltrichlorosilane

C

1826

Potassium Borohydride

F

1827

Puinone

T

1828

Pyrazoxon

T

1829

Pyrene

T

1830

Pyrethroid Pesticide, Liquid, Flammable, Toxic

F

1831

Pyrethroid Pesticide, Liquid, Toxic

T

1832

Pyrethroid Pesticide, Liquid, Toxic, Flammable

T

1833

Pyrethroid Pesticide, Solid, Toxic

T

1834

Pyridine

F

F

1835

Pyridine,

2-Methyl-3-Vinyl

T

1836

Pyridine,4-Nitro,

1-Oxide

O

T

|-

1837

Pyriminil

T

1838

Pyrophoric Liquid, Inorganic, N.O.S.

F

1839

Pyrophoric Liquid, Organic, N.O.S.

F

1840

Pyrophoric Metal, N.O.S. or Pyrophoric Alloy, N.O.S.

F

1841

Pyrophoric Organometallic Compound,Water-Reactive, N.O.S., Liquid

F

1842

Pyrophoric Solid, Inorganic, N.O.S.

F

1843

Pyrophoric Solid, Organic, N.O.S.

F

1844

Pyrosulphuryl Chloride

C

1845

Pyrrolidine

T

1846

Quinaliphos

T

1847

Quinoline

T

1848

Quinone

T

1849

Radioactive Material, Uranium Hexafluoride

Ra

1850

Radioactive Material, Uranium Hexafluoride, Fissile

Ra

1851

Rare Gases and Nitrogen Mixture, Compressed

G

1852

Rare Gases and Oxygen Mixture, Compressed

G

1853

Rare gases Mixture, Compressed

G

1854

Receptacles, Small, Containing Gas(Gas Cartridges)

G

1855

Refrigerant Gas R 404A

G

1856

Refrigerant Gas R 407A

G

1857

Refrigerant Gas R 407B

G

1858

Refrigerant Gas R 407C

G

1859

Refrigerating Machines

G

1860

Resin Solution

F

1861

Resorcinol

T

1862

Rhodium Trichloride

T

1863

Rockets

E

1864

Rubidium Hydroxide

C

1865

Rubidium Hydroxide Solution

C

1866
Salcomine
T
1867
Sarin
T
1868
Seed Cake
F
1869
Selenates or Selenites
T
1870
Selenic Acid
C
1871
Selenious Acid
T
1872
Selenium Compound, N.O.S.
T
1873
Selenium Disulphide
T
1874
Selenium Hexafluoride
T
G
1875
Selenium Oxychloride
C
1876
Self-Heating Liquid, Corrosive Inorganic, N.O.S.
F
1877
Self-Heating Liquid, Corrosive, Organic, N.O.S.
F
1878
Self-Heating Liquid, Inorganic, N.O.S.
F
1879
Self-Heating Liquid, Organic, N.O.S.
F
1880
Self-Heating Liquid, Toxic, Inorganic, N.O.S.
F
1881
Self-Heating Liquid, Toxic, Organic, N.O.S.
F
1882
Self-Heating Solid, Corrosive, Organic, N.O.S.

F
1883
Self-Heating Solid, Corrosive, Inorganic, N.O.S.
F
1884
Self-Heating Solid, Inorgarc, N.O.S.
F
1885
Self-Heating Solid, Organic, N.O.S.
F
1886
Self-Heating Solid, Oxidizing, N.O.S.
F
1887
Self
-Heating Solid, Toxic, Inorganic, N.O.S.
F
1888
Self
-Heating Solid, Toxic, Organic, N.O.S.
F
1889
Self
-Reactive Liquid Type B
F
1890
Self-Reactive Liquid Type B, TemperatureControlled
F
1891
Self-Reactive Liquid Type C
F
1892
Self-Reactive Liquid. Type C, TemperatureControlled
F
1893
Self
-Reactive Liquid Type D
F
1894
Self-Reactive Liquid Type D, TemperatureControlled
F
1895
Self-Reactive Liquid Type E
F
1896
Self-Reactive Liquid Type E, TemperatureControlled
F
1897
Self-Reactive Liquid Type F
F
1898

Self-Reactive Liquid Type F, TemperatureControlled

F

1899

Self-Reactive Solid Type B

F

1900

Self-Reactive Solid Type B, TemperatureControlled

F

1901

Self-Reactive Solid Type C

F

1902

Self-Reactive Solid Type C, TemperatureControlled

F

1903

Self-Reactive Solid Type D

F

1904

Self-Reactive Solid Type D, TemperatureControlled

F

1905

Self-Reactive Solid Type E

F

1906

Self-Reactive Solid Type E, TemperatureControlled

F

1907

Self-Reactive Solid Type F

F

1908

Self-Reactive Solid Type F, TemperatureControlled

F

1909

Semicarbazide Hydrochloride

T

I-

1910

Silane

(4-Amino Butyl) Diethoxy-Meth

T

1911

Silane, Compressed

G

1912

Silicon Tetrachloride

C

1913

Silicon Tetrafluoride, Compressed

G

1914

Silver Arsenite

T
1915
Silver Cyanide
T
1916
Silver Nitrate
O
1917
Silver Picrate, Wetted
F
1918
Sludge Acid
C
1919
Soda Lime
C
1920
Sodium
F
1921
Sodium Hydrosulphide
C
1922
Sodium Acetoxy Triphenyl
T
1923
Sodium Aluminate Solution
C
1924
Sodium Aluminate, Solid
C
1925
Sodium Aluminium Hydride
F
1926
Sodium Ammonium Vanadate
T
1927
Sodium Anthra-Quinone-I-Sulphonate
T
1928.
Sodium Arsanilate
T
1929
Sodium Arsenate
T
1930
Sodium Arsenite
T
1931
Sodium Arsenite, Aqueous Solution

T-
1932
Sodium Arsenite, Solid
T
1933
Sodium Azide
T
1934
Sodium Borohydride and Sodium Hydroxide Solution
C
1935
Sodium Bromate
O
1936
Sodium Cacodylate
T
1937
Sodium Chlorate
E
O
R
1938
Sodium Chlorate, Aqueous Solution
O
1939
Sodium Chlorite
O
1940
Sodium Chloroacetate
T
1941
Sodium Cuprocyanide, Solid
T
1942
Sodium Cuprocyanide, Solution
T
1943
Sodium Cyanide
T
1944
Sodium Dinitro-O-Cresolate
E
1945
Sodium Dinitro-O-Cresolate Wetted
F
1946
Sodium Dithionite (Sodium Hydrosulphite)
F
1947
Sodium Fluoride
T

1948

Sodium Fluoroacetate

T

1949

Sodium Fluoro-Acetate

T

1950

Sodium Fluorosilicate

T

1951

Sodium Hydride

F

1952

Sodium Hydrogendifluoride

C

1953

Sodium Hydrosulphide

F

1954

Sodium Hydroxide

C

1955

Sodium Hydroxide, Solution

C

1956

Sodium Hydroxide, Solid

C

1957

Sodium Methyrate

F

T

1958

Sodium Monoxide

C

1959

Sodium Nitrate

O

T

1960

Sodium Nitrate and Potassium Nitrate Mixture

O

1961

Sodium Nitrite

O

1962

Sodium Pentachlorophenate

T

1963

Sodium Pentachloro-Phenate

T

1964

Sodium Perchlorate

O

1965

Sodium Permanganate

O

1966

Sodium Peroxide

O

1967

Sodium Peroxoborate, Anhydrous

O

1968

Sodium Persulphate

O

1969

Sodium Phosphide

F

1970

Sodium Picramate

E

T

1971

Sodium Picramate, Wetted

F

1972

Sodium Selenate

T

1973

Sodium Selenite

T

1974

Sodium Sulphide

O

C

1975

Sodium Sulphide, Anhydrous or Sodium Sulphide

F

1976

Sodium Sulphide, Hydrated

C

1977

Sodium Superoxide

O

1978

Sodium Tellorite

C

1979

Sodiumanthra-Qunone-I-Sulphonate

C

1980

Solids containing Corrosive Liquid, N.O.S.

C

1981

Solids containing Flammable Liquid, N.O.S.

F

1982

Solids containing Toxic Liquid, N.O.S.

T

1983

Sopropyl

T

1984

Stannane Acetoxy Triphenyl

T

1985

Stannic Chloride Pentahydrate

C

1986

Stannic Chloride, Anhydrous

C

1987

Stannic Phosphides

F

1988

Stibine

G

1989

Stibine

(Antimony Hydride)

T

1990

Strontium Arsenite

T

1991

Strontium Chlorate

O

1992

Strontium Nitrate

O

1993

Strontium Perchlorate

O

1994

Strontium Peroxide

O

1995

Strontium Phosphide

F

1996

Strychnine or Strychnine Salts

T

1997

Strychnine Sulphate

T

1998

Styphinic Acid (2,4, 6-Trinitroresorcinol)

T

1999

Styrene

F

2000

Styrene Monomer, Stabilized

F

2001

Styrene,

1, 1, 2, 2-Tetrachloroethane

F

T

2002

Substituted Nitrophenol Pesticide, Liquid, Flammable

F

2003

Substituted Nitrophenol Pesticide, Liquid, Toxic

T

2004

Substituted Nitrophenol Pesticide, Liquid, Toxic, Flammable

T

2005

Substituted Nitrophenol Pesticide, Solid, Toxic

T

2006

Sulfotep

T

2007

Sulotep

T

2008

Sulphamic Acid

C

2009

Sulphotec

C

2010

Sulphoxide,

3-Chloropropyl Octyl

T

2011

Sulphur Chlorides

C

2012

Sulphur Dichloride

T

2013

Sulphur Dioxide

T

G

2014

Sulphur Hexafluoride

G

2015

Sulphur Monochloride

T

2016

Sulphur Tetrafluoride

G

2017

Sulphur Trioxide

C

2018

Sulphur Trioxide, Stabilized

C

2019

Sulphur, Molten

F

2020

Sulphuric Acid

C

2021

Sulphuric Acid or Battery Fluid, Acid

C

2022

Sulphuric Acid, Fuming

C

2023

Sulphuric Acid, Spent

C

2024

Sulphurous Acid

C

2025

Sulphuryl Chloride

C

2026

Sulphuryl Fluoride

G

2027

Suphuric Acid

C

T

2028

Tars, Liquid

F

2029

T-Chloro 1, 2,2,2-

G

2030

Tear Gas Candles

T

2031

Tellurium Compound, N.O.S.

T

2032

Tellurium Hexafluoride

T

G

2033

Tellurium Hexafluoride

T

2034

Tellurium

(Powder)

T

2035

Tepp

(Tetraethyl Pyrophosphate)

T

2036

Terbufos

T

2037

Terpene Hydrocarbons, N.O.S.

F

2038

Terpinolene

F

2039

Tert Buty Peroxyiso-Butyrate

T

2040

Tert Butyl Peroxy Carbonate

T

2041

Tert Butyl Peroxy Isopropyl

T

2042

Tert Butyl Peroxyacetate (Conc>-70%)

T

2043

Tert-Butyl Alcohol

T

2044

Tert-Butyl Anate

T

2045

Tert-Butyl Hypochlorite

F

2046

Tert-Butylcyclohexyl Chloroformate

T

2047

Tetra Hydrofuran

F

2048

Tetra Methyl Lead

T

2049

Tetra Nitromethane

T

2050

Tetrabromobisphenol-A

T

2051

Tetrabromoethane

T

2052

Tetrachloro 2,2, 5, 6, 2, 5-Cyclohexadiene-1, 4-Dion

T

2053

Tetrachlorodibenzo-P-Dioxin,
-2,3,7,8 (TCDD)

T

2054

Tetrachloroethane

T

2055

Tetrachoroethylene

T

2056

Tetractyle Lead

T

2057

Tetraethyl Dithiopyrophosphate

T

2058

Tetraethyl Lead

T

2059

Tetraethyl Silicate

F

2060

Tetraethylenepentamine

C

2061

Tetrafluoroethane

T

2062

Tetrafluoroethylene, Stabilized

G

2063

Tetrafluoromethane Compressed (Refrigerant Gas R 14, Compressed)

G

2064

Tetrafluoroethylene

T

2065

Tetrahydrofuran

F

T

2066

Tetrahydrofurfurylamine

F

2067

Tetrahydrophthalic Anhydrides

C

2068

Tetrahydrothiophene

F

2069

Tetramethyl Lead

T

2070

Tetramethylammonium Hydroxide

C

2071

Tetramethylene Disulphotetramine

T

2072

Tetramethylsilane

F

2073

Tetranitroaniline

E

2074

Tetranitromethane

O

T

2075

Tetrapropyl Orthotitanate

F

2076

Tetrazol-1-Acetic Acid

E

2077

Thallium and Compounds

T

2078

Thallium Carbonate

T

2079

Thallium Chlorate

O

2080

Thallium Compound, N.O.S.

T

2081

Thallium Nitrate

T

2082

Thallic Oxide

T

2083

Thallium Sulphate

T

2084

Thallous Chloride

T

2085

Thallous Malonate

T

2086

Thallous Sulphate

T

2087

Thinoyl Chloride

T

2088

Thioacetic Acid

F

2089

Thioactic Acid

T

2090

Thiocarbamate Pesticide, Liquid, Flammable Toxic

F

2091

Thiocarbamate Pesticide, Liquid, Toxic

T

2092

Thiocarbamate Pesticide, Liquid, Toxic, Flammable

T

2093

Thiocarbamate Pesticide, Solid, Toxic

T

2094

Thiocarbazide

T

2095

Thiocynamic acid, 2-(Benzothiazolyethio) Methyl

T

2096

Thiofamox

T

2097

Thioglycol

T

2098

Thioglycolic Acid

C

2099

Thiometon

T

2100

Thionazin

T

2101

Thionyl Chloride

C

2102

Thiophene

F

2103

Thiophenol

T

2104

Thiophosgene

T

2105

Thiophosphoryl Chloride

C

2106

Thiosemicarbazide

T

2107

Thiourea

(2-Methyl Phenyl)

C

2108

Thiourea Dioxide

F

2109

Thiourea

(2-Chloro-Phenyl)

C

2110

Thiourea

(2-Methyl-I-3-Dithiolane)

C

2111

Thiram

T
2112
Tirpate
T
2113
Tirpate(2,4-Dimethyl-I-3-Dithiolane)
T
2114
Titanium Disulphide
F
2115
Titanium Hydride
F
2116
Titanium Powder
T
2117
Titanium Powder, Dry
F
2118
Titanium Sponge Granules or Titanium SpongePowders
F
2119
Titanium Tetrachloride
C
2120
Titanium Tetra-Chloride
T
2121
Titanium Trichloride, Pyrophoric or TitaniumTrichloride Mixture,Pyrophoric
F
2122
Titanium Trichlorode Mixture
C
2123
Toluene
F
T
2124
Toluene 2, 6-Diisocyanate
T
2125
Toluene 2, 4-Diisocyanate
T
2126
Toluene Diisocyanate
T
2127
Toluene-2,
-4-Ditsocynate
T

2128

Toluene-2-4-Diisocyanate

T

2129

Toluidine-O

T

2130

Toluidines,Liquid/Solid

T

2131

Toxic Liquid, Corrosive, Inorganic, N.O.S.

T

2132

Toxic Liquid, Flammable, Organic, N.O.S.

T

2133

Toxic Liquid, Inorganic, N.O.S.

T

2134

Toxic Liquid, Organic, N.O.S.

T

2135

Toxic Liquid, Oxidizing, N.O.S.

T

2136

Toxic Liquid, Water-Reactive, N.O.S.

T

2137

Toxic Solid, Corrosive, Inorganic, N.O.S.

T

2138

Toxic Solid, Corrosive, Organic, N.O.S.

T

2139

Toxic Solid, Flammable, Organic, N.O.S.

T

2140

Toxic Solid, Inorganic, N.O.S.

T

2141

Toxic Solid, Organic, N.O.S.

T

2142

Toxic Solid, Oxidizing, N.O.S.

T

2143

Toxic Solid, Self-Heating, N.O.S.

T

2144

Toxic Solid, Water Reactive, N.O.S.

T

2145

Toxins, Extracted From Living Sources, Liquid/Solid N.O.S.

T

2146

Trans-1,

4-Di Chloro-Butene

T

2147

Tri Nitro Anisole

T

2148

Tri Orthocresyl Phosphate

T

2149

Tri

(Cyclohexyl) Methylstannyl 1, 2,4 Triazole

T

2150

Tri-I

(cyclohexyl) Stannyl-1-H-1, 2, 4-Triazole

T

2151

Triallyl Borate

T

2152

Triallylamine

F

2153

Triamino,

-1, 3, 5, 2, 4, 6-Trinitro-Benzene

E

T

2154

Triaminotrinitrobenzene

T

2155

Triazine Pesticide, Liquid, Flammable, Toxic

F

2156

Triazine Pesticide, Liquid, Toxic

T

2157

Triazine Pesticide, Liquid, Toxic, Flammable

T

2158

Triazine Pesticide, Solid, Toxic

T

2159

Tribromophenol 2,4,6

T

2160

Tributylamine

T

2161

Tributylphosphane

F

2162

Trichloro

(Chloromethyl) Silane

T

2163

Trichloro Acetyl Chloride

T

2164

Trichloro Chloromethyl Silane

T

2165

Trichloro Ethane

T

2166

Trichloro Napthalene

T

2167

Trichloroacetic Acid

C

2168

Trichloroacetic Acid Solution

C

2169

Trichloroacetyl Chloride

C

2170

Trichlorobenzenes, Liquid

T

2171

Trichlorobutene

T

2172

Trichlorodethylene

T

2173

Trichlorodichlorophenylsilane

T

2174

Trichloroethane,

1, 1,-1

T

2175

Trichloroethyl Silane

T

2176

Trichloroethylene

T

2177

Trichloroisocyanuric Acid, Dry

O

2178

Trichloromethane Sulphenyl Chloride

T

2179

Trichloronate

T

2180

Trichlorophenol 2,3,6

T

2181

Trichlorophenol 2, 4, 5

T

2182

Trichlorophenol 2,2,6

T

2183

Trichlorophenol,
2,4,5

T

2184

Trichlorophenyl Silane

T

2185

Trichlorophon

T

2186

Trichlorosilane

F

2187

Tricresyl Phosphate

O

T

2188

Triethoxy Silane

T

2189

Triethyl Phosphite

F

2190

Triethylamine

F

C

2191

Triethylene Melamine

T

2192

Triethylenetetramine

C

2193

Trifluoroacetic Acid

C

2194

Trifluoroacetyl Chloride

G

2195

Trifluoromethane

(Refrigerant Gas R 23)

G

2196

Trifluoromethane, Refrigerated Liquid

G

2197

Trisobutylene

F

2198

Trimethyl Borate

F

2199

Trirnethyl Chlorosilane

| T

2200

Trimethyl Phosphite

F

||-

2201

Trimethyl Propane Phosphite

T

2202

Trimethyl Tin Chloride

T

2203

Trimethylacetyl Chloride

T

2204

Trimethylarnine, Anhydrous

G

2205

Trimethylamine, Aqueous

F

2206

Trimethylchlorosilane

F

2207

Trimethylcyclohexylamine

C

2208

Trimethylhexamethylene Diisocyanate

T

2209

Trimethylhexamethylene-Diamines

C

2210

Trimethylpropane Phosphite

T

2211

Trinitro Aniline

E

T

2212

Trinitro Benzene.

E

2213

Trinitro Benzoic Acid

C

2214

Trinitro-in-cresol

C

2215

Trinitro Phenetole

C

2216

Trinitroaniline

T

2217

Trinitroaniline

(Picramide)

E

2218

Trinitroanisole,

-2,4,6

E

T

2219

Trinitroanisole

E

2220

Trinitroanisole,

2, 2, 4, 6

T

2221

Trinitrobenzene

E

T

2222

Trinitrobenzene, Wetted

F

2223

Trinitrobenzenesulphonic Acid

E

2224

Trinitrobenzoic Acid

E

T

2225

Trinitrobenzoic Acid, Wetted

F

2226

Trinitrochlorobenzene

(Picryl Chloride)

E

2227

Trinitrochlorobenzene

(Picryl Chloride)

E

2228

Trinitrocresol

E

T

2229

Trinitroresorcinol,

2, 4, 6 (Styphnic Acid)

T

2230

Trinitrofluorenone

E

2231

Trinitro-M-Cresol

E

2232

Trinitronaphthalene

E

2233

Trinitrophenetole

E

2234

Trinitrophenetole,

2,4,6

E

T

2235

Trinitrophenol, Wetted

F

2236

Trinitrophenylmethylnitramine

(Tetryl)

E

2237

Trinitroresorcinol

(Styphnic Acid)

E

2238

Trinitrosorcinol,
-2,4,6 (Styphnic Acid)

E

T

2239

Trinitrotoluene

E

2240

Trinitrotoluene
(TNT)

E

2241

Trinitrotoluene, Wetted

F

2242

Triorthocresyl Phosphate

T

2243

Triplate
(2,4-Dimethyl-1, 3-Dithiolane)

T

2244

Triphenyl Tin Chloride

T

2245

Tripropylamine

F

2246

Tripropylene

F

2247

Tris
(1-Aziridinyl) Phosphine Oxide Solution

T

2248

Tris
(2-Chloroethyl) Amine

T

2249

Trisopropyl Borate

F

2250

Tungsten Hexafluoride

G

2251

Turpentine

F

2252

Uranium and Compounds

T

2253

Urea Hydrogen Peroxide

O

2254

Urea Nitrate

E

2255

Urea Nitrate, Wetted

F

2256

Valeraldehyde

F

2257

Valeryl Chloride

C

2258

Valino Mycin

T

2259

Vanadium and Compounds

T

2260

Vanadium Compound, N.O.S.

T

2261

Vanadium Oxytrichloride

C

2262

Vanadium Pentaoxide

T

2263

Vanadium Pentoxide

T

2264

Vanadium Tetrachloride

C

2265

VanadiumTrichloride

C

2266

Vanadyl Sulphate

T

2267

Vinyl Acetate Monomer

T

2268

Vinyl Bromide

T

2269

Vinyl Bromide, Stabilized

G

2270

Vinyl Butyrate, Stabilized

F

2271

Vinyl Chloride

E

T

2272

Vinyl Chloride, Stabilized

G

2273

Vinyl Chloroacetate

T

2274

Vinyl Fluoride

T

2275

Vinyl Isobutyl Ether, Stabilized

F

2276

Vinyl Methyl Ether, Stabilized

G

2277

Vinyl Norbornene

T

2278

Vinyl Toluene

E

T

2279

Vinylcyclohexen Dioxide

| T

2280

VinylideneChloride

T

2281

Vinylidene Chloride, Stabilized

F

2282

Vinylpyridines, Stabilized

T

2283

Vinyltoluenes, Stabilized

F

2284

Vinyltrichlorosilane, Stabilized

F

2285

Vutyl Amine Tert

T

2286

Warfarin

T

2287

Warfarin Sodium

T

2288

Water-Reactive Liquid, N.O.S.

E

F

O

R

C

T

2289

Water-Reactive Solid, N.O.S.

E

F

O

R

C

T

2290

White Asbestos

T

2291

Xanthates

F

2292

Xenon, Compressed

G

2293

Xenon, Refrigerated Liquid

G

2294

Xylene

F

T

2295

Xylene Dichloride

T

2296

Xylenes

F

2297

Xylenols

T

2298

Xylidine

T

2299

Xylidines, Liquid/Solid

T

2300

Xylyl Bromide

T

2301

Zinc Ammonium Nitrite

O

2302

Zinc and Compounds

T

2303

Zinc Arsenate, Zinc Arsenite or Zinc ArsenateAnd Zinc Arsenite Mixture

T

2304

Zinc Bromate

O

2305

Zinc Chlorate

O

2306

Zinc Chloride Solution

C

2307

Zinc Cyanide

T

2308

Zinc Dichloropentanitrile

T

2309

Zinc Dithionite (Zinc Hydrosulphite)

T

2310

Zinc Fluorosilicate

T

2311

Zinc Phosphide

F

2312

Zinc Resinate

F

2313

Zirconium and Compounds

F

2314

Zirconium Nitrate

O

2315

Zirconium Picramate

E

2316

Zirconium Powder, Dry

F
2317
Zirconium Scrap
F
2318
Zirconium Tetrachloride
C
2319
Zirconium, Dry
F
T]
Chapter VI
Control Of Traffic
138.
Signals and additional safety measures for [motor vehicle]
[Substituted by GSR 214(E), dated 18.3.1999, for 'motor cycle'(w.e.f. 18.3.1999).]
.

(1)
The driver of a [motor vehicle]
[Substituted by GSR 214(E), dated 18.3.1999, for 'motor cycle'(w.e.f. 18.3.1999).]
shall make such signals and on such occasions as are specified in the regulations made under section 118.

(2)
The driver of a motor cycle shall, in addition to the safety measures mentioned in sub-section (1) of section 128, comply with the requirements of rule 123.

[(3) In a motor vehicle, in which seat-belts have been provided under sub-rule (1) or sub-rule(1-A) of rule 125 or rule 125-A, as the case may be, it shall be ensured that the driver, and the person seated in the front seat or the persons occupying front facing rear seats, as the case may be, wear the seat belts while the vehicle is in motion.]
[Inserted by GSR 214(E), dated 18.3.1999 (w.e.f. 18.3.1999).]

(4)
On and after expiry of one year from the date of commencement of the Central Motor Vehicles (Amendment) Rules, 1999, the driver of every vehicle shall ensure that the following items are carried in the vehicle, namely:

(a)
[In case of vehicles other than motorcycles, a set of spare bulbs for head lamps and fuses, and a ready-for-use spare wheel:

[Substituted by Notification No. G.S.R. 625 (E) dated 8.8.2012 (w.e.f. 2.6.1989)]

Provided that in case of M1 and N1 categories of vehicles, use of temporary use spare wheel shall be permitted and the provision of ready to use spare wheel shall not be mandatory, if such vehicles are fitted with Run Flat Tyres as standard.]

(b)
tool kit as prescribed by the manufacturer;

(c)
triangles of size 150 mm with a red reflecting surface as per IS: 83391993 specified by the Bureau of Indian Standards, for keeping in front and rear of the vehicle in case the vehicle is stranded on the road (applicable to vehicles other than two and three-wheelers); as specified below, namely:

one triangle in case of four-wheelers with GVW not exceeding 7.5 tons;

two triangles in case of four-wheelers with GVW exceeding 7.5 tons:

[Provided that in case of vehicles manufactured on and after 1st January, 2003, the triangles of size and specification shall conform to AIS : 022-2001, as maybe amended from time to time, till such time as corresponding Bureau of Indian Standards specifications are notified:]

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

[Provided further that in addition, [M3]

[Proviso inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.3.2006).]

category of vehicles shall also be required to install retro-reflective triangle complying to AIS:022:2001 as amended from time to time, excluding the requirements specified in clauses 7.2, 7.3, 7.4, 7.7, 8.1.2 and 5.0, 6.0, 11.0 of Annexure 4 of the said standard. The colour of the triangle fitted in the front of the vehicle shall be white and that of rear shall be red. The location of both the triangles shall be at least one meter above the ground level at the front and rear, preferably at the centre of the vehicle. For the purposes of white colour warning triangle, the word red shall be substituted by word white, wherever applicable in AIS:022:2001. The colour requirements of white retro-reflective portion shall be as per clause 8.5 of AIS:057 and white fluorescent material shall be as per clause 7.1 of ISO:7591-82(E);]

(d)

first-aid kit containing a tube of antiseptic cream containing 0.5% of Centrimide B.P. in a non-greasy base, sterilise addressing, sterilised elastic plaster, waterproof plaster, gauze and elastic bandage for wounds and burns;

(e)

number of chock blocks for four-wheelers as specified below, namely:

one chock block in case of four-wheelers with GVW exceeding 4 tons and less than 7.5 tons;

two chock blocks in case of 4-wheelers with GVW exceeding 7.5 tons;

The vehicle manufacturer shall ensure that the above items are supplied at the time of first sale of vehicle;

(f)

[at the time of purchase of the two wheeler, the manufacturer of the two wheeler shall supply a protective headgear conforming to specifications prescribed by the Bureau of Indian Standards under the Bureau of Indian Standards Act, 1986 (63 of 1986):

[Clause (f) inserted by GSR 589(E), dated 16.9.2005 (w.e.f. 16.3.2006).]

Provided that these conditions shall not apply to category of persons exempted in terms of section 129 and the rules made thereunder by the concerned State Government.]

(5)

Halogen bulbs with P45t cap shall not be used for headlights on all vehicles. Wattage of halogen bulbs shall not exceed 70/75 watts for 24 volts and 60/65 for 12 volts systems.]

(6)

[On and after 1st April 2016, the driver of motor vehicle of M1 category, manufactured on and after 1st October 2014, excluding transport vehicles and special purpose vehicles shall ensure that a child, up to age of twelve years, carried in the vehicle is seated in an appropriate child restraint system conforming to AIS:072-2009.]

[Inserted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

[138A. Fitment of Radio frequency Identification Tag.

[Inserted by Notification No. G.S.R. 207 (E) dated 8.4.2013 (w.e.f. 2.6.1989)]

- Categories M and N motor vehicles manufactured on or after six months from the date of commencement of the Central Motor Vehicles (First Amendment) Rules, 2013 shall be fitted with Radio Frequency Identification Tag having such specifications as may be determined by the Central Government:

Provided that Radio Frequency Identification Tag in case of vehicles which are sold in the form of drive-away-chassis, shall be installed at the top centre of the windshield of the vehicle by the builder of the body on the drive-away chassis at the time of providing the windshield.]

139.

[Production of license and certificate of registration.

[Substituted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000). Earlier Rule 138 was substituted by GSR 684(E), dated 5.10.1999 (w.e.f. 22.10.1999).]

- The driver or conductor of a motor vehicle shall produce certificate of registration, insurance, fitness and permit, the driving license and any other relevant documents on demand by any police officer in uniform or any other officer authorized by the State Government in this behalf, and if any or all of the documents are not in his possession, he shall produce in person an extract or extracts of the documents duly attested by any police officer or by any other officer or send it to the officer who demanded the documents by registered post within 15 days from the date of demand.]

Chapter VII

Insurance Of Motor Vehicles Against Third Party Risks

140.

Definitions.

- In this Chapter, unless the context otherwise requires,

- (i)
accounting year means the year commencing on the first day of April, and ending with the 31st day of March of the following year;
- (ii)
approved list means the list of foreign insurers and their guarantors maintained by the Central Government under these rules;
- (iii)
Authority means the Central Government or a State Government or any local authority or any State Transport Undertaking, motor vehicles owned by whom have been exempted from the compulsory insurance under sub-section (2) of section 146;
- (iv)
bank means a company which accepts, for the purpose of lending or investment, deposits of money from the public repayable on demand or otherwise, and withdrawal by cheque, draft, order or otherwise;
Explanation. - Any company which is engaged in the manufacture of goods or carries on any trade and which accepts deposits of money from the public merely for the purpose of financing its business as such manufacturer or trader shall not be deemed to be a bank within the meaning of this clause;
- (v)
certificate of foreign insurance means a certificate issued by a foreign insurer in Form 57 in compliance with these rules;
- (vi)
foreign insurer means a person or firm carrying on the business of insurance incorporated or domiciled outside India and not registered under the Insurance Act, 1938 (
- 4 of 1938
-);
- (vii)
fund means the fund established under rule 151;
- (viii)
Government security means a Government security as defined in the Public Debt Act, 1944 (
- 18 of 1944
-);
- (ix)
guarantor means an insurer who has guaranteed a foreign insurer in pursuance of these rules, and guarantee, guaranteed and guaranteeing have corresponding meanings;
- (x)
visitor means a person bringing a motor vehicle into India and making only a temporary stay therein not extending to a continuous period of more than one year.

Inland insurance

141.

Certificate of insurance.

- An authorized insurer shall issue to every holder of a policy of insurance, a certificate of insurance in Form 51 in respect of each such vehicle.

142.

Cover notes.

(1)

Every cover note issued by an authorized insurer shall be in Form 52.

(2)

A cover note referred to in sub-rule (1) shall be valid for a period of sixty days from the date of its issue and the insurer shall issue a policy of insurance before the date of expiry of the cover note.

143.

Issue of certificates and cover notes.

- Every certificate of insurance or cover note issued by an insurer in compliance with the provisions of this Chapter shall be duly authenticated by such person as may be authorized by the insurer.

144.

Transfer of certificate of insurance.

- When the ownership of a motor vehicle covered by a valid insurance certificate is transferred to another person together with the policy of insurance relating thereto the policy of insurance of such vehicle shall automatically stand transferred to that other person from the date of transfer of ownership of the vehicle and the said person shall within fourteen days of the date of transfer intimate to the authorized insurer who has insured the vehicle, the details of the registration of the vehicle, the date of transfer of the vehicle, the previous owner of the vehicle and the number and date of the insurance policy so that the authorized insurer may make the necessary changes in his record.

145.

Exclusion of advertising matter.

- No certificate of the insurance or cover note issued in pursuance of Chapter XI of the Act and of this Chapter shall contain any advertising matter either on the face or on the back thereof.

146.

Certificates or cover notes lost, destroyed, torn, soiled, defaced or mutilated.

(1)

Where the holder of a policy

(a)

lodges with an authorized insurer a declaration in which he declares that a certificate of insurance or cover note issued to him by such insurer has been lost, destroyed, torn, soiled, defaced or mutilated and sets out full particulars of the circumstances connected with the loss or destruction of the certificate or cover note and the efforts made to find it; or

(b)

returns to the authorized insurer the certificate of insurance or cover note issued to him by such insurer in a torn, soiled, defaced or mutilated condition; and

(c)

pays to the insurer a fee of rupees twenty in respect of each such certificate or cover note, the authorized insurer shall, if satisfied that such certificate or cover note has been lost or destroyed and that all reasonable efforts have been made to find it, or that it has been destroyed or is soiled, defaced or mutilated, as the case may be, issue in lieu thereof a duplicate certificate of insurance or cover note with the word Duplicate prominently endorsed to the effect.

(2)

When a duplicate certificate or cover note has been issued in accordance with the provisions of sub-rule (1) on representation that a certificate or cover note has been lost, and the original certificate or cover note is afterwards found by the holder, the original certificate or cover note, as the case may be, shall be surrendered to the insurer.

147.

Records to be maintained by authorized insurers.

- Every authorized insurer shall keep a record of the following particulars in respect of every policy of insurance issued by him for a period of five years, namely:

(i)

full name and address of the person to whom the policy is issued;

(ii)

in the case of a policy relating to a specified motor vehicle, the registration mark and the number of such vehicle and in other cases, description of the vehicle covered;

(iii)

the date on which the policy of insurance comes into force and the date of its expiry;

(iv)

the conditions subject to which the persons or classes of persons specified in the policy of insurance will be indemnified;

(v)

the number and date of issue of every certificate of insurance or cover note issued in connection with the policy of insurance;

(vi)

the date, if any, on which any duplicate certificate of insurance or cover note was issued;

(vii)

whether, after the issue of duplicate, the original certificate of insurance was found and subsequently surrendered to the insurer and if so, on which date.

148.

Records of exempted vehicles.

(1)

In the case of a motor vehicle owned by any of the authorities specified in sub-section (2) of section 146 as also in the case of motor vehicles exempted under sub-section (3) of section 146, a certificate in Form 53 signed by a person authorized in that behalf by such authorities may be produced in evidence that the motor vehicle is not being driven in contravention of section 146.

(2)

The authority referred to in sub-section (2) or exempted under sub-section (3) of section 146 shall keep a record of the motor vehicles owned by it in respect of which a policy of insurance has not been obtained and of any certificates issued by it under these provisions in respect of such vehicles, and of the names and addresses of the persons to whom such certificates have been issued and of the cancellation of any such certificates.

149.

Supply of information.

- Any person, authority or authorized insurer required under the provisions of this Chapter to keep records of documents shall furnish on request without any charge any particulars thereof to the Central Government or a State Government or to any police officer authorized in this behalf by the State Government.

150.

Furnishing of copies of reports to Claims Tribunal.

(1)

The police report referred to in sub-section (6) of section 158 shall be in Form 54.

(3)

A registering authority or a police officer who is required to furnish the required information to the person eligible to claim compensation under section 160, shall furnish the information in Form 54, within seven days from the date of receipt of the request and on payment of a fee of rupees ten.

151.

Establishment of fund.

(1)

Each of the authorities referred to in sub-section (3) of section 146 shall establish a fund for meeting any liability arising out of the use of any motor vehicle of that authority or any person in its employment may incur to third parties including liability arising under the Workmens Compensation Act, 1923(8 of 1923).

152.

Amount of the fund.

(1)

The fund shall be established with an initial amount of not less than rupees five lakhs and the said amount shall be kept in deposit with a bank or the Government.

(2)

Subject to the provisions of sub-rule (3), the authority shall pay into the fund at the beginning of each accounting year in respect of its vehicles in running condition a sum of not less than rupees two hundred per vehicle.

Explanation. - In this sub-rule vehicles in running condition means all the vehicles of the authority which are expected to be in operation at any time during the accounting year.

(3)

When the fund exceeds rupees twenty lakh or rupees two thousand and five hundred per vehicle for the entire fleet of vehicle, whichever is less, annual payment referred in sub-rule (2) shall cease provided that if thereafter the amount at the credit of the fund falls below rupees twenty lakhs or rupees two thousand and five hundred per vehicle for the entire fleet of vehicles, whichever is less, such annual payment shall again be resumed:

Provided that if any authority other than the Central Government is of opinion that the amount of rupees twenty lakhs or

rupees two thousand and five hundred per vehicle for the entire fleet of vehicles, whichever is less, is not adequate, it may, with the previous approval of the Central Government continue the annual payment beyond rupees twenty lakhs or rupees two thousand and five hundred per vehicle, as the case may be.

153.

Investment of the fund.

- From the amount at the credit of the fund the authority shall keep and maintain a cash deposit of not less than rupees fifty thousand in the bank and the rest of the amount at the credit of the fund shall be invested in Government securities.

154.

Securities held as a deposit in the fund.

(1)

All Government securities in which the fund is invested shall be transferred to the bank by the authority.

(2)

It shall be competent for the authority at any time to exchange the Government securities for cash or for other Government securities of equal or greater market value, or both, and the bank shall carry out the instructions issued by the authority for such exchange after charging the usual commission to the authority. The securities so exchanged shall also be transferred to the bank.

155.

Deposit procedure.

(1)

As soon as the fund is established, the bank shall send to the authority a statement specifying the assets held by it on behalf of the authority and shall also send a copy thereof to the Central Government in the Ministry of Surface Transport or the State Government concerned, as the case may be.

(2)

The statement referred to in sub-rule (1) shall be sent in the same manner and to the same authorities whenever there is a change in the assets of the authorities held by the bank.

156.

Interest on deposits.

- Interest realised on each deposit or the securities held in the fund shall be paid by the bank to the authority.

157.

Withdrawal.

(1)

No amount shall be withdrawn from the fund except for the purpose of meeting any liability arising out of the use of any motor vehicle of the authority which the authority or any person in the employment of the authority may incur to third parties including liability arising under the Workmen's Compensation Act, 1923 (8 of 1923).

(2)

The authority shall, subject to such conditions and restrictions as it may impose in this behalf, authorise one of its officers to draw money from the fund for the purpose mentioned in sub-rule (1).

(3)

A copy of the authorisation referred to in sub-rule (2) duly authenticated by a competent officer of the authority shall be sent to the bank which shall permit withdrawal only by the officer named in such authorisation subject to the conditions and restrictions contained therein.

158.

Settlement of claims.

- The authority shall comply with such directions as the Central Government or the State Government, as the case may be, may, from time to time issue, with respect to the procedure to be followed for settlement of claims which are to be met out of the funds.

Foreign insurance

159.

List of foreign insurers.

(1)

The Central Government shall publish in the Official Gazette a list (hereinafter referred to as the approved list) of foreign

insurers who have been guaranteed in accordance with the provisions of this Chapter, together with the name of the guarantor or guarantors in each case and shall also publish from time to time any addition to or removal from the approved list.

(2)

No foreign insurers name shall be added to the approved list until such foreign insurer has been guaranteed by at least one insurer and the name of the foreign insurer who ceases to have at least one guarantor shall be removed from the list.

160.

Guarantor of foreign insurer.

(1)

An insurer who desires to guarantee a foreign insurer shall make application therefor to the Central Government in Form 55.

(2)

The Central Government may, if it is satisfied that the application referred to in sub-rule (1) is in order and that it is expedient that the foreign insurer be placed in the approved list or, where the name of the foreign insurer is already included in the approved list, that the insurer should be added to the approved list as guarantor of the foreign insurer, and the name of the foreign insurer to the approved list if it is not already included, and include the insurer as a guarantor of such foreign insurer.

(3)

A guarantor desiring to cease guaranteeing a foreign insurer shall give notice of not less than two months to the Central Government in Form 56, and where such notice has been given, the guarantor shall be deemed to have ceased to guarantee the foreign insurer from the date specified in the notice:

Provided that the insurer shall be deemed, in respect of all certificates of foreign insurance endorsed or renewed in accordance with the provisions of sub-rule (2) of rule 161 before the date of such cessation, to continue as the guarantor of the foreign insurer who has issued the certificate as if the guarantor had not ceased to be his guarantor.

(4)

If at any time a guarantor ceases to be an insurer, the Central Government may, after giving such notice as may appear to it to be necessary, remove from the approved list the name of such guarantor wherever it appears:

Provided that the guarantor who ceases to be an insurer shall be deemed, in respect of all certificates of foreign insurance endorsed in pursuance of the provisions of sub-rule (2) of rule 161 before the date of removal of the name of the guarantor from the approved list, to continue as the guarantor of the foreign insurers as if the guarantor had not ceased to be an insurer and as if his name had not been removed from the list.

161.

Endorsement of certificate of foreign insurance.

(1)

A visitor wishing to have a certificate of foreign insurance endorsed or re-endorsed shall produce such certificate in Form 57 before the Customs Collector at a port of entry or land customs post or to such other officer as the Central Government may, by notification in the Official Gazette appoint, for the purpose of endorsement in accordance with the provisions of this Chapter or for the purpose of the renewal of any endorsement already made on the certificate in accordance with this Chapter.

(2)

Such officer shall, if satisfied that the certificate of foreign insurance complies with the requirements of the provisions of this chapter, that the period of validity of such certificate in India has not expired, that the certificate has been issued by a foreign insurer in the approved list and that the guarantor specified in the certificate is shown in the approved list as a guarantor of the foreign insurer, make an endorsement thereon in Form 58.

(3)

The period of validity of an endorsement or of the renewal of an endorsement made as aforesaid shall not in any case extend beyond the date on which the certificate of foreign insurance ceases to be effective in India :

Provided that when a visitor obtains a fresh certificate of foreign insurance during the period of his stay in India, the period of validity of an endorsement made upon it added to the period of validity of an endorsement or endorsements that may have been made upon the original certificate, shall not exceed one year in all.

162.

Validity of certificate of foreign insurance.

- A certificate of foreign insurance carrying an endorsement in accordance with the provisions of rule 161 shall have effect as if it were a certificate of insurance issued by the guarantor specified in it and shall be deemed to comply with the requirements of Chapter XI of the Act; and the policy to which it relates shall also be deemed to have been issued by such guarantor and to comply with the requirements of Chapter XI of the Act.

163.

Maintenance of records by the guarantor.

- Every guarantor shall in respect of certificates of foreign insurance issued under his guarantee by the foreign insurer whom he has guaranteed and every person who has ceased to be a guarantor shall, in respect of the certificate of foreign insurance issued under his guarantee by the foreign insurer whom he had guaranteed at any time in the preceding five years, keep a record of such particulars relating to the policies in connection with which the certificates of foreign insurance were issued as are required to be kept by insurers under the provisions of rule 147 in respect of policies, and the necessary additions to those records required to make them up to date shall be made as soon as is reasonably possible in the circumstances.

Chapter VIII

Offences, Penalties And Procedure

164.

Offences for the purpose of section 208.

- The offences for the purpose of sub-section (1) of section 208 shall be

(a)

Driving during the period of disqualification (section 23);

(b)

Failure to stop the vehicle when it is involved in an accident (section 132);

(c)

Obtaining or applying for a driving license without giving particulars of endorsement (section 182);

(d)

Driving dangerously (section 184);

(e)

Driving while under the influence of drinks or drugs (section 185);

(f)

Abetment of an offence under section 184 or section 185 or section 188;

(g)

Taking part in unauthorized race or trial of speed of any kind (section 189);

(h)

Altering a driving license or using an altered license;

(i)

Any other offence punishable with imprisonment in the commission of which a motor vehicle was used.

[FORM 1]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

[See rule 5(2)]

APPLICATION-CUM-DECLARATION AS TO PHYSICAL FITNESS

1.

Name of the applicant

.....

2.

Son/wife/daughter of

.....

3.

Permanent address

.....

4.

Temporary address

.....

Official address (if any)

.....

5.

(a) Date of birth

.....

(b) Age on date of application

.....

6.

Identification marks

(1).....

(2).....

Declaration

(a)

Do you suffer from epilepsy, or from sudden attacks of loss of consciousness or giddlenes from any cause?

Yes/No

(b)

Are you able to distinguish with each eye (or if you have held a driving license to drive a motor vehicle for a period of not less than five years and if you have lost, the sight of one eye after the said period of five years and if the application is for driving a light motor vehicle other than a transport vehicle fitted with an outside mirror on the steering wheel side) or with one eye, at a distance of 25 metres in good day light (with glasses, if worn) a motor car number plate?

Yes/No

(c)

Have you lost either hand or foot or are you suffering from any defect of muscular power of either arm or leg?

Yes/No

(d)

Can you readily distinguish the pigmentary colours, red and green?

Yes/No

(e)

Do you suffer from night blindness?

Yes/No

(f)

Are you so deaf as to be unable to hear (and if the application is for driving a light motor vehicle, with or without hearing aid) the ordinary sound signal?

Yes/No

(g)

Do you suffer from any other disease or disability likely to cause your driving of a motor vehicle to be a source of danger to the public, if so, give details

Yes/No

I hereby declare that, to the best of my knowledge and belief, the particulars given above and the declaration made therein are true.

(Signature or thumb-impression of the applicant)

Notes:- (1) An applicant who answers "Yes" to any of the questions (a), (c), (e), (f) and (g) or "No" to either of the questions (b) and (d) should amplify his answers with full particulars, and may be required to give further information relating thereto.

(2)

This declaration is to be submitted invariably with medical certificate in Form 1-A.

FORM 1-A

[See rules 5(1),(3),7, 10(a), 14(d and 18(d)]

Medical Certificate

(To be filled in by a registered medical practitioner appointed for the purpose by the State Government or person authorized in this behalf by the State Government referred to under sub-section (3) of section 8).

9[Space for passport size photograph of the applicant]

[Inserted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).]

1.

Name of the applicant

.....

2.

Identification marks

(1).....

(2).....

3.

(a) Does the applicant, to the best of your judgment, suffer from any defect of vision? If so, has it been corrected by suitable spectacles?

Yes/No

(b) Can the applicant, to the best of your judgment, readily distinguish the pig-mentary colours, red and green?

Yes/No

(c) In your opinion, is he able to distinguish with his eye sight at a distance of 25 metres in good day light a motor car number plate?

Yes/No

(d) In your opinion, does the applicant suffer from a degree of deafness which would prevent his hearing the ordinary sound signals

Yes/No

(e) In your opinion, does the applicant suffer from night blindness?

Yes/No

(f) Has the applicant any defect or deformity or loss of member which would interfere with the efficient performance of his duties as a driver? If so, give your reasons in details

Yes/No

(g) Optional

(a)Blood group of the applicant (if the applicant so desires that the information may be noted in his driving license.)

(b)RH factor of the applicant (if the applicant so desires that the information may be noted in his driving license).

.....

.....

Declaration made by the applicant in Form 1 as to his physical fitness is attached.

[Certificate of Medical Fitness

I certify that:-

(i)

I have personally examined the applicant Shri/Smt./Kum.....

(ii)

that while examining the applicant I have directed special attention to his/her distant vision;

(iii)

while examining the applicant, I have directed special attention to his/her hearing ability, the condition of the arms, legs, hands and joints of both extremities of the applicant; and

(iv)

I have personally examined the applicant for reaction time, side vision and glare recovery (applicable in case of persons applying for a license to drive goods carriage carrying goods of dangerous or hazardous nature to human life.)

And, therefore, I certify that, to the best of my judgment, he is medically fit/not fit to hold a driving license]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

.

The applicant is not medically fit to hold a license for the following reasons:

Signature:

1. Name and designation of the Medical
Officer/Practitioner

seal)

2. Registration number of Medical Officer.

Date:..... Signature or thumb-impression of the candidate.

Notes.-[1.]

[Note shall be renumbered as '(1)'thereof and Note (2) inserted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

The Medical Officer shall affix his signature over the photograph affixed in such a manner that part of his signature is upon the photograph and part on the certificate.]

2. [Dumb persons without deafness maybe granted a valid certificate of driving license for non-transport vehicle.]

[Note shall be renumbered as '(1)'thereof and Note (2) inserted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

[FORM 2]

[Substituted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

[See rule 101

Form Of Applicant For The Grant Of Learner's License

Space for passport size photograph

To

The Licensing Authority,

.....

.....

I hereby apply for a license authorising me to drive as a learner, the following motor vehicle(s):-

(a)

Motor cycle without gear

(b)

Motor cycle with gear

(c)

Invalid carriage

(d)

Light motor vehicle

(e)

Transport vehicle

(f)

Road roller

(g)

Motor vehicle of a specified description, namely

(h)

[E-rickshaw

[Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

(i)

E-carts.]

Particulars To Be Furnished By Applicant

1.

Full name

.....

2.

Son/wife/daughter of

.....

3.

Permanent address

.....

(Electoral Roll/Life Insurance Policy/

Passport/Pay slip issued by any office of the Central Government/State Government or a local body/Any other document or documents as may be prescribed by the State Government/Affidavit sworn before an Executive Magistrate or a First class Judicial Magistrate or a Notary Public to be enclosed)

4.

Temporary address/Official address (if any)

.....

5.

Duration of stay at the present address

.....

6.

Date of birth

.....

(Birth certificate/school certificated/affidavit sworn before an Executive Magistrate or a First Class Judicial Magistrate or a Notary Public to be enclosed)

7.

Place of birth

.....

8.

If Place of birth out side India, when migrated to Indian

.....

9.

Educational Qualification

.....

10.

Identification mark (s)

(1).....

(2).....

11.

Declaration of citizenship status

.....

(i) [if deemed Citizen of Citizen by Birth,

[Substituted by GSR 148(E), dated 4.3.2009 (w.e.f. 4.3.2009).]

.....

(Any one of the following in support of Citizenship as Indian to be enclosed):-

(a)

Proof of birth in India from municipality or Registrar of births and deaths:

(b)

School leaving certificate/secondary school certificate showing nationality/place of birth;

(c)

Passport showing place of birth/citizenship/nationality;

(d)

Certificate of nationality/citizenship issued by District Magistrate or any other Administrative Officer;

(e)

Residency permit/domicile certificate issued by the State Government;

(f)

Grant of patta/lease of property by the Central/State Government;

(g)

Refugee Registration Card pertaining to the period 1947-1950;

(h)

Certificate of SC/ST/OBC]

(ii) If Citizenship is acquired by Descent/Registration

.....
(In case Citizenship acquired by Descent, Birth Certificate, land/property document of parent/in case of Citizenship acquired by Registration, certificate to be enclosed)

.....
(iii) If Citizenship of Naturalisation

.....
(Certificate of Naturalisation and Certificate of Registration to be enclosed)

(iv) If non-Indian Citizen

.....
(Valid passport or other travel documents and such other document or authority as may be prescribed by law to be enclosed)

12.

Blood group

.....
RH (Rhesus) factor

.....
13.

I hold an effective driving license to drive:

Motor cycle/light motor vehicle/transport vehicle with effect from

.....
14.

Particulars of any driving license previously held by applicant

.....
Whether it was cancelled and if so, for what reason

.....
15.

Particular's of any learner's license previously held by applicant in respect of the description of vehicle to which the applicant has applied

.....
16.

Have you been disqualified for holding or obtaining driving license or learner's license.

If so, for what reasons

.....
17.

I enclose three copies of my recent photograph (passport size photograph)

.....
18. I enclose medical fitness certificate dated.....issued by(doctor)

19. I have submitted along with my earlier application for learner's license/I enclose the written consent of parent/guardian (in the case of applicant being a minor).

20. I enclose driving certificate dated.....issued by.....(Name and address of the driving school).

21. I have paid the fee of Rs.....

22. I am exempted from the medical test under rule 6 of the Central Motor Vehicles Rules, 1989.

23. I am exempted from the preliminary test under rule 11(2) of the Central Motor Vehicles Rules, 1989.

*Strike out whichever is inapplicable.

Date.....

Signature of thumb-impression of applicant.

Specimen signature or thumb-impression of applicant

1.

2.

Declaration under sub-section (2) of section 7 of the Motor Vehicles Act, 1988

Shri/Smt./Kumari.....son/daughter ofwho is a minor is under my care and I accept responsibility for his/her driving. If at a later date I decide not to accept responsibility his/her driving I shall intimate the licensing authority in writing for the cancellation of the license. I give my consent for his/her obtaining learner's license.

Signature

Name and full address of the parent/guardian

.....

Relationship.....

(To be signed in the presence of the licensing authority or person authorized in this behalf by the licensing authority).

FOR OFFICE USE

The applicant is exempted from the medical test under rule 6 and the preliminary test under rule 11(@) of the Central Motor Vehicles Rules, 1989.

Learner's license may be issued.

The applicant was tested with reference to rule 11(1) of the Central Motor Vehicles Rules, 1989. He has passed the test.

Learner's license may be issued.

Learner's license may be refused.

Signature of licensing authority or other
person authorized in his behalf

*Strike out whichever is inapplicable.

Note:- The application along with the scanned copies of the required documents may also be sent to the concerned Licensing Authority through Electronic Mail, if allowed by the concerned State Government/Union Territory Administration.

In such cases, the Licensing Authority shall scrutinize the application and intimate the applicant about the acceptance/any discrepancy.

In case the application is accepted, the applicant shall be intimated through Electronic Mail to report to the Authority concerned on an appointed date along with the documents for further verification, submission of application fee and examination of the applicant.]

FORM 3

[See rules 3(a), 13]

Learner's License

Space for 13[passport size photograph]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

License No.....Date.....

Name to be written across the photograph

Specimen signature/thumb-impression of the
holder of the license.

Signature and seal of the licensing authority

1.

Full name

.....

2.

Son/wife/daughter of

.....

3.

Date of birth

.....

4. [

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

Optional

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

Blood group

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

RH factor]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

.....

5.

Present/permanent address

.....

Temporary/Official

(if any)

.....

6.

Mark(s) of identification

(1).....

(2).....

[is licensed to drive a motor vehicle of the following description throughout India and, in case of E-rickshaw or E-cart, in specified areas or routes, as a learner, subject to the provisions of rule 3 of the Central Motor Vehicles Rules, 1989]

[Substituted for the words 'is licensed to drive throughout India as a learner subject to the provisions of rule 3 of the Central Motor Vehicles Rules, 1989, a motor vehicle of the following description:-'Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

The holder of the license has passed the medical test under rule 5 and the preliminary test referred to in rule 11(1) of the Central Motor Vehicles Rules, 1989.

The holder of the license is exempted from the medical test under rule 6 and from preliminary test under rule 11(2) of the Central Motor Vehicles Rules, 1989.

This license is valid from.....to.....

*Strike out whichever is inapplicable

Signature and designation of the
licensing authority

Warning:The attention of the holder of this license is drawn to rule 3 of the Central Motor Vehicles Rules, 1989, which prohibits him from driving any motor vehicle unless he has besides him a person duly licensed to drive the vehicle and in every case, the vehicle carries "L" plates both in the front and in the rear of the vehicle.

[FORM 4]

[Substituted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

[See rule 14(1)]

Form Of Application For License To Drive A Motor Vehicle

To

Space for passport size photograph

The Licensing Authority,

.....

.....

I apply for a license to enable me to drive vehicles of the following description:-

(a)

Motor cycle without gear

(b)

Motor cycle with gear

(c)

Invalid carriage

(d)

Light motor vehicle

(e)

Transport vehicle

(f)

Road roller

(g)

Motor vehicles of the following description, namely.....

(h)

[E-rickshaw

(i)

E-carts.]

Particulars To Be Furnished By The Applicant

1.

Full name

.....

2.

Son/wife/daughter of

.....

3.

Permanent address

.....

(Electoral Roll/Life Insurance Policy/

Passport/Pay slip issued by any office of the Central Government/State Government or a local body/Any other document or documents as may be prescribed by the State Government/Affidavit sworn before an Executive Magistrate or a First class Judicial Magistrate or a Notary Public to be enclosed)

4.

Temporary address/Official address (if any)

.....

5.

Duration of stay at the present address

.....

6.

Date of birth

.....

(Birth certificate/school certificated/affidavit sworn before an Executive Magistrate or a First Class Judicial Magistrate or a Notary Public to be enclosed)

7.

Place of birth

.....

8.

If Place of birth out side India, when migrated to Indian

.....

9.

Educational Qualification

.....

10.

Identification mark (s)

(1).....

(2).....

11.

Declaration of citizenship status

.....
(i) [if deemed Citizen of Citizen by Birth,]

[Substituted by GSR 148(E), dated 4.3.2009 (w.e.f. 4.3.2009).]

.....
[(Any one of the following in support of Citizenship as Indian to be enclosed):-

(a)

Proof of birth in India from municipality or Registrar of births and deaths:

(b)

School leaving certificate/secondary school certificate showing nationality/place of birth;

(c)

Passport showing place of birth/citizenship/nationality;

(d)

Certificate of nationality/citizenship issued by District Magistrate or any other Administrative Officer;

(e)

Residency permit/domicile certificate issued by the State Government;

(f)

Grant of patta/lease of property by the Central/State Government;

(g)

Refugee Registration Card pertaining to the period 1947-1950;

(h)

Certificate of SC/ST/OBC]

(ii) If Citizenship is acquired by Descent/Registration

.....
(In case Citizenship acquired by Descent, Birth Certificate, land/property document of parent/in case of Citizenship acquired by Registration, certificate to be enclosed)

.....
(iii) If Citizenship of Naturalisation

.....
(Certificate of Naturalisation and Certificate of Registration to be enclosed)

(iv) If non-Indian Citizen

.....
(Valid passport or other travel documents and such other document or authority as may be prescribed by law to be enclosed)

12.

Blood group

.....
RH (Rhesus) factor

.....
13.

Have you previously held driving license?

If so, give details

.....
14.

Particulars and date of every conviction which has been ordered to be endorsed on any license held by the applicant

.....
15.

Have you been disqualified for obtaining a license to drive? If so, for what reasons?

.....
16.

Have you been subjected to a driving test as to your fitness or ability to drive a vehicle in respect of which a license to drive is applied for? If so, give the following details:-

.....

Date of test

Testing authority

Result of test

1.

2.

3.

4.

17. I enclose three copies of my recent passport size photograph (where laminated card is used no photographs are required)

18. I enclose the learner's license No.....dated.....issued by the licensing authority.

19. I enclose the driving certificate No.....dated.....issued by.....

20. I have submitted along with my application for learner's license the written consent of parent/guardian.

21. I have submitted along with the application for learner's license/I enclose the medical fitness certificate.

22. I am exempted from the medical test under rule 6 of the Central Motor Vehicles Rules, 1989.

23. I am exempted from preliminary test under rule 11(2) of the Central Motor Vehicles Rules, 1989.

24. I have paid the fee of Rs.....

*Strike out whichever is inapplicable

Date:.....

Signature/thumb-impression of applicant

Certificate Of Test Of Competence To Drive

The applicant has passed the test prescribed under rule 15 of the Central Motor Vehicles Rules, 1989. The test was conducted on (here enter the registration mark and description of the vehicle).....on date).....

The applicant has failed in the test

(The details of the deficiency to be listed out)

Date :.....

Signature of Testing Authority

.....

.....

Full name and designation

Two specimen signatures of applicant:

1.

2.

*Strike out whichever is inapplicable.

Note:-The application along with the scanned copies of the required documents may also be sent to the concerned Licensing Authority through Electronic Mail, if allowed by the concerned State Government/Union Territory Administration.

In such cases, the Licensing Authority shall scrutinize the application and intimate the applicant about the acceptance/any discrepancy.

In case the application is accepted, the applicant shall be intimated through Electronic Mail to report to the Authority concerned on an appointed date along with the documents for further verification, submission of application fee and examination of the applicant.

[FORM 4-A]

[Inserted by GSR 720(E), dated 10.9.2003 (w.e.f. 10.10.2003).]

See rule 14(2)]

Form Of Application For Issue Of International Driving Permit To Drive A Motor Vehicle In Other Countries
To

Passport size Photograph

The licensing Authority,

.....

.....

I apply for an International Driving Permit to enable me to drive vehicles of the following categories :-

Categories Of Vehicles For Which The Permit Is Applied For

(A)

Motor cycles Category L1 and Category L2;

(B)

Motor vehicles, other than those in category (A) above, having a permissible maximum mass/weight not exceeding 3,500 kg. (7700 1b) and not more than eight seats in addition to the driver's seat in Category M1;

(C)

Motor vehicles used for the carriage of goods and whose permissible maximum mass/weight exceeds 3,500 Kg. (7700 1b);

(D)

Motor vehicles used for the carriage of passengers and having more than eight seats in addition to the driver's seat;

(E)

Combination of vehicles of which the driving vehicle is in a category or categories for which the driver is licensed (B and/or C and/or D), but which are not themselves in that category or categories.

Particulars To Be Furnished By Applicant

1.

Name

.....

(Surname)

(Middle Name).....(First Name)

2.

Father's or husband's name

.....

3.

Place of birth and country

.....

(Proof to be enclosed)

.....

4.

Address

.....

(a)Present

.....

.....

(b)Permanent

.....

.....

.....

5.

Date of birth (proof to be enclosed)

.....

6.

Educational qualification

.....

7.

Identification marks

(1).....

(2).....

8.

Blood group/RH factory

.....

9.

Have you previously held International Driving permit ? If so, give details

.....

10.

Particulars and date of every conviction which has been ordered to be endorsed on any driving license held by the applicant.

.....

11.

Have you been disqualified for obtaining a driving license to drive?

If so, for what reason?

.....

12.

Have you been subjected to a driving test as to your fitness or ability to drive a vehicle in respect of which a driving license is applied for? If so, give the following details:

.....

Date of test

Testing authority

Result of test

1.

2.

3.

4.

13. I enclose three copies of my recent passport size photograph.

14. I enclose the copy of driving license No.....dated.....issued by.....valid up to

.....

15. I enclose a medical certificate in Form 1-A

16. I have paid the fee of Rs.....

I hereby declare that the particulars given above are true to the best of my knowledge and belief.

Date.....Signature/Thumb-impression of applicant.

*Strike out whichever is inapplicable.

FORM 5

[See rules 14(e), 17(1)(b), 27(d) and 31-A(2)]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

Driving Certificate Issued By Driving School Or Establishment

This is to certify that Shri/Smt./Kumari.....son/wife/daughter of.....residing at.....was enrolled in this school on.....residing at.....was enrolled in this school onand his/her name is registered at serial number.....in our register in Form 14 and that he/she has undergone the course of training in driving of.....(mention class of vehicle) according to the syllabus prescribed or a period from.....tosatisfactorily.

I am satisfied with his/her physical fitness and sense of responsibility.

Signature.....

Name and designation.....

.....

Name and address of the driving school with license number and date of issue.

[FORM 6]

[Substituted by GSR 521(E), dated 15.7.2008 (w.e.f. 15.7.2008).]

[See rule 16(1)]

(To be printed in book form of the size six centimetres by eight centimetres)

Form Of Driving License

Name of the license holder.....

Son/wife/daughter of.....

Passport size Photograph

[The holder of this license is licensed to drive vehicles of the following description, throughout India and, in case of E-rickshaw or E-cart, in specified areas or routes.]

[Substituted for the words 'The holder of this license is licensed to drive throughout India vehicles of the following description:-'Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

Name to be written across the photograph (Part of the seal and signature of the licensing authority to be on the photograph and part on the driving license).

.....

Specimen signature/thumb-impression
of the holder of the license

Signature and designation of the
licensing authority

Driving license number

.....

Date of issue

.....

Name

.....

Son/wife/daughter of

.....

Citizenship

.....

Temporary address/official address (if any)

.....

Permanent address

.....

Date of birth

.....

Educational qualifications

.....

Optional

Blood group

.....

RH factor

.....

[The holder of this license is licensed to drive vehicles of the following description, throughout India and, in case of E-rickshaw or E-cart, in specified areas or routes.]

[Substituted for the words 'The holder of this license is licensed to drive throughout India vehicles of the following description:-'Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

Motor cycle without gear

Motor cycle with gear

Invalid carriage

Light motor vehicle

Transport vehicle

Road roller

Motor vehicle of a specified description, namely

The license to drive a motor vehicle other than transport vehicle if valid from.....to.....

[The license to drive a transport vehicle or E-rickshaw or E-cart is valid from to]

[Inserted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

Name and designation of the authority who conducted the driving test.

.....

Signature and designation of the
licensing authority

[Authorisation to drive transport vehicle or E-rickshaw or E-cart]

[Inserted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

Number.....Date.....Authorized to drive transport vehicle with effect
from.....Badge number.....

Signature.....

.....

Designation of the licensing authority

Name and designation of the authority who conducted the driving test

Space for addition of other classes of vehicles

Number.....

Date.....

Also authorized to drive the following class or description of motor vehicles:-

Name and designation of the authority who conducted the driving test.

Signature and designation of the licensing authority

Date.....

Space for renewal of driving license

The license to drive a motor vehicle other than transport vehicle is hereby renewed
from.....to.....

Signature of licensing authority

The license to drive a transport vehicle is hereby renewed from.....to.....

From.....to.....

Signature of licensing authority

From.....to.....

Signature of licensing authority

Space for endorsement by Court

Date

Section and Rule

Fine or other punishment

Signature of the endorsing authority

(1)

(2)

(3)

(4)

Space for endorsement by licensing authority

Date

Proceeding number and date

Disqualification period from.....to.....

Signature of licensing authority

(1)

(2)

(3)

(4)

[FORM 6-A]

[Inserted by G.S.R. 720(E), dated 10-9-2003 (w.e.f. 10-10-2003).]

[See rule 16(4)]

REPUBLIC OF INDIA

INTERNATIONAL MOTOR

TRAFFIC

INTERNATIONAL

DRIVING PERMIT

No. ?.....

Valid until.....(Maximum for 1 year or up to the date of validity of driving license whichever is earlier)

Name and Designation of Issuing Authority

Place of Issue

Date of Issue

Driving License No. and valid upto

Seal of the Authority

Signature of Issuing Authority

White colour

This permit is not valid for the territory of -

(1)

.....

The categories of vehicles for the driving of which it is valid are mentioned in this form at paragraph B.

(2)

This permit shall in no way exempt the holder from the obligation to conform to the laws and regulations relating to residence and the exercise of a profession in each State through which he travels. In particular, it shall cease to be valid in a State if its holder establishes his normal residence there.

English and French versions

A.PARTICULARS CONCERNING THE DRIVER

(1)

Surname/First name/Middle name/

.....

(2)

Father's or husband's name

.....

(3)

Place of birth and country

.....

(4)

Date of Birth/approximate age

.....

(5)

Address

(a)Current address

.....

.....

(b)Permanent address

.....

.....

(6)

Blood group/RH factor

.....

B.CATEGORIES OF VEHICLES FOR WHICH THE PERMIT IS VALID

(A)

Motor cycles Category L1 and Category L2;

(B)

Motor vehicles, other than those in category (A) above, having a permissible maximum mass/weight not exceeding 3,500 kg (7700 lb) and not more than eight seats in addition to the driver's seat in Category M1;

(C)

Motor vehicles used for the carriage of goods and whose permissible maximum mass/weight exceeds 3,500 kg. (7700 lb);

(D)

Motor vehicles used for the carriage of passengers and having more than eight seats in addition to the driver's seat.

(E)

Combination of vehicles of which the driving vehicle is in a category or categories for which the driver is licensed (B and/or C and/or D), but which are not themselves in that category or categories.

Restrictive conditions of use such as:-

Must wear corrective lenses.

Valid only for driving vehicle No.

Vehicle must be equipped to be driven by a one legged person.

Seal or stamp of

The Authority below

In the appropriate

Column.

A.

B.

C.

D.

Photograph 35×45 MM

Seal

or stamp of the Authority

Signature

or thumb print of holder

Disqualifications:-

The holder is deprived of the right to drive in the territory of

(Name of country) at.....

Until.....

On.....

Signature on seal or stamp of the Authority which has invalidated the permit in its territory

Until.....

On.....

The holder is deprived of the right to drive in the territory of

(Name of the country) at.....

Signature and seal or stamp of the Authority which has invalidated the permit in its territory.

DETAILS DU CHAUFFEUR

(1)

Nom/Prenom/deuxieme nom

.....

(2)

Nom du Pere ou de mari

.....

(3)

Dieu de Naissance et pays

.....

(4)

Date de Naissance/1'age

.....

(5)

Adresse

(a)L'adresse en cours

.....
(b) L'adresse permanente

.....
(6)
Groupe Sanguin/Facteur RH

.....
CATEGORIES DES VEHICULES POUR LESQUELLES LE PERMIS EST VALABLE

(A)
Motos (L1 et L2) Categories

(B)
Vehicules sauf ceux de categories A, ayant La masse maximum acceptable ne depassant pas 3,500 Kilos (7700 lb) et pas plus que huit sieges en plus dela siege du chauffeur, (M-1) categorie

(C)
Vehicules utilises pour porter les Marchandises et don't la Masse Maximum acceptable depasse 3,500 Kilos (7700 lb)

(D)
Vehicules utilises pour porter les voyageurs et ayant plus que huit sieges en plus de la siege du chauffeur.

(E)
Combinaison de vehicules don't le Vehicule a conduire est dans la categorie ou categories pour lesquels le chauffeur est donne le permis (B et/ou C/ou D) mais lesquels ne sont pas dans cette/ces categorie(s).

Conditions restrictive d'usage comme

-Doit porter des verres correctifs.

-Valable seulement pour le Numero de vehicule a conduire.

-Vehicule doit etre muni pour conduire par une personne ayant une jambe.

Sceau/Cachet

De l'autorits

au-dessou, dans

I, espace approprie

A.

B.

C.

D.

E.

Photo 35×45 MM

Sceau on cache

del'autorite

Signature ou Print du pouce

Disqualifications:-

Le detenteur est depossede du droit
de conduire dans le territoire (nom de
province) a.....

Jusqu's.....

le.....

Signature et sceau de l'autorite qui a
invalide le permis dans son territoire.

Le detenteur est depossede du droit
de conduire dans le territoire (nom de
province) a.....

Jusqu's.....

Le.....

Signature et sceau de l's autorite qui a
invalide le permis dans son territoire.]

[FORM 7]

[Substituted by GSR 521(E), dated 15.7.2008 (w.e.f. 15.7.2008).]

[See rule 16(2)]

FORM FOR DRIVING LICENCE (LAMINATED/SMART CARD TYPE)

Visual Inspection Zone

Driving License No.....

Date of Issue.....

Photograph

Valid till (Non-Transport)..... Valid till

(Transport)..... Name..... (Surname)..... (Given

name)..... (Middle name)..... Son/Daughter/Wife of

..... (Surname)..... (Given name)..... (Middle

name).....

Address

(Current).....

.....

Citizenship.....

.....

Date of

Birth..... (Date)..... (Month)..... (Year).....

.
Authorisation to drive the following vehicle class throughout India :-

(i)

Class of vehicle.....

(ii)

Issue Date (dd-mm-yyyy).....

Badge Number

Blood Group and Rh factor of the driver.....

Specimen Signature/thumb-impression of the license holder.....

Signature of the Issuing Authority.....

Identification of Issuing Authority.....

Note:-The provision for security features like the ghost image and/or the hologram would be provided in the Visual Inspection Zone of the License by the concerned State Government. Card Serial Number will be printed by card manufacturer on the back side upper left corner of the card.

Machine Readable Zone

The concerned State Governments will provide the following features in the license, in Machine Readable Zone:-

Chip Serial Number.....

Driving License No.....

Date of Issue.....

Valid till (Non-Transport)..... Valid till (Transport).....

Name..... (Surname)..... (Given name)..... (Middle

name)..... Son/Daughter/Wife of..... (Surname)..... (Given

name)..... (Middle name).....

Citizenship.....

[***]

[Omitted by G.S.R. 708(E), dated 30.8.2010]

Date of Birth (dd-mm-yyyy).....

Class of vehicle.....

Respective Date of Issue.....

Short name of the Authority conducted driving test for respective class of vehicle as above.....

Designation of the Authority conducting driving test for respective class of vehicle as above.....

Identification Authority..... Endorsement details (Provision will be made to accommodate the details of 10 Endorsements with following details) Endorsement/Challan Number..... Endorsement/Challan Date..... ID Code of Authority of Endorsement..... Section/Rule/Proceeding No. (Provision for 10 Sections/Rules)..... Fine..... Disqualification period from (dd-mm-yyyy)..... Disqualification period to (dd-mm-yyyy)..... Settlement/Review Date (dd-mm-yyyy)..... Settlement/Review Authority ID..... [Authorisation to drive E-rickshaw or E-cart in.....(specify areas or routes)] [Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)] Badge Details Badge Number..... Valid till..... Authorisation Number..... Authorisation Date..... FORM 8 [See rule 17(1)] Application For The Addition Of A New Class Of Vehicle To A Driving License To Licensing Authority, I, Shri/Smt./Kumari.....hereby apply for the addition of the following class/classes of motor vehicles to the attached license:- (a) [Motor cycle without gear,] [Substituted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000).] (b) Motor cycle with gear, (c) Invalid carriage, (d) Light motor vehicles, (e) [Transport vehicle,] [Substituted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).] (f) Medium passenger motor vehicles, [***] [Items (g) and (h) omitted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).] [***] [Items (g) and (h) omitted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001).] (i) Road rollers, (j) Motor vehicles of the following description:-	of Issuing
--	---------------

[I enclose,

[Inserted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

(a)

A medical certificate in Form 1-A,

(b)

Learner's license in Form 3,

(c)

Driving license in Form 6 or 7 if any;

(d)

Driving certificate in Form 5 if the application is to drive a transport vehicle excluding E-rickshaw or E-cart;

(e)

I have paid the fee of Rs]

(k)

[E-rickshaw

[Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]

(l)

E-cart]

Dated.....20.....

Signature or thumb-impression of
the applicant

Certificate of test of competence to drive

The applicant has passed/failed in the test specified in rule 15 of the Central Motor Vehicles Rules, 1989. The test was conducted on a.....(here enter description of vehicle) on date.....

Signature of Testing Authority

Name and designation

FORM 9

[See rule 18(1)]

Form Of Application For The Renewal Of Driving License

Space for 28[passport size photograph]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

I,

Shri/Smt./Kumari.....son/wife/daughter
of.....hereby apply for the renewal of my
driving license which is attached and particulars of which are as follows:

(a)

Number

.....

(b)

Date of issue

.....

(c)

Licensing authority by which the license was issued

.....

(d)

Licensing authority by which the license was
last renewed

.....

Number and date of renewal

.....

(e)

Class of vehicles authorized to be driven

.....
(f)

Date of expiry of license to drive
.....

(i) transport vehicle
.....

(ii) vehicles other than transport vehicles
.....

My present address is
.....
.....
.....

If this address is not entered on the license, I do/do not wish that it should be so entered.

If the license is not attached, reasons why it is not available?
.....
.....

If the license was not renewed within thirty days of the date of expiry, reasons for delay.....
.....

The renewal of license has not been refused by any licensing authority.

I have not been disqualified for holding or obtaining a driving license. My license has not been revoked.

I enclose a medical fitness certificate in [Form 1-A],

I enclose three copies of my recent passport size photograph (5 cms by 6 cms)

I have paid the fee of Rs.....

I hereby declare that to the best of my knowledge and belief the particulars given above are true.

Date.....

Signature or thumb-impression of applicant.

Name.....

Address.....
.....

FORM 10

[See rule 23(1)]

State Register Of Driving License

1.

(a) Driving license number and date of initial issue
.....

(b) Licensing authority which issued the license
.....

(c) Name and designation of the officer who has taken the driving test and the date of passing the test by the holder of the license
.....

2.

Name, address and other particulars of the holder of the driving license:
.....

(a)(a) Name of the holder (with guardian's name, if minor)
.....

(b)Date of birth
.....

(c)Educational qualifications
.....

(d)Permanent address

.....
(e) Temporary address/
official address (if any)

.....
(f) Subsequent changes of address

.....
(g) Class and types of vehicles for which license is given

.....
(h) Addition of vehicles
(if any) with dates

.....
(i) Date of expiry of the license and further renewal (with details of licensing authority which renewed the license)

.....
(j) Details of disqualifications, fine, cancellation, etc., in relation to the holder of the driving license

.....
FORM 11

[See rules 24(1), 24(4) and 25]

Form Of License For The Establishment Of A Motor Driving School

License No.....

License is hereby granted for the establishment of a school for imparting instructions in driving of motor vehicles specified below:

(a)

Motor cycle,

(b)

Invalid carriage,

(c)

Light motor vehicle,

(d)

Medium goods vehicle,

(e)

Medium passenger motor vehicle,

(f)

Heavy goods vehicle,

(g)

Heavy passenger motor vehicle,

(h)

Motor vehicles of the following description:

by.....

(Name and address of the license holder)

at..... (premises of
the school)

the school being known as the..... subject to the provisions of the Motor Vehicles Act, 1988 and the
Central Motor Vehicles Rules, 1989.

The license is valid from..... to.....

Dated.....

Licensing Authority

This license is hereby renewed from..... to.....

Licensing Authority

FORM 12

[See rule 24(2)]

Form Of Application For A License To Engage In The Business Of Imparting Instructions In Driving Of Motor Vehicles

To

The Regional Transport Officer,

.....

The undersigned hereby applies for obtaining a license to run the business of imparting instructions in driving of motor vehicles:

1.

Full name of the applicant

2.

Son/wife/daughter of

3.

Address

4.

Place where the applicant desires to start his business

5. [

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

| Nature and extent of facilities available]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

6.

Qualifications of staff engaged for imparting instructions

7. [

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

| Make and model of engine to be used for training purposes]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

8.

Details of the registration marks of the vehicles used for imparting driving instructions

9.

I have paid the fee of Rs.

Dated.....

Signature of the applicant

Dated.....

Signature of the applicant

FORM 13

[See rules 24(2) and 25]

Form Of Application For Renewing A License To Engage In The Business Of Imparting Instructions In Driving Of Motor Vehicles

To

The Regional Transport Officer,

.....

.....

The undersigned hereby applies for renewal of a license to run the business of imparting instructions in driving of motor vehicles:

1.

Full name of the applicant

.....

.....

2.

Son/wife/daughter of.....

.....

3.

Address

.....

.....

4.

Place of business

.....

.....

5.

Number of existing licenses

.....

.....

6.

Date of issue

.....

.....

7.

Period of validity

.....

.....

8.

Whether the application has been made before the expiry of existing license, if not, the reasons for delay.....

.....

9.

Whether the earlier license was suspended/cancelled for any reason, details thereof such as date of suspension, reasons for such suspension/cancellation.

Date of revocation of suspension/cancellation

.....

10.

I have paid the fee of Rs.

.....

Dated.....

.....

Dated.....

Signature of the applicant

FORM 14

[See rule 27(a)]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

Register Showing The Enrolment Of Trainee(S) In The Driving School Establishments

Register for the year.....

1.

Enrolment number

.....

2.

Name of the trainee with his photograph

.....

3.

Son/wife/daughter of

.....

4.

Address:

.....

(a) Permanent address

.....
(b) Temporary address/official address (if any)
.....

5.
Date of birth
.....

6.
Class of vehicle for which training imparted
.....

7.
Date of enrolment
.....

8.
Learner's license number and date of its expiry
.....

9.
Date of completion of the course
.....

10.
Date of passing the test of competence to drive
.....

11.
Driving license number and date of issue and the licensing authority which issued the license
.....

12.
Remarks
.....

13.
Signature of the license holder/instructor
.....

[Substituted by GSR 148(E), dated 4.3.2009 (w.e.f. 4.3.2009).]
[Inserted by Notification No. G.S.R. 709 (E) dated 8.10.2014 (w.e.f. 2.6.1989)]
[Substituted by GSR 148(E), dated 4.3.2009 (w.e.f. 4.3.2009).]

FORM 15

[See rule 27(i)]

Register Showing The Driving Hours Spent By A Trainee

Name of the school/establishment
.....

Name of the trainee
.....

Enrolment number
.....

Date of enrolment
.....

Date

Hours spent in actual driving

From....hrs To.....hrs

Class of vehicle

Signature of the instructor

[Signature or thumb-impression of the trainee]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

1
2
3
4
5

1.
2.
3.
4.
5.

FORM 16

[See rule 34(1)]

Form Of Application For Grant Or Renewal Of Trade Certificate
To

The Registering Authority,

.....

I/We hereby apply for issue of/renewal of a trade certificate(s):-

Table-9

1.

Applicant's name

.....

2.

Son/wife/daughter of

.....

3.

Applicant's full address (proof to be attached)

.....

4.

Whether the applicant is a[manufacturer or dealer of automobiles or automobile ancillary or a test agency specified under rule 126 of the said rules]

[Substituted by Notification No. G.S.R. 291 (E) dated 24.4.2014]

in motor vehicles, approved repairer or vehicles, engaged in building bodies of vehicles, engaged in the business of hire purchase/lease/hypothecation of vehicles

5.

Number of certificates required

.....

6.

Class of motor vehicle(s) in respect of which certificate(s) is required

.....

7.

Amount of fee paid

.....

8.

If the application is for renewal indicate the trade certificate

No., date of issue and date of expiry in respect of which renewal is applied

.....

Declaration

I/We do hereby declare that the trade certificate(s) is/are required by me/us for bona fide trade purpose.

Place.....Signature of the applicant

Date.....

*Strike out whichever is inapplicable.

FORM 17

[See rule 35(1)]

Form Of Trade Certificate

(To be printed in circle shape of 70 millimetres diameter)

Trade certificate

1.

Serial number of certificate

2.

Full name and address of certificate holder

3.

Trade number assigned in respect of the certificate

4.

Class of motor vehicle in respect of which the certificate is to be used

5.

Date of expiry of certificate

6.

Amount of fee paid

7.

Date and stamp of office of issue

Station.....

Date.....

Registering Authority of Region/State

Valid throughout India

Schedule

Form of folder for the certificate

The folder shall be of metal and be weather-proof. It shall be circular in shape and conform to the following dimensions:

Circular pattern, without cross bars-certificate tray

The certificate of standard pattern when cut along the outline of the outer of that two circles, shall fit neatly into a sheet-metal tray of suitable thickness, having a turned-up edge of sufficient depth to hold the license and stout cover of transparent white glass.

Ring cover: A circular ring of sheet-metal shaped to fit down closely into the tray, and adopted for fixing by screws, bolts, or otherwise to the vehicle in the prescribed position. A rubber packing ring shall be arranged to fit between the ring cover and the cover glass and tray so as to render the whole carrier weather-proof.

Dimensions: The aperture within the ring-cover shall clearly exhibit the whole of the certificate lying within the inner circle of the certificate and shall have a diameter of 10 cm.

FORM 18

[See rule 38(1)]

INTIMATION OF LOSS OR DESTRUCTION OF A TRADE CERTIFICATE AND APPLICATION FOR DUPLICATE

To

The Registering Authority,

The trade certificate issued to me/us bearing number..... and valid up to..... has been mutilated/soiled/lost/destroyed* in the following circumstances and is not in my possession for the reasons specified below:

I/We surrender the *mutilated/soiled trade certificate.

I/We hereby declare that to my/our knowledge the trade certificate has not been either suspended or cancelled under the provisions of the Rules and that the above certificate is not in the use of any one else. I undertake to surrender the trade certificate if it is found by me or restored to me.

I/We hereby deposit the fee of Rs..... and apply for the issue of duplicate trade certificate.

Signature or thumb-impression of the applicant

Address.....

.....

Dated:.....

*Strike out whichever is inapplicable.

FORM 19

[See rule 43]

REGISTER TO BE MAINTAINED BY THE HOLDER OF TRADE CERTIFICATE

Date

Trade certificate number and in case of vehicle registered

the registration number of the vehicle

Description of motor vehicle

Purpose for which vehicle sent out or brought

Driver's name

license No. and address and whether he is the employee of the holder of trade certificate

Hours of leaving the premises by the vehicle

Mileage covered between the hours noted in columns(6) and

(7)

Signature and designation of the person authorized by the holder

(1)

(2)

(3)

(4)

(5)

(6)

(7)

(8)

(9)

(10)

[FORM 20

[Substituted by GSR 276(E), dated 10.4.2007 (w.e.f. 10.4.2007).]

[See rule 47]

APPLICATION FOR REGISTRATION OF A MOTOR VEHICLE

(To be made in duplicate if the vehicle is held under an agreement of Hire-Purchase/Lease/Hypothecation and duplicate copy with the endorsement of the Registering Authority to be returned to the Financier simultaneously on Registration of motor vehicle)

To

The Registering Authority,

.....

.....

1

Full name of the person to be registered as Registered owner Son/wife/daughter of

.....

2

Age of the person to be registered as Registered owner

.....

3

Permanent address

.....

(Electoral Roll/Life Insurance Policy/Passport/Pay slip issued by any office of the Central Government/State Government or a local body/Any other document or documents as may be prescribed by the State Government/

Affidavit sworn before an Executive Magistrate or a First Class Judicial Magistrate or a Notary Public to be enclosed)

4.

Temporary address/Official address, if any

.....

5.

Duration of stay at the present address

.....

6.

The annual income and PAN/GIR number of the owner

.....

7.

Place of birth

.....

8.

If place of birth is outside India, when migrated to India

.....

9.

Declaration of Citizenship status (i) If deemed Citizen or Citizen by Birth (Birth certificate and school certificate in support of Citizenship as Indian to be enclosed)

(ii) If Citizenship is acquired by Descent/Registration

(In case Citizenship acquired by Descent, Birth Certificate, land/property document of parent/in case of Citizenship acquired by Registration, certificate to be enclosed)

(iii) If Citizenship by Naturalisation (Certificate of Naturalisation and Certificate of Registration to be enclosed)

(iv) If non-Indian Citizen

(Valid passport or other travel documents and such other document or authority as may be prescribed by law to be enclosed)

.....

.....

.....

.....

10.

Name and address of the Dealer or Manufacturer from whom the vehicle was purchased (sale certificate of road worthiness issued by the Manufacturer to be enclosed)

.....

11

If ex-army vehicle or imported vehicle, enclose proof If locally manufactured Trailer/Semi-trailer, enclose the Approval of design by the State Transport Authority and Note the proceedings number and date of approval

.....

12.

Class of vehicle

.....

(if motor cycle, whether with or without gear)

.....

13.

The motor vehicle is

.....

(a) a new vehicle,

.....

(b) ex-army vehicle,

.....

(c) imported vehicle

.....

(d) [in-use E-rickshaw or E-cart]

[Substituted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

.....

14.

Type of body

.....

15.

Type of vehicle

.....

16.

Maker's name

.....

17.

Month and year of manufacture

.....

18.

Number of cylinders

.....

19.

Horse power

.....

20.

Cubic capacity

.....

21.

Maker's classification or if not known, wheel base

.....

22.

Chassis No (affix pencil print)

.....

23.

[Engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

.....

24.

Seating capacity (including driver)

.....

25.

Fuel used in the engine

.....

26.

Unladen weight

.....

27.

Particulars of previous registration and registered number
(if any)

.....

28.

Colour or colours of body, wings and front end

.....

I hereby declare that the motor vehicle has not been registered in any State in India.

ADDITIONAL PARTICULARS TO BE COMPLETED ONLY IN THE CASE OF TRANSPORT VEHICLES OTHER THAN
MOTOR CAB

29.

Number, description, size and ply rating of tyres, as declared by the manufacturer

- (a) Front axle=
(b) Rear axles=.....
(c) Any other axle=.....
(d) Tandem axle=.....

30.

Gross vehicle weight

- (a) as certified by manufacturer.....kgms
(b) To be registered.....kgms

31.

Maximum axle weight

- (a) Front axle=Kgms
(b) Rear axle=.....Kgms
(c) Any other axle=.....kgms
(d) Tandem axle=.....kgms

32.

- (a) Overall length.....
(b) Overall width.....
(c) Overall height.....
(d) Over hang.....

The above particulars are to be filled in for a rigid frame motor vehicle of two or more axles for an articulated vehicle of three or more axles or, to the extent applicable, for trailer, where a second semi-trailer or additional semi-trailer are to be registered with an articulated motor vehicle. The following particulars are to be furnished for each such semi-trailer.

33.

Type of body

.....

34.

Unladen weight

.....

35.

Number, description and size of tyres on each axle

.....

36.

Maximum axle weight in respect of each axle

.....

37.

The vehicle is covered by a valid certificate of insurance under Chapter XI of the Act
Insurance Certificate or Cover Note

No.....

Date.....

Of.....

(Name of company) valid from

.....to.....

38.

The vehicle is exempted from insurance. The relevant order is enclosed

39.

I have paid the prescribed fee of rupees.....

Date.....

Signature or thumb-impression of the person to be registered as registered owner

The Central Motor Vehicles Rules, 1989

Note:-The motor vehicle above described is

(i)
Subject to Hire-purchase agreement/Lease agreement
with.....
.....

(ii)
Subject to Hypothecation in favour
of.....
.....

(iii)
Not held under Hire-purchase agreement, or lease agreement, or subject to Hypothecation

*Strike out whatever is inapplicable. If the vehicle is subject to any such agreement the signature of the
Financier with whom such agreement has been entered into is to be obtained.

.....
.....

Signature of the Financier with whom an agreement of Hire-purchase, Lease or Hypothecation has been entered into.

Signature or thumb-impression of the Registered Owner

CERTIFICATE OF INSPECTION OF MOTOR VEHICLE

Certified that the particulars contained in the application are true and that the vehicle complies with the requirements of
the Motor Vehicles Act, 1988 and the Rules made thereunder.

Date.....

Signature of the Inspecting Authority

Ref. No.....Name.....

Designation.....

Office of the.....

OFFICE ENDORSEMENT

The above said motor vehicle has been assigned the Registration number.....and
registered in the name of the applicant and the vehicle is subject to an agreement of
Hire-purchase/Lease/Hypothecation with the Financier referred above.

Date..... Signature of the Registering Authority

To

The Financier.....
.....

(To be sent by registered post acknowledgment due)

Specimen signature or thumb-impression of the person to be registered as Registered Owner and Financier are to be
obtained in original application for affixing and attestation by the Registering Authority with office seal in Forms 23 and
24 in such a manner that the part of impression of seal or a stamp and attestation shall fall upon each signature.

Specimen signature of the Financier

Specimen signature of the Registered Owner

(1).....

(1).....

(2).....

(2).....]

FORM 21

[See rules 47(a) and (d)]

SALE CERTIFICATE

[(To be issued by manufacturer or dealer or registered E-rickshaw or E-cart Association (in case of E-rickshaw or E-cart)
or officer of Defence Department (in case of military auctioned vehicles) for presentation along with the application for
registration of a motor vehicle).]

[Substituted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

Certified that.....

(brand name of the vehicle)

has been delivered by us to..... on..... (date)

Name of the buyer

.....

Son/wife/daughter of

.....

Address (Permanent)

.....

(Temporary)

.....

The vehicle is held under agreement of hire-purchase/lease/hypothecation with.....

The details of the vehicle are given below:

1.

Class of vehicle

.....

2.

Maker's name

.....

3.

Chassis No.

.....

4.

[Engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

.....

5.

Horse power or cubic capacity

.....

6.

Fuel used

.....

7.

Number of cylinders

.....

8.

Month and year of manufacture

.....

9.

Seating capacity (including driver)

.....

10.

Unladen weight

.....

11.

Maximum axle weight and number and description of tyres (in case of transport vehicle)

.....

(a)Front axle

.....

(b)Rear axle

.....

(c)Any other axle

.....
(d)Tandem axle

.....
12.
Colour or colours of the body

.....
13.
Gross vehicle weight

.....
14.
Type of body

.....
[Signature of the Manufacturer or dealer or officer of Defence Department or registered E-rickshaw or E-cart Association]

[Substituted by Notification No. G.S.R. 27 (E) dated 13.1.2015 (w.e.f. 2.6.1989)]

/ Dealer

or Officer of Defence Department

*Strike out whichever is inapplicable.

[FORM 22]

[Substituted by Notification No. G.S.R. 953 (E), dated 5.10.2016 (w.e.f. 1.4.2017).]

[See Rules 47(g), 115, 124(2) and 127]

Initial Certificate of Compliance with Pollution Standards, Safety Standards of Components and Road-Worthiness

To be issued by the manufacturer or registered E-rickshaw or E-cart Association in case of E-rickshaw or E-cart

It is certified that the following vehicle complies with the emission values, including mass emission norms and noise standards including noise level under the provisions of the Motor Vehicles Act, 1988, and the rules made thereunder as specified below:

1. Brand name of the vehicle:

2. Chassis number:

3. Engine number (motor number, in case of battery operated vehicles):

4. Emission norms applicable:

[Bharat Stage- IV/ VI/ Bharat (Trem) Stage-III/III A etc.]

5. The emission, sound level for horn and pass by noise values of the above vehicle model, obtained during Type Approval as per Central Motor Vehicle Rules, 1989 are given below:

(i)

Emission values [refer rule 115 (2)] :

(a)

For Petrol/ CNG/LPG/ Electric-Hybrid vehicles

Sr.

No.

Pollutant

Mass

in gram/ kilometer or gram/ kilowatt per hour

(1)

(2)

(3)

1

Carbon

Monoxide

2

Hydro

Carbon

3

Non-Methane

HC

4

NO_x,

if applicable

5

HC

+ NO_x, if applicable

(b)

For diesel vehicles :

Sr.

No.

Pollutant

Mass

in gram/ kilometer or gram/ kilowatt per hour

(1)

(2)

(3)

1

Carbon

Monoxide

2

Hydro

Carbon

3

Non-Methane

HC

4

NO_x,

if applicable

5

HC

+ NO_x, if applicable

6

PM

(ii)

Noise level (refer rules 119 and 120) :

(a)

horn (for all vehicles other than agricultural tractors and construction equipment vehicles) as installed on the vehicle:

..... dB(A);

(b)

Bystander's position (for all vehicles other than agricultural tractors and construction equipment vehicles)

dB(A);

(c)

Operator's ear level (for agricultural tractors and construction equipment vehicles)dB(A)

(Signature of manufacturer or of authorised signatory of registered E-rickshaw or E-cart Association)

Note 1: This Form shall be issued with the signature of the manufacturer duly printed in the Form itself by affixing facsimile signature in ink under the hand and seal of the manufacturer.

Note 2: In the case of e-rickshaw or e-cart, this Form shall be issued with the signature of an authorized signatory of

registered E-rickshaw or E-cart association duly printed in the Form itself by affixing facsimile signature in ink under the hand and seal of such signatory.

[FORM 22-A

[Substituted by GSR 784(E), dated 12.11.2008 (w.e.f. 1.4.2009).]

[See Rules 47(g), 115, 124(2), 125C*, [125F, 125G]

[Substituted by Notification No. G.S.R. 287 (E) dated 22.4.2014 (w.e.f. 2.6.1989)]

, 126A, 127]

INITIAL CERTIFICATE OF COMPLIANCE WITH POLLUTION STANDARDS, SAFETY STANDARDS OF COMPONENTS AND ROAD-WORTHINESS (FOR VEHICLES WHERE BODY IS FABRICATED SEPARATELY)

Part I

(TO BE ISSUED BY THE MANUFACTURER)

Certified that the following vehicle complies with the provisions of the Motor Vehicles Act, 1988, and the rules made thereunder, including the following mass emission norms:

Purchased from the Dealer Name and Address

.....

Name of the Registered Owner

.....

Son/wife/daughter of

.....

Full address (Permanent)

.....

Full address (Temporary)

.....

37[PAN No.

.....

Signature of chassis manufacturer

Form 22-A, Part I shall be issued with the signature of the manufacturer duly printed in the Form itself by affixing facsimile signature in ink under the hand and seal of the manufacturer

[PART-II]

[Substituted by Notification No. G.S.R. 287 (E) dated 22.4.2014 (w.e.f. 2.6.1989)]

(To be issued by the body builder)

Certified that the body of the following vehicle has been fabricated by us and the same complies with the provisions of the Motor Vehicles Act, 1988, and the rules made there under:

1. Brand name of the vehicle _____

2. Chassis No. _____

3. Engine No./Motor No. _____

*4. Bus Body Builder Accreditation Certificate Number _____ Date _____ valid up to date _____.

[Substituted by Notification No. G.S.R. 868(E), dated 8.9.2016 (w.e.f. 2.6.1989).]

*5. Vehicle Body construction (Bus/ Road Ambulance/ Motor Caravan/ etc.) Type Approval Certificate Number _____ Date _____ issued by the approved Test Agency.]

* Applicable for buses only

(Signature of the body builder)

[Form 22-A Part II shall be issued with the signature of the body builder duly printed in the Form itself by affixing facsimile signature in ink under the hand and seal of the body builder.]

[FORM 23

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[See rule 48]

CERTIFICATE OF REGISTRATION

Registration Number.....

Brief description of vehicle.....

(e.g. Fiat/Ambassador/Maruti Car, Tata/Ashok Leyland Goods Vehicle, Trailer, Motor Cycle with/without gear, Motor

Cycle with side car, etc.)

Purchased from the Dealer Name and Address

.....

Name of the Registered Owner

.....

Son/wife/daughter of

.....

Full address (Permanent)

.....

Full address (Temporary)

.....

[PAN No.

[Substituted by G.S.R. 708(E), dated 30.8.2010.]

.....]

[Inserted by GSR 148(E), dated 4.3.2009 (w.e.f. 4.3.2009).]

Signature of Registering Authority.....

Date.....

Specimen signature of the REGISTERED OWNED to be affixed and attested by REGISTERING AUTHORITY with his seal

DETAILED DESCRIPTION

1.

Class of vehicle

.....

The motor vehicle is-

.....

(a) a new vehicle

.....

(b) ex-army vehicle

.....

(c) imported vehicle

.....

(d) migration from other States

.....

2.

Maker's name

.....

Dealer's name and address

.....

3.

Type of body

.....

4.

Month and year of manufacture

.....

5.

Number of cylinders

.....

6.

Chassis Number

.....

7.

[Engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

.....

8.

Fuel used in the engine

.....

9.

Horse Power (B.H.P.)

.....

10.

Cubic Capacity

.....

11.

Maker's Classification

.....

12.

Wheelbase

.....

13.

Seating capacity (including driver)

.....

14.

Unladen weight

.....

15.

Colour or colours of body, wings and front end

.....

*Additional particulars in the case of all transport vehicles other than motor cabs

.....

16.

Gross vehicle weight

.....

(a) as certified by the manufacturer

.....kgms

(b) as registered

.....kgms

17.

[Number, description, size and ply rating of tyres,as declared by the manufacturer]

[Substituted for 'Number, description and size of tyres'by GSR 214(E), dated 18.3.1999 (w.e.f. 18.9.1999).]

.....

(a) Front axle

.....

(b) Rear axle

.....

(c) Any other axle

.....

(d) Tandem axle.

.....

Additional particulars of alternative or additional semi-trailer registered with an articulated vehicle

.....

18.

Registered axle weight

.....kgms

(a) Front axle

.....kgms

(b) Rear axle

.....kgms

(c) Any other axle

.....kgms

(d) Tandem axle

.....kgms

19.

Type of body

.....

20.

Unladen weight

.....

21.

Number, description and size of tyres on (each) axle

.....

22.

Registered axle weight (in respect of each axle)

.....

This certificate is valid from.....to.....

Date.....

Signature of the Registering Authority

Note. The motor vehicle above described is

(i)

Subject to a Hire-purchase agreement with

(ii)

Subject to Lease agreement with

(iii)

Subject to Hypothecation in favour of Specimen signature of the Financier (to be affixed)

and attested by the Registering Authority with his seal

Signature of the Registering Authority

Date.....

This certificate is renewed:

From.....

to

.....

Date.....

to

Signature of the Registering Authority

From.....

to

.....

Date.....

to

Signature of the Registering Authority

From.....

to

.....

Date.....

to

Signature of the Registering Authority

From.....

to

.....

Date.....

to

Signature of the Registering Authority

Notes:-

(i)

This shall be in the form of a book having sufficient pages for recording transfer of ownership, change of address, hire-purchase endorsement, cancellation of hire-purchase entries, alteration, suspension and cancellation of certificate of registration, etc. Such entries shall be duly numbered serially in chronological order date wise.

(ii)

Strike out whichever is inapplicable.

(iii)

Wherever transfer of ownership/change of address/note and cancellation of endorsement of any agreement is recorded, specimen signature of the registered owner and financier, as the case may be, shall be affixed, sealed and attested by the registering authority next to the recording, in such manner that part of impression of the seal or stamp and attestation shall fall upon the signature.

(iv)

For two-wheeler and cars, a book be provided without additional particulars of the transport vehicle and trailer or semi-trailer.

(v)

For transport vehicles, a book can be provided without the column of renewal of registration.]

[FORM 23-A

[Inserted by GSR 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

(See rule 48)

CERTIFICATE OF REGISTRATION (IN ELECTRONIC MEDIUM AS SMART CARD, ETC.)

Particulars to be printed on the Visual Inspection Zone of Smart Card:

CONTENTS OF VISUAL INSPECTION ZONE

CERTIFICATE OF REGISTRATION

1. Name of State Transport Department

2. Card Serial Number

3. Vehicle Registration Number

4. Registration Date (In dd-mm-yyyy)

5. Owner's Details:

5.1

Name

5.2

Son/Wife/Daughter of

5.3

Address: Current Postal Address

5. [4 PAN No.....]

[Substituted by G.S.R. 708(E), dated 30.8.2010.]

6. Vehicle's Details:

6.1

Name of Manufacturer with Make

6.2

Colour

6.3

Fuel

6.4

Vehicle Class

6.5

Body Type

6.6

Seating Capacity

6.7

Standing Capacity

6.8

Date of Manufacture (In mm-yyyy)

6.9

Unladen Weight

6.10

Cubic Capacity

6.11

Wheel Base

6.12

Number of Cylinders

6.13

Owner Serial (Optional)

6.14

Chassis Number

6.15

[Engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

7. [Home State tax paid upto (in dd-mm-yyyy)]

[Substituted by G.S.R. 386(E), dated 7.5.2010.]

8. Registration Validity (In dd-mm-yyyy)

9. Signature of Issuing Authority

10. Identification of Issuing Authority

CONTENTS OF MACHINE READABLE ZONE

11. Chip Serial Number

12. Owner Serial (No. of this the ownership has changed)

13. Tax Date (Date of Validity of Tax): dd-mm-yyyy

14. Registration Validity (In dd-mm-yyyy)

15. Hypothecation Details:

15.1

Name of Financier

15.2

Address of Financier

15.3

Hypothecated from (In dd-mm-yyyy)

15.4

Hypothecated up to (In dd-mm-yyyy)

16. NOC Details:-(Future use)

16.1

NOC Number

16.2

State to (Code only)

16.3

RTO to

16.4

NCRB Clearance Number

16.5

NOC Issue Date (In dd-mm-yyyy)

17. Insurance Details: (Future use)

17.1

Name of Company

17.2

Cover note/Policy Number

17.3

Type of Insurance

17.4

Validity up to (In dd-mm-yyyy)

18. Pollution Under Control Details:-(Future use)

18.1

Checking Centre (Code only)

18.2

Validity up to (In dd-mm-yyyy)

19. Tax Payment Details:

Amount

Fine

Exemption/Receipt Number

Payment Date (In dd-mm-yyyy)

Valid from (In dd-mm-yyyy)

Valid up to (In dd-mm-yyyy)

Exemption (Y/N)

20. Fitness Details:

Validity (In dd-mm-yyyy)

Inspecting Officer

Location

21. Additional Information in respect of Transport Vehicle:-

Gross Vehicle Weight (In Kgs.)

Number, Description and Size of Tyres

Registered Axle Weight

Number of Semi-Trailers

22. Challan Details:-

Challan Number

Accused Person (O-Owner, D-Driver, C-Conductor)

Section (Code only)

Challaning Officer

Location

Date and Time (In dd-mm-yyyy/hh:mm)

Disposing Authority (R-RTO, C-Court)

Disposal Date (In dd-mm-yyyy)

Penalty

Receipt Number

23. Permit Details:

Permit Number

Type of Permit

Validity from (In dd-mm-yyyy)

Validity up to (In dd-mm-yyyy)

Area of Operation

Route from

Route up to

Stage 1

Stage 2

Stage 3

24. Permit Actions:

Action Code SUR/SUS/CAN

From Date (In dd-mm-yyyy)

Up to Date (In dd-mm-yyyy)

Reason

25. All India Tourist Permit Details:-

From Date (In dd-mm-yyyy)

Up to Date (In dd-mm-yyyy)

26. [Authorisation Details:

For Tourist Permit:

State (Code only), Authorisation Number, Validity from (In dd-mm-yyyy), Validity upto (In dd-mm-yyyy), Bank Draft Amount Bank Draft Number Bank (Code only), Bank Draft Issue Date (In dd-mm-YYYY).....

For National Permit (valid for operation throughout the territory of India):-

Authorisation Number, Validity from (In dd-mm-yyyy), Validity upto (In dd-mm-yyyy), Amount paid unique receipt number receipt date (In ddmm-yyyy), Bank (Code only) Branch]

27. Counter Signature Details:

Authorising Officer

Validity from (In dd-mm-yyyy)

Validity up to (In dd-mm-yyyy)

Route from

Route up to

Stage 1

Stage 2

Stage 3

28. In case of Auto-rickshaw/Local Taxies:-

Meter Number

Note:-(i) At the time of payment of next instalment of tax, the Issuing Authority shall issue a paper receipt stating that date of validity of tax paid has been extended from so and so date to so and so date. The receipt shall be duly signed by Designated Authority. Name of Issuing Authority shall also be clearly spelt out. The receipt shall be security printed watermark paper carrying such hologram as may be specified by the concerned State.

Note:-(ii) In respect of articulated vehicle, additional information of trailer not required.]

[FORM 24]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[Substituted by Notification No. G.S.R. 386 (E) dated 7.5.2010 (w.e.f. 2.6.1989)]

[See rule 49]

REGISTER OF MOTOR VEHICLE

Description of registration of motor vehicle

Particulars of registered owner on registration/transfer of ownership/change of Address of motor vehicle

Particulars of agreement of hire-purchase, lease and hypothecation

Entries relating to the certificate of registration

Remarks

Particulars

Details

Full Name, Son/wife/daughter of, Present Address

Specimen signature pasted and attested by Registering Authority with official seal affixed

Note and cancellation of an endorsement of such agreement with full name and address of the Financier, attested by Registering Authority

Specimen signature or thumb-impression of Financier, pasted and attested by Registering Authority

Such as suspension/cancellation, issue of duplicate (to the Registered Owner)/fresh

(to the Financier); and exemption granted, N.O.C. issued, vehicle removed to other Dist./State, Alteration of vehicle

1

2

3

4

5

6

7

8

1.Registration No.

1. Registration No.

2. Date of registration

3. Name of the owner

son/wife/daughter of

Full address (Permanent)

(Temporary)

4. Dealers name and address

5. Particulars of previous registration number, viz.

(a) The name of the Registering Authority

(b) Registration Number assigned

(c) Date of expiry of registration

(d) Whether held under HP/Lease & Hypothecation

(e) If so, particulars of Financier, etc.

6. The motor vehicle is

(a) new

(b) ex-army

(c) imported

45[7. Class of vehicle (if motor cycle, with gear or without gear)]

[Substituted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000).]

8. Makers name

9. Type of body

10. Month and year of manufacture

11. No. of Cylinders

12. Classes No. Affix pencil print and to be attested by the Registering Authority

13.[Engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

14. Fuel used in engine

15. Horse power

16. Cubic capacity

17. Makers classification

18. Wheel base

19. Seating capacity including driver

20. Colour or colours of body, wings, front end

21. Unladen weight

22. Gross vehicle weight

(i) as certified by the manufacturer

(ii) as registered

23. Additional particulars in case of transport vehicle other than motor cabs.

1. No. description and size of tyres,

Front axle

Rear axle

Any other axle

Tandem axle.

2. Registered axle weight

Front axle.....

kg.

Rear axle.....kg.

Any other axle..... kg.

Tandem axle..... kg.

24. Additional particulars of alternatives or additional trailer or semi-trailers registered with an articulated vehicle

1. Type of body

2. Unladen weight

3. Number and description and size of tyre on each axle

4. Registered axle weight in respect of each vehicle

25. Insurance certificate/

Cover Note no.....

dated..... vehicle valid forum.....

to..... issued by..... (Name and address of the insurance company)

26. Rate of motor vehicle tax.

27. Validity of registration from..... to..... renewal from..... to

28. Name and designation of

the Inspecting Officer who certified the vehicle as fit for registration

29. Name and designation and signature of the Registering Authority

Note: Specimen signature of the registered owners and financiers pasted in columns 4 & 6, respectively, shall be attested with office seal by the Registering Authority in such a manner that the part of impression of seal or stamp and attestation shall fall upon each signature.]

FORM 25

[See rule 52(1)]

FORM OF APPLICATION FOR RENEWAL OF CERTIFICATE OF REGISTRATION OF A MOTOR VEHICLE, OTHER THAN A TRANSPORT VEHICLE

To

The Registering Authority,

.....

.....

I..... hereby apply for the renewal of a trade certificate of registration which is attached, the particulars of which are as follows:

(a) Registered No.

.....

(b) Date of issue

.....

(c) Date of expiry

.....

(d) Registering Authority by which the certificate was issued/last renewed

.....
My present address is..... If this address is not entered in the certificate of registration, I do/do not wish that it should be so entered. The renewal of the certificate has not been refused by any Registering Authority.

I hereby declare that the certificate of registration has not been cancelled or suspended by any Registering Authority.

1.

Class of vehicle

2.

The motor vehicle was registered as

(a) A new vehicle

(b) Ex-army vehicle

(c) Imported vehicle

3.

Type of body

4.

Maker's name

5.

Month and year of manufacture

6.

Number of cylinders

7.

Cubic capacity/Horse power

8.

Maker's classification

9.

Chassis No.-Affix pencil print

10.

[Engine number or motor number in the case of Battery Operated Vehicles].

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

11.

Seating capacity (including driver)

12.

Unladen weight

13.

Fuel used

I enclose the certificate of insurance for perusal and return.

I have paid the fee of Rs.....

Date:.....

[Signature or thumb-impression of the applicant]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

Note: The motor vehicle above described is not subject to an agreement of hire-purchase, lease or hypothecation.

The vehicle is:

*(i) Subject to hire-purchase agreement/lease agreement with.....

*(i:) Subject to hypothecation in favour of.....

"Strike out whichever is inapplicable

[Signature or thumb-impression of the registered owner]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[Specimen signature or thumb-impression of the registered owner:]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

1.

2.

3.

CERTIFICATE

Inspected the vehicle-verified the chassis number and engine number.

Certified that the particulars contained in the application and the corresponding particulars declared in the certificate of registration of the vehicle are true and that the vehicle complies with the requirements of the Motor Vehicles Act, 1988, and the Rules made thereunder.

Signature of the Inspecting Authority

Name.....

Designation.....

[FORM 26]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[See rule 53]

APPLICATION FOR THE ISSUE OF DUPLICATE CERTIFICATE OF REGISTRATION

(To be made in duplicate if the vehicle is held under an agreement of hire-purchase/lease/hypothecation and in triplicate if the Original Registering Authority is different, the duplicate copy and the triplicate copy with the endorsement of the Registering Authority to be returned to the Financier and Registering Authority simultaneously on issue of duplicate certificate)

To

The Registering Authority

.....

The certificate of registration of my/our moto1 kle, the registration mark of which is..... has been lost/destroyed/completely written off/soiled/torn/mutilated in the following circumstances.

.....
.....

. *I/We hereby declare that to the best of my/our knowledge the registration of the vehicle has not been suspended or cancelled under the provisions of the Act or Rules made thereunder and the circumstance, explained above are true.

I/We do hereby apply for the issue of a duplicate certificate of registration.

The written off/soiled/torn/mutilated Certificate of Registration is enclosed.

The vehicle is not held under any agreement of hire-purchase/lease/hypothecation. The vehicle is also not supcrdari and free from all encumbrances.

I/We hereby declare that I/We on..... (date) have filed a complaint (copy enclosed) w i t h the police about the loss of Certificate of Registration immediately of ter the loss has been noticed.

Date:.....

Signature/thumb-impression of Applicant

*Strike out whichever is inapplicable.

The vehicle is held under hire-purchase/lease/hypothecation agreement with..... and the "No Objection Certificate" has been granted/refused by the Financier hereunder: [Where No Objection Certificate" is refused, applicant shall make a declaration as required under sub-section (8) of section 51.

Signature or thumb-impression of the Owner

Name.....

Full address.....

Date.....

Note:-(1) Full particulars of the circumstances shall be furnished in the case of loss or destruction of the Registration Certificate.

(2)

Strike out whichever is inapplicable.

CONSENT OF THE FINANCIER FOR GRANT OF "NO OBJECTION CERTIFICATE" UNDER SECTION 51(6)

I/We being a party to an agreement of hire-purchase/lease/hypothecation in respect of motor vehicle specified above:

(1)

have "No Objection" in issue of the duplicate certificate of registration of the said vehicle.

(2)

have "Objection" in issue of the duplicate registration certificate of the said vehicle, for the reasons

Given hereunder.....

Signature of the Financier

Date.....

OFFICE ENDORSEMENT

Ref. Number..... Office of the.....

A duplicate certificate of registration as requested above is issued with the note of agreement of hire purchase/lease/hypothecation on..... and is noted in the original registration records in Form 24.

Signature of the Registering Authority

Date.....

To.....

The Financier

The Registering Authority.....

(To be sent to both the above parties by registered post acknowledgement d u c)

Specimen signature or thumb-impression of the Registered Owner and Financier are to be obtained in original application for affixing and attestation by the Registering Authority with the Office seal in Forms 23 and 24 in such a manner that the part of impression of seal or a stamp and attestation shall fall upon each signature.

Specimen signature of the Financier

Specimen signature of the Registered Owner

1.

2.

1.

2.

[FORM 27]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[See rule 54]

APPLICATION FOR ASSIGNMENT OF NEW REGISTRATION MARK TO A MOTOR VEHICLE

(To be made in triplicate if the vehicle is held under an agreement of hire-purchase/lease/hypothecation and in duplicate copy and the triplicate copy with endorsement of the Registering Authority to be returned to the Financier and Original Registering Authority simultaneously, on the assignment of a new registration mark).

To

The Registering Authority,

.....

I/We.....son/wife/daughter
of.....being the Registered Owner of Motor Vehicle
No..... bearing Chassis No..... [Engine number or motor number in the case of
Battery Operated Vehicles]
[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]
Type of vehicle..... Registered in the State of..... hereby declare that I/We have, since
the..... day of..... kept the said motor vehicle in this State and hereby
apply for the assignment of a new registration mark to the said motor vehicle.
I/We hereby declare that the registration is valid up to..... and it has not been
suspended or cancelled under the provisions of this Act.
I/We enclose the certificate of registration and the certificate of fitness (*) of this motor vehicle.
I/We enclose a "No Objection Certificate" from the Registering Authority.
If the "No Objection Certificate" from the Registering Authority is not enclosed the applicant should file along with this
application a declaration as required under the first proviso to sub-section (1) of section 47.
*The vehicle is not subject to an agreement of hire-purchase/lease/hypothecation.
The vehicle is subject to an agreement of hire-purchase/lease/hypothecation with..... and the
NOC has been granted/refused by the Financier thereunder.
If "No Objection Certificate" has been refused by the Financier, the applicant should file along with this application a
declaration as required under sub-section (8) of section 51.
Date..... Signature or thumb-impression of the Applicant
*Strike out whichever is inapplicable.
CONSENT OF THE FINANCIER FOR GRANT OF "NO OBJECTION
CERTIFICATE" UNDER SECTION 51(6)
I/We, being a party to an agreement of hire-purchase/lease/hypothecation in respect of motor vehicle specified above:
(1)
have "No Objection" in assigning the new Registration mark to the said Vehicle
(2)
have "Objection in assigning the new Registration mark to the said Vehicle for the reasons given
hereunder.....
.....
Date..... Signature of the Financier
OFFICE ENDORSEMENT
Ref. Number.....Office of the.....
The Vehicle No..... on removal to this State has been
assigned a new Registration mark..... (here enter the Registration mark).
Date.....Signature of the Registering Authority
To
The Financier.....
.....
The Registering Authority.....
.....
(to be sent to both the above parties by registered post acknowledgement due).
[FORM 28
[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]
[See rules 54,58(I), (3) and (4)]
APPLICATION AND GRANT OF NO OBJECTION CERTIFICATE
(To be made in quadruplicate if the vehicle is held under an agreement of hire-purchase/lease/hypothecation and in
duplicate copy, the triplicate copy and the quadruplicate copy with the endorsement of the Registering Authority to be
returned to the Registered owner of the vehicle, the Registering Authority in whose jurisdiction the vehicle is to be
removed and the Financier simultaneously on grant/refusal of a 'No Objection Certificate')PART I-APPLICATION

To
The Registering Authority,
.....

I/We intend to transfer the vehicle to the jurisdiction of the Registering Authority

I/We intend to sell the vehicle to Shri/Smt./Kumari..... who
resides in the jurisdiction of the Registering Authority..... of I/We, therefore,
request for the issue of a No Objection Certificate for my/our vehicle, the particulars of which are furnished below:

1.
Name and address
.....
2.
Son/wife/daughter of
.....
3.
Registration number of the vehicle
.....
4.
Class of vehicle
.....
5.
Registering Authority which originally registered the vehicle
.....
6.
53[Engine number or motor number in the case of Battery Operated Vehicles]
[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]
.....
7.
Chassis number
(Affix also pencil print)
.....
8.
Period of stay in the State
.....
9.
Period up to which motor vehicle tax has been paid
.....
10.
Whether any demand for tax is pending, if so, give details
.....
11.
Whether the vehicle is involved in any theft cases, if so, give details
.....
12.
Whether any action under section 53, 54 or 55 of the Motor Vehicles Act, 1988 is pending before any Registering
Authority or other prescribed authority, if so, give details
.....
13.
Whether the vehicle is involved in any case of transport of prohibited goods, if so, give details
.....
14.
Whether the vehicle is held under an agreement of hire-purchase/lease/hypothecation, if so, give full name and address

of the Financier]

.....
We solemnly declare that the above statement is true.

Date.....

Signature or thumb-impression of Registered Owner

Part 11 ? CONSENT OF THE FINANCIERS IN THE CASE OF MOTOR

VEHICLE SUBJECT TO AN AGREEMENT

I/We being a party to an agreement of the hire-purchase/lease/hypothecation in respect of the above said vehicle hereby

1. Give consent to issue the No Objection Certificate for the said vehicle only for the purpose referred above.
2. Refuse to give consent for issue of No Objection Certificate for the said vehicle due to the reasons furnished hereunder:

.....
.....
.....
Date..... Signature of the Financier

Part III ? OFFICE ENDORSEMENT

(GRANT/REFUSAL OF "NO OBJECTION CERTIFICATE" UNDER SECTION 48(3) OF MOTOR VEHICLES ACT, 1988)

(1)

No Objection Certificate in respect of the vehicle, the detailed particulars whereof are recorded over above is hereby granted under section 48(3) of the Motor Vehicles Act, 1988 (valid for use at the Registering Authority, on whom it is issued)

(2)

No Objection Certificate in respect of the motor vehicle, the detailed particulars whereof recorded over above is hereby refused under section 48(3) of the Motor Vehicles Act, 1988, for the reasons recorded as under:.....

Date.....

Signature with seal of Registering Authority

Address.....

"Strike out whichever is inapplicable.

To

The Registered Owner.....

The Financier.....]

[FORM 29]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[See rule 55(1)]

NOTICE OF TRANSFER OF OWNERSHIP OF A MOTOR VEHICLE

(To be made in duplicate and the duplicate copy with the endorsement of the Registering Authority to be returned to the transferor immediately on making entries of transfer of ownership in Certificate of Registration and Form 24).

To

The Registering Authority..... (in whose jurisdiction the Transferee resides)

I/We..... resident of..... have on the.....day of the

year..... sold and delivered my/our Vehicle No.....

make.....Chassis No..... [Engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

..... to

Shri/Smt..... (Name) son/wife/daughter of..... residing

at..... (House No./Street/Village/Town/Distt. and State) under an agreement of

hire-purchase/lease/hypothecation with..... The

Registration Certificate and Insurance Certificate have been handed over to him/her/them.

To the best of my/our knowledge and belief the vehicle is not superdari and free from all encumbrances and information

furnished is true. I/We undertake to hold my/our self responsible for any inaccuracy or suppression of information.

Signature of the Financier

(to give his consent)

Date.....

Signature or thumb-impression of the Registered Owner(Transferor)

Date.....

I/We..... (Transferee)

Copy to: The Registering Authority..... in whose jurisdiction the transferor resides.

Note:-To be sent to the Registering Authority by registered post acknowledgement due.....

OFFICE ENDORSEMENT

Ref. No..... Office of the..... The ownership of the vehicle has been transferred to the name of..... with the note of the above said agreement with effect from..... (date)Date.....

Signature of the Registering Authority

with Office Seal.

*Strike out whichever is inapplicable.

[FORM 30]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[See rule 55(2) and (3)]

APPLICATION FOR INTIMATION AND TRANSFER OF OWNERSHIP OF A MOTOR VEHICLE

(To be made in duplicate if the vehicle is held under an agreement of hire-purchase/lease/hypothecation. The duplicate copy with the endorsement of the Registering Authority to be returned to the Financier simultaneously on making the entry of the transfer of ownership in the certificate of registration and registration record in Form 24).

To

The Registering Authority.....

Part I ? FOR THE USE OF THE TRANSFEROR

Name of the Transferor..... son/wife/daughter of..... Full address..... I/We

hereby, declare that I/We have on this..... day of the year..... sold my/our motor vehicle bearing Registration mark..... to Shri/Smt.....

son/wife/daughter of..... residing at..... (full address) and handed over the Certificate of Registration and the Certificate of Insurance to him/her/them.

I/We hereby declare that to the best of my/our knowledge the Certificate of Registration of the vehicle has not been suspended* or cancelled.

*I enclose the "No objection certificate" issued by the Registering Authority.

**If the "No objection certificate" issued from the Registering Authority is not enclosed, the transferor should file along with this application a declaration as required under sub-section (1) of section 50.

Date..... Signature or thumb-impression of the Transferor

*Details of suspension or cancellation.

**Strike out whichever is inapplicable.

Part II ? FOR THE USE OF THE TRANSFeree

Name of the Transferee..... son/wife/daughter of..... Age..... Full address..... (Proof of address to be enclosed).

I, hereby declare that I/We have on this..... day of the year..... purchased the motor vehicle bearing registration number..... from..... (name and full address) and request that necessary entries regarding the transfer of ownership of the vehicle in my/our case may be recorded in the certificate of registration/certificate of fitness of the vehicle, which is enclosed.

The Certificate of Insurance is also enclosed. To the best of my knowledge and belief I/We have not suppressed any facts and information furnished is true. The vehicle is not superdary and free from all encumbrances. I/We undertake to

hold myself/ourselves responsible for any inaccuracy of the information.

Date.....

Signature or thumb-impression of the Transferee

CONSENT OF THE FINANCIER IN THE CASE OF MOTOR VEHICLE SUBJECT TO AN AGREEMENT OF HIRE-PURCHASE/LEASE/HYPOTHECATION

I/We being a party to an agreement of hire-purchase/lease/hypothecation in respect of motor vehicle specified above, give consent to the transfer of ownership of the said motor vehicle in the name of the Transferee named above, with whom I/We have entered into an agreement of hire-purchase/lease/hypothecation.

(Full name and address of the Financier)Signature of the Financier

Date..... Date.....

OFFICE ENDORSEMENT

Ref. No..... Office of the..... The transfer of ownership of vehicle under continuation of an endorsement of hire-purchase/lease/hypothecation agreement has been recorded with effect from..... in the Registration Certificate of the vehicle..... and in the Registration record of this office in Form 24.

Date.....

Signature of the Registering Authority

To

The Transferor

The Financier

(To be sent to both the above parties by registered post acknowledgement due)

Specimen signature or thumb-impression of the Registered Owner and the Financier are to be obtained in the original application for affixing and attestation by the Registering Authority with the office seal in Forms 23 and 24, in such manner that the part of impression of seal or stamp and attestation shall fall upon each signature.

Specimen signature of the Financier

Specimen signature of the Registered Owner

1.

1.

2.

2.

[FORM 31]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993)]

[See rule 56(2)]

APPLICATION FOR TRANSFER OF OWNERSHIP IN THE NAME OF THE PERSON SUCCEEDING TO THE POSSESSION OF THE VEHICLE

(To be made in duplicate if the vehicle is held under an agreement of hire-purchase/lease/hypothecation and duplicate copy with the an endorsement of the Registering Authority to be returned to the Financier simultaneously on making the entry of Transfer of ownership in the certificate of registration and office record in Form 24).

To

The Registering Authority,

.....

1.

Vehicle Registration No.

.....

Make and model

.....

Chassis No.

.....

[Engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

.....

Type of vehicle

.....

2.

Name of the deceased registered owner

.....

3.

Name and age of the person succeeding to the possession of the vehicle son/wife/daughter of

.....

Full postal address

(proof of address to be enclosed)

.....

4.

Relationship with the deceased registered owner

.....

5.

Proof of his succession

.....

Certificate of registration is enclosed herewith. Kindly transfer the ownership of the vehicle in my name.

Date.....

Signature of the Applicant

CONSENT OF THE FINANCIER IN THE CASE OF MOTOR VEHICLE HELD UNDER ANY OF THE AGREEMENTS

I/We being a party to an agreement of hire-purchase/lease/hypothecation in respect of the motor vehicle specified above, consent to the transfer of ownership of the said motor vehicle in the name of the applicant named above, with whom I/We have entered into an agreement of hire-purchase/lease/hypothecation.

.....

.....

.....

(Full name and address of the Financier)Signature of the Financier

Date.....

OFFICE ENDORSEMENT

Ref. Number.....Office of the.....

The transfer of ownership of the motor vehicle under continuation of an endorsement of hire-purchase/lease/hypothecation agreement has been recorded with effect from.....in the certificate of registration of the vehicle and the registration record of this in office Form 24.

Date.....

Signature of the Registering Authority

*Strike out whichever is inapplicable.

To

The Financier

.....

(To be sent by registered post acknowledgement due)

Specimen signature or thumb-impression of the Registered Owner and Financier are to be obtained in original application for affixing and attestation by the Registering Authority with office seal in Forms 23 and 24, in such a manner that the part of impression of seal or stamp and attestation shall fall upon each signature:

Specimen signature of the Financier

Specimen signature of the Registered Owner

1.

1.

2.

2.]

FORM 32

[See rule 57(1)]

APPLICATION FOR TRANSFER OF OWNERSHIP IN CASE OF A MOTOR VEHICLE PURCHASED OR ACQUIRED IN PUBLIC AUCTION

To

The Registering Authority,

.....

I/We..... son/wife/daughter of.....
have..... (full address along

with proof) purchased or acquired the Vehicle No..... bearing Chassis
No..... [Engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

..... make..... model..... type of vehicle. in public auction
conducted by or on behalf of the Government.

I/We enclose the documents required to be submitted by me/us under sub-rule (1) of rule 57.

The ownership of the motor vehicle may kindly be transferred to my/our name.

Date.....

[Signature or thumb-impression of the applicant]

[Substituted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

[FORM 33]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[See rule 59]

INTIMATION OF CHANGE OF ADDRESS FOR RECORDING IN THE CERTIFICATE OF REGISTRATION AND OFFICE RECORDS

(To be made in triplicate if the vehicle is held under an agreement of hire-purchase/lease/hypothecation, the duplicate copy and the triplicate copy with the endorsement of the Registering Authority to be returned to the Financier and the Registering Authority (from whose jurisdiction the vehicle is removed) simultaneously, on making the entry of change of address in the Certificate of Registration and Form 24).

To

THE REGISTERING AUTHORITY,

.....

I/We..... Son/wife/daughter of..... (full address)Registered Owner
of motor vehicle No..... have ceased to reside, do not have the place of business at the address
recorded in the Certificate of Registration with effect from..... The present address is given
below (evidences to be
enclosed).....

.....
The vehicle is not held under any agreement of hire-purchase/lease/hypothecation.

The vehicle is held under an agreement of hire-purchase/lease/hypothecation
with.....

The certificate of registration is enclosed. I/We request that the change of address may be recorded in the certificate of
registration and Form 24.

Date.....Signature or thumb-impression of the

Registered Owner of the vehicle

*Strike out whichever is inapplicable.

CONSENT OF THE FINANCIER IN THE CASE OF MOTOR VEHICLE HELD UNDER AN AGREEMENT

I/We being a party to an agreement of hire-purchase/lease/hypothecation in respect of the above said vehicle, hereby:

1. Give consent for effecting the above change of address with the note of an agreement in my/our favour in Forms 23
and 24 by the Registering Authority.

2. Refuse to give consent for effecting the above change of address by the Registering Authority, due to the reasons
furnished hereunder:

.....

.....
Date.....

Signature of the Financier

OFFICE ENDORSEMENT

Ref. Number..... Office of the.....

The above change of address has been entered with the note of agreement of hire-purchase/lease/hypothecation in favour of the Financier in the certificate of registration and in Form 24.

Date.....

Signature of the Registering Authority

To

The Financier.....

The Registering Authority.....

(To be sent to both the parties by registered post acknowledgement due)

Specimen signature or thumb-impression of the Registered Owner and the Financier are to be obtained in original application for affixing and attestation by the Registering Authority with official seal in Forms 23 and 24 in such a manner that the part of impression of the seal or a stamp and attestation shall fall upon each signature:

Specimen signature of the Financier

Specimen signature of the Registered Owner

1.

1.

2.

2.

[FORM 34]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[See rule 60]

APPLICATION FOR MAKING AN ENTRY OF AN AGREEMENT OF HIRE-PURCHASE/LEASE/HYPOTHECATION
SUBSEQUENT TO REGISTRATION

(To be made in duplicate and in triplicate where the Original Authority is different, the duplicate copy and the triplicate copy with the endorsement of the Registering Authority to be returned to the Financier and the Registering Authority simultaneously on making the entry in the certificate of registration and Form 24).

To

The Registering Authority,

.....

The motor vehicle bearing registration number..... is the subject of an agreement of hire-purchase/lease/hypothecation between..... the registered owner/person to be registered as owner

*and.....(fill the name and full address of the financier)

We request that an entry of the agreement be made in the certificate of registration and the relevant records in your office.

The certificate of registration together with the fee is enclosed.

Date.....

Date.....

Signature or thumb-impression of the Registered owner

Signature of the Financier

*Strike out whichever is inapplicable.

OFFICE ENDORSEMENT

Ref. Number..... Office of the.....

The entry of the agreement of hire-purchase/lease/hypothecation as requested above is recorded in this office registration record in Form 24 and certificate of registration on..... (date).

Date.....

Signature of the Registering Authority

To
The Financier.....
.....
The Registering Authority.....
.....

(To be sent to both the above parties by registered post acknowledgement due)

Specimen signature or thumb-impression of the Registered Owner and the Financier are to be obtained in original application for affixing and attestation by the Registering Authority with his office seal in Forms 23 and 24 in such a manner that the part of impression of the seal or a stamp and attestation shall fall upon each signature:

Specimen signature of the Financier

Specimen signature of the Registered Owner

1.

1.

2.

2.]

[FORM 35]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[See rule 61(1)]

NOTICE OF TERMINATION OF AN AGREEMENT OF HIRE-PURCHASE/LEASE/HYPOTHECATION

(To be made in duplicate and in triplicate where the original Registering Authority is different, the duplicate copy and the triplicate copy with the endorsement of the Registering Authority to be returned to the Financier and the Registering Authority simultaneously on making the termination entry in the certificate of registration and Form 24).

To
The Registering Authority,
.....

We hereby declare that the agreement of hire-purchase/lease/hypothecation entered into between us has been terminated. We, therefore, request that the note endorsed in the certificate of registration of vehicle No..... in respect of the said agreement between us be cancelled.

The certificate of registration together with the fee is enclosed.

Date.....Signature or thumb-impression of the Registered Owner

Date.....Signature of the Financier with official seal and address

*Strike out whichever is inapplicable.

OFFICE ENDORSEMENT

Ref. Number..... Office of the.....

The cancellation of the entry of an agreement as requested above is recorded in this office registration record in Form 24 and registration certificate on..... (date).

Date.....

Signature of the Registering Authority

To
The Financier.....
.....

The
Authority..... Registering
.....

(To be sent to both the above parties by registered post acknowledgement due)

Specimen signature or thumb-impression of the Registered Owner and the Financier are to be obtained in original application for affixing and attestation by the Registering Authority with his office seal in Forms 23 and 24 in such a manner that the part of impression of seal or stamp and attestation shall fall upon each signature.

FORM 36

[See rule 61(2)]

APPLICATION FOR ISSUE OF A FRESH CERTIFICATE OF REGISTRATION IN THE NAME OF THE FINANCIER

To
The Registering Authority,
.....
I/We.....
(Financier)
taken possession of motor vehicle no..... make..... model
..... owing to the default of the registered owner.....
(name)
.....
(full address)
under the provisions of the agreement of hire-purchase/lease/hypothecation:
*(1) The certificate of registration of the said vehicle is surrendered herewith.
*(2) The registered owner has refused to deliver the certificate of registration tome/us.
*(3) The registered owner is absconding.
I/We request you to cancel the certificate and issue a fresh certificate of registration in my/our name.
I/We enclose a fee of Rs.....
Date.....
Signature of the Financier
Specimen signatures of the Financier:
1.
.....
2.
.....

Copy to the original registering authority

*Strike out whichever is inapplicable.

[FORM 37]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[See rule 61(3)]

NOTICE TO THE REGISTERED OWNER OF THE MOTOR VEHICLE TO SURRENDER THE CERTIFICATE OF REGISTRATION FOR CANCELLATION AND ISSUE OF FRESH REGISTRATION CERTIFICATE IN THE NAME OF THE FINANCIER

(To be made in duplicate and duplicate copy to be sent to the Financier simultaneously on issue of notice) Office of the Registering Authority.....

Ref. Number.....

Date.....

Shri/Smt./Kumari..... (Regd. Owner) is/are hereby informed that..... (Financier) has/have reported that he/they have taken possession of the motor vehicle bearing registration number..... covered by an agreement of hire-purchase/lease/hypothecation, owing to your default under the provisions of the said agreement and that

*(1) You have refused to deliver the certificate of registration to him/her/them.

*(2) You have absconded.

He/she/they have requested to cancel the certificate of registration and issue a fresh certificate of registration in his/her/their name.

You are, therefore, directed to surrender the certificate of registration of the said motor vehicle which has been retained by you inspite of your having lost the possession and thereby the ownership of the motor vehicle under section 2(30) and to send your representation in this regard, if any, to this office within seven days from the date of receipt of this notice by you, failing which a fresh certificate of registration will be issued in the name of the Financier, cancelling the certificate of registration held by you, in accordance with section 51(5).

Date.....Signature of the Registering Authority

*Strike out whichever is inapplicable

To

The Financier.....

To be sent by registered post acknowledgement due)

FORM 38

[See rule 62(1)]

CERTIFICATE OF FITNESS (APPLICABLE IN THE CASE OF TRANSPORT VEHICLES ONLY)

Vehicle No..... is certified as complying with the provisions of the Motor Vehicles Act, 1988, and the Rules made thereunder. The certificate will expire on.....

Date.....20..... Signature and designation of Inspecting Authority

or holder of the letter of authority of the authorized testing station.

The certificate of fitness is hereby renewed:-

From..... to..... 20.....

From..... to..... 20.....

From..... to..... 20.....

Signature of Inspecting Authority or the holder of the letter of authority of the authorized testing station.

[Form 38A]

[Inserted by Notification No. G.S.R. 1096 (E), dated 28.11.2016 (w.e.f. 2.6.1989).]

[See rule 62(1)]

Report of inspection conducted on a transport vehicle by an Inspecting Officer or authorised testing station, other than the Inspecting Officer in the office of the registering authority

Vehicle bearing registration number has been inspected by the undersigned today and it is certified that it complies with the provisions of the Motor Vehicles Act, 1988 (

59 of 1988

) and the Central Motor Vehicles Rules, 1989 and is fit for issue of a Fitness Certificate by the registering authority.

This report will be uploaded at the portal <http://parivahan.gov.in/vahan> and the inspection report signed under my hand and seal will be sent to the registering authority by speed post either today or on the next working day for processing the application for issue of certificate of fitness in respect of the vehicle by the registering authority.

Date

Signature, name and designation of the Inspecting Officer or Sign of holder of

Place

Authority letter of authorised testing station

Road Transport Office in which posted. -

District -

State -

Official seal.

FORM 39

[See rule 63(1) and (5)]

FORM OF LETTER OF AUTHORITY ISSUED TO AN AUTHORISED TESTING STATION

Letter of authority No..... Dated.....

The letter of authority is hereby granted to.....

(Name and full address)

for the establishment of a testing station under sub-section (2) of section 56 of the Act at the premises

(Address of the premises in full)

for the purpose of issue and renewal of certificate of fitness to transport vehicles, subject to the provisions of the Motor Vehicles Act, 1988, and the Central Motor Vehicles Rules, 1989, made thereunder.

This letter of authority is valid from..... to.....

Date.....

Registering Authority

This letter of authority is renewed from..... to.....

Date.....

FORM 40

[See rule 63(2)]

APPLICATION FORM FOR GRANT OR RENEWAL OF LETTER OF AUTHORITY

To

The Registering Authority,

.....

I/We..... address..... hereby submit the following information, namely:

1.

Name of the applicant

.....

2.

Son/wife/daughter of

.....

3.

Address(proof to been closed)

.....

4.

Qualification of the applicant

.....

5.

Experience in automobile workshop

.....

6.

Whether involved/connected directly or indirectly in transport business

.....

7.

Machinery and equipment

.....

8.

Staff engaged in different cadres:-

.....

(i) Manager

.....

(ii) Foreman

.....

(iii) Mechanic

.....

(iv) Helpers

.....

9.

Particulars of a person as required under clause (a)of sub-rule (3) of rule 63 of the Central Motor Vehicles Rules, 1989

.....

(a) Name

.....

(b) Age

.....

(c) Qualification in automobile engineering

.....

(d) Actual experience in automobile work shop

.....
(e) Name of firm with full address

.....
(f) Driving experience of various types of transport vehicles:-

.....
(i) Driving license number

.....
(ii) Issued by

.....
(iii) Date of issue

.....
(iv) Type of vehicle

.....
(v) Period of validity of driving license

.....
(vi) Endorsement on driving license, if any

.....
10.

Proof of land owned by or hired by the applicant

.....
11.

Whether garage is equipped with following facilities:

.....
(i) Water supply

.....
(ii) Electricity

.....
(iii) Toilet

.....
(iv) Rest room

.....
12.

Sources of finance

.....
13.

If application is for the renewal of letter of authority, furnish following particulars, namely:

.....
(i) Number of existing letter of authority

.....
(ii) Date of issue

.....
(iii) Period of validity

.....
(iv) If application is not submitted within time, state the reasons

.....
(v) Whether letter of authority suspended/cancelled/surrendered earlier. Furnish details

.....
14. I hereby solemnly declare that the information given above is true and correct. Further, I hereby declare that I shall abide by the rules, regulations and conditions attached to the letter of authority and as prescribed in the Motor Vehicles Act, 1988, and the Central Motor Vehicles Rules, 1989.

Dated.....

Signature of the Applicant

FORM 41

[See rule 75]

STATE REGISTER OF MOTOR VEHICLES

1.

Registration No.

.....

2.

Previous registration
number, if any

.....

3.

Whether the motor vehicle is-

.....

(a) New vehicle

.....

(b) Imported vehicle

.....

(c) Ex-army vehicle

.....

4.

Maker's name

.....

5.

Year of manufacture

.....

6.

65[Engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

.....

7.

Chassis No

.....

8.

Number of cylinders

.....

9.

Cubic capacity/horse power

.....

10.

Type of fuel used

.....

11.

Class of motor vehicle

.....

12.

Name and full address of the registered owner

.....

13.

Seating capacity

.....
14.

Gross vehicle weight

.....
15.

Unladen weight

.....
FORM 42

[See rule 76(1)]

FORM OF APPLICATION FOR REGISTRATION OF MOTOR VEHICLE BY OR ON BEHALF OF A
DIPLOMATIC/CONSULAR OFFICER

(To be forwarded through the competent authority in triplicate)

To

The Registering Authority,

.....

1.

Full name, designation and address of the diplomatic officer/consular officer/full name, address and station of the
diplomatic mission/consular office or post

.....

2.

Age of the person to be registered as registered owner

.....

3.

Name and address of the person from whom the vehicle was purchased/name of the port through which the vehicle was
imported/name of the person or company from whose bonded stocks the vehicle was purchased and the name of the
port

.....

4.

Country from which imported

.....

5.

Class of vehicle

.....

6.

Type of body

.....

7.

Maker's name

.....

8.

Year of manufacture

.....

9.

Number of cylinders

.....

10.

Horse power

.....

11.

Maker's classification or, if not known, wheel base

.....

12.

Chassis No.

.....

13.

[Engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

.....

14.

Seating capacity (including driver)

.....

15.

Unladen weight

.....

16.

Particulars of previous registration and registered number (if any)

.....

17.

I hereby declare that the vehicle has not been registered in any other State in India

.....

18.

Colour or colours of body, wings and front end

.....

19.

Number, description and size of tyres:-

.....

(a)Front axle

.....

(b)Rear axle

.....

(c)Any other axle

.....

20.

Maximum laden weight

.....

21.

Maximum axle weight (To be furnished in the case of heavy motor vehicles only):-

.....

(a)Front axle

.....

(b)Rear axle

.....

(c)Any other axle

.....

The above particulars are to be filled in for a rigid frame motor vehicle of tow or more axles.

Signature of the Applicant

For use in the Ministry of External Affairs (Protocol Division) or in the office of the

Chief Secretary of the State Government concerned

Certified that..... (name and designation) is a diplomatic officer/consular officer recognised by the Government of India and that he/she is not entitled to exemption from payment of registration fees.

Place.....

Date.....

Signature of the Officer.....

Designation.....

FORM 43

[See rule 76(4)]

CERTIFICATE OF REGISTRATION OF A MOTOR VEHICLE BELONGING TO A DIPLOMATIC OR CONSULAR OFFICER

Registered No.....

Brief description of vehicle, (e.g., Fiat 1100 or Hindustan Landmaster car, Willys jeeps, Dodge/Desoto/Gadga petrol/diesel truck, Leyland 36 seater diesel bus, trailer, etc.)

Full name, designation and address of the diplomatic officer/consular officer/full name, address and Station of the Diplomatic Mission/Consular officer or post.....

Transferred to..... Signature of the Registering Authority

Detailed description:

1.

Class of vehicle

.....

2.

Maker's name

.....

3.

Type of body

.....

4.

Year of manufacture

.....

5.

Number of cylinders

.....

6.

Chassis number

.....

7.

[Engine number or motor number in the case of Battery Operated Vehicles],

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

.....

8.

Horse power

.....

9.

Maker's classification, or if not known, wheel base

.....

10.

Seating capacity (including driver)

.....

11.

Unladen weight

.....

ADDITIONAL PARTICULARS IN THE CASE OF ALL TRANSPORT VEHICLES

12.

Colour or colours of body, wings and front end

.....

13.

Registered laden weight

.....

14.

Number, description and size of tyres-

.....

(a)Front axle

.....

(b)Rear axle

.....

(c)Any other axle

.....

15.

Registered axle weight (in the case of heavy motor vehicles only):-

.....

(a)Front axle

.....

(b)Rear axle

.....

(c)Any other axle

.....

Date.....20....

(Signature of Registering Authority)

FORM 44

[See rule 78(1)]

INTIMATION OF CHANGE OF STATE OF RESIDENCE AND APPLICATION FOR ASSIGNMENT OF FRESH REGISTRATION MARK BY OR ON BEHALF OF A DIPLOMATIC OR CONSULAR OFFICER

(To be submitted in triplicate)

To

The Registering Authority,

.....

I.....of that

(Name and designation)

..... being the owner of.....

motor vehicle No..... registered at..... under

section 42 of the Motor Vehicles Act, 1988 hereby declare that I have, since the..... day

of.....19..... kept the said vehicle in the State of..... and

hereby apply for assignment to the motor vehicle of a fresh registration mark.

I enclose the certificate of registration and the certificate of fitness* of the vehicle.

Date..... Signature of the Owner

*Strike out the words "and the certificate of fitness" if inapplicable.

For use in the Ministry of External Affairs (Protocol Division) or in the

Office of the Chief Secretary of the State Government concerned

Certified that.....

(Name and designation)

continues to hold the status of a Diplomatic Officer/Consular Officer.

He/She is at present stationed at.....

Place..... Designation.....

Date.....Signature of the Officer

FORM 45

[See rule 82(l)]

APPLICATION FOR GRANT OF PERMIT IN RESPECT OF TOURIST VEHICLE

To

The State Transport Authority,

.....

I/We, the undersigned hereby apply for the grant of permit for tourist vehicle valid throughout the territory of India/in the State of.....

(specify the names of the States)

1.

Name of the applicant (s) in full

.....

2.

Status of the applicant, whether individual, company or partnership firm, co-operative society, etc

.....

3.

Name of father or husband

(in case of individual) and in case of firm or company the particulars of managing partner or managing director, as the case may be

.....

4.

Full address (to be supported by attested copy of ration card, electricity bill, etc., in the case of individual or any other valid documentary proof of the satisfaction of State Transport Authority and in case of company or firm, certified copy of the Memorandum of Association or copy of partnership deed)

.....

5.

(a) Whether the applicant himself intends to drive the vehicle?

.....

(b) If so, whether the applicant-

.....

(i) Holds heavy passenger motor vehicle driving license

.....

(ii) The number, date and validity period of driving license

.....

(iii) Name and address of the licensing authority

.....

6.

Registration certificate alongwith the date of first registration, insurance certificate number

.....

7.

Details of other permits, if any, held in respect of a particular vehicle

.....

8.

Details of total number of tourist permits held by the applicant

.....

9.

Type of vehicle

.....

10.

Make of motor vehicle

.....

11.

Particulars of convictions/suspensions/cancellation, if any, during the past three years in respect of the vehicle/permit

held by the applicant (s)

12.

I/We forward herewith the certificate of registration of the vehicle or I/We will produce the certificate of registration of the vehicle before the permits are issued

13.

I/We hereby declare that the above statements are true and that I/We am/are resident(s) of this State having principal place of business in this State at

14.

I/We have paid the fee of Rs.....

Date.....

Signature or thumb-impression of the Applicant

FORM 46

[See rules 83(1) and 87(1)]

FORM OF APPLICATION FOR GRANT OF AUTHORISATION FOR TOURIST PERMIT OR NATIONAL PERMIT

To

The Regional/State Transport Authority,

I/We the undersigned hereby apply for the grant of authorisation valid throughout the territory of India/in the State of..... (specify the names of the States)

1.

Name of the applicant(s) in full

????????????????????

2.

Son/wife/daughter of

????????????????????

3.

Address

????????????????????

4.

Registration mark and year of manufacture and date of registration of the motor vehicle

????????????????????

5.

[Engine number or motor number in the case of Battery Operated Vehicles]

????????????????????

6.

Chassis number of the motor vehicle

????????????????????

7.

Permit number, the authority which had issued the permit and date of issue and date of expiry of the permit

????????????????????

8.

Unladen weight of the motor vehicle

????????????????????

9.

Gross vehicle weight of the motor vehicle

????????????????????

10.

Pay load of the motor vehicle (seating capacity in the case of tourist vehicle)

????????????????????

11.

Period for which the authorization is sought for

????????????????????

12.

I/We enclose the certificate of registration and permit of the vehicle

????????????????????

68[***]

[Itme 12-A omitted by G.S.R. 76(E), dated 31.1.2000 (w.e.f. 31.1.2000). Earlier item 12-A was interted by G.S.R. 684(e), dated 5.10.1999(w.e.f. 22.10.1999).]

????????????????????

13. [

[Substituted by G.S.R 386(E), dated 7.5.2010.]

(a) For Tourist Permit

????????????????????

I/We enclose bank draft (S) as described hereunder towards payment of the authorization fee (in case of tourist permit)

Sl.No.

Name of the States

Amount paid

Particulars of bank draft(s) and date

Date of payment

1

2

3

4

5

(b) For National Permit

????????????????????

I/We enclose the receipt towards payment of Rs. 15000/- as consolidated fee for National Permit]

????????????????????

FORM 47

[See rules 83(2) and 87(2)]

AUTHORISATION FOR TOURIST PERMIT OR NATIONAL PERMIT

No.....

Office of the Secretary, Regional/State Transport Authority

Authorisation No.....

Dated.....

This authorisation is valid throughout the territory of India/in the State(s) of:

1.....

2.

.....

3.

4.
.....

5.
.....

6.
.....

7.
.....

8.
.....

9.
.....

10.
.....

(Here write the names of the States applicable)

1.
Name in full and complete address of holder of the permit
.....

2.
Registration mark of the motor vehicle and make Year of manufacture
.....

3.
Year of manufacture
.....

4.
[Engine number or motor number in the case of Battery Operated Vehicles]
[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]
.....

5.
Chassis number of the motor vehicle
.....

6.
Permit number of the motor vehicle
.....

7.
Name of the permit issuing authority
.....

8.
Date of expiry of the permit
.....

9.
Gross vehicle weight of the motor vehicle
.....

10.
Unladen weight of the motor vehicle
.....

11.
Seating capacity in the case of tourist vehicle
.....

12.
Period of validity of the authorisation

From.....to.....

13. [

[Inserted by Notification No. G.S.R. 76(E), dated 31.1.2000 (w.e.f. 2.6.1989).]

The authorization for the following State (s) is subject to payment of taxes by their permit holder to the respective State(s)

.....

1.

.....

2.

.....

3.

.....

4.

.....]

Signature and designation with seal of the
Transport Authority

[Certificate of payment of composite fee/taxes

[Substituted by G.S.R. 386(E), dated 7.5.2010.]

Sl No.

Name of the States for which payment made

Amount paid Rs.P.

No. and date of bank draft and name of bank

Date of receipt of bank draft

Payable to

Period for which paid

Registration mark of the vehicle

Signature and seal of the authority

1

2

3

4

5

6

7

8

9

Certified that the National Permit holder has paid the consolidated fee of Rs. 15,000 vide receipt numberdated.....]

Signature and seal of the Transport Authority

[Note:-This Form shall be security printed watermark paper and shall carry such hologram emblem, as may be specified by the State Government.]

[Inserted by G.S.R. 400(E), dated 31.5.2002 (w.e.f. 31.5.2002).]

Dated.....

Signature or thumb-impression of Applicant(s)

*Strike out whichever is inapplicable.

FORM 48

[See rule 86]

APPLICATION FOR THE GRANT OF NATIONAL PERMIT

To

The Regional/State Transport Authority,

.....

I/We, the undersigned, hereby apply for the grant of national permit valid throughout the territory of India/in the State

of.....

(here write the names of the States desired)

1.

Name of the applicant (s) in full

.....

2.

Status of the applicant, whether individual, company or partnership firm, co-operative society, etc.

3.

Name of father or husband

(in case of individual) and in case of company or firm the particulars of managing partner or managing director, as the case may be

.....

4.

Full address (to be supported by attested copy of ration card, electricity bill, etc. in case of individual or any other valid documentary proof to the satisfaction of the State Transport Authority/Regional Transport Authority and in case of company or firm, the certified copy of the Memorandum of Association or copy of the deed of partnership, as the case may be)

.....

5.

(a) Whether the applicant himself intends to drive the vehicle?

.....

(b)(i) If so, whether the applicant holds heavy goods vehicle driving license

.....

(ii) The number, date and validity period of the driving license

.....

(iii) Name and address of the licensing authority

.....

6.

Registration certificate alongwith the date of first registration, insurance certificate

.....

7.

Details of any other permits if held in respect of a particular vehicle

.....

8.

Details of number of national permits held by the applicant

.....

9.

Type of vehicle, whether two-axle truck or articulated vehicle or multi-axle vehicle or tractor-trailer combination

.....

10.

Make of motor vehicle

.....

11.

Particulars of convictions/suspensions/cancellation, if any, during the past three years in respect of the vehicle/permit held by the applicant (s)

.....

12.

I/We forward herewith the certificate of registration of the vehicle or I/We will produce the certificate of registration of the vehicle before the permits are issued

.....

13.

I/We hereby declare that the above statements are true and that I/We am/are the resident(s) of this State having principal place of business in this State at

.....

14.

I/We have paid the fee of Rs.

.....

Date.....Signature or thumb-impression of the Applicant

[*****]

[Form 49 omitted by G.S.R. 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

FORM 50

[See rule 90(3)]

BILL OF LADING

Bill No.....

Dated.....

Name and address of the national permit holder

.....

Registration number of the motor vehicle

.....

Dated.....

Name of the consignor

.....

Name of the consignee

.....

Point of origin

.....

Point of destination

.....

Number of articles

Description of goods

Kilograms

Freight charges paid

Freight charges to pay

Total

Rs.P.

Rs.P.

|||||

Bill No.....

Dated.....

Received.....

Package.....

From.....

(Truck No.....)

Signature of Consignee

Signature of the Carrier

Signature of Consignor

*At carrier's risk

At owner's risk

Value of the goods Rs.....

Delivery at.....

Note:-The bill of lading shall be in the proforma given above and shall be in quadruplicate, the original (white) to be carried in the motor vehicle, the duplicate (light green) for the consignor, the triplicate (pink) for the consignee and the

fourth copy (cream yellow) for record of the national permit holder.

*Strike out whichever is inapplicable.

FORM 51

[See rule 141]

Certificate of insurance in respect of.....

Certificate No

.....

Policy No.....

1.

Registration mark of the vehicle insured

.....

2.

Description of the vehicle

.....

3.

Make and year of manufacture

4.

[Engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

5.

Carrying capacity

6.

Name and address of the insured

7.

Effective date and time of commencement of insurance

8.

Date of expiry of insurance

9.

Persons or classes of persons entitled to drive:-

Stage carriage/contract carriage/private service vehicle

Any person including insured: Provided that a person driving holds an effective driving license at the time of the accident and is not disqualified from holding or obtaining such a license: Provided also that the person holding an effective learner's license may also drive the vehicle when not used for the transport of passengers at the time of the accident and that such a person satisfies the requirement of rule 3 of the Central Motor Vehicles Rules, 1989.

Goods carriage

Any person including insured:

Provided that a person driving holds an effective driving license at the time of the accident and is not disqualified from holding or obtaining such a license: Provided also that the person holding an effective learner's license may also drive the vehicle when not used for the transport of passengers at the time of the accident and that such a person satisfies the requirement of rule 3 of the Central Motor Vehicles Rules, 1989.

Non-transport vehicles

Any person including insured:

Any person including insured: Provided that a person driving holds an effective driving license at the time of the accident and is not disqualified from holding or obtaining such a license: Provided also that the person holding an effective learner's license may also drive the vehicle when not used for the transport of goods at the time of the accident and that such a person satisfies the requirement of rule 3 of the Central Motor Vehicles Rules, 1989.

10.

Limitations as to use:-

Stage carriage/contract carriage/goods carriage/private service vehicle

The policy covers uses only under a permit within the meaning of the Motor Vehicles Act, 1988, or such a carriage falling under sub-section (3) of section 66 of the Motor Vehicles Act, 1988.

The policy does not cover use for

- (a) Organized racing, or
- (b) Speed testing

11.

Private service vehicle and non-transport vehicle

The policy covers use for any purpose other than-

- (a) Hire or reward,
- (b) Organized racing, or
- (c) Speed testing

|||

We hereby certify that the policy to which this certificate relates as well as this certificate of insurance are issued in accordance with the provisions of Chapter X or XI of the Motor Vehicles Act, 1988.

Authorized Insurer

FORM 52

[See rule 42(1)]

COVER NOTE

1.

Registration mark, number and description of the vehicle insured

.....

2.

Name and address of insured

.....

3.

Effective date and time of commencement of insurance for the purpose of this Act

.....

4.

Date of expiry of insurance

.....

5.

Persons or classes of persons entitled to drive

.....

6.

Any limitations as to use of motor vehicle

.....

7.

The period of validity of this cover note will expire on

.....

I/We hereby certify that this cover is issued in accordance with the provisions of Chapter XI of the Motor vehicles Act, 1988

Authorized Insurer

FORM 53

[See rule 148(1)]

CERTIFICATE IN RESPECT OF EXEMPTION OF MOTOR VEHICLE FROM INSURANCE

Certified that the motor vehicles of the following description:

(a)

Registration number

.....

(b)

Make

.....

(c)

Class, i.e., motor cycle, motor car, stage carriage, goods carriage, contract carriage or other class
(to be described)

.....

(d)

Colour of body

.....

Is the property of-

(i) The Government of

.....

The local authority/State transport undertaking, namely.....the vehicles of which
have been exempted under section 146 of the Motor Vehicles Act, 1988, by the Government of.....by
their order No.....dated.....

This certificate is valid up to.....unless cancelled in the meanwhile.

Dated.....

Signed on behalf of.....

Designation:

FORM 54

[See rule 150(a) and (2)]

ACCIDENT INFORMATION REPORT

1.

Name of the police station

.....

CR No./Traffic accident report

.....

Date, time and place of the accident

.....

Name and full address of the injured/deceased

.....

Name of the hospital to which he/she was removed

.....

Registration number of vehicle and the type of the vehicle

.....

Driving license particulars

.....

(a) Name and address of the driver

.....

(b) Driving license number and date of expiry

.....

(c) Address of the issuing authority

.....

(d) Badge No. in case of public service vehicle

.....

8.

Name and address of the owner of the vehicle at the time of the accident

.....

9.

Name and address of the insurance company with whom the vehicle was insured and the particulars of the Divisional
Officer of the said insurance company

.....

10.

Number of insurance policy/insurance certificate and the date of validity of the insurance policy/insurance certificate

11

Registration particulars of the vehicle (class of vehicles)

(a)Registration No.

(b)[engine number or motor number in the case of Battery Operated Vehicles]

[Substituted by GSR 589(E), dated 16.9.2005, for 'Engine number'(w.e.f. 16.3.2006).]

(c)Chassis No.

12.

Route permit particulars

13.

Action taken, if any, and the result thereof

FORM 55

[See rule 160(1)]

APPLICATION FOR THE APPROVAL OF A FOREIGN INSURER

I/We hereby apply for the inclusion of..... of..... (Name of foreign insurer) constituted/incorporated/domiciled at..... in the approved list maintained under rule 159 of the Central Motor Vehicles Rules, 1989, of the Central Government and for the inclusion of my/our name as the guarantor of the said.....(name of foreign insurer) for the purpose of Chapter XI of the Motor Vehicles Act, 1988, and the said Rules. I/We hereby certify that I/We have entered into an arrangement for the purposes of the said Act and the said Rules with the said foreign insurer and I/We hereby agree to act as guarantor in India in respect of the said foreign insurer for the purposes of the said Act and the said Rules..

Dated.....20.....

Signature of Authorized Insurer

Address.....

FORM 56

[See rule 160(3)]

NOTICE TO CEASE TO ACT AS GUARANTOR

This is to give notice that I/We desire to cease acting as guarantors in India of.....

of.....(Name of foreign insurer)..... (Address of foreign insurer)..... after..... or from..... the expiry of two months from the date on which this notice is delivered to the Central Government, whichever is later, for the purposes of Chapter X I of the Motor Vehicles Act, 1988 and the Central Motor Vehicles Rules, 1989.

Dated the..... day of.....20.....

Authorized Insurer

FORM 57

[See rules 140(v) and 161(1)]

CERTIFICATE FOR FOREIGN INSURANCE

Certificate No.....

Policy No..... (Optional)

Reference Mass, R (kg)

CO

(g/km)

HC(g/km)

(1)

(2)

(3)1

$R < 150$

12

8

$150 \leq R \leq 350$

$12 + 18(R - 150)$

$8 + 4(R - 150)$

200

200

$R > 350$

30

12

Light duty vehicles:

||-

Reference Mass, rw(Kg)

CO(g/km)

HC(g/km)

(1)

(2)

(3)

$rw < 1020$

14.3

2.0

$1020 \leq rw \leq 1250$

16.5

2.1

$1250 \leq rw \leq 1470$

18.8

2.1

$1470 \leq rw \leq 1700$

20.7

2.3

$1700 \leq rw \leq 1930$

22.9

2.5

$1930 \leq rw \leq 2150$

24.9

2.7

$rw > 2150$

27.1

2.9

2. Conformity of Production Tests: Two and three-wheeler vehicles:

||-

Reference Mass, R (kg)

CO (g/km)

HC (g/km)

(1)

(2)

(3)

$R < 150$

15

10

$150 < R < 350$

$15 + 25 (R - 150)$

$10 + 5 (R - 150)$

| 200

200

$R > 350$

40

15

Light duty vehicles:

Reference Mass, r_w (kg)

CO (g/km)

HC (g/km)

(1)

(2)

(3)

r_w

> 1020

17.3

2.7

10205 r_w 51250

19.7

2.7

1250!:-

r_w 51470

22.5

2.8

$1470 < r_w \leq 1700$

24.9

3.0

$1700 < r_w \leq 1930$

27.6

3.3

$1930 < r_w \leq 2150$

29.9

3.5

r_w

> 2150

32.6

3.7

<i>Explanation.</i>-Mass emission standards refers to the gm. of pollutants emitted per km. run of the vehicle, as determined by a Chassis Dynamometer Test using the Indian Driving Cycle.]

ANNEXURE II

[See rule 115(3)]

BREAKDOWN OF THE OPERATING CYCLE USED FOR THE TEST

No.
of operation
Acceleration(m/sec)²
Speed
(km/h)
Duration of each operation(s)
Cumulative time (s)
(1)
(2)
(3)
(4)
(5)
01. Idling
-
-
16
16
02. Acceleration
0.65
0-14
6
22
03. Acceleration
0.56
14-22
4
26
04. Deceleration
-0.63
22-13
4
30
05. Steady speed
-
13
2
32
06. Acceleration
0.56
13-23
5
37
07. Acceleration
0.44
23-31
5
42
08. Deceleration
-0.56
31-25
3

45

09. Steady speed

-

25

4

49

10. Deceleration

-0.56

25-21

2

51

11. Acceleration

0.45

21-34

8

59

12. Acceleration

0.32

34--112

7

66

13. Deceleration

-0.46

42-37

3

69

14. Steady speed

-

37

7

76

15. Deceleration

-0.42

[37-34]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

2

78

16. Acceleration

0.32

34-42

7

85

17. Deceleration

-0.46

42-47

9

94

18. Deceleration

-0.52

27-14

7

101

19. Deceleration

-0-56

14-00

7

103

ANNEXURE III

[See rule 115(3)]

REFERENCE FUEL FOR TYPE AND PRODUCTION CONFORMITY TESTS

Serial No.

Characteristic

Requirements

I I-

(1)

(2)

(3)

(4)

(5)

1.

Colour, visual

Orange

Red

2.

Copper-strip corrosion for 3 hours at 50°C.

Not worse than No.1

P:15

(1968)

3.

Density at 15°C.

Not limited but to be reported

P:16

(1967)

4.

Distillation-

(a) Initial boiling point

Not limited but to be reported

P:18

(1967)

(b) Recovery up to 20°C per cent by volume, min.

10

10

(c) Recovery up to 125°C per cent by volume, min.

50

50

(d) recovery up to 130°C per cent by volume, min.

90

90

(e) Final boiling point, max.

215°C

215°C

(f) Residue per cent by volume, max.

2

2

5.

Octane number (research method)max.

87

94

P : 27 (1960)

6.

Oxidation stability, in minutes, min.

360

360

P : 28 (1966)

7.

Residue on evaporation mg/100 ml, max

4.0

4.0

P : 29 (1960)

8.

Sulphur, total per cent, by weight,max

0.25

0.20

P : 34 (1966)

9.

Lead content (as Pb), g/l max.

0.56

0.80

P : 37 (1967) or

10.

Reid vapour pressure at 38 degree C, kgf/cm³.max.

0.70

0.70

P : 39 (1967)

ANNEXURE IV

[See rule 115(4)]

LIMIT VALUES OF EXHAUST GAS OPACITY APPLICABLE FOR DIESEL-DRIVEN VEHICLES

The engine tests at steady speed

Nominal Flow G(1/s)

Absorption Coefficient[K(1/m)]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

Nominal Flow G(1/s)

Absorption Coefficient[K(1/m)]

[Substituted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

(1)

(2)

(3)

(4)

42

2.00

120

1.20

45

1.91
125
1.17
50
1.82
130
1.15
55
1.75
135
1. [13]
60
1.68
140
1.11
65
1.61
145
1.09
70
1.56
150
1.07
75
1.50
155
1.05
80
1.46
160
1.04
85
1.41
165
1.02
90
1.38
170
1.01
95
1.34
175
1.00
100
1.31
180
0.99
105
1.27
185
0.97

110
1.25
190
0.96
115
1.22
195
0.95
-
-
<200
0.93

[The above standards shall not be applicable to agricultural tractors and the same for the agricultural tractors shall be notified at a later date.]

[Added by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[ANNEXURE IV-A

[Inserted by GSR 338(E), dated 26.3.1993 (w.e.f. 26.3.1993).]

[See rule 115(5)]

TEST CYCLE

The following 13-mode cycle shall be followed in dynamometer operation on the test engine:-

Mode No.

Engine Speed

% Load

(1)

(2)

(3)

1.

Idle

-

2.

Intermediate

10

3.

Intermediate

25

4.

Intermediate

50

5.

Intermediate

75

6.

Intermediate

100

7.

Idle

-

8.

Rated

100

9.

Rated

75

10.

Rated

50

11.

Rated

25

12.

Rated

10

13.

Idle

-]

[ANNEXURE IV-B

[Annexure IV-B, IV-C and IV-D inserted by GSR 493(E), dated 28.8.1997 (w.e.f. 1.4.2000).]

[See rule 115(10)]

DRIVING CYCLES AND COLD START

A. For all 2 and 3-wheelers except diesel vehicles: Cold Start Procedures:-

Test Cell condition

-

Soak Temperature

20-30C

Soak Period

6.30 hrs

Preparatory running before sampling

Idling of 40 seconds and 4 cycles

Number of test cycles

6

Break down of cycles

As per Annexure II to principal rules

B. For all other vehicles including diesel 2, 3 and 4-wheelers:

Soak Temperature

20-30C

Soak Period

6.30 hrs

Preparatory running before sampling

Idling of 40 seconds

Number of test cycles*

4 cycles of Part one and 1 cycle of Part two

Break down of cycles*

Modified Indian driving cycle as per Tables I and II

*For diesel, 2 & 3-wheelers

Number of test cycles

6

Break down of cycles

Indian driving cycles.

As per Annexure II to principal rules.

MODIFIED INDIAN DRIVING CYCLE FOR YEAR 2000

Table I: Operating cycle on the Chassis Dynamometer (Part one)

No of Operation

Operation

Phase

Acceleration

(m/s²)

Speed

(Km/h)

Duration of each

Cumulative time(s)

Gear to be used in the case of manual boxl

1

Idling

1

11

11

11

6GPM+55Kt

(*)

2

Acceleration

2

1.04

0-15

4

4

15

1

3

Steady Speed

3

15

8

8

23

1

4

Deceleration

-0.69

15-10

2

25

1

5

Declaration, clutch

4

5

disengaged

-0.92

10-0

3

28

KI(*)

6

Idling

5

21

21

49

165PM+55K1(*)

7

Acceleration

0.83

0-15

5

54

1

8

Gear Change

6

2

12

56

9

Acceleration

0.94

15-32

5

61

2

10

Steady Speed

7

32

24

24

85

2

11

Deceleration

-0.75

32-10

8

93

2

12

Declaration, clutch disengaged

8

-0.92

10-0

3

11

96

K2(*)

13
Idling
9
21
21
117
165PM+55K1(*)
14
Acceleration
0.83
0-15
5
122
1
15
Gear Change
2
124
16
Acceleration
10
0.62
15-35
9
26
133
2
17
Gear Change
2
135
18
Acceleration
0.52
35-50
8
143
3
19
Steady Speed
11
50
12
12
155
3
20
Deceleration
12
-0.52
50-35

8

8

163

3

21

Steady Speed

13

35

13

13

176

3

22

Gear Change

2

178

23

Deceleration

14

-0.86

32-10

7

12

185

2

24

Deceleration, clutch

disengaged

-0.92

10-0

3

188

KZ(*)

25

Idling

15

7

7

195

75PM(*)

MODIFIED INDIAN DRIVING CYCLE FOR YEAR 2000

Table II: Operating cycle on the chassis Dynamometer (Part two)

No. of Operation

Operation

Phase

Acceleration

(m/s²)

Speed

(km/h)

Duration of each

Cumulative time(s)

Gear to be used in the case of manual gear box

|

||| Operation(s)

Phase(s)

g

l

Idling

1

20

20

20

Kt(*)

2

Acceleration

0.83

0-15

5

25

1

3

Gear Change

2

27

-

4

Acceleration

0.62

15-35

9

36

2

5

Gear Change

2

2

41

38

-

6

Acceleration

0.52

35-50

8

46

3

7

Gear Change

2

48

-

8

Acceleration

0.43

50-70

13

61

4

9

Steady Speed

3

70

50

50

111

5

10

Deceleration

4

-0.69

70-50

8

8

119

4,,

5+4,,4

11

Steady Speed

5

50

69

69

188

4

12

Acceleration

6

0.43

50-70

13

13

201

4

13

Steady Speed

7

70

50

50

251

5

14

Acceleration

8
0.24
70-90
24
24
275
5
15
Steady Speed
9
90
83
83
358
5
16
Deceleration
-0.69
90-80
4
362
5
17
Deceleration
10
-1.04
80-50
8
22
370
5
18
Deceleration
-1.39
50-00
10
380
Ks(*)
19
Idling
11
20
20
400
PM(*)
(*) PM=gearbox in neutral, clutch engaged.
K1K2=First or fifth gear engaged, clutch disengaged
ANNEXURE IV-C
[See rule 115(10)]
REFERENCE FUEL PETROL
||| ASTM Method

Minimum
Maximum
Research Octane Number
95.0
D 2699
Motor Octane Number
85.0
D 2700
Density at 15°C (kg/l)
0.748
0.762
D 1298
Reid Vapour pressure
0.56 bar
0.64 bar
D323
Distillation
:
|||-
Initial boiling point
24°C
40°C
D 86
10%
vol. point
42°C
58°C
50'k vol. point
90°C
110°C
90°/
vol. Point
155°C
180°C
Final boiling point
190°C
215°C
Residue
2%
D86
Hydrocarbon Analysis:
|||-
Olefins
20%vol.
D1319
Aromatics
(including max. 5%
45%
vol.
(*) D 3606/D 2267
Saturates

vol.
benzene)*balance
D1319
Oxidation Stability_
480 Minutes
D 525
Existent Gum
4mg/100m1
D381
Sulphur content
0.04%, mass
D 1266/D 2622/D 2785
Copper Corrosion at 50°C
D 130
Lead content
0.0058/ltr
D3237
Phosphorous content
0.00138/ltr
D3231
*
Addition of oxygenates prohibited.]
ANNEXURE IV-D
[See rule 115(10)]
REFERENCE FUEL DIESEL
ASTM Method
Minimum
Maximum
Cetane Number
49
53
D 613
Density at 15°C (kg/1)
0.835
0.845
D 1298
Distillation:
D86
50%
point
245°C
911%
point
320°C
340°C
Final boiling point
-
370°C
Flash point
55°C
D93

CFI''
(-)
5°C
EN 116 (CEN)
Viscosity at 40°C
2.5 mm²/s
3.5mm²
/s
D445
Sulphur content
to be reported
0.3%mass
D1266/D2622/D2785
Copper Corrosion
1
D 130
Conradson carbon residue
0.2%
mass
D 189
(10%, DR)
Ash content
0.01%
mass
D 482
Water content
0.05%
mass
D95/DI744
Neutralization
(strong acid) No.Oxidation stability
0.20 mg/KOH/g2.5 mg/100ml
D2274]
Additives
*

[ANNEXURE IV-E

[Inserted by GSR 686(E), dated 20.10.2004. Brought into force-(a) in the National Capital Region and the cities of Mumbai, Kolkata, Chennai, Bangalore, Hyderabad including Secundrabad, Ahmedabad, Pune, Surat, Kanpur and Agra in respect of four wheeled vehicles manufactured on and from 1st April 2005, except in respect of four wheeled transport vehicles plying on Inter-State Permits or National Permits or All India Tourist Permits within the jurisdiction of these cities; and (b) in other areas of the country, from such date as may be notified by the Central Government. Here 'National Capital Region'shall have the same meaning as assigned to it in clause (f) of section 2 of the National Capital Region Planning Board Act, 1985 (2 of 1985).]

[See rule 115(14)]

DRIVING CYCLES AND COLDSTART FOR FOUR-WHEELED VEHICLES:AS DESCRIBED IN (A), (B) AND (C)

Soak Temperature

200C-30(1C

Soak Period

6-30 hours

Preparatory running before sampling

Nil

Number of test cycles

4 cycles of Part one and one cycle of Part two

Break down of cycles

Modified Indian Driving Cycle as per Table 1 and 2 of Annexure IV-B of sub-rule (10)]

ANNEXURE IV-F

[See rule 115(14)]

TECHNICAL CHARACTERISTIC OF REFERENCE FUEL PRESCRIBED FOR APPROVAL TESTS AND TO VERIFY CONFORMITY OF PRODUCTION

Parameter

Unit

Limits(1)

Test Method

| Minimum

Maximum

|-

Cetane Number(2)

| 52.0

54.0

EN-ISO 5165

Density at15°C

Kg/m3

833

837

EN-150 3675

Distillation:

-50%point

95%

point

-

final boilingpoint

OC

°C

°C

245

345

--

350

370

EN-ISO 3405EN-ISO 3405EN-ISO 3405

Flash point

°C

55

--

EN 22719

CFPP

°C

--

-5

EN 116

Viscosity at 400C

mm²/s

2.5

3.5

EN-ISO 3104

Polycyclic aromatic hydrocarbons

% m/m

3

6.0

IP 391

Sulphur content(3)

mg/kg

--

300

Pr.

EN-ISO/DIS14596

Copper corrosion

| --

1

EN-ISO2160

Conradson carbon residue (10% DR)

% m/m

--

0.2

EN-ISO 10370

Ash content

%m/m

--

0.01

EN-ISO 6245

Water content

%m/m

--

0.05

EN-ISO 12937

Neutralization(strong acid)number

MgKOH/g

--

0.02

ASTM D 974-95

Oxidation stability(4)

mg/ml

--

0.025

EN-ISO 12205

New and better method for polycyclicaromaticsunder development

% m/m

--

--

EN 12916

(1)

Values quoted in the specification are "true values". In establishment of their limit values the terms of ISO 4259 Petroleum Products-Determination and application of precision data in relation to methods of test have been applied and in fixing a minimum value, a minimum difference of 2R above zero has been taken into account, in fixing a maximum and minimum value, the minimum difference is 4R (R=Reproducibility).

Notwithstanding this measure, which is necessary for technical reasons, the manufacturer of fuels should nevertheless aim at a zero value where the stipulated maximum value is 2R and at the mean value in the case of quotations of maximum and minimum limits. Should it be necessary to clarify the questions as to whether a fuel meets the requirements of the specification, the terms of ISO 4259 should be applied.

(2)

The range of cetane number is not in accordance with the requirements of a minimum range of 4R, however, in the case of a dispute between fuel supplier and fuel user, the terms of ISO 4259 may be used to resolve, such dispute provided replicate measurements, of sufficient number to achieve the necessary precision, are made in preference to single determinations.

(3)

The actual sulphur content of the fuel used for the Type I test shall be reported.

(4)

Even though oxidation stability is controlled, it is likely that shelf life will be limited. Advice should be sought from the supplier as to storage conditions and life.

ANNEXURE IV-G

[See rule 115(14)]

TECHNICAL CHARACTERISTICS OF REFERENCE FUEL PRESCRIBED FOR APPROVAL TESTS AND TO VERIFY CONFORMITY OF PRODUCTION

Type: Unleaded petrol

Parameter

Unit

Limits(n)

Test Method

Minimum

Maximum

Research Octane number, RON

| 95.0

--

EN 25164

Motor octane number, MON

| 85.0

--

EN 25163

Density at 15°C

Kg/m³

748

762

ISO 3675

Reid vapour pressure

kPa

56.0

60.0

EN 12

Distillation:

initial boiling point

evaporated at 100°C

evaporated at 150°C

final boiling point

°C

% v/v

%v/v

°C

24

49.0

81.0

190

40

57.0

87.0

215

EN-ISO 3405

EN-ISO 34115

EN-ISO 3405

EN-ISO 3405

Residue

% volume

--

2

EN-ISO 3405

Hydrocarbon analysis

Olefins

Aromatics

-benzene

-

saturates

%v/v

%v/v

% v/v

% v/v

--

28.0

--

--

10

40.0

1.0

Balance

ASTMD1319

ASTMD1319

Pr, EN 12177

ASTM D 1319

Carbon/

hydrogen ratio

| Report

Report

Oxidation Stability2

minutes

480

--

EN-ISO 7536

Oxygen content

%m/m

--

2.3

EN 1601

Existent gum

mg/ml

--

0.04

EN-ISO 6246

Sulphur content(3)

mg/kg

--

100

Pr.

EN

ISO/

DIS 14596

Copper corrosion for 3 hours at 50°C

-

1

EN-ISO 2160

Lead content

mg/l

--

5

EN 237

Phosphorous content

mg/l

-

1.3

ASTM D 3231

(1)

The value quoted in the specification are "true value". In establishment of their limit values the terms of ISO 4259 "Petroleum products - Determination and application of precision data in relation to methods of test" have been applied and in fixing a minimum value, a minimum difference of 2R above zero has been taken into account; in fixing a maximum and minimum value, the minimum difference is 4R (R=reproducibility). Notwithstanding this measure, which is necessary for statistical reasons, the manufacturer of fuels should nevertheless aim at a zero value where the stipulated maximum value is 2R and at the mean value in case of quotations of maximum and minimum limits. Should it be necessary to clarify the question as to whether a fuel meets the requirements of the specifications, the terms of ISO 4259 should be applied.

(2)

The fuel may contain oxidation inhibitors and metal deactivators normally used to stabilise refinery gasoline streams, but detergent/dispersive additives and solvent oils must not be added.

(3)

. The actual sulphur content of the fuel used for the Type I test shall be reported.

Annexure IV-H

[See rule 115(14)]

Liquefied Petroleum Gas (LPG)

Parameter
Unit
Limits Fuel A
Limits Fuel B
Test Method
| Minimum
Maximum
Minimum
Maximum
|-
Motor octane number
| 93.5
| 93.5
| EN 589
Annex B
Composition:
|||||-
C3content
%vol.
48
52
83
87
IS07941
C4content
% vol.
48
52
13
17
ISO 7941
Olefins
%vol.
0
12
9
15
1S07941
Evaporation residue
mg/kg
| 50
| 50
NFM 41-015
Total sulphur content
ppm
|||||-
weight
| 50
| 50
EN 24261)
(1)

||||-

Hydrogen sulphide

--

| None

| None

IS08819

Copper strip corrosion

Rating

| Class I

| Class I

ISO 6251(2)

Water at 0°C

|| Free

| Free

Visual inspection

(1)

Value to be determined at standard conditions 293,2K (20°C) and 101,3 kPa.

(2)

This method may not accurately determine the presence of corrosive materials if the sample contains corrosion inhibitors or other chemicals, which diminish the corrosivity of the sample to the copper strip. Therefore, the addition of such compounds for the sole purpose of basing the test method is prohibited.

Note.-Fuel A and Fuel B are two types of LPG fuels used for testing of vehicles/engines, to take care of the variation in commercial LPG fuel.

ANNEXURE IV-I

[See rule 115(14)]

NATURAL GAS (NG)

Reference Fuel G 20

Characteristics

Units

Basis

Limits

Test Method

Minimum

Maximum

Composition:

Methane

%mole

11A1

99

100

IS06974

Balance

[Inerts+C2/C2+I

%mole

--

--

I

IS06974

N2

%mole

--

--
 --
 ISO 6974
 Sulphur content
 mg/
 M3(1)

 50
 IS06326-5
 (1)
 Value to be determined at standard conditions 293,2K (20C) and 101, 3 k Pa.
 Characteristics
 Units
 Basis
 Limits
 Test Method
 Minimum
 Maximum
 composition:
 Methane
 %mole
 92.5
 91.5
 93.5
 IS06974
 Balance
 [inerts+C2/C2+I
 %mole
 --
 -
 1
 ISO6974
 N2
 %mole
 7.5
 6.5
 8.5
 ISO6974
 Sulphur content
 m',/m3(1)
 --
 --
 (1)
 Value to be determined at standard conditions 293, 2K (20C) and 101, 3k Pa.
 Reference Fuel G25
 Characteristics
 Units
 Basis
 Limits
 Test Method

| Minimum
Maximum
Composition:

|
Methane
%mole

86

84

88

ISO 6974

Balance

|
[Inerts+C2/C2+I
%mole

|
ISO6974

N2

%

mole

14

12

16

ISO 6974

Sulphur content

| --

--

50

ISO6326-5

(1)

Value to be determined at standard conditions 293, 2K (20C) and 101, 3 k Pa.

Note: G-20, G-23 and G-25 are three type of CNG fuels, out of which any two is selected for testing of vehicles/engines to take care of the variation in the commercial NG Fuel. The nomenclatures G-20, G-23 and G-25 are as used in EEC.

[ANNEXURE IV-J

[Inserted by GSR 84(E), dated 9.2.2009 (w.e.f. 9.2.2009).]

[See rule 115(15)]

Technical Specification of the Reference Fuel to be used for testing vehicles equipped with Gasoline engines.

Parameter

Unit

Limits(1)

Test Method

Minimum

Maximum

Research octane number, RON

| 95.0

-

EN 25164

Motor octane number, MON

| 85.0

-

EN 25163

Density at 15 degreesC

kg/m³

740

754

ISO 3675

Reid vapour pressure

kPa

56.0

60.0

Pr.EN ISO;13016-1;(DVPE)

Distillation:

||

--evaporated at 70 degrees C

% v/v

24.0

40.0

EN-

ISO 3405

-evaporated at 100degrees C

%v/v

50.0

58.0

EN-ISO 3405

--evaporated at 150 degrees C

% v/v

83.0

89.0

EN-

ISO 3405

-finalboiling point,

degreeC

190

|-

Residue

% v/v -

| 2.0

EN-ISO 3405

Hydrocarbon analysis:

||

-olefins

%v/v -

| 10.0

ASTM D 1319

-aromatics

% v/v

29.0

35.0

ASTM D 1319

-benzene

% v/v -

| 1.0
 ASTM D 1319
 -saturates
 %v/v
 Report
 Report
 Pr.
 EN 12177
 Carbon/Hydrogen ratio
 || Report
 ASTM D 1319
 Inductionperiod
 (2)
 minutes
 480
 -
 EN-ISO 7536
 Oxygen content
 % m/m -
 -
 1.0
 EN 1601
 Existent gum
 mg/ml -
 -
 0.04
 EN-ISO6246
 Sulphur content (3)
 mg/kg -
 -
 10
 ASTM D 5453
 Copper corrosion
 -
 -
 Class 1
 EN-ISO 2160
 Lead content
 mg/l -
 -
 5
 EN 237
 Phosphorus content
 mg/l -
 -
 1.3
 ASTM D 3231
 |||||
 (1)

The values quoted in the specifications are "true values". In establishment of their limit values the terms of ISO 4259 Petroleum products-Determination and application of precision data in relation to methods of test have been applied and

in fixing a minimum value, a minimum difference of 2R above zero has been taken into account; in fixing a maximum and minimum value, the minimum difference is 4R (R=reproducibility). Notwithstanding this measure, which is necessary for technical reasons, the manufacturer of fuels should nevertheless aim at a zero value where the stipulated maximum value is 2R and at the mean value in the case of quotations of maximum and minimum limits. Should it be necessary to clarify the questions as to whether a fuel meets the requirements of the specifications, the terms of ISO 4259 should be applied.

(2)

The fuel may contain oxidation inhibitors and metal deactivators normally used to stabilize refinery gasoline streams, but detergent/dispersive additives and solvent oils must not be added.

(3)

The actual sulphur content of the fuel used for the Type I test shall be reported.]

ANNEXURE IV-K

[See rule 115(15)]

Technical Specification of the Reference Fuel to be used for testing vehicles equipped with Diesel engines.

Parameter

Unit

Minimum

Maximum

Test Method

Cetane number(2)

52.0

54.0

EN-ISO 5165

Density at 15 degrees C

Kg/m³

833

837

EN-ISO 3675

Distillation:

-50% point

Degree C

245

-

EN-ISO 3405

-95% point

Degree C

345

350

EN-ISO 3405

-final boiling point

Degree C

-

370

EN-ISO 3405

Flash point

Degree C

55

-

EN 22719

CFPP

Degree C

-

-5

EN 116

Viscosity at 40 degrees C

mm²/s

2.3

3.3

EN-ISO 3104

Polycyclic aromatic hydrocarbons

%m/m

3.0

6.0

IP 391

Sulphur content(3)

Mg/kg

-

10

ASTM D 5453

Copper corrosion

-

Class 1

EN-ISO 2160

Conradson carbon residue (10% DR)

%m/m

-

0.2

EN-ISO 2160

Ash content

%m/m

-

0.01

EN-ISO 6245

Water content

%m/m

-

0.02

EN-ISO 12937

Neutralisation (strong acid) number

Mg KOH/g

-

0.02

ASTM D 974

Oxidation stability⁴

Mg/ml

-

0.025

EN-ISO 12205

Lubricity (HFRR wear scan diameter at 60 degrees C)

Micrometer

um

-

400

CEC F-06-A-96

FAME

Prohibited

(1)

The values quoted in the specifications are "true values". In establishment of their limit values the terms of ISO 4259 Petroleum products-Determination and application of precision data in relation to methods of test have been applied and in fixing a minimum value, a minimum difference of 2R above zero has been taken into account; in fixing a maximum and minimum value, the minimum difference is 4R (R=reproducibility). Notwithstanding this measure, which is necessary for technical reasons, the manufacturer of fuels should nevertheless aim at a zero value where the stipulated maximum value is 2R and at the mean value in "the case of quotations of maximum and minimum limits. limits. Should it be necessary to clarify the questions as to whether a fuel meets the requirements of the specifications, the terms of ISO 4259 should be applied.

(2)

The range for cetane number is not in accordance with the requirements of a minimum range of 4R. However, in the case of a dispute between fuel supplier and fuel user, the terms of ISO 4259 may be used to resolve such disputes provided replicate measurements, of sufficient number to archive the necessary precision, are made in preference to single determinations.

(3)

The actual sulphur content of the fuel used for the Type I test shall be reported.

(4)

Even though oxidation stability is controlled, it is likely that shelf life will be limited. Advice should be sought from the supplier as to storage conditions and life.

ANNEXURE IV-L

[See rule 115(15)]

SPECIFICATION OF REFERENCE FUEL FOR CNG

CNG Reference Fuel for Category M and Category N Vehicles not exceeding 3.500 Kgs GVW and two and three wheelers.

||| Limits

Characteristic

Units

Basis

minimum

maximum

Test method

Reference fuel G20

||||-

Composition:

||||-

Methane

%

mole

100

99

100

ISO 6974

Balance(1)

%

mole

-

-

1
 ISO6974
 N2
 %
 mole
 ||| ISO 6974
 Sulphur content
 mg/m3(2)
 -
 -
 10
 ISO 6326-5
 Wobbe Index (net)
 MJ/m3(3)
 48.2
 47.2
 49.2
 |-
 Reference fuel G25
 ||||-
 Composition:
 ||||-
 Methane
 %
 mole
 86
 84
 88
 ISO 6974
 Balance(1)
 %
 mole
 -
 -
 1
 ISO 6974
 N2
 %
 mole
 14
 12
 16
 ISO 6974
 Sulphur content
 mg/m3(2)
 -
 -
 10
 ISO 6326-5
 Wobbe Index (net)
 MJ/m3(3)

39.4
38.2
40.6
(1)
Inerts (different from N2) + C2+C2+.
(2)
Value to be determined at 293,2 K (20°C) and 101.3 kPa.
(3)
Value to be determined at 273,2 K (0°C) and 101.3kPa.
The above type of vehicles should be tested with both types of Reference Fuels CNG Reference Fuel for Vehicles above 3.500 Kgs GVW
Limits
-
Characteristic
Units
Basis
Minimum
Maximum
Test method
Reference Fuel G8
-
Composition:
Methane
87
84
89
Ethane
13
11
15
Balance(1)
% -
mole
-
-
1
ISO 6974
Sulphur content
mg/m3(2)
10
ISO 6326-5
(1)
Inerts + C2.
(2)
Value to be determined at standard conditions (293.2 K (20°C) and 101.3 kPa).
Limits
Characteristic
Units
Basis
minimum
maximum

Test method

Reference fuel G23

||||-

Composition:

||||-

Methane

| 92.5

91.5

93.5

|-

Balance(1)

% - mole

-

-

1

ISO 6974

N2

| 7.5

6.5

8.5

|-

Sulphur content

mg/m3(2)

-

-

10

ISO6326-5

(1)

Inerts (different form N2) + C2 + C2+.

(2)

Value to be determined at standard conditions (293.2 K (200C) and 101.3 kPa).

Limits

Characteristic

Units

Basis

minimum

maximum

Test method

Reference fuel G25

||||-

Composition:

||||-

Methane

| 86

84

89

|-

Balance(1)

% - mole

-

-

1
ISO 6974
N ₂
14
12
16
-
Sulphur content
mg/m ³ (2)
-
-
10
ISO 6326-5
(1)
Inerts (different from N ₂ + C ₂ + C ₂
(2)
Value to be determined at standard conditions (293.2 K/20°C and 101.3 kPa).
[Annexure IV-LA]
[Inserted by Notification No. G.S.R. 643(E), dated 27.6.2017 (2.6.1989).]
(see the proviso to sub-rule (3) of rule 115B)
Technical Specifications of the Reference LNG Fuel
Sr. No.
Component
Concentration
1.
Methane %
87.33-99.71
2.
Ethane %
0.09-10.26
3.
Propane %
0.03-3.56
4.
Butane + %
0-1.48
5.
Sulphur
< 10 ppm
6.
LNG Density kg/m ³
421.39-467.35
7.
Expansion ratio m ³ (n)/m ³ liq
558-600.0
8.
Gas GCV MJ/m ³ (n)
39.91-46.24
9.
Wobbe Index MJ/m ³ (n)
53.51-56.77

ANNEXURE IV-M

[See rule 115(15)]

(SPECIFICATION OF REFERENCE FUEL FOR LPG)

LPG Reference Fuel for Category M and Category N vehicles not exceeding 3,500 kgs GVW and two and three wheelers

Parameter

Unit

Fuel A

Fuel B

Test method

Composition

ISO 7941

C3-content

%vol.

30±2

85±2

C4-content

%

vol.

balance

balance

<C3>C4

%

vol.

maximum 2

maximum 2

Olefins

%

vol.

maximum 12

maximum 15

Evaporation residue

mg/kg

Maximum 50

Maximum 50

ISO 13757

Water at 00C

Free

Free

Visual inspection

Total sulphur content

Mg/kg

Maximum 10

Maximum 10

EN 24260

Hydrogen Sulphide

none

none

ISO 8819

Copper strip corrosion

Rating

Class 1

Class 1

ISO 6251(1)

Odour

Characteristic

Characteristic

Motor octane number

Minimum 89

Minimum 89

EN 589 Annex B

(1)

This method may not accurately determine the presence of corrosive materials if the sample contains corrosion inhibitors or other chemicals which diminish the corrosivity of the sample to the copper strip. Therefore, the addition of such compounds for the sole purpose of biasing the test method is prohibited.

LPG Reference Fuel for Vehicles above 3,500 Kgs GVW

Parameter

Unit

Fuel A

Fuel B

Test method

Composition:

1507941

C3content

% vol

50+2

85+2

|-

C4content

% vol

balance

balance

|-

<C3>C4

%vol

max. 2

max.

2

|-

Olefins

%vol

max. 12

max.

14

|-

Evaporation residue

mg/kg

max. 50

max. 50

IS013757

Water at 0°C

Free

free

Visual inspection

Total sulphur content

mg/kg

max. 10

max. 10

EN 24260

Hydrogen sulphide

none

none

ISO 8819

Copper strip corrosion

rating

Class 1

Class 1

ISO 6251(1)

Odour

Characteristic

Characteristic

|-

Motor octane number

min. 92.5

min. 92.5

EN 589 Annex B

(1)

This method may not accurately determine the presence of corrosive materials if the sample contains corrosion inhibitors or other chemicals which diminish the corrosivity of the sample to the copper strip. Therefore, the addition of such compounds for the sole purpose of biasing the test method is prohibited.

ANNEXURE IV-N

[See rule 115(15)]

SPECIFICATION OF COMMERCIAL GASOLINE FUEL

Characteristics

Unit

Requirements

Unleaded regular

Unleaded premium

Color, visual

Orange

Red

Density

@ 150C

Kg/m³

720-775

720-775

Distillation

:

(a) Recovery up to 70°C (E 70)

%

volume

10-45

10-45

(b) Recovery up to 100°C (E 100)

%

volume

40-70

40-70

(c) Recovery up to 150°C (E 150)

%

volume

75 min

75 min

(d) Final Boiling Point (FBP), max

0C

210

210

(e) Residue, max.

%

volume.

2

2

Research Octane Number (RON) min

91

95

Motor Octane Number (MON). min

81

85

Gum content (solvent washed), max

mg/100 ml

5

5

Oxidation Stability min

minutes

360

360

Sulphur, total, max

mg/kg

50

50

Lead content (as Pb), max

g/1

0.005

0.005

Reid Vapour Pressure (RVP), max

kPa

60

60

Vapour Lock Index (VU)

(a) Summer, max

750

750

(b) Other months max

950

950

Benzene Content, max

%

volume

1

1

Copper strip corrosion for 3 hrs @ 50°C,max

Rating

Class 1

Class 1

Olefin content, max

% volume

21

18

Aromatics content max

% volume

35

35

Oxygen content max

%

mass

2.7

2.7

Oxygenates Content

(a) Methanol, max

% volume

3

3

(b) Ethanol, max

% volume

5

5

(c) Iso-propyl alcohol, max

% volume

10

10

(d) Iso-Butyl alcohol max

%

volume

10

10

(e) Tertiary-butyl alcohol. max

%

volume

7

7

(f) Ethers containing 5 or more carbon atoms per molecule, max

%

volume

15

15

(g) Other oxygenates, max
 %
 volume
 8
 8

1. Test methods and other provisions details along with the requirements as given above shall be issued by Bureau of Indian Standards.
2. Petrol of 89 RON and 79 MON and having all other properties as the unleaded regular grade indicated above shall also be available for meeting requirements of the older vehicles which will be conforming to pre-Euro III equivalent vehicular emission norms.
3. Type test for Phosphorous content in petrol shall be introduced.
4. These standards specifications have been finalized by the Expert Committee after discussions with the automobile and oil industry as per Auto Fuel Policy.

ANNEXURE IV-O

[See rule 115(15)]

SPECIFICATION OF COMMERCIAL DIESEL FUEL

Characteristics

Unit

Requirements

Ash, max

% mass

0.01

Carbon Residue (Ramsbottom) on 10 % residue max

% mass

0.3 without additives

Cetane number (CN), min

| 51

Cetane Index (CI), min

| 46

Distillation:

| | -

95%

vol. recovery at °C, max

°C

360

Flash point:

| | -

(a) Abel, min

°C

35

Kinematic viscosity @ 40°C

Cst

2.0-4.5

Density

@15 °C

kg/m³

820-845

Total Sulphur max

mg/kg

50

Water content, max

mg/kg

200

Cold filter Plugging point (CFPP)

||-

(a) Summer, max

°C

18

.

(b) Winter, max

°C

6

Total contaminations, max

mg/kg

24

Oxidation stability, max

g/m³

25

Polycyclic Aromatic Hydrocarbon (PAH), max

% mass

11

Lubricity, corrected wear scar diameter (wsd 1, 4) @ 60°C, max

µm (microns)

460

Coper strip corrosion for 3 hrs @ 50°C

Rating

Class 1

1. These density and 95 per cent distillation recovery temperature limits shall be company pool average values. However, all samples shall meet the density @ 15°C limit of 820-860 kg/m³ and 95 per cent. minimum distillation recovery at 370°C.

2. For diesel processed from Assam crude, relaxation of CN & CI by 3 units and density shall be applicable as provided in the present BIS specification.

3. Test methods and other provisions/details along with the requirements as given above shall be issued by Bureau of Indian Standards.

4. These standards specifications have been finalized by the Expert Committee after discussions with the automobile and oil industry as per Auto Fuel Policy.

Annexure IV-P

(See Rule 115A(7))

Diesel Fuel Specifications

Characteristics

Minimum

Maximum

Test Method

Cetane Number

52

54

EN-ISO 5165

Density at 15°C (kg/m³)

833

837

EN-ISO 3675

Distillation

: in °C

|||-

50%

point (OC)

245

||-

95%

point (°C)

345

350

EN- ISO 3405

Final boilingpoint

(°C)

-

370

|-

Flash point (°C)

55

| EN 22719

CFPP

(°C)

| (-) 5

EN 116

Viscosity at 40°C (mm²/s).

2.5

3.5

EN-ISO 3104

Polycyclic aromatic hydrocarbons (% m/m)

3.0

6.0

IP 391

Sulphur Content (mg/kg)

-

300

ASTM D 5453

Copper Corrosion

-

Class 1

EN-ISO 2160

Conradson carbon residue (10%DR) (%m/m)

-

0.2

EN-ISO 10370

Ash Content (% m/m)

-

0.01

EN-ISO 6245

Water Content (% m/m)

-

0.05

EN-ISO 12937

Neutralisation

(strong acid) No. (mg KOH/g)

-

0.02

ASTM D 974

Oxidation Stability (mg/ml)

-

0.025

EN-ISO 122051

[Annexure IV-Q]

[Inserted by Notification No. G.S.R. 412(E), dated 19.5.2015 (w.e.f. 2.6.1989)]

[See rule 115E]

Technical specifications of the reference fuel E85

Parameter

Unit

Limits¹

Test method²

Minimum

Maximum

Research octane number, RON

95

-

EN ISO 5164

Motor octane number, MON

85

-

EN ISO 5163

Density at 15 °C

kg/m³

Report

ISO 3675

Vapour pressure

kPa

40

60

EN ISO 13016-1 (DVPE)

Sulphur content^{3, 4}

mg/kg

-

10

EN ISO 20846

EN ISO 20884

Oxidation stability

minutes

360

EN ISO 7536

Existent gum content (solvent washed)

mg/(100 ml)

-

5

EN-ISO 6246

Appearance

This shall be determined at ambient temperature or 15 °C
whichever is higher.

Clear and bright, visibly free of suspended or
precipitated contaminants

Visual inspection

Ethanol and higher alcohols⁷

% V/V

83

85

EN 1601

EN 13132

EN 14517

Higher alcohols (C3-C8)

% V/V

-

2

Methanol

% V/V

0.5

Petrol⁵

% V/V

Balance

EN 228

Phosphorus

mg/l

0.36

ASTM D 3231

Water content

% V/V

0.3

ASTM E 1064

Inorganic chloride content

mg/l

1

ISO 6227

pHe

6.5

9

ASTM D 6423

Copper strip corrosion (3h at 50 °C)

Rating

Class 1

EN ISO 2160

Acidity, (as acetic acid CH₃COOH)

% m/m (mg/l)

-

0.005 (40)

ASTM D 1613

Carbon/ hydrogen ratio

Report

Carbon/ oxygen ration

Report

1. The values quoted in the specifications are "true values". In establishment of their limit values the terms of ISO 4259 Petroleum products - Determination and application of precision data in relation to methods of test have been applied and in fixing a minimum value, a minimum difference of 2R above zero has been taken into account; in fixing a maximum and minimum value, the minimum difference is 4R (R = reproducibility). Notwithstanding this measure, which is necessary for technical reasons, the manufacturer of fuels shall nevertheless aim at a zero value where the stipulated maximum value is 2R and at the mean value in the case of quotations of maximum and minimum limits. Should it be necessary to clarify whether a fuel meets the requirements of the specifications, the terms of ISO 4259 shall be applied.
2. In case of dispute, the procedure for dissolving the dispute and interpretations of the results based on test method precision, describe in EN ISO 4259 shall be used.
3. In case of national dispute concerning sulphur content, either EN ISO 20846 or EN IS) 20884 shall be called up similar to the reference in the National annex of EN 228.
4. The actual sulphur content of the fuel used for the Type I Test shall be reported.
5. The unleaded petrol content can be determined as 100-minus the sum of the per cent content of water and alcohol.
6. There shall be no intentional addition of compounds containing phosphorus, iron, manganese, or lead to this reference fuel.
7. Ethanol to meet the specification of EN 15376 is the only oxygenate that shall be intentionally added to this reference fuel.

[Annexure IV-R]

[Inserted by Notification No. G.S.R. 412(E), dated 19.5.2015 (w.e.f. 2.6.1989)]

[See rule 115E]

Technical specifications of the reference fuel (ED95)¹

Parameter

Unit

Limits²

Test method³

Minimum

Maximum

Total alcohol (Ethanol including content on higher saturated alcohols)

% m/m

92.4

EN 15721

Other higher saturated mono-alcohols (C3-C5)

% m/m

2

EN 15721

Methanol

% m/m

0.3

EN 15721

Density 150C

kg/m³

793

815

EN ISO 12185

Acidity, calculated as acetic acid

% m/m

0.0025

EN 15491

Appearance

Bright and clear

Flashpoint

0C

10

EN 3679

Dry residue

mg/kg

15

EN 15691

Water content

% m/m

6.5

EN 154894

EN-ISO 12937

EN15692

Aldehydes calculated as acetaldehyde

% m/m

0.01

ISO 1388-4

Esters calculated as ethylacetat

% m/m

0.1

ASTM D1617

Sulphur content

mg/kg

10

EN 15485

EN 15486

Sulphates

mg/kg

4

EN 15492

Particulate contamination

mg/kg

24

EN 12662

Phosphorus

mg/l

0.2

EN 15487

Inorganic chloride

mg/kg

1

EN 15484 or EN 15492

Copper

mg/kg

0.1

EN 15488

Electrical conductivity

μS/cm

2.5

DIN 51627-4 or prEN 15938

1. Additives are necessary to fulfill the ED95 fuel specification such as cetane improver as specified by the engine manufacturer, shall be added to the ethanol fuel, as long as no negative side effects are known. If these conditions are satisfied, the maximum allowed amount is 10 % m/m.

Denaturants for ED95 fuel, if required, shall be approved by the vehicle manufacturer or shall be either Ethyl Tert Butyl Ether (ETBE); or Iso butanol; or Methyl Ethyl Ketone (MEK); or Tert butanol or Iso Propanol.

2. The values quoted in the specifications are "true values". In establishment of their limit values the terms of ISO 4259 Petroleum products - Determination and application of precision data in relation to methods of test have been applied and in fixing a minimum value, a minimum difference of 2R above zero has been taken into account; in fixing a maximum and minimum value, the minimum difference is 4R (R =reproducibility). Notwithstanding this measure, which is necessary for technical reasons, the manufacturer of fuels shall nevertheless aim at a zero value where the stipulated maximum value is 2R and at the mean value in the case of quotations of maximum and minimum limits. Should it be necessary to clarify whether a fuel meets the requirements of the specifications, the terms of ISO 4259 shall be applied.

3. Equivalent EN/ISO methods will be adopted when issued for properties listed above.

4. Should it be necessary to clarify whether a fuel meets the requirements of the specifications, the terms of EN 15489 shall be applied.

[Annexure IV-S

[Substituted by Notification No. G.S.R. 682(E), dated 12.7.2016 (w.e.f. 2.6.1989).]

[See rule 115 (E)]

Technical specifications of the reference fuel E100 (As per IS 15464:2004)

Sr. No.

Characteristic

Requirement

1

Relative density at 15.6/15.6 OC, max

0.7961

2

Ethanol content percent by volume at 15.6/15.6 OC, min
(excluding denaturant)

99.5

3

Miscibility with water

Miscible

4

Alkalinity

Nil

5

Acidity (as CH₃COOH) mg/l, max

30

6

Residue on evaporation percent by mass, Max

0.005

7

Aldehyde content (as CH₃CHO) mg/l, max

60

8

Cooper mg/kg, max

0.1

9

Conductivity, ìS/m, max

300

10

Methyl alcohol, mg/litre, max

300

11

Appearance

Clear and bright]

[Annexure IV-S

[Inserted by Notification No. G.S.R. 412(E), dated 11.4.2016 (w.e.f. 2.6.1989).]

[See rule 115F]

Technical specifications of the reference fuel B100

{

Serial number

Characteristic

Requirement

Method of Test, reference to

ISO/ASTM/EN

[P:] of IS 1448

1

Density@ 150C, kg/m³

860-900

ISO 3675

ISO 12185

D 4052

[P:16/P:32]

2

Kinematic Viscosity @ 400C, cSt

2.5-6.0

ISO 3104

[P:25]

3

Flash Point, Pensky-Martens Closed ? Cup test(PMCC)0C

, minimum

120

ISO 3679

[P:21]

4

Sulphur, mg/kg, maximum

10.0 D

5453

[P:83]

5

Carbon residue (Ramsbottom)(1)per cent by mass, maximum

0.05

D 4530

ISO 10370

--

6

Sulphated ash, per cent by mass, maximum

0.02

ISO 6245

[P:4]

7

Water content, mg/kg, maximum

500

D 2709

ISO 3733

ISO 6296

[P:40]

8

Total contamination, mg/kg, maximum

24

EN 12662

--

9

Copper corrosion 3 hours @ 500C, maximum

1

ISO 2160

[P:15]

10

Cetane No., minimum

51

ISO 5165

[P:9]

11

Acid value, mg KOH/g, maximum

0.5

EN 14101

[P:1/sec 1]

12

Methanol(2), per cent by mass, maximum

0.2

EN 14110

--

13

Ethanol(3), per cent by mass, maximum

0.2

--

--

14

Ester content, per cent by mass, minimum

99.5

EN 14103

--

15

Free Glycerol, per cent by mass, maximum

0.02

D 6584

--

16

Total Glycerol, per cent by mass, maximum

0.25

D 6584

--

17

Phosphorus, mg/kg, maximum

10

D 4951

--

18

Sodium and Potassium , mg/kg, maximum

To report

EN 14108 and

EN 14109

--

19

Calcium and Magnesium, mg/kg, maximum

To report

(4)

--

20

Iodine value

To report

EN 14111

--

21

Oxidation stability at 1100C, h, minimum

6

EN 14112

--

22

Mono-glyceride content, per cent by mass, maximum

0.05

EN 14105

--

23

Di-glyceride content, per cent by mass, maximum

0.01

EN 14105

--

24

Tri-glyceride content, per cent by mass, maximum

0.01

EN 14105

--

(1)

Carbon residue shall be run on 100 per cent sample.

(2)

Applicable for fatty acid methyl ester.

(3)

Applicable for fatty acid ethyl ester.

(4)

European method is under development.]

]}
 [Annexure IV-T]
 [Inserted by Notification No. G.S.R. 889(E), dated 16.9.2016 (w.e.f. 2.6.1989).]
 [See Rule 115 (18)]
 Technical specifications of the reference Diesel Fuel (B7)
 Parameter
 Unit
 Limits¹
 Test method
 Minimum
 Maximum
 Cetane Index
 46.0
 EN ISO 4264
 Cetane number²
 52.0
 56.0
 EN ISO 5165
 Density at 15 °C
 Kg/m³
 833.0
 837.0
 EN ISO 12185
 Distillation:
 - 50% point
 °C
 245.0
 -
 EN ISO 3405
 - 95% point
 °C
 345.0
 360.0
 EN ISO 3405
 - final boiling point
 °C
 -
 370.0
 EN ISO 3405
 Flash point
 °C
 55
 -
 EN ISO 2719
 Cloud point
 °C
 -
 -10
 EN 23015
 Viscosity at 40 °C
 mm²/s

2.30

3.30

EN ISO 3104

Polycyclic aromatic hydrocarbons

% m/m

2.0

4.0

EN 12916

Sulphur content

mg/kg

-

10.0

EN ISO 20846

EN ISO 20884

Copper corrosion 3hrs, 50°C

-

Class 1

EN ISO 2160

Conradson carbon residue (10 % DR)

% m/m

-

0.20

EN ISO 10370

Ash content

% m/m

-

0.010

EN ISO 6245

Total contamination

mg/kg

-

24

EN 12662

Water content

mg/kg

-

200

EN ISO 12937

Acid number

mg KOH/g

-

0.10

EN ISO 6618

Lubricity (HFRR wear scan diameter at 60 °C)

µm

-

400

EN ISO 12156

Oxidation stability @ 110 °C

h

20.0

EN

15751

FAME4

% v/v

6.0

7.0

EN 14078

1. The values quoted in the specifications are 'true values'. In establishment of their limit values the terms of ISO 4259 Petroleum products - Determination and application of precision data in relation to methods of test have been applied and in fixing a minimum value, a minimum difference of 2R above zero has been taken into account; in fixing a maximum and minimum value, the minimum difference is 4R (R = reproducibility). Notwithstanding this measure, which is necessary for technical reasons, the manufacturer of fuels shall nevertheless aim at a zero value where the stipulated maximum value is 2R and at the mean value in the case of quotations of maximum and minimum limits. Should it be necessary to clarify whether a fuel meets the requirements of the specifications, the terms of ISO 4259 shall be applied.

2. The range for cetane number is not in accordance with the requirements of a minimum range of 4R. However, in the case of a dispute between fuel supplier and fuel user, the terms of ISO 4259 may be used to resolve such disputes provided replicate measurements, of sufficient number to achieve the necessary precision, are made in preference to single determinations.

3. Even though oxidation stability is controlled, it is likely that shelf life will be limited. Advice shall be sought from the supplier as to storage conditions and life.

4. FAME content to meet the specification of EN 14214.

[Annexure IV-U]

[Inserted by Notification No. G.S.R. 889(E), dated 16.9.2016 (w.e.f. 2.6.1989).]

[See rule 115(19)]

Specification of Commercial Gasoline Fuel

Characteristics

Unit

Requirements

Regular

Premium

Color, visual

Orange

Red

Density @ 150C

Kg/m³

720-775

720-775

Distillation :

a) Recovery up to 700C (E 70)

% volume

10-55 (summer)10-58 (other month)

10-55 (summer)10-58 (other month)

b) Recovery up to 1000C (E 100)

% volume

40-70

40-70

c) Recovery up to 1500C (E 150)

% volume

75 min

75 min

d) Final Boiling Point (FBP), max

0C
210
210
e) Residue, max
% volume
2
2
Research Octane Number (RON) min
91
95
Motor Octane Number (MON), min
81
85
Gum content (solvent washed), max
mg/100ml
4
4
Oxidation Stability, min
minutes
360
360
Sulphur, total, max
mg/kg
10
10
Lead content (as Pb), max
g/l
0.005
0.005
Reid Vapour Pressure (RVP) @ 380C, max
kPa
67
67
Vapour Lock Index (VLI)
a) Summer, max
1050
1050
b) Other months, max
1100
1100
Benzene Content, max
% volume
1
1
Copper strip corrosion for 3 hrs @ 500C, max
rating
Class 1
Class 1
Olefin content, max
% volume
21

18

Aromatics content, max

% volume

35

35

Oxygen content, max

% mass

3.7

4.5

Oxygenates Content

a) Methanol, max

% volume

3

3

b) Ethanol, max

% volume

10

10

c) Iso-propyl alcohol, max

% volume

10

10

d) Iso-Butyl alcohol, max

% volume

10

10

e) Tertiary-butyl alcohol, max

% volume

7

7

f) Ethers containing 5 or more carbon atoms per molecule, max

% volume

15

15

g) Other oxygenates, max

% volume

8

8

Note:

1. Test methods and other provisions and details along with the requirements as given above shall be issued by Bureau of Indian Standards.

2. The

Aromatics content, (max) shall be permitted up to 40% in North Eastern States till 01.04.2023

[Annexure IV-V]

[Inserted by Notification No. G.S.R. 889(E), dated 16.9.2016 (w.e.f. 2.6.1989).]

[See rule 115(19)]

Specification of Commercial Diesel Fuel

Characteristics

Unit

Requirements

Ash, max

% mass

0.01

Carbon Residue (Ramsbottom) on 10 % residue, max

% mass

0.3without additives

Cetane number (CN), min

51

Cetane Index (CI), min

46

Distillation :

95% vol. recovery at0C, max

0C

360

Flash point :

a) Abel, min

0C

35

Kinematic Viscosity @ 400C

cst

2.0-4.5

Density @150C, max

kg/m³

845

Total Sulphur, max.

mg/kg

10

Water content, max

mg/kg

200

Cold filter Plugging point (CFPP)

a) Summer, max

0C

18

b) Winter, max

0C

6

Total contaminations, max

mg/kg

24

Oxidation stability, max

g/m³

25

Polycyclic Aromatic Hydrocarbon (PAH), max

% mass

8

Lubricity, corrected wear scar diameter @ 600C,

max

?m (microns)

460

Copper strip corrosion for 3 hrs @ 500C

rating

Class ? 1

FAME content max.

% v/v

7.0

Note :

1. Test methods and other provisions/ details along with the requirements as given above shall be issued by Bureau of Indian Standards.

2. The

Cetane number (CN), (min) shall be permitted up to 48 in North

Eastern States till 01.04.2023

[Annexure IV-W]

[Inserted by Notification No. G.S.R. 889(E), dated 16.9.2016 (w.e.f. 2.6.1989).]

[See rule 115(18)]

Technical Specification of Reference Hydrogen Fuel.

Characteristics

Units

Limits

Test Method

Minimum

Maximum

Hydrogen Purity

% mole

98

100

ISO 14687-1

Total Hydrocarbon

?mol/mol

0

100

ISO 14687-1

Water¹

?mol/mol

0

2

ISO 14687-1

Oxygen

?mol/mol

0

2

ISO 14687-1

Argon

?mol/mol

0

2

ISO 14687-1

Nitrogen

?mol/mol

0

2

ISO 14687-1

CO

?mol/mol

0

1

ISO 14687-1

Sulphur

?mol/mol

0

2

ISO 14687-1

Permanent Particulates³

ISO 14687-1

(1)

Not to be condensed

(2)

Combined water, oxygen, nitrogen, argon: 1.900 ?mol/mol.

(3)

The hydrogen shall not contain dust, sand, dirt, gums, oils or other substances in an amount sufficient to damage the fuelling station equipment of the vehicle (engine) being fuelled.

[Annexure IV-X]

[Inserted by Notification No. G.S.R. 889(E), dated 16.9.2016 (w.e.f. 2.6.1989).]

See Rule 115

Technical specification for Reference fuel E-5

Parameter

Unit

Limits¹

Test method

Minimum

Maximum

Research octane number, RON

95.0

-

EN25164/prENISO5164

Motor octane number, MON

85.0

-

EN25163/prENISO5163

Density at 15°C

kg/m³

743

756

ENISO 3675/ENISO12185

Vapour pressure

kPa

56.0

60.0

ENISO 13016-1(DVPE)

Water content

%v/v

0.015
ASTME
1064
Distillation:
? Evaporated at 70°C
%v/v
24.0
44.0
ENISO3405
? Evaporated at 100°C
%v/v
48.0
60.0
ENISO 3405
? Evaporated at 150°C
%v/v
82.0
90.0
ENISO 3405
? Final boiling point
°C
190
210
ENISO 3405
Residue
%v/v
?
2.0
ENISO 3405
Hydro-carbon analysis:
? Olefins
%v/v
3.0
13.0
ASTMD1319
? Aromatics
%v/v
29.0
35.0
ASTMD1319
? Benzene
%v/v
-
1.0
EN12177
? Saturates
%v/v
Report
ASTM1319
Carbon/ hydrogen ratio
Report

Carbon/ oxygen ratio

Report

Induction period²

minutes

480

-

ENISO 7536

Oxygen content⁴

%m/m

Report

EN1601

Existent gum

mg/ml

-

0.04

ENISO 6246

Sulphur content³

mg/kg

-

10

ENISO 20846/ENISO20884

Copper corrosion

-

Class 1

ENISO 2160

Lead content

mg/l

-

5

EN237

Phosphorus content

mg/l

-

1.3

ASTMD3231

Ethanol⁵

%v/v

4.7

5.3

EN1601/EN 13132

¹The values quoted in the specifications are

"true values". For establishing the limit values, the

terms of ISO4259:2006 (Petroleum products? Determination

and application of precision data in relation to methods of test)

have been applied and for fixing a minimum value, a minimum

difference of 2 R above zero has been taken into account; for

fixing a maximum and minimum value, the minimum difference is 4R

(R=reproducibility).

Notwithstanding this measure, which is necessary for technical

reasons, the fuel manufacturer shall nevertheless aim at a zero

value where the stipulated maximum value is 2R and at the mean

value when quoting maximum and minimum limits. Should it be necessary to clarify whether a fuel meets the requirements of the specifications, the terms of ISO4259:2006 shall be applied.

2The fuel may contain oxidation inhibitors and metal deactivators normally used to stabilize refinery petrol streams, but detergent/dispersive additives and solvent oils shall not be added.

3The actual sulphur content of the fuel used for the type I test shall be reported.

4Ethanol meeting the specification of prEN15376 is the only oxygenate that shall be intentionally added to the reference fuel.

5There shall be no intentional addition to this reference fuel of compounds containing phosphorus, iron, manganese or lead.

Annexure V

[See rule 132(2)]

TRANSPORT EMERGENCY CARD (ROAD)

Cargo

Mention chemical identity of the dangerous and hazardous goods

Nature of hazard

.....

Protective devices

.....

Emergency action

Notify police and fire brigade immediately

Spillage

.....

Fire

.....

First-aid-

Additional information provided by the manufacturer or sender.

[Annexure VI

[Inserted by GSR 933(E), dated 28.10.1989 (w.e.f. 28.10.1989).]

[See rule 1-A]

Specimen Of Objective Examination of a Driver

1. You are driving upto an intersection where there is no signal, people are crossing in front of your car, you should

(a)

continue into the intersection without reducing speed

(b)

slow down and be careful

(c)

stop and allow persons to cross the road.

2. You wish to take a "U" turn at an intersection controlled by a traffic light, you should

(a)

drive to another intersection that has no traffic light

(b)

wait until the light turns green before making the "U" turn

(c)

make the "U" turn if there is a policeman at the intersection.

3. You are driving towards an intersection where flashing yellow traffic light is displayed, you should
- (a) slow down and proceed with caution
 - (b) stop, if possible to do so safely
 - (c) continue at the same speed.
4. You are driving on a two-lane street, the vehicle in front of you is moving very slowly, and the road ahead is clear for overtaking, you should
- (a) pass the vehicle from the left hand side
 - (b) pass the vehicle from the right hand side
 - (c) pass the vehicle from any convenient side.
5. Your car is involved in an accident hurting people, you should
- (a) report to the nearest police station and take the persons to the hospital
 - (b) need not report to the police station
 - (c) need not report to the police station but should take the persons to the hospital.
6. While driving, to make a right turn, the proper hand signal is
- (a) extend right palm in a horizontal position outside of and to the right of vehicle with palm of the hand turned to the front
 - (b) extend right arm and rotate in anti-clockwise direction
 - (c) extend right arm with palm downward and move up and down several times.
7. A pedestrian is crossing the street at an intersection in an unmarked cross-walk, you should
- (a) yield to the pedestrian the "right of way"
 - (b) proceed with care as pedestrian is "Jay-walking"
 - (c) reduce speed and warn pedestrian.
8. While driving, you wish to change from one lane to another, you should
- (a) give the proper turn signal
 - (b) change lanes only when it is safe to do so by giving the proper turn signal
 - (c) never change lanes as it is against the law.
9. You approach an intersection that does not have traffic lights, a policeman or traffic signs, you should
- (a) slow down and use caution
 - (b) come to a full stop
 - (c) not change speed if the way is clear.
10. You have a valid learner's license to drive a car, you should

(a)

drive only in daylight hours

(b)

have someone with a valid driver's license on the seat beside you when you drive

(c)

practice driving only on streets that have very little traffic.]

[ANNEXURE VII

[Inserted by GSR 221(E), dated 28.3.2001 (w.e.f. 28.3.2001). Earlier it was omitted by GSR 76(E), dated 31.1.2000 (w.e.f. 31.1.2000) and inserted by GSR 684(E), dated 5.10.1999 (w.e.f. 22.10.1999).]

[See Table below rule 62(1)]

CHECK HEAD LAMP BEAM

The Horizontal cut off of the passing beam when tested at 10 metres.

Distance in an unladen condition of the vehicle shall be always below the head lamp center line and the difference shall be within 5 cm to 25 cm.

Note-Each head lamp shall be checked individually by blocking the other lamp.]

FIGURE

[ANNEXURE VIII

[Annexure VIII substituted by G.S. Section R 788(E), dated 27.11.2002 (w.e.f. 2.6.2003).]

[See clause (c) of sub-rule (4) and sub-rule (9) of rule 115-C]

SAFETY CHECKS FOR USE OF LPG FUEL IN FOUR-WHEELED VEHICLES AND ABOVE (AS PER AIS 026) AND TWO-WHEELED AND THREE-WHEELED VEHICLES (AS PER) AIS 027) AND INDIAN GAS CYLINDER RULES, 1981 (as amended from time to time)

LPG Kit Component

[Approving/Certifying/Verifying Authority]

[Substituted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004).]

Clause of AIS 026/027/Other Rules, Standards, etc.

86[(1)(a) Cylinder for four-wheelers and above

*Department of Explosives, Nagpur to approve/endorse in case of foreign make

*ECE-R-67-01 or IS:14899-2000 or as approved under Gas Cylinder Rules, 1981

(b) Cylinder for two-wheelers and three-wheelers

*Department of Explosives, Nagpur to approve/endorse in case of foreign make

*ECE-R-67-01 or IS:14899-2000 or as approved under Gas Cylinder Rules, 1981

(2) Cylinder Valves/Multi Function Valve

*Department of Explosives, Nagpur to approve/endorse in case of foreign make

*ECE-R-67-01 or IS:15100-2001 or as approved under Gas Cylinder Rules, 1981]

(3) Regulator/vaporizer*

Testing or verification of certificate with test report by Test Agency as per United Nations Economic Commission for Europe Regulation No. 67 Rev.1

United Nations Economic Commission for Europe Regulation No. 67 Rev.1

Note:-Regulator/vaporizer is to be tested, as per Economic Commission for Europe Regulation No. 67(Rev.1), including endurance test for 6,000 number of cycles

(4) Gas-Air Mixer*

Testing/verification of certificate with test report by Test Agency as per United Nations Economic Commission for Europe Regulation No. 67 Rev.1

United Nations Economic Commission for Europe Regulation No. 67 Rev.1

(5) Petrol and Gas Solenoid Valves*

Testing/verification of certificate with test report by Test Agency as per United Nations Economic Commission for Europe Regulation No. 67 Rev.1

United Nations Economic Commission for Europe Regulation No. 67 Rev.1 or equivalent standard.

Note:-Petrol solenoid valve is to be tested, as per Economic Commission for Europe Regulation No. 67 (Rev. 1), for endurance only at a pressure 1.5 times the working pressure for 6,000 number of cycles.

(6) Inspection, Testing and Commissioning Certificate

(a) Leak testing

(b) Excess flow valve test*

(c) Automatic fill limiter*

(d) Compartment/sub-compartment

To be tested by Test Agency

Clause 14 of AIS 026/AIS 027

(7) Filling Connection

Installation on vehicle to be checked by Test Agency

As per Appendix A, Clause (d) of AIS 026/AIS 027

(8) Ventilation

Test agency to verify

Clause 8(E) of AIS 026/AIS 027

(9) Testing of Conduit*

Testing/Verification of Certificate with Test Report by Test Agency as per equivalent standard

Clause 8(F)(iii) of AIS 026/AIS 027

(10)(a) LPG Fuel line exceeding 4.5 kg/cm²

Clause 9 of AIS 026/AIS 027

*Pressure testing

Testing/Verification of Certificate with Test Report by Test Agency as per equivalent standard

Clause 9(i) of AIS 026/AIS 027

*Size of tube as per engine capacity

Manufacturer's declaration to be verified by Test Agency

Clause 9(ii) of AIS 026/AIS 027

*Fitment on vehicle

Verification by Test Agency as per Safety Code of Practice

Clause 9(v)f of AIS 026/AIS 027

(b) Flexible Hose/fuel line not exceeding* 4.5 kg/cm²

Clause 10 of AIS 026/AIS 027

*Material

Testing/Verification of Certificate with Test Report by Test Agency as per equivalent standard

Clause 9(ii)(a) of AIS 026/AIS 027

*Fitment on vehicle

Verification by Test Agency as per Safety Code of Practice

Clause 10(b), 9(v) of AIS 026/AIS 027

*Pressure

Testing/Verification of certificate with Test Report by Test Agency as per Equivalent standard

Clause 10(A)(i) of AIS 026/AIS 027

(c) Joints and connections to withstand Pressure without any leakage

Verification by Test Agency

Clause 9(iv) and 10(A) of AIS 026/AIS 027

(11) Compartment/Sub-compartment*

Test to be carried out by Test Agency as per Safety Code of Practice

Clause 8D of AIS 026/AIS 027

(12) Safety check for installation of LPG system

Safety checks to be carried out by Test Agency as per Safety Code of Practice

Relevant clauses of AIS 026/AIS 027

*Certificate issued conforming to equivalent prescribed standards by accredited testing agency of the country of origin or a report issued by internationally accredited test laboratory may also be accepted.

Note:-Only the latest version of all the standards as mentioned, shall be referred for compliance.

[ANNEXURE IX

[Substituted by Notification No. G.S.R. 643(E), dated 27.6.2017 (2.6.1989).]

[See para E of rule 115B]

Safety Checks for use of CNG/ Bio-CNG/ LNG Fuels in internal combustion engined vehicles (as per AIS 028) and Indian Gas Cylinder Rules, 2004

(as amended from time to time)

Sr. No.

CNG/ BIO-CNG/ LNG Kit Component

Certifying/ Verifying Authority

Clause of AIS-028/ Other Rules and Standards

1

CNG/ BIO-CNG/ LNG Cylinder*

PESO, Nagpur to certify or endorse in case of foreign make

Gas cylinder rules 2004 or International standards as endorsed by PESO

1.1

Fitment of cylinder on vehicle

Test agency to verify as per AIS-028

Clause no. 2.3, 2.5 and 2.6 of AIS-028

2

CNG/ LNG (Shut off valve) Cylinder valves*

PESO, Nagpur to certify or endorse in case of foreign make

IS: 3224 (for CNG valves) or Gas cylinder rules 2004 or International standards as endorsed by PESO

3

Regulator (CNG)/ Regulator and Vaporiser/ heat exchanger (LNG)*

Testing of the component as per IS: 15713 or ISO-15500 by test agency. Alternatively, test agency to verify the test certificate or report conforming to the above standard issued by accredited testing laboratory.

IS: 15713 or ISO-15500

LNG regulator and Vaporiser/ heat exchanger

shall meet requirements of ECE R110 or equivalent standard
ECE R110 or equivalent standard

4

Gas-Air Mixer*

Testing of the component as per IS :15714 or

ISO-15500 by test agency. Alternatively, test agency to verify the test certificate or report conforming to the above standard issued by accredited testing laboratory.

IS: 15714 or ISO-15500

5

Gas Injector*

Testing of the component as per ISO-15500 by test agency. Alternatively, test agency to verify the test certificate or report conforming to the above standard issued by accredited testing laboratory.

ISO-15500

6

Petrol Solenoid Valve*

Testing of the component as per IS: 15717 by test agency. Alternatively, test agency to verify the test certificate or report conforming to the above standard issued by accredited testing laboratory.

IS: 15717

6.1

Gas Solenoid Valve*

Testing of the component as per IS: 15712 or ISO- 15500 by test agency. Alternatively, test agency to verify the test certificate or report conforming to the above standard issued by accredited testing laboratory.

IS: 15712 or ISO-15500

Automatic valve of LNG System shall meet requirements of ECE R110 or equivalent standard.

Automatic Valve for LNG System : ECE R110 or equivalent standard

7

Filling Connection (NZS & NGV-1 type) for CNG/ LNG receptacle

Installation on vehicle to be checked by test agency as per AIS-028

Clauses 2.2.2, 2.2.3, 2.2.4, 2.2.5 and 2.2.6 of AIS-028

8

Ventilation

Test agency to verify.

Clause 2.4.2 of AIS-028

9

Testing of Conduit*

Testing of the component or verification of certificate or test report as per IS: 15715 by test agency.

IS: 15715

10

CNG/ BIO-CNG/ LNG fuel line

10.1

High pressure - exceeding 100 kPa*

10.1.1

Exceeding 2.15 MPa

- Rigid pipe.

Testing of the component or verification of certificate or test report as per IS: 15716 by test agency.

IS: 15716

LNG rigid pipeline shall meet requirements of

ECE R110 or equivalent standard

ECE R 110 or equivalent standard

- Flexible hose

Testing of the component or verification of certificate or test report as per IS 15718 by test agency.

IS 15718

LNG pipeline shall meet requirements of ECE R110

or equivalent standard

ECE R110 or equivalent standard

10.1.2

Pressure upto 2.15 Mpa

Testing of the component or verification of certificate or test report as per IS: 15722 by test agency.

IS: 15722 with amendments

LNG pipeline shall meet requirements of ECE R110

or equivalent standard

ECE R110 or equivalent standard

10.2

Joints and connections*

Testing by test agency.

Clause 3.1.4.1, 3.2.1 (b) of AIS-028

LNG joints & connection shall meet requirements of ECE R110 or equivalent standard.

ECE R110 or equivalent standard

11

Compartment or Sub-compartment*

Testing of the component or verification of certificate or test report as per IS: 15720 by test agency.

IS: 15720

12

Specific LNG components

(a) Following

specific components, as applicable shall meet requirements of ECE R 110 or other International standards

(b) Electronic Control Unit, Pressure and/ or temperature sensor (if not part of LNG cylinder)

ECE R 110 or equivalent standard

13

Safety check for installation of CNG/ BIO-CNG/ LNG system

Safety checks to be carried out by test agency as per AIS-028.

Relevant clauses of AIS-028

* Certificate issued by accredited testing agency of the country of origin or a report issued by internationally accredited test laboratory may also be accepted.

Note 1 - Only the standards, as amended from time to time, as mentioned above, shall be referred for compliance.

Note 2 - LNG system Components downstream of Vaporiser or heat exchanger shall be considered as CNG components.

Note 3 - Test agency to conduct applicable CMVR test as applicable with commercial available LNG fuel.]

ANNEXURE X [(See Item F of rule 115-B and sub-rule (10) of rule 115-C)]

[Substituted by G.Section R 788(E), dated 27.11.2002, for '(See Item F of rule 115-B)'(w.e.f. 2.6.2003).]

SAFETY AND PROCEDURAL REQUIREMENTS FOR TYPE APPROVAL OF CNG AND LPG OPERATED VEHICLES
Ministry of Road Transport and Highways has prescribed Safety Code of Practice and Procedure to be followed by the test agencies prescribed under CMVR for the purposes of issuing type approval certificates for CNG and LPG operated vehicles. The safety code of practice and type approval procedure to be followed for CNG and LPG operated vehicles is given in AIS 024 (Safety and Procedural Requirements for Type Approval of CNG Operated Vehicles) and AIS 025 (Safety and Procedural Requirements for Type Approval of LPG Operated Vehicles) standards respectively. These documents contain safety code of practice and procedure to be followed for installation of CNG/LPG kits by vehicle

manufacturers (OE), kit installers or kit manufacturers or kit suppliers or kit importers. These standards also contain technical specifications of vehicle and kit, checklist for fitness tests of in-use converted vehicles, criteria to authorise kit installer and details about installation.

Role and responsibility of each agency concerned is given in the above referred documents, salient features of which are described below:

Role of Test Agency (Page No. 3 to 6 of AIS 024 and Page Nos. 3 and 4 of AIS 025). - Type Approval of CNG and LPG vehicles is carried out by the test agencies according to the Safety and Procedural Requirements for Type Approval of CNG/LPG Operated Vehicles. The test agencies carry out type approval certification trials on the vehicles and components submitted by vehicle/kit manufacturers/kit suppliers. Type Approval certification trials basically involve testing and evaluation of vehicles and components for performance and safety and installation checks on the vehicle. If the vehicle meets the type approval norms and prescribed testing for components, type approval certificate is awarded to the vehicle/kit manufacturers/kit suppliers and the vehicle/kit manufacturers/kit suppliers are supposed to manufacture and market the vehicles fitted with kits conforming to those specifications. Necessary owner's manual, service manual, periodical inspection and maintenance instruction and adequate infrastructure to offer after sales service is the responsibility of vehicle/kit manufacturers/kit suppliers.

Responsibility of vehicle/kit manufacturer/kit supplier (Page Nos. 3 and 4 of AIS 024 and Page 3 of AIS 025).-Prime responsibility of the vehicle/kit manufacturers/kit suppliers, as the case may be, is to manufacture and supply the vehicles fitted with CNG/LPG kits conforming to the specifications declared at the time of type approval. Necessary owner's manual giving the instructions about periodical maintenance, safety checks and do's and don'ts is to be prepared by vehicle/kit manufacturers/kit suppliers and provided to the vehicle owners. Necessary tools and gadgets to carry out installation, periodical inspection and maintenance of the vehicle shall be provided. If the kit manufacturer/supplier feels that additional safety instructions need to be provided in the vehicle, then it should be displayed at an appropriate location inside and outside the vehicle. During warranty period vehicle/kit manufacturers/kit suppliers should strictly adhere to the maintenance schedule and give appropriate training to the users. If the vehicle/kit manufacturers/kit suppliers feel that normal training is not sufficient, they should arrange comprehensive training to the users, drivers and other technicians on inspection, operation and maintenance. Vehicle/kit manufacturers/kit suppliers shall establish necessary infrastructure while establishing/appointing service centres/kit installers as per Annexure V of AIS 024 and AIS 15 standards.

Responsibility of Owners/ Users (Clause Nos. 12 and 15 of Annexure V of AIS 024/AIS 025)

- The owner/ driver shall be instructed in the correct way that the gas system and controls function alongwith owner's operation manual for the gas system outlining the following:
 - * Basic gas system explanation with a diagram
 - * Fuel change over switch operation if bi-fuel system is fitted
 - * Starting procedure for cold and hot start
 - * How the vehicle is refueled
 - * In the event of backfire check procedure and compliance
 - * In the event of gas leak shut off procedure and compliance
 - * Emergency or information contact numbers in the event of emergency
- Users should comply with all the instructions given by the vehicle manufacturers/ kit installers. Necessary periodic inspection, as listed in owner's manual, shall be carried out by the users.
- Users should follow the instructions while filling gas and carry out leakage test periodically.

Users to insist on appropriate training to be given to the drivers and technicians by vehicle manufacturers/ kit installers/suppliers. Periodic inspection of valves, pipelines, cylinders and regulator/ vaporizer shall be carried out.

In case of malfunctioning of any component, necessary repair and maintenance to be carried out at authorized service station under the assistance/ guidance of installers, vehicle/ kit manufacturers/ suppliers.

- The vehicle owner shall apply to the concerned registering authority within 14 days of undertaking the alteration for endorsement of particular alteration in the registration certificate mentioning place and date of installation and installation certificate number.

Statutory Requirements for Registration of Vehicle.-Enhancement of safety can be ensured taking the following measures:-

- While register in every converted bus, vehicle manufacturers/kit installers along with bus body builders and transport

authority shall jointly examine the bus prior to registration. The registration of such a vehicle; half be done only after signing the report jointly by all the concerned along with the transport authority.

- Details of training module and frequency of training shall be communicated to the users/competent authority such as transport authority/registration authority by vehicle manufacturers/kit installers. User-friendly approach from vehicle manufacturers and kit installers for servicing, maintenance and supply of spare parts is essential. The details shall be worked out prior to placement of order.
- Additional safety features such as 2 Nos. of dry powder type fire extinguishers of 2 kg each shall be provided one in driver's cabin and another in passenger compartment. Gas leakage detector will further enhance safety.
- For electrical installation, flameproof cables shall be used, especially positive terminals shall be locked firmly with all cables and pipes with proper looming to take care of vibrations; tire retardant material shall be used for seat/upholstery/root and side lining. Safety instructions about alertness in case of gas leakage and Tire hazard shall be displayed.

Note:-The AIS standards referred to in this Annexure are available with the Automotive Research Association of India (ARAD), P.B. No. 832, Pune 411004, India (Fax-91-20-5434190, Website <http://www.araiindia.com>). Copies of this document are also available with the other testing agencies, as referred to in rule 126 of the Central Motor Vehicles Rules, 1989.

[ANNEXURE XI]

[Inserted by GSR 513(E), dated 10.8.2004 (w.e.f. 10.9.2004).]

[See clause (s) of rule 2]

I. Smart Card specifications for Driving License, Registration Certificate, Regional Transport Office cards, endorsing authority cards, reviewing authority cards, key generation authorities cards, etc.

(a)

Microprocessor based Integrated Circuit Card with contacts and with a minimum of 4 kb to available Electrically Erasable Programmable Read Only Memory (EEPROM)

(b)

Compliant to ISO/IEC 7816-1,2 and 3

(c)

Compliant to SCOSTA VI.2b, dated March 15, 2002

(d)

Supply voltage 3V nominal

(e)

(e)

T=0 or T=1 transport protocol

(f)

Min 10 years data retention

(g)

Min 3,00,000 EEPROM write cycles

(h)

Operating ambient temperature range -25°C to +55°C

(i)

Glossy surface, Poly Vinyl Chloride PVC)/Acrylonitrile Butadiene Styrene (ABS) plastic construction with overlay to allow color dye sublimation printing

(j)

Smart Cards must have data objects for card sequence no (Tag 5F34) and cards primary account no (Tag 5A) at the Master File level as per International Standards Organisation 7816 Once programmed these data objects cannot be changed.

11. Specifications of Hand Held Terminals

(a)

Display 4 lines x 16 characters back lit Liquid Crystal Display (LCD). Contrast level should such that it can be read in broad day light

(b)

Key Pad : Numeric, Function and scroll keys. Support for entering non-numeric characters using this key pad should also be available.

(c)

Power On/Off : Switch or automated sleep mode enabled.

(d)

Smart Car Readers : Two built in International Standards Organisation 7816 compliant smart card readers with 3V interface and with both T=0 and T=1 transport protocols.

(e)

Battery pack : (Rechargeable and removable) with 8 hours of on time and 7 days stand-by time. Preferably support should be there to operate device with the help of standard 1.5 Volts Dry Cells of standard size.

(f)

Memory : Memory requirements will depend on the application and the number of applications supported by the Terminal.

(g)

Printer : Printer is Optional and Printer Port is desirable.

(h)

Application : National Standard of Driving License and Registration Certificate as specified in this Annexure.

(i)

Communication : Standard Communication interfaces for loading and unloading of software (u grades).

III. Specifications of Dye Sublimation Printer

Print Process: Dye Sublimation

Resolution: 300 dpi.

Print Speed approximately 30 seconds per side.

Colours-up to 16.7 million colours by using YMCK+O/YMCKO/KO ribbon.

Capable of edge to edge printing

Having card input hopper and in-built card cleaning system.

Capable of printing and smart card electronic personalisation in single pass.

Smart card encoder within the printer shall be Factory Standard for PC to Smart Card Reader interface, International Standards Organisation 7816 compliant, support 3V chip card with T=0 and T=1 protocol.

IV. Specifications of Smart Card Reader

Factory Standard for PC to Smart Card Reader interface, ISO 7816 compliant, support 3V chip card with T=0 and T=1 protocol, USB interface, external. Readers must have Factory Standard for PC to Smart Card Reader interface drivers.

Note.-The microprocessor chip of the Smart Card mentioned at Para I shall necessarily conform to the specifications given in this Annexure for Smart Card based Driving License and Vehicle Registration documents for Transport and Non-Transport vehicles and shall contain the information prescribed by these rules. This microprocessor chip shall not carry any other information not prescribed for the purpose. In addition to this microprocessor chip, any extra information as maybe required by any State Government or Union Territory Administration may be stored on the card in the form of any additional information storage media or any other technological media outside the above referred microprocessor chip embedded in the Smart Card, which shall not conflict in any way with the minimum specifications prescribed by the Central Government under these rules or the operation of the same. Further, the operating environment in the form of Operating System, Protocol and other details given above relating to the microprocessor chip, as given in items (a) to (j) of paragraph I shall be complied with, without any variation, whatsoever.]

[Sub-Rule (2) substituted by GSR 111(E), dated 10.2.2004 (w.e.f. 10.8.2004) and as corrected by vide GSR 176(E), dated 5.3.2004.]

Related AI tags, queries and research notes

Translation