

Specification of Maximum Gross Vehicle Weight and Maximum Safe Axle Weight

Source: <https://indiankanoon.org/doc/135868528/>

[Skip to main content](#)

[Legal Document View](#)

[Tools for analyzing structure and cite text of judgments](#)

[Unlock Advanced Research with PRISM](#)

[AI](#)

Integrated with over 4 crore judgments and laws ? designed for legal practitioners, researchers, students and institutions

-

[Know your Kanoon](#)

-

[Doc Gen Hub](#)

-

[Counter Argument](#)

-

[Case Predict AI](#)

-

[Talk with IK Doc](#)

-

...

[Upgrade to Premium](#)

[\[Cites](#)

0

, Cited by

0

]

Union of India - Act

Specification of Maximum Gross Vehicle Weight and Maximum Safe Axle Weight

UNION OF INDIA

India

Specification of Maximum Gross Vehicle Weight and Maximum Safe Axle Weight

Rule SPECIFICATION-OF-MAXIMUM-GROSS-VEHICLE-WEIGHT-AND-MAXIMUM-SAFE-AXLE-WEIGHT of 1996

Published on 18 October 1996

Commenced on 18 October 1996

[This is the version of this document from 18 October 1996.]

[Note: The original publication document is not available and this content could not be verified.]

Specification of Maximum Gross Vehicle Weight and Maximum Safe Axle Weight

Published Vide Notification No. S.O. 728(E), dated 18.10.1996.

17.

/764

S.O. 416(E), dated 8-6-1989-Superseded by S.O. 479(E), dated 4-7-1996

S.O. 681(E), dated 30-8-1989 in partial modification of S.O. 416(E), dated 8-6-1989-Superseded by S.O. 479(E), dated 4-7-1996

S.O. 479(E), dated 4-7-1996-Superseded by S.O.728(E), dated 18-10-1996

1.

Specification of Maximum Gross Vehicle Weight and Maximum Safe Axle Weight

In exercise of the powers conferred by sub-section (1) of section 58 of the Motor Vehicles Act, 1988 (59 of 1988

) and in supersession of the notification of the Government of India in the Ministry of Surface Transport S.O. No. 479 (E), dated the 4th July, 1996, the Central Government hereby specifies that in relation to the transport vehicles (other than motor cabs) of various categories detailed in the Schedule below, the maximum gross vehicle weight and the maximum safe axle weight of each axle of such vehicles shall, having regard to the size, nature and number of tyres and maximum weight permitted to be carried by the tyres as per rule 95 of the Central Motor Vehicles Rules, 1989, be

(i) vehicle manufacturers rating of the gross vehicle weight and axle weight respectively for each make and model as duly certified by the testing agencies for compliance of rule 126 of the Central Motor Vehicles Rules, 1989, or

(ii) the maximum gross vehicle weight and the maximum safe axle weight of each vehicle respectively as specified in the Schedule below for the relevant category, or

(iii) the maximum load permitted to be carried by the tyre(s) as specified in the rule 95 of the Central Motor Vehicles Rules, 1989, for the size and number of the tyres fitted on the axle (s) of the relevant make and model, whichever is less:

Provided that the maximum gross vehicle weight in respect of all such transport vehicles, including multi-axle vehicles shall not be more than the sum total of all the maximum safe axle weight put together subject to the restrictions, if any, on the maximum gross vehicle weight given in the said Schedule.

SCHEDULE

Transport Vehicles Category

Max GVW Tonnes

Maximum Safe Axle Weight

1

2

3

4

I Rigid Vehicles

(i)

Two Axle

9.00

One tyre on front axle, and

3 tonnes on front axle

Two tyres on rear axle,

6 tonnes on rear axle

(ii)

Two Axle

12.0

Two tyres on each axle

6 tonnes on front axle

6 tonnes on rear axle

(iii)

Two Axle

16.2

Two tyres on front axle, and

6 tonnes on front axle

Four tyres on rear axle

10.2 tonnes on rear axle

(iv)

Three Axle

25.0

Two tyres on front axle, and

6 tonnes on front axle

Eight tyres on rear tandem axle

19 tonnes on rear tandem axle

(v) [

[Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]

[Four Axle

[Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]

31. [0

[Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]

[Four tyres on front axle, and

[Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]

[12 tonnes on two front axle

[Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]

[Eight tyres on rear tandem axle

[Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]

[19 tonnes on rear tandem axle]

[Inserted by S.O. 732(E), dated 8.9.1999 (w.e.f. 8.9.1999).]

II Semi-Articulated Vehicles

(i)

Two Axle Tractor

26.4

Single Axle Trailer

Tractor:

2 tyres on front axle

6 tonnes on front axle

4 tyres on rear axle

10.2 tonnes on rear axle

Trailer:

4 tyres on single axle

10.2 tonnes on single trailer axle

(ii)

Two Axle Tractor

35.2

Tandem Axle Trailer

Tractor:

2 tyres on front axle

6 tonnes on front axle

4 tyres on rear axle

10.2 tonnes on rear axle

Trailer:

8 tyres on tandem axle

19 tonnes on tandem axle

(iii)

Two Axle Tractor

40.2

Three Axle Trailer

Tractor:

2 tyres on front axle

6 tonnes on front axle

4 tyres on rear axle

10.2 tonnes on rear axle

Trailer:

12 tyres on 3 axles

24 tonnes on 3 axles

(iv)

Three Axle Tractor

35.2

Single Axle Trailer

Tractor:

2 tyres on front axle

6 tonnes on front axle

8 tyres on rear axle

19 tonnes on rear axle

Trailer:

8 tyres on single axle

10.2 tonnes on single axle

(v)

Three Axle Tractor

44.0

Tandem Axle Trailer

Tractor:

2 tyres on front axle

6 tonnes on front axle

8 tyres on tandem axle

19 tonnes on rear tandem axle

Trailer:

8 tyres on tandem axle

19 tonnes on tandem axle

III Truck-Trailer Combinations

(i)

Two Axle Truck

Two Axle Trailer

Truck:

2 tyres on front axle

6 tonnes on front axle

4 tyres on rear axle

10.2 tonnes on rear axle

Trailer:

4 tyres on front axle

10.2 tonnes on front axle

4 tyres on rear axle

10.2 tonnes on front axle

(ii)

Three Axle Truck

45.4

Two Axle Trailer

(restricted to 44.0 tonnes)

Truck:

2 tyres on front axle

6 tonnes on front axle

8 tyres on rear tandem axle

19 tonnes on rear tandem axle

Trailer:

4 tyres on front axle

10.2 tonnes on front axle

4 tyres on rear axle

10.2 tonnes on rear axle

(iii)

Three Axle Truck

45.4

Three Axle Trailer

(restricted to 44.0 tonnes)

Truck:

2 tyres on front axle

6 tonnes on front axle

4 tyres on rear axle

10.2 tonnes on rear axle

Trailer:

4 tyres on rear axle

6 tonnes on front axle

Trailer:

4 tyres on rear axle

10.2 tonnes on front axle

8 tyres on rear tandem axle

19.0 tonnes on rear tandem axle

(iv)

Three Axle Truck

54.2

Three Axle Trailer

(restricted to 44.0 tonnes)

Truck:

2 tyres on front axle

6 tonnes on front axle

8 tyres on rear tandem axle

19 tonnes on rear tandem axle

Trailer:

4 tyres on front axle

10.2 tonnes on front axle

8 tyres on rear tandem axle

19.0 tonnes on rear tandem axle

Related AI tags, queries and research notes

Translation